ACCREDITED
Certificate # 3939.01

FCC TEST REPORT
(Part 15, Subpart C)

Applicant:	HMD Global Oy
Address:	Bertel Jungin aukio 9, 02600 Espoo, Finland

Manufacturer or Supplier:	HMD Global Oy
Address:	Bertel Jungin aukio 9, 02600 Espoo, Finland
Product:	Multi-band GSM/WCDMA/LTE phone with Bluetooth&WLAN
Brand Name:	NOKIA
Model Name:	TA-1404
FCC ID:	2AJOTTA-1404
Date of tests:	Nov. 25, 2021 ~ Dec. 12, 2021

The tests have been carried out according to the requirements of the following standard:

☒ **FCC Part 15, Subpart C, Section 15.247**

☒ **ANSI C63.10-2013**

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Prepared by Simon Wang Engineer / Mobile Department	Approved by Luke Lu Manager / Mobile Department
Simon Date: Dec. 13, 2021	Luke Lu Date: Dec. 13, 2021

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute you unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

BV 7Layers Communications Technology (Shenzhen) Co. Ltd

No.B102, Dazu Chuangxin Mansion, North of Beihuan Avenue, North Area, Hi-Tech Industrial Park, Nanshan District, Shenzhen, Guangdong, China

Tel: +86 755 8869 6566
Fax: +86 755 8869 6577
Email: customerservice.sw@bureauveritas.com

TABLE OF CONTENTS

RELEASE CONTROL RECORD **5**
1 SUMMARY OF TEST RESULTS **6**
1.1 MEASUREMENT UNCERTAINTY **7**
2 GENERAL INFORMATION **8**
2.1 GENERAL DESCRIPTION OF EUT **8**
2.2 DESCRIPTION OF TEST MODES **10**
2.2.1 CONFIGURATION OF SYSTEM UNDER TEST 11
2.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL 11
2.3 GENERAL DESCRIPTION OF APPLIED STANDARDS **13**
2.4 DESCRIPTION OF SUPPORT UNITS **13**
3 TEST TYPES AND RESULTS **14**
3.1 CONDUCTED EMISSION MEASUREMENT **14**
3.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT 14
3.1.2 TEST INSTRUMENTS 14
3.1.3 TEST PROCEDURES 14
3.1.4 DEVIATION FROM TEST STANDARD 15
3.1.5 TEST SETUP 15
3.1.6 EUT OPERATING CONDITIONS 15
3.1.7 TEST RESULTS 16
3.2 Radiated Emission AND BANDEDGE Measurement **18**
3.2.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT 18
3.2.2 TEST INSTRUMENTS 19
3.2.3 TEST PROCEDURES 20
3.2.4 DEVIATION FROM TEST STANDARD 20
3.2.5 TEST SETUP 21
3.2.6 EUT OPERATING CONDITIONS 22
3.2.7 TEST RESULTS 23
3.3 NUMBER OF HOPPING FREQUENCY USED **28**
3.3.1 LIMIT OF HOPPING FREQUENCY USED 28
3.3.2 TEST SETUP 28
3.3.3 TEST INSTRUMENTS 28
3.3.4 TEST PROCEDURES 29
3.3.5 DEVIATION FROM TEST STANDARD 29
3.3.6 TEST RESULTS 29
3.4 DWELL TIME ON EACH CHANNEL **31**

3.4.1 LIMIT OF DWELL TIME USED....31
3.4.2 TEST SETUP....31
3.4.3 TEST INSTRUMENTS....31
3.4.4 TEST PROCEDURES....31
3.4.5 DEVIATION FROM TEST STANDARD....32
3.4.6 TEST RESULTS....32
3.5 CHANNEL BANDWIDTH....33
3.5.1 LIMITS OF CHANNEL BANDWIDTH....33
3.5.2 TEST SETUP....33
3.5.3 TEST INSTRUMENTS....33
3.5.4 TEST PROCEDURE....33
3.5.5 DEVIATION FROM TEST STANDARD....33
3.5.6 EUT OPERATING CONDITION....34
3.5.7 TEST RESULTS....34
3.6 HOPPING CHANNEL SEPARATION....35
3.6.1 LIMIT OF HOPPING CHANNEL SEPARATION....35
3.6.2 TEST SETUP....35
3.6.3 TEST INSTRUMENTS....35
3.6.4 TEST PROCEDURES....35
3.6.5 DEVIATION FROM TEST STANDARD....35
3.6.6 TEST RESULTS....36
3.7 MAXIMUM OUTPUT POWER....36
3.7.1 LIMITS OF MAXIMUM OUTPUT POWER MEASUREMENT....36
3.7.2 TEST SETUP....36
3.7.3 TEST INSTRUMENTS....36
3.7.4 TEST PROCEDURES....36
3.7.5 DEVIATION FROM TEST STANDARD....37
3.7.6 EUT OPERATING CONDITION....37
3.7.7 TEST RESULTS....38
3.7.7.1 MAXIMUM PEAK OUTPUT POWER....38
3.7.7.2 Average Output Power (FOR REFERENCE)....39
3.8 out of band MEASUREMENT....40
3.8.1 LIMITS OF OUT OF BAND MEASUREMENT....40
3.8.2 TEST INSTRUMENTS....40
3.8.3 TEST PROCEDURE....40
3.8.4 DEVIATION FROM TEST STANDARD....40

3.8.5 EUT OPERATING CONDITION..... 40
3.8.6 TEST RESULTS..... 40
4 PHOTOGRAPHS OF THE TEST CONFIGURATION..... 41
5 MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB..... 42
6 Appendix..... 43
20dB Emission Bandwidth..... 43
Test Result..... 43
Test Graphs..... 44
Occupied Channel Bandwidth..... 49
Test Result..... 49
Test Graphs..... 50
Maximum conducted output power..... 55
Peak Power Test Result..... 55
4.3.1 Average Power Test Result..... 55
Carrier frequency separation..... 56
Test Result..... 56
Test Graphs..... 57
Time of occupancy..... 59
Test Result..... 59
Test Graphs..... 60
Number of hopping channels..... 69
Test Result..... 69
Test Graphs..... 70
Band edge measurements..... 72
Test Result..... 72
Test Graphs..... 73
Conducted Spurious Emission..... 79
Test Result..... 79
Test Graphs..... 80
Duty Cycle..... 94
Test Result..... 94
Test Graphs..... 95

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
W7L-P21100018-1RF01	Original release	Dec. 13, 2021

1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C		
STANDARD	**TEST TYPE AND LIMIT**	**RESULT**
15.207	AC Power Conducted Emission	Compliance
15.247(a)(1)(iii)	Number of Hopping Frequency Used	Compliance
15.247(a)(1)(iii)	Dwell Time on Each Channel	Compliance
15.247(a)(1)	1. Hopping Channel Separation 2. Spectrum Bandwidth of a Frequency Hopping Sequence Spread Spectrum System	Compliance
15.247(b)	Maximum Peak Output Power	Compliance
15.247(d)& 15.209	Transmitter Radiated Emissions	Compliance
15.247(d)	Out of band Measurement	Compliance
15.203	Antenna Requirement	Compliance

NOTE:

1. If the Frequency Hopping System operating in 2400-2483.5MHz band and the output power less than 125mW. The hopping channel carrier frequencies separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of hopping channel whichever is greater.
2. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

Test Lab Information Reference:

BV 7Layers Communications Technology (Shenzhen) Co. Ltd

Lab Address:

No.B102, Dazu Chuangxin Mansion, North of Beihuan Avenue, North Area, Hi-Tech Industrial Park, Nanshan District, Shenzhen, Guangdong, China

Accredited Test Lab Cert 3939.01

1.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	UNCERTAINTY
AC Power Conducted emissions	±2.70dB
Radiated emissions (30MHz~1GMHz)	±4.98dB
Radiated emissions (1GMHz ~6GMHz)	±4.70dB
Radiated emissions (6GMHz ~18GMHz)	±4.60dB
Radiated emissions (18GMHz ~40GMHz)	±4.12dB
Conducted emissions	±4.01dB
Occupied Channel Bandwidth	±43.58KHz
Conducted Output power	±2.06dB
Power Spectral Density	±0.85 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

2 GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Multi-band GSM/WCDMA/LTE phone with Bluetooth&WLAN
BRAND NAME	NOKIA
MODEL NAME	TA-1404
NOMINAL VOLTAGE	5.0/9.0/12.0Vdc(adapter or host equipment) 3.85Vdc (Li-ion, battery)
MODULATION TECHNOLOGY	FHSS
MODULATION TYPE	GFSK, 8DPSK, π/4 DQPSK
OPERATING FREQUENCY	2402MHz~2480MHz
NUMBER OF CHANNEL	79
MAX. OUTPUT POWER	9.29mW (Max. Measured)
ANTENNA TYPE	Fixed Internal Antenna with 1.19dBi gain
HW VERSION	19655-1-11M12
SW VERSION	00WW_0_010
I/O PORTS	Refer to user's manual
CABLE SUPPLIED	USB1 cable: unshielded without ferrite, 1.0meter USB2 cable: unshielded without ferrite, 1.0meter USB3 cable: unshielded without ferrite, 1.0meter Earphone1: non-shielded cable, with w/o ferrite core, 1.2 meter Earphone2: non-shielded cable, with w/o ferrite core, 1.2 meter

NOTE:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
2. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.

List of Accessory:

ACCESSORIES	BRAND	MANUFACTURER	MODEL	SPECIFICATION
Battery	Nokia	Hunan Gaoyuan Battery Co., Ltd.	WT341	Capacity：3.85 Vdc, 4900mAh
AC Adapter 1	Nokia	ShenZhenBaiJunDa ElectronicCO.,LTD.	AD-010U	I/P: 100-240Vac, 0.35A, O/P: 5.0Vdc, 2.0A
AC Adapter 2	Nokia	SHENZHEN TIANYIN ELECTRONICS CO., LTD.	CH-21U	I/P: 100-240Vac, 0.3A, O/P: 5.0Vdc, 2.0A
AC Adapter 3	Nokia	YuTong Electronics(HuiZhou) Co.,Ltd	PA-US5V2A-03 6	I/P: 100-240Vac, 0.5A, O/P: 5.0Vdc, 2.0A
AC Adapter 4	Nokia	Dongguan Aohai Technology Co., Ltd.	A829US	I/P: 100 - 240Vac, 0.5A, O/P:5.0 Vdc,3A/9.0 Vdc, 2.2 3A/12.0 Vdc,1.67A
Earphone 1	Nokia	NEW LEADER INDUSTRY CO.,LTD	HS-34	Signal Line, 1.2meter
Earphone 2	Nokia	Guangdong Wivtak Technology Co., Ltd.	HS-34	Signal Line, 1.2meter
USB Cable 1	Nokia	HUIZHOU WASHIN ELECTRONICS CO.,LTD	CB-36A	Signal Line, 1.0meter
USB Cable 2	Nokia	Shenzhen BRL Technology Co.,Ltd.	CB-36A	Signal Line, 1.0meter
USB Cable 3	Nokia	Saibao(Jiangi) Communication Industial Co.,Ltd	CB-12A	Signal Line, 1.0meter

NOTE：BT test in the engineer mode,power setting at “ MAXIMUM CONDUCTED OUTPUT POWER”, the steps for entering engineering mode are as follows:

1. In the finger plate, dial the code for entering Engineer mode: *#*#83781#*#*
2. EngineerMode->CONNECTIVITY->BT->Tx

2.2 DESCRIPTION OF TEST MODES

79 channels are provided to this EUT:

CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		

2.2.1 CONFIGURATION OF SYSTEM UNDER TEST

Please see section 5 photograph of the test configuration for reference.

2.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports.
The worst case was found when positioned on X axis for radiated emission.
Following channel(s) was (were) selected for the final test as listed below:

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE<1G	RE≥1G	PLC	APCM	
-	√	√	√	√	-

Where **RE<1G:** Radiated Emission below 1GHz **RE≥1G:** Radiated Emission above 1GHz
PLC: Power Line Conducted Emission **APCM:** Antenna Port Conducted Measurement

RADIATED EMISSION TEST (BELOW 1 GHz):

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, XYZ axis, antenna ports (if EUT with antenna diversity architecture) and packet type.
☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
-	0 to 78	39	FHSS	8DPSK	3DH5

RADIATED EMISSION TEST (ABOVE 1 GHz):

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, XYZ axis, antenna ports (if EUT with antenna diversity architecture) and packet type.
☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
-	0 to 78	0, 39, 78	FHSS	GFSK	DH5
-	0 to 78	0, 39, 78	FHSS	8DPSK	3DH5

POWER LINE CONDUCTED EMISSION TEST:

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture) and packet type.

☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
-	0 to 78	39	FHSS	8DPSK	3DH5

ANTENNA PORT CONDUCTED MEASUREMENT:

☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture), and packet types.

☒ Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
0 to 78	0, 39, 78	FHSS	GFSK	DH1/DH3/DH5
0 to 78	0, 39, 78	FHSS	π/4 DQPSK	2DH1/2DH3/2DH5
0 to 78	0, 39, 78	FHSS	8DPSK	3DH1/3DH3/3DH5

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	TEST VOLTAGE (SYSTEM)	TESTED BY
RE<1G	23deg. C, 70%RH	DC 5V By Adapter	Jace Hu
RE≥1G	23deg. C, 70%RH	DC5V By Adapter	Jace Hu
PLC	25deg. C, 52%RH	DC5V By Adapter	James Fu
APCM	25deg. C, 60%RH	DC 3.85V By Battery	James Fu

2.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C. Section 15.247
ANSI C63.10-2013

NOTE:
1. All test items have been performed and recorded as per the above standards.
2. The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (Certification). The test report has been issued separately.

2.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	Desktop	Lenovo	M73 SFF	PC04GRQV	N/A
2	Desktop	Lenovo	M73 SFF	PC06CS27	N/A
3	Laptop	Lenovo	Thnikpad L440	R90FTFKN	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	AC Line: Unshielded, Detachable 1.5m
2	AC Line: Unshielded, Detachable 1.5m
3	AC Line: Unshielded, Detachable 1.5m

3 TEST TYPES AND RESULTS

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBμV)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

NOTE: 1.The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

3.1.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESR3	101900	Mar. 03,21	Mar. 02,22
EMC32 test software	Rohde&Schwarz	EMC32	NA	NA	NA
LISN network	Rohde&Schwarz	ENV216	101922	Feb. 25,21	Feb. 24,22

NOTE: 1. The test was performed in CE shielded room.

2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.

3.1.3 TEST PROCEDURES

a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.

b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.

c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

NOTE: All modes of operation were investigated and the worst-case emissions are reported.

3.1.4 DEVIATION FROM TEST STANDARD

No deviation.

3.1.5 TEST SETUP



Note: 1.Support units were connected to second LISN.
2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

3.1.6 EUT OPERATING CONDITIONS

a. Turned on the power and connected of all equipment.
b. EUT was operated according to the type used was description in manufacturer's specifications or the User's Manual.

3.1.7 TEST RESULTS

CONDUCTED WORST-CASE DATA:

Frequency Range	150KHz ~ 30MHz	**Detector Function & Resolution Bandwidth**	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120Vac, 60Hz	**Environmental Conditions**	26deg. C, 51%RH
Tested By	Carl xie		

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
1.052000	---	18.33	46.00	27.67	L1	ON	9.7
1.052000	26.00	---	56.00	30.00	L1	ON	9.7
1.700000	---	23.03	46.00	22.97	L1	ON	9.7
1.700000	28.42	---	56.00	27.58	L1	ON	9.7
3.792000	---	27.31	46.00	18.69	L1	ON	9.7
3.792000	34.57	---	56.00	21.43	L1	ON	9.7
7.364000	---	37.76	50.00	12.24	L1	ON	9.7
7.364000	43.75	---	60.00	16.25	L1	ON	9.7
12.008000	---	36.14	50.00	13.86	L1	ON	9.8
12.008000	41.54	---	60.00	18.46	L1	ON	9.8
18.092000	---	25.34	50.00	24.66	L1	ON	9.8
18.092000	30.92	---	60.00	29.08	L1	ON	9.8

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Limit value - Emission level
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.

Full Spectrum



Frequency Range	150KHz ~ 30MHz	**Detector Function & Resolution Bandwidth**	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120Vac, 60Hz	**Environmental Conditions**	26deg. C, 51%RH
Tested By	Carl xie		

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
1.656000	---	21.18	46.00	24.82	N	ON	9.8
1.656000	27.22	---	56.00	28.78	N	ON	9.8
3.540000	---	24.94	46.00	21.06	N	ON	9.8
3.540000	30.99	---	56.00	25.01	N	ON	9.8
4.976000	---	29.88	46.00	16.12	N	ON	9.8
4.976000	36.11	---	56.00	19.89	N	ON	9.8
7.684000	---	38.41	50.00	11.59	N	ON	9.8
7.684000	44.34	---	60.00	15.66	N	ON	9.8
10.588000	---	36.65	50.00	13.35	N	ON	9.8
10.588000	42.06	---	60.00	17.94	N	ON	9.8
17.892000	---	25.50	50.00	24.50	N	ON	9.9
17.892000	30.93	---	60.00	29.07	N	ON	9.9

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Limit value - Emission level
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



3.2 RADIATED EMISSION AND BANDEDGE MEASUREMENT

3.2.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a). Other emissions shall be at least 20dB below the highest level of the desired power.

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

3.2.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	Euroshieldpn-CT0001143-1216	May. 19,20	May. 18,23
Bilog Antenna	ETS-LINDGREN	3143B	00161965	Mar. 05,21	Mar. 04,22
Horn Antenna	ETS-LINDGREN	3117	00168728	Apr. 02, 21	Apr. 01, 22
Horn Antenna (18GHz-40GHz)	N/A	QWH-SL-18-40-K-SG/QMS-00361	15433	Aug. 25, 21	Aug. 24, 22
Test Software	E3	V 9.160323	N/A	N/A	N/A
Test Software	ADT	ADT_Radiated_V7.6.15.9.2	N/A	N/A	N/A
10dB Attenuator	JFW/USA	50HF-010-SMA	1505	Jun. 03,21	Jun. 02,22
MXE EMI Receiver	KEYSIGHT	N9038A-544	MY54450026	Apr. 27,21	Apr. 26,22
Signal Pre-Amplifier	EMSI	EMC 9135	980249	Jun. 02,21	Jun. 01,22
Signal Pre-Amplifier	EMSI	EMC 012645B	980257	Jun. 02,21	Jun. 01,22
Signal Pre-Amplifier	EMSI	EMC 184045B	980259	Apr. 30,21	Apr. 29,22
DC Source	Kikusui/JP	PMX18-5A	0000001	Aug. 25,21	Aug. 24,22
Power Meter	Anritsu	ML2495A	1506002	Feb. 25,21	Feb. 24,22
Power Sensor	Anritsu	MA2411B	1339352	Feb. 25,21	Feb. 24,22
Loop Antenna	Schwarzbeck	FMZB 1519B	1519B-051	Feb 14,20	Feb. 13,23

NOTE: 1. The calibration interval of the above test instruments is 12 months or 36 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.

2. The test was performed in 3m Chamber.

3. The FCC Site Registration No. is 525120; The Designation No. is CN1171.

3.2.3 TEST PROCEDURES

a. The EUT was placed on the top of a rotating table 0.8 meters (for below 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

f. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using fresh batteries. The turntable was rotated to maximize the emission level.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz for Average detection (AV) at frequency above 1GHz.
4. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a “duty cycle correction factor”, derived from 20log(dwell time/100 ms), in an effort to demonstrate compliance with the 15.209 limit.
5. All modes of operation were investigated and the worst-case emissions are reported.

3.2.4 DEVIATION FROM TEST STANDARD

No deviation.

3.2.5 TEST SETUP

<Frequency Range 9KHz~30MHz >



< Frequency Range 30MHz~1GHz >



<Frequency Range above 1GHz>



Note: Above 1G is a directional antenna

Depends on the EUT height and the antenna 3dB beamwidth both, refer to section 7.3 of CISPR 16-2-3.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

3.2.6 EUT OPERATING CONDITIONS

a. Set the EUT under full load condition and placed them on a testing table.

b. Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.

c. The necessary accessories enable the EUT in full functions.

3.2.7 TEST RESULTS

BELOW 1GHz WORST-CASE DATA:

Note: For frequency below 30MHz, the emission was tested 20db below the limit so the data not recorded in the sheet.

30 MHz – 1GHz data:

BT_8DPSK

CHANNEL	Channel 39	**DETECTOR FUNCTION**	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
62.980	33.45	14.04	1.32	32.57	16.24	40.00	-23.76	QP
142.520	29.36	13.80	2.03	32.54	12.65	43.50	-30.85	QP
339.430	32.29	13.86	3.22	32.64	16.73	46.00	-29.27	QP
749.740	27.15	20.79	5.01	32.55	20.40	46.00	-25.60	QP
806.000	27.92	21.09	5.20	32.46	21.75	46.00	-24.25	QP
902.030	27.56	21.92	5.74	31.73	23.49	46.00	-22.51	QP

CHANNEL	Channel 39	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
37.760	45.31	14.22	0.97	32.60	27.90	40.00	-12.10	QP
62.010	38.56	14.31	1.31	32.58	21.60	40.00	-18.40	QP
84.320	41.60	8.90	1.51	32.53	19.48	40.00	-20.52	QP
161.920	33.07	13.86	2.18	32.56	16.55	43.50	-26.95	QP
329.730	33.06	13.66	3.16	32.63	17.25	46.00	-28.75	QP
608.120	28.64	18.88	4.49	32.69	19.32	46.00	-26.68	QP

ABOVE 1GHz WORST-CASE DATA:

Note: For higher frequency, the emission is too low to be detected.

1GHz – 25GHz: (Scan with GFSK, π/4-DQPSK, 8DPSK mode, the worst case is 8DPSK Mode)

BT_8DPSK

CHANNEL	TX Channel 0	**DETECTOR FUNCTION**	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	44.06	27.38	4.08	35.68	39.84	74.00	-34.16	Peak
2390.000	45.13	27.56	4.16	35.88	40.97	74.00	-33.03	Peak
2402.060	104.44	27.58	4.17	35.91	100.28	74.00	26.28	Peak
2310.000	32.62	27.38	4.08	35.68	28.40	54.00	-25.60	Average
2390.000	33.08	27.56	4.16	35.88	28.92	54.00	-25.08	Average
2402.060	100.86	27.58	4.17	35.91	96.70	54.00	42.70	Average

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2310.000	46.22	27.38	4.08	35.68	42.00	74.00	-32.00	Peak
2388.515	50.97	27.55	4.16	35.87	46.81	74.00	-27.19	Peak
2390.000	46.73	27.56	4.16	35.88	42.57	74.00	-31.43	Peak
2402.060	104.42	27.58	4.17	35.91	100.26	74.00	26.26	Peak
2310.000	32.62	27.38	4.08	35.68	28.40	54.00	-25.60	Average
2390.000	33.05	27.56	4.16	35.88	28.89	54.00	-25.11	Average
2402.060	100.89	27.58	4.17	35.91	96.73	54.00	42.73	Average

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
   Margin value = Emission level – Limit value.
2. 2402MHz: Fundamental frequency.

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4882.000	28.67	31.03	7.03	34.03	32.70	54.00	-21.30	Average
4882.000	40.48	31.03	7.03	34.03	44.51	74.00	-29.49	Peak
7323.000	27.09	35.68	8.98	34.49	37.26	54.00	-16.74	Average
7323.000	39.24	35.68	8.98	34.49	49.41	74.00	-24.59	Peak
9764.000	28.00	38.51	11.15	34.21	43.45	54.00	-10.55	Average
9764.000	39.43	38.51	11.15	34.21	54.88	74.00	-19.12	Peak
2441.000	105.40	27.67	4.18	36.00	101.25	74.00	27.25	Peak

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
4882.000	28.34	31.03	7.03	34.03	32.37	54.00	-21.63	Average
4882.000	40.17	31.03	7.03	34.03	44.20	74.00	-29.80	Peak
7323.000	26.99	35.68	8.98	34.49	37.16	54.00	-16.84	Average
7323.000	38.73	35.68	8.98	34.49	48.90	74.00	-25.10	Peak
9764.000	27.88	38.51	11.15	34.21	43.33	54.00	-10.67	Average
9764.000	39.71	38.51	11.15	34.21	55.16	74.00	-18.84	Peak
2441.000	103.62	27.67	4.18	36.00	99.47	74.00	25.47	Peak

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
   Margin value = Emission level – Limit value.
2. 2441MHz: Fundamental frequency.

CHANNEL	TX Channel 78	DETECTOR FUNCTION	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2480.003	104.62	27.76	4.19	36.10	100.47	74.00	26.47	Peak
2483.500	61.59	27.76	4.19	36.11	57.43	74.00	-16.57	Peak
2500.000	44.71	27.80	4.19	36.15	40.55	74.00	-33.45	Peak
2479.937	100.67	27.76	4.19	36.10	96.52	54.00	42.52	Average
2483.500	41.51	27.76	4.19	36.11	37.35	54.00	-16.65	Average
2500.000	32.32	27.80	4.19	36.15	28.16	54.00	-25.84	Average

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
2480.069	97.53	27.76	4.19	36.10	93.38	54.00	39.38	Average
2483.500	39.60	27.76	4.19	36.11	35.44	54.00	-18.56	Average
2500.000	32.40	27.80	4.19	36.15	28.24	54.00	-25.76	Average
2479.970	101.40	27.76	4.19	36.10	97.25	74.00	23.25	Peak
2483.500	58.58	27.76	4.19	36.11	54.42	74.00	-19.58	Peak
2500.000	46.78	27.80	4.19	36.15	42.62	74.00	-31.38	Peak

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
   Margin value = Emission level – Limit value.
2. 2480MHz: Fundamental frequency.

3.3 NUMBER OF HOPPING FREQUENCY USED

3.3.1 LIMIT OF HOPPING FREQUENCY USED

At least 15 channels frequencies, and should be equally spaced.

3.3.2 TEST SETUP



3.3.3 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Power Meter	ANRITSU	ML2495A	1506002	Feb. 25,21	Feb. 24,22
EXA Signal Analyzer	KEYSIGHT	N9010A-526	MY54510322	Apr. 26,21	Apr. 25,22
EXA Signal Analyzer	KEYSIGHT	N9010A-544	MY54510355	Feb. 25,21	Feb. 24,22
Power Sensor	ANRITSU	MA2411B	1339352	Feb. 25,21	Feb. 24,22
CBT32 BLUETOOTH TESTER 4HU	Rohde&Schwarz	CBT32	101176	Mar. 09,21	Mar. 08,22

NOTE:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
2. The test was performed in RF Oven room.

3.3.4 TEST PROCEDURES

a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.

b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.

c. Set the SA on MaxHold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.

d. Set the SA on View mode and then plot the result on SA screen.

e. Repeat above procedures until all frequencies measured were completed.

3.3.5 DEVIATION FROM TEST STANDARD

No deviation.

3.3.6 TEST RESULTS

There are 79 hopping frequencies in the hopping mode. Please refer to next two pages for the test result. On the plots, it shows that the hopping frequencies are equally spaced.

Please Refer to Appendix Of this test report.

3.4 DWELL TIME ON EACH CHANNEL

3.4.1 LIMIT OF DWELL TIME USED

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

3.4.2 TEST SETUP



3.4.3 TEST INSTRUMENTS

Refer to section 3.3.3 to get information of above instrument.

3.4.4 TEST PROCEDURES

a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.

b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.

c. Adjust the center frequency of SA on any frequency be measured and set SA to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.

d. Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.

e. Repeat above procedures until all different time-slot modes have been completed.

3.4.5 DEVIATION FROM TEST STANDARD

No deviation.

3.4.6 TEST RESULTS

Please Refer to Appendix Of this test report

3.5 CHANNEL BANDWIDTH

3.5.1 LIMITS OF CHANNEL BANDWIDTH

For frequency hopping system operating in the 2400-2483.5MHz, If the 20dB bandwidth of hopping channel is greater than 25kHz, two-thirds 20dBbandwidth of hopping channel shell be a minimum limit for the hopping channel separation.

3.5.2 TEST SETUP



3.5.3 TEST INSTRUMENTS

Refer to section 3.3.3 to get information of above instrument.

3.5.4 TEST PROCEDURE

a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.

b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.

c. Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.

d. Repeat above procedures until all frequencies measured were complete.

3.5.5 DEVIATION FROM TEST STANDARD

No deviation.

3.5.6 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

3.5.7 TEST RESULTS

Please Refer to Appendix Of this test report.

3.6 HOPPING CHANNEL SEPARATION

3.6.1 LIMIT OF HOPPING CHANNEL SEPARATION

At least 25kHz or two-third of 20dB hopping channel bandwidth (whichever is greater).

3.6.2 TEST SETUP



3.6.3 TEST INSTRUMENTS

Refer to section 3.3.3 to get information of above instrument.

3.6.4 TEST PROCEDURES

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
3. By using the MaxHold function record the separation of two adjacent channels.
4. Measure the frequency difference of these two adjacent channels by SA MARK function. And then plot the result on SA screen.
5. Repeat above procedures until all frequencies measured were complete.

3.6.5 DEVIATION FROM TEST STANDARD

No deviation.

3.6.6 TEST RESULTS

Please Refer to Appendix B Of this test report.

3.7 MAXIMUM OUTPUT POWER

3.7.1 LIMITS OF MAXIMUM OUTPUT POWER MEASUREMENT

The Maximum Output Power Measurement is 125mW.

3.7.2 TEST SETUP



3.7.3 TEST INSTRUMENTS

Refer to section 3.3.3 to get information of above instrument.

3.7.4 TEST PROCEDURES

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.

3.7.5 DEVIATION FROM TEST STANDARD

No deviation.

3.7.6 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

3.7.7 TEST RESULTS

3.7.7.1 MAXIMUM PEAK OUTPUT POWER

Please Refer to Appendix Of this test report.

3.7.7.2 Average Output Power (FOR REFERENCE)

The average power sensor was used on the output port of the EUT. A power meter was used to read the response of the power sensor. Record the power level.

Please Refer to Appendix Of this test report.

3.8 OUT OF BAND MEASUREMENT

3.8.1 LIMITS OF OUT OF BAND MEASUREMENT

Below –20dB of the highest emission level of operating band (in 100KHz RBW).

3.8.2 TEST INSTRUMENTS

Refer to section 3.3.3 to get information of above instrument.

3.8.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low loss cable. Spectrum Analyzer was set RBW to 100 kHz and VBW to 300 kHz with suitable frequency span including 100 MHz bandwidth from band edge. Detector = PEAK and Trace mode = Max Hold. The band edges was measured and recorded.

3.8.4 DEVIATION FROM TEST STANDARD

No deviation.

3.8.5 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

3.8.6 TEST RESULTS

The spectrum plots are attached on the following images. D1 line indicates the highest level. D2 line indicates the 20dB offset below D1. It shows compliance to the requirement.

Please Refer to Appendix Of this test report.

4 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).

5 MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

6 APPENDIX

20DB EMISSION BANDWIDTH

TEST RESULT

TestMode	Antenna	Channel	20db EBW[MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
DH5	Ant1	2402	0.942	2401.544	2402.486	---	PASS
		2441	0.957	2440.544	2441.501	---	PASS
		2480	0.945	2479.544	2480.489	---	PASS
2DH5	Ant1	2402	1.311	2401.349	2402.660	---	PASS
		2441	1.284	2440.367	2441.651	---	PASS
		2480	1.320	2479.343	2480.663	---	PASS
3DH5	Ant1	2402	1.278	2401.355	2402.633	---	PASS
		2441	1.278	2440.361	2441.639	---	PASS
		2480	1.281	2479.355	2480.636	---	PASS

TEST GRAPHS

DH5_Ant1_2402

DH5_Ant1_2441

DH5_Ant1_2480

2DH5_Ant1_2402

2DH5_Ant1_2441

2DH5_Ant1_2480

3DH5_Ant1_2402

3DH5_Ant1_2441

3DH5_Ant1_2480

Center Freq 2.480000000 GHz
PNO: Wide
IFGain:Low
Trig: Free Run
#Atten: 40 dB
#Avg Type: RMS
Avg|Hold: 100/100
Ref Offset 11 dB
10 dB/div
Ref 30.00 dBm
ΔMkr3 1.281 MHz
-0.222 dB
Center 2.480000 GHz
#Res BW 20 kHz
#VBW 62 kHz
Span 3.000 MHz
Sweep 7.200 ms (1001 pts)
1 N 1 f 2.479 355 GHz -17.416 dBm
2 N 1 f 2.480 174 GHz 2.713 dBm
3 Δ1 1 f (Δ) 1.281 MHz (Δ) -0.222 dB
Frequency
Auto Tune
Center Freq
2.480000000 GHz
Start Freq
2.478500000 GHz
Stop Freq
2.481500000 GHz
CF Step
300.000 kHz
Auto
Man
Freq Offset
0 Hz
Scale Type
Log
Lin

OCCUPIED CHANNEL BANDWIDTH

TEST RESULT

TestMode	Antenna	Channel	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
DH5	Ant1	2402	0.86630	2401.570	2402.436	---	PASS
		2441	0.86650	2440.569	2441.435	---	PASS
		2480	0.87112	2479.563	2480.434	---	PASS
2DH5	Ant1	2402	1.1893	2401.410	2402.599	---	PASS
		2441	1.1892	2440.411	2441.600	---	PASS
		2480	1.1895	2479.409	2480.598	---	PASS
3DH5	Ant1	2402	1.1980	2401.400	2402.598	---	PASS
		2441	1.1914	2440.407	2441.598	---	PASS
		2480	1.2054	2479.395	2480.600	---	PASS

TEST GRAPHS

DH5_Ant1_2402

DH5_Ant1_2441

DH5_Ant1_2480

2DH5_Ant1_2402

2DH5_Ant1_2441

2DH5_Ant1_2480

3DH5_Ant1_2402

3DH5_Ant1_2441

3DH5_Ant1_2480

Keysight Spectrum Analyzer - Occupied BW
Center Freq 2.480000000 GHz
Center Freq: 2.480000000 GHz
Trig: Free Run
Avg|Hold: 100/100
#Atten: 40 dB
Radio Std: None
Radio Device: BTS
Frequency
Ref Offset 11 dB
10 dB/div
Ref 30.00 dBm
Mkr1 2.480162 GHz
0.63253 dBm
Center Freq
2.480000000 GHz
Center 2.480000 GHz
#Res BW 20 kHz
#VBW 62 kHz
Span 3.000 MHz
Sweep 7.2 ms
CF Step
300.000 kHz
Auto
Man
Occupied Bandwidth
1.2054 MHz
Total Power
12.5 dBm
Transmit Freq Error
-2.340 kHz
% of OBW Power
99.00 %
x dB Bandwidth
1.362 MHz
x dB
-26.00 dB
Freq Offset
0 Hz
MSG
STATUS

MAXIMUM CONDUCTED OUTPUT POWER

PEAK POWER TEST RESULT

TestMode	Antenna	Channel	Result[dBm]	Result[mW]	Limit[dBm]	Verdict	Power setting
DH5	Ant1	2402	8.56	7.18	≤20.97	PASS	defult
		2441	8.34	6.82	≤20.97	PASS	defult
		2480	7.12	5.15	≤20.97	PASS	defult
2DH5	Ant1	2402	9.28	8.47	≤20.97	PASS	defult
		2441	9.42	8.75	≤20.97	PASS	defult
		2480	7.80	6.03	≤20.97	PASS	defult
3DH5	Ant1	2402	9.45	8.81	≤20.97	PASS	defult
		2441	9.68	9.29	≤20.97	PASS	defult
		2480	8.02	6.34	≤20.97	PASS	defult

4.3.1 AVERAGE POWER TEST RESULT

TestMode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict	Power setting
DH5	Ant1	2402	7.04	/	PASS	defult
		2441	6.76	/	PASS	defult
		2480	5.58	/	PASS	defult
2DH5	Ant1	2402	5.96	/	PASS	defult
		2441	5.86	/	PASS	defult
		2480	4.38	/	PASS	defult
3DH5	Ant1	2402	5.98	/	PASS	defult
		2441	5.87	/	PASS	defult
		2480	4.45	/	PASS	defult

CARRIER FREQUENCY SEPARATION

TEST RESULT

TestMode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
DH5	Ant1	Hop	0.988	≥0.957	PASS
2DH5	Ant1	Hop	1.146	≥0.880	PASS
3DH5	Ant1	Hop	1.318	≥1.281	PASS

TEST GRAPHS

DH5_Ant1_Hop

2DH5_Ant1_Hop

3DH5_Ant1_Hop

Center Freq 2.441500000 GHz
PNO: Wide
IFGain:Low
Trig: Free Run
#Atten: 40 dB
#Avg Type: RMS
Avg|Hold:>100/100
Ref Offset 11 dB
10 dB/div
Ref 30.00 dBm
Log
ΔMkr2 1.318 MHz
-0.495 dB
1
2Δ1
Start 2.440500 GHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 2.442500 GHz
Sweep 1.000 ms (1001 pts)
Frequency
Auto Tune
Center Freq
2.441500000 GHz
Start Freq
2.440500000 GHz
Stop Freq
2.442500000 GHz
CF Step
200.000 kHz
Auto
Man
Freq Offset
0 Hz
Scale Type
Log
Lin

TIME OF OCCUPANCY

TEST RESULT

TestMode	Antenna	Channel	BurstWidth [ms]	TotalHops [Num]	Result[s]	Limit[s]	Verdict
DH1	Ant1	Hop	0.40	330	0.133	≤0.4	PASS
DH3	Ant1	Hop	1.66	210	0.348	≤0.4	PASS
DH5	Ant1	Hop	2.91	90	0.262	≤0.4	PASS
2DH1	Ant1	Hop	0.40	330	0.131	≤0.4	PASS
2DH3	Ant1	Hop	1.65	170	0.28	≤0.4	PASS
2DH5	Ant1	Hop	2.90	60	0.174	≤0.4	PASS
3DH1	Ant1	Hop	0.40	320	0.126	≤0.4	PASS
3DH3	Ant1	Hop	1.64	170	0.28	≤0.4	PASS
3DH5	Ant1	Hop	2.90	130	0.376	≤0.4	PASS

TEST GRAPHS

DH1_Ant1_Hop

DH3_Ant1_Hop

Center Freq 2.441000000 GHz
Trig Delay-2.000 ms
#Avg Type: RMS
Trig: Video
#Atten: 40 dB
Ref Offset 11 dB
10 dB/div Ref 30.00 dBm
ΔMkr2 1.659 ms
2.86 dB
Center 2.441000000 GHz
Res BW 1.0 MHz
#VBW 3.0 MHz
Span 0 Hz
Sweep 10.13 ms (8000 pts)
Frequency
Auto Tune
Center Freq 2.441000000 GHz
Start Freq 2.441000000 GHz
Stop Freq 2.441000000 GHz
CF Step 1.000000 MHz
Freq Offset 0 Hz
Scale Type

Center Freq 2.441000000 GHz
Trig Delay0.000 s
#Avg Type: RMS
Trig: Video
#Atten: 40 dB
Ref Offset 11 dB
10 dB/div Ref 30.00 dBm
Center 2.441000000 GHz
Res BW 510 kHz
#VBW 3.0 MHz
Span 0 Hz
Sweep 3.162 s (30000 pts)
Frequency
Auto Tune
Center Freq 2.441000000 GHz
Start Freq 2.441000000 GHz
Stop Freq 2.441000000 GHz
CF Step 510.000 kHz
Freq Offset 0 Hz
Scale Type

DH5_Ant1_Hop

2DH1_Ant1_Hop



2DH3_Ant1_Hop

2DH5_Ant1_Hop

3DH1_Ant1_Hop

3DH3_Ant1_Hop

3DH5_Ant1_Hop

Center Freq 2.441000000 GHz
Trig Delay-2.000 ms
#Avg Type: RMS
Trig: Video
#Atten: 40 dB
Frequency
Auto Tune
Ref Offset 11 dB
10 dB/div
Ref 30.00 dBm
ΔMkr2 2.896 ms
1.59 dB
Center Freq
2.441000000 GHz
Start Freq
2.441000000 GHz
Stop Freq
2.441000000 GHz
CF Step
1.000000 MHz
Auto
Man
Freq Offset
0 Hz
Scale Type
Log
Lin
Center 2.441000000 GHz
Res BW 1.0 MHz
#VBW 3.0 MHz
Span 0 Hz
Sweep 10.13 ms (8000 pts)

Center Freq 2.441000000 GHz
Trig Delay0.000 s
#Avg Type: RMS
Trig: Video
#Atten: 40 dB
Frequency
Auto Tune
Ref Offset 11 dB
10 dB/div
Ref 30.00 dBm
Center Freq
2.441000000 GHz
Start Freq
2.441000000 GHz
Stop Freq
2.441000000 GHz
CF Step
510.000 kHz
Auto
Man
Freq Offset
0 Hz
Scale Type
Log
Lin
Center 2.441000000 GHz
Res BW 510 kHz
#VBW 3.0 MHz
Span 0 Hz
Sweep 3.162 s (30000 pts)

NUMBER OF HOPPING CHANNELS

TEST RESULT

TestMode	Antenna	Channel	Result[Num]	Limit[Num]	Verdict
DH5	Ant1	Hop	79	≥15	PASS
2DH5	Ant1	Hop	79	≥15	PASS
3DH5	Ant1	Hop	79	≥15	PASS

TEST GRAPHS

DH5_Ant1_Hop

2DH5_Ant1_Hop



3DH5_Ant1_Hop


Center Freq 2.441750000 GHz
PNO: Fast
IFGain:Low
Trig: Free Run
#Atten: 40 dB
#Avg Type: RMS
Avg|Hold: 1000/1000
Ref Offset 11 dB
10 dB/div
Ref 30.00 dBm
Log
Start 2.40000 GHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 2.48350 GHz
Sweep 8.000 ms (1001 pts)
Frequency
Auto Tune
Center Freq
2.441750000 GHz
Start Freq
2.400000000 GHz
Stop Freq
2.483500000 GHz
CF Step
8.350000 MHz
Auto
Man
Freq Offset
0 Hz
Scale Type
Log
Lin

BAND EDGE MEASUREMENTS

TEST RESULT

TestMode	Antenna	ChName	Channel	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
DH5	Ant1	Low	2402	8.09	-25.66	≤-11.91	PASS
		High	2480	6.85	-44.04	≤-13.15	PASS
		Low	Hop_2402	6.85	-43.96	≤-13.15	PASS
		High	Hop_2480	8.12	-44.62	≤-11.88	PASS
2DH5	Ant1	Low	2402	7.38	-43.11	≤-12.62	PASS
		High	2480	5.96	-44.44	≤-14.05	PASS
		Low	Hop_2402	7.66	-44.87	≤-12.34	PASS
		High	Hop_2480	6.63	-43.64	≤-13.37	PASS
3DH5	Ant1	Low	2402	7.63	-42.36	≤-12.37	PASS
		High	2480	6.20	-44.58	≤-13.8	PASS
		Low	Hop_2402	3.87	-44.32	≤-16.13	PASS
		High	Hop_2480	5.45	-44.08	≤-14.55	PASS

TEST GRAPHS

DH5_Ant1_Low_2402



DH5_Ant1_High_2480



DH5_Ant1_Low_Hop_2402



DH5_Ant1_High_Hop_2480



2DH5_Ant1_Low_2402



2DH5_Ant1_High_2480



2DH5_Ant1_Low_Hop_2402



2DH5_Ant1_High_Hop_2480



3DH5_Ant1_Low_2402



3DH5_Ant1_High_2480



3DH5_Ant1_Low_Hop_2402



3DH5_Ant1_High_Hop_2480



CONDUCTED SPURIOUS EMISSION

TEST RESULT

TestMode	Antenna	Channel	FreqRange [MHz]	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
DH5	Ant1	2402	Reference	7.66	7.66	---	PASS
			30~1000	7.66	-53.59	≤-12.34	PASS
			1000~26500	7.66	-38.47	≤-12.34	PASS
		2441	Reference	7.08	7.08	---	PASS
			30~1000	7.08	-53.91	≤-12.92	PASS
			1000~26500	7.08	-38.76	≤-12.92	PASS
		2480	Reference	5.88	5.88	---	PASS
			30~1000	5.88	-54.17	≤-14.12	PASS
			1000~26500	5.88	-39.02	≤-14.12	PASS
2DH5	Ant1	2402	Reference	5.78	5.78	---	PASS
			30~1000	5.78	-54.91	≤-14.22	PASS
			1000~26500	5.78	-38.42	≤-14.22	PASS
		2441	Reference	4.68	4.68	---	PASS
			30~1000	4.68	-53.78	≤-15.32	PASS
			1000~26500	4.68	-38.66	≤-15.32	PASS
		2480	Reference	5.46	5.46	---	PASS
			30~1000	5.46	-54.4	≤-14.54	PASS
			1000~26500	5.46	-38.16	≤-14.54	PASS
3DH5	Ant1	2402	Reference	5.66	5.66	---	PASS
			30~1000	5.66	-53.98	≤-14.34	PASS
			1000~26500	5.66	-38.47	≤-14.34	PASS
		2441	Reference	4.51	4.51	---	PASS
			30~1000	4.51	-54.36	≤-15.49	PASS
			1000~26500	4.51	-38.39	≤-15.49	PASS
		2480	Reference	5.12	5.12	---	PASS
			30~1000	5.12	-54.33	≤-14.88	PASS
			1000~26500	5.12	-37.88	≤-14.88	PASS

TEST GRAPHS

DH5_Ant1_2402_0~Reference

DH5_Ant1_2402_30~1000



DH5_Ant1_2402_1000~26500

DH5_Ant1_2441_0~Reference

DH5_Ant1_2441_30~1000



DH5_Ant1_2441_1000~26500

DH5_Ant1_2480_0~Reference

DH5_Ant1_2480_30~1000



DH5_Ant1_2480_1000~26500

2DH5_Ant1_2402_0~Reference

2DH5_Ant1_2402_30~1000



2DH5_Ant1_2402_1000~26500

2DH5_Ant1_2441_0~Reference

2DH5_Ant1_2441_30~1000



2DH5_Ant1_2441_1000~26500

2DH5_Ant1_2480_0~Reference

2DH5_Ant1_2480_30~1000



2DH5_Ant1_2480_1000~26500

3DH5_Ant1_2402_0~Reference

3DH5_Ant1_2402_30~1000



3DH5_Ant1_2402_1000~26500

3DH5_Ant1_2441_0~Reference

3DH5_Ant1_2441_30~1000

3DH5_Ant1_2441_1000~26500

3DH5_Ant1_2480_0~Reference

3DH5_Ant1_2480_30~1000

3DH5_Ant1_2480_1000~26500

Center Freq 13.750000000 GHz
PNO: Fast
IFGain:Low
Trig: Free Run
#Atten: 20 dB
#Avg Type: RMS
Avg|Hold: 10/10
Ref Offset 11 dB
10 dB/div
Ref 20.00 dBm
Mkr2 25.989 15 GHz
-37.882 dBm
Start 1.00 GHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 26.50 GHz
Sweep 2.438 s (30001 pts)
1 N 1 f 2.479 85 GHz 3.365 dBm
2 N 1 f 25.989 15 GHz -37.882 dBm
Frequency
Auto Tune
Center Freq
13.750000000 GHz
Start Freq
1.000000000 GHz
Stop Freq
26.500000000 GHz
CF Step
2.550000000 GHz
Auto
Man
Freq Offset
0 Hz
Scale Type
Log
Lin

DUTY CYCLE

TEST RESULT

TestMode	Antenna	Channel	ON Time [ms]	Period [ms]	X	DC [%]	xFactor	Limit	Verdict
DH5	Ant1	2402	2.91	3.75	0.7760	77.60	1.10	---	PASS
		2441	2.91	3.75	0.7760	77.60	1.10	---	PASS
		2480	2.91	3.75	0.7760	77.60	1.10	---	PASS
2DH5	Ant1	2402	2.90	3.75	0.7733	77.33	1.12	---	PASS
		2441	2.90	3.75	0.7733	77.33	1.12	---	PASS
		2480	2.90	3.75	0.7733	77.33	1.12	---	PASS
3DH5	Ant1	2402	2.89	3.75	0.7707	77.07	1.13	---	PASS
		2441	2.90	3.75	0.7733	77.33	1.12	---	PASS
		2480	2.90	3.75	0.7733	77.33	1.12	---	PASS

TEST GRAPHS

DH5_Ant1_2402



DH5_Ant1_2441



DH5_Ant1_2480



2DH5_Ant1_2402



2DH5_Ant1_2441



2DH5_Ant1_2480



3DH5_Ant1_2402



3DH5_Ant1_2441



3DH5_Ant1_2480


Keysight Spectrum Analyzer - Swept SA
Center Freq 2.480000000 GHz
Trig Delay-2.000 ms
Trig: Video
#Avg Type: RMS
PNO: Fast
IFGain:Low
#Atten: 20 dB
Ref Offset 11 dB
10 dB/div
Ref 21.00 dBm
ΔMkr3 3.750 ms
-0.01 dB
Center 2.480000000 GHz
Span 0 Hz
Res BW 8 MHz
#VBW 8.0 MHz
Sweep 10.00 ms (1001 pts)
1 N 1 t 5.370 ms 6.13 dBm
2 Δ1 1 t (Δ) 2.900 ms (Δ) 0.50 dB
3 Δ1 t (Δ) 3.750 ms (Δ) -0.01 dB
Frequency
Auto Tune
Center Freq
2.480000000 GHz
Start Freq
2.480000000 GHz
Stop Freq
2.480000000 GHz
CF Step
8.000000 MHz
Auto
Man
Freq Offset
0 Hz
Scale Type
Log
Lin