Certificate #6613.01

EMC TEST REPORT

Applicant:	HMD Global Oy
Address:	Bertel Jungin aukio 9, 02600 Espoo, Finland

Manufacturer or Supplier:	HMD Global Oy
Address:	Bertel Jungin aukio 9, 02600 Espoo, Finland
Product:	Mobile phone
Brand Name:	HMD
Model Name:	H1702V
FCC ID:	2AJOTTA-1702
Date of tests:	Jan, 13, 2025 ~ Mar. 13, 2025

The submitted sample of the above equipment has been tested for according to the requirements of the following standards:

☐ **FCC Part 15, Subpart B, Class A**
☒ **FCC Part 15, Subpart B, Class B**
☒ **ANSI C63.4:2014**

CONCLUSION: The submitted sample was found to <u>COMPLY</u> with the test requirement

Prepared by Hanwen Xu Engineer / Mobile Department	Approved by Peibo Sun Manager / Mobile Department
Xu Hanwen	Sun Peibo
Date: Mar. 13, 2025	Date: Mar. 13, 2025

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/ and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

TABLE OF CONTENTS

TABLE OF CONTENTS 2
RELEASE CONTROL RECORD 3
1 GENERAL INFORMATION 4
1.1 GENERAL DESCRIPTION OF EUT 4
1.2 SUMMARY OF TEST RESULTS 7
1.3 MEASUREMENT UNCERTAINTY 8
1.4 DESCRIPTION OF TEST MODES 9
1.5 DESCRIPTION OF SUPPORT UNITS 10
2 EMISSION TEST 11
2.1.1 CONDUCTED EMISSION MEASUREMENT 11
2.1.2 IMITS OF CONDUCTED EMISSION MEASUREMENT 11
2.1.3 TEST INSTRUMENTS 11
2.1.3 TEST PROCEDURES 12
2.1.4 DEVIATION FROM TEST STANDARD 12
2.1.5 TEST SETUP 13
2.1.6 EUT OPERATING CONDITIONS 13
2.1.7 TEST RESULTS 14
2.2 RADIATED EMISSION MEASUREMENT 16
2.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT 16
2.2.2 TEST INSTRUMENTS 17
2.2.3 TEST PROCEDURE 18
2.2.4 DEVIATION FROM TEST STANDARD 19
2.2.5 TEST SETUP 20
2.2.6 EUT OPERATING CONDITIONS 20
2.2.7 TEST RESULTS 21
3 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB 25

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
PSU-NQN2412090110EM01	Original release	Mar. 13, 2025

1 GENERAL INFORMATION

1.1 GENERAL DESCRIPTION OF EUT

PRODUCT*	Mobile phone	
BRAND NAME*	HMD	
MODEL NAME*	H1702V	
NOMINAL VOLTAGE*	3.87Vdc (Li-ion, battery)	
MODULATION TYPE*	**BT_LE**	GFSK
	Bluetooth	GFSK, π/4-DQPSK, 8DPSK
	FM	FM
	NFC	ASK
	WLAN	DSSS, OFDM
	GPS/GALILEO	BPSK
	GSM/GPRS/EDGE	GMSK, 8PSK
	WCDMA	QPSK/16QAM
	LTE	QPSK/16QAM/64QAM/256QAM
	5G NR	DFT-s-OFDM(π/2BPSK,QPSK,16QAM,64QAM,256QAM); CP-OFDM(QPSK,16QAM,64QAM,256QAM);
OPERATING FREQUENCY*	**Bluetooth/BT_LE**	2402MHz ~ 2480MHz
	FM	87.5MHz ~ 108MHz
	NFC	13.56 MHz
	WLAN	2412 ~ 2462MHz for 11b/g/n(HT20/40) 5180 ~ 5240MHz, 5260 ~ 5320 MHz, 5500~5720MHz, 5745 ~ 5825 MHz for 11a/ n(HT20)/ n(HT40) / ac(VHT20)/ ac(VHT40) / ac(VHT80)
	GPS/GALILEO/GLONASS/BDS	1559MHz ~ 1610MHz
	GSM	824.2MHz ~ 848.8MHz (FOR GSM 850) 1850.2MHz ~ 1909.8MHz (FOR GSM 1900)
	WCDMA	1852.4MHz ~ 1907.6MHz(FOR WCDMA Band 2) 826.4MHz ~ 846.6MHz (FOR WCDMA Band 5)

OPERATING FREQUENCY	LTE	1850.7MHz ~ 1909.3MHz (FOR LTE Band2) 1710.7MHz ~ 1754.3MHz (FOR LTE Band4) 824.7MHz ~ 848.3MHz (FOR LTE Band5) 2502.5MHz ~ 2567.5MHz (FOR LTE Band7) 699.7MHz ~ 715.3MHz (FOR LTE Band12) 779.5MHz ~ 784.5MHz (FOR LTE Band13) 3552.5MHz ~3697.5MHz (FOR LTE Band48) 1710.7MHz ~ 1779.3MHz (FOR LTE Band66) **UL+DL:** CA_2A-4A CA_4A-5A CA_4A-13A CA_66B CA_66C CA_2A-66A CA_2A-13A CA_2A-5A CA_5B CA_48B CA_48C CA_5A-66A CA_13A-66A
	5G NR	**SA:** n2 (1852.5MHz ~1907.5MHz) n5(826.5MHz ~ 846.5MHz) n48(3555 ~ 3694.98MHz) n66(1712.5 ~ 1777.5MHz) n77(Part27Q)(3455.01 ~ 3544.98MHz) n77(Part27O)(3705 ~ 3974.97MHz) **ENDC:** DC 2A-n5A DC 2A-n66A DC 2A-n77A DC 5A-n2A DC 5A-n66A DC 5A-n77A DC 13A-n2A DC 13A-n66A DC 13A-n77A DC 48A-n5A DC 66A-n2A DC 66A-n5A DC 66A-n77A
HW VERSION*	V1.0	
SW VERSION*	000T_0_310	
I/O PORTS*	Refer to user's manual	
CABLE SUPPLIED*	USB cable: non-shielded cable, with w/o ferrite core, 1.0meter	
ACCESSORY DEVICES*	Refer to note as below	

NOTE:

1. *Since the above data and/or information is provided by the client relevant results or conclusions of this report are only made for these data and/or information, Test Lab is not responsible for the authenticity, integrity and results of the data and information and/or the validity of the conclusion.
2. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
3. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in the test report.
4. The differences between the sample 1 and sample 2 as Listings below, others are the same. And only the worst case was shown in the test report.

Raptor 5G(H1702V)

Object	**Sample 1** **1st source**		**Sample 2** **2nd source**	
	Specifications	**Supplier**	**Specifications**	**Supplier**
Display	Y92232	DZX	TD-TCHJ6615-5D	CDOT
Memory	LPDDR4X 6GB FLXC4006G-49	Longsys	BWCC4X32N2A-48G-X	Biwin
	128GB eMMC5.1 MEMDNN128G-M1D03	Longsys	MEMDNN128G-M1D03	Biwin
Motor	C0830H-C138ZN-021	KunWang	CY0830-05-FPC-182	Chaoying
Mic	SM2718B381YR2-01	Rayking	S150B381-155	Goertek
Charger IC	UPM6720	Unisemi	SC8541CFFR	Southchip

5. List of Accessory:

ACCESSORIES	**BRAND**	**MANUFACTURER**	**MODEL**	**SPECIFICATION**
Battery	HMD	HuiZhou GanFeng LiEnergy Battery Technology Co., Ltd.	HBA-5033AA	Capacity：3.87Vdc, 4900mAh
USB Cable	Saibao	Saibao (Jiangxi) Industry Co.,Ltd.	SZN-A047A	Signal Line,1.0meter

1.2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart B			
Standard Section	**Test Item**	**Result**	**Test lab***
FCC Part 15, Subpart B, Class B ANSI C63.4:2014	Conducted Test	Compliance	A
	Radiated Emission Test (30MHz ~ 1GHz)	Compliance	A
	Radiated Emission Test (Above 1GHz)	Compliance	A

***Test Lab Information Reference**

Lab A:

Huarui 7Layers High Technology (Suzhou) Co., Ltd.

Lab Address:

Tower N, Innovation Center, 88 Zuyi Road, High-tech District, Suzhou City, Anhui Province

Accredited Test Lab Cert 6613.01

The FCC Site Registration No. is 434559; The Designation No. is CN1325.

1.3 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	150kHz ~ 30MHz	±2.70dB
Radiated emissions	30MHz~1GHz	±4.98dB
	1GHz ~6GHz	±4.70dB
	6GHz ~18GHz	±4.60dB
	18GHz ~40GHz	±4.12dB



The verdicts in this test report are given according the above diagram:

Case	Measured Value	Uncertainty Range	Verdict
1	below pass mark	below pass mark	Passed
2	below pass mark	within pass mark	Passed
3	above pass mark	within pass mark	Failed
4	above pass mark	above pass mark	Failed

That means, the laboratory applies, as decision rule (see ISO/IEC 17025:2017), the so-called shared risk principle.

1.4 DESCRIPTION OF TEST MODES

Test Mode	Test Condition
Radiated emission test	
1	GSM850 Idle + Adapter + USB cable + Front Camera On + SIM + sample1 + SD + earphone
2	WCDMA B5 Idle + Adapter + USB cable + Back Camera On + SIM + sample1 + SD + earphone
3	LTE B5 Idle + Adapter + USB cable + flashlight on + SIM + sample1 + SD + earphone
4	LTE B12 Idle + Adapter + USB cable + MPG4 + SIM + sample1 + SD + earphone
5	LTE B13 Idle + Adapter + USB cable + NFC + SIM + sample1 + SD + earphone
6	NR N5 Idle + Adapter + USB cable + FM + SIM + sample1 + SD + earphone
7	GSM850 Idle + USB Link + Data Transmission + Notebook to EUT + SIM + sample1 + SD + earphone
8	CA 5B Idle + USB Link + Data Transmission + SD to Notebook + SIM + sample1 + SD + earphone
9	Powered by battery + SIM + sample1 + SD
10	worse of 1~9 + sample2

Test Mode	Test Condition
Conducted emission test	
1	GSM850 Idle + Adapter + USB cable + Front Camera On + SIM + sample1 + SD + earphone
2	WCDMA B5 Idle + Adapter + USB cable + Back Camera On + SIM + sample1 + SD + earphone
3	LTE B5 Idle + Adapter + USB cable + flashlight on + SIM + sample1 + SD + earphone
4	LTE B12 Idle + Adapter + USB cable + MPG4 + SIM + sample1 + SD + earphone
5	LTE B13 Idle + Adapter + USB cable + NFC + SIM + sample1 + SD + earphone
6	NR N5 Idle + Adapter + USB cable + FM + SIM + sample1 + SD + earphone
7	GSM850 Idle + USB Link + Data Transmission + Notebook to EUT + SIM + sample1 + SD + earphone
8	CA 5B Idle + USB Link + Data Transmission + SD to Notebook + SIM + sample1 + SD + earphone
9	worse of 1~8 + sample2

NOTE:

1. For radiated emission test, test mode 2 was the verification case and only this mode was presented in this report
2. For conducted emission test, test mode 3 was the verification case and only this mode was presented in this report

1.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

FOR All TESTS

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	Laptop	Lenovo	Thinkpad E14	SL10W47313	N/A
2	Micro SD	SAM SUNG	N/A	N/A	N/A
3	Universal radio communication tester	Rohde&Schwarz	CMW500	169399	N/A
4	WIFI Router	HUAWEI	N/A	N/A	N/A
5	Adapter	N/A	N/A	N/A	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	USB Line: Shielded, Detachable 1.0m;

2 EMISSION TEST

2.1.1 CONDUCTED EMISSION MEASUREMENT

2.1.2 IMITS OF CONDUCTED EMISSION MEASUREMENT

TEST STANDARD: FCC Part 15, Subpart B (Section: 15.107 a CLASS B)

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBμV)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

TEST STANDARD: FCC Part 15, Subpart B (Section: 15.107 b CLASS A)

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBμV)	
	Quasi-peak	Average
0.15 ~ 0.5	79	66
0.5 ~ 30	73	60

NOTE: 1.The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

3. All emanations from a class A/B digital device or system, including any network of conductors

and apparatus connected thereto, shall not exceed the level of field strengths specified above.

2.1.3 TEST INSTRUMENTS

Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Due Date
WIDEBANDRADIO COMMUNICATION TESTER	Rohde&Schwarz	CMW500	169399	Jun.19,24	Jun.18,26
EMI Test Receiver	Rohde&Schwarz	ESR3	102749	Mar.28,24	Mar.27,26
ELEKTRA test software	Rohde&Schwarz	ELEKTRA	NA	N/A	N/A
LISN network	Rohde&Schwarz	ENV216	102640	Mar.28,24	Mar.27,26
CABLE	Rohde&Schwarz	W61.01	N/A	Apr.27,24	Apr.26,25
CABLE	Rohde&Schwarz	W601	N/A	Apr.27,24	Apr.26,25

NOTE: 1. The test was performed in CE shielded room.

2.1.3 TEST PROCEDURES

a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.

b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.

c. The frequency range from 150 kHz to 30MHz was searched. Emission levels under (Limit - 20dB) were not recorded.

NOTE: All modes of operation were investigated and the worst-case emissions are reported.

2.1.4 DEVIATION FROM TEST STANDARD

No deviation.

2.1.5 TEST SETUP



Note: 1.Support units were connected to second LISN.
2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

2.1.6 EUT OPERATING CONDITIONS

a. Turned on the power and connected of all equipment.
b. EUT was operated according to the use type described in the manufacturer's specifications or the user's manual.

2.1.7 TEST RESULTS

TEST VOLTAGE	Input 120 Vac, 60 Hz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
ENVIRONMENTAL CONDITIONS	26deg. C, 51%RH	TESTED BY	Hanwen Xu

Rg	Frequency [MHz]	QPK Level [dBμV]	QPK Limit [dBμV]	QPK Margin [dB]	CAV Level [dBμV]	CAV: AVG Limit [dBμV]	CAV Margin [dB]	Correction [dB]	Line	Meas. BW [kHz]
1	0.186	51.03	64.21	13.18	35.79	54.21	18.42	12.17	L1	9.000
1	0.519	47.78	56.00	8.22	42.01	46.00	3.99	11.75	L1	9.000
1	1.869	31.16	56.00	24.84	21.89	46.00	24.11	11.76	L1	9.000
1	3.876	28.04	56.00	27.96	18.43	46.00	27.57	11.78	L1	9.000
1	8.489	43.00	60.00	17.00	34.38	50.00	15.62	11.82	L1	9.000
1	24.576	30.96	60.00	29.04	20.93	50.00	29.07	11.89	L1	9.000

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Limit value- Emission level
4. Correction factor = Insertion loss + Cable loss + Attenuate
5. Emission Level = Correction Factor + Reading Value.



TEST VOLTAGE	INPUT 120 VAC, 60 HZ	**DETECTOR FUNCTION & RESOLUTION BANDWIDTH**	QUASI-PEAK (QP) / AVERAGE (AV), 9 KHZ
ENVIRONMENTAL CONDITIONS	26DEG. C, 51%RH	**TESTED BY**	HANWEN XU

Rg	Frequency [MHz]	QPK Level [dBμV]	QPK Limit [dBμV]	QPK Margin [dB]	CAV Level [dBμV]	CAV: AVG Limit [dBμV]	CAV Margin [dB]	Correction [dB]	Line	Meas. BW [kHz]
1	0.155	52.10	65.75	13.65	36.74	55.75	19.01	12.15	N	9.000
1	0.524	37.90	56.00	18.10	31.28	46.00	14.72	12.77	N	9.000
1	1.383	34.87	56.00	21.13	23.45	46.00	22.55	12.74	N	9.000
1	4.628	31.87	56.00	24.13	22.17	46.00	23.83	12.76	N	9.000
1	10.437	46.60	60.00	13.40	36.36	50.00	13.64	12.79	N	9.000
1	26.385	35.56	60.00	24.44	24.26	50.00	25.74	12.88	N	9.000

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Limit value- Emission level
4. Correction factor = Insertion loss + Cable loss + Attenuate
5. Emission Level = Correction Factor + Reading Value.



2.2 RADIATED EMISSION MEASUREMENT

2.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

TEST STANDARD: FCC Part 15, Subpart B (Section: 15.109)
Emissions radiated outside of the specified bands, shall be according to the general radiated limits as following:

Radiated Emissions Limits at 3 meters (dBμV/m)		
Frequencies (MHz)	**FCC 15B Class A**	**FCC 15B Class B**
30-88	49	40
88-216	53.5	43.5
216-960	56	46
960-1000	59.5	54
Above 1000	Avg: 59.5 Peak: 79.5	Avg: 54 Peak: 74

Frequency Range (For unintentional radiators)

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705-108	1000
108-500	2000
500-1000	5000
Above 1000	5th harmonic of the highest frequency or 40GHz, whichever is lower

NOTE:
1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.
4. QP detector shall be applied if not specified.

2.2.2 TEST INSTRUMENTS

Frequency range below 1GHz

Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Due Date
WIDEBANDRADIO COMMUNICATION TESTER	Rohde&Schwarz	CMW500	169399	Jun.19,24	Jun.18,26
3m Semi-anechoic Chamber	TDK	9m*6m*6m	HRSW-SZ-EMC-02Chamber	Nov.24,22	Nov.23,25
Bilog Antenna	SCHWARZBECK	VULB 9163	1264	Dec.26,23	Dec.25,25
EMI Test Receiver	R&S	ESW44	101973	Mar.28,24	Mar.27,26
Measurement Software	R&S	ELEKTRA	N/A	N/A	N/A
6DB attenuator	Tonscend Technology Co., Ltd	N/A	23062787	N/A	N/A
Pre-Amplifier	R&S	SCU08F1	101028	Jan.22,24	Jan.21,26
CABLE	R&S	W13.01	N/A	Apr.27,24	Apr.26,25
CABLE	R&S	W13.02	N/A	Apr.27,24	Apr.26,25
CABLE	R&S	W12.14	N/A	Apr.27,24	Apr.26,25

Frequency range above 1GHz

Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Due Date
WIDEBANDRADIO COMMUNICATION TESTER	Rohde&Schwarz	CMW500	169399	Jun.19,24	Jun.18,26
3m Fully-anechoic Chamber	TDK	9m*6m*6m	HRSW-SZ-EMC-01Chamber	Nov.24,22	Nov.23,25
Horn Antenna	ETS-LINDGREN	3117	227836	Aug.22,23	Aug.21,25
EMI Test Receiver	R&S	ESW44	101973	Mar.28,24	Mar.27,26
Pre-Amplifier	R&S	SCU08F1	101028	Jan.22,24	Jan.21,26
Measurement Software	R&S	ELEKTRA	N/A	N/A	N/A
CABLE	R&S	W13.01	N/A	Apr.27,24	Apr.26,25
CABLE	R&S	W13.02	N/A	Apr.27,24	Apr.26,25
CABLE	R&S	W12.14	N/A	Apr.27,24	Apr.26,25

NOTE: 1. The calibration interval of the above test instruments is 12/ 24/ 36 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.

2. The test was performed in 3m Chamber.

2.2.3 TEST PROCEDURE

<Frequency Range below 1GHz>

The basic test procedure was in accordance with ANSI C63.4:2014 (section 12).

a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. The height of antenna is varied from 1 meter to 4 meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1GHz.

NOTE:

1. The resolution bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
3. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) (if the raw value not contains the amplifier);
4. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Amplifier Gain(dB) (if the raw value contains the amplifier).
5. Margin value = Limit value -Emission level.

<Frequency Range above 1GHz>

a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter fully-anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. The bore sight should be used during the test above 1GHz.

d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz

NOTE:

1. The resolution bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth is 1MHz and video bandwidth of test receiver/spectrum analyzer is 3MHz for Peak detection at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth of test receiver/spectrum analyzer is 1Hz for Average detection (AV) at frequency above 1GHz.
3. For measurement of frequency above 1000 MHz, the EUT was set 3 meters away from the receiver antenna.
4. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
5. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) (if the raw value not contains the amplifier);
6. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Amplifier Gain(dB) (if the raw value contains the amplifier)
7. Margin value = Limit value- Emission level.

2.2.4 DEVIATION FROM TEST STANDARD

No deviation.

2.2.5 TEST SETUP

<Frequency Range below 1GHz>



<Frequency Range above 1GHz>



Note: Above 1G is a directional antenna depends on the EUT height and the antenna 3dB bandwidth both, refer to section 7.3 of CISPR 16-2-3.

2.2.6 EUT OPERATING CONDITIONS

Same as item 2.1.6.

2.2.7 TEST RESULTS

TEST VOLTAGE	Input 120 Vac, 60 Hz	**FREQUENCY RANGE**	30-1000 MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	**DETECTOR FUNCTION & RESOLUTION BANDWIDTH**	Quasi-Peak, 120 kHz
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	QPK Level [dBµV/m]	QPK Limit [dBµV/m]	QPK Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]	Meas. BW [kHz]
1	38.299	35.71	40.00	4.29	-4.44	H	1	1.00	120.000
1	49.993	35.89	40.00	4.11	-2.82	H	219.2	1.00	120.000
1	92.888	26.85	43.50	16.65	-6.52	H	359	2.00	120.000
1	149.472	27.77	43.50	15.73	-8.13	H	66.6	2.00	120.000
1	261.938	26.79	46.00	19.21	-1.62	H	4.9	1.00	120.000
1	514.461	26.99	46.00	19.01	3.48	H	295.7	1.00	120.000

REMARKS:

1. Peak detector quick scan is shown on the graph and final quasi-peak detector data is measured corresponding to relevant limit and recorded in the data table.
2. Negative sign (-) in the margin column signify levels below the limit.
3. Frequency range scanned: 30MHz to 1000MHz.
4. Only emissions significantly above the equipment noise floor are reported.



TEST VOLTAGE	Input 120 Vac, 60 Hz	**FREQUENCY RANGE**	30-1000 MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70 %RH	**DETECTOR FUNCTION & RESOLUTION BANDWIDTH**	Quasi-Peak, 120 kHz
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	QPK Level [dBµV/m]	QPK Limit [dBµV/m]	QPK Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]	Meas. BW [kHz]
1	35.658	31.46	40.00	8.54	-7.18	V	1	1.00	120.000
1	52.094	29.88	40.00	10.12	-4.20	V	359.1	1.00	120.000
1	95.691	29.94	43.50	13.56	-5.95	V	359.1	1.00	120.000
1	145.107	19.98	43.50	23.52	-8.01	V	4.3	2.00	120.000
1	261.992	24.25	46.00	21.75	-2.04	V	1	1.00	120.000
1	570.290	27.71	46.00	18.29	3.08	V	1	2.00	120.000

REMARKS:

1. Peak detector quick scan is shown on the graph and final quasi-peak detector data is measured corresponding to relevant limit and recorded in the data table.
2. Negative sign (-) in the margin column signify levels below the limit.
3. Frequency range scanned: 30MHz to 1000MHz.
4. Only emissions significantly above the equipment noise floor are reported.



TEST VOLTAGE	Input 120 Vac, 60 Hz	**FREQUENCY RANGE**	1-18 GHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70 %RH	**DETECTOR FUNCTION & RESOLUTION BANDWIDTH**	Peak/Average, 1 MHz
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBµV/m]	PK+ Limit [dBµV/m]	PK+ Margin [dB]	AVG Level [dBµV/m]	AVG Limit [dBµV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,563.000	44.86	74.00	29.14	32.58	54.00	21.42	6.98	H	359	2.00
1	4,218.000	45.35	74.00	28.65	33.86	54.00	20.14	9.74	H	194.6	2.00
1	6,326.500	50.09	74.00	23.91	37.02	54.00	16.98	14.47	H	1	1.00

REMARKS:

1. Peak detector quick scan is shown on the graph and final quasi-peak detector data is measured corresponding to relevant limit and recorded in the data table.
2. Negative sign (-) in the margin column signify levels below the limit.
3. Frequency range scanned: 1GHz to 5th harmonic of the highest frequency or 40GHz, whichever is lower. For frequency above 18GHz, the emission was tested 20db below the limit so the data not recorded in the sheet.
4. Only emissions significantly above the equipment noise floor are reported.



TEST VOLTAGE	Input 120 Vac, 60 Hz	**FREQUENCY RANGE**	1-18 GHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70 %RH	**DETECTOR FUNCTION & RESOLUTION BANDWIDTH**	Peak/Average, 1 MHz
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBµV/m]	PK+ Limit [dBµV/m]	PK+ Margin [dB]	AVG Level [dBµV/m]	AVG Limit [dBµV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,407.500	43.20	74.00	30.80	32.12	54.00	21.88	6.54	V	0.9	2.00
1	3,559.000	44.59	74.00	29.41	32.94	54.00	21.06	8.69	V	58.3	2.00
1	6,125.000	48.80	74.00	25.20	36.25	54.00	17.75	13.78	V	359.1	1.00

REMARKS:

1. Peak detector quick scan is shown on the graph and final quasi-peak detector data is measured corresponding to relevant limit and recorded in the data table.
2. Negative sign (-) in the margin column signify levels below the limit.
3. Frequency range scanned: 1GHz to 5th harmonic of the highest frequency or 40GHz, whichever is lower. For frequency above 18GHz, the emission was tested 20db below the limit so the data not recorded in the sheet.
4. Only emissions significantly above the equipment noise floor are reported.



3 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications were made to the EUT by the lab during the test.

---END---