

**RF EXPOSURE EVALUATION METHOD**

RF EXPOSURE EVALUATION METHOD- KDB 447498 D01V06

**SAR Test Exclusion Thresholds for 100 MHz - 6 GHz and  $\leq 50$  mm**

Approximate SAR Test Exclusion Power Thresholds at Selected Frequencies and Test Separation Distances are illustrated in the following Table.

| MHz  | 5  | 10 | 15  | 20  | 25  | mm                                      |
|------|----|----|-----|-----|-----|-----------------------------------------|
| 150  | 39 | 77 | 116 | 155 | 194 | SAR Test<br>Exclusion<br>Threshold (mW) |
| 300  | 27 | 55 | 82  | 110 | 137 |                                         |
| 450  | 22 | 45 | 67  | 89  | 112 |                                         |
| 835  | 16 | 33 | 49  | 66  | 82  |                                         |
| 900  | 16 | 32 | 47  | 63  | 79  |                                         |
| 1500 | 12 | 24 | 37  | 49  | 61  |                                         |
| 1900 | 11 | 22 | 33  | 44  | 54  |                                         |
| 2450 | 10 | 19 | 29  | 38  | 48  |                                         |
| 3600 | 8  | 16 | 24  | 32  | 40  |                                         |
| 5200 | 7  | 13 | 20  | 26  | 33  |                                         |
| 5400 | 6  | 13 | 19  | 26  | 32  |                                         |
| 5800 | 6  | 12 | 19  | 25  | 31  |                                         |

Note: 10-g Extremity SAR Test Exclusion Power Thresholds are 2.5 times higher than the 1-g SAR Test Exclusion Thresholds indicated above. These thresholds do not apply, by extrapolation or other means, to occupational exposure limits.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$$\left[ \frac{\text{max. power of channel, including tune-up tolerance, mW}}{\text{min. test separation distance, mm}} \right] \cdot \left[ \sqrt{f(\text{GHz})} \right] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where } f(\text{GHz}) \text{ is the RF channel transmit frequency in GHz}$$

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

**BT**

|                       |                           |
|-----------------------|---------------------------|
| Mode                  | Frequency:2402 – 2480 MHz |
| Detector              | PEAK                      |
| GFSK(1Mbps)           | 3±1dBm                    |
| $\pi/4$ -DQPSK(2Mbps) | 2±1dBm                    |
| 8DPSK(3Mbps)          | 3±1dBm                    |

| Mode                  | frequency (GHz) | Maximum Peak Conducted Output Power (dBm) | Tune up Power (dBm) | Tune up Power (mW) | Result | Limit |
|-----------------------|-----------------|-------------------------------------------|---------------------|--------------------|--------|-------|
| GFSK(1Mbps)           | 2.441           | 3.5                                       | 4                   | 2.512              | 0.785  | 3     |
| $\pi/4$ -DQPSK(2Mbps) | 2.441           | 2.7                                       | 3                   | 1.995              | 0.623  | 3     |
| 8DPSK(3Mbps)          | 2.402           | 2.85                                      | 4                   | 2.512              | 0.779  | 3     |

**BLE**

|           |              |
|-----------|--------------|
| Mode      | 2402-2480MHz |
| Detector  | PEAK         |
| BLE 1Mbps | 4±1dBm       |
| BLE 2Mbps | 4±1dBm       |

| Mode      | frequency (GHz) | Maximum Peak Conducted Output Power (dBm) | Tune up Power (dBm) | Tune up Power (mW) | Result | Limit |
|-----------|-----------------|-------------------------------------------|---------------------|--------------------|--------|-------|
| BLE 1Mbps | 2.402           | 4.42                                      | 5                   | 3.162              | 0.980  | 3     |
| BLE 2Mbps | 2.402           | 4.42                                      | 5                   | 3.162              | 0.980  | 3     |

Remark:

Threshold at which no SAR required is  $\text{Max.} 0.98 \leq 3.0$  for 1-g SAR, Separation distance is 5mm.