TEST REPORT

Report No.:	8432EU012723W1
Applicant:	QUEST USA CORP
Address:	495 Flatbush Ave, Brooklyn, NY 11225, USA
Product Name:	KLAZZO MULTI FUNCTIONAL CAR CHARGER
Model No.:	IJ10821-DT
Trademark:	IJOY
FCC ID:	2AJQ7KLAZZOMULTI
Test Standard(s):	47 CFR Part 15.247
Test Result:	Pass
Date of Receipt:	Jun. 29, 2026
Test Date:	Jun. 29, 2026 - Jul. 28, 2026
Date of Issue:	Sep. 22, 2026

ISSUED BY:

SHENZHEN EU TESTING LABORATORY LIMITED

SHENZHEN EU TESTING LABORATORY LIMITED APPROVED

Prepared by: **Reviewed and Approved by:**

Peach Zheng/ Engineer

Sally Zhang/ Manager

Revision Record

Report Version	Issued Date	Description	Status
V0	Sep. 22, 2026	Original	Valid

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

Table of Contents

1 COVER PAGE 1
2 GENERAL INFORMATION 5
2.1 APPLICANT INFORMATION 5
2.2 MANUFACTURER INFORMATION 5
2.3 FACTORY INFORMATION 5
2.4 GENERAL DESCRIPTION OF E.U.T. 5
2.5 TECHNICAL INFORMATION OF E.U.T. 6
3 TEST SUMMARY 7
3.1 TEST STANDARD 7
3.2 TEST VERDICT 7
3.3 TEST LABORATORY 8
4 TEST CONFIGURATION 9
4.1 TEST ENVIRONMENT 9
4.2 TEST EQUIPMENT 9
4.3 DESCRIPTION OF SUPPORT UNIT 11
4.4 TEST MODE 11
4.5 DESCRIPTION OF CALCULATION 11
4.5.1 Field Strength Calculation 11
4.5.2 Disturbance Calculation 11
4.6 MEASUREMENT UNCERTAINTY 12
4.7 DEVIATION FROM STANDARDS 12
4.8 ABNORMALITIES FROM STANDARD CONDITION 12
5 EVALUATION RESULTS (EVALUATION) 13
5.1 ANTENNA REQUIREMENT 13
5.1.1 Test Specification 13
5.1.2 Test Data 13
6 RADIO SPECTRUM MATTER TEST RESULTS (RF) 14
6.1 20DB BANDWIDTH 14
6.1.1 Test Specification 14
6.1.2 E.U.T. Operation 15
6.1.3 Test Setup Diagram 15
6.1.4 Test Data 15
6.2 MAXIMUM CONDUCTED OUTPUT POWER 16
6.2.1 Test Specification 16
6.2.2 E.U.T. Operation 16
6.2.3 Test Setup Diagram 16
6.2.4 Test Data 16
6.3 CHANNEL SEPARATION 17
6.3.1 Test Specification 17
6.3.2 E.U.T. Operation 17
6.3.3 Test Setup Diagram 17
6.3.4 Test Data 18
6.4 NUMBER OF HOPPING FREQUENCIES 19
6.4.1 Test Specification 19
6.4.2 E.U.T. Operation 19
6.4.3 Test Setup Diagram 20

6.4.4 Test Data 20
6.5 DWELL TIME 21
6.5.1 Test Specification 21
6.5.2 E.U.T. Operation 22
6.5.3 Test Setup Diagram 22
6.5.4 Test Data 22
6.6 EMISSIONS IN NON-RESTRICTED FREQUENCY BANDS 23
6.6.1 Test Specification 23
6.6.2 E.U.T. Operation 23
6.6.3 Test Setup Diagram 23
6.6.4 Test Data 23
6.7 BAND EDGE EMISSIONS (RADIATED) 24
6.7.1 Test Specification 24
6.7.2 E.U.T. Operation 24
6.7.3 Test Setup Diagram 24
6.7.4 Test Data 25
6.8 EMISSIONS IN FREQUENCY BANDS (BELOW 1GHZ) 29
6.8.1 Test Specification 29
6.8.2 E.U.T. Operation 29
6.8.3 Test Setup Diagram 29
6.8.4 Test Data 30
6.9 EMISSIONS IN FREQUENCY BANDS (ABOVE 1GHZ) 33
6.9.1 Test Specification 33
6.9.2 E.U.T. Operation 33
6.9.3 Test Setup Diagram 34
6.9.4 Test Data 34
ANNEX A TEST SETUP PHOTOS 38
ANNEX B EXTERNAL PHOTOS 38
ANNEX C INTERNAL PHOTOS 38
ANNEX D TEST DATA 39

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

2 General Information

2.1 Applicant Information

Applicant	QUEST USA CORP
Address	495 Flatbush Ave, Brooklyn, NY 11225, USA

2.2 Manufacturer Information

Manufacturer	NINGBO COMAX IMP.&EXP. CO.,LTD.
Address	No.933, Tiantong North Road, A608, Hebang Tower,Yinzhou District, Ningbo, China

2.3 Factory Information

Factory	NINGBO COMAX IMP.&EXP. CO.,LTD.
Address	No.933, Tiantong North Road, A608, Hebang Tower,Yinzhou District, Ningbo, China

2.4 General Description of E.U.T.

Product Name	KLAZZO MULTI FUNCTIONAL CAR CHARGER
Model No. Under Test	IJ10821-DT
List Model No.	N/A
Description of Model differentiation	N/A
Rating(s)	Input: 12-24VDC USB Output 1: 5VDC, 2.4A USB Output 2: 5VDC, 1A
Product Type	☐ Mobile ☒ Portable ☐ Fix Location
Test Sample No.	8432EU012723W-1/2(Normal),8432EU012723W-2/2(Engineering)
Hardware Version	N/A
Software Version	N/A
Remark	For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.5 Technical Information of E.U.T.

Network and Wireless Connectivity	Bluetooth (BDR+EDR) FM Transmission

The requirement for the following technical information of the EUT was tested in this report:

Operating Frequency	2402MHz to 2480MHz
Modulation Type	GFSK, π/4 DQPSK, 8DPSK
Number of Channels	79
Antenna Type	PCB Antenna
Antenna Gain(Peak)	-0.58 dBi
Remark	The above information are declared by the applicant, EU-LAB is not responsible for the information accuracy provided by the applicant.

All channels were listed on the following table:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461	-	-

3 Test Summary

3.1 Test Standard

The tests were performed according to following standards:

47 CFR Part 15.247: Operation within the bands 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz

Remark:

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product maybe which result in lowering the emission/immunity should be checked to ensure compliance has been maintained.

3.2 Test Verdict

Test Items	Standard	Method	Requirement	Results
Antenna requirement	47 CFR Part 15.247	---	47 CFR 15.203	Pass
20dB Bandwidth	47 CFR Part 15.247	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024, section 7.8.6 KDB 558074 D01 15.247 Meas Guidance v05r02	47 CFR 15.247(a)(1)	Pass
Maximum Conducted Output Power	47 CFR Part 15.247	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024, section 7.8.5 KDB 558074 D01 15.247 Meas Guidance v05r02	47 CFR 15.247(b)(1)	Pass
Channel Separation	47 CFR Part 15.247	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024, section 7.8.2 KDB 558074 D01 15.247 Meas Guidance v05r02	47 CFR 15.247(a)(1)	Pass
Number of Hopping Frequencies	47 CFR Part 15.247	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024, section 7.8.3 KDB 558074 D01 15.247 Meas Guidance v05r02	47 CFR 15.247(a)(1)(iii)	Pass
Dwell Time	47 CFR Part 15.247	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024,	47 CFR 15.247(a)(1)(iii)	Pass

		section 7.8.4 KDB 558074 D01 15.247 Meas Guidance v05r02		
Emissions in non-restricted frequency bands	47 CFR Part 15.247	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 section 7.8.7 KDB 558074 D01 15.247 Meas Guidance v05r02	47 CFR 15.247(d)	Pass
Band edge emissions (Radiated)	47 CFR Part 15.247	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 section 6.10 KDB 558074 D01 15.247 Meas Guidance v05r02	47 CFR 15.247(d), 15.209, 15.205	Pass
Emissions in frequency bands (below 1GHz)	47 CFR Part 15.247	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 section 6.5.4 KDB 558074 D01 15.247 Meas Guidance v05r02	47 CFR 15.247(d), 15.209, 15.205	Pass
Emissions in frequency bands (above 1GHz)	47 CFR Part 15.247	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 section 6.5.4 KDB 558074 D01 15.247 Meas Guidance v05r02	47 CFR 15.247(d), 15.209, 15.205	Pass
Note: (1) “N/A” denotes test is not applicable in this Test Report.				

3.3 Test Laboratory

Test Laboratory	Shenzhen EU Testing Laboratory Limited
Address	101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Designation Number	CN1368
Test Firm Registration Number	952583

4 Test Configuration

4.1 Test Environment

During the measurement, the normal environmental conditions were within the listed ranges:

Relative Humidity	30% to 60%	
Atmospheric Pressure	86 kPa to 106 kPa	
Temperature	NT (Normal Temperature)	+15℃ to +35℃
Working Voltage of the EUT	NV (Normal Voltage)	12VDC

4.2 Test Equipment

20dB Bandwidth
Maximum Conducted Output Power
Channel Separation
Number of Hopping Frequencies
Dwell Time
Emissions in non-restricted frequency bands

Equipment	Manufacturer	Model No	Serial No	Cal Date	Cal Due Date
MXA Signal Analyzer	Agilent	N9020A	EE-011	2026-04-07	2027-04-06
MXG RF Vector Signal Generator	Agilent	N5182A	EE-012	2026-04-07	2027-04-06
MIMO Power Measurement Module	TSTPASS	TSPS 2023R	EE-016	2026-04-11	2027-04-10
MXG RF Analog Signal Generator	Agilent	N5181A	EE-406	2026-02-13	2027-02-12
Power Meter	Anritsu	ML2495A	EE-416	2026-02-13	2027-02-12
Constant Temperature Humidity Chamber	Guangxin	GXP-401	ES-002	2026-07-14	2027-07-13
RF Test Software	TSTPASS	TS32893 V2.0	EE-017	/	/
Band-Stop Filter	COM-MW	ZBSF8-L2400-2483.5-1016	EE-025	2026-04-07	2027-04-06
Band-Stop Filter	COM-MW	K6-5150-5850-250S5020-001	EE-026	2026-04-07	2027-04-06
Filter	COM-MW	ZHPF6-M3000-18000-174	EE-027	2026-04-07	2027-04-06
Filter	COM-MW	ZHPF6-M1300-18000-5356	EE-028	2026-04-07	2027-04-06
Wideband Radio Communication Tester	ROHDE & SCHWARZ	CMW500	EE-030	2026-04-07	2027-04-06

Band edge emissions (Radiated) Emissions in frequency bands (above 1GHz)					
Equipment	**Manufacturer**	**Model No**	**Serial No**	**Cal Date**	**Cal Due Date**
EMI Test Receiver	ROHDE & SCHWARZ	ESPI	EE-006	2026-04-08	2027-04-07
Double Ridged Horn Antenna	A-INFOMW	LB-10180-NF	EE-008	2026-04-12	2027-04-11
Pre-amplifier	Agilent	8449B	EE-010	2026-04-07	2027-04-06
MXG RF Vector Signal Generator	Agilent	N5182A	EE-012	2026-04-07	2027-04-06
Test Software	Farad	EZ-EMC	EE-015	/	/
Band-Stop Filter	COM-MW	ZBSF8-L2400-2483.5-1016	EE-025	2026-04-07	2027-04-06
Band-Stop Filter	COM-MW	K6-5150-5850-250S5020-001	EE-026	2026-04-07	2027-04-06
Filter	COM-MW	ZHPF6-M3000-18000-174	EE-027	2026-04-07	2027-04-06
Filter	COM-MW	ZHPF6-M1300-18000-5356	EE-028	2026-04-07	2027-04-06
Spectrum Analyzer	ROHDE & SCHWARZ	FSV40-N	EE-029	2026-04-07	2027-04-06
40G Horn Antenna	HCT	HA-018040L	EE-031	2026-04-12	2027-04-11
40G Pre-amplifier	HCT	HC180400-50G25	EE-032	2026-04-07	2027-04-06

Emissions in frequency bands (below 1GHz)					
Equipment	**Manufacturer**	**Model No**	**Serial No**	**Cal Date**	**Cal Due Date**
EMI Test Receiver	ROHDE & SCHWARZ	ESPI	EE-006	2026-04-08	2027-04-07
Bilog Broadband Antenna	SCHWARZBECK	VULB 9163	EE-007	2026-04-12	2027-04-11
Pre-amplifier	Agilent	8447D	EE-009	2026-04-08	2027-04-07
MXA Signal Analyzer	Agilent	N9020A	EE-011	2026-04-07	2027-04-06
Test Software	Farad	EZ-EMC	EE-015	/	/
Loop Antenna	SCHWARZBECK	FMZB 1519-60	EE-022	2026-04-12	2027-04-11
Band-Stop Filter	COM-MW	ZBSF6-C902-928-2389	EE-023	2026-04-07	2027-04-06
Band-Stop Filter	COM-MW	ZBSF6-C855-880-5938	EE-024	2026-04-07	2027-04-06

4.3 Description of Support Unit

No.	Title	Manufacturer	Model No.	Serial No.
1	12V Battery	CHILWEE	6-DZF-12.2	EMC-PJ-031
2	Pink Notebook	ADOL	ADOL13F	EMC-PJ-030

4.4 Test Mode

No.	**Test Modes**	**Description**
TM1	TX-GFSK (Non-Hopping)	Keep the EUT in continuously transmitting mode (non-hopping) with GFSK modulation at lowest, middle and highest channel.
TM2	TX-π/4DQPSK (Non-Hopping)	Keep the EUT in continuously transmitting mode (non-hopping) with π/4DQPSK modulation at lowest, middle and highest channel.
TM3	TX-8DPSK (Non-Hopping)	Keep the EUT in continuously transmitting mode (non-hopping) with 8DPSK modulation at lowest, middle and highest channel.
TM4	TX-GFSK (Hopping)	Keep the EUT in continuously transmitting mode (hopping) with GFSK modulation.
TM5	TX-π/4DQPSK (Hopping)	Keep the EUT in continuously transmitting mode (hopping) with π/4DQPSK modulation.
TM6	TX-8DPSK (Hopping)	Keep the EUT in continuously transmitting mode (hopping) with 8DPSK modulation.

4.5 Description of Calculation

4.5.1 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

FS (dBuV/m) = RA (dBuV) + AF (dB/m) + CL (dB) – AG (dB)

Where FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	AG = Amplifier Gain
AF = Antenna Factor	

4.5.2 Disturbance Calculation

The AC mains conducted disturbance is calculated by adding the 10dB Pulse Limiter and Cable Factor and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

CD (dBuV) = RA (dBuV) + PL (dB) + CL (dB)

Where CD = Conducted Disturbance	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	PL = 10 dB Pulse Limiter Factor

4.6 Measurement Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2.

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Test Item	Measurement Uncertainty
Occupied Channel Bandwidth	69 kHz
RF output power, conducted	1.07 dB
Time of Occupancy (Dwell Time)	1.8 %
Unwanted Emissions, conducted	2.73 dB
Radiated Emission (1GHz- 18GHz)	Ur = 3.58 dB (Horizontal) Ur = 3.58 dB (Vertical)
Radiated Emission (9kHz- 30MHz)	Ur = 3.06 dB
Radiated Emission (30MHz- 1GHz)	Ur = 2.76 dB (Horizontal) Ur = 2.76 dB (Vertical)
Radiated Emission (18GHz-40GHz)	Ur = 5.29 dB (Horizontal) Ur = 5.21 dB (Vertical)

4.7 Deviation from Standards

None

4.8 Abnormalities from Standard Condition

None

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

5 Evaluation Results (Evaluation)

5.1 Antenna requirement

5.1.1 Test Specification

Test Requirement:	Refer to 47 CFR Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.
Test Method:	---

5.1.2 Test Data

PASS.

The Antenna Anti-Replacement as following method:

Protected Method	Description
The antenna is embedded in the product.	An embedded-in antenna-design is used.

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

6 Radio Spectrum Matter Test Results (RF)

6.1 20dB Bandwidth

6.1.1 Test Specification

Test Requirement:	47 CFR 15.247(a)(1)
Test Limit:	Refer to 47 CFR 15.215(c), intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.
Test Method:	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024, section 7.8.6, For occupied bandwidth measurements, use the procedure in 6.9.2. Frequency hopping shall be disabled for this test. KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	A dBc bandwidth is measured as the width of the spectral envelope of the modulated signal, at an amplitude level reduced from a reference value by a specified ratio (or in decibels, a specified number of dB down from the reference value). Typical ratios, expressed in dB, are −6 dB, −20 dB, and −26 dB, corresponding to 6 dB BW, 20 dB BW, and 26 dB BW, respectively. In this subclause, the ratio is designated by "−xx dB." The reference value is either the level of the unmodulated carrier or the highest level of the spectral envelope of the modulated signal, as stated by the applicable requirement. Some requirements might specify a specific maximum or minimum value for the "−xx dB" bandwidth; other requirements might specify that the "−xx dB" bandwidth be entirely contained within the authorized or designated frequency band.51 a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the EMI receiver or spectrum analyzer shall be between two times and five times the OBW. b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be at least three times RBW, unless otherwise specified by the applicable requirement. c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than [10 log (OBW/RBW)] below the reference level. Specific guidance is given in 4.1.6.2. d) Steps a) through c) might require iteration to adjust within the specified tolerances. e) The dynamic range of the instrument at the selected RBW shall be more than 10 dB below the target "−xx dB down" requirement; that is, if the requirement calls for measuring the −20 dB OBW, the instrument noise floor at the selected RBW shall be at least 30 dB below the reference value. f) Set detection mode to peak and trace mode to max-hold. g) Determine the reference value: Set the EUT to transmit an unmodulated carrier or modulated signal, as applicable. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace (this is the reference value). h) Determine the "−xx dB down amplitude" using [(reference value) - xx]. Alternatively, this calculation may be made by using the marker-delta function of the instrument. i) If the reference value is determined by an unmodulated carrier, then turn the EUT modulation ON, and either clear the existing trace or start a new trace on the spectrum analyzer and allow the new trace to stabilize. Otherwise, the trace from step g) shall be used for step j). j) Place two markers, one at the lowest frequency and the other at the highest

	frequency of the envelope of the spectral display, such that each marker is at or slightly below the “−xx dB down amplitude” determined in step h). If a marker is below this “−xx dB down amplitude” value, then it shall be as close as possible to this value. The dBc bandwidth is the frequency difference between the two markers. Alternatively, set a marker at the lowest frequency of the envelope of the spectral display, such that the marker is at or slightly below the “−xx dB down amplitude” determined in step h). Reset the marker-delta function and move the marker to the other side of the emission until the delta marker amplitude is at the same level as the reference marker amplitude. The marker-delta frequency reading at this point is the specified emission bandwidth. k) The dBc bandwidth shall be reported by providing spectral plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

6.1.2 E.U.T. Operation

Pre test mode:	TM1, TM2, TM3
Final test mode:	TM1, TM2, TM3

6.1.3 Test Setup Diagram



6.1.4 Test Data

PASS.

Please refer to Annex D for details.

6.2 Maximum Conducted Output Power

6.2.1 Test Specification

Test Requirement:	47 CFR 15.247(b)(1)
Test Limit:	Refer to 47 CFR 15.247(b)(1), For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.
Test Method:	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024, section 7.8.5 KDB 558074 D01 15.247 Meas Guidance v05r02

6.2.2 E.U.T. Operation

Pre test mode:	TM1, TM2, TM3
Final test mode:	TM1, TM2, TM3

6.2.3 Test Setup Diagram



6.2.4 Test Data

PASS.

Please refer to Annex D for details.

6.3 Channel Separation

6.3.1 Test Specification

Test Requirement:	47 CFR 15.247(a)(1)
Test Limit:	Refer to 47 CFR 15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.
Test Method:	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024, section 7.8.2 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings: a) Span: Wide enough to capture the peaks of two adjacent channels. b) RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel. c) Video (or average) bandwidth (VBW) ≥ RBW. d) Sweep: No faster than coupled (auto) time. e) Detector function: Peak. f) Trace: Max-hold. g) Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. Compliance of an EUT with the appropriate regulatory limit shall be determined. A spectral plot of the data shall be included in the test report.

6.3.2 E.U.T. Operation

Pre test mode:	TM4, TM5, TM6
Final test mode:	TM4, TM5, TM6

6.3.3 Test Setup Diagram



6.3.4 Test Data

PASS.

Please refer to Annex D for details.

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

6.4 Number of Hopping Frequencies

6.4.1 Test Specification

Test Requirement:	47 CFR 15.247(a)(1)(iii)
Test Limit:	Refer to 47 CFR 15.247(a)(1)(iii), Fequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.
Test Method:	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024, section 7.8.3 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings: a) Span: The frequency band of operation. Depending on the number of channels the device supports, it could be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen. b) RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller. c) VBW ≥ RBW. d) Sweep: No faster than coupled (auto) time. e) Detector function: Peak. f) Trace: Max-hold. g) Allow the trace to stabilize. It might prove necessary to break the span up into subranges to show clearly all of the hopping frequencies. Compliance of an EUT with the appropriate regulatory limit shall be determined for the number of hopping channels. A spectral plot of the data shall be included in the test report.

6.4.2 E.U.T. Operation

Pre test mode:	TM4, TM5, TM6
Final test mode:	TM4, TM5, TM6

6.4.3 Test Setup Diagram



6.4.4 Test Data

PASS.

Please refer to Annex D for details.

6.5 Dwell Time

6.5.1 Test Specification

Test Requirement:	47 CFR 15.247(a)(1)(iii)
Test Limit:	Refer to 47 CFR 15.247(a)(1)(iii), Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.
Test Method:	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024, section 7.8.4 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	The dwell time per hop on a channel is the time from the start of the first transmission to the end of the last transmission for that hop. If the device has a single transmission per hop then the dwell time is the duration of that transmission. If the device has a multiple transmissions per hop then the dwell time is measured from the start of the first transmission to the end of the last transmission. The time of occupancy is the total time that the device dwells on a channel over an observation period specified in the regulatory requirement. To determine the time of occupancy the spectrum analyzer will be configured to measure both the dwell time per hop and the number of times the device transmits on a specific channel in a given period. The EUT shall have its hopping function enabled. Compliance with the requirements shall be made with the minimum and with the maximum number of channels enabled. If the dwell time per channel does not vary with the number of channels than compliance with the requirements may be based on the minimum number of channels. If the device supports different dwell times per channel (example Bluetooth devices can dwell on a channel for 1, 3 or 5 time slots) then measurements can be limited to the longest dwell time with the minimum number of channels. Use the following spectrum analyzer settings to determine the dwell time per hop: a) Span: Zero span, centered on a hopping channel. b) RBW shall be ≤ channel spacing and where possible RBW should be set >> 1 / T, where T is the expected transmission time per hop. c) Sweep time: Set so that the start of the first transmission and end of the last transmission for the hop are clearly captured. Setting the sweep time to be slightly longer than the hopping period per channel (hopping period = 1/hopping rate) should achieve this. d) Use a video trigger, where possible with a trigger delay, so that the start of the transmission is clearly observed. The trigger level might need adjustment to reduce the chance of triggering when the system hops on an adjacent channel. e) Detector function: Peak. f) Trace: Clear-write, single sweep. g) Place markers at the start of the first transmission on the channel and at the end of the last transmission. The dwell time per hop is the time between these two markers. To determine the number of hops on a channel in the regulatory observation period repeat the measurement using a longer sweep time. When the device uses a single hopping sequence the period of measurement should be sufficient to capture at least 2 hops. When the device uses a dynamic hopping sequence, or

	the sequence varies, the period of measurement may need to capture multiple hops to better determine the average time of occupancy. Count the number of hops on the channel across the sweep time. The average number of hops on the same channel within the regulatory observation period is calculated from the number of hops on the channel divided by the spectrum analyzer sweep time multiplied by the regulatory observation period. For example, if three hops are counted with an analyzer sweep time of 500 ms and the regulatory observation period is 10 s, then the number of hops in that ten seconds is 3 / 0.5 × 10, or 60 hops. The average time of occupancy is calculated by multiplying the dwell time per hop by the number of hops in the observation period.

6.5.2 E.U.T. Operation

Pre test mode:	TM4, TM5, TM6
Final test mode:	TM4, TM5, TM6

6.5.3 Test Setup Diagram



6.5.4 Test Data

PASS.

Please refer to Annex D for details.

6.6 Emissions in non-restricted frequency bands

6.6.1 Test Specification

Test Requirement:	47 CFR 15.247(d)
Test Limit:	Refer to 47 CFR 15.247(d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required.
Test Method:	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 section 7.8.7 KDB 558074 D01 15.247 Meas Guidance v05r02

6.6.2 E.U.T. Operation

Pre test mode:	TM1, TM2, TM3, TM4, TM5, TM6
Final test mode:	TM1, TM2, TM3, TM4, TM5, TM6

6.6.3 Test Setup Diagram



6.6.4 Test Data

PASS.

Please refer to Annex D for details.

6.7 Band edge emissions (Radiated)

6.7.1 Test Specification

Test Requirement:	Refer to 47 CFR 15.247(d), In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).
Test Limit:	

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100 **	3
88-216	150 **	3
216-960	200 **	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.
In the emission table above, the tighter limit applies at the band edges.
The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

Test Method:	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 section 6.10 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 section 6.10.5.2

6.7.2 E.U.T. Operation

Pre test mode:	TM1, TM2, TM3
Final test mode:	TM1, TM2, TM3

6.7.3 Test Setup Diagram



6.7.4 Test Data

PASS.

Please refer to the following pages.

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

Band Edge Emissions (Restricted frequency bands):

Test Mode: GFSK					CH Low: 2402 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	2310.00	42.60	-2.81	39.79	74.00	-34.21	PK	PASS
H	2390.00	45.07	-2.69	42.38	74.00	-31.62	PK	PASS
H	**2400.00	62.02	-2.68	59.34	74.00	-14.66	PK	PASS
V	2310.00	44.47	-2.81	41.66	74.00	-32.34	PK	PASS
V	2390.00	45.91	-2.69	43.22	74.00	-30.78	PK	PASS
V	**2400.00	61.65	-2.68	58.97	74.00	-15.03	PK	PASS
H	2310.00	32.48	-2.81	29.67	54.00	-24.33	AV	PASS
H	2390.00	37.59	-2.69	34.90	54.00	-19.10	AV	PASS
H	**2400.00	45.39	-2.68	42.71	54.00	-11.29	AV	PASS
V	2310.00	34.33	-2.81	31.52	54.00	-22.48	AV	PASS
V	2390.00	36.42	-2.69	33.73	54.00	-20.27	AV	PASS
V	**2400.00	46.28	-2.68	43.60	54.00	-10.40	AV	PASS

Test Mode: GFSK					CH High: 2480 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	**2483.50	48.68	-2.56	46.12	74.00	-27.88	PK	PASS
H	2500.00	50.62	-2.54	48.08	74.00	-25.92	PK	PASS
V	**2483.50	48.24	-2.56	45.68	74.00	-28.32	PK	PASS
V	2500.00	48.51	-2.54	45.97	74.00	-28.03	PK	PASS
H	**2483.50	37.27	-2.56	34.71	54.00	-19.29	AV	PASS
H	2500.00	39.46	-2.54	36.92	54.00	-17.08	AV	PASS
V	**2483.50	39.00	-2.56	36.44	54.00	-17.56	AV	PASS
V	2500.00	41.15	-2.54	38.61	54.00	-15.39	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Band Edge Emissions (Restricted frequency bands):

Test Mode: π/4DQPSK					CH Low: 2402 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	2310.00	44.49	-2.81	41.68	74.00	-32.32	PK	PASS
H	2390.00	46.65	-2.69	43.96	74.00	-30.04	PK	PASS
H	**2400.00	60.74	-2.68	58.06	74.00	-15.94	PK	PASS
V	2310.00	44.18	-2.81	41.37	74.00	-32.63	PK	PASS
V	2390.00	47.15	-2.69	44.46	74.00	-29.54	PK	PASS
V	**2400.00	62.04	-2.68	59.36	74.00	-14.64	PK	PASS
H	2310.00	33.53	-2.81	30.72	54.00	-23.28	AV	PASS
H	2390.00	35.56	-2.69	32.87	54.00	-21.13	AV	PASS
H	**2400.00	48.15	-2.68	45.47	54.00	-8.53	AV	PASS
V	2310.00	34.50	-2.81	31.69	54.00	-22.31	AV	PASS
V	2390.00	36.27	-2.69	33.58	54.00	-20.42	AV	PASS
V	**2400.00	45.83	-2.68	43.15	54.00	-10.85	AV	PASS

Test Mode: π/4DQPSK					CH High: 2480 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	**2483.50	48.85	-2.56	46.29	74.00	-27.71	PK	PASS
H	2500.00	50.80	-2.54	48.26	74.00	-25.74	PK	PASS
V	**2483.50	48.27	-2.56	45.71	74.00	-28.29	PK	PASS
V	2500.00	50.81	-2.54	48.27	74.00	-25.73	PK	PASS
H	**2483.50	36.61	-2.56	34.05	54.00	-19.95	AV	PASS
H	2500.00	40.86	-2.54	38.32	54.00	-15.68	AV	PASS
V	**2483.50	38.23	-2.56	35.67	54.00	-18.33	AV	PASS
V	2500.00	40.26	-2.54	37.72	54.00	-16.28	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

Band Edge Emissions (Restricted frequency bands):

Test Mode: 8DPSK					CH Low: 2402 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	2310.00	43.99	-2.81	41.18	74.00	-32.82	PK	PASS
H	2390.00	47.51	-2.69	44.82	74.00	-29.18	PK	PASS
H	**2400.00	62.56	-2.68	59.88	74.00	-14.12	PK	PASS
V	2310.00	42.67	-2.81	39.86	74.00	-34.14	PK	PASS
V	2390.00	46.69	-2.69	44.00	74.00	-30.00	PK	PASS
V	**2400.00	63.86	-2.68	61.18	74.00	-12.82	PK	PASS
H	2310.00	31.05	-2.81	28.24	54.00	-25.76	AV	PASS
H	2390.00	36.06	-2.69	33.37	54.00	-20.63	AV	PASS
H	**2400.00	46.49	-2.68	43.81	54.00	-10.19	AV	PASS
V	2310.00	34.62	-2.81	31.81	54.00	-22.19	AV	PASS
V	2390.00	36.07	-2.69	33.38	54.00	-20.62	AV	PASS
V	**2400.00	49.12	-2.68	46.44	54.00	-7.56	AV	PASS

Test Mode: 8DPSK					CH High: 2480 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
H	**2483.50	47.86	-2.56	45.30	74.00	-28.70	PK	PASS
H	2500.00	49.60	-2.54	47.06	74.00	-26.94	PK	PASS
V	**2483.50	48.99	-2.56	46.43	74.00	-27.57	PK	PASS
V	2500.00	47.99	-2.54	45.45	74.00	-28.55	PK	PASS
H	**2483.50	37.15	-2.56	34.59	54.00	-19.41	AV	PASS
H	2500.00	39.79	-2.54	37.25	54.00	-16.75	AV	PASS
V	**2483.50	37.71	-2.56	35.15	54.00	-18.85	AV	PASS
V	2500.00	40.52	-2.54	37.98	54.00	-16.02	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

6.8 Emissions in frequency bands (below 1GHz)

6.8.1 Test Specification

Test Requirement:	Refer to 47 CFR 15.247(d), In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).
Test Limit:	

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100 **	3
88-216	150 **	3
216-960	200 **	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.
In the emission table above, the tighter limit applies at the band edges.
The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

Test Method:	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 section 6.5.4 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 section 6.5.4

6.8.2 E.U.T. Operation

Pre test mode:	TM1, TM2, TM3, TM4, TM5, TM6
Final test mode:	TM1

6.8.3 Test Setup Diagram



Figure 1. Below 30MHz



Figure 2. 30MHz to 1GHz

6.8.4 Test Data

PASS.

The test results of 9kHz-30MHz was attenuated more than 20dB below the permissible limits, so the results don't record in the report.

During the test, for 30MHz to 1000MHz, pre-scan all modulations, and found the GFSK modulation Low channel which is the worst case, only the worst case is recorded in the report.

Emissions in frequency bands (below 1GHz) Test Data

TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 1 / CH: L



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1 !	87.4177	55.66	-21.11	34.55	40.00	-5.45	QP	P	
2	262.8955	55.81	-16.46	39.35	46.00	-6.65	QP	P	
3	438.6554	51.04	-11.94	39.10	46.00	-6.90	QP	P	
4 *	614.2142	49.16	-7.94	41.22	46.00	-4.78	QP	P	
5	787.8513	40.48	-5.98	34.50	46.00	-11.50	QP	P	
6	875.2470	32.83	-4.95	27.88	46.00	-18.12	QP	P	

Emissions in frequency bands (below 1GHz) Test Data

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 1 / CH: L



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	87.4177	44.13	-21.11	23.02	40.00	-16.98	QP	P	
2	262.8955	48.30	-16.57	31.73	46.00	-14.27	QP	P	
3	438.6554	49.19	-11.94	37.25	46.00	-8.75	QP	P	
4 *	614.2142	49.94	-7.91	42.03	46.00	-3.97	QP	P	
5	787.8513	37.14	-5.95	31.19	46.00	-14.81	QP	P	
6	875.2470	32.82	-5.16	27.66	46.00	-18.34	QP	P	

6.9 Emissions in frequency bands (above 1GHz)

6.9.1 Test Specification

<table>
<tr><td>Test Requirement:</td><td>Refer to 47 CFR 15.247(d), in addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).</td></tr>
<tr><td>Test Limit:</td><td>
<table>
<tr><td>Frequency (MHz)</td><td>Field strength (microvolts/meter)</td><td>Measurement distance (meters)</td></tr>
<tr><td>0.009-0.490</td><td>2400/F(kHz)</td><td>300</td></tr>
<tr><td>0.490-1.705</td><td>24000/F(kHz)</td><td>30</td></tr>
<tr><td>1.705-30.0</td><td>30</td><td>30</td></tr>
<tr><td>30-88</td><td>100 **</td><td>3</td></tr>
<tr><td>88-216</td><td>150 **</td><td>3</td></tr>
<tr><td>216-960</td><td>200 **</td><td>3</td></tr>
<tr><td>Above 960</td><td>500</td><td>3</td></tr>
</table>
** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.
In the emission table above, the tighter limit applies at the band edges.
The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.
</td></tr>
<tr><td>Test Method:</td><td>ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 section 6.5.4
KDB 558074 D01 15.247 Meas Guidance v05r02</td></tr>
<tr><td>Procedure:</td><td>ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024 section 6.5.4</td></tr>
</table>

6.9.2 E.U.T. Operation

Pre test mode:	TM1, TM2, TM3
Final test mode:	TM1

6.9.3 Test Setup Diagram



6.9.4 Test Data

PASS.

During the test, for 1GHz- 25GHz, pre-scan all modulations, and found the GFSK modulation which is the worst case, only the worst case is recorded in the report.

Radiated Spurious Emission (1GHz-25GHz)

Test Mode: GFSK					CH Low: 2402 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
V	4804.90	41.54	4.68	46.22	74.00	-27.79	PK	PASS
V	7206.95	33.37	9.84	43.21	74.00	-30.80	PK	PASS
V	9608.89	28.12	13.17	41.29	74.00	-32.72	PK	PASS
V	12010.85	*	*	*	74.00	*	PK	PASS
V	14412.33	*	*	*	74.00	*	PK	PASS
V	16814.59	*	*	*	74.00	*	PK	PASS
H	4804.90	41.49	4.68	46.17	74.00	-27.83	PK	PASS
H	7206.34	33.30	9.84	43.14	74.00	-30.87	PK	PASS
H	9608.41	30.11	13.17	43.28	74.00	-30.72	PK	PASS
H	12010.80	*	*	*	74.00	*	PK	PASS
H	14412.87	*	*	*	74.00	*	PK	PASS
H	16814.15	*	*	*	74.00	*	PK	PASS
V	4804.33	30.65	4.68	35.33	54.00	-18.68	AV	PASS
V	7206.59	22.18	9.84	32.02	54.00	-21.99	AV	PASS
V	9608.33	17.72	13.17	30.89	54.00	-23.12	AV	PASS
V	12010.78	*	*	*	54.00	*	AV	PASS
V	14412.80	*	*	*	54.00	*	AV	PASS
V	16814.35	*	*	*	54.00	*	AV	PASS
H	4804.26	30.28	4.68	34.96	54.00	-19.05	AV	PASS
H	7206.34	22.79	9.84	32.63	54.00	-21.37	AV	PASS
H	9608.41	19.97	13.17	33.14	54.00	-20.87	AV	PASS
H	12010.80	*	*	*	54.00	*	AV	PASS
H	14412.87	*	*	*	54.00	*	AV	PASS
H	16814.15	*	*	*	54.00	*	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.
2. “*” means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.

Radiated Spurious Emission (1GHz-25GHz)

Test Mode: GFSK					CH Middle: 2441 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
V	4882.93	42.95	4.92	47.87	74.00	-26.13	PK	PASS
V	7323.72	34.24	9.83	44.07	74.00	-29.93	PK	PASS
V	9764.67	29.56	13.22	42.78	74.00	-31.22	PK	PASS
V	12205.15	*	*	*	74.00	*	PK	PASS
V	14646.80	*	*	*	74.00	*	PK	PASS
V	17087.46	*	*	*	74.00	*	PK	PASS
H	4882.74	42.63	4.92	47.55	74.00	-26.46	PK	PASS
H	7323.79	35.70	9.83	45.53	74.00	-28.47	PK	PASS
H	9764.92	29.95	13.22	43.17	74.00	-30.84	PK	PASS
H	12205.29	*	*	*	74.00	*	PK	PASS
H	14646.48	*	*	*	74.00	*	PK	PASS
H	17087.65	*	*	*	74.00	*	PK	PASS
V	4882.51	32.41	4.92	37.33	54.00	-16.67	AV	PASS
V	7323.77	23.45	9.83	33.28	54.00	-20.72	AV	PASS
V	9764.15	18.85	13.22	32.07	54.00	-21.93	AV	PASS
V	12205.98	*	*	*	54.00	*	AV	PASS
V	14646.84	*	*	*	54.00	*	AV	PASS
V	17087.73	*	*	*	54.00	*	AV	PASS
H	4882.74	32.49	4.92	37.41	54.00	-16.59	AV	PASS
H	7323.79	23.18	9.83	33.01	54.00	-20.99	AV	PASS
H	9764.92	19.09	13.22	32.31	54.00	-21.70	AV	PASS
H	12205.29	*	*	*	54.00	*	AV	PASS
H	14646.48	*	*	*	54.00	*	AV	PASS
H	17087.65	*	*	*	54.00	*	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.

2. “*” means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.

Radiated Spurious Emission (1GHz-25GHz)

Test Mode: GFSK					CH High: 2480 MHz			
Pol.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type	Result
V	4960.30	40.28	5.17	45.45	74.00	-28.56	PK	PASS
V	7440.80	33.14	9.83	42.97	74.00	-31.03	PK	PASS
V	9920.47	29.65	13.27	42.92	74.00	-31.08	PK	PASS
V	12400.76	*	*	*	74.00	*	PK	PASS
V	14880.27	*	*	*	74.00	*	PK	PASS
V	17360.11	*	*	*	74.00	*	PK	PASS
H	4960.19	41.19	5.17	46.36	74.00	-27.64	PK	PASS
H	7440.19	34.06	9.83	43.89	74.00	-30.12	PK	PASS
H	9920.17	29.17	13.27	42.44	74.00	-31.57	PK	PASS
H	12400.84	*	*	*	74.00	*	PK	PASS
H	14880.49	*	*	*	74.00	*	PK	PASS
H	17360.62	*	*	*	74.00	*	PK	PASS
V	4960.93	31.72	5.17	36.89	54.00	-17.11	AV	PASS
V	7440.13	24.74	9.83	34.57	54.00	-19.44	AV	PASS
V	9920.75	17.91	13.27	31.18	54.00	-22.83	AV	PASS
V	12400.29	*	*	*	54.00	*	AV	PASS
V	14880.70	*	*	*	54.00	*	AV	PASS
V	17360.66	*	*	*	54.00	*	AV	PASS
H	4960.19	30.42	5.17	35.59	54.00	-18.41	AV	PASS
H	7440.19	23.54	9.83	33.37	54.00	-20.63	AV	PASS
H	9920.17	17.08	13.27	30.35	54.00	-23.65	AV	PASS
H	12400.84	*	*	*	54.00	*	AV	PASS
H	14880.49	*	*	*	54.00	*	AV	PASS
H	17360.62	*	*	*	54.00	*	AV	PASS

Remark:

1. Emission Level = Reading + Factor, Margin= Emission Level – Limit.
2. “*” means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.

ANNEX A TEST SETUP PHOTOS

Please refer to the document "8432EU012723W-ANNEX A.PDF"

ANNEX B EXTERNAL PHOTOS

Please refer to the document "8432EU012723W-ANNEX B.PDF"

ANNEX C INTERNAL PHOTOS

Please refer to the document "8432EU012723W-ANNEX C.PDF"

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

ANNEX D TEST DATA

1. Duty Cycle

1.1 Test Result

1.1.1 Ant1

Ant1								
Mode	TX Type	Frequency (MHz)	Packet Type	T_on (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	Max. DC Variation (%)
GFSK	SISO	2402	DH5	2.921	3.749	77.91	1.08	0.03
		2441	DH5	2.920	3.750	77.87	1.09	0.04
		2480	DH5	2.921	3.750	77.89	1.08	0.04
π /4DQPSK	SISO	2402	2DH5	2.927	3.751	78.03	1.08	0.03
		2441	2DH5	2.927	3.749	78.07	1.07	10.97
		2480	2DH5	2.927	3.750	78.05	1.08	0.04
8DPSK	SISO	2402	3DH5	2.930	3.750	78.13	1.07	0.03
		2441	3DH5	2.930	3.750	78.13	1.07	10.92
		2480	3DH5	2.931	3.751	78.14	1.07	0.04

1.2 Test Graph

1.2.1 Ant1

GFSK_DH5_LCH_2402MHz_Ant1_NTNV



GFSK_DH5_MCH_2441MHz_Ant1_NTNV



GFSK_DH5_HCH_2480MHz_Ant1_NTNV



π /4DQPSK_2DH5_LCH_2402MHz_Ant1_NTNV



π /4DQPSK_2DH5_MCH_2441MHz_Ant1_NTNV



π /4DQPSK_2DH5_HCH_2480MHz_Ant1_NTNV



8DPSK_3DH5_LCH_2402MHz_Ant1_NTNV



8DPSK_3DH5_MCH_2441MHz_Ant1_NTNV



8DPSK_3DH5_HCH_2480MHz_Ant1_NTNV



2. Bandwidth

2.1 Test Result

2.1.1 OBW

Mode	TX Type	Frequency (MHz)	Packet Type	ANT	99% Occupied Bandwidth (MHz)		Verdict
					Result	Limit	
GFSK	SISO	2402	DH5	1	0.852	/	Pass
		2441	DH5	1	0.855	/	Pass
		2480	DH5	1	0.856	/	Pass
π /4DQPSK	SISO	2402	2DH5	1	1.180	/	Pass
		2441	2DH5	1	1.185	/	Pass
		2480	2DH5	1	1.185	/	Pass
8DPSK	SISO	2402	3DH5	1	1.181	/	Pass
		2441	3DH5	1	1.186	/	Pass
		2480	3DH5	1	1.189	/	Pass

2.1.2 20dB BW

Mode	TX Type	Frequency (MHz)	Packet Type	ANT	20dB Bandwidth (MHz)		Verdict
					Result	Limit	
GFSK	SISO	2402	DH5	1	0.918	/	Pass
		2441	DH5	1	0.921	/	Pass
		2480	DH5	1	0.921	/	Pass
π /4DQPSK	SISO	2402	2DH5	1	1.322	/	Pass
		2441	2DH5	1	1.324	/	Pass
		2480	2DH5	1	1.322	/	Pass
8DPSK	SISO	2402	3DH5	1	1.307	/	Pass
		2441	3DH5	1	1.308	/	Pass
		2480	3DH5	1	1.316	/	Pass

2.2 Test Graph

2.2.1 OBW

GFSK_DH5_LCH_2402MHz_Ant1_NTNV



GFSK_DH5_MCH_2441MHz_Ant1_NTNV



GFSK_DH5_HCH_2480MHz_Ant1_NTNV



π /4DQPSK_2DH5_LCH_2402MHz_Ant1_NTNV



π /4DQPSK_2DH5_MCH_2441MHz_Ant1_NTNV



π /4DQPSK_2DH5_HCH_2480MHz_Ant1_NTNV



8DPSK_3DH5_LCH_2402MHz_Ant1_NTNV



8DPSK_3DH5_MCH_2441MHz_Ant1_NTNV



8DPSK_3DH5_HCH_2480MHz_Ant1_NTNV



2.2.2 20dB BW

GFSK_DH5_LCH_2402MHz_Ant1_NTNV



GFSK_DH5_MCH_2441MHz_Ant1_NTNV



GFSK_DH5_HCH_2480MHz_Ant1_NTNV



π /4DQPSK_2DH5_LCH_2402MHz_Ant1_NTNV



π /4DQPSK_2DH5_MCH_2441MHz_Ant1_NTNV



π /4DQPSK_2DH5_HCH_2480MHz_Ant1_NTNV



8DPSK_3DH5_LCH_2402MHz_Ant1_NTNV



8DPSK_3DH5_MCH_2441MHz_Ant1_NTNV



8DPSK_3DH5_HCH_2480MHz_Ant1_NTNV



3. Maximum Conducted Output Power

3.1 Test Result

3.1.1 Power

Mode	TX Type	Frequency (MHz)	Packet Type	Maximum Peak Conducted Output Power (dBm)		Verdict
				ANT1	Limit	
GFSK	SISO	2402	DH5	1.11	<=30	Pass
		2441	DH5	1.85	<=30	Pass
		2480	DH5	2.05	<=30	Pass
π /4DQPSK	SISO	2402	2DH5	3.39	<=20.97	Pass
		2441	2DH5	4.10	<=20.97	Pass
		2480	2DH5	4.32	<=20.97	Pass
8DPSK	SISO	2402	3DH5	3.78	<=20.97	Pass
		2441	3DH5	4.48	<=20.97	Pass
		2480	3DH5	4.67	<=20.97	Pass

3.2 Test Graph

3.2.1 Power

GFSK_DH5_LCH_2402MHz_Ant1_NTNV



GFSK_DH5_MCH_2441MHz_Ant1_NTNV



GFSK_DH5_HCH_2480MHz_Ant1_NTNV



π /4DQPSK_2DH5_LCH_2402MHz_Ant1_NTNV



π /4DQPSK_2DH5_MCH_2441MHz_Ant1_NTNV



π /4DQPSK_2DH5_HCH_2480MHz_Ant1_NTNV



8DPSK_3DH5_LCH_2402MHz_Ant1_NTNV



8DPSK_3DH5_MCH_2441MHz_Ant1_NTNV



8DPSK_3DH5_HCH_2480MHz_Ant1_NTNV



4. Carrier Frequency Separation

4.1 Test Result

4.1.1 Ant1

Ant1							
Mode	TX Type	Frequency (MHz)	Packet Type	Channel Separation (MHz)	20dB Bandwidth (MHz)	Limit (MHz)	Verdict
GFSK	SISO	HOPP	DH5	1.000	0.921	>=0.921	Pass
π /4DQPSK	SISO	HOPP	2DH5	1.032	1.324	>=0.883	Pass
8DPSK	SISO	HOPP	3DH5	0.979	1.316	>=0.877	Pass

4.2 Test Graph

4.2.1 Ant1

GFSK_DH5_HOPP_Ant1_NTNV



π /4DQPSK_2DH5_HOPP_Ant1_NTNV



8DPSK_3DH5_HOPP_Ant1_NTNV



5. Number of Hopping Frequencies

5.1 Test Result

5.1.1 HoppNum

Mode	TX Type	Frequency (MHz)	Packet Type	Num of Hopping Frequencies		Verdict
				ANT1	Limit	
GFSK	SISO	HOPP	DH5	79	>=15	Pass
π /4DQPSK	SISO	HOPP	2DH5	79	>=15	Pass
8DPSK	SISO	HOPP	3DH5	79	>=15	Pass

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

5.2 Test Graph

5.2.1 HoppNum

GFSK_DH5_HOPP_Ant1_NTNV



π /4DQPSK_2DH5_HOPP_Ant1_NTNV



8DPSK_3DH5_HOPP_Ant1_NTNV



6. Time of Occupancy (Dwell Time)

6.1 Test Result

6.1.1 Ant1

Ant1									
Mode	TX Type	Frequency (MHz)	Packet Type	Duration of Single Pulse (ms)	Observation Period (s)	Num of Pulse in Observation Period	Dwell Time (ms)	Limit (ms)	Verdict
GFSK	SISO	HOPP	DH1	0.422	31.600	320	135.040	<=400	Pass
			DH3	1.680	31.600	159	267.120	<=400	Pass
			DH5	2.924	31.600	110	321.640	<=400	Pass
π /4DQPSK	SISO	HOPP	2DH1	0.424	31.600	320	135.680	<=400	Pass
			2DH3	1.680	31.600	164	275.520	<=400	Pass
			2DH5	2.930	31.600	107	313.510	<=400	Pass
8DPSK	SISO	HOPP	3DH1	0.436	31.600	320	139.520	<=400	Pass
			3DH3	1.686	31.600	161	271.446	<=400	Pass
			3DH5	2.938	31.600	111	326.118	<=400	Pass

6.2 Test Graph

6.2.1 Ant1

GFSK_DH1_HOPP_Ant1_NTNV



GFSK_DH1_HOPP_Ant1_NTNV



GFSK_DH3_HOPP_Ant1_NTNV



GFSK_DH3_HOPP_Ant1_NTNV



GFSK_DH5_HOPP_Ant1_NTNV



GFSK_DH5_HOPP_Ant1_NTNV



π /4DQPSK_2DH1_HOPP_Ant1_NTNV



π /4DQPSK_2DH1_HOPP_Ant1_NTNV



π /4DQPSK_2DH3_HOPP_Ant1_NTNV



π /4DQPSK_2DH3_HOPP_Ant1_NTNV



π /4DQPSK_2DH5_HOPP_Ant1_NTNV



π /4DQPSK_2DH5_HOPP_Ant1_NTNV



8DPSK_3DH1_HOPP_Ant1_NTNV



8DPSK_3DH1_HOPP_Ant1_NTNV



8DPSK_3DH3_HOPP_Ant1_NTNV



8DPSK_3DH3_HOPP_Ant1_NTNV



8DPSK_3DH5_HOPP_Ant1_NTNV



8DPSK_3DH5_HOPP_Ant1_NTNV



7. Unwanted Emissions In Non-restricted Frequency Bands

7.1 Test Result

7.1.1 Ref

Mode	TX Type	Frequency (MHz)	Packet Type	ANT	Level of Reference (dBm)
GFSK	SISO	2402	DH5	1	0.64
		2441	DH5	1	1.37
		2480	DH5	1	1.57
		HOPP	DH5	1	1.64
					1.64
π /4DQPSK	SISO	2402	2DH5	1	0.69
		2441	2DH5	1	1.41
		2480	2DH5	1	1.62
		HOPP	2DH5	1	1.81
					1.81
8DPSK	SISO	2402	3DH5	1	0.94
		2441	3DH5	1	1.69
		2480	3DH5	1	1.87
		HOPP	3DH5	1	1.92
					1.92

7.1.2 CSE

Mode	TX Type	Frequency (MHz)	Packet Type	ANT	Level of Reference (dBm)	Limit (dBm)	Verdict
GFSK	SISO	2402	DH5	1	0.64	-19.36	Pass
		2441	DH5	1	1.37	-18.63	Pass
		2480	DH5	1	1.57	-18.43	Pass
		HOPP	DH5	1	1.64	-18.36	Pass
					1.64	-18.36	Pass
π /4DQPSK	SISO	2402	2DH5	1	0.69	-19.31	Pass
		2441	2DH5	1	1.41	-18.59	Pass
		2480	2DH5	1	1.62	-18.38	Pass
		HOPP	2DH5	1	1.81	-18.19	Pass
					1.81	-18.19	Pass
8DPSK	SISO	2402	3DH5	1	0.94	-19.06	Pass
		2441	3DH5	1	1.69	-18.31	Pass
		2480	3DH5	1	1.87	-18.13	Pass
		HOPP	3DH5	1	1.92	-18.08	Pass
					1.92	-18.08	Pass

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com

7.2 Test Graph

7.2.1 Ref

GFSK_DH5_LCH_2402MHz_Ant1_NTNV



GFSK_DH5_MCH_2441MHz_Ant1_NTNV



GFSK_DH5_HCH_2480MHz_Ant1_NTNV



GFSK_DH5_HOPP_Ant1_NTNV



GFSK_DH5_HOPP_Ant1_NTNV



π /4DQPSK_2DH5_LCH_2402MHz_Ant1_NTNV



π /4DQPSK_2DH5_MCH_2441MHz_Ant1_NTNV



π /4DQPSK_2DH5_HCH_2480MHz_Ant1_NTNV



π /4DQPSK_2DH5_HOPP_Ant1_NTNV



π /4DQPSK_2DH5_HOPP_Ant1_NTNV



8DPSK_3DH5_LCH_2402MHz_Ant1_NTNV



8DPSK_3DH5_MCH_2441MHz_Ant1_NTNV



8DPSK_3DH5_HCH_2480MHz_Ant1_NTNV



8DPSK_3DH5_HOPP_Ant1_NTNV



8DPSK_3DH5_HOPP_Ant1_NTNV



7.2.2 CSE

GFSK_DH5_LCH_2402MHz_Ant1_NTNV



GFSK_DH5_LCH_2402MHz_Ant1_NTNV



GFSK_DH5_LCH_2402MHz_Ant1_NTNV



GFSK_DH5_LCH_2402MHz_Ant1_NTNV



GFSK_DH5_LCH_2402MHz_Ant1_NTNV



GFSK_DH5_MCH_2441MHz_Ant1_NTNV



GFSK_DH5_MCH_2441MHz_Ant1_NTNV



GFSK_DH5_MCH_2441MHz_Ant1_NTNV



GFSK_DH5_MCH_2441MHz_Ant1_NTNV



GFSK_DH5_HCH_2480MHz_Ant1_NTNV



GFSK_DH5_HCH_2480MHz_Ant1_NTNV



GFSK_DH5_HCH_2480MHz_Ant1_NTNV



GFSK_DH5_HCH_2480MHz_Ant1_NTNV



GFSK_DH5_HCH_2480MHz_Ant1_NTNV



GFSK_DH5_HOPP_Ant1_NTNV



GFSK_DH5_HOPP_Ant1_NTNV



π /4DQPSK_2DH5_LCH_2402MHz_Ant1_NTNV



π /4DQPSK_2DH5_LCH_2402MHz_Ant1_NTNV



π /4DQPSK_2DH5_LCH_2402MHz_Ant1_NTNV



π /4DQPSK_2DH5_LCH_2402MHz_Ant1_NTNV



π /4DQPSK_2DH5_LCH_2402MHz_Ant1_NTNV



π /4DQPSK_2DH5_MCH_2441MHz_Ant1_NTNV



π /4DQPSK_2DH5_MCH_2441MHz_Ant1_NTNV



π /4DQPSK_2DH5_MCH_2441MHz_Ant1_NTNV



π /4DQPSK_2DH5_MCH_2441MHz_Ant1_NTNV



π /4DQPSK_2DH5_HCH_2480MHz_Ant1_NTNV



π /4DQPSK_2DH5_HCH_2480MHz_Ant1_NTNV



π /4DQPSK_2DH5_HCH_2480MHz_Ant1_NTNV



π /4DQPSK_2DH5_HCH_2480MHz_Ant1_NTNV



π /4DQPSK_2DH5_HCH_2480MHz_Ant1_NTNV



π /4DQPSK_2DH5_HOPP_Ant1_NTNV



π /4DQPSK_2DH5_HOPP_Ant1_NTNV



8DPSK_3DH5_LCH_2402MHz_Ant1_NTNV



8DPSK_3DH5_LCH_2402MHz_Ant1_NTNV



8DPSK_3DH5_LCH_2402MHz_Ant1_NTNV



8DPSK_3DH5_LCH_2402MHz_Ant1_NTNV



8DPSK_3DH5_LCH_2402MHz_Ant1_NTNV



8DPSK_3DH5_MCH_2441MHz_Ant1_NTNV



8DPSK_3DH5_MCH_2441MHz_Ant1_NTNV



8DPSK_3DH5_MCH_2441MHz_Ant1_NTNV



8DPSK_3DH5_MCH_2441MHz_Ant1_NTNV



8DPSK_3DH5_HCH_2480MHz_Ant1_NTNV



8DPSK_3DH5_HCH_2480MHz_Ant1_NTNV



8DPSK_3DH5_HCH_2480MHz_Ant1_NTNV



8DPSK_3DH5_HCH_2480MHz_Ant1_NTNV



8DPSK_3DH5_HCH_2480MHz_Ant1_NTNV



8DPSK_3DH5_HOPP_Ant1_NTNV



8DPSK_3DH5_HOPP_Ant1_NTNV



STATEMENT

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the “inspection and testing dedicated stamp” or test report stamp.
5. The test data and results are only valid for the tested samples provided by the customer.
6. This report shall not be partially reproduced without the written permission of the laboratory.
7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--- End of Report ---

Address: 101, Building B1, Fuqiao Fourth Area, Qiaotou Community, Fuhai Subdistrict, Baoan District, Shenzhen, Guangdong, China
Website: www.eu-test.com
Tel: (86)-755-2357-9714 Email: Service@eu-test.com