Antenna Specification

Specifications

Summary

ITEM	SPEC.	
Antenna Type	Type_2_single wiggle Antenna	
Center Frequency	2402 MHz 2441 MHz 2480 MHz	2.34 dBi 2.07dBi 1.45 dBi
MAX. GAIN	2.34 dBi	
Polarization	Horizontal	
Azimuth Beam Pattern	Omni-directional	
Impedance	50 Ω	
Antenna Length	3.1cm	

Antenna Photo & Length (mm)





Test Address	**16 Tzu Chiang Road, Hsinchu Industrial District Hsinchu Hsien 303, Taiwan**
Test Date	**2009-04-14**
Test Instrument	**vector network analyzer - R&S ZVB20**

Manufacturer: Yizhao Microelectronics (Hangzhou) Co., LTD
Room 501, 5th Floor, Area A, Building 1, No. 57, Jiang 'er Road, Changhe Sub-district, Binjiang District, Hangzhou City, Zhejiang Province

1. Main antenna : 2402 MHz

1.1 Horizontal



Frequency(MHZ): **2402** Antenna Polarity: **Horizontal**

Maximum Value(dBi): **2. 34**

Average Gain(dBi) : **-2.48**

Minimum Gain(dBi): **-55.18**

1.2 Vertical



Frequency(MHZ): **2402** Antenna Polarity: **Vertical**

Maximum Value(dBi): **-4.51**

Average Gain(dBi) : **-8.98**

Minimum Gain(dBi): **-62.3**

2. Main antenna : 2441 MHz

2.1 Horizontal



Frequency(MHZ): **2441** Antenna Polarity: **Horizontal**

Maximum Value(dBi): 2.07

Average Gain(dBi) : **-2.54**

Minimum Gain(dBi): **-66.98**

2.2 Vertical



Frequency(MHZ): **2441** Antenna Polarity: **Vertical**

Maximum Value(dBi): **-4.29**

Average Gain(dBi) : **-8.81**

Minimum Gain(dBi): **-51.4**

2. Main antenna : 2480 MHz

2.1 Horizontal



Frequency(MHZ): **2480** Antenna Polarity: **Horizontal**

Maximum Value(dBi): **1.45**

Average Gain(dBi) : **-3.34**

Minimum Gain(dBi): **-53.4**

2.2 Vertical



Frequency(MHZ): **2480** Antenna Polarity: **Vertical**

Maximum Value(dBi): **-4.95**

Average Gain(dBi) : **-9.06**

Minimum Gain(dBi): **-60.00**