




# PCTEST ENGINEERING LABORATORY, INC.

6660-B Dobbin Road, Columbia, MD 21045 USA  
Tel. 410.290.6652 / Fax 410.290.6554  
<http://www.pctestlab.com>



## RF EXPOSURE EVALUATION Maximum Permissible Exposure (MPE)

**Applicant Name:**

Wivity Inc.  
665 3<sup>rd</sup> Street STE 150  
San Francisco, CA 94107  
United States

**Date of Testing:**

9/21-10/18/2016

**Test Site/Location:**

PCTEST Lab, Columbia, MD, USA

**Test Report Serial No.:**

0Y1609201565.2AJRF

**FCC ID:** 2AJRFGFR2001

**APPLICANT:** Wivity Inc.

**EUT Type:** 900MHz Tx Modem

**FCC Rule Part(s):** FCC Part 1 (§1.1310) and Part 2 (§2.1091)

**FCC Classification:** FCC Part 15 Frequency Hopping Spread Spectrum Transceiver (DSS)

**Test Procedure:** KDB 447498 D01 v06

The device bearing the FCC Identifier specified above has been shown to comply with the applicable technical standards as indicated in the measurement report and has been tested in accordance with the measurement procedures specified in FCC KDB 447498. These measurements were performed with no deviation from the standards. Test results reported herein relate only to the item(s) tested.

I authorize and attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

  
Randy Ortanez  
President



|                                               |                                       |                                                                                                                                           |  |                                                                                       |                                        |
|-----------------------------------------------|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|--|---------------------------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> 2AJRFGFR2001                   |                                       |  <b>MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT</b> |  |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Test Report S/N:</b><br>0Y1609201565.2AJRF | <b>Test Dates:</b><br>9/21-10/18/2016 | <b>EUT Type:</b><br>900MHz Tx Modem                                                                                                       |  |                                                                                       | Page 1 of 7                            |

## TABLE OF CONTENTS

---

|     |                                                                   |   |
|-----|-------------------------------------------------------------------|---|
| 1.0 | RF EXPOSURE EVALUATION – MAXIMUM PERMISSIBLE EXPOSURE (MPE) ..... | 3 |
| 1.1 | Introduction .....                                                | 3 |
| 1.2 | EUT Description.....                                              | 3 |
| 1.3 | MPE Requirements Overview.....                                    | 4 |
| 1.4 | Procedure .....                                                   | 5 |
| 1.5 | Summary of Results .....                                          | 6 |
| 2.0 | CONCLUSION.....                                                   | 7 |

|                                               |                                                                                     |                                                       |                                                                                       |                                        |
|-----------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> 2AJRFGFR2001                   |  | <b>MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT</b> |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Test Report S/N:</b><br>0Y1609201565.2AJRF | <b>Test Dates:</b><br>9/21-10/18/2016                                               | <b>EUT Type:</b><br>900MHz Tx Modem                   |                                                                                       | Page 2 of 7                            |

## 1.0 RF EXPOSURE EVALUATION – MAXIMUM PERMISSIBLE EXPOSURE (MPE)

### 1.1 Introduction

This document is prepared on behalf of Wivity Inc. to show compliance with the RF Exposure requirements as required in §1.1310 of the FCC Rules and Regulations and RSS-102 of Industry Canada.

The limit for Maximum Permissible Exposure (MPE), specified in FCC §1.1310, is listed in Table 1-1. According to FCC §1.1310 and RSS-102: the criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in §1.1307(b).

| Frequency Range (MHz)                                                     | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) | Power Density (mW/cm <sup>2</sup> ) | Average Time (Minutes) |
|---------------------------------------------------------------------------|-------------------------------|-------------------------------|-------------------------------------|------------------------|
| (A) Limits For Occupational / Control Exposures (f = frequency)           |                               |                               |                                     |                        |
| 30-300                                                                    | 61.4                          | 0.163                         | 1.0                                 | 6                      |
| 300-1500                                                                  | ...                           | ...                           | f/300                               | 6                      |
| 1500-100,000                                                              | ...                           | ...                           | 5.0                                 | 6                      |
| (B) Limits For General Population / Uncontrolled Exposure (f = frequency) |                               |                               |                                     |                        |
| 30-300                                                                    | 27.5                          | 0.073                         | 0.2                                 | 30                     |
| 300-1500                                                                  | ...                           | ...                           | f/1500                              | 30                     |
| 1500-100,000                                                              | ...                           | ...                           | 1.0                                 | 30                     |

Table 1-1. Limits for Maximum Permissible Exposure (MPE)

### 1.2 EUT Description

The EUT (FCC ID: 2AJRFSGFR2001) consists of a development board used to control the 900MHz transmitter. For this MPE evaluation, the power density is determined based on the conducted output power of the EUT along with the gain of the internal and external antennas.

#### EUT:

**Model:** SGF-R2-001  
**Grantee:** Wivity Inc.  
**FCC ID:** 2AJRFSGFR2001  
**Antenna(s):** External Antenna Gain: 1.2 dBi  
 Internal Antenna Gain: -1.0 dBi

|                                        |                                                                                     |                                                |                                                                                       |                                 |
|----------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: 2AJRFSGFR2001                  |  | MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1609201565.2AJRF | Test Dates:<br>9/21-10/18/2016                                                      | EUT Type:<br>900MHz Tx Modem                   |                                                                                       | Page 3 of 7                     |

### 1.3 MPE Requirements Overview

Three different categories of transmitters are defined by the FCC in KDB 447498 D01 v06. These categories are fixed installation, mobile, and portable and are defined as follows:

- **Fixed Installations:** fixed location means that the device, including its antenna, is physically secured at a permanent location and is not able to be easily moved to another location. Additionally, distance to humans from the antenna is maintained to at least 2 meters.
- **Mobile Devices:** a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to be generally used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structures and the body of the user or nearby persons. Transmitters designed to be used by consumers or workers that can be easily re-located, such as a wireless modem operating in a laptop computer, are considered mobile devices if they meet the 20 centimeter separation requirement. The FCC rules for evaluating mobile devices for RF compliance are found in 47 CFR §2.1091.
- **Portable Devices:** a portable device is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user. Portable device requirements are found in Section 2.1093 of the FCC's Rules (47 CFR§2.1093).

The FCC also categorizes the use of the device as based upon the user's awareness and ability to exercise control over his or her exposure. The two categories defined are Occupational/ Controlled Exposure and General Population/Uncontrolled Exposure. These two categories are defined as follows:

- **Occupational/Controlled Exposure:** In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means. Awareness of the potential for RF exposure in a workplace or similar environment can be provided through specific training as part of a RF safety program. If appropriate, warning signs and labels can also be used to establish such awareness by providing prominent information on the risk of potential exposure and instructions on methods to minimize such exposure risks.
- **General Population/Uncontrolled Exposure:** The general population / uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity. Warning labels placed on low-power consumer devices such as cellular telephones are not considered sufficient to allow the device to be considered under the occupational/controlled category, and the general population/uncontrolled exposure limits apply to these devices.

The Wivity Inc. 900MHz Tx Modem FCC ID: 2AJRFGFR2001 is evaluated to the Mobile Device requirements and is considered a device to be used by the General Population/Uncontrolled Exposure.

|                                        |                                                                                     |                                                |                                                                                       |                                 |
|----------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------|
| FCC ID: 2AJRFGFR2001                   |  | MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT |  | Reviewed by:<br>Quality Manager |
| Test Report S/N:<br>0Y1609201565.2AJRF | Test Dates:<br>9/21-10/18/2016                                                      | EUT Type:<br>900MHz Tx Modem                   |                                                                                       | Page 4 of 7                     |

## 1.4 Procedure

The procedure used to determine the RF power density was based upon a calculation for determining compliance with the MPE requirements.

The power generated by the 900MHz transmitter was measured by a spectrum analyzer and the power was recorded. Through use of the Friis transmission formula and knowledge of the maximum antenna gain to be used, the power density level is calculated at a distance of 20cm.

The antenna gains of each antenna to be used with the EUT were used to calculate the MPE in the 900MHz band.

### Friis Transmission Formula

Friis transmission formula:  $P_d = (P_{out} * G) / (4\pi r^2)$

Where,

$P_d$  = Power Density (mW/cm<sup>2</sup>)

$\pi$  = 3.1416

$P_{out}$  = output power to antenna (mW)

$r$  = distance between observation point and center of the radiator (cm)

$G$  = gain of antenna in linear scale

### Calculated MPE

The power density limit for General Population/Uncontrolled Exposure at each frequency is determined based on the information in Table 1-1.

|                               |                          |           |  |
|-------------------------------|--------------------------|-----------|--|
| <b>Frequency</b>              | 903.3875 MHz             |           |  |
| <b>Limit</b>                  | 0.602 mW/cm <sup>2</sup> |           |  |
| <b>Distance (cm), R =</b>     | 20 cm                    |           |  |
| <b>Power (dBm), P =</b>       | 22.72 dBm                | 187.07 mW |  |
| <b>TX Ant Gain (dBi), G =</b> | 1.2 dBi                  |           |  |
| <b>Power Density (S) =</b>    | 0.049 mW/cm <sup>2</sup> | (at 20cm) |  |
| <b>Minimum Distance =</b>     | 5.7 cm                   |           |  |

Table 1-2. Calculated MPE Data for 900MHz Band (External Antenna)

|                               |                          |           |  |
|-------------------------------|--------------------------|-----------|--|
| <b>Frequency:</b>             | 903.3875 MHz             |           |  |
| <b>Limit:</b>                 | 0.602 mW/cm <sup>2</sup> |           |  |
| <b>Distance (cm), R =</b>     | 20 cm                    |           |  |
| <b>Power (dBm), P =</b>       | 22.72 dBm                | 187.07 mW |  |
| <b>TX Ant Gain (dBi), G =</b> | -1 dBi                   |           |  |
| <b>Power Density (S) =</b>    | 0.030 mW/cm <sup>2</sup> | (at 20cm) |  |
| <b>Minimum Distance =</b>     | 4.4 cm                   |           |  |

Table 1-3. Calculated MPE Data for 900MHz Band (Internal Antenna)

|                                               |                                                                                     |                                                       |                                                                                       |                                        |
|-----------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> 2AJRFSGFR2001                  |  | <b>MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT</b> |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Test Report S/N:</b><br>0Y1609201565.2AJRF | <b>Test Dates:</b><br>9/21-10/18/2016                                               | <b>EUT Type:</b><br>900MHz Tx Modem                   |                                                                                       | Page 5 of 7                            |

## 1.5 Summary of Results

| Frequency Band [MHz] | Antenna Type | Maximum Antenna Gain [dBi] | MPE @ 20cm (mW/cm <sup>2</sup> ) | Test Result |
|----------------------|--------------|----------------------------|----------------------------------|-------------|
| 902.1375 — 904.6625  | External     | 1.2                        | 0.049                            | PASS        |
| 902.1375 — 904.6625  | Internal     | -1.0                       | 0.030                            | PASS        |

**Table 1-4. Maximum Permissible Exposure Summary Table**

|                                               |                                                                                     |                                                       |                                                                                       |                                        |
|-----------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> 2AJRFGFR2001                   |  | <b>MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT</b> |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Test Report S/N:</b><br>0Y1609201565.2AJRF | <b>Test Dates:</b><br>9/21-10/18/2016                                               | <b>EUT Type:</b><br>900MHz Tx Modem                   |                                                                                       | Page 6 of 7                            |

## 2.0 CONCLUSION

The device meets the mobile RF exposure limit at a 20cm separation distance as specified in §2.1091 of the FCC Rules and Regulations and Health Canada Safety Code 6. An appropriate RF exposure compliance statement will be placed in the user's manual.

|                                               |                                                                                                                                   |                                                       |                                                                                       |                                        |
|-----------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------|---------------------------------------------------------------------------------------|----------------------------------------|
| <b>FCC ID:</b> 2AJRFGFR2001                   |  <b>PCTEST</b><br>ENGINEERING LABORATORY, INC. | <b>MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT</b> |  | <b>Reviewed by:</b><br>Quality Manager |
| <b>Test Report S/N:</b><br>0Y1609201565.2AJRF | <b>Test Dates:</b><br>9/21-10/18/2016                                                                                             | <b>EUT Type:</b><br>900MHz Tx Modem                   |                                                                                       | Page 7 of 7                            |