



RF EXPOSURE MEASUREMENT AND TEST REPORT

For

Foshan Amplitec Tech Development Co.,Ltd

4th Floor, 4th Building, NO.60 of Langbao West Road,
Chancheng District, Foshan City, Guangdong Province, China.

FCC ID: 2AJULC15F-5B

Report Type: Original Report	Product Type: Repeater
Test Engineer: Tom Tang	<i>Tom Tang</i>
Report Number: RSC161201003B	
Report Date: 2017-08-02	
Reviewed By: Henry Ding	<i>Henry Ding</i>
Test Laboratory:	EMC Leader
Bay Area Compliance Laboratories Corp. (Chengdu) No.5040, Huilongwan Plaza, No. 1, Shawan Road, Jinniu District, Chengdu, Sichuan, China Tel: 028-65525123 Fax: 028-65525125 www.baclcorp.com.cn	

Note: This test report was prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Chengdu) Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. This report was valid only with a valid digital signature.

FCC §1.1307(b) & §2.1091 - MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Averaging Time (minutes)
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	/	/	f/1500	30
1500–100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculated Formulary:

Predication of MPE limit at a given distance

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

Calculated Data:

Mode	Frequency Band	Antenna Gain		Cable Loss	Max Tune-up Conducted Power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
		(dBi)	(numeric)		(dBm)	(mW)			
Uplink	824-849	7.0	5.01	2.44	24.0	251.19	20.00	0.143	0.55
	1850-1910	7.0	5.01	2.95	24.0	251.19	20.00	0.127	1.00
	1710-1755	7.0	5.01	2.78	24.0	251.19	20.00	0.132	1.00
	704-716	7.0	5.01	2.13	24.0	251.19	20.00	0.153	0.47
	776-787	7.0	5.01	2.25	24.0	251.19	20.00	0.149	0.52
Downlink	869-894	9.0	7.94	2.63	5.0	3.16	20.00	0.003	0.58
	1930-1990	9.0	7.94	3.13	5.0	3.16	20.00	0.002	1.00
	2110-2155	9.0	7.94	3.25	5.0	3.16	20.00	0.002	1.00
	734-746	9.0	7.94	2.21	5.0	3.16	20.00	0.003	0.49
	746-757	9.0	7.94	2.32	5.0	3.16	20.00	0.003	0.50

Note: The power was used for evaluation is rated power including tolerance.

The worst antenna kitting is option 1 for outdoor antenna and option 1 for indoor antenna.
Please refer the user manual.

Result: The device meet FCC MPE at 20 cm distance.