

# FCC RADIO TEST REPORT

Applicant..... : Foto Electric Supply Co., INC.  
Address..... : 1 Rewe St. Brooklyn, New York 11211 United States  
Manufacturer..... : Foto Electric Supply Co., INC.  
Address..... : 1 Rewe St. Brooklyn, New York 11211 United States  
Factory..... : Foto Electric Supply Co., INC.  
Address..... : 1 Rewe St. Brooklyn, New York 11211 United States  
Product Name..... : Waterproof Activity Tracking Fitness Band  
Brand Name..... : Chargeworx, Coby  
Model No. .... : KH138NVPK, SB138BKPK, SB138BK, SB138PK, SB138CR, SB138OR,  
SB138BL, SB138BKOR (For model differences refer to section 2)  
FCC ID..... : 2AJVKKH138  
Measurement Standard..... : 47 CFR FCC Part 15, Subpart C (Section 15.247)  
Receipt Date of Samples..... : June 09, 2026  
Date of Tested..... : June 10, 2026 to June 13, 2026  
Date of Report..... : July 29, 2026

This report shows that above equipment is technically compliant with the requirements of the standards above. All test results in this report apply only to the tested sample(s). Without prior written approval of Dongguan Nore Testing Center Co., Ltd, this report shall not be reproduced except in full.



Prepared by

Alina Guo / Project Engineer



Approved by

Iori Fan / Authorized Signatory

## Table of Contents

|                                                                        |    |
|------------------------------------------------------------------------|----|
| 1. Summary of Test Result.....                                         | 4  |
| 2. General Description of EUT .....                                    | 5  |
| 3. Test Channels and Modes Detail .....                                | 8  |
| 4. Configuration of EUT .....                                          | 8  |
| 5. Modification of EUT .....                                           | 8  |
| 6. Description of Support Device.....                                  | 9  |
| 7. Test Facility and Location .....                                    | 10 |
| 8. Applicable Standards and References.....                            | 11 |
| 9. Deviations and Abnormalities from Standard Conditions .....         | 11 |
| 10. Test Conditions .....                                              | 12 |
| 11. Measurement Uncertainty .....                                      | 13 |
| 12. Sample Calculations .....                                          | 14 |
| 13. Test Items and Results .....                                       | 15 |
| 13.1 Conducted Emissions Measurement .....                             | 15 |
| 13.2 Maximum Conducted Output Power Measurement.....                   | 19 |
| 13.3 6dB Bandwidth Measurement.....                                    | 21 |
| 13.4 Power Spectral Density Measurement .....                          | 25 |
| 13.5 Band Edge and Conducted Spurious Emissions Measurement.....       | 29 |
| 13.6 Radiated Spurious Emissions and Restricted Bands Measurement..... | 34 |
| 13.7 Antenna Requirement .....                                         | 60 |
| 14. Test Equipment List.....                                           | 61 |

## Revision History

[illegible]

## 1. Summary of Test Result

| FCC Rules                    | Description of Test                              | Result | Remarks |
|------------------------------|--------------------------------------------------|--------|---------|
| §15.207 (a)                  | AC Power Conducted Emission                      | PASS   | ---     |
| §15.247(b)(3)                | Maximum Conducted Output Power                   | PASS   | ---     |
| §15.247(a)(2)                | 6dB Bandwidth                                    | PASS   | ---     |
| §15.247(e)                   | Power Spectral Density                           | PASS   | ---     |
| §15.247(d)                   | Band Edge and Conducted Spurious Emissions       | PASS   | ---     |
| §15.247(d), §15.209, §15.205 | Radiated Spurious Emissions and Restricted Bands | PASS   | ---     |
| §15.203                      | Antenna Requirement                              | PASS   | ---     |

## 2. General Description of EUT

| Product Information     |                                                                                                                                                                         |
|-------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product Name:           | Waterproof Activity Tracking Fitness Band                                                                                                                               |
| Main Model Name:        | KH138NVPK                                                                                                                                                               |
| Additional Model Name:  | SB138BKPK, SB138BK, SB138PK, SB138CR, SB138OR, SB138BL, SB138BKOR                                                                                                       |
| Model Difference:       | These models have the same circuit schematic, construction, PCB Layout and PCB components. Their difference is model name, brand name and color due to trading purpose. |
| S/N:                    | 2606-3119                                                                                                                                                               |
| Brand Name:             | Chargeworx, Coby                                                                                                                                                        |
| Hardware Version:       | ZC03_V2.0_20250620                                                                                                                                                      |
| Software Version:       | KH138 V0.0.2(33304)                                                                                                                                                     |
| Rating:                 | DC 5V from adapter<br>DC 3.8V from internal battery                                                                                                                     |
| Typical Arrangement:    | Table-top                                                                                                                                                               |
| I/O Port:               | Refer to the user manual                                                                                                                                                |
| Accessories Information |                                                                                                                                                                         |
| Adapter:                | N/A                                                                                                                                                                     |
| Cable:                  | USB cable: 0.64m unshielded, detachable                                                                                                                                 |
| Other:                  | N/A                                                                                                                                                                     |
| Additional Information  |                                                                                                                                                                         |
| Note:                   | According to the model differences and manufacturer's requirement, all tests were performed on model KH138NVPK.                                                         |
| Remark:                 | All the information above are provided by the manufacturer. More detailed feature of the EUT please refers to the user manual.                                          |

| Technical Specification (BLE)               |                                                  |
|---------------------------------------------|--------------------------------------------------|
| Bluetooth Version:                          | V5.4                                             |
| Frequency Range:                            | 2402-2480MHz                                     |
| Modulation Type:                            | GFSK                                             |
| Number of Channel:                          | 40 (refer to following channel list for details) |
| Channel Space:                              | 2MHz                                             |
| Antenna Type:                               | FPC Antenna                                      |
| Number of Antenna                           | 1                                                |
| Antenna Gain:                               | -3.11 dBi (Declared by the manufacturer)         |
| RF PHY Support:                             | 1Mbps, 2Mbps                                     |
| Note: The EUT supports BLE technology only. |                                                  |


| Channel List |                 |         |                 |         |                 |
|--------------|-----------------|---------|-----------------|---------|-----------------|
| Channel      | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
| 0            | 2402            | 14      | 2430            | 28      | 2458            |
| 1            | 2404            | 15      | 2432            | 29      | 2460            |
| 2            | 2406            | 16      | 2434            | 30      | 2462            |
| 3            | 2408            | 17      | 2436            | 31      | 2464            |
| 4            | 2410            | 18      | 2438            | 32      | 2466            |
| 5            | 2412            | 19      | 2440            | 33      | 2468            |
| 6            | 2414            | 20      | 2442            | 34      | 2470            |
| 7            | 2416            | 21      | 2444            | 35      | 2472            |
| 8            | 2418            | 22      | 2446            | 36      | 2474            |
| 9            | 2420            | 23      | 2448            | 37      | 2476            |
| 10           | 2422            | 24      | 2450            | 38      | 2478            |
| 11           | 2424            | 25      | 2452            | 39      | 2480            |
| 12           | 2426            | 26      | 2454            | -       | -               |
| 13           | 2428            | 27      | 2456            | -       | -               |

### 3. Test Channels and Modes Detail

| Mode |         | Channel |     | Frequency (MHz) | Modulation | RF PHY (Mbps) |
|------|---------|---------|-----|-----------------|------------|---------------|
| 1    | TX      | Low     | 0   | 2402            | GFSK       | 1, 2          |
| 2    |         | Mid     | 19  | 2440            | GFSK       | 1, 2          |
| 3    |         | High    | 39  | 2480            | GFSK       | 1, 2          |
| 4    | BT Link | ---     | --- | ---             | ---        | ---           |

Note: TX mode means that the EUT was programmed to be in continuously transmitting mode.

### 4. Configuration of EUT



### 5. Modification of EUT

No modifications are made to the EUT during all test items.

## 6. Description of Support Device

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| No. | Equipment            | Brand  | M/N              | S/N                 | Specification                                                                                                                      | Remarks               |
|-----|----------------------|--------|------------------|---------------------|------------------------------------------------------------------------------------------------------------------------------------|-----------------------|
| 1.  | Laptop               | Lenovo | TP00067A         | PF-0DS3Y<br>C 15/12 | I/P: AC 100-240V<br>50-60Hz, 1.8A<br>O/P: DC 20V 3.25A<br>AC Line: 1.10m<br>unshielded<br>DC Line: 1.15m<br>unshielded with a core | Provide by the<br>Lab |
| 2.  | Adapter of<br>laptop | Delta  | ADLX65NL<br>C3A  | N/A                 |                                                                                                                                    | Provide by the<br>Lab |
| 3.  | Adapter              | HUAWEI | HW-100225<br>C00 | HC78EAM<br>9408538  |                                                                                                                                    | Provide by the<br>Lab |

| No. | Test Software | Modulation | Power Setting |
|-----|---------------|------------|---------------|
| 1.  | RF Test       | GFSK       | -5dBm         |

## 7. Test Facility and Location

|                                   |   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|-----------------------------------|---|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Site                         | : | Dongguan Nore Testing Center Co., Ltd. (Dongguan NTC Co., Ltd.)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Accreditations and Authorizations | : | <p>The Laboratory has been assessed and proved to be in compliance with CNAS/CL01</p> <p>Listed by CNAS, August 13, 2018</p> <p>The Certificate Registration Number is L5795.</p> <p>The Certificate is valid until August 13, 2030</p><br><p>The Laboratory has been assessed and proved to be in compliance with ISO17025</p> <p>Listed by A2LA, November 01, 2017</p> <p>The Certificate Registration Number is 4429.01</p> <p>The Certificate is valid until December 31, 2027</p><br><p>Listed by FCC, November 06, 2017</p> <p>Test Firm Registration Number: 907417</p><br><p>Listed by Industry Canada, June 08, 2017</p> <p>The Certificate Registration Number. Is 46405-9743A</p> |
| Test Site Location                | : | Room 101, 1101, Building 2, No. 61, Hongmei Section, Wangsha Road, Hongmei Town, Dongguan, Guangdong, People's Republic of China                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |

---

## 8. Applicable Standards and References

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

### Test Standards:

47 CFR Part 15, Subpart C, 15.247

ANSI C63.10-2020 + Cor.1-2023+C63.10a-2024 + Errata to C63.10a-2024

### References Test Guidance:

DTS KDB 558074 D01 15.247 Meas Guidance v05r02

### Remark:

The EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

## 9. Deviations and Abnormalities from Standard Conditions

No additions, deviations and exclusions from the standard.

## 10. Test Conditions

| No. | Test Item                                        | Test Mode | Test Voltage            | Tested by | Remarks    |
|-----|--------------------------------------------------|-----------|-------------------------|-----------|------------|
| 1.  | AC Power Conducted Emission                      | 1-3       | AC 120V 60Hz            | Desn      | See note 1 |
| 2.  | Max. Conducted Output Power                      | 1-3       | DC 3.8V                 | Desn      | See note 1 |
| 3.  | 6dB Bandwidth                                    | 1-3       | DC 3.8V                 | Desn      | See note 1 |
| 4.  | Power Spectral Density                           | 1-3       | DC 3.8V                 | Desn      | See note 1 |
| 5.  | Band Edge and Conducted Spurious Emissions       | 1-3       | DC 3.8V                 | Desn      | See note 1 |
| 6.  | Radiated Spurious Emissions and Restricted Bands | 1-4       | AC 120V 60Hz<br>DC 3.8V | Desn      | See note 1 |
| 7.. | Antenna Requirement                              | ---       | ---                     | ---       | ---        |

**Note:**

1. The testing climatic conditions for temperature, humidity, and atmospheric pressure are within: 15~35°C, 30~70%, 86~106kPa.
2. As the EUT can be operated multiple positions, all X,Y,Z axis were considered during the test and only the worst case X was recorded.
3. For test voltage DC 3.8V from internal battery, AC 120V 60Hz from adapter.
4. Only the worst case was recorded in the report.

## 11. Measurement Uncertainty

| No. | Test Item                    | Frequency      | Uncertainty | Remarks |
|-----|------------------------------|----------------|-------------|---------|
| 1.  | Conducted Emission           | 150KHz ~ 30MHz | ±2.92 dB    | ---     |
| 2.  | Radiated Emission            | 9kHz ~ 30MHz   | ±5.63 dB    | ---     |
|     |                              | 30MHz ~ 1GHz   | ±5.63 dB    | ---     |
|     |                              | 1GHz ~ 18GHz   | ±5.16 dB    | ---     |
|     |                              | 18GHz ~ 40GHz  | ±5.16 dB    | ---     |
| 3.  | Conducted Spurious Emissions | 10Hz ~ 40GHz   | ±1.06 dB    | ---     |
| 4.  | RF Output Power              | 10Hz ~ 40GHz   | ±1.08 dB    | ---     |
| 5.  | Power Spectral Density       | 10Hz ~ 40GHz   | ±1.08 dB    | ---     |
| 6.  | Occupied Channel Bandwidth   | ---            | ±0.71%      | ---     |

**Note:**

1. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.
2. The measurement uncertainty levels above are estimated and calculated according to CISPR 16-4-2.
3. The conformity assessment statement in this report is based solely on the test results, measurement uncertainty is excluded.

## 12. Sample Calculations

| Conducted Emission                                                                                                                                                                                                                                                                                                                                                                                   |                      |                     |                    |              |           |          |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------|---------------------|--------------------|--------------|-----------|----------|
| Freq. (MHz)                                                                                                                                                                                                                                                                                                                                                                                          | Reading Level (dBUV) | Correct Factor (dB) | Measurement (dBUV) | Limit (dBUV) | Over (dB) | Detector |
| 0.2740                                                                                                                                                                                                                                                                                                                                                                                               | 28.29                | 20.61               | 48.90              | 61.00        | -12.10    | QP       |
| <p>Where,</p> <p>Freq. = Emission frequency in MHz</p> <p>Reading Level = Spectrum Analyzer/Receiver reading</p> <p>Corrector Factor = Insertion loss of LISN + Cable Loss + RF Switching Unit attenuation</p> <p>Measurement = Reading + Corrector Factor</p> <p>Limit = Limit stated in standard</p> <p>Margin = Measurement - Limit</p> <p>Detector = Reading for Quasi-Peak / Average / Peak</p> |                      |                     |                    |              |           |          |

| Radiated Spurious Emissions and Restricted Bands                                                                                                                                                                                                                                                                                                                                                       |                      |                       |                      |                |           |          |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------|-----------------------|----------------------|----------------|-----------|----------|
| Freq. (MHz)                                                                                                                                                                                                                                                                                                                                                                                            | Reading Level (dBUV) | Correct Factor (dB/m) | Measurement (dBUV/m) | Limit (dBUV/m) | Over (dB) | Detector |
| 186.1700                                                                                                                                                                                                                                                                                                                                                                                               | 39.83                | -8.63                 | 31.20                | 43.50          | -12.30    | QP       |
| <p>Where,</p> <p>Freq. = Emission frequency in MHz</p> <p>Reading Level = Spectrum Analyzer/Receiver reading</p> <p>Corrector Factor = Antenna Factor + Cable Loss - Pre-amplifier</p> <p>Measurement = Reading + Corrector Factor</p> <p>Limit = Limit stated in standard</p> <p>Over = Margin, which calculated by Measurement - Limit</p> <p>Detector = Reading for Quasi-Peak / Average / Peak</p> |                      |                       |                      |                |           |          |

Note: For all conducted test items, the spectrum analyzer offset or transducer is derived from RF cable loss and attenuator factor. The offset or transducer is equal to the RF cable loss plus attenuator factor.

## 13. Test Items and Results

### 13.1 Conducted Emissions Measurement


#### LIMIT

According to the requirements of FCC PART 15.207, the limits are as follows:

| Frequency (MHz) | Quasi-peak | Average  |
|-----------------|------------|----------|
| 0.15 to 0.5     | 66 to 56   | 56 to 46 |
| 0.5 to 5        | 56         | 46       |
| 5 to 30         | 60         | 50       |

- Note:
1. If the limits for the average detector are met when using the quasi-peak detector, then the limits for the measurements with the average detector are considered to be met.
  2. The lower limit shall apply at the transition frequencies.
  3. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5MHz.

#### BLOCK DIAGRAM OF TEST SETUP



---

## TEST PROCEDURES

- a. The EUT was placed on a wooden table 0.8m height from the metal ground plan and 0.4m from the conducting wall of the shielding room and it was kept at 0.8m from any other grounded conducting surface.
- b. All I/O cables and support devices were positioned as per ANSI C63.10.
- c. Connect mains power port of the EUT to a line impedance stabilization network (LISN).
- d. Connect all support devices to the other LISN and AAN, if needed.
- e. Scan the frequency range from 150KHz to 30MHz at both sides of AC line for maximum conducted interference checking and record the test data.

## TEST RESULTS

PASS


Please refer to the following pages.

|                |                                 |
|----------------|---------------------------------|
| M/N: KH138NVPK | Testing Voltage: AC 120V / 60Hz |
| Phase: L1      | Detector: QP & AVG              |
| Test Mode: 1   |                                 |

## Conducted Emission Measurement

Date: 2026/6/10

Time: 11:00:41




| No. Mk. | Freq.   | Reading Level | Correct Factor | Measurement | Limit | Over   | Detector | Comment |
|---------|---------|---------------|----------------|-------------|-------|--------|----------|---------|
|         | MHz     | dBuV          | dB             | dBuV        | dBuV  | dB     |          |         |
| 1       | 0.1700  | 14.57         | 20.79          | 35.36       | 64.96 | -29.60 | QP       |         |
| 2       | 0.1700  | -6.80         | 20.79          | 13.99       | 54.96 | -40.97 | AVG      |         |
| 3       | 0.2660  | 7.83          | 21.07          | 28.90       | 61.24 | -32.34 | QP       |         |
| 4       | 0.2660  | -10.07        | 21.07          | 11.00       | 51.24 | -40.24 | AVG      |         |
| 5 *     | 1.1019  | 7.66          | 21.14          | 28.80       | 56.00 | -27.20 | QP       |         |
| 6       | 1.1019  | -4.24         | 21.14          | 16.90       | 46.00 | -29.10 | AVG      |         |
| 7       | 2.9620  | 4.63          | 20.87          | 25.50       | 56.00 | -30.50 | QP       |         |
| 8       | 2.9620  | -10.37        | 20.87          | 10.50       | 46.00 | -35.50 | AVG      |         |
| 9       | 6.1739  | 6.02          | 20.38          | 26.40       | 60.00 | -33.60 | QP       |         |
| 10      | 6.1739  | -8.08         | 20.38          | 12.30       | 50.00 | -37.70 | AVG      |         |
| 11      | 13.5900 | 5.07          | 20.03          | 25.10       | 60.00 | -34.90 | QP       |         |
| 12      | 13.5900 | -9.63         | 20.03          | 10.40       | 50.00 | -39.60 | AVG      |         |

|                |                                 |
|----------------|---------------------------------|
| M/N: KH138NVPK | Testing Voltage: AC 120V / 60Hz |
| Phase: N       | Detector: QP & AVG              |
| Test Mode: 1   |                                 |

## Conducted Emission Measurement

Date: 2026/6/10

Time: 11:06:35



| No. Mk. | Freq.   | Reading Level | Correct Factor | Measurement | Limit | Over   |          |         |
|---------|---------|---------------|----------------|-------------|-------|--------|----------|---------|
|         | MHz     | dBuV          | dB             | dBuV        | dBuV  | dB     | Detector | Comment |
| 1       | 0.1980  | 8.77          | 20.83          | 29.60       | 63.69 | -34.09 | QP       |         |
| 2       | 0.1980  | -8.03         | 20.83          | 12.80       | 53.69 | -40.89 | AVG      |         |
| 3       | 0.2860  | 6.81          | 21.09          | 27.90       | 60.64 | -32.74 | QP       |         |
| 4       | 0.2860  | -10.39        | 21.09          | 10.70       | 50.64 | -39.94 | AVG      |         |
| 5 *     | 1.0980  | 5.60          | 21.10          | 26.70       | 56.00 | -29.30 | QP       |         |
| 6       | 1.0980  | -7.10         | 21.10          | 14.00       | 46.00 | -32.00 | AVG      |         |
| 7       | 4.9979  | 4.89          | 20.51          | 25.40       | 56.00 | -30.60 | QP       |         |
| 8       | 4.9979  | -9.61         | 20.51          | 10.90       | 46.00 | -35.10 | AVG      |         |
| 9       | 6.0419  | 6.54          | 20.36          | 26.90       | 60.00 | -33.10 | QP       |         |
| 10      | 6.0419  | -8.66         | 20.36          | 11.70       | 50.00 | -38.30 | AVG      |         |
| 11      | 12.7259 | 5.33          | 19.87          | 25.20       | 60.00 | -34.80 | QP       |         |
| 12      | 12.7259 | -9.87         | 19.87          | 10.00       | 50.00 | -40.00 | AVG      |         |

## 13.2 Maximum Conducted Output Power Measurement


### LIMIT

For system using digital modulation in the 2400-2483.5 MHz bands, the limit for peak output power is 1 Watt.

If the transmitting antenna of directional gain greater than 6dBi are used the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the Antenna exceeds 6dBi. The e.i.r.p. shall not exceed 4W.

In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of Antenna exceeds 6dBi.

### BLOCK DIAGRAM OF TEST SETUP



### TEST PROCEDURES

ANSI C63.10, Section 11.9.1.3

ANSI C63.10, Section 11.9.2.3.2

### TEST RESULTS

PASS

Please refer to the following table.


| GFSK    |                 |               |                         |             |        |
|---------|-----------------|---------------|-------------------------|-------------|--------|
| Channel | Frequency (MHz) | RF PHY (Mbps) | Peak Output Power (dBm) | Limit (dBm) | Result |
| 0       | 2402            | 1             | -8.686                  | ≤30         | PASS   |
| 19      | 2440            | 1             | -7.636                  | ≤30         | PASS   |
| 39      | 2480            | 1             | -7.825                  | ≤30         | PASS   |
| 0       | 2402            | 2             | -8.659                  | ≤30         | PASS   |
| 19      | 2440            | 2             | -7.633                  | ≤30         | PASS   |
| 39      | 2480            | 2             | -7.797                  | ≤30         | PASS   |

### 13.3 6dB Bandwidth Measurement

#### LIMIT

The minimum 6dB bandwidth shall be at least 500 kHz

#### BLOCK DIAGRAM OF TEST SETUP



#### TEST PROCEDURES

The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer was set as below according to FCC KDB558074 (v05r02):

- Set the RBW = shall be in the range of 1% to 5% of the OBW but not less than 100KHz.
- Set the VBW  $\geq 3 \times$  RBW
- Set the Detector = peak.
- Set the Sweep time = No faster than coupled (auto) time.
- Set the Trace mode = max hold.
- Allow trace to fully stabilize.
- Measure the maximum width of the emission by placing two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-6dB down amplitude”. If a marker is below this “-6 dB down amplitude” value, then it shall be as close as possible to this value.

#### TEST RESULTS


PASS

Please refer to the following tables.


| GFSK    |                 |               |                     |                     |                 |        |
|---------|-----------------|---------------|---------------------|---------------------|-----------------|--------|
| Channel | Frequency (MHz) | RF PHY (Mbps) | 6dB Bandwidth (MHz) | 99% Bandwidth (MHz) | 6dB Limit (MHz) | Result |
| 0       | 2402            | 1             | 0.6977              | -                   | >0.5            | PASS   |
| 19      | 2440            | 1             | 0.6984              | -                   | >0.5            | PASS   |
| 39      | 2480            | 1             | 0.7031              | -                   | >0.5            | PASS   |
| 0       | 2402            | 2             | 1.192               | -                   | >0.5            | PASS   |
| 19      | 2440            | 2             | 1.192               | -                   | >0.5            | PASS   |
| 39      | 2480            | 2             | 1.195               | -                   | >0.5            | PASS   |

## Test Plots of 6dB Bandwidth


### RF PHY 1Mbps 2402MHz



### RF PHY 1Mbps 2440MHz




### RF PHY 1Mbps 2480MHz




### Test Plots of 6dB Bandwidth


#### RF PHY 2Mbps 2402MHz



#### RF PHY 2Mbps 2440MHz



#### RF PHY 2Mbps 2480MHz




### 13.4 Power Spectral Density Measurement

#### LIMIT

The Maximum of Power Spectral Density Measurement is 8dBm in any 3 kHz.

#### BLOCK DIAGRAM OF TEST SETUP



#### TEST PROCEDURES

The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer was set as below according to FCC KDB558074 (v05r02):

- a. Set analyzer center frequency to DTS channel center frequency.
- b. Set the span to 1.5 times the DTS bandwidth.
- c. Set the RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100\text{KHz}$
- d. Set the VBW  $\geq 3 \times \text{RBW}$ .
- e. Set the Detector = peak.
- f. Set the Sweep time = auto couple.
- g. Set the Trace mode = max hold.
- h. Allow trace to fully stabilize.
- i. Use the peak marker function to determine the maximum amplitude level within the RBW.
- j. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

#### TEST RESULTS


PASS

Please refer to the following tables.


| GFSK    |                 |               |                |                  |         |
|---------|-----------------|---------------|----------------|------------------|---------|
| Channel | Frequency (MHz) | RF PHY (Mbps) | PSD dBm / 3kHz | Limit dBm / 3kHz | Results |
| 0       | 2402            | 1             | -21.476        | 8                | PASS    |
| 19      | 2440            | 1             | -19.887        | 8                | PASS    |
| 39      | 2480            | 1             | -20.581        | 8                | PASS    |
| 0       | 2402            | 2             | -21.138        | 8                | PASS    |
| 19      | 2440            | 2             | -20.349        | 8                | PASS    |
| 39      | 2480            | 2             | -21.283        | 8                | PASS    |

## Test Plots of Power Spectral Density


RF PHY 1Mbps 2402MHz



RF PHY 1Mbps 2440MHz




RF PHY 1Mbps 2480MHz




## Test Plots of Power Spectral Density


RF PHY 2Mbps 2402MHz



RF PHY 2Mbps 2440MHz



RF PHY 2Mbps 2480MHz




### 13.5 Band Edge and Conducted Spurious Emissions Measurement

#### LIMIT

In any 100KHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100KHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

#### BLOCK DIAGRAM OF TEST SETUP



#### TEST PROCEDURES

The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer was set as below according to ANSI C63.10, Section 11.11

##### Measurement Procedure REF

- a. Set the RBW = 100 kHz.
- b. Set the VBW  $\geq$  300 kHz.
- c. Set the Detector = peak.
- d. Set the Sweep time = auto couple.
- e. Trace mode = max hold.
- f. Allow trace to fully stabilize.
- g. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

---

### Measurement Procedure OOB

- a. Set RBW = 100 kHz.
- b. Set VBW  $\geq$  300 kHz.
- c. Set the Detector = peak.
- d. Set the Sweep = auto couple.
- e. Set the Trace Mode = max hold.
- f. Allow trace to fully stabilize.
- g. Use the peak marker function to determine the maximum amplitude level.


### TEST RESULTS

PASS


Please refer to the following test plots.

## Band Edge


### RF PHY 1Mbps Low Channel




### RF PHY 1Mbps High Channel



### RF PHY 2Mbps Low Channel



### RF PHY 2Mbps High Channel




## Conducted Spurious Emissions (GFSK: 1Mbps)


### Low Channel / 30MHz~26.5GHz



### Mid Channel / 30MHz~26.5GHz



### High Channel / 30MHz~26.5GHz



## Conducted Spurious Emissions (GFSK: 2Mbps)


### Low Channel / 30MHz~26.5GHz



### Mid Channel / 30MHz~26.5GHz



### High Channel / 30MHz~26.5GHz



### 13.6 Radiated Spurious Emissions and Restricted Bands Measurement


#### LIMIT

| Frequency range<br>MHz | Distance Meters | Field Strengths Limit (15.209) |
|------------------------|-----------------|--------------------------------|
|                        |                 | $\mu\text{V/m}$                |
| 0.009 ~ 0.490          | 300             | $2400/F(\text{kHz})$           |
| 0.490 ~ 1.705          | 30              | $24000/F(\text{kHz})$          |
| 1.705 ~ 30             | 30              | 30                             |
| 30 ~ 88                | 3               | 100                            |
| 88 ~ 216               | 3               | 150                            |
| 216 ~ 960              | 3               | 200                            |
| Above 960              | 3               | 500                            |


- Remark:
- (1) Emission level  $(\text{dB})\mu\text{V} = 20 \log \text{Emission level } \mu\text{V/m}$
  - (2) The smaller limit shall apply at the cross point between two frequency bands.
  - (3) As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.
  - (4) The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.
  - (5) §15.247(d) specifies that emissions which fall in the restricted bands, as defined in §15.205 comply with radiated emission limits specified in §15.209.

## BLOCK DIAGRAM OF TEST SETUP


For Radiated Emission below 30MHz



For Radiated Emission 30-1000MHz



For Radiated Emission Above 1000MHz.



## TEST PROCEDURES

- a. Below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi- anechoic chamber room.
- b. For the radiated emission test above 1GHz:  
The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter full anechoic chamber room. The table was rotated 360 degrees to determine the position of the highest radiation. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, de on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- c. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. The test-receiver system was set to peak detect function and specified bandwidth with maximum hold mode.
- f. A Quasi-peak measurement was then made for that frequency point for below 1GHz test. PK and AV for above 1GHz emission test.

During the radiated emission test, the spectrum analyzer was set with the following configurations:

| Frequency Band (MHz) | Detector | Resolution Bandwidth | Video Bandwidth |
|----------------------|----------|----------------------|-----------------|
| 0.009~0.15           | QP & AVG | 200 Hz               | 1 kHz           |
| 0.15~30              | QP & AVG | 10 kHz               | 30 kHz          |
| 30 to 1000           | QP       | 120 kHz              | 300 kHz         |
| Above 1000           | Peak     | 1 MHz                | 3 MHz           |
|                      | Average  | 1 MHz                | 10 Hz           |

## TEST RESULTS

PASS

Please refer to the following pages of the worst case.


|                          |                               |
|--------------------------|-------------------------------|
| M/N: KH138NVPK           | Testing Voltage: AC 120V 60Hz |
| Polarization: Horizontal | Detector: QP                  |
| Test Mode: 4             | Distance: 3m                  |

## Radiated Emission Measurement

Date: 2026/6/11

Time: 18:20:42

80.0 dBuV/m



| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB/m | Measure-<br>ment<br>dBuV/m | Limit<br>dBuV/m | Over<br>dB | Detector | Comment |
|-----|-----|--------------|--------------------------|---------------------------|----------------------------|-----------------|------------|----------|---------|
| 1   |     | 579.9900     | 25.29                    | -1.09                     | 24.20                      | 46.00           | -21.80     | QP       |         |
| 2   |     | 709.9699     | 22.96                    | 1.14                      | 24.10                      | 46.00           | -21.90     | QP       |         |
| 3   |     | 750.7100     | 23.58                    | 1.72                      | 25.30                      | 46.00           | -20.70     | QP       |         |
| 4   |     | 859.3500     | 23.32                    | 3.38                      | 26.70                      | 46.00           | -19.30     | QP       |         |
| 5   | *   | 898.1500     | 28.37                    | 3.73                      | 32.10                      | 46.00           | -13.90     | QP       |         |
| 6   |     | 949.5600     | 22.96                    | 3.84                      | 26.80                      | 46.00           | -19.20     | QP       |         |


**Note:** Below 30MHz, the emissions are lower than 20dB below the allowable limit.

|                        |                               |
|------------------------|-------------------------------|
| M/N: KH138NVPK         | Testing Voltage: AC 120V 60Hz |
| Polarization: Vertical | Detector: QP                  |
| Test Mode: 4           | Distance: 3m                  |

## Radiated Emission Measurement

Date: 2026/6/11

Time: 18:26:42



| No. | Mk. | Freq.    | Reading Level | Correct Factor | Measurement | Limit  | Over   |          |         |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------|---------|
|     |     | MHz      | dBuV          | dB/m           | dBuV/m      | dBuV/m | dB     | Detector | Comment |
| 1   |     | 42.6100  | 29.63         | -8.33          | 21.30       | 40.00  | -18.70 | QP       |         |
| 2   | *   | 53.2800  | 35.91         | -7.91          | 28.00       | 40.00  | -12.00 | QP       |         |
| 3   |     | 797.2700 | 25.36         | 2.34           | 27.70       | 46.00  | -18.30 | QP       |         |
| 4   |     | 867.1100 | 24.44         | 3.46           | 27.90       | 46.00  | -18.10 | QP       |         |
| 5   |     | 917.5500 | 23.85         | 3.75           | 27.60       | 46.00  | -18.40 | QP       |         |
| 6   |     | 957.3200 | 22.71         | 3.89           | 26.60       | 46.00  | -19.40 | QP       |         |

**Note:** Below 30MHz, the emissions are lower than 20dB below the allowable limit.

M/N: KH138NVPK

Testing Voltage: DC 3.8V

Polarization: Horizontal

Detector: PK, AVG


Test Mode: GFSK ((Low Channel) (2Mbps)

Distance: 3m

## Radiated Emission Measurement

Date: 2026/6/11

Time: 19:56:18



| No. | Mk. | Freq.     | Reading Level | Correct Factor | Measurement | Limit  | Over   |                  |
|-----|-----|-----------|---------------|----------------|-------------|--------|--------|------------------|
|     |     | MHz       | dBuV          | dB/m           | dBuV/m      | dBuV/m | dB     | Detector Comment |
| 1   |     | 4808.000  | 50.95         | 3.82           | 54.77       | 74.00  | -19.23 | peak             |
| 2   | *   | 4808.000  | 46.98         | 3.82           | 50.80       | 54.00  | -3.20  | AVG              |
| 3   |     | 7206.000  | 52.90         | 8.66           | 61.56       | 74.00  | -12.44 | peak             |
| 4   |     | 7206.000  | 41.81         | 8.66           | 50.47       | 54.00  | -3.53  | AVG              |
| 5   |     | 17643.000 | 35.25         | 19.05          | 54.30       | 74.00  | -19.70 | peak             |
| 6   |     | 17643.000 | 26.05         | 19.05          | 45.10       | 54.00  | -8.90  | AVG              |


|                                        |                          |
|----------------------------------------|--------------------------|
| M/N: KH138NVPK                         | Testing Voltage: DC 3.8V |
| Polarization: Vertical                 | Detector: PK, AVG        |
| Test Mode: GFSK ((Low Channel) (2Mbps) | Distance: 3m             |

## Radiated Emission Measurement

Date: 2026/6/11

Time: 20:04:21

106.0 dBuV/m



| No. Mk. | Freq.     | Reading Level | Correct Factor | Measurement | Limit  | Over   |          |         |
|---------|-----------|---------------|----------------|-------------|--------|--------|----------|---------|
|         | MHz       | dBuV          | dB/m           | dBuV/m      | dBuV/m | dB     | Detector | Comment |
| 1       | 4804.000  | 51.97         | 3.80           | 55.77       | 74.00  | -18.23 | peak     |         |
| 2       | 4804.000  | 42.11         | 3.80           | 45.91       | 54.00  | -8.09  | AVG      |         |
| 3       | 7206.000  | 48.35         | 8.66           | 57.01       | 74.00  | -16.99 | peak     |         |
| 4 *     | 7206.000  | 41.16         | 8.66           | 49.82       | 54.00  | -4.18  | AVG      |         |
| 5       | 17881.000 | 34.72         | 20.18          | 54.90       | 74.00  | -19.10 | peak     |         |
| 6       | 17881.000 | 26.97         | 20.18          | 47.15       | 54.00  | -6.85  | AVG      |         |


|                                        |                          |
|----------------------------------------|--------------------------|
| M/N: KH138NVPK                         | Testing Voltage: DC 3.8V |
| Polarization: Horizontal               | Detector: PK, AVG        |
| Test Mode: GFSK ((Low Channel) (2Mbps) | Distance: 3m             |

## Radiated Emission Measurement

Date: 2026/6/11

Time: 20:44:05

106.0 dBuV/m



| No. | Mk. | Freq.     | Reading Level | Correct Factor | Measurement | Limit  | Over   |          |         |
|-----|-----|-----------|---------------|----------------|-------------|--------|--------|----------|---------|
|     |     | MHz       | dBuV          | dB/m           | dBuV/m      | dBuV/m | dB     | Detector | Comment |
| 1   |     | 19216.000 | 42.55         | 7.09           | 49.64       | 74.00  | -24.36 | peak     |         |
| 2   |     | 19216.000 | 33.42         | 7.09           | 40.51       | 54.00  | -13.49 | AVG      |         |
| 3   |     | 21618.000 | 41.72         | 4.98           | 46.70       | 74.00  | -27.30 | peak     |         |
| 4   |     | 21618.000 | 35.36         | 4.98           | 40.34       | 54.00  | -13.66 | AVG      |         |
| 5   |     | 24020.000 | 42.90         | 5.44           | 48.34       | 74.00  | -25.66 | peak     |         |
| 6   | *   | 24020.000 | 35.94         | 5.44           | 41.38       | 54.00  | -12.62 | AVG      |         |


|                                        |                          |
|----------------------------------------|--------------------------|
| M/N: KH138NVPK                         | Testing Voltage: DC 3.8V |
| Polarization: Vertical                 | Detector: PK, AVG        |
| Test Mode: GFSK ((Low Channel) (2Mbps) | Distance: 3m             |

## Radiated Emission Measurement

Date: 2026/6/11

Time: 20:52:47

106.0 dBuV/m



| No. | Mk. | Freq.     | Reading Level | Correct Factor | Measurement | Limit  | Over   | Detector | Comment |
|-----|-----|-----------|---------------|----------------|-------------|--------|--------|----------|---------|
|     |     | MHz       | dBuV          | dB/m           | dBuV/m      | dBuV/m | dB     |          |         |
| 1   |     | 19216.000 | 42.51         | 7.09           | 49.60       | 74.00  | -24.40 | peak     |         |
| 2   | *   | 19216.000 | 34.52         | 7.09           | 41.61       | 54.00  | -12.39 | AVG      |         |
| 3   |     | 21618.000 | 43.36         | 4.98           | 48.34       | 74.00  | -25.66 | peak     |         |
| 4   |     | 21618.000 | 35.23         | 4.98           | 40.21       | 54.00  | -13.79 | AVG      |         |
| 5   |     | 24020.000 | 42.39         | 5.44           | 47.83       | 74.00  | -26.17 | peak     |         |
| 6   |     | 24020.000 | 35.64         | 5.44           | 41.08       | 54.00  | -12.92 | AVG      |         |


|                                        |                          |
|----------------------------------------|--------------------------|
| M/N: KH138NVPK                         | Testing Voltage: DC 3.8V |
| Polarization: Horizontal               | Detector: PK, AVG        |
| Test Mode: GFSK ((Mid Channel) (2Mbps) | Distance: 3m             |

## Radiated Emission Measurement

Date: 2026/6/11

Time: 20:20:17

106.0 dBuV/m



| No. | Mk. | Freq.     | Reading Level | Correct Factor | Measurement | Limit  | Over   |          |         |
|-----|-----|-----------|---------------|----------------|-------------|--------|--------|----------|---------|
|     |     | MHz       | dBuV          | dB/m           | dBuV/m      | dBuV/m | dB     | Detector | Comment |
| 1   |     | 4880.000  | 49.81         | 4.05           | 53.86       | 74.00  | -20.14 | peak     |         |
| 2   | *   | 4880.000  | 46.84         | 4.05           | 50.89       | 54.00  | -3.11  | AVG      |         |
| 3   |     | 7320.000  | 46.92         | 9.01           | 55.93       | 74.00  | -18.07 | peak     |         |
| 4   |     | 7320.000  | 41.76         | 9.01           | 50.77       | 54.00  | -3.23  | AVG      |         |
| 5   |     | 17830.000 | 35.38         | 19.93          | 55.31       | 74.00  | -18.69 | peak     |         |
| 6   |     | 17830.000 | 27.71         | 19.93          | 47.64       | 54.00  | -6.36  | AVG      |         |


|                                        |                          |
|----------------------------------------|--------------------------|
| M/N: KH138NVPK                         | Testing Voltage: DC 3.8V |
| Polarization: Vertical                 | Detector: PK, AVG        |
| Test Mode: GFSK ((Mid Channel) (2Mbps) | Distance: 3m             |

## Radiated Emission Measurement

Date: 2026/6/11

Time: 20:12:22

106.0 dBuV/m



| No. | Mk. | Freq.     | Reading Level | Correct Factor | Measurement | Limit  | Over   |          |         |
|-----|-----|-----------|---------------|----------------|-------------|--------|--------|----------|---------|
|     |     | MHz       | dBuV          | dB/m           | dBuV/m      | dBuV/m | dB     | Detector | Comment |
| 1   |     | 4880.000  | 48.39         | 4.05           | 52.44       | 74.00  | -21.56 | peak     |         |
| 2   |     | 4880.000  | 44.31         | 4.05           | 48.36       | 54.00  | -5.64  | AVG      |         |
| 3   |     | 7320.000  | 46.12         | 9.01           | 55.13       | 74.00  | -18.87 | peak     |         |
| 4   | *   | 7320.000  | 40.42         | 9.01           | 49.43       | 54.00  | -4.57  | AVG      |         |
| 5   |     | 17881.000 | 33.52         | 20.18          | 53.70       | 74.00  | -20.30 | peak     |         |
| 6   |     | 17881.000 | 26.94         | 20.18          | 47.12       | 54.00  | -6.88  | AVG      |         |


|                                        |                          |
|----------------------------------------|--------------------------|
| M/N: KH138NVPK                         | Testing Voltage: DC 3.8V |
| Polarization: Horizontal               | Detector: PK, AVG        |
| Test Mode: GFSK ((Mid Channel) (2Mbps) | Distance: 3m             |

## Radiated Emission Measurement

Date: 2026/6/11

Time: 21:08:05

106.0 dBuV/m



| No. | Mk. | Freq.     | Reading Level | Correct Factor | Measurement | Limit  | Over   |          |         |
|-----|-----|-----------|---------------|----------------|-------------|--------|--------|----------|---------|
|     |     | MHz       | dBuV          | dB/m           | dBuV/m      | dBuV/m | dB     | Detector | Comment |
| 1   |     | 19520.000 | 40.94         | 6.68           | 47.62       | 74.00  | -26.38 | peak     |         |
| 2   |     | 19520.000 | 33.68         | 6.68           | 40.36       | 54.00  | -13.64 | AVG      |         |
| 3   |     | 21960.000 | 41.90         | 5.43           | 47.33       | 74.00  | -26.67 | peak     |         |
| 4   | *   | 21960.000 | 35.83         | 5.43           | 41.26       | 54.00  | -12.74 | AVG      |         |
| 5   |     | 24400.000 | 42.93         | 5.67           | 48.60       | 74.00  | -25.40 | peak     |         |
| 6   |     | 24400.000 | 34.65         | 5.67           | 40.32       | 54.00  | -13.68 | AVG      |         |


|                                        |                          |
|----------------------------------------|--------------------------|
| M/N: KH138NVPK                         | Testing Voltage: DC 3.8V |
| Polarization: Vertical                 | Detector: PK, AVG        |
| Test Mode: GFSK ((Mid Channel) (2Mbps) | Distance: 3m             |

## Radiated Emission Measurement

Date: 2026/6/11

Time: 21:00:51

106.0 dBuV/m



| No. | Mk. | Freq.     | Reading Level | Correct Factor | Measurement | Limit  | Over   | Detector | Comment |
|-----|-----|-----------|---------------|----------------|-------------|--------|--------|----------|---------|
|     |     | MHz       | dBuV          | dB/m           | dBuV/m      | dBuV/m | dB     |          |         |
| 1   |     | 19520.000 | 40.52         | 6.68           | 47.20       | 74.00  | -26.80 | peak     |         |
| 2   |     | 19520.000 | 33.67         | 6.68           | 40.35       | 54.00  | -13.65 | AVG      |         |
| 3   |     | 21960.000 | 41.89         | 5.43           | 47.32       | 74.00  | -26.68 | peak     |         |
| 4   | *   | 21960.000 | 36.19         | 5.43           | 41.62       | 54.00  | -12.38 | AVG      |         |
| 5   |     | 24400.000 | 41.86         | 5.67           | 47.53       | 74.00  | -26.47 | peak     |         |
| 6   |     | 24400.000 | 34.72         | 5.67           | 40.39       | 54.00  | -13.61 | AVG      |         |


|                                        |                          |
|----------------------------------------|--------------------------|
| M/N: KH138NVPK                         | Testing Voltage: DC 3.8V |
| Polarization: Horizontal               | Detector: PK, AVG        |
| Test Mode: GFSK (High Channel) (2Mbps) | Distance: 3m             |

## Radiated Emission Measurement

Date: 2026/6/11

Time: 20:28:47

106.0 dBuV/m



| No. | Mk. | Freq.     | Reading Level | Correct Factor | Measurement | Limit  | Over   |          |         |
|-----|-----|-----------|---------------|----------------|-------------|--------|--------|----------|---------|
|     |     | MHz       | dBuV          | dB/m           | dBuV/m      | dBuV/m | dB     | Detector | Comment |
| 1   |     | 4960.000  | 50.84         | 4.30           | 55.14       | 74.00  | -18.86 | peak     |         |
| 2   | *   | 4960.000  | 45.89         | 4.30           | 50.19       | 54.00  | -3.81  | AVG      |         |
| 3   |     | 7440.000  | 47.22         | 9.60           | 56.82       | 74.00  | -17.18 | peak     |         |
| 4   |     | 7440.000  | 39.76         | 9.60           | 49.36       | 54.00  | -4.64  | AVG      |         |
| 5   |     | 17983.000 | 34.61         | 20.66          | 55.27       | 74.00  | -18.73 | peak     |         |
| 6   |     | 17983.000 | 27.24         | 20.66          | 47.90       | 54.00  | -6.10  | AVG      |         |


|                                        |                          |
|----------------------------------------|--------------------------|
| M/N: KH138NVPK                         | Testing Voltage: DC 3.8V |
| Polarization: Vertical                 | Detector: PK, AVG        |
| Test Mode: GFSK (High Channel) (2Mbps) | Distance: 3m             |

## Radiated Emission Measurement

Date: 2026/6/11

Time: 20:36:51

106.0 dBuV/m



| No. | Mk. | Freq.     | Reading Level | Correct Factor | Measure-ment | Limit  | Over   |          |
|-----|-----|-----------|---------------|----------------|--------------|--------|--------|----------|
|     |     | MHz       | dBuV          | dB/m           | dBuV/m       | dBuV/m | dB     | Detector |
| 1   |     | 4960.000  | 47.84         | 4.30           | 52.14        | 74.00  | -21.86 | peak     |
| 2   | *   | 4960.000  | 46.11         | 4.30           | 50.41        | 54.00  | -3.59  | AVG      |
| 3   |     | 7440.000  | 43.58         | 9.60           | 53.18        | 74.00  | -20.82 | peak     |
| 4   |     | 7440.000  | 33.69         | 9.60           | 43.29        | 54.00  | -10.71 | AVG      |
| 5   |     | 17966.000 | 34.59         | 20.58          | 55.17        | 74.00  | -18.83 | peak     |
| 6   |     | 17966.000 | 26.50         | 20.58          | 47.08        | 54.00  | -6.92  | AVG      |


|                                        |                          |
|----------------------------------------|--------------------------|
| M/N: KH138NVPK                         | Testing Voltage: DC 3.8V |
| Polarization: Horizontal               | Detector: PK, AVG        |
| Test Mode: GFSK (High Channel) (2Mbps) | Distance: 3m             |

## Radiated Emission Measurement

Date: 2026/6/11

Time: 21:16:53

106.0 dBuV/m



| No. | Mk. | Freq.     | Reading Level | Correct Factor | Measure-ment | Limit  | Over   |          |         |
|-----|-----|-----------|---------------|----------------|--------------|--------|--------|----------|---------|
|     |     | MHz       | dBuV          | dB/m           | dBuV/m       | dBuV/m | dB     | Detector | Comment |
| 1   |     | 19840.000 | 41.05         | 6.57           | 47.62        | 74.00  | -26.38 | peak     |         |
| 2   |     | 19840.000 | 33.81         | 6.57           | 40.38        | 54.00  | -13.62 | AVG      |         |
| 3   |     | 22320.000 | 41.98         | 5.53           | 47.51        | 74.00  | -26.49 | peak     |         |
| 4   | *   | 22320.000 | 35.98         | 5.53           | 41.51        | 54.00  | -12.49 | AVG      |         |
| 5   |     | 24800.000 | 43.90         | 5.72           | 49.62        | 74.00  | -24.38 | peak     |         |
| 6   |     | 24800.000 | 34.67         | 5.72           | 40.39        | 54.00  | -13.61 | AVG      |         |


|                                        |                          |
|----------------------------------------|--------------------------|
| M/N: KH138NVPK                         | Testing Voltage: DC 3.8V |
| Polarization: Vertical                 | Detector: PK, AVG        |
| Test Mode: GFSK (High Channel) (2Mbps) | Distance: 3m             |

## Radiated Emission Measurement

Date: 2026/6/11

Time: 21:24:56

106.0 dBuV/m



| No. | Mk. | Freq.     | Reading Level | Correct Factor | Measure-ment | Limit  | Over   |          |
|-----|-----|-----------|---------------|----------------|--------------|--------|--------|----------|
|     |     | MHz       | dBuV          | dB/m           | dBuV/m       | dBuV/m | dB     | Detector |
| 1   |     | 19840.000 | 41.73         | 6.57           | 48.30        | 74.00  | -25.70 | peak     |
| 2   | *   | 19840.000 | 34.75         | 6.57           | 41.32        | 54.00  | -12.68 | AVG      |
| 3   |     | 22320.000 | 41.77         | 5.53           | 47.30        | 74.00  | -26.70 | peak     |
| 4   |     | 22320.000 | 34.83         | 5.53           | 40.36        | 54.00  | -13.64 | AVG      |
| 5   |     | 24800.000 | 43.25         | 5.72           | 48.97        | 74.00  | -25.03 | peak     |
| 6   |     | 24800.000 | 34.56         | 5.72           | 40.28        | 54.00  | -13.72 | AVG      |

M/N: KH138NVPK

Testing Voltage: DC 3.8V

Polarization: Horizontal

Detector: PK, AVG

Test Mode: GFSK (Band Edge) (1Mbps)


Distance: 3m

## Radiated Emission Measurement

Date: 2026/6/11

Time: 19:40:46

106.0 dBuV/m



| No. | Mk. | Freq.    | Reading Level | Correct Factor | Measurement | Limit  | Over   |          |         |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------|---------|
|     |     | MHz      | dBuV          | dB/m           | dBuV/m      | dBuV/m | dB     | Detector | Comment |
| 1   |     | 2377.600 | 32.93         | -2.99          | 29.94       | 74.00  | -44.06 | peak     |         |
| 2   |     | 2377.600 | 23.22         | -2.99          | 20.23       | 54.00  | -33.77 | AVG      |         |
| 3   |     | 2390.000 | 34.79         | -2.98          | 31.81       | 74.00  | -42.19 | peak     |         |
| 4   | *   | 2390.000 | 24.12         | -2.98          | 21.14       | 54.00  | -32.86 | AVG      |         |


|                                     |                          |
|-------------------------------------|--------------------------|
| M/N: KH138NVPK                      | Testing Voltage: DC 3.8V |
| Polarization: Vertical              | Detector: PK, AVG        |
| Test Mode: GFSK (Band Edge) (1Mbps) | Distance: 3m             |

## Radiated Emission Measurement

Date: 2026/6/11

Time: 19:48:05

106.0 dBuV/m



| No. Mk. | Freq.    | Reading Level | Correct Factor | Measurement | Limit  | Over   |          |         |
|---------|----------|---------------|----------------|-------------|--------|--------|----------|---------|
|         | MHz      | dBuV          | dB/m           | dBuV/m      | dBuV/m | dB     | Detector | Comment |
| 1       | 2382.400 | 34.56         | -2.99          | 31.57       | 74.00  | -42.43 | peak     |         |
| 2       | 2382.400 | 22.61         | -2.99          | 19.62       | 54.00  | -34.38 | AVG      |         |
| 3       | 2390.000 | 32.63         | -2.98          | 29.65       | 74.00  | -44.35 | peak     |         |
| 4 *     | 2390.000 | 23.12         | -2.98          | 20.14       | 54.00  | -33.86 | AVG      |         |


|                                     |                          |
|-------------------------------------|--------------------------|
| M/N: KH138NVPK                      | Testing Voltage: DC 3.8V |
| Polarization: Horizontal            | Detector: PK, AVG        |
| Test Mode: GFSK (Band Edge) (1Mbps) | Distance: 3m             |

## Radiated Emission Measurement

Date: 2026/6/11

Time: 19:32:48

106.0 dBuV/m



| No. | Mk. | Freq.    | Reading Level | Correct Factor | Measure-ment | Limit  | Over   |          |         |
|-----|-----|----------|---------------|----------------|--------------|--------|--------|----------|---------|
|     |     | MHz      | dBuV          | dB/m           | dBuV/m       | dBuV/m | dB     | Detector | Comment |
| 1   |     | 2483.500 | 35.09         | -2.83          | 32.26        | 74.00  | -41.74 | peak     |         |
| 2   | *   | 2483.500 | 23.42         | -2.83          | 20.59        | 54.00  | -33.41 | AVG      |         |
| 3   |     | 2489.000 | 34.33         | -2.83          | 31.50        | 74.00  | -42.50 | peak     |         |
| 4   |     | 2489.000 | 23.25         | -2.83          | 20.42        | 54.00  | -33.58 | AVG      |         |


|                                     |                          |
|-------------------------------------|--------------------------|
| M/N: KH138NVPK                      | Testing Voltage: DC 3.8V |
| Polarization: Vertical              | Detector: PK, AVG        |
| Test Mode: GFSK (Band Edge) (1Mbps) | Distance: 3m             |

## Radiated Emission Measurement

Date: 2026/6/11

Time: 19:34:00

106.0 dBuV/m



| No. | Mk. | Freq.    | Reading Level | Correct Factor | Measurement | Limit  | Over   |          |         |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------|---------|
|     |     | MHz      | dBuV          | dB/m           | dBuV/m      | dBuV/m | dB     | Detector | Comment |
| 1   |     | 2483.500 | 36.49         | -2.83          | 33.66       | 74.00  | -40.34 | peak     |         |
| 2   |     | 2483.500 | 23.30         | -2.83          | 20.47       | 54.00  | -33.53 | AVG      |         |
| 3   |     | 2499.400 | 33.45         | -2.82          | 30.63       | 74.00  | -43.37 | peak     |         |
| 4   | *   | 2499.400 | 24.10         | -2.82          | 21.28       | 54.00  | -32.72 | AVG      |         |


|                                     |                          |
|-------------------------------------|--------------------------|
| M/N: KH138NVPK                      | Testing Voltage: DC 3.8V |
| Polarization: Horizontal            | Detector: PK, AVG        |
| Test Mode: GFSK (Band Edge) (2Mbps) | Distance: 3m             |

## Radiated Emission Measurement

Date: 2026/6/11

Time: 19:04:31

106.0 dBuV/m



| No. | Mk. | Freq.    | Reading Level | Correct Factor | Measurement | Limit  | Over   |                  |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|------------------|
|     |     | MHz      | dBuV          | dB/m           | dBuV/m      | dBuV/m | dB     | Detector Comment |
| 1   |     | 2378.600 | 33.66         | -2.99          | 30.67       | 74.00  | -43.33 | peak             |
| 2   |     | 2378.600 | 22.74         | -2.99          | 19.75       | 54.00  | -34.25 | AVG              |
| 3   |     | 2390.000 | 33.94         | -2.98          | 30.96       | 74.00  | -43.04 | peak             |
| 4   | *   | 2390.000 | 22.90         | -2.98          | 19.92       | 54.00  | -34.08 | AVG              |


|                                     |                          |
|-------------------------------------|--------------------------|
| M/N: KH138NVPK                      | Testing Voltage: DC 3.8V |
| Polarization: Vertical              | Detector: PK, AVG        |
| Test Mode: GFSK (Band Edge) (2Mbps) | Distance: 3m             |

## Radiated Emission Measurement

Date: 2026/6/11

Time: 19:12:40

106.0 dBuV/m



| No. | Mk. | Freq.    | Reading Level | Correct Factor | Measurement | Limit  | Over   |          |         |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------|---------|
|     |     | MHz      | dBuV          | dB/m           | dBuV/m      | dBuV/m | dB     | Detector | Comment |
| 1   |     | 2372.400 | 33.24         | -3.00          | 30.24       | 74.00  | -43.76 | peak     |         |
| 2   |     | 2372.400 | 22.88         | -3.00          | 19.88       | 54.00  | -34.12 | AVG      |         |
| 3   |     | 2390.000 | 34.41         | -2.98          | 31.43       | 74.00  | -42.57 | peak     |         |
| 4   | *   | 2390.000 | 23.08         | -2.98          | 20.10       | 54.00  | -33.90 | AVG      |         |


|                                     |                          |
|-------------------------------------|--------------------------|
| M/N: KH138NVPK                      | Testing Voltage: DC 3.8V |
| Polarization: Horizontal            | Detector: PK, AVG        |
| Test Mode: GFSK (Band Edge) (2Mbps) | Distance: 3m             |

## Radiated Emission Measurement

Date: 2026/6/11

Time: 19:18:36

106.0 dBuV/m



| No. | Mk. | Freq.    | Reading Level | Correct Factor | Measurement | Limit  | Over   |          |         |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------|---------|
|     |     | MHz      | dBuV          | dB/m           | dBuV/m      | dBuV/m | dB     | Detector | Comment |
| 1   |     | 2483.500 | 35.24         | -2.83          | 32.41       | 74.00  | -41.59 | peak     |         |
| 2   |     | 2483.500 | 23.75         | -2.83          | 20.92       | 54.00  | -33.08 | AVG      |         |
| 3   |     | 2492.600 | 32.72         | -2.83          | 29.89       | 74.00  | -44.11 | peak     |         |
| 4   | *   | 2492.600 | 24.31         | -2.83          | 21.48       | 54.00  | -32.52 | AVG      |         |


|                                     |                          |
|-------------------------------------|--------------------------|
| M/N: KH138NVPK                      | Testing Voltage: DC 3.8V |
| Polarization: Vertical              | Detector: PK, AVG        |
| Test Mode: GFSK (Band Edge) (2Mbps) | Distance: 3m             |

## Radiated Emission Measurement

Date: 2026/6/11

Time: 19:26:41

106.0 dBuV/m



| No. | Mk. | Freq.    | Reading Level | Correct Factor | Measure-ment | Limit  | Over   |          |         |
|-----|-----|----------|---------------|----------------|--------------|--------|--------|----------|---------|
|     |     | MHz      | dBuV          | dB/m           | dBuV/m       | dBuV/m | dB     | Detector | Comment |
| 1   |     | 2483.500 | 33.80         | -2.83          | 30.97        | 74.00  | -43.03 | peak     |         |
| 2   |     | 2483.500 | 23.36         | -2.83          | 20.53        | 54.00  | -33.47 | AVG      |         |
| 3   |     | 2502.800 | 33.91         | -2.81          | 31.10        | 74.00  | -42.90 | peak     |         |
| 4   | *   | 2502.800 | 24.02         | -2.81          | 21.21        | 54.00  | -32.79 | AVG      |         |

---

## 13.7 Antenna Requirement

### STANDARD APPLICABLE

According to of FCC part 15C section 15.203 and 15.247:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Systems operating in the 2400-2483.5MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum peak output power of the intentional radiator is reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

### ANTENNA CONNECTED CONSTRUCTION

The antenna is FPC antenna that no antenna other than furnished by the responsible party shall be used with the device, and the best case gain of the antenna is -3.11dBi, Therefore, the antenna is considered to meet the requirement.

## 14. Test Equipment List

| Item | Equipment                         | Manufacturer                            | Model No.             | Serial No.        | Last Cal.     | Cal. Interval |
|------|-----------------------------------|-----------------------------------------|-----------------------|-------------------|---------------|---------------|
| 1.   | Test Receiver                     | Rohde & Schwarz                         | ESCI                  | 101152            | Aug. 21, 2025 | 1 Year        |
| 2.   | L.I.S.N                           | Rohde & Schwarz                         | ENV 216               | 101317            | Aug. 21, 2025 | 1 Year        |
| 3.   | L.I.S.N                           | Schwarzbeck                             | NNLK8129              | 00558             | Aug. 23, 2025 | 1 Year        |
| 4.   | RF Switching Unit                 | Compliance<br>Direction Systems<br>Inc. | RSU-M2                | 38311             | Aug. 21, 2025 | 1 Year        |
| 5.   | Test Receiver                     | Rohde & Schwarz                         | ESCI7                 | 100837            | Aug. 21, 2025 | 1 Year        |
| 6.   | Spectrum Analyzer                 | Keysight                                | N9020A                | MY50510314        | Aug. 21, 2025 | 1 Year        |
| 7.   | Spectrum Analyzer                 | Keysight                                | N9020A                | MY54200831        | Aug. 22, 2025 | 1 Year        |
| 8.   | Spectrum Analyzer                 | Keysight                                | N9010B                | MY62170254        | Aug. 21, 2025 | 1 Year        |
| 9.   | Antenna                           | Schwarzbeck                             | VULB9163              | 01552             | Aug. 16, 2025 | 2 Year        |
| 10.  | Loop Antenna                      | Schwarzbeck                             | FMZB 1513             | 1513-272          | Aug. 16, 2025 | 2 Year        |
| 11.  | Horn Antenna                      | COM-Power                               | AH-118                | 071078            | Aug. 16, 2025 | 2 Year        |
| 12.  | Pre-Amplifier                     | HP                                      | HP 8447D              | 1145A00203        | Aug. 21, 2025 | 1 Year        |
| 13.  | Pre-Amplifier                     | HP                                      | HP 8449B              | 3008A00964        | Aug. 23, 2025 | 1 Year        |
| 14.  | Communication<br>Tester           | Rohde & Schwarz                         | CMW500                | 109851            | Aug. 28, 2025 | 1 Year        |
| 15.  | Power Sensor                      | DARE                                    | RPR3006W              | 15I00041SNO<br>64 | Aug. 28, 2025 | 1 Year        |
| 16.  | Horn Antenna                      | COM-Power                               | AH-840                | 10100020          | Aug. 28, 2025 | 2 Year        |
| 17.  | Temperature &<br>Humidity Chamber | Wanshun                                 | SS-HWHS-80            | N/A               | Aug. 09, 2025 | 1 Year        |
| 18.  | DC Source                         | ZHAOXIN                                 | KXN305D               | N/A               | Aug. 23, 2025 | 1 Year        |
| 19.  | Temporary<br>antenna connector    | TESCOM                                  | SS402                 | N/A               | N/A           | N/A           |
| 20.  | Chamber                           | YIHENG                                  | 9*6*6m                | N/A               | Sep. 22, 2025 | 2 Year        |
| 21.  | Test Software                     | MWRF                                    | MTS 8310,<br>V2.0.0.0 | N/A               | N/A           | N/A           |
| 22.  | Test Software                     | EZ                                      | EZ_EMC,<br>NTC-3A1.1  | N/A               | N/A           | N/A           |

Note: For photographs of EUT and measurement, please refer to appendix in separate documents.

---End---