

Test report No:
2660719R.701A

FCC TEST REPORT

Product Name	WiFi/BT Module
Model and /or type reference	WM55UP01
Trademark	Hisense
FCC ID	2AJVQ-WM55UP01
Applicant's name / address	Qingdao Intelligent & Precise Electronics Co., Ltd. No.218, Qianwangang Road, Economic and Technological Development Zone, Qingdao, Shandong Province, China
Test method requested, standard	47 CFR FCC Part 15 (Section 15.247) ANSI C63.10: 2020
Verdict Summary	IN COMPLIANCE
Tested By (name / position & signature)	Reyn Chen / Supervisor 
Approved by (name / position & signature)	Well Wei / Manager 
Date of issue	2026-08-03
Report Version	V1.0
Report template No	Template_FCC Part 15C-RF-V1.0

INDEX

	page
Competences and Guarantees.....	4
General conditions.....	4
Environmental conditions.....	5
Possible test case verdicts	5
Abbreviations	5
Document History	6
Remarks and Comments	6
Used Equipment	7
Uncertainty.....	9
1 General Information.....	10
1.1 General Description of the Item(s)	10
1.2 Channel List	11
2 Description of Test Setup	12
2.1 Auxiliary equipment /Accessories/Test software for the EUT	12
2.2 Worst-case configuration and mode	13
2.3 Power setting in test.....	14
3 Verdict summary section	15
3.1 Standards	15
3.2 Deviation(s) from the Standard(s) / Test Specification(s)	15
3.3 Overview of results	16
3.4 Test Facility	17
4 TEST ITEMS OF LIMIT/SETUP/PROCEDURE	18
4.1 Emissions in restricted frequency bands	18
4.1.1 Limit.....	18
4.1.2 Test Setup.....	20
4.1.3 Test Procedure	21
4.2 Emissions in non-restricted frequency band	22
4.2.1 Limit.....	22
4.2.2 Test Setup.....	22
4.2.3 Test Procedure	22
4.3 Duty cycle.....	23
4.3.1 Limit.....	23
4.3.2 Test Setup.....	23
4.3.3 Test Procedure	23

4.4	Radiated Emission Band Edge	24
4.4.1	Limit.....	24
4.4.2	Test Setup.....	24
4.4.3	Test Procedure	25
4.5	DTS Bandwidth	26
4.5.1	Limit.....	26
4.5.2	Test Setup.....	26
4.5.3	Test Procedure	26
4.6	Fundamental emission output power	27
4.6.1	Limit.....	27
4.6.2	Test Setup.....	27
4.6.3	Test Procedure	28
4.7	Power Density	30
4.7.1	Limit:.....	30
4.7.2	Test Setup.....	30
4.7.3	Test Procedure	30
4.8	AC Power Line Conducted Emission	32
4.8.1	Limit.....	32
4.8.2	Test Setup	32
4.8.3	Test Procedure.....	32
4.9	Antenna Requirement	33
4.9.1	Limit:.....	33
4.9.2	Antenna Connector Construction:.....	33
5	Test setup photo and EUT Photo	34
6	Test Result	35
	Appendix A: DTS Bandwidth	35
	Appendix C: Maximum power spectral density	43
	Appendix D: Band edge measurements.....	50
	Appendix E: Conducted Spurious Emission.....	82
	Appendix F: Duty Cycle	100
	Appendix G: Emissions in Restricted Bands	103

COMPETENCES AND GUARANTEES

DEKRA is a testing laboratory competent to carry out the tests described in this report.

In order to assure the traceability to other national and international laboratories, DEKRA has a calibration and maintenance program for its measurement equipment.

DEKRA guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated in the report and it is based on the knowledge and technical facilities available at DEKRA at the time of performance of the test.

DEKRA is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA.

GENERAL CONDITIONS

Test Location	Room 101, 1/F., Building 7, Smart Science Park Phase 5. No. 8213, Fanhua Avenue, Economic and Technological Development Zone, Hefei, Anhui, China
Date(receive sample)	Jun. 29, 2026
Date (start test)	Jul. 05, 2026
Date (finish test)	Jul. 23, 2026

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or Competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA.

ENVIRONMENTAL CONDITIONS

The climatic conditions during the tests are within the limits specified by the manufacturer for the operation of the EUT and the test equipment. The climatic conditions during the tests were within the following limits:

Ambient temperature	15 °C – 35 °C
Relative Humidity air	30% - 60%

If explicitly required in the basic standard or applied product / product family standard the climatic values are recorded and documented separately in this test report.

POSSIBLE TEST CASE VERDICTS

Test case does not apply to test object	N/A
Test object does meet requirement	P (Pass) / PASS
Test object does not meet requirement	F (Fail) / FAIL
Not measured	N/M

ABBREVIATIONS

For the purposes of the present document, the following abbreviations apply:

EUT	: Equipment Under Test
QP	: Quasi-Peak
CAV	: CISPR Average
AV	: Average
CDN	: Coupling Decoupling Network
SAC	: Semi-Anechoic Chamber
OATS	: Open Area Test Site
BW	: Bandwidth
AM	: Amplitude Modulation
PM	: Pulse Modulation
HCP	: Horizontal Coupling Plane
VCP	: Vertical Coupling Plane
U_N	: Nominal voltage
T_x	: Transmitter
R_x	: Receiver
N/A	: Not Applicable
N/M	: Not Measured

DOCUMENT HISTORY

Report No.	Version	Description	Issued Date
2660719R.701A	V1.0	Initial issue of report.	2026-08-03

REMARKS AND COMMENTS

1. The equipment under test (EUT) does meet the essential requirements of the stated standard(s)/test(s).
2. These test results on a sample of the device are for the purpose of demonstrating Compliance with 47 CFR FCC Part 15 (Section 15.247).
3. The measurement result is considered in conformance with the requirement if it is within the prescribed limit, It is not necessary to account the uncertainty associated with the measurement result.
4. The test results presented in this report relate only to the object tested.
5. The test report shall not be reproduced without the written approval of DEKRA Testing and Certification (Suzhou) Co., Ltd.
6. This report will not be used for social proof function in China market.
7. DEKRA declines any responsibility with the following test data provided by customer that may affect the validity of result:
 - Chapter 1.1 General Description of the Item(s);
 - Chapter 1.2 Channel List;

USED EQUIPMENT

Conducted Test/ SR103

Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date	Firmware Version	Software Version
Constant temperature and humidity chamber	Chuang Cexing	CCX-KS80DH	0005037	2026.05.11	2027.05.10	N/A	N/A
Frequency extender for EXG or MXG	Keysight	N5182BX07	MY59362500	2026.06.17	2027.06.16	N/A	N/A
Wideband Radio Communication Tester	R&S	CMW 500	163864	2026.05.08	2027.05.07	V 4.0.60	N/A
MAX Signal Analyzer	Keysight	N9020A	MY56060147	2026.06.17	2027.06.16	A.17.55	N/A
RF Control Unit	Tonscend	JS0806-2	806JS2X02 1710251017	2026.06.23	2027.06.22	N/A	N/A
Signal Generator	R&S	SMR 20	100654	2026.06.09	2027.06.08	N/A	N/A
MXG-B RF Vector Signal Generator	Keysight	N5182B	MY61252529	2026.06.17	2027.06.16	N/A	N/A
Test Software	Tonscend	TS1120	JS1120-3	N/A	N/A	N/A	V3.6.21
Temperature/Humidity Meter	RITERS	RTS-8S	034	2025.08.25	2026.08.24	N/A	N/A

Radiated Emission(9KHz-1GHz) / AC102

Instrument	Manufacturer	Model No.	Serial No.	Cal. Date	Next Cal. Date	Firmware Version	Software version
semi-anechoic chamber	Maorui	9m*6m*6m	AC102	2023.08.23	2026.08.22	N/A	N/A
Bilog Antenna	TESEQ	CBL6112D	57867	2025.10.27	2026.10.26	N/A	N/A
Loop Antenna	R&S	HFH2-Z2E	101181	2025.10.24	2026.10.23	N/A	N/A
EMI test receiver	R&S	ESR7	102753	2026.05.07	2027.05.06	V3.66SP1	
Temperature/ Humidity Meter	RTS-8S	RTS-8S	013	2025.08.29	2026.08.28	N/A	N/A
Temperature/ Humidity Meter	RTS-8S	RTS-8S	015	2025.08.25	2026.08.24	N/A	N/A
Test Software	TS+	TS Testing System	N/A	N/A	N/A	N/A	V1.0

Radiated Emission (1GHz-40GHz) / AC103

Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date	Firmware Version	Software Version
Fully-anechoic chamber	Maorui	9m*6m*6m	AC103	2023.08.23	2026.08.22	N/A	N/A
MAX Signal Analyzer	Keysight	N9020B	MY63490118	2025.08.08	2026.08.07	A35.06	N/A
Horn Antenna	RF SPIN	DRH18-E	KV2D11A18ES	2025.10.19	2026.10.18	N/A	N/A
Low Noise Amplifier	Tonscend	TAP01018048S	AP23J8060307	2025.10.17	2026.10.16	N/A	N/A
Broad-Band Horn Antenna	Schwarzbeck	BBHA9170	01312	2025.10.18	2026.10.17	N/A	N/A
Low Noise Amplifier	ESE	LNA1840	LNA23070301	2025.10.17	2026.10.16	N/A	N/A
Temperature/Humidity Meter	RITERS	RTS-8S	029	2025.08.25	2026.08.24	N/A	N/A
Temperature/Humidity Meter	RITERS	RTS-8S	010	2025.08.25	2026.08.24	N/A	N/A
Test Software	Tonscend	J536	JS36-RSE	N/A	N/A	N/A	5.0.0

UNCERTAINTY

Uncertainties have been calculated according to the DEKRA internal document. The reported expanded uncertainties are based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95%.

Test item	Uncertainty
AC Power Line Conducted Emission	9kHz~150kHz: 2.8 dB 150kHz~30MHz: 2.4 dB
Power Output	± 1.3 dB
Radiated Emission(30MHz~1GHz)	Horizontal: 30MHz~300MHz: 3.5 dB, 300MHz~1GHz: 3.6 dB Vertical: 30MHz~300MHz: 3.6 dB, 300MHz~1GHz: 3.5 dB
Radiated Emission(1GHz~40GHz)	Horizontal: 1GHz~40GHz: 5.0 dB Vertical: 1GHz~40GHz: 4.8 dB
RF antenna conducted test	± 1.3 dB
Radiated Emission Band Edge	± 3.9 dB
DTS Bandwidth	± 1.0 kHz
Occupied Bandwidth	± 1.0 kHz
Power Density	± 1.3 dB

1 GENERAL INFORMATION

1.1 General Description of the Item(s)

Product Name:	WiFi/BT Module				
Model Name:	WM55UP01				
Trademark.:	Hisense				
FCC ID:	2AJVQ-WM55UP01				
Power Supply:	3.3Vdc				
Hardware Version:	N/A				
Software Version:	N/A				
Manufacturer:	Qingdao Intelligent & Precise Electronics Co., Ltd.				
Manufacturer Address:	No.218, Qianwangang Road, Economic and Technological Development Zone, Qingdao, Shandong Province, China				
Test Matrix/ IMEI:	RF Conducted	#1			
	RSE	#2			
Wireless specifiction:	802.11b/g/n				
Operating frequency range(s):	2412~2462MHz				
Type of Modulation :	802.11b: DSSS (DBPSK, DQPSK, CCK) 802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM)				
Smart System:	☒	SISO			
	☒	MIMO-CDD			
	☐	MIMO-Beamforming			
Antenna Type:	WiFi0: PIFA Antenna WiFi1: Metel Antenna				
Antenna Gain:	Power:	SISO:	WiFi0: 6.04dBi WiFi1: 2.00dBi		CDD: 6.04dBi
	PSD:	SISO:	WiFi0: 6.04dBi WiFi1: 2.00dBi		CDD: 7.26dBi

Remark:

As above information is provided and confirmed by the applicant. DEKRA is not liable to the accuracy, suitability, reliability or/and integrity of the information.

1.2 Channel List

IEEE 802.11b/g & IEEE 802.11n (20MHz)

Working Frequency of Each Channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412 MHz	2	2417 MHz	3	2422 MHz	4	2427 MHz
5	2432 MHz	6	2437 MHz	7	2442 MHz	8	2447 MHz
9	2452 MHz	10	2457 MHz	11	2462 MHz	-	-

IEEE 802.11n (40MHz)

Working Frequency of Each Channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
3	2422 MHz	4	2427 MHz	5	2432 MHz	6	2437 MHz
7	2442 MHz	8	2447 MHz	9	2452 MHz	-	-

Note: The General Description of the Item, Channel List in clause 1 are provided and confirmed by the client.

2 DESCRIPTION OF TEST SETUP

2.1 Auxiliary equipment /Accessories/Test software for the EUT

Auxiliary equipment	Type / Version	Manufacturer	Supplied by
(1) Notebook	Think pad x220	Lenovo	Adapter
(2) USB Control Cable	N/A	N/A	N/A
(3) USB Control Cable	N/A	N/A	N/A
software	Type / Version		
QATool	0.0.1.38		

Accessories Information	Cable		
	Length used during test [m]	Attached during test	Shielded
(2)USB Control Cable	1	☒	☒
(3)USB Control Cable	8	☒	☒

2.2 Worst-case configuration and mode

Low data rate was used to test on antenna port conducted tests and radiated spurious emissions since it has the highest maximum power. Following are the worst-case data rates set for test:

Modulation Type	Data Rate
802.11b	1Mbps
802.11g	6Mbps
802.11n 20	MCS0(6.5 Mbps)
802.11n 40	MCS0(13.5 Mbps)
Note.EUT supports SISO WIFI0 antenna mode, SISO WIFI1 mode and MIMO WIFI 0+1 mode.What is shown in the report is the data of the worst antenna mode.	

2.3 Power setting in test

Mode	Channel	Frequency (MHz)	Power setting
802.11b	01	2412	16
	06	2437	16
	11	2462	16
802.11g	01	2412	0D
	06	2437	0D
	11	2462	0D
802.11n20	01	2412	08
	06	2437	08
	11	2462	08
802.11n40	03	2422	06
	06	2437	06
	09	2452	06

3 VERDICT SUMMARY SECTION

This chapter presents an overview of standards and results. Refer to the next chapters for details of measured test results and applied test levels.

3.1 Standards

Standard	Year	Description
FCC CFR Title 47 Part 15 Subpart C Section 15.247	2024	Operation within the bands 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz.
ANSI C63.10	2020	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
KDB 558074 D01V05r02	2019	Guidance for performing compliance measurements on Digital Transmission System (DTS) operating under section 15.247

3.2 Deviation(s) from the Standard(s) / Test Specification(s)

The following deviation(s) was / were made from the published requirements of the listed standards: N/A.

(Please define the deviations from the standard(s) if applicable)

3.3 Overview of results

Requirement – Test Item of FCC	Standard(s)	Verdict	Remark
DTS Bandwidth	FCC 15.247(a)(2)	PASS	Test data please refer to Appendix A
Maximum conducted output power	15.247 (b)(3)	PASS	Test data please refer to Appendix B
Maximum power spectral density	FCC 15.247(e)	PASS	Test data please refer to Appendix C
Band edge measurements	FCC 15.247(d) FCC 15.205 FCC 15.209	PASS	Test data please refer to Appendix D
Conducted Spurious Emission	FCC 15.247(d), FCC 15.209	PASS	Test data please refer to Appendix E
Duty cycle	ANSI C63.10:2020	PASS	Test data please refer to Appendix F
Emissions in Restricted Bands	FCC 15.205 FCC 15.209	PASS	Test data please refer to Appendix G
AC Power Line Conducted Emission	FCC 15.207	N/A	Not applicable. The EUT is powered by DC.
Antenna Requirement	FCC 15.203	PASS	---
Note: The radiation measurement is pre tested under X, Y, and Z axis positioning to find the worst placement for final testing.			

3.4 Test Facility

Tset Location : FCC Designation Number: CN1321

4 TEST ITEMS OF LIMIT/SETUP/PROCEDURE


4.1 Emissions in restricted frequency bands	VERDICT: PASS
--	----------------------

4.1.1 Limit			
Standard		FCC Part 15 Subpart C Paragraph 15.205; 15.209.	
Restricted Bands of operation for FCC			
Frequency (MHz)	Frequency (MHz)	Frequency (MHz)	Frequency (GHz)
0.090 – 0.110	16.42 – 16.423	399.9 – 410	4.5 – 5.15
0.495 – 0.505	16.69475 –16.69525	608 – 614	5.35 – 5.46
2.1735 – 2.1905	16.80425 – 16.80475	960 – 1240	7.25 – 7.75
4.125 – 4.128	25.5 – 25.67	1300 – 1427	8.025 – 8.5
4.17725 – 4.17775	37.5 – 38.25	1435 – 1626.5	9.0 – 9.2
4.20725 – 4.20775	73 – 74.6	1645.5 – 1646.5	9.3 – 9.5
6.215 – 6.218	74.8 – 75.2	1660 – 1710	10.6 – 12.7
6.26775 – 6.26825	108 – 121.94	1718.8 – 1722.2	13.25 – 13.4
6.31175 – 6.31225	123 – 138	2200 – 2300	14.47 – 14.5
8.291 – 8.294	149.9 – 150.05	2310 – 2390	15.35 – 16.2
8.362 – 8.366	156.52475 – 156.52525	2483.5 – 2500	17.7 – 21.4
8.37625 – 8.38675	156.7 – 156.9	2690 – 2900	22.01 – 23.12
8.81425 – 8.81475	162.0125 – 167.17	3260 – 3267	23.6 – 24.0
12.29 – 12.293	167.72 – 173.2	3332 – 3339	31.2 – 31.8
12.51975–12.52025	240 – 285	3345.8 – 3358	36.43 – 36.5
12.57675–12.57725	322 – 335.4	3600 – 4400	Above 38.6
13.36 – 13.41	--	--	--
Restricted Band Emissions Limit			
Frequency (MHz)	Field strength (μV/m)	Field strength (dBμV/m)	Measurement distance (m)
0.009 - 0.49	2400/F(kHz)	48.5 – 13.8	300 _(Note 1)
0.49 - 1.705	24000/F(kHz)	33.8 - 23	30 _(Note 1)
1.705 - 30	30	29.5	30 _(Note 1)
30 - 88	100	40	3 _(Note 2)
88 - 216	150	43.5	3 _(Note 2)
216 - 960	200	46	3 _(Note 2)
Above 960	500	54	3 _(Note 2)
Note 1: At frequencies below 30 MHz, measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field. Pending the development of an appropriate measurement procedure for measurements performed below 30 MHz, when performing measurements at a closer distance than specified, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade).			
Note 2: At frequencies at or above 30 MHz, measurements may be performed at a distance other than what is specified provided: measurements are not made in the near field except where it can be shown that near field			


measurements are appropriate due to the characteristics of the device; and it can be demonstrated that the signal levels needed to be measured at the distance employed can be detected by the measurement equipment. Measurements shall not be performed at a distance greater than 30 meters unless it can be further demonstrated that measurements at a distance of 30 meters or less are impractical. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse linear-distance for field strength measurements; inverse-linear-distance-squared for power density measurements).

4.1.2 Test Setup


Below 30MHz Test Setup:



30MHz-1GHz Test Setup:



Above 1GHz Test Setup:




4.1.3 Test Procedure

	References Rule		Chapter	Description
☒	ANSI C63.10		11.12	Emissions in restricted frequency bands
	☒	ANSI C63.10	11.12.1	Radiated emission measurements
	☒	ANSI C63.10	6.3	Radiated spurious emission test
	☒	ANSI C63.10	6.4	Radiated emissions from unlicensed wireless devices below 30 MHz
	☒	ANSI C63.10	6.5	Radiated emissions from unlicensed wireless devices in the frequency range of 30 MHz to 1000 MHz
	☒	ANSI C63.10	6.6	Radiated emissions from unlicensed wireless devices above 1 GHz
	☐	ANSI C63.10	11.12.2	Antenna-port conducted measurements
	☐	ANSI C63.10	11.12.2.3	Quasi-peak measurement procedure
	☐	ANSI C63.10	11.12.2.4	Peak power measurement procedure
	☐	ANSI C63.10	11.12.2.5	Average power measurement procedures
	☐	ANSI C63.10	11.12.2.5.1	Trace averaging with continuous EUT transmission at full power
	☐	ANSI C63.10	11.12.2.5.2	Trace averaging across ON and OFF times of the EUT transmissions followed by duty cycle correction
	☐	ANSI C63.10	11.12.2.5.3	Reduced VBW averaging across ON and OFF times of the EUT transmissions with max hold

4.2 Emissions in non-restricted frequency band	VERDICT: PASS
---	----------------------


4.2.1 Limit	
Standard	FCC Part 15 Subpart C Paragraph 15.247(d).
RF Output power (Detection methods)	Limit(dB)
RF Output power(Average detector)	30dBc(Note1)
RF Output power(PK detector)	20dBc(Note2)
Note 1: If maximum conducted (average) output power was used to demonstrate compliance as described in 9.2, then the peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 30 dBc). Note 2: If the maximum peak conducted output power procedure was used, then the peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 20 dBc).	

4.2.2 Test Setup
 The diagram illustrates the test setup. On the left, a 'Test system' is shown, which includes a spectrum analyzer and other electronic equipment. On the right, a 'Temperature and chamber' is depicted, containing the Equipment Under Test (EUT). Both the test system and the temperature chamber are placed on a 'Ground Reference Plane', which is indicated by a horizontal line with arrows at both ends. A cable connects the test system to the temperature chamber.

4.2.3 Test Procedure			
References Rule		Chapter	Description
☒	ANSI C63.10	11.11	Emissions in non-restricted frequency bands
	☒ ANSI C63.10	11.11.1	General
	☒ ANSI C63.10	11.11.2	Reference level measurement
	☒ ANSI C63.10	11.11.3	Emission level measurement

4.3 Duty cycle	VERDICT: PASS
----------------	---------------

4.3.1 Limit
N/A

4.3.2 Test Setup


4.3.3 Test Procedure			
References Rule		Chapter	Description
☒	ANSI C63.10	11.6	Duty cycle (D), transmission duration (T), and maximum power control level

4.4 Radiated Emission Band Edge

VERDICT: PASS


4.4.1 Limit

Standard		FCC Part 15 Subpart C Paragraph 15.247(d) , 15.205, 15.209		
Frequency bands (MHz)	Detector	Limit (dBμV/m)	RBW (MHz)	Distance (m)
2310-2390 2483.5-2500	PK	74	1	3
	AV	54	1	3

Note: The field strength of emissions appearing within these frequency bands shall not exceed the limits.

4.4.2 Test Setup


Above 1GHz Test Setup:



4.4.3 Test Procedure			
	References Rule	Chapter	Description
☒	ANSI C63.10	6.10	Band-edge testing
	☒ ANSI C63.10	6.10.5	Restricted-band band-edge measurements
	☐ ANSI C63.10	6.10.6	Marker-delta method
☒	ANSI C63.10	11.12	Emissions in restricted frequency bands
	☒ ANSI C63.10	11.12.1	Radiated emission measurements
	☒ ANSI C63.10	6.3	Radiated spurious emission test
☐	ANSI C63.10	6.4	Radiated emissions from unlicensed wireless devices below 30 MHz
☐	ANSI C63.10	6.5	Radiated emissions from unlicensed wireless devices in the frequency range of 30 MHz to 1000 MHz
☒	ANSI C63.10	6.6	Radiated emissions from unlicensed wireless devices above 1 GHz

4.5 DTS Bandwidth	VERDICT: PASS
--------------------------	----------------------

4.5.1 Limit	
Standard	FCC Part 15 Subpart C Paragraph 15.247 (a)(2)
Systems using digital modulation techniques operate in the 2400-2483.5 MHz. The minimum 6 dB bandwidth shall be at least 500 kHz	
Standard	ANSI C63.10 Paragraph 6.7
The occupied bandwidth or the “99% emission bandwidth” is defined as the frequency range between two points, one above and the other below the carrier frequency, within which 99% of the total transmitted power of the fundamental transmitted emission is contained. The occupied bandwidth shall be reported for all equipment in addition to the specified bandwidth required in the applicable RSSs. The occupied bandwidth should be within the required frequency range.	

4.5.2 Test Setup	
 The diagram illustrates the test setup. On the left, a 'Test system' is shown with a spectrum analyzer display. On the right, a 'Temperature and chamber' is shown with an 'EUT' (Equipment Under Test) inside. A 'Ground Reference Plane' is indicated at the base of the setup with arrows pointing outwards.	


4.5.3 Test Procedure			
	Reference Rule	Chapter	Description
☒	ANSI C63.10	11.8	DTS bandwidth
☐	ANSI C63.10	11.8.1	Option 1
☒	ANSI C63.10	11.8.2	Option 2
☒	ANSI C63.10	6.9	Occupied bandwidth
☐	ANSI C63.10	6.9.2	relative measurement procedure
☒	ANSI C63.10	6.9.3	power bandwidth (99%) measurement procedure

4.6 Fundamental emission output power VERDICT: PASS

4.6.1 Limit

Standard		FCC Part 15 Subpart C Paragraph 15.247 (b)(3)	
☐	GTX <6dBi		Pout≤30dBm
☒	GTX >6dBi		
	☒	Non-Fix point-point	Pout≤30-(GTX -6)
	☐	Fix point-point	Pout≤30-[(GTX-6)]/3
	☐	Point-to-multipoint	Pout≤30-(GTX-6)
	☐	Overlap Beams	Pout≤30-[(GTX-6)]/3
	☐	Avgregate power transmitted simultaneously on all beams	Pout≤30-[(GTX-6)]/3
	☐	single directional beam	Pout≤30-[(GTX-6)]/3+8dB
Note 1 : GTX directional gain of transmitting antennas.			
Note 2 : Pout is maximum conducted output power .			

4.6.2 Test Setup




4.6.3 Test Procedure				
	References Rule		Chapter	Description
☒	ANSI C63.10		11.9	Fundamental emission output power
	☒	ANSI C63.10		Maximum peak conducted output power
	☐	☐	ANSI C63.10	11.9.1.1 RBW ≥ DTS bandwidth
		☐	ANSI C63.10	11.9.1.2 Integrated band power method
		☒	ANSI C63.10	11.9.1.3 PKPM1 Peak power meter method
	☒	ANSI C63.10		Maximum conducted (average) output power
	☐	☐	ANSI C63.10	11.9.2.2 Measurement using a spectrum analyzer (SA)
		☐	ANSI C63.10	11.9.2.2.2 Method AVGSA-1(Duty cycle≥98%)
		☐	ANSI C63.10	11.9.2.2.3 Method AVGSA-1A(Duty cycle≥98%)
		☐	ANSI C63.10	11.9.2.2.4 Method AVGSA-2(Duty cycle≤98%)
		☐	ANSI C63.10	11.9.2.2.5 Method AVGSA-2A(Duty cycle≤98%)
		☐	ANSI C63.10	11.9.2.2.4 Method AVGSA-3
		☐	ANSI C63.10	11.9.2.2.5 Method AVGSA-3A
		☒	ANSI C63.10	11.9.2.3 Measurement using a power meter (PM)
		☒	ANSI C63.10	11.9.2.3.1 Method AVGPM
		☐	ANSI C63.10	11.9.2.3.2 Method AVGPM-G

Directional Gain Calculations for In-Band test method

	References Rule	Chapter	Description
☐	KDB 662911	F2)a)	Basic methodology
	☐ KDB 662911	F2)a) (i)	transmit signals are correlated
	☐ KDB 662911	F2)a) (ii)	transmit signals are uncorrelated
☐	KDB 662911	F2)b)	Sectorized antenna systems.
☐	KDB 662911	F2)c)	Cross-polarized antennas
	☐ ANSI C63.10	F2)c) (i)	Cross-polarized antennas
	☐ ANSI C63.10	F2)c) (ii)	Multiple antennas
☐	KDB 662911	F2)e)	Spatial stream
	☐ KDB 662911	F2)e) (i)	Antennas have the same gain
	☐ KDB 662911	F2)e) (ii)	Antenna have the different gain with one spatial stream
	☐ KDB 662911	F2)e) (iii)	Antenna have the different gain with more than one spatial stream
☒	KDB 662911	F2)f)	Cyclic Delay Diversity (CDD)
	☐ KDB 662911	F2)f) (i)	Antennas have the same gain
	☐ KDB 662911	F2)f) (ii)	Antenna have the different gain with one spatial stream
	☒ KDB 662911	F2)f) (iii)	Antenna have the different gain with more than one spatial stream

4.7 Power Density	VERDICT: PASS
--------------------------	----------------------

4.7.1 Limit:	
Standard	FCC Part 15 Subpart C Paragraph 15.247 (e)
Power Spectral Density≤8dBm/3kHz	

4.7.2 Test Setup
 The diagram illustrates the test setup. On the left, a 'Test system' is shown, which includes a spectrum analyzer displaying a peak. This system is connected via a cable to a 'Temperature and chamber' on the right. The chamber has a door labeled 'EUT' (Equipment Under Test). Below both units, a horizontal line with arrows at both ends is labeled 'Ground Reference Plane'.


4.7.3 Test Procedure				
	References Rule		Chapter	Description
☒	ANSI C63.10		11.10	Maximum power spectral density level in the fundamental emission
	☒	ANSI C63.10	11.10.2	Method PKPSD (peak PSD)
	☐	ANSI C63.10	11.10.3	Method AVGPSD-1(Duty cycle≥98%)
	☐	ANSI C63.10	11.10.4	Method AVGPSD-1A(Duty cycle≥98%)
	☐	ANSI C63.10	11.10.5	Method AVGPSD-2(Duty cycle<98%)
	☐	ANSI C63.10	11.10.6	Method AVGPSD-2A(Duty cycle<98%)
	☐	ANSI C63.10	11.10.7	Method AVGPSD-3
	☐	ANSI C63.10	11.10.8	Method AVGPSD-3A

Directional Gain Calculations for In-Band test method				
	References Rule		Chapter	Description
☒	KDB 662911		E)2)	In-Band Power Spectral Density (PSD) Measurements
	☐	KDB 662911	E)2)a)	Measure and sum the spectra across the outputs.
	☐	KDB 662911	E)2)b)	Measure and sum spectral maxima across the outputs.
	☒	KDB 662911	E)2)c)	Measure and add 10 log(NANT) dB, where NANT is the number of outputs.
☐	KDB 662911		F2)a)	Basic methodology
	☐	KDB 662911	F2)a) (i)	transmit signals are correlated
	☐	KDB 662911	F2)a) (ii)	transmit signals are uncorrelated
☐	KDB 662911		F2)b)	Sectorized antenna systems.
☐	KDB 662911		F2)c)	Cross-polarized antennas
	☐	ANSI C63.10	F2)c) (i)	Cross-polarized antennas
	☐	ANSI C63.10	F2)c) (ii)	Multiple antennas
☐	KDB 662911		F2)e)	Spatial stream
	☐	KDB 662911	F2)e) (i)	Antennas have the same gain
	☐	KDB 662911	F2)e) (ii)	Antenna have the different gain with one spatial stream
	☐	KDB 662911	F2)e) (iii)	Antenna have the different gain with more than one spatial stream
☒	KDB 662911		F2)f)	Cyclic Delay Diversity (CDD)
	☐	KDB 662911	F2)f) (i)	Antennas have the same gain
	☒	KDB 662911	F2)f) (ii)	Antenna have the different gain with one spatial stream
	☐	KDB 662911	F2)f) (iii)	Antenna have the different gain with more than one spatial stream

4.8 AC Power Line Conducted Emission	VERDICT: N/A
---	---------------------

4.8.1 Limit		
Standard	FCC Part 15 Subpart C Paragraph 15.207 ;	
Frequency range [MHz]	Limit: QP [dB(μV) ¹⁾]	Limit: AV [dB(μV) ¹⁾]
0,15 - 0,50	66 – 56 ²⁾	56 - 46 ²⁾
0,50 - 5,0	56	46
5,0 - 30	60	50

¹⁾ At the transition frequency, the lower limit applies.
²⁾ The limit decreases linearly with the logarithm of the frequency.
NOTE 1: The exclusion band for transmitters shall be considered for transmitters operating at frequencies below 30 MHz.
NOTE 2: Where the AC output port is directly connected (or via a circuit breaker) to the AC power input port of the EUT the AC power output port need not to be tested.



4.8.3 Test Procedure			
	References Rule	Chapter	Item
☐	ANSI C63.10	6.2	Standard test method for ac power-line conducted emissions from unlicensed wireless devices

4.9 Antenna Requirement**VERDICT: PASS****4.9.1 Limit:**

Standard	FCC Part 15 Subpart C Paragraph 15.203
----------	--

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

4.9.2 Antenna Connector Construction:

- | | |
|-------------------------------------|--|
| ☒ | The use of a permanently attached antenna |
| ☒ | The antenna use of a unique coupling to the intentional radiator |
| ☐ | The use of a nonstandard antenna jack or electrical connector |

Please refer to the attached document "Internal Photograph" to show the antenna connector.

5 TEST SETUP PHOTO AND EUT PHOTO


Remark: The test setup photo and EUT Photo please see appendix.

6 TEST RESULT


Appendix A: DTS Bandwidth

Mode	Frequency (MHz)	ANT	6dB Bandwidth (MHz)		Verdict
			Result	Limit	
802.11b	2412	1	9.139	≥ 0.5	Pass
	2437	1	9.116	≥ 0.5	Pass
	2462	1	9.121	≥ 0.5	Pass
802.11g	2412	1	16.028	≥ 0.5	Pass
	2437	1	16.033	≥ 0.5	Pass
	2462	1	16.046	≥ 0.5	Pass
802.11n (HT20)	2412	1	17.174	≥ 0.5	Pass
	2437	1	17.253	≥ 0.5	Pass
	2462	1	17.201	≥ 0.5	Pass
802.11n (HT40)	2422	1	35.429	≥ 0.5	Pass
	2437	1	34.802	≥ 0.5	Pass
	2452	1	35.518	≥ 0.5	Pass


802.11b_LCH_2412MHz_Ant1_NTNV




802.11b_MCH_2437MHz_Ant1_NTNV




802.11b_HCH_2462MHz_Ant1_NTNV




802.11g_LCH_2412MHz_Ant1_NTNV




802.11g_MCH_2437MHz_Ant1_NTNV




802.11g_HCH_2462MHz_Ant1_NTNV




802.11n(HT20)_LCH_2412MHz_Ant1_NTNV




802.11n(HT20)_MCH_2437MHz_Ant1_NTNV




802.11n(HT20)_HCH_2462MHz_Ant1_NTNV




802.11n(HT40)_LCH_2422MHz_Ant1_NTNV



802.11n(HT40)_MCH_2437MHz_Ant1_NTNV



802.11n(HT40)_HCH_2452MHz_Ant1_NTNV



Appendix B: Maximum conducted output power

Mode	Channel	Test Frequency (MHz)	Conducted Power(dBm)			Limit(dBm)			Result
			WIFI0	WIFI1	WIFI0+1	WIFI0	WIFI1	WIFI0+1	
802.11b	1	2412	15.61	15.38	N/A	≤29.96	≤30	N/A	Pass
	6	2437	15.89	15.70	N/A	≤29.96	≤30	N/A	Pass
	11	2462	15.54	15.47	N/A	≤29.96	≤30	N/A	Pass
802.11g	1	2412	15.57	15.78	N/A	≤29.96	≤30	N/A	Pass
	6	2437	15.54	15.80	N/A	≤29.96	≤30	N/A	Pass
	11	2462	15.61	15.82	N/A	≤29.96	≤30	N/A	Pass
802.11n20	1	2412	12.20	12.29	15.26	≤29.96	≤30	≤29.96	Pass
	6	2437	12.27	12.53	15.41	≤29.96	≤30	≤29.96	Pass
	11	2462	12.43	12.57	15.51	≤29.96	≤30	≤29.96	Pass
802.1140	3	2422	10.41	11.43	13.96	≤29.96	≤30	≤29.96	Pass
	6	2437	10.47	11.47	14.01	≤29.96	≤30	≤29.96	Pass
	9	2452	10.48	11.37	13.96	≤29.96	≤30	≤29.96	Pass
Note: WIFI0 and WIFI0+1 Limit = 30dBm - (6.04dBi-6.0dBi)									

Appendix C: Maximum power spectral density


Mode	Channel	Test Frequency (MHz)	PSD(dBm/3kHz)		Limit (dBm/3kHz)		Result
			SISO	MIMO	SISO	MIMO	
802.11b	1	2412	4.56	N/A	≤7.96	≤6.74	Pass
	6	2437	4.81	N/A	≤7.96	≤6.74	Pass
	11	2462	4.73	N/A	≤7.96	≤6.74	Pass
802.11g	1	2412	-2.25	N/A	≤7.96	≤6.74	Pass
	6	2437	-2.86	N/A	≤7.96	≤6.74	Pass
	11	2462	-2.85	N/A	≤7.96	≤6.74	Pass
802.11n20	1	2412	-7.39	-4.38	≤7.96	≤6.74	Pass
	6	2437	-6.60	-3.59	≤7.96	≤6.74	Pass
	11	2462	-6.36	-3.35	≤7.96	≤6.74	Pass
802.1140	3	2422	-10.54	-7.53	≤7.96	≤6.74	Pass
	6	2437	-10.34	-7.33	≤7.96	≤6.74	Pass
	9	2452	-10.44	-7.43	≤7.96	≤6.74	Pass

Note1: SISO Limit = 8 dBm/3kHz - (6.04dBi-6.0dBi), MIMO Limit = 8 dBm/3kHz - (7.26dBi-6.0dBi)


Note2: For SISO mode, we evaluated WIFI0 and WIFI1. Since the RF output power of WIFI0 and WIFI1 is approximately the same, only the test data for WIFI0 is shown in this report.

Note3: CDD PSD = SISO PSD + 10*Log(N), N = Antenna number.


802.11b_LCH_2412MHz_Ant1 _NTNV




802.11b_MCH_2437MHz_Ant1_NTNV




802.11b_HCH_2462MHz_Ant1_NTNV




802.11g_LCH_2412MHz_Ant1_NTNV




802.11g_MCH_2437MHz_Ant1_NTNV




802.11g_HCH_2462MHz_Ant1_NTNV




802.11n(HT20)_LCH_2412MHz_Ant1_NTNV




802.11n(HT20)_MCH_2437MHz_Ant1_NTNV




802.11n(HT20)_HCH_2462MHz_Ant1_NTNV




802.11n(HT40)_LCH_2422MHz_Ant1_NTNV



802.11n(HT40)_MCH_2437MHz_Ant1_NTNV




802.11n(HT40)_HCH_2452MHz_Ant1_NTNV




Appendix D: Band edge measurements

Transmit at 2412MHz by 802.11b with Ant0




Data List									
NO	Frequency [MHz]	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Det	Pol	Verdict
1	2385.15	41.12	46.22	5.10	74.00	27.78	PK	Horizo	PASS
2	2390.00	38.58	43.72	5.14	74.00	30.28	PK	Horizo	PASS

Transmit at 2412MHz by 802.11b with Ant0




Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2386.27	30.66	35.77	5.11	54.00	18.23	AV	Horizo	PASS
2	2390.00	28.27	33.41	5.14	54.00	20.59	AV	Horizo	PASS

Transmit at 2412MHz by 802.11b with Ant0




Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2384.93	40.35	45.45	5.10	74.00	28.55	PK	Vertic	PASS
2	2390.00	38.26	43.40	5.14	74.00	30.60	PK	Vertic	PASS

Transmit at 2412MHz by 802.11b with Ant0




Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2386.16	29.69	34.80	5.11	54.00	19.20	AV	Vertic	PASS
2	2390.00	28.12	33.26	5.14	54.00	20.74	AV	Vertic	PASS

Transmit at 2462MHz by 802.11b with Ant0




Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2483.50	37.99	43.50	5.51	74.00	30.50	PK	Horizo	PASS
2	2488.96	41.02	46.56	5.54	74.00	27.44	PK	Horizo	PASS

Transmit at 2462MHz by 802.11b with Ant0




Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2483.50	28.04	33.55	5.51	54.00	20.45	AV	Horizo	PASS
2	2488.72	31.28	36.81	5.53	54.00	17.19	AV	Horizo	PASS

Transmit at 2462MHz by 802.11b with Ant0




Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2483.50	38.20	43.71	5.51	74.00	30.29	PK	Vertic	PASS
2	2491.84	41.33	46.88	5.55	74.00	27.12	PK	Vertic	PASS

Transmit at 2462MHz by 802.11b with Ant0




Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2483.50	28.02	33.53	5.51	54.00	20.47	AV	Vertic	PASS
2	2488.82	30.21	35.75	5.54	54.00	18.25	AV	Vertic	PASS

Transmit at 2412MHz by 802.11g with Ant0




Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2383.25	41.92	47.01	5.09	74.00	26.99	PK	Horizo	PASS
2	2390.00	41.52	46.66	5.14	74.00	27.34	PK	Horizo	PASS

Transmit at 2412MHz by 802.11g with Ant0




Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2389.97	30.76	35.90	5.14	54.00	18.10	AV	Horizo	PASS
2	2390.00	30.48	35.62	5.14	54.00	18.38	AV	Horizo	PASS

Transmit at 2412MHz by 802.11g with Ant0




Data List									
NO	Frequency [MHz]	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Det	Pol	Verdict
1	2388.85	41.52	46.65	5.13	74.00	27.35	PK	Vertic	PASS
2	2390.00	40.33	45.47	5.14	74.00	28.53	PK	Vertic	PASS

Transmit at 2412MHz by 802.11g with Ant0




Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2389.07	29.95	35.08	5.13	54.00	18.92	AV	Vertic	PASS
2	2390.00	29.88	35.02	5.14	54.00	18.98	AV	Vertic	PASS

Transmit at 2462MHz by 802.11g with Ant0




Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2483.50	48.23	53.74	5.51	74.00	20.26	PK	Horizo	PASS
2	2483.54	48.23	53.74	5.51	74.00	20.26	PK	Horizo	PASS

Transmit at 2462MHz by 802.11g with Ant0




Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2483.50	31.34	36.85	5.51	54.00	17.15	AV	Horizo	PASS
2	2483.92	31.51	37.02	5.51	54.00	16.98	AV	Horizo	PASS

Transmit at 2462MHz by 802.11g with Ant0




Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2483.50	42.01	47.52	5.51	74.00	26.48	PK	Vertic	PASS
2	2483.73	45.24	50.75	5.51	74.00	23.25	PK	Vertic	PASS

Transmit at 2462MHz by 802.11g with Ant0




Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2483.50	31.19	36.70	5.51	54.00	17.30	AV	Vertic	PASS
2	2483.73	31.35	36.86	5.51	54.00	17.14	AV	Vertic	PASS

Transmit at 2412MHz by 802.11n(20MHz) with Ant0+1




Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2389.30	40.35	45.48	5.13	74.00	28.52	PK	Horizo	PASS
2	2390.00	39.44	44.58	5.14	74.00	29.42	PK	Horizo	PASS

Transmit at 2412MHz by 802.11n(20MHz) with Ant0+1




Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2388.96	29.15	34.28	5.13	54.00	19.72	AV	Horizo	PASS
2	2390.00	28.33	33.47	5.14	54.00	20.53	AV	Horizo	PASS

Transmit at 2412MHz by 802.11n(20MHz) with Ant0+1




Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2376.86	39.56	44.60	5.04	74.00	29.40	PK	Vertic	PASS
2	2390.00	38.30	43.44	5.14	74.00	30.56	PK	Vertic	PASS

Transmit at 2412MHz by 802.11n(20MHz) with Ant0+1




Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2388.74	28.28	33.41	5.13	54.00	20.59	AV	Vertic	PASS
2	2390.00	27.55	32.69	5.14	54.00	21.31	AV	Vertic	PASS

Transmit at 2462MHz by 802.11n(20MHz) with Ant0+1




Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2483.50	39.31	44.82	5.51	74.00	29.18	PK	Horizo	PASS
2	2484.54	40.16	45.69	5.53	74.00	28.31	PK	Horizo	PASS

Transmit at 2462MHz by 802.11n(20MHz) with Ant0+1




Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2483.50	29.82	35.33	5.51	54.00	18.67	AV	Horizo	PASS
2	2484.16	30.44	35.96	5.52	54.00	18.04	AV	Horizo	PASS

Transmit at 2462MHz by 802.11n(20MHz) with Ant0+1




Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2483.50	39.85	45.36	5.51	74.00	28.64	PK	Vertic	PASS
2	2487.23	40.14	45.67	5.53	74.00	28.33	PK	Vertic	PASS

Transmit at 2462MHz by 802.11n(20MHz) with Ant0+1




Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2483.50	29.01	34.52	5.51	54.00	19.48	AV	Vertic	PASS
2	2483.54	29.01	34.52	5.51	54.00	19.48	AV	Vertic	PASS

Transmit at 2422MHz by 802.11n(40MHz) with Ant0+1




Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2389.86	41.52	46.66	5.14	74.00	27.34	PK	Horizo	PASS
2	2390.00	40.20	45.34	5.14	74.00	28.66	PK	Horizo	PASS

Transmit at 2422MHz by 802.11n(40MHz) with Ant0+1




Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2389.74	31.28	36.42	5.14	54.00	17.58	AV	Horizo	PASS
2	2390.00	30.50	35.64	5.14	54.00	18.36	AV	Horizo	PASS

Transmit at 2422MHz by 802.11n(40MHz) with Ant0+1




Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2386.16	40.67	45.78	5.11	74.00	28.22	PK	Vertic	PASS
2	2390.00	39.36	44.50	5.14	74.00	29.50	PK	Vertic	PASS

Transmit at 2422MHz by 802.11n(40MHz) with Ant0+1




Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2385.94	29.75	34.86	5.11	54.00	19.14	AV	Vertic	PASS
2	2390.00	28.99	34.13	5.14	54.00	19.87	AV	Vertic	PASS

Transmit at 2452MHz by 802.11n(40MHz) with Ant0+1




Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2483.50	38.73	44.24	5.51	74.00	29.76	PK	Horizo	PASS
2	2484.63	41.48	47.01	5.53	74.00	26.99	PK	Horizo	PASS

Transmit at 2452MHz by 802.11n(40MHz) with Ant0+1




Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2483.50	29.79	35.30	5.51	54.00	18.70	AV	Horizo	PASS
2	2484.63	31.33	36.86	5.53	54.00	17.14	AV	Horizo	PASS

Transmit at 2452MHz by 802.11n(40MHz) with Ant0+1



Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2483.50	38.59	44.10	5.51	74.00	29.90	PK	Vertic	PASS
2	2485.79	40.71	46.24	5.53	74.00	27.76	PK	Vertic	PASS

Transmit at 2452MHz by 802.11n(40MHz) with Ant0+1



Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	2483.50	28.82	34.33	5.51	54.00	19.67	AV	Vertic	PASS
2	2484.29	30.04	35.56	5.52	54.00	18.44	AV	Vertic	PASS

Note:

1.Level=Reading+Factor


2. Margin=Limit-Level

Appendix E: Conducted Spurious Emission


Test Result for Reference level:

Mode	Frequency (MHz)	ANT	Level of Reference (dBm)
802.11b	2412	1	5.11
	2437	1	5.64
	2462	1	4.82
802.11g	2412	1	2.18
	2437	1	-2.35
	2462	1	-2.22
802.11n(HT20)	2412	1	-2.43
	2437	1	-2.18
	2462	1	-2.20
802.11n(HT40)	2422	1	-5.26
	2437	1	-6.07
	2452	1	-6.98


802.11b_LCH_2412MHz_Ant1_NTNV




802.11b MCH 2437MHz Ant1 NTNV




802.11b_HCH_2462MHz_Ant1_NTNV




802.11g_LCH_2412MHz_Ant1_NTNV




802.11g_MCH_2437MHz_Ant1_NTNV




802.11g_HCH_2462MHz_Ant1_NTNV




802.11n(HT20)_LCH_2412MHz_Ant1_NTNV




802.11n(HT20)_MCH_2437MHz_Ant1_NTNV




802.11n(HT20)_HCH_2462MHz_Ant1_NTNV




802.11n(HT40)_LCH_2422MHz_Ant1_NTNV



802.11n(HT40)_MCH_2437MHz_Ant1_NTNV




802.11n(HT40)_HCH_2452MHz_Ant1_NTNV




Conducted Spurious Emission:

Mode	Frequency (MHz)	ANT	Level of Reference (dBm)	Limit (dBm)	Verdict
802.11b	2412	1	5.11	-14.89	Pass
	2437	1	5.64	-14.36	Pass
	2462	1	4.82	-15.18	Pass
802.11g	2412	1	2.18	-17.82	Pass
	2437	1	-2.35	-22.35	Pass
	2462	1	-2.22	-22.22	Pass
802.11n (HT20)	2412	1	-2.43	-22.43	Pass
	2437	1	-2.18	-22.18	Pass
	2462	1	-2.20	-22.20	Pass
802.11n (HT40)	2422	1	-5.26	-25.26	Pass
	2437	1	-6.07	-26.07	Pass
	2452	1	-6.98	-26.98	Pass


802.11b_LCH_2412MHz_Ant1_NTNV




802.11b_LCH_2412MHz_Ant1_NTNV




802.11b_MCH_2437MHz_Ant1_NTNV




802.11b_HCH_2462MHz_Ant1_NTNV




802.11b_HCH_2462MHz_Ant1_NTNV




802.11g_LCH_2412MHz_Ant1_NTNV




802.11g_LCH_2412MHz_Ant1_NTNV




802.11g_MCH_2437MHz_Ant1_NTNV




802.11g_HCH_2462MHz_Ant1_NTNV




802.11g_HCH_2462MHz_Ant1_NTNV




802.11n(HT20)_LCH_2412MHz_Ant1_NTNV




802.11n(HT20)_LCH_2412MHz_Ant1_NTNV




802.11n(HT20)_MCH_2437MHz_Ant1_NTNV




802.11n(HT20)_HCH_2462MHz_Ant1_NTNV




802.11n(HT20)_HCH_2462MHz_Ant1_NTNV




802.11n(HT40)_LCH_2422MHz_Ant1_NTNV




802.11n(HT40)_LCH_2422MHz_Ant1_NTNV




802.11n(HT40)_MCH_2437MHz_Ant1_NTNV




802.11n(HT40)_HCH_2452MHz_Ant1_NTNV




802.11n(HT40)_HCH_2452MHz_Ant1_NTNV




Appendix F: Duty Cycle




802.11g_LCH_2412MHz_Ant1_NTNV




802.11n(HT20)_LCH_2412MHz_Ant1_NTNV






Appendix G: Emissions in Restricted Bands

Transmit at 2412MHz by 802.11b with Ant0




Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	4824.00	54.33	49.33	-5.00	74.00	24.67	PK	Horizo	PASS
2	4824.50	52.57	47.57	-5.00	54.00	6.43	AV	Horizo	PASS
3	7235.50	37.11	40.22	3.11	54.00	13.78	AV	Horizo	PASS
4	7236.00	40.69	43.80	3.11	74.00	30.20	PK	Horizo	PASS
5	9648.00	25.91	32.93	7.02	54.00	21.07	AV	Horizo	PASS
6	9648.00	33.26	40.28	7.02	74.00	33.72	PK	Horizo	PASS

Transmit at 2412MHz by 802.11b with Ant0



Data List									
NO	Freque ncy [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdi ct
1	4824.00	50.30	45.30	-5.00	74.00	28.70	PK	Vertic	PASS
2	4824.50	48.14	43.14	-5.00	54.00	10.86	AV	Vertic	PASS
3	7236.00	33.37	36.48	3.11	54.00	17.52	AV	Vertic	PASS
4	7236.00	39.02	42.13	3.11	74.00	31.87	PK	Vertic	PASS
5	9648.00	26.66	33.68	7.02	54.00	20.32	AV	Vertic	PASS
6	9648.00	33.88	40.90	7.02	74.00	33.10	PK	Vertic	PASS


Transmit at 2437MHz by 802.11b with Ant0



Data List									
NO	Freque y [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdi ct
1	4874.00	55.84	50.76	-5.08	74.00	23.24	PK	Horizo	PASS
2	4874.50	54.77	49.69	-5.08	54.00	4.31	AV	Horizo	PASS
3	7311.00	36.96	40.07	3.11	54.00	13.93	AV	Horizo	PASS
4	7311.00	42.81	45.92	3.11	74.00	28.08	PK	Horizo	PASS
5	9748.00	25.51	32.67	7.16	54.00	21.33	AV	Horizo	PASS
6	9748.00	32.93	40.09	7.16	74.00	33.91	PK	Horizo	PASS

Transmit at 2437MHz by 802.11b with Ant0


Test Graph



Data List

NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	4874.00	52.97	47.89	-5.08	74.00	26.11	PK	Vertic	PASS
2	4874.50	51.40	46.32	-5.08	54.00	7.68	AV	Vertic	PASS
3	7311.00	41.04	44.15	3.11	74.00	29.85	PK	Vertic	PASS
4	7312.50	37.68	40.80	3.12	54.00	13.20	AV	Vertic	PASS
5	9748.00	35.05	42.21	7.16	74.00	31.79	PK	Vertic	PASS
6	9748.00	24.98	32.14	7.16	54.00	21.86	AV	Vertic	PASS


Transmit at 2462MHz by 802.11b with Ant0



Data List									
NO	Freque ncy [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdi ct
1	4924.00	56.42	51.36	-5.06	74.00	22.64	PK	Horizo	PASS
2	4924.50	54.72	49.66	-5.06	54.00	4.34	AV	Horizo	PASS
3	7386.00	42.22	45.45	3.23	74.00	28.55	PK	Horizo	PASS
4	7387.50	38.44	41.67	3.23	54.00	12.33	AV	Horizo	PASS
5	9848.00	33.50	40.09	6.59	74.00	33.91	PK	Horizo	PASS
6	9848.00	25.00	31.59	6.59	54.00	22.41	AV	Horizo	PASS

Transmit at 2462MHz by 802.11b with Ant0


Test Graph



Data List


NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	4924.00	51.69	46.63	-5.06	74.00	27.37	PK	Vertic	PASS
2	4924.50	50.30	45.24	-5.06	54.00	8.76	AV	Vertic	PASS
3	7386.00	37.03	40.26	3.23	54.00	13.74	AV	Vertic	PASS
4	7388.00	42.31	45.54	3.23	74.00	28.46	PK	Vertic	PASS
5	9848.00	33.86	40.45	6.59	74.00	33.55	PK	Vertic	PASS
6	9848.00	25.85	32.44	6.59	54.00	21.56	AV	Vertic	PASS

Transmit at 2412MHz by 802.11g with Ant0




Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	4824.00	42.49	37.49	-5.00	74.00	36.51	PK	Horizo	PASS
2	4824.00	34.92	29.92	-5.00	54.00	24.08	AV	Horizo	PASS
3	7236.00	28.14	31.25	3.11	54.00	22.75	AV	Horizo	PASS
4	7236.00	36.12	39.23	3.11	74.00	34.77	PK	Horizo	PASS
5	9648.00	33.99	41.01	7.02	74.00	32.99	PK	Horizo	PASS
6	9648.00	25.73	32.75	7.02	54.00	21.25	AV	Horizo	PASS

Transmit at 2412MHz by 802.11g with Ant0



Data List									
NO	Freque ncy [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdi ct
1	4824.00	40.24	35.24	-5.00	74.00	38.76	PK	Vertic	PASS
2	4824.00	32.44	27.44	-5.00	54.00	26.56	AV	Vertic	PASS
3	7236.00	28.50	31.61	3.11	54.00	22.39	AV	Vertic	PASS
4	7236.00	38.39	41.50	3.11	74.00	32.50	PK	Vertic	PASS
5	9648.00	33.12	40.14	7.02	74.00	33.86	PK	Vertic	PASS
6	9648.00	25.37	32.39	7.02	54.00	21.61	AV	Vertic	PASS

Transmit at 2437MHz by 802.11g with Ant0



Data List									
NO	Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Det	Pol	Verdict
1	4874.00	37.67	32.59	-5.08	54.00	21.41	AV	Horizo	PASS
2	4879.00	45.65	40.57	-5.08	74.00	33.43	PK	Horizo	PASS
3	7311.00	36.00	39.11	3.11	74.00	34.89	PK	Horizo	PASS
4	7311.00	28.74	31.85	3.11	54.00	22.15	AV	Horizo	PASS
5	9748.00	32.93	40.09	7.16	74.00	33.91	PK	Horizo	PASS
6	9748.00	24.74	31.90	7.16	54.00	22.10	AV	Horizo	PASS