FCC TEST REPORT

FCC ID: 2AJXE-ASR-M30S

On Behalf of

Asterisk Inc.

AsReader SLIM RFID Reader

Model No.: ASR-M30S

Prepared for	:	Asterisk Inc.
Address	:	2-2-1,Kikawanishi,Yodogawa-ku,Osaka-city,Osaka,532-0013,Japan

Prepared By	:	Shenzhen PSI Testing Co., Ltd.
Address	:	1-2/F., Building 5, Yudafu Industrial Park, No.10, Xingye West Road, Shajing Subdistrict, Bao'an District, Shenzhen, Guangdong, China

Report Number	:	psi2601075-C01-R01
Date of Receipt	:	Aug. 26, 2025
Date of Test	:	Aug.28, 2025-Nov.31, 2025
Date of Report	:	Jan.12, 2026
Version Number	:	V0

TABLE OF CONTENTS

Description	Page
1. Summary Of Standards And Results	**6**
1.1. Description of Standards and Results	6
2. General Information	**7**
2.1. Description of Device (EUT)	7
2.2. Accessories of Device (EUT)	8
2.3. Tested Supporting System Details	8
2.4. Block Diagram of connection between EUT and simulators	8
2.5. Test Mode Description	8
2.6. Software test version and power setting information	9
2.7. Test Conditions	10
2.8. Test Facility	10
2.9. Measurement Uncertainty	10
2.10. Test Equipment List	11
3. Maximum Peak Output Power	**12**
3.1. Limit	12
3.2. Test Procedure	12
3.3. Test Setup	12
3.4. Test Result	12
4. Bandwidth	**13**
4.1. Limit	13
4.2. Test Procedure	13
4.3. Test Result	13
5. Carrier Frequency Separation	**15**
5.1. Limit	15
5.2. Test Procedure	15
5.3. Test Result	15
6. Number Of Hopping Channel	**16**
6.1. Limit	16
6.2. Test Procedure	16
6.3. Test Result	16
7. Dwell Time	**17**
7.1. Test limit	17
7.2. Test Procedure	17
7.3. Test Result	17
8. Out-of-band Emissions	**18**
8.1. Test Limits	18
8.2. Test Procedure	18
8.3. Test Setup	18
8.4. Test Results	18
9. Radiated Emissions	**26**
9.1. Limit	26
9.2. Block Diagram of Test setup	29

9.3. Test Procedure 30
9.4. Test Results 30
10. Band Edge Test 36
10.1. Block Diagram of Test Setup 36
10.2. Test Limit 36
10.3. Test Procedure 36
10.4. Test Results 37
11. Power Line Conducted Emissions 38
11.1. Block Diagram of Test Setup 38
11.2. Limit 38
11.3. Test Procedure 38
11.4. Test Results 39
12. Frequency stability 42
12.1. Test limit 42
12.2. Test Procedure 42
12.3. Test Setup 42
12.4. Test Results 42
13. Antenna Requirements 43
13.1. Limit 43
13.2. Result 43
14. Photos of test setup 44
15. Photos of EUT 44

TEST REPORT DECLARATION

Applicant	:	Asterisk Inc.
Address	:	2-2-1, Kikawanishi, Yodogawa-ku, Osaka-city, Osaka, 532-0013, Japan
Manufacturer	:	Asterisk Inc.
Address	:	2-2-1, Kikawanishi, Yodogawa-ku, Osaka-city, Osaka, 532-0013, Japan
EUT Description	:	AsReader SLIM RFID Reader
		(A) Model No. : ASR-M30S
		(B) Trademark : AsReader

Measurement Standard Used:

FCC Rules and Regulations Part 15 Subpart C Section 15.247

ANSI C63.10-2020

Test Result: PASS

The device described above is tested by Shenzhen PSI Testing Co., Ltd. to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The test results are contained in this test report and Shenzhen PSI Testing Co., Ltd. is assumed full responsibility for the accuracy and completeness of test. Also, this report shows that the EUT is technically compliant with the FCC Part15 requirements.

This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Shenzhen PSI Testing Co., Ltd.

Tested by (name + signature).....:	Felix Pang Test Engineer	
Approved by (name + signature).....:	Simple Guan Project Manager	
Date of issue.....:	January 12, 2026	

Revision History

Revision	Issue Date	Revisions	Revised By
V0	January 12, 2026	Initial released Issue	Felix Pang

1. Summary Of Standards And Results

1.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below:

Test Item	Standards Paragraph	Result
Maximum Peak Output Power	FCC Part 15: 15.247(b)(2), ANSI C63.10-2020	P
Bandwidth	FCC Part 15: 15.247(a)(1), ANSI C63.10-2020	P
Carrier Frequency Separation	FCC Part 15: 15.247(a)(1), ANSI C63.10-2020	P
Number Of Hopping Channel	FCC Part 15: 15.247(a)(1), ANSI C63.10-2020	P
Dwell Time	FCC Part 15: 15.247(a)(1), ANSI C63.10-2020	P
Radiated Spurious Emission	FCC Part 15: 15.209, FCC Part 15: 15.247(d), ANSI C63.10-2020	P
Out-of-band Emissions	FCC Part 15: 15.247(d), RSS-Gen(8.9), ANSI C63.10-2020	P
Radiated Band Edge Emission	FCC Part 15: 15.247(d), RSS-Gen(6.13), RSS-247(5.5), ANSI C63.10 :2020	P
Power Line Conducted Emissions	FCC Part 15: 15.207, ANSI C63.10-2020	P
Antenna requirement	FCC Part 15: 15.203, 15.247(b)(4)	P

Note: 1. P is an abbreviation for Pass.

2. F is an abbreviation for Fail.

3. N/A is an abbreviation for Not Applicable.

4. Conclusion determination rules of this report: Unless there are clear provisions on measurement uncertainty in the standard or customer requirements, decision by actual test data without considering measurement uncertainty.

5. Measurement method usage KDB 558074 D01 15.247 Meas Guidance v05r02.

2. General Information

2.1. Description of Device (EUT)

Product Name	:	AsReader SLIM RFID Reader
Model No.	:	ASR-M30S
Diff	:	N/A
Power supply	:	DC 5V From Notebook computer
Radio Technology	:	RF ID
Operation frequency	:	902.750MHz~927.250MHz
Channel No.	:	50 channels
Modulation	:	ASK
Antenna Type	:	PCB Antenna, Maximum Gain is 2.79dBi.
PMN	:	N/A
HVIN	:	N/A
Software version	:	N/A
Hardware version/FVIN	:	N/A
Note	:	Antenna information is provided by applicant. Testing lab is not responsible for the accuracy of the information.

2.2. Accessories of Device (EUT)

Accessories	:	N/A
Manufacturer	:	N/A
Model	:	N/A
Rating	:	N/A

2.3. Tested Supporting System Details

No.	Description	Manufacturer	Model	Serial Number
1	Notebook	DELL	Vostro 3520	N/A
2	N/A	N/A	N/A	N/A

2.4. Block Diagram of connection between EUT and simulators



2.5. Test Mode Description

The test software used to control EUT work in Continuous TX mode, and select test channel, wireless mode

Tested mode, channel, and data rate information		
Mode	Channel	Frequency (MHz)
ASK Carrier Tx Mode	CH1	902.75
	CH26	915.25
	CH50	927.25
ASK hopping on Tx Mode	CH1 to CH50	902.75 to 927.25
ASK hopping off Tx Mode	CH1	902.75
	CH26	915.25
	CH50	927.25

2.6. Software test version and power setting information

Software testing version	ReaderManager.exe		
Mode	The client 's preset testing software is used to control the operation of EUT in continuous transmission mode and select the testing channel, wireless mode:		
Power level setup by client			
Mode	Channel	Frequency (MHz)	Soft Set
ASK	CH1	902.75	TX level is set as defaults
	CH26	915.25	TX level is set as defaults
	CH50	927.25	TX level is set as defaults

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	902.750	18	911.250	35	919.750
02	903.250	19	911.750	36	920.250
03	903.750	20	912.250	37	920.750
04	904.250	21	912.750	38	921.250
05	904.750	22	913.250	39	921.750
06	905.250	23	913.750	40	922.250
07	905.750	24	914.250	41	922.750
08	906.250	25	914.750	42	923.250
09	906.750	26	915.250	43	923.750
10	907.250	27	915.750	44	924.250
11	907.750	28	916.250	45	924.750
12	908.250	29	916.750	46	925.250
13	908.750	30	917.250	47	925.750
14	909.250	31	917.750	48	926.250
15	909.750	32	918.250	49	926.750
16	910.250	33	918.750	50	927.25
17	910.750	34	919.250	/	/

2.7. Test Conditions

Items	Required	Actual
Temperature range:	15-35℃	26℃
Humidity range:	25-75%	54%
Pressure range:	86-106kPa	101kPa

2.8. Test Facility

Shenzhen PSI Testing Co., Ltd.

1-2/F., Building 5, Yudafu Industrial Park, No.10, Xingye West Road, Shajing Subdistrict, Bao'an District, Shenzhen, Guangdong, China

September 13, 2023 File on Federal Communication Commission
Registration Number: 916281

September 21, 2023 Certificated by IC
Registration Number: 31123
CAB identifier: CN0158

2.9. Measurement Uncertainty

(95% confidence levels, k=2)

Item	**Uncertainty**
Uncertainty for Power Line Conducted Emissions Test	2.17dB
Uncertainty for Radiation Emission test in 3m chamber (below 30MHz)	3.5dB
Uncertainty for Radiation Emission test in 3m chamber (30MHz to 1GHz)	2.74dB(Polarize: V)
	2.76dB(Polarize: H)
Uncertainty for Radiation Emission test in 3m chamber (1GHz to 18GHz)	4.29dB(Polarize: V)
	4.82dB(Polarize: H)
Uncertainty for Radiation Emission test in 3m chamber (18GHz to 40GHz)	4.31dB(Polarize: V)
	4.30dB(Polarize: H)
Uncertainty for radio frequency	48.24KHz
Uncertainty for conducted RF Power	0.41dB
Uncertainty for Power Spectral Density	0.39 dB
Occupied-Bandwidth	968Hz
Conducted-Spurious Emission	1.26dB

2.10.Test Equipment List

Item	Equipment	Manufacturer	Model No.	Serial No.	Firmware Version	Last Cal.	Cal. Interval
1.	9*6*6 anechoic chamber	SKET	9*6*6	N/A	/	2025.12.19	3 Year
2.	Test Receiver	Rohde&Schwarz	ESCI 7	101032/003	4.42 SP3	2025.12.18	1 Year
3.	L.I.S.N.#1	Rohde&Schwarz	ENV216	102282	/	2025.12.18	1 Year
4.	L.I.S.N.#2	RFT	NNB111	13835240	/	2025.12.18	1 Year
5.	Loop Antenna	Schwarz beck	FMZB 1519B	00128	/	2025.01.02	2 Year
6.	Bilog Antenna	Schwarz beck	VULB 9168	01448	/	2025.01.02	2 Year
7.	Spectrum Analyzer	Rohde&Schwarz	FSV-40N	101648	3.70	2025.12.18	1 Year
8.	Horn Antenna	Schwarz beck	BBHA 9120 D	02706	/	2025.01.02	2 Year
9.	Amplifier	SKET	LAPA_01G18G-45dB	SK2022032901	/	2025.12.18	1 Year
10.	Horn Antenna	Schwarz beck	BBHA 9170	00946	/	2024.12.31	2 Year
11.	Amplifier	SKET	LNPA_0118G-45	SK2020010801	/	2025.12.18	1 Year
12	RF Power Probe	Rohde&Schwarz	NRP-Z11	1138.3004.02-1111533-Fz	/	2025.12.18	1 Year
13	RF Sensor Unit	Tachoy	TR1029-2	20220428P008	/	2025.12.18	1 Year
14	Spectrum Analyzer	Agilent	N9020A	MY51281067	A.14.03	2025.12.18	1 Year
15	Temp. & Humid Chamber	Auchno	9606	/	/	2025.12.18	1 Year
16	Regulated DC Power Supply	Xinouhua	ADC120V10A	202211251638		2025.12.18	1 Year

For Test Software Information

Item	Software Name	Manufacturer	Version
RE	EZ_EMC	Farad	PSI-3A1
CE	EZ_EMC	Farad	PSI-3A1
RF	RTS	TACHOY	V1.0.0

3. Maximum Peak Output Power

3.1. Limit

Please refer FCC part 15.247 & RSS-247.

For frequency hopping systems operating in the 902-928 MHz band: 1 watt for systems employing at least 50 hopping channels; and, 0.25 watts for systems employing less than 50 hopping channels, but at least 25 hopping channels, as permitted under paragraph (a)(1)(i) of this section. the e.i.r.p shall not exceed 4W

3.2. Test Procedure

The transmitter output is connected to the RF Power meter. The Power meter is set to the peak power detection.

3.3. Test Setup



3.4. Test Result

Condition	Antenna	Modulation	Frequency (MHz)	Max. Conducted Power(dBm)	Limit(dBm)	Result
NVNT	ANT1	ASK	902.75	26.92	30	Pass
NVNT	ANT1	ASK	915.25	27.02	30	Pass
NVNT	ANT1	ASK	927.25	26.88	30	Pass

4. Bandwidth

4.1. Limit

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in RSS-GEN, FCC Section 15.247(a)(1) (i), For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz

4.2. Test Procedure

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 3kHz RBW and 10kHz VBW. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

4.3. Test Result

Condition	Antenna	Modulation	Frequency (MHz)	-20dB BW(MHz)	Limit (kHz)	Results
NVNT	ANT1	ASK	902.75	0.072	≤250	PASS
NVNT	ANT1	ASK	915.25	0.072	≤250	PASS
NVNT	ANT1	ASK	927.25	0.071	≤250	PASS

-20dB_Bandwidth_NVNT_ANT1_ASK_902_75


-20dB_Bandwidth_NVNT_ANT1_ASK_915_25

-20dB_Bandwidth_NVNT_ANT1_ASK_927_25


5. Carrier Frequency Separation

5.1. Limit

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW

Please refer FCC part 15.247 & RSS-247.

5.2. Test Procedure

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The carrier frequency was measured by spectrum analyzer with 30kHz RBW and 100kHz VBW.

5.3. Test Result

Condition	Antenna	Modulation	Frequency(MHz)	Carrier Frequencies Separation(MHz)	Limit(MHz)	Result
NVNT	ANT1	ASK	915.25	0.5003	0.072	Pass

Carrier_Frequencies_Separation_(Hopping)_NVNT_ANT1_ASK_Hopping



6. Number Of Hopping Channel

6.1. Limit

FCC Part15 C Section 15.247(a)(1)(i)

For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.

6.2. Test Procedure

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The number of hopping channel was measured by spectrum analyzer with 100kHz RBW and 300KHz VBW.

6.3. Test Result

Condition	Antenna	Modulation	Hopping Num	Limit	Result
NVNT	ANT1	ASK	50	⩾ 50	Pass

Number_of_Hopping_Channel_(Hopping)_NVNT_ANT1_ASK_Hopping


7. Dwell Time

7.1. Test limit

For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.

7.2. Test Procedure

Place the EUT on the table and set it in transmitting mode.

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

Set center frequency of spectrum analyzer = operating frequency.

Set the spectrum analyzer as RBW=100KHz, VBW=300KHz, Span = 0Hz, Sweep = auto.

Repeat above procedures until all frequency measured were complete.

The test period: T= 0.4 Second/Channel x 50 Channel = 20.0 s

Dwell Time=Pulse Time* Hops Number

7.3. Test Result

Condition	Antenna	Packet Type	Pulse Time(ms)	Hops	Dwell Time(ms)	Limit(s)	Result
NVNT	ANT1	ASK	378.00	1.00	378.00	0.40	Pass

Dwell_Time_(Hopping)_NVNT_ANT1_ASK_902_75_One_Burst_Time



8. Out-of-band Emissions

8.1. Test Limits

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in FCC Part 15.209(a) is not required.
Please refer section RSS-GEN&15.247.

8.2. Test Procedure

Connect the transmitter ouput to spectrum analvzer using a low loss RF cable, and set the spectrum analvzer to RBW=100 kHz, VBW= 300 kHz, peak detector, and max hold. Measurements utilizing these setting are made of the in-band reference level, band edge and out-of-band emissions.

8.3. Test Setup



8.4. Test Results

PASS.

The test results are listed in next pages.

Band Edge: Pass

1_Reference_Level_NVNT_ANT1_ASK_902_75

2_Bandedge_NVNT_ANT1_ASK_902_75


1_Reference_Level_Hopping_NVNT_ANT1_ASK_Hopping

2_Band_Edge_(Hopping)_NVNT_ANT1_ASK_Hopping


1_Reference_Level_NVNT_ANT1_ASK_927_25

2_Bandedge_NVNT_ANT1_ASK_927_25


1_Reference_Level_Hopping_NVNT_ANT1_ASK_Hopping

2_Band_Edge_(Hopping)_NVNT_ANT1_ASK_Hopping


Conducted spurious emission: Pass

1_Reference_Level_NVNT_ANT1_ASK_902_75

2_Spurious_Emissions_NVNT_ANT1_ASK_902_75


1_Reference_Level_NVNT_ANT1_ASK_915_25

2_Spurious_Emissions_NVNT_ANT1_ASK_914_75


1_Reference_Level_NVNT_ANT1_ASK_927_25

2_Spurious_Emissions_NVNT_ANT1_ASK_927_25


9. Radiated Emissions

9.1. Limit

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
[1]0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	([2])

RSS-GEN Restricted frequency band

Table 7 – Restricted frequency bands[Note 1]		
MHz	MHz	GHz
0.090 - 0.110	149.9 - 150.05	9.0 - 9.2
0.495 - 0.505	156.52475 - 156.52525	9.3 - 9.5
2.1735 - 2.1905	156.7 - 156.9	10.6 - 12.7
3.020 - 3.026	162.0125 - 167.17	13.25 - 13.4
4.125 - 4.128	167.72 - 173.2	14.47 - 14.5
4.17725 - 4.17775	240 – 285	15.35 - 16.2
4.20725 - 4.20775	322 - 335.4	17.7 - 21.4
5.677 - 5.683	399.9 - 410	22.01 - 23.12
6.215 - 6.218	608 - 614	23.6 - 24.0
6.26775 - 6.26825	960 - 1427	31.2 - 31.8
6.31175 - 6.31225	1435 - 1626.5	36.43 - 36.5

8.291 - 8.294	1645.5 - 1646.5	Above 38.6
8.362 - 8.366	1660 - 1710	
8.37625 - 8.38675	1718.8 - 1722.2	
8.41425 - 8.41475	2200 - 2300	
12.29 - 12.293	2310 - 2390	
12.51975 - 12.52025	2483.5 - 2500	
12.57675 - 12.57725	2655 - 2900	
13.36 - 13.41	3260 – 3267	
16.42 - 16.423	3332 - 3339	
16.69475 - 16.69525	3345.8 - 3358	
16.80425 - 16.80475	3500 - 4400	
25.5 - 25.67	4500 - 5150	
37.5 - 38.25	5350 - 5460	
73 - 74.6	7250 - 7750	
74.8 - 75.2	8025 – 8500	
108 – 138		

Note 1: Certain frequency bands listed in table 7 and in bands above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSS.

15.209 Limit

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		μV/m	dB(μV)/m
0.009-0.490	300	2400/F(KHz)	/
0.490-1.705	30	24000/F(KHz)	/
1.705-30	30	30	29.5
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)	

Note: The peak limit is 20 dB higher than the average limit

Table 5 – General field strength limits at frequencies above 30 MHz

Frequency (MHz)	Field strength (μV/m at 3 m)
30 – 88	100
88 – 216	150
216 – 960	200
Above 960	500

Table 6 – General field strength limits at frequencies below 30 MHz

Frequency	Magnetic field strength (H-Field) (μA/m)	Measurement distance (m)
9 - 490 kHz[Note 1]	6.37/F (F in kHz)	300
490 - 1705 kHz	63.7/F (F in kHz)	30
1.705 - 30 MHz	0.08	30

Note 1: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

9.2. Block Diagram of Test setup

9.2.1 In 3m Anechoic Chamber Test Setup Diagram for below 30MHz



9.2.1 In 3m Anechoic Chamber Test Setup Diagram for below 1GHz



9.2.2 In 3m Anechoic Chamber Test Setup Diagram for frequency above 1GHz



Note: For harmonic emissions test a appropriate high pass filter was inserted in the input port of AMP.

9.3. Test Procedure

(1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber.

(2) Setup EUT and simulator

(3) Test antenna was located 3m from the EUT on an adjustable mast. Below pre-scan procedure was first performed in order to find prominent radiated emissions.

(a) Change work frequency or channel of device if practicable.

(b) Change modulation type of device if practicable.

(c) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions

(4) Spectrum frequency from 9KHz to 25GHz (tenth harmonic of fundamental frequency) was investigated

(5) For final emissions measurements at each frequency of interest, the EUT were rotated and the antenna height was varied between 1m and 4m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10:2020on Radiated Emission test.

(6) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1MHz, VBW is set at 3MHz for Peak measure; RBW is set at 1MHz, VBW is set at 10Hz for Average measure.

9.4. Test Results

We have scanned from 9kHz to the 10th harmonic of the EUT's highest frequency.

Detailed information please see the following page.

<table>
<tr><td colspan="4">From 9KHz to 30MHz:</td></tr>
<tr><td>Test Date</td><td>: 2025.11.02</td><td>Temperature</td><td>: 26℃</td></tr>
<tr><td>Test Engineer</td><td>: Felix Pang</td><td>Humidity</td><td>: 54%</td></tr>
<tr><td>Test Mode</td><td colspan="3">: ASK mode</td></tr>
<tr><td>Test Results</td><td colspan="3">: PASS</td></tr>
<tr><td>Note:</td><td colspan="3">The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.</td></tr>
</table>

From 30MHz to 1000MHz:					
Test Date	:	2025.11.02	Temperature	:	26℃
Test Engineer	:	Felix Pang	Humidity	:	54%
Test Mode	:	ASK mode			
Test Results	:	**PASS**			
Note:	1. The test results are listed in next pages. 2. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector and quasi-peak detector need not be carried out. 3. All modes have been tested, and only worst data of ASK mode, Channel 902.75MHzwas listed in this report.				

Polarization: Vertical



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	38.4808	46.10	-20.81	25.29	40.00	-14.71	QP
2	47.1597	47.82	-20.96	26.86	40.00	-13.14	QP
3	92.7870	49.13	-20.06	29.07	43.50	-14.43	QP
4	185.7880	43.39	-18.49	24.90	43.50	-18.60	QP
5	300.3672	41.89	-18.06	23.83	46.00	-22.17	QP
6	399.0300	38.56	-16.47	22.09	46.00	-23.91	QP

Note: Level = Reading + Factor Margin = Level - Limit

Polarization: Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	87.7245	45.24	-20.31	24.93	40.00	-15.07	QP
2	197.8925	39.07	-18.50	20.57	43.50	-22.93	QP
3	305.6800	44.95	-18.44	26.51	46.00	-19.49	QP
4	574.6258	35.82	-11.41	24.41	46.00	-21.59	QP
5	724.2607	40.44	-8.72	31.72	46.00	-14.28	QP
6	796.1829	36.40	-7.56	28.84	46.00	-17.16	QP

Note: Level = Reading + Factor Margin = Level - Limit

From 1GHz to 25GHz:					
Test Date	:	2025.11.28	Temperature	:	26℃
Test Engineer	:	Felix Pang	Humidity	:	54%
Test Mode	:	ASK mode			
Test Results	:	**PASS**			
Note:	1. The test results are listed in next pages. 2. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector and quasi-peak detector need not be carried out. 3. If the limits for the measurement with the average detector are met when using a receiver with a quasi-peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out.				

Test Mode : ASK TX Low CH01								
No.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	1805.50	V	76.11	-21.76	54.35	74.00	-19.65	Peak
2	1805.50	V	69.01	-21.76	47.25	54.00	-6.75	Avg
3	2708.25	--	--	--	--	--	--	--
4	3611.00	--	--	--	--	--	--	--
5	1805.50	H	75.29	-21.76	53.53	74.00	-20.47	Peak
6	1805.50	H	69.88	-21.76	48.12	54.00	-5.88	Avg
7	2708.25	--	--	--	--	--	--	--
8	3611.00	--	--	--	--	--	--	--
Test Mode : ASK TX Mid CH26								
1	1829.50	V	75.57	-21.76	53.81	74.00	-20.19	Peak
2	1829.50	V	70.03	-21.76	48.27	54.00	-5.73	Avg
3	2744.25	--	--	--	--	--	--	--
4	3659.00	--	--	--	--	--	--	--
5	1829.50	H	74.70	-21.76	52.94	74.00	-21.06	Peak
6	1829.50	H	70.07	-21.76	48.31	54.00	-5.69	Avg
7	2744.25	--	--	--	--	--	--	--
8	3659.00	--	--	--	--	--	--	--
Test Mode : ASK TX High CH50								
1	1854.50	V	75.33	-21.74	53.59	74.00	-20.41	Peak
2	1854.50	V	70.11	-21.74	48.37	54.00	-5.63	Avg
3	2781.75	--	--	--	--	--	--	--
4	3709.00	--	--	--	--	--	--	--
5	1854.50	H	72.62	-21.74	50.88	74.00	-23.12	Peak
6	1854.50	H	68.80	-21.74	47.06	54.00	-6.94	Avg
7	2781.75	--	--	--	--	--	--	--
8	3709.00	--	--	--	--	--	--	--
Note:	1. Means other frequency and mode comply with standard requirements and at least have 20dB margin. 2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor, Margin= Result-Limit.							

10. Band Edge Test

10.1.Block Diagram of Test Setup



10.2.Test Limit

Radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

Please refer section RSS-GEN&15.247.

10.3.Test Procedure

Refer to ANSI C 63.10, Clause 6.10.

All restriction band and non- restriction band have been tested, only worse case is reported.

10.4.Test Results

Test Date	:	2025.11.28	Temperature	:	26℃
Test Engineer	:	Felix Pang	Humidity	:	54%
Test Results	:	**PASS**			

Frequency Range : **902MHz~928MHz**								
Test Mode : ASK TX Low CH01, ASK TX High CH50								
No.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	902.0	H	9.59	28.09	37.68	46	-8.32	QP
2	928.0	H	10.47	28.36	38.83	46	-8.17	QP
3	902.0	V	12.06	28.09	40.15	46	-7.85	QP
4	928.0	V	12.50	28.36	40.86	46	-8.14	QP

Note:
1. Means other frequency and mode comply with standard requirements and at least have 20dB margin.
2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain.
Result=Reading + Correct Factor. Margin= Result-Limit.
3. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out.

11. Power Line Conducted Emissions

11.1.Block Diagram of Test Setup



11.2.Limit

Frequency	Maximum RF Line Voltage	
	Quasi-Peak Level dB(μV)	Average Level dB(μV)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Notes: 1. * Decreasing linearly with logarithm of frequency.

2. The lower limit shall apply at the transition frequencieS.

11.3.Test Procedure

(1) The EUT was placed on a non-metallic table, 80cm above the ground plane.

(2) Setup the EUT and simulator as shown in 10.1

(3) The EUT Power connected to the power mains through a power adapter and a line impedance stabilization network (L.I.S.N1). The other peripheral devices power cord connected to the power mains through a line impedance stabilization network (L.I.S.N2), this provided a 50-ohm coupling impedance for the EUT (Please refer to the block diagram of the test setup and photographs). Both sides of power line were checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10:2020on conducted Emission test.

(4) The bandwidth of test receiver is set at 10KHz.

(5) The frequency range from 150 KHz to 30MHz is checked.

11.4.Test Results

Test Date	: 2025.11.28	Temperature	: 24℃
Test Engineer	: Felix Pang	Humidity	: 56%
Test Mode	: ASK mode		
Test Results	: **PASS**		
Note:	1. The test results are listed in next pages. 2. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector and quasi-peak detector need not be carried out. 3. If the limits for the measurement with the average detector are met when using a receiver with a quasi-peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out. 4. All modes have been tested, and only worst data of ASK mode, Channel 902.75MHz was listed in this report.		

Polarization: L



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.2355	11.71	9.82	21.53	62.25	-40.72	QP
2	0.2355	7.51	9.82	17.33	52.25	-34.92	AVG
3	0.3030	9.44	9.86	19.30	60.16	-40.86	QP
4	0.3030	2.36	9.86	12.22	50.16	-37.94	AVG
5	0.8519	6.75	9.96	16.71	56.00	-39.29	QP
6	0.8519	-3.98	9.96	5.98	46.00	-40.02	AVG
7	2.1569	6.94	9.85	16.79	56.00	-39.21	QP
8	2.1569	-4.58	9.85	5.27	46.00	-40.73	AVG
9	11.8770	11.89	9.81	21.70	60.00	-38.30	QP
10	11.8770	-0.25	9.81	9.56	50.00	-40.44	AVG
11	18.4380	10.96	9.70	20.66	60.00	-39.34	QP
12	18.4380	-1.22	9.70	8.48	50.00	-41.52	AVG

Note: Level = Reading + Factor Margin = Level - Limit

Polarization: N



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.2355	14.38	9.82	24.20	62.25	-38.05	QP
2	0.2355	6.99	9.82	16.81	52.25	-35.44	AVG
3	0.4425	16.27	9.92	26.19	57.01	-30.82	QP
4	0.4425	2.52	9.92	12.44	47.01	-34.57	AVG
5	0.7754	11.01	9.96	20.97	56.00	-35.03	QP
6	0.7754	-1.26	9.96	8.70	46.00	-37.30	AVG
7	1.8600	11.17	9.86	21.03	56.00	-34.97	QP
8	1.8600	-1.94	9.86	7.92	46.00	-38.08	AVG
9	11.6385	16.63	9.82	26.45	60.00	-33.55	QP
10	11.6385	2.86	9.82	12.68	50.00	-37.32	AVG
11	18.1140	15.89	9.70	25.59	60.00	-34.41	QP
12	18.1140	2.01	9.70	11.71	50.00	-38.29	AVG

Note: Level = Reading + Factor Margin = Level - Limit

12. Frequency stability

12.1.Test limit

Please refer section RSS-Gen.

Regulation RSS-Gen If the frequency stability of the licence-exempt radio apparatus is not specified in the applicable RSS, the fundamental emissions of the radio apparatus should be kept within at least the central 80% of its permitted operating frequency band in order to minimize the possibility of out-of-band operation. In addition, its occupied bandwidth shall be entirely outside the restricted bands and the prohibited TV bands of 54-72 MHz, 76-88 MHz, 174-216 MHz, and 470-602 MHz, unless otherwise indicated.

12.2.Test Procedure

The following equipment are installed on the emission measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

12.3.Test Setup



Temperature controller

12.4.Test Results

Not Applicable

13. Antenna Requirements

13.1.Limit

For intentional device, according to FCC 47 CFR Section 15.203 and RSS-GEN, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

13.2.Result

The EUT antenna is PCB antenna. It complies with the standard requirement.

14. Photos of test setup

Reference to the **appendix I Test Setup Photo** for details.

15. Photos of EUT

Reference to the **appendix II external photos** and **appendix III internal photos** for details.

------ END OF REPORT------