

FCC RF EXPOSURE REPORT


FCC ID: 2AJYB-S1832AE

Project No. : 2404C068
Equipment : Network Audio Streaming Module
Brand Name : StreamUnlimited
Test Model : Stream1832AE
Series Model : N/A
Applicant : StreamUnlimited Engineering GmbH
Address : StreamUnlimited Engineering GmbH, Gutheil Schoder Gasse 10,
Vienna 1100, Austria
Manufacturer : StreamUnlimited Engineering GmbH
Address : StreamUnlimited Engineering GmbH, Gutheil Schoder Gasse 10,
Vienna 1100, Austria
Factory : StreamUnlimited Engineering GmbH
Address : StreamUnlimited Engineering GmbH, Gutheil Schoder Gasse 10,
Vienna 1100, Austria
Date of Receipt : Apr. 09, 2024
Date of Test : Apr. 10, 2024 ~ May 30, 2024
Issued Date : Jun. 25, 2024
Report Version : R01
Test Sample : Engineering Sample No.: DG20240409194
Standard(s) : FCC Guidelines for Human Exposure IEEE C95.1 & FCC Part 2.1091
FCC Title 47 Part 2.1091 & KDB 447498 D01 v06

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

Prepared by

:


Antony Liang

Approved by

:


Chay Cai

Room 108, Building 2, No.1, Yile Road, Songshan Lake Zone, Dongguan City, Guangdong,
People's Republic of China.

Tel: +86-769-8318-3000

Web: www.newbtl.com

Service mail: btl_qa@newbtl.com

REPORT ISSUED HISTORY

Report No.	Version	Description	Issued Date	Note
BTL-FCCP-6-2404C068	R00	Original Report.	Jun. 17, 2024	Invalid
BTL-FCCP-6-2404C068	R01	Updated the antenna information.	Jun. 25, 2024	Valid

1. MPE CALCULATION METHOD

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi^2} = \frac{EIRP}{4\pi^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

2. ANTENNA SPECIFICATION

Group 1:

For BT/LE:

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1		N/A	FPC	MHF4	3

Note: The antenna gain is provided by the manufacturer.

For 2.4G:

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1		N/A	FPC	MHF4	3
2		N/A	FPC	MHF4	3

Note:

(1) There are two antennas but only one antenna works at a time.

(2) The antenna gain is provided by the manufacturer.

For 5G:

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1		N/A	FPC	MHF4	4
2		N/A	FPC	MHF4	4

Note:

(1) There are two antennas but only one antenna works at a time.

(2) The antenna gain is provided by the manufacturer.

Group 2:

For BT/LE:

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1		2JF0102	FPC	Most RF Connectors	2.2

Note: The antenna gain is provided by the manufacturer.

For 2.4GHz:

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1		2JF0102	FPC	Most RF Connectors	2.2
2		2JF0102	FPC	Most RF Connectors	2.2

Note:

- (1) There are two antennas but only one antenna works at a time.
- (2) The antenna gain is provided by the manufacturer.

For 5GHz:

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1		2JF0102	FPC	Most RF Connectors	3.8
2		2JF0102	FPC	Most RF Connectors	3.8

Note:

- (1) There are two antennas but only one antenna works at a time.
- (2) The antenna gain is provided by the manufacturer.

3. CALCULATED RESULT

For BT:

Antenna Gain (dBi)	Antenna Gain (numeric)	Max. Peak Output Power (dBm)	Max. Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
3	1.9953	6.26	4.2267	0.00168	1	Complies

For LE:

Antenna Gain (dBi)	Antenna Gain (numeric)	Max. Peak Output Power (dBm)	Max. Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
3	1.9953	6.11	4.0832	0.00162	1	Complies

For 2.4GHz:

Antenna Gain (dBi)	Antenna Gain (numeric)	Max. Output Power (dBm)	Max. Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
3	1.9953	15.44	34.9945	0.01390	1	Complies

For 5GHz:

Antenna Gain (dBi)	Antenna Gain (numeric)	Max. Output Power (dBm)	Max. Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
4	2.5119	15.93	39.1742	0.01959	1	Complies

For the max simultaneous transmission MPE:

Ratio		Total	Limit of Ratio	Test Result
BT	5GHz			
0.00168	0.01959	0.02127	1	Complies

Note: The calculated distance is 20 cm.

End of Test Report