# TEST REPORT

| | | | |
|---|---|---|---|
| **Report Reference No. ..... :** | **TRE16090060** | R/C…….: | 63930 |
| **FCC ID ..... :** | **2AJZPF07** | | |
| **Applicant's name ..... :** | **Mason America, Inc.** | | |
| Address.....: | 300 Park Street , Suite 380,Birmingham, Michigan 48009, United States | | |
| Manufacturer.....: | Foneric Technology Co.,Ltd | | |
| Address.....: | 4/5F,Fuxing Buliding,No.6 Binglang Road Futian Free Trade Zone,Shenzhen,PR.China | | |
| **Test item description ..... :** | **F07 By Mason** | | |
| Trade Mark .....: | Mason | | |
| Model/Type reference.....: | Mason F07 | | |
| Listed Model(s) .....: | - | | |
| **Standard ..... :** | **FCC 47 CFR Part2.1093**<br>**ANSI/IEEE C95.1: 1999**<br>**IEEE 1528: 2013** | | |
| Date of receipt of test sample……..: | Sept.13,2016 | | |
| Date of testing……: | Sept.14,2016 ~ Oct.10, 2016 | | |
| Date of issue……...: | Oct.10, 2016 | | |
| **Result..... ……...:** | **PASS** | | |

| | | | |
|---|---|---|---|
| Compiled by<br>( position+printedname+signature)...: | File administrators: | SiyuanRao | Siyuan Rao |
| Supervised by<br>( position+printedname+signature)...: | Test Engineer: | SiyuanRao | Siyuan Rao |
| Approved by<br>( position+printedname+signature)...: | Manager: | Hans Hu | Hans Hu |

| | |
|---|---|
| **Testing Laboratory Name ..... :** | **Shenzhen Huatongwei International Inspection Co., Ltd** |
| Address.....: | 1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China |

**Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

*The test report merely corresponds to the test sample.*
*It is not permitted to copy extracts of these test result without the written permission of the test laboratory.*

# Contents


1. Test Standards and Report version 3
   1.1. Test Standards 3
   1.2. Report version 3
2. Summary 4
   2.1. Client Information 4
   2.2. Product Description 4
3. Test Environment 6
   3.1. Address of the test laboratory 6
   3.2. Test Facility 6
4. Equipments Used during the Test 7
5. Measurement Uncertainty 8
6. SAR Measurements System Configuration 10
   6.1. SAR Measurement Set-up 10
   6.2. DASY5 E-field Probe System 11
   6.3. Phantoms 12
   6.4. Device Holder 12
7. SAR Test Procedure 13
   7.1. Scanning Procedure 13
   7.2. Data Storage and Evaluation 14
8. Position of the wireless device in relation to the phantom 16
   8.1. Head Position 16
   8.2. Body Position 17
   8.3. Hotspot Mode Exposure conditions 17
9. System Check 18
   9.1. Tissue Dielectric Parameters 18
   9.2. SAR System Check 20
10. SAR Exposure Limits 32
11. Conducted Power Measurement Results 33
12. Maximum Tune-up Limit 49
13. Antenna Location 52
14. SAR Measurement Results 53
15. SAR Measurement Variability 70
16. Simultaneous Transmission analysis 89
17. TestSetup Photos 93
18. External and Internal Photos of the EUT 96

# 1 . Test Standards and Report version

## 1.1. Test Standards

The tests were performed according to following standards:

FCC 47 Part 2.1093 Radiofrequency Radiation Exposure Evaluation:Portable Devices
IEEE Std C95.1, 1999: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 KHz to 300 GHz.
IEEE Std 1528™-2013: IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques.
KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04: SAR Measurement Requirements for 100 MHz to 6 GHz
KDB 865664 D02 RF Exposure Reporting v01r02: RF Exposure Compliance Reporting and Documentation Considerations
KDB 447498 D01 General RF Exposure Guidance v06: Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies
KDB248227 D01 802 11 Wi-Fi SAR v02r02: SAR Measurement Proceduresfor802.11 a/b/g Transmitters
KDB 648474 D04 Handset SAR v01r03: SAR Evaluation Considerations for Wireless Handsets
KDB 616217 D04 SAR for laptop and tablets v01r02:SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers
KDB941225 D01 3G SAR Procedures v03r01: SAR Measurement Procedures for 3G Devices
KDB 941225 D06 Hotspot Mode v02r01: SAR Evaluation Procedures for Portable Devices with Wireless Router Capabilities
KDB941225 D05 SAR for LTE Devices v02r04: SAR Evaluation Considerations for LTE Devices

## 1.2. Report version

| Version No. | Date of issue | Description |
|---|---|---|
| 00 | Oct.10, 2016 | Original |
| | | |
| | | |
| | | |
| | | |

# 2. Summary

## 2.1. Client Information

| | |
|---|---|
| Applicant: | Mason America, Inc. |
| Address: | 300 Park Street , Suite 380,Birmingham, Michigan 48009, United States |
| Manufacturer: | Foneric Technology Co.,Ltd |
| Address: | 4/5F,Fuxing Buliding,No.6 Binglang Road Futian Free Trade Zone,Shenzhen,PR.China |

## 2.2. Product Description

| | |
|---|---|
| Name of EUT | F07 By Mason |
| Trade Mark: | Mason |
| Model No.: | Mason F07 |
| Listed Model(s): | - |
| Power supply: | DC 3.8V From internal battery |
| Device Category: | Portable |
| Product stage: | Production unit |
| RF Exposure Environment: | General Population / Uncontrolled |
| IMEI: | 865006020015377 |
| Device Class: | B |
| Hardware version: | V1.0.3-8011E |
| Software version: | V2.0.8.0 |
| **Maximum SAR Value** | |
| Separation Distance: | Head: 0mm<br>Body: 0mm |
| Max Report SAR Value (1g): | Head: **0.24W/Kg**<br>Body: **1.08W/Kg** |
| **GSM** | |
| Support Network: | GSM, GPRS, EGPRS |
| Support Band: | GSM850, DCS1900 |
| Modulation: | GSM/GPRS: GMSK<br>EGPRS: GMSK 8PSK |
| Transmit Frequency: | GSM850: 824.20MHz-848.80MHz<br>PCS1900: 1850.20MHz-1909.80MHz |
| Receive Frequency: | GSM850: 869.20MHz-893.80MHz<br>PCS1900: 1930.20MHz-1989.80MHz |
| GPRS Class: | 12 |
| EGPRS Class: | 12 |
| Antenna type: | Intergal Antenna |

| | |
|---|---|
| **WCDMA** | |
| Operation Band: | FDD Band II and FDD Band V |
| Power Class: | Power Class 3 |
| Modilation Type: | QPSK/16QAM/HSUPA/HSDPA |
| DC-HSUPA Release Version: | Not Supported |
| Antenna type: | Intergal Antenna |
| **LTE** | |
| Operation Band: | FDD Band 2,FDD Band 4, FDD Band 5, FDD Band 12, FDD Band 17 |
| Modilation Type: | QPSK， 16QAM |
| **WIFI** | |
| Supported type: | 802.11b/802.11g/802.11n(H20)/802.11n(H40) |
| Modulation: | 802.11b: DSSS (DBPSK / DQPSK / CCK)<br>802.11g/n(H20)/ n(H40): OFDM (BPSK / QPSK / 16QAM / 64QAM) |
| Operation frequency: | 802.11b/g/n(H20): 2412MHz~2462MHz<br>802.11n(H40): 2422MHz~2452MHz |
| Channel number: | 802.11b/g/n(H20): 11<br>802.11n(H40):7 |
| Channel separation: | 5MHz |
| Antenna type: | Internal Antenna |
| **Bluetooth** | |
| Version: | Supported BT4.0+EDR |
| Modulation: | GFSK, π/4DQPSK, 8DPSK |
| Operation frequency: | 2402MHz~2480MHz |
| Channel number: | 79 |
| Channel separation: | 1MHz |
| Antenna type: | Integral Antenna |
| **Bluetooth** | |
| Version: | Supported BT4.0+BLE |
| Modulation: | GFSK |
| Operation frequency: | 2402MHz~2480MHz |
| Channel number: | 40 |
| Channel separation: | 2MHz |
| Antenna type: | Integral Antenna |
| *Remark:*<br>*The EUT battery must be fully charged and checked periodically during the test to ascertain uniform power* | |

**Note**:

1. **Per FCC KDB Publication 616217 D04v01r03，Regardless of device dimensions, when next to the ear voice calls are supported the smart phone and phablets procedures in KDB 648474 must be applied.**
2. **Per FCC KDB Publication 648474 D04v01r03, this device is considered a "phablet".Therefore, phablet SAR tests are required whenwireless router mode does not apply or if wireless router 1g SAR > 1.2 W/kg. Phablet SAR was not evaluatedfor licensed technologies since wireless router 1g SAR was < 1.2 W/kg for these modes.**
3. **This device supports both LTE Band 12 and LTE Band 17. Since the supported frequency span for LTE Band17 falls completely within the supported frequency span for LTE Band 12, LTE Band 17 target power is lessthan or equal to LTE Band 12 target power, and both LTE bands share the same transmission path, SAR wasonly assessed for LTE Band 12.**

# 3. Test Environment

## 3.1. Address of the test laboratory

Laboratory:Shenzhen Huatongwei International Inspection Co., Ltd.
Address: 1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China
Phone: 86-755-26748019 Fax: 86-755-26748089

## 3.2. Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

**CNAS-Lab Code: L1225**
Shenzhen Huatongwei International Inspection Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories
(identical to ISO/IEC17025: 2005 General Requirements) for the Competence of Testing and Calibration Labo ratories, Date of Registration: February 28, 2015. Valid time is until February 27, 2018.

**A2LA-Lab Cert. No. 3902.01**
Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been accredited by A2LA for tec hnical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional progra m requirements in the identified field of testing. Valid time is until December 31, 2016.

**FCC-Registration No.: 317478**
Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been registered and fully descri bed in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FC C is maintained in our files. Registration 317478, Renewal date Jul. 18, 2014, valid time is until Jul. 18, 2017.

**IC-Registration No.: 5377A&5377B**
The 3m Alternate Test Site of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 5377A on Dec. 31, 2013, valid time is until Dec. 31, 2016.
Two 3m Alternate Test Site of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 5377B on Dec.03, 2014, valid time is until Dec.03, 2017.

**ACA**
Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory can also perform testing for the Aust ralian C-Tick mark as a result of our A2LA accreditation.

# 4. Equipments Used during the Test

| Test Equipment | Manufacturer | Type/Model | Serial Number | Calibration | |
|---|---|---|---|---|---|
| | | | | Last Calibration | Calibration Interval |
| Data Acquisition Electronics DAEx | SPEAG | DAE4 | 1315 | 2016/07/26 | 1 |
| E-field Probe | SPEAG | ES3DV3 | 3292 | 2016/09/02 | 1 |
| System Validation Dipole D750V3 | SPEAG | D750V3 | 1156 | 2016/02/02 | 3 |
| System Validation Dipole D835V2 | SPEAG | D835V2 | 4d134 | 2014/07/24 | 3 |
| System Validation Dipole D1750V2 | SPEAG | D1750V2 | 1062 | 2015/07/25 | 3 |
| System Validation Dipole D1900V2 | SPEAG | D1900V2 | 5d150 | 2015/12/12 | 3 |
| System Validation Dipole D2450V2 | SPEAG | D2450V2 | 884 | 2015/09/01 | 3 |
| Dielectric Probe Kit | Agilent | 85070E | US44020288 | / | / |
| Power meter | Agilent | E4417A | GB41292254 | 2015/10/26 | 1 |
| Power sensor | Agilent | 8481H | MY41095360 | 2015/10/26 | 1 |
| Power sensor | Agilent | E9327A | US40441621 | 2015/10/26 | 1 |
| Network analyzer | Agilent | 8753E | US37390562 | 2015/10/25 | 1 |
| Universal Radio Communication Tester | ROHDE & SCHWARZ | CMU200 | 112012 | 2015/10/23 | 1 |
| Universal Radio Communication Tester | ROHDE & SCHWARZ | CMW500 | 1556902 | 2015/12/28 | 1 |
| Signal Generator | ROHDE & SCHWARZ | SMBV100A | 258525 | 2015/10/23 | 1 |
| Power Divider | ARRA | A3200-2 | N/A | N/A | N/A |
| Dual Directional Coupler | Agilent | 778D | 50783 | Note | |
| Attenuator 1 | PE | PE7005-10 | N/A | Note | |
| Attenuator 2 | PE | PE7005-10 | N/A | Note | |
| Attenuator 3 | PE | PE7005-3 | N/A | Note | |
| Power Amplifier | AR | 5S1G4M2 | 0328798 | Note | |

*Note:*

1. *The Probe,Dipole and DAE calibration reference to the Appendix A.*
2. *Referring to KDB865664 D01, the dipole calibration interval can be extended to 3 years with justifcatio. The dipole are also not physically damaged or repaired during the interval.*

# 5. Measurement Uncertainty

| Measurement Uncertainty | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|
| No. | Error Description | Type | Uncertainty Value | Probably Distribution | Div. | (Ci) 1g | (Ci) 10g | Std. Unc. (1g) | Std. Unc. (10g) | Degree of freedom |
| Measurement System | | | | | | | | | | |
| 1 | Probe calibration | B | 6.0% | N | 1 | 1 | 1 | 6.0% | 6.0% | ∞ |
| 2 | Axial isotropy | B | 4.70% | R | $\sqrt{3}$ | 0.7 | 0.7 | 1.90% | 1.90% | ∞ |
| 3 | Hemispherical isotropy | B | 9.60% | R | $\sqrt{3}$ | 0.7 | 0.7 | 3.90% | 3.90% | ∞ |
| 4 | Boundary Effects | B | 1.00% | R | $\sqrt{3}$ | 1 | 1 | 0.60% | 0.60% | ∞ |
| 5 | Probe Linearity | B | 4.70% | R | $\sqrt{3}$ | 1 | 1 | 2.70% | 2.70% | ∞ |
| 6 | Detection limit | B | 1.00% | R | $\sqrt{3}$ | 1 | 1 | 0.60% | 0.60% | ∞ |
| 7 | RF ambient conditions-noise | B | 0.00% | R | $\sqrt{3}$ | 1 | 1 | 0.00% | 0.00% | ∞ |
| 8 | RF ambient conditions-reflection | B | 0.00% | R | $\sqrt{3}$ | 1 | 1 | 0.00% | 0.00% | ∞ |
| 9 | Response time | B | 0.80% | R | $\sqrt{3}$ | 1 | 1 | 0.50% | 0.50% | ∞ |
| 10 | Integration time | B | 5.00% | R | $\sqrt{3}$ | 1 | 1 | 2.90% | 2.90% | ∞ |
| 11 | RF ambient | B | 3.00% | R | $\sqrt{3}$ | 1 | 1 | 1.70% | 1.70% | ∞ |
| 12 | Probe positioned mech. restrictions | B | 0.40% | R | $\sqrt{3}$ | 1 | 1 | 0.20% | 0.20% | ∞ |
| 13 | Probe positioning with respect to phantom shell | B | 2.90% | R | $\sqrt{3}$ | 1 | 1 | 1.70% | 1.70% | ∞ |
| 14 | Max.SAR evalation | B | 3.90% | R | $\sqrt{3}$ | 1 | 1 | 2.30% | 2.30% | ∞ |
| Test Sample Related | | | | | | | | | | |
| 15 | Test sample positioning | A | 1.86% | N | 1 | 1 | 1 | 1.86% | 1.86% | ∞ |
| 16 | Device holder uncertainty | A | 1.70% | N | 1 | 1 | 1 | 1.70% | 1.70% | ∞ |
| 17 | Drift of output power | B | 5.00% | R | $\sqrt{3}$ | 1 | 1 | 2.90% | 2.90% | ∞ |
| Phantom and Set-up | | | | | | | | | | |
| 18 | Phantom uncertainty | B | 4.00% | R | $\sqrt{3}$ | 1 | 1 | 2.30% | 2.30% | ∞ |
| 19 | Liquid conductivity (target) | B | 5.00% | R | $\sqrt{3}$ | 0.64 | 0.43 | 1.80% | 1.20% | ∞ |
| 20 | Liquid conductivity (meas.) | A | 0.50% | N | 1 | 0.64 | 0.43 | 0.32% | 0.26% | ∞ |
| 21 | Liquid permittivity (target) | B | 5.00% | R | $\sqrt{3}$ | 0.64 | 0.43 | 1.80% | 1.20% | ∞ |
| 22 | Liquid cpermittivity (meas.) | A | 0.16% | N | 1 | 0.64 | 0.43 | 0.10% | 0.07% | ∞ |
| Combined standard uncertainty | | $u_c = \sqrt{\sum_{i=1}^{22} c_i^2 u_i^2}$ | | / | / | / | / | 9.79% | 9.67% | ∞ |
| Expanded uncertainty (confidence interval of 95 %) | | $u_e = 2u_c$ | | R | K=2 | / | / | 19.57% | 19.34% | ∞ |

| System Check Uncertainty | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|
| No. | Error Description | Type | Uncertainty Value | Probably Distribution | Div. | (Ci) 1g | (Ci) 10g | Std. Unc. (1g) | Std. Unc. (10g) | Degree of freedom |
| Measurement System | | | | | | | | | | |
| 1 | Probe calibration | B | 6.0% | N | 1 | 1 | 1 | 6.0% | 6.0% | ∞ |
| 2 | Axial isotropy | B | 4.70% | R | $\sqrt{3}$ | 0.7 | 0.7 | 1.90% | 1.90% | ∞ |
| 3 | Hemispherical isotropy | B | 9.60% | R | $\sqrt{3}$ | 0.7 | 0.7 | 3.90% | 3.90% | ∞ |
| 4 | Boundary Effects | B | 1.00% | R | $\sqrt{3}$ | 1 | 1 | 0.60% | 0.60% | ∞ |
| 5 | Probe Linearity | B | 4.70% | R | $\sqrt{3}$ | 1 | 1 | 2.70% | 2.70% | ∞ |
| 6 | Detection limit | B | 1.00% | R | $\sqrt{3}$ | 1 | 1 | 0.60% | 0.60% | ∞ |
| 7 | RF ambient conditions-noise | B | 0.00% | R | $\sqrt{3}$ | 1 | 1 | 0.00% | 0.00% | ∞ |
| 8 | RF ambient conditions-reflection | B | 0.00% | R | $\sqrt{3}$ | 1 | 1 | 0.00% | 0.00% | ∞ |
| 9 | Response time | B | 0.80% | R | $\sqrt{3}$ | 1 | 1 | 0.50% | 0.50% | ∞ |
| 10 | Integration time | B | 5.00% | R | $\sqrt{3}$ | 1 | 1 | 2.90% | 2.90% | ∞ |
| 11 | RF ambient | B | 3.00% | R | $\sqrt{3}$ | 1 | 1 | 1.70% | 1.70% | ∞ |
| 12 | Probe positioned mech. restrictions | B | 0.40% | R | $\sqrt{3}$ | 1 | 1 | 0.20% | 0.20% | ∞ |
| 13 | Probe positioning with respect to phantom shell | B | 2.90% | R | $\sqrt{3}$ | 1 | 1 | 1.70% | 1.70% | ∞ |
| 14 | Max.SAR evalation | B | 3.90% | R | $\sqrt{3}$ | 1 | 1 | 2.30% | 2.30% | ∞ |
| System validation source-dipole | | | | | | | | | | |
| 15 | Deviation of experimental dipole from numerical dipole | A | 1.58% | N | 1 | 1 | 1 | 1.58% | 1.58% | ∞ |
| 16 | Dipole axis to liquid distance | A | 1.35% | N | 1 | 1 | 1 | 1.35% | 1.35% | ∞ |
| 17 | Input power and SAR drift | B | 4.00% | R | $\sqrt{3}$ | 1 | 1 | 2.30% | 2.30% | ∞ |
| Phantom and Set-up | | | | | | | | | | |
| 18 | Phantom uncertainty | B | 4.00% | R | $\sqrt{3}$ | 1 | 1 | 2.30% | 2.30% | ∞ |
| 20 | Liquid conductivity (meas.) | A | 0.50% | N | 1 | 0.64 | 0.43 | 0.32% | 0.26% | ∞ |
| 22 | Liquid cpermittivity (meas.) | A | 0.16% | N | 1 | 0.64 | 0.43 | 0.10% | 0.07% | ∞ |
| Combined standard uncertainty | | $u_c = \sqrt{\sum_{i=1}^{22} c_i^2 u_i^2}$ | | / | / | / | / | 8.80% | 8.79% | ∞ |
| Expanded uncertainty (confidence interval of 95 %) | | $u_e = 2u_c$ | | R | K=2 | / | / | 17.59% | 17.58% | ∞ |

# 6. SAR Measurements System Configuration

## 6.1. SAR Measurement Set-up

The DASY5 system for performing compliance tests consists of the following items:

A standard high precision 6-axis robot (Stäubli RX family) with controller and software. An arm extension for accommodating the data acquisition electronics (DAE).

A dosimetric probe, i.e. an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.

A data acquisition electronic (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.

A unit to operate the optical surface detector which is connected to the EOC.

The Electro-Optical Coupler (EOC) performs the conversion from the optical into a digital electric signal of the DAE. The EOC is connected to the DASY5 measurement server.

The DASY5 measurement server, which performs all real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operation. A computer operating Windows 2003.

DASY5 software and SEMCAD data evaluation software.

Remote control with teach panel and additional circuitry for robot safety such as warning lamps, etc.

The generic twin phantom enabling the testing of left-hand and right-hand usage.

The device holder for handheld Mobile Phones.

Tissue simulating liquid mixed according to the given recipes.

System validation dipoles allowing to validate the proper functioning of the system.



## 6.2. DASY5 E-field Probe System

The SAR measurements were conducted with the dosimetric probe ES3DV3 (manufactured by SPEAG), designed in the classical triangular configuration and optimized for dosimetric evaluation.

- **Probe Specification**

| | |
|---|---|
| Construction | Symmetrical design with triangular core<br>Interleaved sensors<br>Built-in shielding against static charges<br>PEEK enclosure material (resistant to organic solvents, e.g., DGBE) |
| Calibration | ISO/IEC 17025 calibration service available. |
| Frequency | 10 MHz to 4 GHz;<br>Linearity: ± 0.2 dB (30 MHz to 4 GHz) |
| Directivity | ± 0.2 dB in HSL (rotation around probe axis)<br>± 0.3 dB in tissue material (rotation normal to probe axis) |
| Dynamic Range | 5 µW/g to > 100 mW/g;<br>Linearity: ± 0.2 dB |
| Dimensions | Overall length: 337 mm (Tip: 20 mm)<br>Tip diameter: 3.9 mm (Body: 12 mm)<br>Distance from probe tip to dipole centers: 2.0 mm |
| Application | General dosimetry up to 4 GHz<br>Dosimetry in strong gradient fields<br>Compliance tests of Mobile Phones |
| Compatibility | DASY3, DASY4, DASY52 SAR and higher, EASY4/MRI |

- **Isotropic E-Field Probe**

The isotropic E-Field probe has been fully calibrated and assessed for isotropicity, and boundary effect within a controlled environment. Depending on the frequency for which the probe is calibrated the method utilized for calibration will change.

The E-Field probe utilizes a triangular sensor arrangement as detailed in the diagram below:



## 6.3. Phantoms

The phantom used for all tests i.e. for both system checks and device testing, was the twin-headed "SAM Phantom", manufactured by SPEAG. The SAM twin phantom is a fiberglass shell phantom with 2mm shell thickness (except the ear region, where shell thickness increases to 6mm).
System checking was performed using the flat section, whilst Head SAR tests used the left and right head profile sections. Body SAR testing also used the flat section between the head profiles.

SAM Twin Phantom

## 6.4. Device Holder

The device was placed in the device holder (illustrated below) that is supplied by SPEAG as an integral part of the DASY system.
The DASY device holder is designed to cope with the different positions given in the standard. It has two scales for device rotation (with respect to the body axis) and device inclination (with respect to the line between the ear reference points). The rotation centers for both scales is the ear reference point (ERP). Thus the device needs no repositioning when changing the angles.

Device holder supplied by SPEAG

# 7. SAR Test Procedure

## 7.1. Scanning Procedure

The DASY5 installation includes predefined files with recommended procedures for measurements and validation. They are read-only document files and destined as fully defined but unmeasured masks. All test positions (head or body-worn) are tested with the same configuration of test steps differing only in the grid definition for the different test positions.

The “reference” and “drift” measurements are located at the beginning and end of the batch process. They measure the field drift at one single point in the liquid over the complete procedure. The indicated drift is mainly the variation of the DUT’s output power and should vary max. ± 5 %.

The “surface check” measurement tests the optical surface detection system of the DASY5 system by repeatedly detecting the surface with the optical and mechanical surface detector and comparing the results. The output gives the detecting heights of both systems, the difference between the two systems and the standard deviation of the detection repeatability. Air bubbles or refraction in the liquid due to separation of the sugar-water mixture gives poor repeatability (above ± 0.1mm). To prevent wrong results tests are only executed when the liquid is free of air bubbles. The difference between the optical surface detection and the actual surface depends on the probe and is specified with each probe (It does not depend on the surface reflectivity or the probe angle to the surface within ± 30°.)

**Area Scan**
The Area Scan is used as a fast scan in two dimensions to find the area of high field values before running a detailed measurement around the hot spot.Before starting the area scan a grid spacing of 15 mm x 15 mm is set. During the scan the distance of the probe to the phantom remains unchanged. After finishing area scan, the field maxima within a range of 2 dB will be ascertained.

**Zoom Scan**
Zoom Scans are used to estimate the peak spatial SAR values within a cubic averaging volume containing 1 g and 10 g of simulated tissue. The default Zoom Scan is done by 7x7x5 points within a cube whose base is centered around the maxima found in the preceding area scan.

**Spatial Peak Detection**
The procedure for spatial peak SAR evaluation has been implemented and can determine values of masses of 1g and 10g, as well as for user-specific masses.The DASY5 system allows evaluations that combine measured data and robot positions, such as: • maximum search • extrapolation • boundary correction • peak search for averaged SAR During a maximum search, global and local maxima searches are automatically performed in 2-D after each Area Scan measurement with at least 6 measurement points. It is based on the evaluation of the local SAR gradient calculated by the Quadratic Shepard’s method. The algorithm will find the global maximum and all local maxima within -2 dB of the global maxima for all SAR distributions.

Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. Several measurements at different distances are necessary for the extrapolation. Extrapolation routines require at least 10 measurement points in 3-D space. They are used in the Zoom Scan to obtain SAR values between the lowest measurement points and the inner phantom surface. The routine uses the modified Quadratic Shepard’s method for extrapolation. For a grid using 7x7x5 measurement points with 5mm resolution amounting to 343 measurement points, the uncertainty of the extrapolation routines is less than 1% for 1g and 10g cubes.

A Z-axis scan measures the total SAR value at the x-and y-position of the maximum SAR value found during the cube 7x7x5 scan. The probe is moved away in z-direction from the bottom of the SAM phantom in 5mm steps.

## 7.2. Data Storage and Evaluation

**Data Storage**

The DASY5 software stores the acquired data from the data acquisition electronics as raw data (in microvolt readings from the probe sensors),s together with all necessary software parameters for the data evaluation (probe calibration data, liquid parameters and device frequency and modulation data) in measurement files with the extension ".DA4". The software evaluates the desired unit and format for output each time the data is visualized or exported. This allows verification of the complete software setup even after the measurement and allows correction of incorrect parameter settings. For example, if a measurement has been performed with a wrong crest factor parameter in the device setup, the parameter can be corrected afterwards and the data can be re-evaluated.

The measured data can be visualized or exported in different units or formats, depending on the selected probe type ([V/m], [A/m], [°C], [mW/g], [mW/cm²], [dBrel], etc.). Some of these units are not available in certain situations or show meaningless results, e.g., a SAR output in a lossless media will always be zero. Raw data can also be exported to perform the evaluation with other software packages.

**Data Evaluation**

The SEMCAD software automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software:

| | | |
|---|---|---|
| Probe parameters: | Sensitivity: | Normi, ai0, ai1, ai2 |
| | Conversion factor: | ConvFi |
| | Diode compression point: | Dcpi |
| Device parameters: | Frequency: | f |
| | Crest factor: | cf |
| Media parameters: | Conductivity: | σ |
| | Density: | ρ |

These parameters must be set correctly in the software. They can be found in the component documents or they can be imported into the software from the configuration files issued for the DASY5 components. In the direct measuring mode of the multimeter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics. If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given as:

$$V_i = U_i + U_i^2 \cdot \frac{cf}{dcp_i}$$

Vi: compensated signal of channel ( i = x, y, z )
Ui: input signal of channel ( i = x, y, z )
cf: crest factor of exciting field (DASY parameter)
dcpi: diode compression point (DASY parameter)

From the compensated input signals the primary field data for each channel can be evaluated:

$$\mathbf{E} - \text{fieldprobes}: \qquad E_i = \sqrt{\frac{V_i}{Norm_i \cdot ConvF}}$$

$$\mathbf{H} - \text{fieldprobes}: \qquad H_i = \sqrt{V_i} \cdot \frac{a_{i0} + a_{i1} f + a_{i2} f^2}{f}$$

Vi: compensated signal of channel ( i = x, y, z )
Normi: sensor sensitivity of channel ( i = x, y, z ), [mV/(V/m)2] for E-field Probes
ConvF: sensitivity enhancement in solution
aij: sensor sensitivity factors for H-field probes
f: carrier frequency [GHz]
Ei: electric field strength of channel i in V/m
Hi: magnetic field strength of channel i in A/m

The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{tot} = \sqrt{E_x^2 + E_y^2 + E_z^2}$$

The primary field data are used to calculate the derived field units.

$$SAR = E_{tot}^2 \cdot \frac{\sigma}{\rho \cdot 1'000}$$

SAR: local specific absorption rate in mW/g
Etot: total field strength in V/m
σ: conductivity in [mho/m] or [Siemens/m]
ρ: equivalent tissue density in g/cm3

Note that the density is normally set to 1 (or 1.06), to account for actual brain density rather than the density of the simulation liquid.

# 8. Position of the wireless device in relation to the phantom

## 8.1. Head Position

The wireless device define two imaginary lines on the handset, the vertical centreline and the horizontal line, for the handset in vertical orientation as shown in Figures 5a and 5b.
**The vertical centreline** passes through two points on the front side of the handset: the midpoint of the width $W_t$ of the handset at the level of the acoustic output (point A in Figures 5a and 5b), and the midpoint of the width $W_b$ of the bottom of the handset (point B).
**The horizontal line** is perpendicular to the vertical centreline and passes through the centre of the acoustic output (see Figures 5a and 5b). The two lines intersect at point A.
Note that for many handsets, point A coincides with the centre of the acoustic output. However, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centreline is not necessarily parallel to the front face of the handset (see Figure 5b), especially for clam-shell handsets, handsets with flip cover pieces, and other irregularly shaped handsets.




Figures 5a




Figures 5b

| | |
|---|---|
| $W_t$ | Width of the handset at the level of the acoustic |
| $W_b$ | Width of the bottom of the handset |
| A | Midpoint of the widthwt of the handset at the level of the acoustic output |
| B | Midpoint of the width wb of the bottom of the handset |

**Cheek position**




Picture 2 Cheek position of the wireless device on the left side of SAM

**Tilt position**




Picture 3 Tilt position of the wireless device on the left side of SAM

## 8.2. Body Position

Devices that support transmission while used with body-worn accessories must be tested for body-worn accessory SAR compliance, typically according to the smallest test separation distance required for the group of body-worn accessories with similar operating and exposure characteristics.
Devices that are designed to operate on the body of users using lanyards and straps or without requiring additional body-worn accessories must be tested for SAR compliance using a conservative minimum test separation distance **≤ 5 mm** to support compliance




Picture 4 Test positions for body-worn devices

## 8.3. Hotspot Mode Exposure conditions

The hotspot mode and body-worn accessory SAR test configurations may overlap for handsets. When the same wireless mode transmission configurations for voice and data are required for SAR measurements, the more conservative configuration with a smaller separation distance should be tested for the overlapping SAR configurations. This typically applies to the back and front surfaces of a handset when SAR is required for both hotspot mode and body-worn accessory exposure conditions. Depending on the form factor and dimensions of a device, the test separation distance used for hotspot mode SAR measurement is either **10 mm** or that used in the body-worn accessory configuration, whichever is less for devices with dimension > 9 cm x 5 cm. For smaller devices with dimensions ≤ 9 cm x 5 cm because of a greater potential for next to body use a test separation of ≤ 5 mm must be used.



Picture 5 Test positions for Hotspot Mode

# 9. System Check

## 9.1. Tissue Dielectric Parameters

The liquid is consisted of water,salt,Glycol,Sugar,Preventol and Cellulose.The liquid has previously been proven to be suited for worst-case.The table 3 and table 4 show the detail solition.It's satisfying the latest tissue dielectric parameters requirements proposed by the KDB865664.

| Frequency (MHz) | Water (%) | Sugar (%) | Cellulose (%) | Salt (%) | Preventol (%) | DGBE (%) | Conductivity (σ) | Permittivity (εr) |
|---|---|---|---|---|---|---|---|---|
| For Head | | | | | | | | |
| 835 | 40.3 | 57.9 | 0.2 | 1.4 | 0.2 | 0 | 0.9 | 41.5 |
| 1800,1900,2000 | 55.2 | 0 | 0 | 0.3 | 0 | 44.5 | 1.4 | 40 |
| 2450 | 55 | 0 | 0 | 0 | 0 | 45 | 1.8 | 39.2 |
| For Body | | | | | | | | |
| 835 | 50.8 | 48.2 | 0 | 0.9 | 0.1 | 0 | 0.97 | 55.2 |
| 1800.1900.2000 | 70.2 | 0 | 0 | 0.4 | 0 | 29.4 | 1.52 | 53.3 |
| 2450 | 68.6 | 0 | 0 | 0 | 0 | 31.4 | 1.95 | 52.7 |

| Tissue dielectric parameters for head and body phantoms | | | | |
|---|---|---|---|---|
| Target Frequency | Head | | Body | |
| (MHz) | εr | σ(s/m) | εr | σ(s/m) |
| 750 | 41.94 | 0.89 | 55.5 | 0.96 |
| 835 | 41.5 | 0.90 | 55.2 | 0.97 |
| 1800-2000 | 40.0 | 1.40 | 53.3 | 1.52 |
| 2450 | 39.2 | 1.80 | 52.7 | 1.95 |
| 2600 | 39.0 | 1.96 | 52.5 | 2.16 |

**Check Result:**

| Dielectric performance of Head tissue simulating liquid | | | | |
|---|---|---|---|---|
| Frequency (MHz) | Description | DielectricParameters | | Temp |
| | | εr | σ(s/m) | ℃ |
| 750 | Recommended result ±5% window | 41.90 39.81 to 44.00 | 0.89 0.85 to 0.93 | / |
| | Measurement value 2016-09-27 | 41.01 | 0.89 | 21 |
| 835 | Recommended result ±5% window | 41.50 39.43 to 43.58 | 0.90 0.86 to 0.95 | / |
| | Measurement value 2016-09-27 | 41.62 | 0.92 | 21 |
| 1750 | Recommended result ±5% window | 40.10 38.10- 42.11 | 1.37 1.30 - 1.44 | / |
| | Measurement value 2016-09-29 | 40.73 | 1.41 | 21 |
| 1900 | Recommended result ±5% window | 40.0 38.00 to 42.00 | 1.40 1.33 to 1.47 | / |
| | Measurement value 2016-09-30 | 40.05 | 1.42 | 21 |
| 2450 | Recommended result ±5% window | 39.2 37.24 to 41.16 | 1.80 1.71 to 1.89 | / |
| | Measurement value 2016-10-08 | 39.11 | 1.79 | 21 |

| Dielectric performance of Body tissue simulating liquid | | | | |
|---|---|---|---|---|
| Frequency (MHz) | Description | DielectricParameters | | Temp |
| | | εr | σ(s/m) | ℃ |
| 750 | Recommended result ±5% window | 55.50 52.73 to 58.28 | 0.96 0.91 to 1.01 | / |
| | Measurement value 2016-09-27 | 57.87 | 0.97 | 21 |
| 835 | Recommended result ±5% window | 55.2 52.44 to 57.96 | 0.97 0.92 to 1.02 | / |
| | Measurement value 2016-09-28 | 55.15 | 0.96 | 21 |
| 1750 | Recommended result ±5% window | 53.4 50.73–56.07 | 1.49 1.42 - 1.56 | / |
| | Measurement value 2016-09-30 | 53.52 | 1.44 | 21 |
| 1900 | Recommended result ±5% window | 53.3 50.64 to 55.97 | 1.52 1.44 to 1.60 | / |
| | Measurement value 2016-09-29 | 53.12 | 1.53 | 21 |
| 2450 | Recommended result ±5% window | 52.7 50.07 to 55.34 | 1.95 1.85 to 2.05 | / |
| | Measurement value 2016-10-08 | 52.52 | 1.94 | 21 |

## 9.2. SAR System Check

The purpose of the system check is to verify that the system operates within its specifications at the decice test frequency.The system check is simple check of repeatability to make sure that the system works correctly at the time of the compliance test;

System check results have to be equal or near the values determined during dipole calibration with the relevant liquids and test system (±10 %).
System check is performed regularly on all frequency bands where tests are performed with the DASY5 system.




The output power on dipole port must be calibrated to 24 dBm (250mW) before dipole is connected.

Photo of Dipole Setup

**Check Result:**

| Head | | | | |
|---|---|---|---|---|
| Frequency (MHz) | Description | SAR(W/kg) | | Temp |
| | | 1g | 10g | ℃ |
| 750 | Recommended result ±5% window | 2.03<br>1.93 - 2.13 | 1.33<br>1.26 - 1.40 | / |
| | Measurement value 2016-09-27 | 2.08 | 1.39 | 21 |
| 835 | Recommended result ±5% window | 2.41<br>2.29 - 2.53 | 1.57<br>1.49 - 1.65 | / |
| | Measurement value 2016-09-27 | 2.34 | 1.52 | 21 |
| 1750 | Recommended result ±5% window | 9.20<br>8.28 -10.12 | 4.97<br>4.48 - 5.46 | / |
| | Measurement value 2016-09-29 | 9.62 | 4.98 | 21 |
| 1900 | Recommended result ±5% window | 9.71<br>9.22 - 10.20 | 5.08<br>4.83 - 5.33 | / |
| | Measurement value 2016-09-30 | 9.62 | 4.96 | 21 |
| 2450 | Recommended result ±5% window | 13.1<br>11.79 - 14.41 | 6.17<br>5.56 - 6.78 | / |
| | Measurement value 2016-10-08 | 12.40 | 5.80 | 21 |

| Body | | | | |
|---|---|---|---|---|
| Frequency (MHz) | Description | SAR(W/kg) | | Temp |
| | | 1g | 10g | ℃ |
| 750 | Recommended result ±5% window | 2.21<br>2.10 - 2.32 | 1.45<br>1.38 - 1.52 | / |
| | Measurement value 2016-09-28 | 2.26 | 1.46 | 21 |
| 835 | Recommended result ±5% window | 2.47<br>2.35 - 2.59 | 1.64<br>1.55 - 1.71 | / |
| | Measurement value 2016-09-28 | 2.47 | 1.59 | 21 |
| 1750 | Recommended result ±5% window | 9.22<br>8.76 – 9.68 | 4.95<br>4.70 – 5.20 | / |
| | Measurement value 2016-09-30 | 9.30 | 4.99 | 21 |
| 1900 | Recommended result ±5% window | 9.98<br>9.48 – 10.48 | 5.26<br>5.00 – 5.52 | / |
| | Measurement value 2016-09-29 | 10.3 | 5.34 | 21 |
| 2450 | Recommended result ±5% window | 13.1<br>11.79 -14.41 | 6.11<br>5.50 -6.72 | / |
| | Measurement value 2016-10-08 | 12.5 | 5.76 | 21 |

*Note:*

1. *the graph results see follow.*
2. *Recommended Values used derive from the calibration certificate and 250 mW is used asfeeding power to the calibrated dipole.*

**System Performance Check at 750 MHz Head**

DUT: Dipole 750 MHz; Type: D750V3; Serial: 1156
Date:2016-09-27
Communication System: CW; Frequency: 750 MHz;Duty Cycle: 1:1
Medium parameters used (interpolated): f = 750 MHz; σ = 0.89 S/m; εr = 41.01; ρ = 1000 kg/m3
Phantom section: Flat Section

**DASY5 Configuration:**
•Probe: ES3DV3 - SN3292; ConvF(6.76, 6.76, 6.76); Calibrated: 02/09/2016;
•Sensor-Surface: 4mm (Mechanical Surface Detection)
•Electronics: DAE4 Sn1315; Calibrated: 26/07/2016
•Phantom: SAM 1; Type: SAM;
•Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6824)

**Area Scan (61x91x1):**Measurement grid: dx=15.00 mm, dy=15.00 mm
Maximum value of SAR (interpolated) = 2.60 mW/g

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7mm, dy=7mm, dz=5mm
Reference Value = 55.49 V/m; Power Drift = -0.04 dB
Peak SAR (extrapolated) = 3.07 W/kg
**SAR(1 g) = 2.08 W/kg; SAR(10 g) = 1.39 W/kg**
Maximum value of SAR (measured) = 2.62 W/kg



System Performance Check 750MHz Head 250mW

**System Performance Check at 750 MHz Body**

DUT: Dipole 750 MHz; Type: D750V3; Serial: 1156
Date:2016-09-28
Communication System: CW; Frequency: 750 MHz;Duty Cycle: 1:1
Medium parameters used (interpolated): f = 750 MHz; $\sigma$ = 0.97 S/m; $\varepsilon_r$ = 57.87; $\rho$ = 1000 kg/m$^3$
Phantom section: Flat Section

**DASY5 Configuration:**
•Probe: ES3DV3 - SN3292; ConvF(6.25, 6.25, 6.25); Calibrated: 02/09/2016;
•Sensor-Surface: 4mm (Mechanical Surface Detection)
•Electronics: DAE4 Sn1315; Calibrated: 26/07/2016
•Phantom: SAM 1; Type: SAM;
•Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6824)

**Area Scan (61x91x1):**Measurement grid: dx=15.00 mm, dy=15.00 mm
Maximum value of SAR (interpolated) = 2.89 mW/g
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 51.70 V/m; Power Drift = 0.03 dB
Peak SAR (extrapolated) = 3.87 W/kg
**SAR(1 g) = 2.26 W/kg; SAR(10 g) = 1.46 W/kg**
Maximum value of SAR (measured) = 2.89 W/kg



System Performance Check 750MHz Body 250mW

**System Performance Check at 835 MHz Head**

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d134
Date:2016-09-27
Communication System: CW; Frequency: 835 MHz;Duty Cycle: 1:1
Medium parameters used (interpolated): f = 835 MHz; σ = 0.92 S/m; εr = 41.62; ρ = 1000 kg/m3
Phantom section: Flat Section

**DASY5 Configuration:**
•Probe: ES3DV3 - SN3292; ConvF(6.53, 6.53, 6.53); Calibrated: 02/09/2016;
•Sensor-Surface: 4mm (Mechanical Surface Detection)
•Electronics: DAE4 Sn1315; Calibrated: 26/07/2016
•Phantom: SAM 1; Type: SAM;
•Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6824)

**Area Scan (61x91x1):**Measurement grid: dx=15.00 mm, dy=15.00 mm
Maximum value of SAR (interpolated) = 2.834 mW/g

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7mm, dy=7mm, dz=5mm
Reference Value = 49.865 V/m; Power Drift = -0.01 dB
Peak SAR (extrapolated) = 3.286 W/kg
**SAR(1 g) = 2.34 mW/g; SAR(10 g) = 1.52 mW/g**

Maximum value of SAR (measured) = 2.825 mW/g




System Performance Check 835MHz Head 250mW

**System Performance Check at 835 MHz Body**

DUT: Dipole 835 MHz; Type: D835V2; Serial: 4d134
Date:2016-09-28
Communication System: CW; Frequency: 835 MHz;Duty Cycle: 1:1
Medium parameters used (interpolated): f = 835 MHz; σ = 0.96 S/m; $\varepsilon_r$ = 55.15; ρ = 1000 kg/m$^3$
Phantom section: Flat Section

**DASY5 Configuration:**
•Probe: ES3DV3 - SN3292; ConvF(6.27, 6.27, 6.27); Calibrated: 02/09/2016;
•Sensor-Surface: 4mm (Mechanical Surface Detection)
•Electronics: DAE4 Sn1315; Calibrated: 26/07/2016
•Phantom: SAM 1; Type: SAM;
•Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6824)

**Area Scan (61x91x1):**Measurement grid: dx=15.00 mm, dy=15.00 mm
Maximum value of SAR (interpolated) = 2.888 mW/g
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 50.236 V/m; Power Drift = -0.02 dB
Peak SAR (extrapolated) = 3.339 W/kg
**SAR(1 g) = 2.47 mW/g; SAR(10 g) = 1.59 mW/g**

Maximum value of SAR (measured) = 2.871 mW/g



System Performance Check 835MHz Body 250mW

**System Performance Check at 1750 MHz Head**

DUT: Dipole 1750 MHz; Type: D1750V2; Serial: D1750V2
Date:2016-09-29
Communication System: CW; Frequency: 1750 MHz;Duty Cycle: 1:1
Medium parameters used (interpolated): f =1750 MHz; σ =1.41 S/m; εr =40.73; ρ =1000 kg/m3
Phantom section: Flat Section

DASY5 Configuration:
Probe: ES3DV3 - SN3292; ConvF(5.54,5.54,5.54); Calibrated: 02/09/2016;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1315; Calibrated: 26/07/2016
Phantom: SAM 1; Type: SAM;
Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

**Area Scan** (61x91x1): Measurement grid: dx=15.00 mm, dy=15.00 mm
Maximum value of SAR (interpolated) = 12.6 W/kg
**Zoom Scan** (7x7x5)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 99.561 V/m; Power Drift = -0.03 dB
Peak SAR (extrapolated) = 16.828 mW/g

**SAR(1 g) =9.62 mW/g; SAR(10 g) = 4.98 mW/g**

Maximum value of SAR (measured) = 13.0 W/kg




System Performance Check 1750MHz 250mW

**System Performance Check at 1750 MHz Body**

DUT: Dipole 1750 MHz; Type: D1750V2; Serial: D1750V2
Date:2016-09-30
Communication System: CW; Frequency: 1750 MHz;Duty Cycle: 1:1
Medium parameters used (interpolated): f =1750 MHz; σ =1.44 S/m; εr =53.52; ρ =1000 kg/m3
Phantom section: Flat Section

DASY5 Configuration:
Probe: ES3DV3 - SN3292; ConvF(5.28,5.28,5.28); Calibrated: 02/09/2016;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1315; Calibrated: 26/07/2016
Phantom: SAM 1; Type: SAM;
Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

**AreaScan(61x61x1):**Measurementgrid:dx=15mm,dy=15mm
MaximumvalueofSAR(interpolated)=13.354mW/g

**ZoomScan(5x5x7)/Cube0:**Measurementgrid:dx=8mm,dy=8mm,dz=5mm
ReferenceValue=87.582V/m;PowerDrift=-0.06dB
Peak SAR (extrapolated) = 16.752 W/kg
**SAR(1 g) = 9.30 mW/g; SAR(10 g) = 4.99 mW/g**
Maximum value of SAR (measured) = 13.273 mW/g




System Performance Check 1750MHz 250mW

**System Performance Check at 1900 MHz Head**

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d150
Date:2016-09-30
Communication System: CW; Frequency: 1900 MHz;Duty Cycle: 1:1
Medium parameters used (interpolated): f = 1900 MHz; σ = 1.42S/m; εr = 40.05; ρ = 1000 kg/m3
Phantom section: Flat Section

**DASY5 Configuration:**
Probe: ES3DV3 - SN3292; ConvF(5.26,5.26,5.26); Calibrated: 02/09/2016;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1315; Calibrated: 26/07/2016
Phantom: SAM 1; Type: SAM;
Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

**Area Scan (61x91x1):**Measurement grid: dx=15.00 mm, dy=15.00 mm
Maximum value of SAR (interpolated) = 10.61 W/kg

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=7mm, dy=7mm, dz=5mm
Reference Value = 94.79 V/m; Power Drift = -0.06 dB
Peak SAR (extrapolated) = 12.34 W/kg

**SAR(1 g) = 9.62 W/kg; SAR(10 g) = 4.96 W/kg**

Maximum value of SAR (measured) = 12.44 W/kg



System Performance Check 1900MHz Head 250mW

**System Performance Check at 1900 MHz Body**

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: 5d150
Date:2016-09-29
Communication System: CW; Frequency: 1900 MHz;Duty Cycle: 1:1
Medium parameters used (interpolated): f = 1900 MHz; σ = 1.53S/m; εr = 53.12; ρ = 1000 kg/m3
Phantom section: Flat Section

**DASY5 Configuration:**
Probe: ES3DV3 - SN3292; ConvF(5.05,5.05,5.05); Calibrated: 02/09/2016;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1315; Calibrated: 26/07/2016
Phantom: SAM 1; Type: SAM;
Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

**Area Scan (61x91x1):**Measurement grid: dx=15.00 mm, dy=15.00 mm
Maximum value of SAR (interpolated) = 15.187 mW/g
**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 87.679 V/m; Power Drift = -0.14 dB
Peak SAR (extrapolated) = 19.027 W/kg
**SAR(1 g) = 10.3 mW/g; SAR(10 g) = 5.34 mW/g**

Maximum value of SAR (measured) = 15.09 mW/g



System Performance Check 1900MHz Body250mW

**System Performance Check at 2450 MHz Head**

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 884
Date:2016-10-08
Communication System: CW; Frequency: 2450 MHz;Duty Cycle: 1:1
Medium parameters used (interpolated): f = 2450 MHz; σ = 1.79S/m; εr = 39.11; ρ = 1000 kg/m3
Phantom section: Flat Section

**DASY5 Configuration:**
Probe: ES3DV3 - SN3292; ConvF(4.97,4.97,4.97); Calibrated: 02/09/2016;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1315; Calibrated: 26/07/2016
Phantom: SAM 1; Type: SAM;
Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

**Area Scan (61x91x1):**Measurement grid: dx=10.00 mm, dy=10.00 mm
Maximum value of SAR (interpolated) = 19.313 mW/g
**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 84.314 V/m; Power Drift = 0.02 dB
Peak SAR (extrapolated) = 25.703 W/kg
**SAR(1 g) = 12.4 mW/g; SAR(10 g) = 5.8 mW/g**

Maximum value of SAR (measured) = 18.871 mW/g




System Performance Check 2450MHz Head250mW

**System Performance Check at 2450 MHz Body**
Date:2016-10-08
DUT: Dipole 2450 MHz; Type: D2450V2; Serial: 884

Communication System: CW; Frequency: 2450 MHz;Duty Cycle: 1:1
Medium parameters used (interpolated): f = 2450 MHz; σ = 1.94S/m; εr = 52.52; ρ = 1000 kg/m3
Phantom section: Flat Section

**DASY5 Configuration:**
Probe: ES3DV3 - SN3292; ConvF(4.70,4.70,4.70); Calibrated: 02/09/2016;
Sensor-Surface: 3mm (Mechanical Surface Detection)
Electronics: DAE4 Sn1315; Calibrated: 26/07/2016
Phantom: SAM 1; Type: SAM;
Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

**Area Scan (61x91x1):**Measurement grid: dx=10.00 mm, dy=10.00 mm
Maximum value of SAR (interpolated) = 19.266 mW/g
**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 84.170 V/m; Power Drift = 0.03 dB
Peak SAR (extrapolated) = 26.174 W/kg
**SAR(1 g) = 12.5 mW/g; SAR(10 g) = 5.76 mW/g**

Maximum value of SAR (measured) = 19.27mW/g




System Performance Check 2450MHz Body250mW

# 10. SAR Exposure Limits

SAR assessments have been made in line with the requirements of ANSI/IEEE C95.1-1992

| Type Exposure | Limit (W/kg) | |
|---|---|---|
| | General Population / Uncontrolled Exposure Environment | Occupational / Controlled Exposure Environment |
| Spatial Average SAR (whole body) | 0.08 | 0.4 |
| Spatial Peak SAR (1g cube tissue for head and trunk) | 1.60 | 8.0 |
| Spatial Peak SAR (10g for limb) | 4.0 | 20.0 |

Population/Uncontrolled Environments: are defined as locations where there is the exposure of individual who have no knowledge or control of their exposure.

Occupational/Controlled Environments: are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure (i.e. as a result of employment or occupation).

# 11. Conducted Power Measurement Results

## GSM Conducted Power

1. *Per KDB 447498 D01, the maximum output power channel is used for SAR testing and further SAR test reduction*
2. *Per KDB 941225 D01, considering the possibility of e.g. 3rd party VoIP operation for Head and Body-worn SAR test reduction for GSM and GPRS modes is determined by the source-base time-averaged output power including tune-up tolerance. The mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested. Therefore, the EUT was set in GPRS (4Tx slots) for GSM850 and GPRS (4Tx slots) for PCS1900.*
3. *Per KDB941225 D01, for hotspot SAR test reduction for GPRS modes is determined by the source-based time-averaged output power including tune-up tolerance, For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested. Therefore, the EUT was set in GPRS (4Tx slots) for GSM850 and GPRS (4Tx slots) for PCS1900.*

| **Mode: GSM850** | | **Conducted Power (dBm)** | | | Division Factors | **Averager Power (dBm)** | | |
|---|---|---|---|---|---|---|---|---|
| | | CH128 | CH190 | CH251 | | CH128 | CH190 | CH251 |
| | | 824.2MHz | 836.6MHz | 848.8MHz | | 824.2MHz | 836.6MHz | 848.8MHz |
| GSM | | 32.91 | 33.15 | 33.28 | -9.03 | 23.88 | 24.12 | 24.25 |
| GPRS (GMSK) | 1TXslot | 32.88 | 33.12 | 33.26 | -9.03 | 23.85 | 24.09 | 24.23 |
| | 2TXslots | 30.31 | 30.61 | 30.72 | -6.02 | 24.29 | 24.59 | 24.70 |
| | 3TXslots | 28.59 | 28.83 | 28.92 | -4.26 | 24.33 | 24.57 | 24.66 |
| | 4TXslots | 27.35 | 27.56 | 27.65 | -3.01 | 24.34 | 24.55 | 24.64 |
| EGPRS (GMSK) | 1TXslot | 32.86 | 33.11 | 33.22 | -9.03 | 23.83 | 24.08 | 24.19 |
| | 2TXslots | 30.26 | 30.57 | 30.67 | -6.02 | 24.24 | 24.55 | 24.65 |
| | 3TXslots | 28.55 | 28.80 | 28.87 | -4.26 | 24.29 | 24.54 | 24.61 |
| | 4TXslots | 27.31 | 27.52 | 27.60 | -3.01 | 24.30 | 24.51 | 24.59 |
| **Mode: PCS1900** | | **Conducted Power (dBm)** | | | Division Factors | **Averager Power (dBm)** | | |
| | | CH512 | CH661 | CH810 | | CH512 | CH661 | CH810 |
| | | 1850.2MHz | 1880.0MHz | 1909.8MHz | | 1850.2MHz | 1880.0MHz | 1909.8MHz |
| GSM | | 30.52 | 30.41 | 30.44 | -9.03 | 21.49 | 21.38 | 21.41 |
| GPRS (GMSK) | 1TXslot | 30.49 | 30.38 | 30.43 | -9.03 | 21.46 | 21.35 | 21.40 |
| | 2TXslots | 28.11 | 28.08 | 28.10 | -6.02 | 22.09 | 22.06 | 22.08 |
| | 3TXslots | 26.51 | 26.45 | 26.45 | -4.26 | 22.25 | 22.19 | 22.19 |
| | 4TXslots | 25.36 | 25.28 | 25.29 | -3.01 | 22.35 | 22.27 | 22.28 |
| EGPRS (GMSK) | 1TXslot | 30.48 | 30.35 | 30.42 | -9.03 | 21.45 | 21.32 | 21.39 |
| | 2TXslots | 28.07 | 28.02 | 28.08 | -6.02 | 22.05 | 22.00 | 22.06 |
| | 3TXslots | 26.48 | 26.40 | 26.43 | -4.26 | 22.22 | 22.14 | 22.17 |
| | 4TXslots | 25.33 | 25.23 | 25.27 | -3.01 | 22.32 | 22.22 | 22.26 |

Note:

1) Division Factors

To average the power, the division factor is as follows:

1TX-slot = 1 transmit time slot out of 8 time slots=> conducted power divided by (8/1) => -9.03dB

2TX-slots = 2 transmit time slots out of 8 time slots=> conducted power divided by (8/2) => -6.02dB

3TX-slots = 3 transmit time slots out of 8 time slots=> conducted power divided by (8/3) => -4.26dB

4TX-slots = 4 transmit time slots out of 8 time slots=> conducted power divided by (8/4) => -3.01dB

## WCDMA Conducted Power

1. *The following tests were conducted according to the test requirements outlines in 3GPP TS34.121 specification.*
2. *The procedures in KDB 941225 D01 are applied for 3GPP Rel. 6 HSPA to configure the device in the required sub-test mode to determine SAR test exclusion*

A summary of thest setting are illustrated belowe:

**HSDPA Setup Configureation:**

a) The EUT was connected to base station RS CMU200 referred to the setup configuration
b) The RF path losses were compensated into the measurements
c) A call was established between EUT and base station with following setting:
   i. Set Gain Factors (βc and βd) and parameters were set according to each specific sub-test in the following table, C10.1.4, Quoted from the TS 34.121
   ii. Set RMC 12.2Kbps + HSDPA mode
   iii. Set Cell Power=-86dBm
   iv. Set HS-DSCH Configuration Type to FRC (H-set 1, QPSK)
   v. Select HSDPA uplink parameters
   vi. Set Delta ACK, Delta NACK and Delta CQI=8
   vii. Set Ack-Nack repetition Factor to 3
   viii. Set CQI Feedback Cycle (K) to 4ms
   ix. Set CQI repetition factor to 2
   x. Power ctrl mode= all up bits
d) The transmitter maximum output power waw recorded.

**Table C.10.1.4: β values for transmitter characteristics tests with HS-DPCCH**

| Sub-test | $\beta_c$ | $\beta_d$ | $\beta_d$ (SF) | $\beta_c/\beta_d$ | $\beta_{HS}$ (Note1, Note 2) | CM (dB) (Note 3) | MPR (dB) (Note 3) |
|---|---|---|---|---|---|---|---|
| 1 | 2/15 | 15/15 | 64 | 2/15 | 4/15 | 0.0 | 0.0 |
| 2 | 12/15 (Note 4) | 15/15 (Note 4) | 64 | 12/15 (Note 4) | 24/15 | 1.0 | 0.0 |
| 3 | 15/15 | 8/15 | 64 | 15/8 | 30/15 | 1.5 | 0.5 |
| 4 | 15/15 | 4/15 | 64 | 15/4 | 30/15 | 1.5 | 0.5 |

Note 1: $\Delta_{ACK}$, $\Delta_{NACK}$ and $\Delta_{CQI}$ = 30/15 with $\beta_{hs}$ = 30/15 * $\beta_c$.

Note 2: For the HS-DPCCH power mask requirement test in clause 5.2C, 5.7A, and the Error Vector Magnitude (EVM) with HS-DPCCH test in clause 5.13.1A, and HSDPA EVM with phase discontinuity in clause 5.13.1AA, $\Delta_{ACK}$ and $\Delta_{NACK}$ = 30/15 with $\beta_{hs}$ = 30/15 * $\beta_c$, and $\Delta_{CQI}$ = 24/15 with $\beta_{hs}$ = 24/15 * $\beta_c$.

Note 3: CM = 1 for $\beta_c/\beta_d$ =12/15, $\beta_{hs}/\beta_c$=24/15. For all other combinations of DPDCH, DPCCH and HS-DPCCH the MPR is based on the relative CM difference. This is applicable for only UEs that support HSDPA in release 6 and later releases.

Note 4: For subtest 2 the $\beta_c/\beta_d$ ratio of 12/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c$ = 11/15 and $\beta_d$ = 15/15.

**Setup Configuration**

**HSUPA Setup Configureation:**

a) The EUT was connected to base station RS CMU200 referred to the setup configuration
b) The RF path losses were compensated into the measurements
c) A call was established between EUT and base station with following setting:
   i. Call configs = 5.2b, 5.9b, 5.10b, and 5.13.2B with QPSK
   ii. Set Gain Factors (βc and βd) and parameters (AG index) were set according to each specific sub-test in the following table, C11.1.3, Quoted from the TS 34.121
   iii. Set Cell Power=-86dBm
   iv. Set channel type= 12.2Kbps + HSPA mode
   v. Set UE Target power
   vi. Set Ctrl mode=Alternating bits
   vii. Set and observe the E-TFCI
   viii. Confirm that E-TFCI is equal the target E-TFCI of 75 for Sub-test 1, and other subtest's E-TFCI
d) The transmitter maximum output power waw recorded.

**Table C.11.1.3: β values for transmitter characteristics tests with HS-DPCCH and E-DCH**

| Sub-test | $\beta_c$ | $\beta_d$ | $\beta_d$ (SF) | $\beta_c/\beta_d$ | $\beta_{HS}$ (Note1) | $\beta_{ec}$ | $\beta_{ed}$ (Note 5) (Note 6) | $\beta_{ed}$ (SF) | $\beta_{ed}$ (Codes) | CM (dB) (Note 2) | MPR (dB) (Note 2) | AG Index (Note 6) | E-TFCI |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 1 | 11/15 (Note 3) | 15/15 (Note 3) | 64 | 11/15 (Note 3) | 22/15 | 209/225 | 1309/225 | 4 | 1 | 1.0 | 0.0 | 20 | 75 |
| 2 | 6/15 | 15/15 | 64 | 6/15 | 12/15 | 12/15 | 94/75 | 4 | 1 | 3.0 | 2.0 | 12 | 67 |
| 3 | 15/15 | 9/15 | 64 | 15/9 | 30/15 | 30/15 | $\beta_{ed}1$: 47/15<br>$\beta_{ed}2$: 47/15 | 4<br>4 | 2 | 2.0 | 1.0 | 15 | 92 |
| 4 | 2/15 | 15/15 | 64 | 2/15 | 4/15 | 2/15 | 56/75 | 4 | 1 | 3.0 | 2.0 | 17 | 71 |
| 5 | 15/15 (Note 4) | 15/15 (Note 4) | 64 | 15/15 (Note 4) | 30/15 | 24/15 | 134/15 | 4 | 1 | 1.0 | 0.0 | 21 | 81 |

Note 1: $\Delta_{ACK}$, $\Delta_{NACK}$ and $\Delta_{CQI}$ = 30/15 with $\beta_{hs}$ = 30/15 * $\beta_c$ .

Note 2: CM = 1 for $\beta_c/\beta_d$ =12/15, $\beta_{hs}/\beta_c$=24/15. For all other combinations of DPDCH, DPCCH, HS- DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.

Note 3: For subtest 1 the $\beta_c/\beta_d$ ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c$ = 10/15 and $\beta_d$ = 15/15.

Note 4: For subtest 5 the $\beta_c/\beta_d$ ratio of 15/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c$ = 14/15 and $\beta_d$ = 15/15.

Note 5: In case of testing by UE using E-DPDCH Physical Layer category 1, Sub-test 3 is omitted according to TS25.306 Table 5.1g.

Note 6: $\beta_{ed}$ can not be set directly, it is set by Absolute Grant Value.

**Setup Configuration**

**General Note:**

1. Per KDB 941225 D01, SAR for Head / Hotsport / Body-worn Exposure is measured using a 12.2Kbps RMC with TPC bit ocnfigured to all 1s
2. Per KDB 941225 D01 RMC12.2Kbps setting is used to evaluate SAR. If the maximum output power and Tune-up tolerance specified for production units in HSDPA/HSUPA is ≦1/4dB higher than RMC 12.2Kbps or when the highest reported SAR of the RMC12.2Kbps is scaled by the ratio fo specified maximum output power and tune-up tolerance of HSDPA / HSUPA to RMC 12.2Kbps and the adjusted SAR is ≦1.2 W/kg, SAR measurement is not required for HSDPA / HSUPA.

| Mode | | WCDMA Band V | | | WCDMA Band II | | |
|---|---|---|---|---|---|---|---|
| | | Conducted Power (dBm) | | | Conducted Power (dBm) | | |
| | | CH4132 | CH4183 | CH4233 | CH9262 | CH9400 | CH9538 |
| | | 826.4 | 836.6 | 846.6 | 1852.4 | 1880.0 | 1907.6 |
| AMR 12.2K | | 23.21 | 23.24 | 23.11 | 23.95 | 23.91 | 23.96 |
| RMC 12.2K | | 23.24 | 23.29 | 23.12 | 23.98 | 23.94 | 23.97 |
| HSDPA | Subtest-1 | 21.34 | 21.37 | 21.25 | 22.02 | 21.98 | 22.03 |
| | Subtest-2 | 21.17 | 21.19 | 21.07 | 21.84 | 21.80 | 21.85 |
| | Subtest-3 | 21.17 | 21.21 | 21.06 | 21.84 | 21.81 | 21.84 |
| | Subtest-4 | 20.89 | 20.92 | 20.80 | 21.56 | 21.52 | 21.56 |
| HSUPA | Subtest-1 | 20.77 | 20.80 | 20.68 | 21.44 | 21.40 | 21.44 |
| | Subtest-2 | 20.61 | 20.64 | 20.52 | 21.27 | 21.23 | 21.28 |
| | Subtest-3 | 20.52 | 20.54 | 20.43 | 21.17 | 21.14 | 21.18 |
| | Subtest-4 | 20.46 | 20.48 | 20.37 | 21.11 | 21.07 | 21.12 |
| | Subtest-5 | 20.40 | 20.43 | 20.32 | 21.05 | 21.02 | 21.06 |

## LTE Conducted Power

**General Note:**

*1. CMW500 base station simulator was used to setup the connection with EUT; the frequency band, channel,bandwidth, RB allocation configuration, modulation type are set in the base station simulator to configure EUTtransmitting at maximum power and at different configurations which are requested to be reported to FCC, forconducted power measurement and SAR testing.*
*2. Per KDB 941225 D05v02r03, when a properly configured base station simulator is used for the SAR and powermeasurements, spectrum plots for each RB allocation and offset configuration is not required.*
*3. Per KDB 941225 D05v02r03, start with the largest channel bandwidth and measure SAR for QPSK with 1 RBallocation, using the RB offset and required test channel combination with the highest maximum output power for RBoffsets at the upper edge, middle and lower edge of each required test channel.*
*4. Per KDB 941225 D05v02r03, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.*
*5. Per KDB 941225 D05v02r03, for QPSK with 100% RB allocation, SAR is not required when the highest maximumoutput power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations andthe highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highestoutput power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also betested.*
*6. Per KDB 941225 D05v02r03, 16QAM output power for each RB allocation configuration is > not ½ dB higher than thesame configuration in QPSK and the reported SAR for the QPSK configuration is ≤ 1.45 W/kg; Per KDB 941225D05v02r03, 16QAM SAR testing is not required.*
*7. Per KDB 941225 D05v02r03, smaller bandwidth output power for each RB allocation configuration is > not ½ dBhigher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supportedbandwidth is ≤ 1.45 W/kg; Per KDB 941225 D05v02r03, smaller bandwidth SAR testing is not required.*

| LTE-FDD Band 2 | | | | Actual output Power (dBm) | | |
|---|---|---|---|---|---|---|
| **Band-width** | **RBallocation** | **RBoffset** | **Modulation** | **Low** | **Middle** | **High** |
| 1.4 MHz | | | | **1850.7MHz** | **1880MHz** | **1909.3MHz** |
| | 1RB | **High** | **QPSK** | 22.14 | 22.19 | 22.11 |
| | | | **16QAM** | 21.27 | 21.31 | 21.24 |
| | | **Middle** | **QPSK** | 22.13 | 22.18 | 22.08 |
| | | | **16QAM** | 21.28 | 21.33 | 21.25 |
| | | **Low** | **QPSK** | 22.15 | 22.15 | 22.08 |
| | | | **16QAM** | 21.3 | 21.33 | 21.26 |
| | 3RB | **High** | **QPSK** | 22.02 | 22.08 | 21.98 |
| | | | **16QAM** | 21.04 | 21.07 | 20.99 |
| | | **Middle** | **QPSK** | 22.03 | 22.06 | 21.99 |
| | | | **16QAM** | 21.06 | 21.1 | 21 |
| | | **Low** | **QPSK** | 22.02 | 22.09 | 22.01 |
| | | | **16QAM** | 21.04 | 21.09 | 21.01 |
| | 6RB | / | **QPSK** | 21.19 | 21.25 | 21.14 |
| | | | **16QAM** | 20.13 | 20.18 | 20.1 |
| 3 MHz | | | | **1851.5MHz** | **1880MHz** | **1908.5MHz** |
| | 1RB | **High** | **QPSK** | 22.12 | 22.16 | 22.09 |
| | | | **16QAM** | 21.31 | 21.34 | 21.27 |
| | | **Middle** | **QPSK** | 22.1 | 22.16 | 22.07 |
| | | | **16QAM** | 21.32 | 21.37 | 21.28 |
| | | **Low** | **QPSK** | 22.12 | 22.17 | 22.09 |
| | | | **16QAM** | 21.3 | 21.34 | 21.26 |
| | 8RB | **High** | **QPSK** | 21.47 | 21.51 | 21.42 |
| | | | **16QAM** | 20.42 | 20.46 | 20.39 |
| | | **Middle** | **QPSK** | 21.42 | 21.44 | 21.39 |
| | | | **16QAM** | 20.41 | 20.46 | 20.37 |
| | | **Low** | **QPSK** | 21.43 | 21.47 | 21.4 |
| | | | **16QAM** | 20.43 | 20.46 | 20.41 |
| | 15RB | / | **QPSK** | 21.39 | 21.45 | 21.37 |
| | | | **16QAM** | 20.4 | 20.47 | 20.35 |

| | | | | | | |
|---|---|---|---|---|---|---|
| 5 MHz | | | | **1852.5MHz** | **1880MHz** | **1907.5MHz** |
| | 1RB | **High** | **QPSK** | 22.1 | 22.14 | 22.07 |
| | | | **16QAM** | 21.3 | 21.34 | 21.27 |
| | | **Middle** | **QPSK** | 22.12 | 22.17 | 22.09 |
| | | | **16QAM** | 21.32 | 21.37 | 21.27 |
| | | **Low** | **QPSK** | 22.11 | 22.14 | 22.06 |
| | | | **16QAM** | 21.3 | 21.34 | 21.27 |
| | 12RB | **High** | **QPSK** | 21.48 | 21.54 | 21.42 |
| | | | **16QAM** | 20.47 | 20.55 | 20.44 |
| | | **Middle** | **QPSK** | 21.48 | 21.53 | 21.45 |
| | | | **16QAM** | 20.48 | 20.53 | 20.43 |
| | | **Low** | **QPSK** | 21.47 | 21.51 | 21.44 |
| | | | **16QAM** | 20.5 | 20.54 | 20.47 |
| | 25RB | | **QPSK** | 21.45 | 21.5 | 21.42 |
| | | | **16QAM** | 20.44 | 20.48 | 20.4 |
| 10 MHz | | | | **1855MHz** | **1880MHz** | **1905MHz** |
| | 1RB | **High** | **QPSK** | 22.11 | 22.15 | 22.07 |
| | | | **16QAM** | 21.29 | 21.33 | 21.26 |
| | | **Middle** | **QPSK** | 22.12 | 22.17 | 22.08 |
| | | | **16QAM** | 21.31 | 21.36 | 21.26 |
| | | **Low** | **QPSK** | 22.12 | 22.17 | 22.08 |
| | | | **16QAM** | 21.31 | 21.34 | 21.27 |
| | 25RB | **High** | **QPSK** | 21.44 | 21.5 | 21.42 |
| | | | **16QAM** | 20.47 | 20.52 | 20.44 |
| | | **Middle** | **QPSK** | 21.44 | 21.5 | 21.42 |
| | | | **16QAM** | 20.51 | 20.54 | 20.46 |
| | | **Low** | **QPSK** | 21.43 | 21.48 | 21.4 |
| | | | **16QAM** | 20.49 | 20.53 | 20.46 |
| | 50RB | **/** | **QPSK** | 21.46 | 21.5 | 21.41 |
| | | | **16QAM** | 20.45 | 20.49 | 20.4 |
| 15 MHz | | | | **1857.5MHz** | **1880MHz** | **1902.5MHz** |
| | 1RB | **High** | **QPSK** | 22.14 | 22.18 | 22.11 |
| | | | **16QAM** | 21.3 | 21.34 | 21.27 |
| | | **Middle** | **QPSK** | 22.11 | 22.18 | 22.07 |
| | | | **16QAM** | 21.31 | 21.37 | 21.27 |
| | | **Low** | **QPSK** | 22.13 | 22.17 | 22.1 |
| | | | **16QAM** | 21.32 | 21.36 | 21.29 |
| | 36RB | **High** | **QPSK** | 21.46 | 21.51 | 21.43 |
| | | | **16QAM** | 20.47 | 20.5 | 20.43 |
| | | **Middle** | **QPSK** | 21.44 | 21.5 | 21.39 |
| | | | **16QAM** | 20.49 | 20.53 | 20.44 |
| | | **Low** | **QPSK** | 21.47 | 21.53 | 21.45 |
| | | | **16QAM** | 20.45 | 20.5 | 20.42 |
| | 75RB | **/** | **QPSK** | 21.37 | 21.42 | 21.34 |
| | | | **16QAM** | 20.4 | 20.46 | 20.37 |

| | | | | 1860MHz | 1880MHz | 1900MHz |
|---|---|---|---|---|---|---|
| 20 MHz | 1RB | **High** | **QPSK** | 22.10 | 22.17 | 22.07 |
| | | | **16QAM** | 21.3 | 21.36 | 21.28 |
| | | **Middle** | **QPSK** | 22.13 | 22.18 | 22.1 |
| | | | **16QAM** | 21.33 | 21.36 | 21.27 |
| | | **Low** | **QPSK** | 22.15 | 22.19 | 22.12 |
| | | | **16QAM** | 21.33 | 21.37 | 21.3 |
| | 50RB | **High** | **QPSK** | 21.47 | 21.54 | 21.35 |
| | | | **16QAM** | 20.45 | 20.52 | 20.42 |
| | | **Middle** | **QPSK** | 21.46 | 21.51 | 21.43 |
| | | | **16QAM** | 20.51 | 20.56 | 20.48 |
| | | **Low** | **QPSK** | 21.47 | 21.51 | 21.44 |
| | | | **16QAM** | 20.52 | 20.56 | 20.49 |
| | 100RB | / | **QPSK** | 21.40 | 21.47 | 21.35 |
| | | | **16QAM** | 20.39 | 20.46 | 20.34 |

| LTE-FDD Band 4 | | | | Actual output Power (dBm) | | |
|---|---|---|---|---|---|---|
| **Band-width** | **RBallocation** | **RBoffset** | **Modulation** | **Low** | **Middle** | **High** |
| 1.4 MHz | | | | **1710.7MHz** | **1732.5MHz** | **1754.3MHz** |
| | 1RB | **High** | **QPSK** | 22.33 | 22.37 | 22.34 |
| | | | **16QAM** | 21.46 | 21.49 | 21.47 |
| | | **Middle** | **QPSK** | 22.32 | 22.36 | 22.31 |
| | | | **16QAM** | 21.47 | 21.51 | 21.48 |
| | | **Low** | **QPSK** | 22.34 | 22.33 | 22.31 |
| | | | **16QAM** | 21.49 | 21.51 | 21.49 |
| | 3RB | **High** | **QPSK** | 22.21 | 22.26 | 22.21 |
| | | | **16QAM** | 21.23 | 21.25 | 21.22 |
| | | **Middle** | **QPSK** | 22.22 | 22.24 | 22.22 |
| | | | **16QAM** | 21.25 | 21.28 | 21.23 |
| | | **Low** | **QPSK** | 22.21 | 22.27 | 22.24 |
| | | | **16QAM** | 21.23 | 21.27 | 21.24 |
| | 6RB | / | **QPSK** | 21.38 | 21.43 | 21.37 |
| | | | **16QAM** | 20.32 | 20.36 | 20.33 |
| 3 MHz | | | | **1711.5MHz** | **1732.5MHz** | **1753.5MHz** |
| | 1RB | **High** | **QPSK** | 22.31 | 22.34 | 22.32 |
| | | | **16QAM** | 21.5 | 21.52 | 21.5 |
| | | **Middle** | **QPSK** | 22.29 | 22.34 | 22.3 |
| | | | **16QAM** | 21.51 | 21.55 | 21.51 |
| | | **Low** | **QPSK** | 22.31 | 22.35 | 22.32 |
| | | | **16QAM** | 21.49 | 21.52 | 21.49 |
| | 8RB | **High** | **QPSK** | 21.66 | 21.69 | 21.65 |
| | | | **16QAM** | 20.61 | 20.64 | 20.62 |
| | | **Middle** | **QPSK** | 21.61 | 21.62 | 21.62 |
| | | | **16QAM** | 20.6 | 20.64 | 20.6 |
| | | **Low** | **QPSK** | 21.62 | 21.65 | 21.63 |
| | | | **16QAM** | 20.62 | 20.64 | 20.64 |
| | 15RB | / | **QPSK** | 21.58 | 21.63 | 21.6 |
| | | | **16QAM** | 20.59 | 20.65 | 20.58 |
| 5 MHz | | | | **1712.5MHz** | **1732.5MHz** | **1752.5MHz** |
| | 1RB | **High** | **QPSK** | 22.29 | 22.32 | 22.3 |
| | | | **16QAM** | 21.49 | 21.52 | 21.5 |
| | | **Middle** | **QPSK** | 22.31 | 22.35 | 22.32 |
| | | | **16QAM** | 21.51 | 21.55 | 21.5 |
| | | **Low** | **QPSK** | 22.3 | 22.32 | 22.29 |
| | | | **16QAM** | 21.49 | 21.52 | 21.5 |
| | 12RB | **High** | **QPSK** | 21.67 | 21.72 | 21.65 |
| | | | **16QAM** | 20.66 | 20.73 | 20.67 |
| | | **Middle** | **QPSK** | 21.67 | 21.71 | 21.68 |
| | | | **16QAM** | 20.67 | 20.71 | 20.66 |
| | | **Low** | **QPSK** | 21.66 | 21.69 | 21.67 |
| | | | **16QAM** | 20.69 | 20.72 | 20.7 |
| | 25RB | / | **QPSK** | 21.64 | 21.68 | 21.65 |
| | | | **16QAM** | 20.63 | 20.66 | 20.63 |

| | | | | | | |
|---|---|---|---|---|---|---|
| 10 MHz | | | | **1715MHz** | **1732.5MHz** | **1750MHz** |
| | 1RB | **High** | **QPSK** | 22.30 | 22.33 | 22.3 |
| | | | **16QAM** | 21.48 | 21.51 | 21.49 |
| | | **Middle** | **QPSK** | 22.31 | 22.35 | 22.31 |
| | | | **16QAM** | 21.5 | 21.54 | 21.49 |
| | | **Low** | **QPSK** | 22.31 | 22.35 | 22.31 |
| | | | **16QAM** | 21.5 | 21.52 | 21.5 |
| | 25RB | **High** | **QPSK** | 21.63 | 21.68 | 21.65 |
| | | | **16QAM** | 20.66 | 20.7 | 20.67 |
| | | **Middle** | **QPSK** | 21.63 | 21.68 | 21.65 |
| | | | **16QAM** | 20.7 | 20.72 | 20.69 |
| | | **Low** | **QPSK** | 21.62 | 21.66 | 21.63 |
| | | | **16QAM** | 20.68 | 20.71 | 20.69 |
| | 50RB | / | **QPSK** | 21.65 | 21.68 | 21.64 |
| | | | **16QAM** | 20.64 | 20.67 | 20.63 |
| 15 MHz | | | | **1717.5MHz** | **1732.5MHz** | **1747.5MHz** |
| | 1RB | **High** | **QPSK** | 22.33 | 22.36 | 22.34 |
| | | | **16QAM** | 21.49 | 21.52 | 21.5 |
| | | **Middle** | **QPSK** | 22.3 | 22.36 | 22.3 |
| | | | **16QAM** | 21.5 | 21.55 | 21.5 |
| | | **Low** | **QPSK** | 22.32 | 22.35 | 22.33 |
| | | | **16QAM** | 21.51 | 21.54 | 21.52 |
| | 36RB | **High** | **QPSK** | 21.65 | 21.69 | 21.66 |
| | | | **16QAM** | 20.66 | 20.68 | 20.66 |
| | | **Middle** | **QPSK** | 21.63 | 21.68 | 21.62 |
| | | | **16QAM** | 20.68 | 20.71 | 20.67 |
| | | **Low** | **QPSK** | 21.66 | 21.71 | 21.68 |
| | | | **16QAM** | 20.64 | 20.68 | 20.65 |
| | 75RB | / | **QPSK** | 21.56 | 21.6 | 21.57 |
| | | | **16QAM** | 20.59 | 20.64 | 20.6 |
| 20 MHz | | | | **1720MHz** | **1732.5MHz** | **1745MHz** |
| | 1RB | **High** | **QPSK** | 22.29 | 22.35 | 22.30 |
| | | | **16QAM** | 21.49 | 21.54 | 21.51 |
| | | **Middle** | **QPSK** | 22.32 | 22.36 | 22.33 |
| | | | **16QAM** | 21.52 | 21.54 | 21.5 |
| | | **Low** | **QPSK** | 22.34 | 22.37 | 22.35 |
| | | | **16QAM** | 21.52 | 21.55 | 21.53 |
| | 50RB | **High** | **QPSK** | 21.66 | 21.72 | 21.58 |
| | | | **16QAM** | 20.64 | 20.7 | 20.65 |
| | | **Middle** | **QPSK** | 21.65 | 21.69 | 21.66 |
| | | | **16QAM** | 20.7 | 20.74 | 20.71 |
| | | **Low** | **QPSK** | 21.66 | 21.69 | 21.67 |
| | | | **16QAM** | 20.71 | 20.74 | 20.72 |
| | 100RB | / | **QPSK** | 21.59 | 21.65 | 21.58 |
| | | | **16QAM** | 20.58 | 20.64 | 20.57 |

| LTE-FDD Band 5 | | | | Actual output Power (dBm) | | |
|---|---|---|---|---|---|---|
| **Band-width** | **RBallocation** | **RBoffset** | **Modulation** | **Low** | **Middle** | **High** |
| 1.4 MHz | | | | **824.7MHz** | **836.5MHz** | **848.3MHz** |
| | 1RB | **High** | **QPSK** | 22.69 | 22.72 | 22.67 |
| | | | **16QAM** | 21.9 | 21.92 | 21.85 |
| | | **Middle** | **QPSK** | 22.71 | 22.73 | 22.7 |
| | | | **16QAM** | 21.9 | 21.94 | 21.89 |
| | | **Low** | **QPSK** | 22.68 | 22.73 | 22.71 |
| | | | **16QAM** | 21.89 | 21.9 | 21.88 |
| | 3RB | **High** | **QPSK** | 22.52 | 22.51 | 22.49 |
| | | | **16QAM** | 21.59 | 21.61 | 21.62 |
| | | **Middle** | **QPSK** | 22.52 | 22.51 | 22.49 |
| | | | **16QAM** | 21.59 | 21.61 | 21.62 |
| | | **Low** | **QPSK** | 22.49 | 22.51 | 22.5 |
| | | | **16QAM** | 21.65 | 21.66 | 21.61 |
| | 6RB | / | **QPSK** | 21.51 | 21.55 | 21.51 |
| | | | **16QAM** | 20.64 | 20.69 | 20.62 |
| 3 MHz | | | | **825.5MHz** | **836.5MHz** | **847.5MHz** |
| | 1RB | **High** | **QPSK** | 22.68 | 22.72 | 22.67 |
| | | | **16QAM** | 21.9 | 21.9 | 21.89 |
| | | **Middle** | **QPSK** | 22.71 | 22.75 | 22.7 |
| | | | **16QAM** | 21.89 | 21.91 | 21.9 |
| | | **Low** | **QPSK** | 22.67 | 22.74 | 22.7 |
| | | | **16QAM** | 21.89 | 21.93 | 21.87 |
| | 8RB | **High** | **QPSK** | 21.54 | 21.53 | 21.52 |
| | | | **16QAM** | 20.62 | 20.63 | 20.66 |
| | | **Middle** | **QPSK** | 21.52 | 21.54 | 21.52 |
| | | | **16QAM** | 20.66 | 20.65 | 20.65 |
| | | **Low** | **QPSK** | 21.51 | 21.56 | 21.5 |
| | | | **16QAM** | 20.6 | 20.67 | 20.59 |
| | 15RB | / | **QPSK** | 21.53 | 21.52 | 21.5 |
| | | | **16QAM** | 20.62 | 20.64 | 20.6 |
| 5 MHz | | | | **826.5MHz** | **836.5MHz** | **846.5MHz** |
| | 1RB | **High** | **QPSK** | 22.64 | 22.66 | 22.66 |
| | | | **16QAM** | 21.88 | 21.88 | 21.87 |
| | | **Middle** | **QPSK** | 22.7 | 22.72 | 22.67 |
| | | | **16QAM** | 21.88 | 21.9 | 21.91 |
| | | **Low** | **QPSK** | 22.7 | 22.73 | 22.71 |
| | | | **16QAM** | 21.91 | 21.9 | 21.91 |
| | 12RB | **High** | **QPSK** | 21.58 | 21.56 | 21.57 |
| | | | **16QAM** | 20.68 | 20.65 | 20.69 |
| | | **Middle** | **QPSK** | 21.59 | 21.61 | 21.56 |
| | | | **16QAM** | 20.63 | 20.67 | 20.68 |
| | | **Low** | **QPSK** | 21.62 | 21.64 | 21.59 |
| | | | **16QAM** | 20.67 | 20.68 | 20.62 |
| | 25RB | / | **QPSK** | 21.58 | 21.57 | 21.52 |
| | | | **16QAM** | 20.68 | 20.69 | 20.65 |

| | | | | 829MHz | 836.5MHz | 844MHz |
|---|---|---|---|---|---|---|
| 10 MHz | 1RB | **High** | **QPSK** | 22.72 | 22.75 | 22.68 |
| | | | **16QAM** | 21.93 | 21.94 | 21.91 |
| | | **Middle** | **QPSK** | 22.72 | 22.76 | 22.72 |
| | | | **16QAM** | 21.9 | 21.93 | 21.88 |
| | | **Low** | **QPSK** | 22.71 | 22.73 | 22.7 |
| | | | **16QAM** | 21.9 | 21.94 | 21.89 |
| | 25RB | **High** | **QPSK** | 21.61 | 21.62 | 21.57 |
| | | | **16QAM** | 20.62 | 20.64 | 20.6 |
| | | **Middle** | **QPSK** | 21.59 | 21.61 | 21.57 |
| | | | **16QAM** | 20.66 | 20.71 | 20.66 |
| | | **Low** | **QPSK** | 21.58 | 21.62 | 21.58 |
| | | | **16QAM** | 20.69 | 20.66 | 20.64 |
| | 50RB | / | **QPSK** | 21.63 | 21.59 | 21.52 |
| | | | **16QAM** | 20.69 | 20.71 | 20.66 |

| LTE-FDD Band 12 | | | | Actual output Power (dBm) | | |
|---|---|---|---|---|---|---|
| **Band-width** | **RBallocation** | **RBoffset** | **Modulation** | **Low** | **Middle** | **High** |
| 1.4 MHz | | | | **699.7MHz** | **707.5MHz** | **715.3MHz** |
| | 1RB | **High** | **QPSK** | 22.77 | 22.65 | 22.78 |
| | | | **16QAM** | 21.93 | 21.67 | 21.73 |
| | | **Middle** | **QPSK** | 22.9 | 22.61 | 22.95 |
| | | | **16QAM** | 21.99 | 21.66 | 21.86 |
| | | **Low** | **QPSK** | 22.84 | 22.59 | 22.82 |
| | | | **16QAM** | 21.95 | 21.57 | 21.72 |
| | 3RB | **High** | **QPSK** | 22.73 | 22.69 | 22.8 |
| | | | **16QAM** | 21.58 | 21.79 | 21.56 |
| | | **Middle** | **QPSK** | 22.89 | 22.73 | 22.93 |
| | | | **16QAM** | 21.67 | 21.8 | 21.68 |
| | | **Low** | **QPSK** | 22.88 | 22.74 | 22.79 |
| | | | **16QAM** | 21.6 | 21.81 | 21.65 |
| | 6RB | / | **QPSK** | 21.69 | 21.77 | 21.76 |
| | | | **16QAM** | 20.81 | 20.93 | 20.83 |
| 3 MHz | | | | **700.5MHz** | **707.5MHz** | **714.5MHz** |
| | 1RB | **High** | **QPSK** | 22.67 | 22.49 | 22.73 |
| | | | **16QAM** | 21.62 | 21.74 | 21.64 |
| | | **Middle** | **QPSK** | 22.71 | 22.62 | 22.75 |
| | | | **16QAM** | 21.56 | 21.65 | 21.72 |
| | | **Low** | **QPSK** | 22.74 | 22.67 | 22.82 |
| | | | **16QAM** | 21.76 | 21.72 | 21.83 |
| | 8RB | **High** | **QPSK** | 21.74 | 21.81 | 21.68 |
| | | | **16QAM** | 20.65 | 20.76 | 20.92 |
| | | **Middle** | **QPSK** | 21.63 | 21.68 | 21.72 |
| | | | **16QAM** | 20.64 | 20.69 | 20.96 |
| | | **Low** | **QPSK** | 21.56 | 21.67 | 21.74 |
| | | | **16QAM** | 20.6 | 20.79 | 20.97 |
| | 15RB | / | **QPSK** | 21.64 | 21.68 | 21.74 |
| | | | **16QAM** | 20.63 | 20.66 | 20.83 |
| 5 MHz | | | | **701.5MHz** | **707.5MHz** | **713.5MHz** |
| | 1RB | **High** | **QPSK** | 22.79 | 22.75 | 22.7 |
| | | | **16QAM** | 21.65 | 21.78 | 21.72 |
| | | **Middle** | **QPSK** | 22.68 | 22.67 | 22.72 |
| | | | **16QAM** | 21.44 | 21.75 | 21.85 |
| | | **Low** | **QPSK** | 22.55 | 22.83 | 22.75 |
| | | | **16QAM** | 21.49 | 21.97 | 21.87 |
| | 12RB | **High** | **QPSK** | 21.75 | 21.63 | 21.68 |
| | | | **16QAM** | 20.74 | 20.59 | 20.76 |
| | | **Middle** | **QPSK** | 21.67 | 21.82 | 21.65 |
| | | | **16QAM** | 20.76 | 20.7 | 20.95 |
| | | **Low** | **QPSK** | 21.64 | 21.68 | 21.68 |
| | | | **16QAM** | 20.82 | 20.75 | 20.91 |
| | 25RB | / | **QPSK** | 21.61 | 21.72 | 21.69 |
| | | | **16QAM** | 20.6 | 20.77 | 20.81 |

| | | | | 704MHz | 707.5MHz | 711MHz |
|---|---|---|---|---|---|---|
| 10 MHz | 1RB | **High** | **QPSK** | 22.79 | 22.76 | 22.72 |
| | | | **16QAM** | 21.61 | 21.78 | 21.72 |
| | | **Middle** | **QPSK** | 22.87 | 22.70 | 22.51 |
| | | | **16QAM** | 21.81 | 21.94 | 21.67 |
| | | **Low** | **QPSK** | 22.81 | 22.61 | 22.71 |
| | | | **16QAM** | 21.75 | 21.77 | 21.78 |
| | 25RB | **High** | **QPSK** | 21.63 | 21.68 | 21.72 |
| | | | **16QAM** | 20.69 | 20.78 | 20.85 |
| | | **Middle** | **QPSK** | 21.78 | 21.68 | 21.59 |
| | | | **16QAM** | 20.76 | 20.67 | 20.77 |
| | | **Low** | **QPSK** | 21.71 | 21.70 | 21.67 |
| | | | **16QAM** | 20.68 | 20.76 | 20.82 |
| | 50RB | / | **QPSK** | 21.64 | 21.49 | 21.71 |
| | | | **16QAM** | 20.82 | 20.56 | 20.77 |

| LTE-FDD Band 17 | | | | Actual output Power (dBm) | | |
|---|---|---|---|---|---|---|
| **Band-width** | **RBallocation** | **RBoffset** | **Modulation** | **High** | **Middle** | **Low** |
| 5 MHz | | | | **706.5MHz** | **710MHz** | **713.5MHz** |
| | 1RB | **High** | **QPSK** | 22.55 | 22.55 | 22.53 |
| | | | **16QAM** | 21.61 | 21.64 | 21.6 |
| | | **Middle** | **QPSK** | 22.51 | 22.53 | 22.54 |
| | | | **16QAM** | 21.58 | 21.62 | 21.6 |
| | | **Low** | **QPSK** | 22.51 | 22.54 | 22.54 |
| | | | **16QAM** | 21.59 | 21.62 | 21.58 |
| | 12RB | **High** | **QPSK** | 21.55 | 21.53 | 21.54 |
| | | | **16QAM** | 20.76 | 20.77 | 20.76 |
| | | **Middle** | **QPSK** | 21.53 | 21.55 | 21.53 |
| | | | **16QAM** | 20.74 | 20.75 | 20.73 |
| | | **Low** | **QPSK** | 21.53 | 21.56 | 21.53 |
| | | | **16QAM** | 20.72 | 20.76 | 20.75 |
| | 25RB | / | **QPSK** | 21.5 | 21.51 | 21.5 |
| | | | **16QAM** | 20.71 | 20.72 | 20.71 |
| 10 MHz | | | | **709MHz** | **710MHz** | **711MHz** |
| | 1RB | **High** | **QPSK** | 22.56 | 22.6 | 22.53 |
| | | | **16QAM** | 21.64 | 21.66 | 21.63 |
| | | **Middle** | **QPSK** | 22.52 | 22.54 | 22.53 |
| | | | **16QAM** | 21.62 | 21.64 | 21.61 |
| | | **Low** | **QPSK** | 22.54 | 22.56 | 22.55 |
| | | | **16QAM** | 21.61 | 21.64 | 21.6 |
| | 25RB | **High** | **QPSK** | 21.59 | 21.65 | 21.6 |
| | | | **16QAM** | 20.77 | 20.78 | 20.77 |
| | | **Middle** | **QPSK** | 21.54 | 21.56 | 21.55 |
| | | | **16QAM** | 20.73 | 20.77 | 20.78 |
| | | **Low** | **QPSK** | 21.54 | 21.55 | 21.55 |
| | | | **16QAM** | 20.73 | 20.72 | 20.76 |
| | 50RB | / | **QPSK** | 21.51 | 21.54 | 21.54 |
| | | | **16QAM** | 20.71 | 20.75 | 20.76 |

## WLAN Conducted Power

For 2.4GHz WLAN SAR testing, highest average RF output power channel for the lowest data rate for 802.11b were for SAR evaluation. 802.11g/n were not investigated since the average putput powers over all channels and data rates were not more than 0.25dB higher than the tested channel in the lowest data rate of 802.11b mode.

| WIFI | | | | | |
|---|---|---|---|---|---|
| Mode | Channel | Frequency (MHz) | Conducted Peak Power (dBm) | Conducted Average Power (dBm) | Data rate |
| 802.11b | 01 | 2412 | 17.15 | 14.63 | 1 Mbps |
| | 06 | 2437 | 17.14 | 14.63 | 1 Mbps |
| | 11 | 2462 | 16.98 | 14.47 | 1 Mbps |
| 802.11g | 01 | 2412 | 13.86 | 10.86 | 6 Mbps |
| | 06 | 2437 | 13.91 | 10.87 | 6 Mbps |
| | 11 | 2462 | 13.77 | 10.77 | 6 Mbps |
| 802.11n(H20) | 01 | 2412 | 13.45 | 10.26 | 6.5 Mbps |
| | 06 | 2437 | 13.65 | 10.39 | 6.5 Mbps |
| | 11 | 2462 | 13.54 | 10.31 | 6.5 Mbps |
| 802.11n(H40) | 3 | 2422 | 12.14 | 9.26 | 13.5 Mbps |
| | 6 | 2437 | 12.25 | 9.32 | 13.5 Mbps |
| | 9 | 2452 | 12.33 | 9.39 | 13.5 Mbps |

*Note:*The output power was test all data rate and recorded worst case at recorded data rate.

**Bluetooth Conducted Power**

| Bluetooth | | | |
|---|---|---|---|
| Mode | Channel | Frequency (MHz) | Conducted power (dBm) |
| GFSK | 0 | 2402 | 2.27 |
| | 39 | 2441 | 2.39 |
| | 78 | 2480 | 2.24 |
| π/4QPSK | 0 | 2402 | 2.03 |
| | 39 | 2441 | 2.19 |
| | 78 | 2480 | 2.14 |
| 8DPSK | 0 | 2402 | 2.03 |
| | 39 | 2441 | 2.21 |
| | 78 | 2480 | 2.15 |
| BLE | 0 | 2402 | -5.78 |
| | 19 | 2440 | -5.89 |
| | 39 | 2480 | -6.30 |

Per KDB 447498 D01, the 1-g and 10-g SAR test exclusion thresholds for 100MHz to 6GHz at test separation distances ≦50mm are determined by:

[(max. Power of channel, including tune-up tolerance, mW) / (min. test separation distance, mm)] * [√f(GHz)] ≦3.0 for 1-g SAR

| Band/Mode | F(GHz) | Position | SAR test exclusion threshold (mW) | RF output power | | SAR test exclusion |
|---|---|---|---|---|---|---|
| | | | | dBm | mW | |
| Bluetooth | 2.45 | Head | 9.6 | 3 | 2.00 | Yes |
| | | Body | 19.2 | 3 | 2.00 | Yes |
| WiFi | 2.45 | Head | 9.6 | 15 | 31.62 | No |
| | | Body | 19.2 | 15 | 31.62 | No |

Per KDB 447498 D01, when the minimum test separation distance is <5mm, a distance of 5mm is applied to determine SAR test exclusion.

The test exclusion thereshold is ≦3, SAR testing is not required.

## 12. Maximum Tune-up Limit

| Mode | Burst Average Power (dBm) | |
|---|---|---|
| | GSM850 | PCS1900 |
| GSM (GMSK, 1Tx Slot) | 34.00 | 31.00 |
| GPRS (GMSK, 1Tx Slot) | 34.00 | 31.00 |
| GPRS (GMSK, 2Tx Slot) | 31.00 | 29.00 |
| GPRS (GMSK, 3Tx Slot) | 29.00 | 27.00 |
| GPRS (GMSK, 4Tx Slot) | 28.00 | 26.00 |
| EGPRS (GMSK, 1Tx Slot) | 34.00 | 31.00 |
| EGPRS (GMSK, 2Tx Slot) | 31.00 | 29.00 |
| EGPRS (GMSK, 3Tx Slot) | 29.00 | 27.00 |
| EGPRS (GMSK, 4Tx Slot) | 28.00 | 26.00 |

| Mode | Burst Average Power (dBm) | |
|---|---|---|
| | WCDMA Band V | WCDMA Band II |
| AMR 12.2Kbps | 24.00 | 24.00 |
| RMC 12.2Kbps | 24.00 | 24.00 |
| HSDPA Subtest-1 | 22.00 | 22.00 |
| HSDPA Subtest-2 | 22.00 | 22.00 |
| HSDPA Subtest-3 | 22.00 | 22.00 |
| HSDPA Subtest-4 | 22.00 | 22.00 |
| HSUPA Subtest-1 | 21.00 | 21.50 |
| HSUPA Subtest-2 | 21.00 | 21.50 |
| HSUPA Subtest-3 | 21.00 | 21.50 |
| HSUPA Subtest-4 | 21.00 | 21.50 |
| HSUPA Subtest-5 | 21.00 | 21.50 |

**LTE**

| LTE Band 2 | | | |
|---|---|---|---|
| Channel | Channel 19100 | Channel 18900 | Channel 18700 |
| Tune-up(dB) | 23 | 23 | 23 |
| LTE Band 4 | | | |
| Channel | Channel 20300 | Channel 20175 | Channel 20050 |
| Tune-up(dB) | 23 | 23 | 23 |
| LTE Band 5 | | | |
| Channel | Channel 20600 | Channel 20525 | Channel 20450 |
| Tune-up(dB) | 23 | 23 | 23 |
| LTE Band 12 | | | |
| Channel | Channel 23130 | Channel 23095 | Channel 23060 |
| Tune-up(dB) | 23 | 23 | 23 |
| LTE Band 17 | | | |
| Channel | Channel 23800 | Channel 23790 | Channel 23780 |
| Tune-up(dB) | 23 | 23 | 23 |

**LTEMPRwillfollowup3GPPsettingasbelow:**

| Modulation | Channel bandwidth / Transmission bandwidth (NRB) | | | | | | MPR (dB) |
|---|---|---|---|---|---|---|---|
| | 1.4MHz | 3.0MHz | 5MHz | 10MHz | 15MHz | 20MHz | |
| QPSK | ≤ 5 | ≤ 4 | ≤ 8 | ≤ 12 | ≤ 16 | ≤ 18 | 0 |
| QPSK | > 5 | > 4 | > 8 | > 12 | > 16 | > 18 | 1 |
| 16 QAM | ≤ 5 | ≤ 4 | ≤ 8 | ≤ 12 | ≤ 16 | ≤ 18 | 1 |
| 16 QAM | > 5 | > 4 | > 8 | > 12 | > 16 | > 18 | 2 |

| WLAN | | |
|---|---|---|
| Mode | Peak Power (dBm) | Burst Average Power (dBm) |
| 802.11b | 17.50 | 15.00 |
| 802.11g | 15.00 | 12.00 |
| 802.11n(HT20) | 14.00 | 11.00 |
| 802.11n(HT40) | 13.00 | 10.00 |

| Mode | Conducted Peak Power (dBm) |
|---|---|
| GFSK | 3.00 |
| π /4QPSK | 3.00 |
| 8DPSK | 3.00 |
| BLE | -5.50 |

## 13. Antenna Location




| Positions for SAR tests; Hotspot mode | | | | | | |
|---|---|---|---|---|---|---|
| Antenna | Back | Front | Top side | Bottom side | Right side | Left side |
| WWAN | Yes | Yes | No | Yes | Yes | Yes |
| WIFI / BT | Yes | Yes | No | Yes | Yes | No |

General note:
Referring to KDB941225 D06, when the overall device length and width are >9cm*5cm, the test distance is 10mm. SAR must be measured for all sides and surfaces with a transmitting antenna located within 25mm from that surface or edge.

# 14. SAR Measurement Results

## Head SAR

| GSM850 | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|
| Mode | Test Position | Frequency | | Conducted Power (dBm) | Tune up limit (dBm) | Tune up scaling factor | Power Drift(dB) | Measured SAR(1g) (W/kg) | Report SAR(1g) (W/kg) | Test Plot |
| | | CH | MHz | | | | | | | |
| GPRS (4Tx slot) | Left-Cheek | 128 | 824.2 | 27.35 | 28.00 | 1.16 | - | - | - | - |
| | | 190 | 836.6 | 27.56 | 28.00 | 1.11 | 0.09 | 0.039 | 0.04 | H1 |
| | | 251 | 848.8 | 27.65 | 28.00 | 1.08 | - | - | - | - |
| | Left-Tilt | 128 | 824.2 | 27.35 | 28.00 | 1.16 | - | - | - | - |
| | | 190 | 836.6 | 27.56 | 28.00 | 1.11 | -0.10 | 0.030 | 0.03 | - |
| | | 251 | 848.8 | 27.65 | 28.00 | 1.08 | - | - | - | - |
| | Right-Cheek | 128 | 824.2 | 27.35 | 28.00 | 1.16 | - | - | - | - |
| | | 190 | 836.6 | 27.56 | 28.00 | 1.11 | -0.04 | 0.037 | 0.04 | - |
| | | 251 | 848.8 | 27.65 | 28.00 | 1.08 | - | - | - | - |
| | Right-Tilt | 128 | 824.2 | 27.35 | 28.00 | 1.16 | - | - | - | - |
| | | 190 | 836.6 | 27.56 | 28.00 | 1.11 | 0.05 | 0.029 | 0.03 | - |
| | | 251 | 848.8 | 27.65 | 28.00 | 1.08 | - | - | - | - |

| PCS1900 | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|
| Mode | Test Position | Frequency | | Conducted Power (dBm) | Tune up limit (dBm) | Tune up scaling factor | Power Drift(dB) | Measured SAR(1g) (W/kg) | Report SAR(1g) (W/kg) | Test Plot |
| | | CH | MHz | | | | | | | |
| GPRS (4Tx slot) | Left-Cheek | 512 | 1850.2 | 25.36 | 26.00 | 1.16 | - | - | - | - |
| | | 661 | 1880.0 | 25.28 | 26.00 | 1.18 | 0.13 | 0.025 | 0.03 | H2 |
| | | 810 | 1909.8 | 25.29 | 26.00 | 1.18 | - | - | - | - |
| | Left-Tilt | 512 | 1850.2 | 25.36 | 26.00 | 1.16 | - | - | - | - |
| | | 661 | 1880.0 | 25.28 | 26.00 | 1.18 | 0.09 | 0.019 | 0.02 | - |
| | | 810 | 1909.8 | 25.29 | 26.00 | 1.18 | - | - | - | - |
| | Right-Cheek | 512 | 1850.2 | 25.36 | 26.00 | 1.16 | - | - | - | - |
| | | 661 | 1880.0 | 25.28 | 26.00 | 1.18 | -0.07 | 0.023 | 0.03 | - |
| | | 810 | 1909.8 | 25.29 | 26.00 | 1.18 | - | - | - | - |
| | Right-Tilt | 512 | 1850.2 | 25.36 | 26.00 | 1.16 | - | - | - | - |
| | | 661 | 1880.0 | 25.28 | 26.00 | 1.18 | -0.08 | 0.017 | 0.02 | - |
| | | 810 | 1909.8 | 25.29 | 26.00 | 1.18 | - | - | - | - |

Note:
Per KDB865664 D01v01r04, Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg

| WCDMA Band V | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|
| Mode | Test Position | Frequency | | Conducted Power (dBm) | Tune up limit (dBm) | Tune up scaling factor | Power Drift(dB) | Measured SAR(1g) (W/kg) | Report SAR(1g) (W/kg) | Test Plot |
| | | CH | MHz | | | | | | | |
| RMC 12.2K bps | Left-Cheek | 4132 | 826.4 | 23.24 | 24.00 | 1.19 | - | - | - | - |
| | | 4183 | 836.6 | 23.29 | 24.00 | 1.18 | 0.13 | 0.038 | 0.04 | H3 |
| | | 4233 | 846.6 | 23.12 | 24.00 | 1.22 | - | - | - | - |
| | Left-Tilt | 4132 | 826.4 | 23.24 | 24.00 | 1.19 | - | - | - | - |
| | | 4183 | 836.6 | 23.29 | 24.00 | 1.18 | 0.11 | 0.031 | 0.04 | - |
| | | 4233 | 846.6 | 23.12 | 24.00 | 1.22 | - | - | - | - |
| | Right-Cheek | 4132 | 826.4 | 23.24 | 24.00 | 1.19 | - | - | - | - |
| | | 4183 | 836.6 | 23.29 | 24.00 | 1.18 | 0.18 | 0.036 | 0.04 | - |
| | | 4233 | 846.6 | 23.12 | 24.00 | 1.22 | - | - | - | - |
| | Right-Tilt | 4132 | 826.4 | 23.24 | 24.00 | 1.19 | - | - | - | - |
| | | 4183 | 836.6 | 23.29 | 24.00 | 1.18 | -0.06 | 0.029 | 0.03 | - |
| | | 4233 | 846.6 | 23.12 | 24.00 | 1.22 | - | - | - | - |

| WCDMA Band II | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|
| Mode | Test Position | Frequency | | Conducted Power (dBm) | Tune up limit (dBm) | Tune up scaling factor | Power Drift(dB) | Measured SAR(1g) (W/kg) | Report SAR(1g) (W/kg) | Test Plot |
| | | CH | MHz | | | | | | | |
| RMC 12.2K bps | Left-Cheek | 9262 | 1852.4 | 23.98 | 24.00 | 1.01 | - | - | - | - |
| | | 9400 | 1880.0 | 23.94 | 24.00 | 1.01 | 0.17 | 0.05 | 0.05 | H4 |
| | | 9538 | 1907.6 | 23.97 | 24.00 | 1.01 | - | - | - | - |
| | Left-Tilt | 9262 | 1852.4 | 23.98 | 24.00 | 1.01 | - | - | - | - |
| | | 9400 | 1880.0 | 23.94 | 24.00 | 1.01 | 0.10 | 0.040 | 0.04 | - |
| | | 9538 | 1907.6 | 23.97 | 24.00 | 1.01 | - | - | - | - |
| | Right-Cheek | 9262 | 1852.4 | 23.98 | 24.00 | 1.01 | - | - | - | - |
| | | 9400 | 1880.0 | 23.94 | 24.00 | 1.01 | -0.29 | 0.048 | 0.05 | - |
| | | 9538 | 1907.6 | 23.97 | 24.00 | 1.01 | - | - | - | - |
| | Right-Tilt | 9262 | 1852.4 | 23.98 | 24.00 | 1.01 | - | - | - | - |
| | | 9400 | 1880.0 | 23.94 | 24.00 | 1.01 | -0.09 | 0.036 | 0.04 | - |
| | | 9538 | 1907.6 | 23.97 | 24.00 | 1.01 | - | - | - | - |

Note:
Per KDB865664 D01v01r04, Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg

| LTE Band II | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|
| Mode | Test Position | Frequency | | Conducted Power (dBm) | Tune up limit (dBm) | Tune up scaling factor | Power Drift(dB) | Measured SAR(1g) (W/kg) | Report SAR(1g) (W/kg) | Test Plot |
| | | CH | MHz | | | | | | | |
| 20M_1RB | Left-Cheek | 18700 | 1860.0 | 22.10 | 23.00 | 1.23 | - | - | - | - |
| | | 18900 | 1880.0 | 22.17 | 23.00 | 1.21 | -0.11 | 0.065 | 0.08 | H5 |
| | | 19100 | 1900.0 | 22.07 | 23.00 | 1.24 | - | - | - | - |
| | Left-Tilt | 18700 | 1860.0 | 22.10 | 23.00 | 1.23 | - | - | - | - |
| | | 18900 | 1880.0 | 22.17 | 23.00 | 1.21 | 0.12 | 0.050 | 0.06 | - |
| | | 19100 | 1900.0 | 22.07 | 23.00 | 1.24 | - | - | - | - |
| | Right-Cheek | 18700 | 1860.0 | 22.10 | 23.00 | 1.23 | - | - | - | - |
| | | 18900 | 1880.0 | 22.17 | 23.00 | 1.21 | 0.05 | 0.061 | 0.07 | - |
| | | 19100 | 1900.0 | 22.07 | 23.00 | 1.24 | - | - | - | - |
| | Right-Tilt | 18700 | 1860.0 | 22.10 | 23.00 | 1.23 | - | - | - | - |
| | | 18900 | 1880.0 | 22.17 | 23.00 | 1.21 | -0.06 | 0.049 | 0.06 | - |
| | | 19100 | 1900.0 | 22.07 | 23.00 | 1.24 | - | - | - | - |
| 20M_50RB | Left-Cheek | 18700 | 1860.0 | 21.47 | 22.00 | 1.13 | - | - | - | - |
| | | 18900 | 1880.0 | 21.54 | 22.00 | 1.11 | -0.11 | 0.056 | 0.06 | - |
| | | 19100 | 1900.0 | 21.35 | 22.00 | 1.16 | - | - | - | - |
| | Left-Tilt | 18700 | 1860.0 | 21.47 | 22.00 | 1.13 | - | - | - | - |
| | | 18900 | 1880.0 | 21.54 | 22.00 | 1.11 | 0.12 | 0.043 | 0.05 | - |
| | | 19100 | 1900.0 | 21.35 | 22.00 | 1.16 | - | - | - | - |
| | Right-Cheek | 18700 | 1860.0 | 21.47 | 22.00 | 1.13 | - | - | - | - |
| | | 18900 | 1880.0 | 21.54 | 22.00 | 1.11 | 0.05 | 0.053 | 0.06 | - |
| | | 19100 | 1900.0 | 21.35 | 22.00 | 1.16 | - | - | - | - |
| | Right-Tilt | 18700 | 1860.0 | 21.47 | 22.00 | 1.13 | - | - | - | - |
| | | 18900 | 1880.0 | 21.54 | 22.00 | 1.11 | -0.06 | 0.042 | 0.05 | - |
| | | 19100 | 1900.0 | 21.35 | 22.00 | 1.16 | - | - | - | - |

Note:

1. Per KDB865664 D01v01r04, Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg
2. Per KDB 941225 D05v02r03, for QPSK with 100% RB allocation, SAR is not required when the highest maximumoutput power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations andthe highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highestoutput power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also betested.

| LTE Band IV | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|
| Mode | Test Position | Frequency | | Conducted Power (dBm) | Tune up limit (dBm) | Tune up scaling factor | Power Drift(dB) | Measured SAR(1g) (W/kg) | Report SAR(1g) (W/kg) | Test Plot |
| | | CH | MHz | | | | | | | |
| 20M_1 RB | Left-Cheek | 20050 | 1720 | 22.29 | 23.00 | 1.18 | - | - | - | - |
| | | 20175 | 1732.5 | 22.35 | 23.00 | 1.16 | 0.1 | 0.055 | 0.06 | H6 |
| | | 20300 | 1745 | 22.30 | 23.00 | 1.17 | - | - | - | - |
| | Left-Tilt | 20050 | 1720 | 22.29 | 23.00 | 1.18 | - | - | - | - |
| | | 20175 | 1732.5 | 22.35 | 23.00 | 1.16 | 0.07 | 0.041 | 0.05 | - |
| | | 20300 | 1745 | 22.30 | 23.00 | 1.17 | - | - | - | - |
| | Right-Cheek | 20050 | 1720 | 22.29 | 23.00 | 1.18 | - | - | - | - |
| | | 20175 | 1732.5 | 22.35 | 23.00 | 1.16 | -0.05 | 0.050 | 0.06 | - |
| | | 20300 | 1745 | 22.30 | 23.00 | 1.17 | - | - | - | - |
| | Right-Tilt | 20050 | 1720 | 22.29 | 23.00 | 1.18 | - | - | - | - |
| | | 20175 | 1732.5 | 22.35 | 23.00 | 1.16 | -0.06 | 0.038 | 0.04 | - |
| | | 20300 | 1745 | 22.30 | 23.00 | 1.17 | - | - | - | - |
| 20M_5 0RB | Left-Cheek | 20050 | 1720 | 21.66 | 22.00 | 1.08 | - | - | - | - |
| | | 20175 | 1732.5 | 21.72 | 22.00 | 1.07 | -0.11 | 0.042 | 0.04 | - |
| | | 20300 | 1745 | 21.58 | 22.00 | 1.10 | - | - | - | - |
| | Left-Tilt | 20050 | 1720 | 21.66 | 22.00 | 1.08 | - | - | - | - |
| | | 20175 | 1732.5 | 21.72 | 22.00 | 1.07 | -0.08 | 0.031 | 0.03 | - |
| | | 20300 | 1745 | 21.58 | 22.00 | 1.10 | - | - | - | - |
| | Right-Cheek | 20050 | 1720 | 21.66 | 22.00 | 1.08 | - | - | - | - |
| | | 20175 | 1732.5 | 21.72 | 22.00 | 1.07 | 0.06 | 0.039 | 0.04 | - |
| | | 20300 | 1745 | 21.58 | 22.00 | 1.10 | - | - | - | - |
| | Right-Tilt | 20050 | 1720 | 21.66 | 22.00 | 1.08 | - | - | - | - |
| | | 20175 | 1732.5 | 21.72 | 22.00 | 1.07 | 0.07 | 0.029 | 0.03 | - |
| | | 20300 | 1745 | 21.58 | 22.00 | 1.10 | - | - | - | - |

Note:

1. Per KDB865664 D01v01r04, Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg
2. Per KDB 941225 D05v02r03, for QPSK with 100% RB allocation, SAR is not required when the highest maximumoutput power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations andthe highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highestoutput power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also betested.

| LTE Band V | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|
| Mode | Test Position | Frequency | | Conducted Power (dBm) | Tune up limit (dBm) | Tune up scaling factor | Power Drift(dB) | Measured SAR(1g) (W/kg) | Report SAR(1g) (W/kg) | Test Plot |
| | | CH | MHz | | | | | | | |
| 10M_1 RB | Left-Cheek | 20450 | 829 | 22.72 | 23.00 | 1.07 | - | - | - | - |
| | | 20525 | 836.5 | 22.75 | 23.00 | 1.06 | -0.11 | 0.032 | 0.03 | H7 |
| | | 20600 | 844 | 22.68 | 23.00 | 1.08 | - | - | - | - |
| | Left-Tilt | 20450 | 829 | 22.72 | 23.00 | 1.07 | - | - | - | - |
| | | 20525 | 836.5 | 22.75 | 23.00 | 1.06 | -0.09 | 0.022 | 0.02 | - |
| | | 20600 | 844 | 22.68 | 23.00 | 1.08 | - | - | - | - |
| | Right-Cheek | 20450 | 829 | 22.72 | 23.00 | 1.07 | - | - | - | - |
| | | 20525 | 836.5 | 22.75 | 23.00 | 1.06 | -0.15 | 0.026 | 0.03 | - |
| | | 20600 | 844 | 22.68 | 23.00 | 1.08 | - | - | - | - |
| | Right-Tilt | 20450 | 829 | 22.72 | 23.00 | 1.07 | - | - | - | - |
| | | 20525 | 836.5 | 22.75 | 23.00 | 1.06 | 0.05 | 0.014 | 0.01 | - |
| | | 20600 | 844 | 22.68 | 23.00 | 1.08 | - | - | - | - |
| 10M_25RB | Left-Cheek | 20450 | 829 | 21.61 | 22.00 | 1.09 | - | - | - | - |
| | | 20525 | 836.5 | 21.62 | 22.00 | 1.09 | -0.11 | 0.021 | 0.02 | - |
| | | 20600 | 844 | 21.57 | 22.00 | 1.10 | - | - | - | - |
| | Left-Tilt | 20450 | 829 | 21.61 | 22.00 | 1.09 | - | - | - | - |
| | | 20525 | 836.5 | 21.62 | 22.00 | 1.09 | -0.09 | 0.017 | 0.02 | - |
| | | 20600 | 844 | 21.57 | 22.00 | 1.10 | - | - | - | - |
| | Right-Cheek | 20450 | 829 | 21.61 | 22.00 | 1.09 | - | - | - | - |
| | | 20525 | 836.5 | 21.62 | 22.00 | 1.09 | -0.15 | 0.020 | 0.02 | - |
| | | 20600 | 844 | 21.57 | 22.00 | 1.10 | - | - | - | - |
| | Right-Tilt | 20450 | 829 | 21.61 | 22.00 | 1.09 | - | - | - | - |
| | | 20525 | 836.5 | 21.62 | 22.00 | 1.09 | 0.05 | 0.012 | 0.01 | - |
| | | 20600 | 844 | 21.57 | 22.00 | 1.10 | - | - | - | - |

Note:

1. Per KDB865664 D01v01r04, Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg
2. Per KDB 941225 D05v02r03, for QPSK with 100% RB allocation, SAR is not required when the highest maximumoutput power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations andthe highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highestoutput power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also betested.

| LTE Band 12 | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|
| Mode | Test Position | Frequency | | Conducted Power (dBm) | Tune up limit (dBm) | Tune up scaling factor | Power Drift(dB) | Measured SAR(1g) (W/kg) | Report SAR(1g) (W/kg) | Test Plot |
| | | CH | MHz | | | | | | | |
| 10M_1 RB | Left-Cheek | 23060 | 704 | 22.79 | 23.00 | 1.05 | - | - | - | - |
| | | 23095 | 707.5 | 22.76 | 23.00 | 1.06 | 0.14 | 0.050 | 0.05 | H8 |
| | | 23130 | 711 | 22.72 | 23.00 | 1.07 | - | - | - | - |
| | Left-Tilt | 23060 | 704 | 22.79 | 23.00 | 1.05 | - | - | - | - |
| | | 23095 | 707.5 | 22.76 | 23.00 | 1.06 | 0.08 | 0.040 | 0.04 | - |
| | | 23130 | 711 | 22.72 | 23.00 | 1.07 | - | - | - | - |
| | Right-Cheek | 23060 | 704 | 22.79 | 23.00 | 1.05 | - | - | - | - |
| | | 23095 | 707.5 | 22.76 | 23.00 | 1.06 | -0.24 | 0.048 | 0.05 | - |
| | | 23130 | 711 | 22.72 | 23.00 | 1.07 | - | - | - | - |
| | Right-Tilt | 23060 | 704 | 22.79 | 23.00 | 1.05 | - | - | - | - |
| | | 23095 | 707.5 | 22.76 | 23.00 | 1.06 | -0.07 | 0.036 | 0.04 | - |
| | | 23130 | 711 | 22.72 | 23.00 | 1.07 | - | - | - | - |
| 10M_25RB | Left-Cheek | 23060 | 704 | 21.63 | 22.00 | 1.09 | - | - | - | - |
| | | 23095 | 707.5 | 21.58 | 22.00 | 1.10 | 0.14 | 0.038 | 0.04 | - |
| | | 23130 | 711 | 21.72 | 22.00 | 1.07 | - | - | - | - |
| | Left-Tilt | 23060 | 704 | 21.63 | 22.00 | 1.09 | - | - | - | - |
| | | 23095 | 707.5 | 21.58 | 22.00 | 1.10 | 0.08 | 0.031 | 0.03 | - |
| | | 23130 | 711 | 21.72 | 22.00 | 1.07 | - | - | - | - |
| | Right-Cheek | 23060 | 704 | 21.63 | 22.00 | 1.09 | - | - | - | - |
| | | 23095 | 707.5 | 21.58 | 22.00 | 1.10 | -0.24 | 0.036 | 0.04 | - |
| | | 23130 | 711 | 21.72 | 22.00 | 1.07 | - | - | - | - |
| | Right-Tilt | 23060 | 704 | 21.63 | 22.00 | 1.09 | - | - | - | - |
| | | 23095 | 707.5 | 21.58 | 22.00 | 1.10 | -0.07 | 0.028 | 0.03 | - |
| | | 23130 | 711 | 21.72 | 22.00 | 1.07 | - | - | - | - |

Note:

1. Per KDB865664 D01v01r04, Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg
2. Per KDB 941225 D05v02r03, for QPSK with 100% RB allocation, SAR is not required when the highest maximumoutput power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations andthe highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highestoutput power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also betested.

| WLAN | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|
| Mode | Test Position | Frequency | | Conducted Power (dBm) | Tune up limit (dBm) | Tune up scaling factor | Power Drift(dB) | Measured SAR(1g) (W/kg) | Report SAR(1g) (W/kg) | Test Plot |
| | | CH | MHz | | | | | | | |
| 802.11 b 1Mbps | Left-Cheek | 01 | 2412 | 14.63 | 15.00 | 1.09 | - | - | - | - |
| | | 06 | 2437 | 14.63 | 15.00 | 1.09 | -0.15 | 0.20 | 0.22 | H9 |
| | | 11 | 2462 | 14.47 | 15.00 | 1.13 | - | - | - | - |
| | Left-Tilt | 01 | 2412 | 14.63 | 15.00 | 1.09 | - | - | - | - |
| | | 06 | 2437 | 14.63 | 15.00 | 1.09 | 0.20 | 0.170 | 0.18 | - |
| | | 11 | 2462 | 14.47 | 15.00 | 1.13 | - | - | - | - |
| | Right-Cheek | 01 | 2412 | 14.63 | 15.00 | 1.09 | - | - | - | - |
| | | 06 | 2437 | 14.63 | 15.00 | 1.09 | 0.08 | 0.182 | 0.20 | - |
| | | 11 | 2462 | 14.47 | 15.00 | 1.13 | - | - | - | - |
| | Right-Tilt | 01 | 2412 | 14.63 | 15.00 | 1.09 | - | - | - | - |
| | | 06 | 2437 | 14.63 | 15.00 | 1.09 | -0.11 | 0.158 | 0.17 | - |
| | | 11 | 2462 | 14.47 | 15.00 | 1.13 | - | - | - | - |

Note:
1. According to the above table, the initial test position for head is “LeftCheek”, and its reported SAR is≤ 0.4W/kg. Thus further SAR measurement is not required for the other (remaining) test positions. Because the reported SAR of the highest measured maximum output power channel for the exposureconfiguration is ≤ 0.8W/kg, no further SAR testing is required for 802.11b DSSS in that exposureconfiguration.
2. When SAR measurement is required for 2.4 GHz 802.11g/n OFDM configurations, the measurement and test reduction procedures for OFDM are applied. SAR is not required for the following 2.4 GHz OFDM conditions.
   a) When KDB Publication 447498 D01 SAR test exclusion applies to the OFDM configuration.
   b) When the highest *reported* SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg,the 802.11g/n is not required.

| WLAN- Scaled Reported SAR | | | | | | | |
|---|---|---|---|---|---|---|---|
| Mode | Test Position | Frequency | | Actual duty factor | maximum duty factor | Reported SAR (1g)(W/kg) | Scaled reported SAR (1g)(W/kg) |
| | | CH | MHz | | | | |
| 802.11b 1Mbps | Left-Cheek | 6 | 2437 | 91.00% | 100% | 0.22 | 0.24 |
| | Left-Tilt | 6 | 2437 | 91.00% | 100% | 0.18 | 0.20 |
| | Right-Cheek | 6 | 2437 | 91.00% | 100% | 0.20 | 0.22 |
| | Right-Tilt | 6 | 2437 | 91.00% | 100% | 0.17 | 0.19 |

Note:
1. According to the KDB248227 D01, The reported SAR must be scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit. A maximum transmission duty factor of 91.00% is achievable for WLAN in this project.

## Body SAR

| GSM850 | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|
| Mode | Test Position | Frequency | | Conducted Power (dBm) | Tune up limit (dBm) | Tune up scaling factor | Power Drift(dB) | Measured SAR(1g) (W/kg) | Report SAR(1g) (W/kg) | Test Plot |
| | | CH | MHz | | | | | | | |
| GPRS (4Tx slot) | Front | 128 | 824.2 | 27.35 | 28.00 | 1.16 | - | - | - | - |
| | | 190 | 836.6 | 27.56 | 28.00 | 1.11 | 0.04 | 0.620 | 0.69 | - |
| | | 251 | 848.8 | 27.65 | 28.00 | 1.08 | - | - | - | - |
| | Back | 128 | 824.2 | 27.35 | 28.00 | 1.16 | -0.06 | 0.889 | 1.03 | - |
| | | 190 | 836.6 | 27.56 | 28.00 | 1.11 | -0.08 | 0.940 | 1.04 | B1 |
| | | 251 | 848.8 | 27.65 | 28.00 | 1.08 | -0.12 | 0.912 | 0.99 | - |

| PCS1900 | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|
| Mode | Test Position | Frequency | | Conducted Power (dBm) | Tune up limit (dBm) | Tune up scaling factor | Power Drift(dB) | Measured SAR(1g) (W/kg) | Report SAR(1g) (W/kg) | Test Plot |
| | | CH | MHz | | | | | | | |
| GPRS (4Tx slot) | Front | 512 | 1850.2 | 25.36 | 26.00 | 1.16 | - | - | - | - |
| | | 661 | 1880.0 | 25.28 | 26.00 | 1.18 | 0.04 | 0.371 | 0.44 | - |
| | | 810 | 1909.8 | 25.29 | 26.00 | 1.18 | - | - | - | - |
| | Back | 512 | 1850.2 | 25.36 | 26.00 | 1.16 | - | - | - | - |
| | | 661 | 1880.0 | 25.28 | 26.00 | 1.18 | -0.05 | 0.569 | 0.67 | B2 |
| | | 810 | 1909.8 | 25.29 | 26.00 | 1.18 | - | - | - | - |

| WCDMA Band V | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|
| Mode | Test Position | Frequency | | Conducted Power (dBm) | Tune up limit (dBm) | Tune up scaling factor | Power Drift(dB) | Measured SAR(1g) (W/kg) | Report SAR(1g) (W/kg) | Test Plot |
| | | CH | MHz | | | | | | | |
| RMC 12.2Kbps | Front | 4132 | 826.4 | 23.24 | 24.00 | 1.19 | - | - | - | - |
| | | 4183 | 836.6 | 23.29 | 24.00 | 1.18 | 0.00 | 0.636 | 0.75 | - |
| | | 4233 | 846.6 | 23.12 | 24.00 | 1.22 | - | - | - | - |
| | Back | 4132 | 826.4 | 23.24 | 24.00 | 1.19 | 0.03 | 0.861 | 1.03 | - |
| | | 4183 | 836.6 | 23.29 | 24.00 | 1.18 | 0.00 | 0.894 | 1.05 | B3 |
| | | 4233 | 846.6 | 23.12 | 24.00 | 1.22 | 0.07 | 0.833 | 1.02 | - |

| WCDMA Band II | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|
| Mode | Test Position | Frequency | | Conducted Power (dBm) | Tune up limit (dBm) | Tune up scaling factor | Power Drift(dB) | Measured SAR(1g) (W/kg) | Report SAR(1g) (W/kg) | Test Plot |
| | | CH | MHz | | | | | | | |
| RMC 12.2Kbps | Front | 9262 | 1852.4 | 23.98 | 24.00 | 1.01 | - | - | - | - |
| | | 9400 | 1880.0 | 23.94 | 24.00 | 1.01 | -0.08 | 0.734 | 0.74 | - |
| | | 9538 | 1907.6 | 23.97 | 24.00 | 1.01 | - | - | - | - |
| | Back | 9262 | 1852.4 | 23.98 | 24.00 | 1.01 | -0.06 | 1.02 | 1.03 | - |
| | | 9400 | 1880.0 | 23.94 | 24.00 | 1.01 | -0.18 | 1.07 | 1.08 | B4 |
| | | 9538 | 1907.6 | 23.97 | 24.00 | 1.01 | -0.12 | 1.04 | 1.05 | - |

| LTEBand II | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|
| Mode | Test Position | Frequency | | Conducted Power (dBm) | Tune up limit (dBm) | Tune up scaling factor | Power Drift(dB) | Measured SAR(1g) (W/kg) | Report SAR(1g) (W/kg) | Test Plot |
| | | CH | MHz | | | | | | | |
| 20M_1RB | Front | 18700 | 1860.0 | 22.10 | 23.00 | 1.23 | - | - | - | - |
| | | 18900 | 1880.0 | 22.17 | 23.00 | 1.21 | -0.05 | 0.501 | 0.61 | - |
| | | 19100 | 1900.0 | 22.07 | 23.00 | 1.24 | - | - | - | - |
| | Back | 18700 | 1860.0 | 22.10 | 23.00 | 1.23 | 0.07 | 0.741 | 0.91 | - |
| | | 18900 | 1880.0 | 22.17 | 23.00 | 1.21 | 0.11 | 0.759 | 0.92 | B5 |
| | | 19100 | 1900.0 | 22.07 | 23.00 | 1.24 | 0.11 | 0.735 | 0.91 | - |
| 20M_50RB | Front | 18700 | 1860.0 | 21.47 | 22.00 | 1.13 | - | - | - | - |
| | | 18900 | 1880.0 | 21.54 | 22.00 | 1.11 | 0.03 | 0.341 | 0.38 | - |
| | | 19100 | 1900.0 | 21.35 | 22.00 | 1.16 | - | - | - | - |
| | Back | 18700 | 1860.0 | 21.47 | 22.00 | 1.13 | - | - | - | - |
| | | 18900 | 1880.0 | 21.54 | 22.00 | 1.11 | -0.06 | 0.517 | 0.57 | - |
| | | 19100 | 1900.0 | 21.35 | 22.00 | 1.16 | - | - | - | - |
| 20M_100RB | Back | 18900 | 1880.0 | 21.47 | 22.00 | 1.11 | -0.12 | 0.506 | 0.56 | - |

| LTEBand IV | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|
| Mode | Test Position | Frequency | | Conducted Power (dBm) | Tune up limit (dBm) | Tune up scaling factor | Power Drift(dB) | Measured SAR(1g) (W/kg) | Report SAR(1g) (W/kg) | Test Plot |
| | | CH | MHz | | | | | | | |
| 20M_1RB | Front | 20050 | 1720 | 22.29 | 23.00 | 1.18 | - | - | - | - |
| | | 20175 | 1732.5 | 22.35 | 23.00 | 1.16 | -0.05 | 0.524 | 0.61 | - |
| | | 20300 | 1745 | 22.30 | 23.00 | 1.17 | - | - | - | - |
| | Back | 20050 | 1720 | 22.29 | 23.00 | 1.18 | 0.02 | 0.768 | 0.90 | - |
| | | 20175 | 1732.5 | 22.35 | 23.00 | 1.16 | 0.07 | 0.803 | 0.93 | B6 |
| | | 20300 | 1745 | 22.30 | 23.00 | 1.17 | 0.13 | 0.782 | 0.92 | - |
| 20M_50RB | Front | 20050 | 1720 | 21.66 | 22.00 | 1.08 | - | - | - | - |
| | | 20175 | 1732.5 | 21.72 | 22.00 | 1.07 | 0.08 | 0.354 | 0.38 | - |
| | | 20300 | 1745 | 21.58 | 22.00 | 1.10 | - | - | - | - |
| | Back | 20050 | 1720 | 21.66 | 22.00 | 1.08 | - | - | - | - |
| | | 20175 | 1732.5 | 21.72 | 22.00 | 1.07 | -0.10 | 0.543 | 0.58 | - |
| | | 20300 | 1745 | 21.58 | 22.00 | 1.10 | - | - | - | - |
| 20M_100RB | Back | 20175 | 1732.5 | 21.65 | 22.00 | 1.07 | 0.10 | 0.510 | 0.55 | - |

| LTEBand V | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|
| Mode | Test Position | Frequency | | Conducted Power (dBm) | Tune up limit (dBm) | Tune up scaling factor | Power Drift(dB) | Measured SAR(1g) (W/kg) | Report SAR(1g) (W/kg) | Test Plot |
| | | CH | MHz | | | | | | | |
| 10M_1RB | Front | 20450 | 829 | 22.72 | 23.00 | 1.07 | - | - | - | - |
| | | 20525 | 836.5 | 22.75 | 23.00 | 1.06 | 0.00 | 0.423 | 0.45 | - |
| | | 20600 | 844 | 22.68 | 23.00 | 1.08 | - | - | - | - |
| | Back | 20450 | 829 | 22.72 | 23.00 | 1.07 | - | - | - | - |
| | | 20525 | 836.5 | 22.75 | 23.00 | 1.06 | 0.00 | 0.594 | 0.63 | B7 |
| | | 20600 | 844 | 22.68 | 23.00 | 1.08 | - | - | - | - |
| 10M_25RB | Front | 20450 | 829 | 21.61 | 22.00 | 1.09 | - | - | - | - |
| | | 20525 | 836.5 | 21.62 | 22.00 | 1.09 | 0.01 | 0.311 | 0.34 | - |
| | | 20600 | 844 | 21.57 | 22.00 | 1.10 | - | - | - | - |
| | Back | 20450 | 829 | 21.61 | 22.00 | 1.09 | - | - | - | - |
| | | 20525 | 836.5 | 21.62 | 22.00 | 1.09 | -0.03 | 0.437 | 0.48 | - |
| | | 20600 | 844 | 21.57 | 22.00 | 1.10 | - | - | - | - |

| LTE Band 12 | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|
| Mode | Test Position | Frequency | | Conducted Power (dBm) | Tune up limit (dBm) | Tune up scaling factor | Power Drift(dB) | Measured SAR(1g) (W/kg) | Report SAR(1g) (W/kg) | Test Plot |
| | | CH | MHz | | | | | | | |
| 10M_1RB | Front | 23060 | 704 | 22.79 | 23.00 | 1.05 | - | - | - | - |
| | | 23095 | 707.5 | 22.76 | 23.00 | 1.06 | -0.04 | 0.179 | 0.19 | - |
| | | 23130 | 711 | 22.72 | 23.00 | 1.07 | - | - | - | - |
| | Back | 23060 | 704 | 22.79 | 23.00 | 1.05 | - | - | - | - |
| | | 23095 | 707.5 | 22.76 | 23.00 | 1.06 | -0.1 | 0.261 | 0.28 | B8 |
| | | 23130 | 711 | 22.72 | 23.00 | 1.07 | - | - | - | - |
| 10M_25RB | Front | 23060 | 704 | 21.63 | 22.00 | 1.09 | - | - | - | - |
| | | 23095 | 707.5 | 21.58 | 22.00 | 1.10 | -0.05 | 0.128 | 0.14 | - |
| | | 23130 | 711 | 21.72 | 22.00 | 1.07 | - | - | - | - |
| | Back | 23060 | 704 | 21.63 | 22.00 | 1.09 | - | - | - | - |
| | | 23095 | 707.5 | 21.58 | 22.00 | 1.10 | -0.12 | 0.186 | 0.20 | - |
| | | 23130 | 711 | 21.72 | 22.00 | 1.07 | - | - | - | - |

Note:

1. Per KDB865664 D01v01r04, Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg
2. Per KDB 941225 D05v02r03, for QPSK with 100% RB allocation, SAR is not required when the highest maximumoutput power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations andthe highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highestoutput power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also betested.

| WLAN | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|
| Mode | Test Position | Frequency | | Conducted Power (dBm) | Tune up limit (dBm) | Tune up scaling factor | Power Drift(dB) | Measured SAR(1g) (W/kg) | Report SAR(1g) (W/kg) | Test Plot |
| | | CH | MHz | | | | | | | |
| 802.11b 1Mbps | Front | 1 | 2412 | 14.63 | 15.00 | 1.09 | - | - | - | - |
| | | 6 | 2437 | 14.63 | 15.00 | 1.09 | -0.25 | 0.096 | 0.11 | - |
| | | 11 | 2462 | 14.47 | 15.00 | 1.13 | - | - | - | - |
| | Back | 1 | 2412 | 14.63 | 15.00 | 1.09 | - | - | - | - |
| | | 6 | 2437 | 14.63 | 15.00 | 1.09 | 0.17 | 0.157 | 0.17 | B9 |
| | | 11 | 2462 | 14.47 | 15.00 | 1.13 | - | - | - | - |

Note:

1. According to the above table, the initial test position for body is “Back”, and its reported SAR is≤ 0.4W/kg. Thus further SAR measurement is not required for the other (remaining) test positions. Because the reported SAR of the highest measured maximum output power channel for the exposureconfiguration is ≤ 0.8W/kg, no further SAR testing is required for 802.11b DSSS in that exposureconfiguration.
2. When SAR measurement is required for 2.4 GHz 802.11g/n OFDM configurations, the measurement and test reduction procedures for OFDM are applied. SAR is not required for the following 2.4 GHz OFDM conditions.
   c) When KDB Publication 447498 D01 SAR test exclusion applies to the OFDM configuration.
   d) When the highest *reported* SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg. the 802.11g/n is not required.

## Hotspot SAR

| Positions for SAR tests; Hotspot mode | | | | | | |
|---|---|---|---|---|---|---|
| Antenna | Back | Front | Top side | Bottom side | Right side | Left side |
| WWAN | Yes | Yes | No | Yes | Yes | Yes |
| WIFI / BT | Yes | Yes | No | Yes | Yes | No |

General note:
Referring to KDB941225 D06, when the overall device length and width are >9cm*5cm, the test distance is 10mm. SAR must be measured for all sides and surfaces with a transmitting antenna located within 25mm from that surface or edge.

| GSM850 | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| Mode | Test Position | Frequency | | Conducted Power (dBm) | Tune up limit (dBm) | Tune up scaling factor | Power Drift(dB) | Measured SAR(1g) (W/kg) | Report SAR(1g) (W/kg) |
| | | CH | MHz | | | | | | |
| GPRS (4Tx slot) | Front | 128 | 824.2 | 27.35 | 28.00 | 1.16 | - | - | - |
| | | 190 | 836.6 | 27.56 | 28.00 | 1.11 | 0.04 | 0.620 | 0.69 |
| | | 251 | 848.8 | 27.65 | 28.00 | 1.08 | - | - | - |
| | Back | 128 | 824.2 | 27.35 | 28.00 | 1.16 | -0.06 | 0.889 | 1.03 |
| | | 190 | 836.6 | 27.56 | 28.00 | 1.11 | -0.08 | 0.940 | 1.04 |
| | | 251 | 848.8 | 27.65 | 28.00 | 1.08 | -0.12 | 0.912 | 0.99 |
| | Left | 190 | 836.6 | 27.56 | 28.00 | 1.11 | 0.05 | 0.414 | 0.46 |
| | Right | 190 | 836.6 | 27.56 | 28.00 | 1.11 | -0.03 | 0.300 | 0.33 |
| | Top | 190 | 836.6 | 27.56 | 28.00 | 1.11 | - | - | - |
| | Bottom | 190 | 836.6 | 27.56 | 28.00 | 1.11 | -0.11 | 0.536 | 0.59 |

| PCS1900 | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| Mode | Test Position | Frequency | | Conducted Power (dBm) | Tune up limit (dBm) | Tune up scaling factor | Power Drift(dB) | Measured SAR(1g) (W/kg) | Report SAR(1g) (W/kg) |
| | | CH | MHz | | | | | | |
| GPRS (4Tx slot) | Front | 512 | 1850.2 | 25.36 | 26.00 | 1.16 | - | - | - |
| | | 661 | 1880.0 | 25.28 | 26.00 | 1.18 | 0.04 | 0.371 | 0.44 |
| | | 810 | 1909.8 | 25.29 | 26.00 | 1.18 | - | - | - |
| | Back | 512 | 1850.2 | 25.36 | 26.00 | 1.16 | - | - | - |
| | | 661 | 1880.0 | 25.28 | 26.00 | 1.18 | -0.05 | 0.569 | 0.67 |
| | | 810 | 1909.8 | 25.29 | 26.00 | 1.18 | - | - | - |
| | Left | 661 | 1880.0 | 25.28 | 26.00 | 1.18 | 0.02 | 0.248 | 0.29 |
| | Right | 661 | 1880.0 | 25.28 | 26.00 | 1.18 | 0.01 | 0.189 | 0.22 |
| | Top | 661 | 1880.0 | 25.28 | 26.00 | 1.18 | - | - | - |
| | Bottom | 661 | 1880.0 | 25.28 | 26.00 | 1.18 | -0.05 | 0.324 | 0.38 |

| WCDMA Band V | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| Mode | Test Position | Frequency | | Conducted Power (dBm) | Tune up limit (dBm) | Tune up scaling factor | Power Drift(dB) | Measured SAR(1g) (W/kg) | Report SAR(1g) (W/kg) |
| | | CH | MHz | | | | | | |
| RMC 12.2Kbps | Front | 4132 | 826.4 | 23.24 | 24.00 | 1.19 | - | - | - |
| | | 4183 | 836.6 | 23.29 | 24.00 | 1.18 | 0.00 | 0.636 | 0.75 |
| | | 4233 | 846.6 | 23.12 | 24.00 | 1.22 | - | - | - |
| | Back | 4132 | 826.4 | 23.24 | 24.00 | 1.19 | 0.03 | 0.861 | 1.03 |
| | | 4183 | 836.6 | 23.29 | 24.00 | 1.18 | 0.00 | 0.894 | 1.05 |
| | | 4233 | 846.6 | 23.12 | 24.00 | 1.22 | 0.07 | 0.833 | 1.02 |
| | Left | 4183 | 836.6 | 23.29 | 24.00 | 1.18 | 0.00 | 0.424 | 0.50 |
| | Right | 4183 | 836.6 | 23.29 | 24.00 | 1.18 | 0.00 | 0.394 | 0.46 |
| | Top | 4183 | 836.6 | 23.29 | 24.00 | 1.18 | - | - | - |
| | Bottom | 4183 | 836.6 | 23.29 | 24.00 | 1.18 | 0.00 | 0.510 | 0.60 |

| WCDMA Band II | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| Mode | Test Position | Frequency | | Conducted Power (dBm) | Tune up limit (dBm) | Tune up scaling factor | Power Drift(dB) | Measured SAR(1g) (W/kg) | Report SAR(1g) (W/kg) |
| | | CH | MHz | | | | | | |
| RMC 12.2Kbps | Front | 9262 | 1852.4 | 23.98 | 24.00 | 1.01 | - | - | - |
| | | 9400 | 1880.0 | 23.94 | 24.00 | 1.01 | -0.08 | 0.734 | 0.74 |
| | | 9538 | 1907.6 | 23.97 | 24.00 | 1.01 | - | - | - |
| | Back | 9262 | 1852.4 | 23.98 | 24.00 | 1.01 | -0.06 | 1.02 | 1.03 |
| | | 9400 | 1880.0 | 23.94 | 24.00 | 1.01 | -0.18 | 1.07 | 1.08 |
| | | 9538 | 1907.6 | 23.97 | 24.00 | 1.01 | -0.12 | 1.04 | 1.05 |
| | Left | 9400 | 1880.0 | 23.94 | 24.00 | 1.01 | 0.13 | 0.507 | 0.51 |
| | Right | 9400 | 1880.0 | 23.94 | 24.00 | 1.01 | -0.10 | 0.577 | 0.58 |
| | Top | 9400 | 1880.0 | 23.94 | 24.00 | 1.01 | - | - | - |
| | Bottom | 9400 | 1880.0 | 23.94 | 24.00 | 1.01 | -0.09 | 0.553 | 0.56 |

| LTE Band II | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| Mode | Test Position | Frequency | | Conducted Power (dBm) | Tune up limit (dBm) | Tune up scaling factor | Power Drift(dB) | Measured SAR(1g) (W/kg) | Report SAR(1g) (W/kg) |
| | | CH | MHz | | | | | | |
| 20M_1RB | Front | 18700 | 1860.0 | 22.10 | 23.00 | 1.23 | - | - | - |
| | | 18900 | 1880.0 | 22.17 | 23.00 | 1.21 | -0.05 | 0.501 | 0.61 |
| | | 19100 | 1900.0 | 22.07 | 23.00 | 1.24 | - | - | - |
| | Back | 18700 | 1860.0 | 22.10 | 23.00 | 1.23 | 0.07 | 0.741 | 0.91 |
| | | 18900 | 1880.0 | 22.17 | 23.00 | 1.21 | 0.11 | 0.759 | 0.92 |
| | | 19100 | 1900.0 | 22.07 | 23.00 | 1.24 | 0.11 | 0.735 | 0.91 |
| | Left | 18900 | 1880.0 | 22.17 | 23.00 | 1.21 | -0.06 | 0.334 | 0.40 |
| | Right | 18900 | 1880.0 | 22.17 | 23.00 | 1.21 | 0.04 | 0.242 | 0.29 |
| | Top | 18900 | 1880.0 | 22.17 | 23.00 | 1.21 | - | - | - |
| | Bottom | 18900 | 1880.0 | 22.17 | 23.00 | 1.21 | 0.15 | 0.433 | 0.52 |
| 20M_50RB | Front | 18700 | 1860.0 | 21.47 | 22.00 | 1.13 | - | - | - |
| | | 18900 | 1880.0 | 21.54 | 22.00 | 1.11 | 0.03 | 0.341 | 0.38 |
| | | 19100 | 1900.0 | 21.35 | 22.00 | 1.16 | - | - | - |
| | Back | 18700 | 1860.0 | 21.47 | 22.00 | 1.13 | - | - | - |
| | | 18900 | 1880.0 | 21.54 | 22.00 | 1.11 | -0.06 | 0.517 | 0.57 |
| | | 19100 | 1900.0 | 21.35 | 22.00 | 1.16 | - | - | - |
| | Left | 18900 | 1880.0 | 21.54 | 22.00 | 1.11 | 0.04 | 0.227 | 0.25 |
| | Right | 18900 | 1880.0 | 21.54 | 22.00 | 1.11 | -0.02 | 0.165 | 0.18 |
| | Bottom | 18900 | 1880.0 | 21.54 | 22.00 | 1.11 | -0.09 | 0.295 | 0.33 |
| 20M_100RB | Back | 18900 | 1880.0 | 21.47 | 22.00 | 1.11 | -0.12 | 0.506 | 0.56 |

| LTE Band IV | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| Mode | Test Position | Frequency | | Conducted Power (dBm) | Tune up limit (dBm) | Tune up scaling factor | Power Drift(dB) | Measured SAR(1g) (W/kg) | Report SAR(1g) (W/kg) |
| | | CH | MHz | | | | | | |
| 20M_1RB | Front | 20050 | 1720 | 22.29 | 23.00 | 1.18 | - | - | - |
| | | 20175 | 1732.5 | 22.35 | 23.00 | 1.16 | -0.05 | 0.524 | 0.61 |
| | | 20300 | 1745 | 22.30 | 23.00 | 1.17 | - | - | - |
| | Back | 20050 | 1720 | 22.29 | 23.00 | 1.18 | 0.02 | 0.768 | 0.90 |
| | | 20175 | 1732.5 | 22.35 | 23.00 | 1.16 | 0.07 | 0.803 | 0.93 |
| | | 20300 | 1745 | 22.30 | 23.00 | 1.17 | 0.13 | 0.782 | 0.92 |
| | Left | 20175 | 1732.5 | 22.35 | 23.00 | 1.16 | -0.03 | 0.350 | 0.41 |
| | Right | 20175 | 1732.5 | 22.35 | 23.00 | 1.16 | -0.02 | 0.266 | 0.31 |
| | Top | 20175 | 1732.5 | 22.35 | 23.00 | 1.16 | - | - | - |
| | Bottom | 20175 | 1732.5 | 22.35 | 23.00 | 1.16 | 0.07 | 0.458 | 0.53 |
| 20M_50RB | Front | 20050 | 1720 | 21.66 | 22.00 | 1.08 | - | - | - |
| | | 20175 | 1732.5 | 21.72 | 22.00 | 1.07 | 0.08 | 0.354 | 0.38 |
| | | 20300 | 1745 | 21.58 | 22.00 | 1.10 | - | - | - |
| | Back | 20050 | 1720 | 21.66 | 22.00 | 1.08 | - | - | - |
| | | 20175 | 1732.5 | 21.72 | 22.00 | 1.07 | -0.10 | 0.543 | 0.58 |
| | | 20300 | 1745 | 21.58 | 22.00 | 1.10 | - | - | - |
| | Left | 20175 | 1732.5 | 21.72 | 22.00 | 1.07 | 0.05 | 0.236 | 0.25 |
| | Right | 20175 | 1732.5 | 21.72 | 22.00 | 1.07 | 0.03 | 0.180 | 0.19 |
| | Top | 20175 | 1732.5 | 21.72 | 22.00 | 1.07 | - | - | - |
| | Bottom | 20175 | 1732.5 | 21.72 | 22.00 | 1.07 | -0.11 | 0.310 | 0.33 |
| 20M_100RB | Back | 20175 | 1732.5 | 21.65 | 22.00 | 1.07 | 0.10 | 0.510 | 0.55 |

| LTE Band V | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| Mode | Test Position | Frequency | | Conducted Power (dBm) | Tune up limit (dBm) | Tune up scaling factor | Power Drift(dB) | Measured SAR(1g) (W/kg) | Report SAR(1g) (W/kg) |
| | | CH | MHz | | | | | | |
| 10M_1RB | Front | 20450 | 829 | 22.72 | 23.00 | 1.07 | - | - | - |
| | | 20525 | 836.5 | 22.75 | 23.00 | 1.06 | 0.00 | 0.423 | 0.45 |
| | | 20600 | 844 | 22.68 | 23.00 | 1.08 | - | - | - |
| | Back | 20450 | 829 | 22.72 | 23.00 | 1.07 | - | - | - |
| | | 20525 | 836.5 | 22.75 | 23.00 | 1.06 | 0.00 | 0.594 | 0.63 |
| | | 20600 | 844 | 22.68 | 23.00 | 1.08 | - | - | - |
| | Left | 20525 | 836.5 | 22.75 | 23.00 | 1.06 | 0.00 | 0.282 | 0.30 |
| | Right | 20525 | 836.5 | 22.75 | 23.00 | 1.06 | 0.00 | 0.262 | 0.28 |
| | Top | 20525 | 836.5 | 22.75 | 23.00 | 1.06 | - | - | - |
| | Bottom | 20525 | 836.5 | 22.75 | 23.00 | 1.06 | 0.00 | 0.339 | 0.36 |
| 10M_25RB | Front | 20450 | 829 | 21.61 | 22.00 | 1.09 | - | - | - |
| | | 20525 | 836.5 | 21.62 | 22.00 | 1.09 | 0.01 | 0.311 | 0.34 |
| | | 20600 | 844 | 21.57 | 22.00 | 1.10 | - | - | - |
| | Back | 20450 | 829 | 21.61 | 22.00 | 1.09 | - | - | - |
| | | 20525 | 836.5 | 21.62 | 22.00 | 1.09 | -0.03 | 0.437 | 0.48 |
| | | 20600 | 844 | 21.57 | 22.00 | 1.10 | - | - | - |
| | Left | 20525 | 836.5 | 21.62 | 22.00 | 1.09 | -0.05 | 0.207 | 0.23 |
| | Right | 20525 | 836.5 | 21.62 | 22.00 | 1.09 | 0.03 | 0.193 | 0.21 |
| | Top | 20525 | 836.5 | 21.62 | 22.00 | 1.09 | - | - | - |
| | Bottom | 20525 | 836.5 | 21.62 | 22.00 | 1.09 | 0.01 | 0.249 | 0.27 |

Note:
1. Per KDB865664 D01v01r04, Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg
2. Per KDB 941225 D05v02r03, for QPSK with 100% RB allocation, SAR is not required when the highest maximumoutput power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations andthe highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highestoutput power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also betested.

| LTE Band 12 | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| Mode | Test Position | Frequency | | Conducted Power (dBm) | Tune up limit (dBm) | Tune up scaling factor | Power Drift(dB) | Measured SAR(1g) (W/kg) | Report SAR(1g) (W/kg) |
| | | CH | MHz | | | | | | |
| 10M_1RB | Front | 23060 | 704 | 22.79 | 23.00 | 1.05 | - | - | - |
| | | 23095 | 707.5 | 22.76 | 23.00 | 1.06 | -0.04 | 0.179 | 0.19 |
| | | 23130 | 711 | 22.72 | 23.00 | 1.07 | - | - | - |
| | Back | 23060 | 704 | 22.79 | 23.00 | 1.05 | - | - | - |
| | | 23095 | 707.5 | 22.76 | 23.00 | 1.06 | -0.1 | 0.261 | 0.28 |
| | | 23130 | 711 | 22.72 | 23.00 | 1.07 | - | - | - |
| | Left | 23095 | 707.5 | 22.76 | 23.00 | 1.06 | 0.07 | 0.124 | 0.13 |
| | Right | 23095 | 707.5 | 22.76 | 23.00 | 1.06 | -0.13 | 0.141 | 0.15 |
| | Top | 23095 | 707.5 | 22.76 | 23.00 | 1.06 | - | - | - |
| | Bottom | 23095 | 707.5 | 22.76 | 23.00 | 1.06 | -0.05 | 0.135 | 0.14 |
| 10M_25RB | Front | 23060 | 704 | 21.63 | 22.00 | 1.09 | - | - | - |
| | | 23095 | 707.5 | 21.58 | 22.00 | 1.10 | -0.05 | 0.128 | 0.14 |
| | | 23130 | 711 | 21.72 | 22.00 | 1.07 | - | - | - |
| | Back | 23060 | 704 | 21.63 | 22.00 | 1.09 | - | - | - |
| | | 23095 | 707.5 | 21.58 | 22.00 | 1.10 | -0.12 | 0.186 | 0.20 |
| | | 23130 | 711 | 21.72 | 22.00 | 1.07 | - | - | - |
| | Left | 23095 | 707.5 | 21.63 | 22.00 | 1.09 | 0.09 | 0.088 | 0.10 |
| | Right | 23095 | 707.5 | 21.58 | 22.00 | 1.10 | -0.15 | 0.100 | 0.11 |
| | Top | 23095 | 707.5 | 21.72 | 22.00 | 1.07 | - | - | - |
| | Bottom | 23095 | 707.5 | 21.63 | 22.00 | 1.09 | -0.06 | 0.096 | 0.10 |

Note:

1. Per KDB865664 D01v01r04, Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg
2. Per KDB 941225 D05v02r03, for QPSK with 100% RB allocation, SAR is not required when the highest maximumoutput power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations andthe highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highestoutput power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also betested.

| WLAN | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| Mode | Test Position | Frequency | | Conducted Power (dBm) | Tune up limit (dBm) | Tune up scaling factor | Power Drift(dB) | Measured SAR(1g) (W/kg) | Report SAR(1g) (W/kg) |
| | | CH | MHz | | | | | | |
| 802.11b 1Mbps | Front | 1 | 2412 | 14.63 | 15.00 | 1.09 | - | - | - |
| | | 6 | 2437 | 14.63 | 15.00 | 1.09 | -0.25 | 0.096 | 0.11 |
| | | 11 | 2462 | 14.47 | 15.00 | 1.13 | - | - | - |
| | Back | 1 | 2412 | 14.63 | 15.00 | 1.09 | - | - | - |
| | | 6 | 2437 | 14.63 | 15.00 | 1.09 | 0.17 | 0.157 | 0.17 |
| | | 11 | 2462 | 14.47 | 15.00 | 1.13 | - | - | - |
| | Left | 6 | 2437 | 14.63 | 15.00 | 1.09 | 0.13 | 0.024 | 0.03 |
| | Right | 6 | 2437 | 14.63 | 15.00 | 1.09 | -0.14 | 0.056 | 0.06 |
| | Top | 6 | 2437 | 14.63 | 15.00 | 1.09 | - | - | - |
| | Bottom | 6 | 2437 | 14.63 | 15.00 | 1.09 | 0.22 | 0.081 | 0.09 |

Note:

1. According to the above table, the initial test position for body is “Back”, and its reported SAR is≤ 0.4W/kg. Thus further SAR measurement is not required for the other (remaining) test positions. Because the reported SAR of the highest measured maximum output power channel for the exposureconfiguration is ≤ 0.8W/kg, no further SAR testing is required for 802.11b DSSS in that exposureconfiguration.
2. When SAR measurement is required for 2.4 GHz 802.11g/n OFDM configurations, the measurement and test reduction procedures for OFDM are applied. SAR is not required for the following 2.4 GHz OFDM conditions.
   a) When KDB Publication 447498 D01 SAR test exclusion applies to the OFDM configuration.
   b) When the highest *reported* SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg. the 802.11g/n is not required

| WLAN- Scaled Reported SAR | | | | | | | |
|---|---|---|---|---|---|---|---|
| Mode | Test Position | Frequency | | Actual duty factor | maximum duty factor | Reported SAR (1g)(W/kg) | Scaled reported SAR (1g)(W/kg) |
| | | CH | MHz | | | | |
| 802.11b 1Mbps | Front | 6 | 2437 | 91.00% | 100% | 0.11 | 0.12 |
| | Back | 6 | 2437 | 91.00% | 100% | 0.17 | 0.19 |
| | Left | 6 | 2437 | 91.00% | 100% | 0.03 | 0.03 |
| | Right | 6 | 2437 | 91.00% | 100% | 0.06 | 0.07 |
| | Bottom | 6 | 2437 | 91.00% | 100% | 0.09 | 0.10 |

Note:

1. According to the KDB248227 D01, The reported SAR must be scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit. A maximum transmission duty factor of 91.00% is achievable for WLAN in this project.

# 15. SAR Measurement Variability

SAR measurement variability must be assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media are required for SAR measurements in a frequency band, the variability measurement procedures should be applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium.
The following procedures are applied to determine if repeated measurements are required.
1) Repeated measurement is not required when the original highest measured SAR is < 0.80 W/kg; steps 2) through 4) do not apply.
2) When the original highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
3) Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is ≥ 1.45 W/kg (~ 10% from the 1-g SAR limit).
4) Perform a third repeated measurement only if the original, first or second repeated measurement is ≥ 1.5 W/kg and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20.

SAR Measurement Variability for Body GSM850 (1g)

| Frequency | | Mode | Test Position | Spacing (mm) | Original SAR (W/kg) | First Repeated SAR (W/kg) | The Ratio | Second Repeated SAR (W/kg) |
|---|---|---|---|---|---|---|---|---|
| CH | MHz | | | | | | | |
| 190 | 836.6 | GPRS (4Tx slot) | Back | 10 | 0.940 | 0.926 | 1.02 | / |

SAR Measurement Variability for Body WCDMA Band V(1g)

| Frequency | | Mode | Test Position | Spacing (mm) | Original SAR (W/kg) | First Repeated SAR (W/kg) | The Ratio | Second Repeated SAR (W/kg) |
|---|---|---|---|---|---|---|---|---|
| CH | MHz | | | | | | | |
| 4183 | 836.6 | RMC 12.2Kbps | Back | 10 | 0.894 | 0.857 | 1.04 | / |

SAR Measurement Variability for Body WCDMA Band II(1g)

| Frequency | | Mode | Test Position | Spacing (mm) | Original SAR (W/kg) | First Repeated SAR (W/kg) | The Ratio | Second Repeated SAR (W/kg) |
|---|---|---|---|---|---|---|---|---|
| CH | MHz | | | | | | | |
| 9400 | 1880.0 | RMC 12.2Kbps | Back | 10 | 1.07 | 1.02 | 1.05 | / |

SAR Measurement Variability for Body LTEBand IV(1g)

| Frequency | | Mode | Test Position | Spacing (mm) | Original SAR (W/kg) | First Repeated SAR (W/kg) | The Ratio | Second Repeated SAR (W/kg) |
|---|---|---|---|---|---|---|---|---|
| CH | MHz | | | | | | | |
| 20175 | 1732.5 | 20M_1RB | Back | 10 | 0.803 | 0.785 | 1.02 | / |

SAR Test Data Plots

| Test mode: | GSM850-GPRS 4TS | Test Position: | Left Head Cheek | Test Plot: | H1 |
|---|---|---|---|---|---|

Date:2016-09-27
Communication System: Customer System; Frequency:836.6 MHz;Duty Cycle:1:2
Medium parameters used (interpolated): f=836.6 MHz; σ=0.91S/m; εr=41.48; ρ=1000 kg/m3
Phantom section: Left Section
DASY5 Configuration:
•Probe: ES3DV3 - SN3292; ConvF(6.53, 6.53, 6.53);
•Sensor-Surface: 4mm (Mechanical Surface Detection)
•Electronics: DAE4 Sn1315; Calibrated: 2016/7/26
•Phantom: SAM 1; Type: SAM;
•Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6824)

**Area Scan (61x111x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.0406 W/kg
**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 2.834 V/m; Power Drift = 0.09 dB
Peak SAR (extrapolated) = 0.048 mW/g
**SAR(1 g) = 0.039 mW/g; SAR(10 g) = 0.031 mW/g**

Maximum value of SAR (measured) = 0.0409 W/kg




Left Head Cheek (GSM850 GPRS 4TS Middle Channel)

| Test mode: | PCS1900 GPRS 4TS | Test Position: | Left Head Cheek | Test Plot: | H2 |
|---|---|---|---|---|---|

Date:2016-09-30
Communication System: Customer System; Frequency: 1880.0 MHz;Duty Cycle: 1:2
Medium parameters used (interpolated): f = 1880.0 MHz; σ = 1.41 mho/m; ε = 40.01; ρ = 1000 kg/m 3
Phantom section: Left Section

DASY5 Configuration:

•Probe: ES3DV3 - SN3292; ConvF(5.26,5.26,5.26); Calibrated: 02/09/2016;
•Sensor-Surface: 4mm (Mechanical Surface Detection)
•Electronics: DAE4 Sn1315; Calibrated: 2016/7/26
•Phantom: SAM 1; Type: SAM;
•Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6824)

**Area Scan (61x111x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.0271 W/kg
**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 1.719 V/m; Power Drift = 0.13 dB
Peak SAR (extrapolated) = 0.037 mW/g
**SAR(1 g) = 0.025 mW/g; SAR(10 g) = 0.015 mW/g**
Maximum value of SAR (measured) = 0.0251 W/kg




Left Head (PCS1900 Middle Channel)

| Test mode: | WCDMA Band V | Test Position: | Left Head Cheek | Test Plot: | H3 |
|---|---|---|---|---|---|

Date:2016-09-27
Communication System: Customer System; Frequency: 836.6 MHz;Duty Cycle:1:1
Medium parameters used (interpolated): f=836.6 MHz; σ=0.91S/m; εr=41.48; ρ=1000 kg/m3
Phantom section: Left Head Section:

**DASY5 Configuration:**
•Probe: ES3DV3 - SN3292; ConvF(6.53, 6.53, 6.53); Calibrated: 02/09/2016;
•Sensor-Surface: 4mm (Mechanical Surface Detection)
•Electronics: DAE4 Sn1315; Calibrated: 26/07/2016
•Phantom: SAM 1; Type: SAM;
•Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6824)

**Area Scan (51x101x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) =0.0392 W/kg

**Zoom Scan (5x5x6**)/Cube 0: Measurement grid: dx=7mm, dy=7mm, dz=5mm
Reference Value = 3.203 V/m; Power Drift = 0.13 dB
Peak SAR (extrapolated) = 0.046 mW/g
**SAR(1 g) = 0.038 mW/g; SAR(10 g) = 0.030 mW/g**

Maximum value of SAR (measured) = 0.0392W/kg




Left Head Cheek (WCDMA Band V Middle Channel)

| Test mode: | WCDMA Band II | Test Position: | Left Head Cheek | Test Plot: | H4 |
|---|---|---|---|---|---|

Date:2016-09-30
Communication System: Customer System; Frequency: 1880.0 MHz;Duty Cycle:1:1
Medium parameters used (interpolated): f =1880.0 MHz; σ = 1.41 mho/m; ε = 40.01; ρ=1000 kg/m3
Phantom section: Left Head Section:

**DASY5 Configuration:**
•Probe: ES3DV3 - SN3292; ConvF(5.26,5.26,5.26); Calibrated: 02/09/2016;
•Sensor-Surface: 4mm (Mechanical Surface Detection)
•Electronics: DAE4 Sn1315; Calibrated: 26/07/2016
•Phantom: SAM 1; Type: SAM;
•Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6824)

**Area Scan (51x101x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) =0.0607 W/kg

**Zoom Scan (5x5x6**)/Cube 0: Measurement grid: dx=7mm, dy=7mm, dz=5mm
Reference Value = 2.796 V/m; Power Drift = 0.17 dB
Peak SAR (extrapolated) = 0.071 mW/g
**SAR(1 g) = 0.050 mW/g; SAR(10 g) = 0.031 mW/g**
Maximum value of SAR (measured) = 0.0620 W/kg




Left Head Cheek (WCDMA Band II Middle Channel)

| Test mode: | LTE Band II | Test Position: | Left Head Cheek | Test Plot: | H5 |
|---|---|---|---|---|---|

Date:2016-09-30
Communication System: Customer System; Frequency: 1880.0 MHz;Duty Cycle:1:1
Medium parameters used (interpolated): f =1880.0 MHz; σ = 1.41 mho/m; ε = 40.01; ρ=1000 kg/m3
Phantom section: Left Head Section:

**DASY5 Configuration:**
•Probe: ES3DV3 - SN3292; ConvF(5.26,5.26,5.26); Calibrated: 02/09/2016;
•Sensor-Surface: 4mm (Mechanical Surface Detection)
•Electronics: DAE4 Sn1315; Calibrated: 26/07/2016
•Phantom: SAM 1; Type: SAM;
•Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6824)

**Area Scan (51x101x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.0691 W/kg
**Zoom Scan (6x6x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 3.039 V/m; Power Drift = -0.11 dB
Peak SAR (extrapolated) = 0.101 mW/g
**SAR(1 g) = 0.065 mW/g; SAR(10 g) = 0.042 mW/g**
Maximum value of SAR (measured) = 0.0684 W/kg




Left Head Cheek (LTE Band II Middle Channel)

| Test mode: | LTE Band IV | Test Position: | Left Head Cheek | Test Plot: | H6 |
|---|---|---|---|---|---|

Date:2016-09-29
Communication System: Generic LTE; Frequency: 1732.5 MHz;Duty Cycle: 1:1
Medium parameters used (interpolated): f = 1732.5 MHz; σ = 1.363 mho/m; εr = 40.136; ρ = 1000 kg/m3
Phantom section: Left Head Section:

**DASY5 Configuration:**
Probe: ES3DV3 - SN3292; ConvF(5.54,5.54,5.54); Calibrated: 02/09/2016;
•Sensor-Surface: 4mm (Mechanical Surface Detection)
•Electronics: DAE4 Sn1315; Calibrated: 26/07/2016
•Phantom: SAM 1; Type: SAM;
•Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6824)

**Area Scan (51x101x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) =0.0576 W/kg

**Zoom Scan (5x5x6**)/Cube 0: Measurement grid: dx=7mm, dy=7mm, dz=5mm
Reference Value = 2.831 V/m; Power Drift = 0.10 dB
Peak SAR (extrapolated) = 0.075 mW/g
**SAR(1 g) = 0.055 mW/g; SAR(10 g) = 0.036 mW/g**

Maximum value of SAR (measured) = 0.0577 W/kg




Left Head Cheek (LTE Band IV Middle Channel)

| Test mode: | LTE Band V | Test Position: | Left Head Cheek | Test Plot: | H7 |
|---|---|---|---|---|---|

Date:2016-09-27
Communication System: Customer System; Frequency: 836.5 MHz;Duty Cycle:1:1
Medium parameters used (interpolated): f =836.5 MHz; σ = 1.91 mho/m; εr=41.48; ρ=1000 kg/m3
Phantom section: Left Head Section:

**DASY5 Configuration:**
•Probe: ES3DV3 - SN3292; ConvF(6.53, 6.53, 6.53); Calibrated: 02/09/2016;
•Sensor-Surface: 4mm (Mechanical Surface Detection)
•Electronics: DAE4 Sn1315; Calibrated: 26/07/2016
•Phantom: SAM 1; Type: SAM;
•Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6824)

**Area Scan (51x101x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) =0.0339 W/kg

**Zoom Scan (5x5x6**)/Cube 0: Measurement grid: dx=7mm, dy=7mm, dz=5mm
Reference Value = 2.501 V/m; Power Drift = -0.11 dB
Peak SAR (extrapolated) = 0.040 mW/g
**SAR(1 g) = 0.032 mW/g; SAR(10 g) = 0.026 mW/g**
Maximum value of SAR (measured) =0.0332 W/kg




Left Head Cheek (LTE Band V Middle Channel)

| Test mode: | LTE Band 12 | Test Position: | Left Head Cheek | Test Plot: | H8 |
|---|---|---|---|---|---|

Date:2016-09-27
Communication System: Generic LTE; Frequency: 707.5 MHz;Duty Cycle: 1:1
Medium parameters used (interpolated): f = 707.5 MHz; σ = 0.86 mho/m; εr = 42.412; ρ = 1000 kg/m3
Phantom section: Left Section
**DASY5 Configuration:**
•Probe: ES3DV3 - SN3292; ConvF(6.76,6.76,6.76); Calibrated: 02/09/2016;
•Sensor-Surface: 4mm (Mechanical Surface Detection)
•Electronics: DAE4 Sn1315; Calibrated: 26/07/2016
•Phantom: SAM 1; Type: SAM;
•Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6824)

**Area Scan (51x101x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.0518 W/kg
**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 3.841 V/m; Power Drift = 0.14 dB
Peak SAR (extrapolated) = 0.060 mW/g
**SAR(1 g) = 0.050 mW/g; SAR(10 g) = 0.040 mW/g**
Maximum value of SAR (measured) = 0.0516 W/kg



Left Head Cheek (LTE Band 12 Middle Channel)

| Test mode: | WLAN 802.11b | Test Position: | Left Head Cheek | Test Plot: | H9 |
|---|---|---|---|---|---|

Date:2016-10-08
Communication System: Customer System; Frequency: 2437.0 MHz;Duty Cycle:1:1
Medium parameters used (interpolated): f=2437.0 MHz; σ=1.78S/m; εr=39.00; ρ=1000 kg/m3
Phantom section: Left Head Section:

**DASY5 Configuration:**

•Probe: ES3DV3 - SN3292; ConvF(4.97,4.97,4.97); Calibrated: 02/09/2016;
•Sensor-Surface: 4mm (Mechanical Surface Detection)
•Electronics: DAE4 Sn1315; Calibrated: 26/07/2016
•Phantom: SAM 1; Type: SAM;
•Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6824)

**Area Scan (51x101x1):** Interpolated grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) =0.217 W/kg

**Zoom Scan (6x6x6**)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 10.106 V/m; Power Drift = -0.15 dB
Peak SAR (extrapolated) = 0.345 mW/g
**SAR(1 g) = 0.200 mW/g; SAR(10 g) = 0.111 mW/g**

Maximum value of SAR (measured) = 0.219W/kg




Left Head Cheek (WLAN middle Channel)

| Test mode: | GSM850 GPRS 4TS | Test Position: | Body- worn Rear Side | Test Plot: | B1 |
|---|---|---|---|---|---|

Date:2016-09-28
Communication System: Customer System; Frequency:836.6 MHz;Duty Cycle:1:2
Medium parameters used (interpolated): f=836.6 MHz; σ=0.97S/m; εr=55.10; ρ=1000 kg/m3
Phantom section: Flat Section:

**DASY 5 Configuration:**
•Probe: ES3DV3 - SN3292; ConvF(6.27, 6.27, 6.27); Calibrated: 02/09/2016;
•Sensor-Surface: 4mm (Mechanical Surface Detection)
•Electronics: DAE4 Sn1315; Calibrated: 26/07/2016
•Phantom: SAM 1; Type: SAM;
•Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6824)

**Area Scan (51x101x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) =1.25W/kg

**Zoom Scan (5x5x6**)/Cube 0: Measurement grid: dx=7mm, dy=7mm, dz=5mm
Reference Value = 7.917 V/m; Power Drift = -0.08 dB
Peak SAR (extrapolated) = 1.767 mW/g
**SAR(1 g) = 0.940 mW/g; SAR(10 g) = 0.654 mW/g**
Maximum value of SAR (measured) = 1.19 W/kg




Body- worn Rear Side (GSM850 GPRS 4TS Middle Channel)

| Test mode: | PCS1900 GPRS 4TS | Test Position: | Body- worn Rear Side | Test Plot: | B2 |
|---|---|---|---|---|---|

Date:2016-09-29
Communication System: Customer System; Frequency: 1880.0 MHz;Duty Cycle: 1:2
Medium parameters used (interpolated): f = 1880.0 MHz; σ = 1.51 mho/m; ε = 53.21; ρ = 1000 kg/m 3
Phantom section: Flat Section

**DASY5 Configuration:**
•Probe: ES3DV3 - SN3292; ConvF(5.05,5.05,5.05); Calibrated: 02/09/2016;
•Sensor-Surface: 4mm (Mechanical Surface Detection)
•Electronics: DAE4 Sn1315; Calibrated: 26/07/2016
•Phantom: SAM 1; Type: SAM;
•Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6824)

**Area Scan (51x101x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) =0.618 W/kg

**Zoom Scan (5x5x6**)/Cube 0: Measurement grid: dx=7mm, dy=7mm, dz=5mm
Reference Value = 3.938 V/m; Power Drift = -0.05 dB
Peak SAR (extrapolated) = 1.081 mW/g
**SAR(1 g) = 0.569 mW/g; SAR(10 g) = 0.316 mW/g**
Maximum value of SAR (measured) = 0.606 W/kg




Body- worn Rear Side (PCS1900 GPRS 4TS Middle Channel)

| Test mode: | WCDMA Band V | Test Position: | Body- worn Rear Side | Test Plot: | B3 |
|---|---|---|---|---|---|

Date:2016-09-28
Communication System: Customer System; Frequency: 836.6 MHz;Duty Cycle:1:1
Medium parameters used (interpolated): f=836.6 MHz; σ=0.97S/m; εr=55.10; ρ=1000 kg/m3
Phantom section: Flat Section

**DASY5 Configuration:**
•Probe: ES3DV3 - SN3292; ConvF(6.27, 6.27, 6.27); Calibrated: 02/09/2016;
•Sensor-Surface: 4mm (Mechanical Surface Detection)
•Electronics: DAE4 Sn1315; Calibrated: 26/07/2016
•Phantom: SAM 1; Type: SAM;
•Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6824)

**Area Scan (51x101x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) =1.16 W/kg

**Zoom Scan (5x5x6**)/Cube 0: Measurement grid: dx=7mm, dy=7mm, dz=5mm
Reference Value = 6.783 V/m; Power Drift = 0.00 dB
Peak SAR (extrapolated) = 1.625 mW/g
**SAR(1 g) = 0.894 mW/g; SAR(10 g) = 0.595 mW/g**
Maximum value of SAR (measured) = 1.09 W/kg




Body- worn Rear Side (WCDMA Band V Middle Channel)

| Test mode: | WCDMA Band II | Test Position: | Body- worn Rear Side | Test Plot: | B4 |
|---|---|---|---|---|---|

Date:2016-09-29
Communication System: Customer System; Frequency: 1880.0 MHz;Duty Cycle:1:1
Medium parameters used (interpolated): f=1880.0 MHz; σ=1.51S/m; εr=53.21; ρ=1000 kg/m3
Phantom section: Flat Section

**DASY5 Configuration:**
•Probe: ES3DV3 - SN3292; ConvF(5.05,5.05,5.05); Calibrated: 02/09/2016;
•Sensor-Surface: 4mm (Mechanical Surface Detection)
•Electronics: DAE4 Sn1315; Calibrated: 26/07/2016
•Phantom: SAM 1; Type: SAM;
•Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6824)

**Area Scan (51x101x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) =1.24W/kg

**Zoom Scan (5x5x6**)/Cube 0: Measurement grid: dx=7mm, dy=7mm, dz=5mm
Reference Value = 5.369 V/m; Power Drift = -0.18 dB
Peak SAR (extrapolated) = 2.081 mW/g
**SAR(1 g) = 1.07 mW/g; SAR(10 g) = 0.636 mW/g**
Maximum value of SAR (measured) = 1.20 W/kg




Body- worn Rear Side (WCDMA Band II Middle Channel)

| Test mode: | LTE Band II | Test Position: | Body- worn Rear Side | Test Plot: | B5 |
|---|---|---|---|---|---|

Date:2016-09-29
Communication System: Customer System; Frequency: 1880.0 MHz;Duty Cycle:1:1
Medium parameters used (interpolated): f=1880.0 MHz; σ=1.51S/m; εr=53.21; ρ=1000 kg/m3
Phantom section: Flat Section

**DASY5 Configuration:**
•Probe: ES3DV3 - SN3292; ConvF(5.05,5.05,5.05); Calibrated: 02/09/2016;
•Sensor-Surface: 4mm (Mechanical Surface Detection)
•Electronics: DAE4 Sn1315; Calibrated: 26/07/2016
•Phantom: SAM 1; Type: SAM;
•Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6824)

**Area Scan (51x101x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.827 W/kg
**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 4.227 V/m; Power Drift = 0.11 dB
Peak SAR (extrapolated) = 1.385 mW/g
**SAR(1 g) = 0.759 mW/g; SAR(10 g) = 0.435 mW/g**
Maximum value of SAR (measured) = 0.815 W/kg




Body- worn Rear Side (LTE Band II Middle Channel)

| Test mode: | LTE Band IV | Test Position: | Body- worn Rear Side | Test Plot: | B6 |
|---|---|---|---|---|---|

Date:2016-09-30
Communication System: Generic LTE; Frequency: 1732.5 MHz;Duty Cycle: 1:1 Medium parameters used (interpolated): f = 1732.5 MHz; σ = 1.459 mho/m; εr = 53.239; ρ = 1000 kg/m3
Phantom section: Flat Section

**DASY5 Configuration:**
•Probe: ES3DV3 - SN3292; ConvF(5.28,5.28,5.28); Calibrated: 02/09/2016;
•Sensor-Surface: 4mm (Mechanical Surface Detection)
•Electronics: DAE4 Sn1315; Calibrated: 26/07/2016
•Phantom: SAM 1; Type: SAM;
•Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6824)

**Area Scan (51x101x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) =0.891W/kg
**Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 5.740 V/m; Power Drift = 0.07 dB
Peak SAR (extrapolated) = 1.358 mW/g
**SAR(1 g) = 0.803 mW/g; SAR(10 g) = 0.476 mW/g**
Maximum value of SAR (measured) = 0.860 W/kg




Body- worn Rear Side (LTE Band IV Middle Channel)

| Test mode: | LTE Band V | Test Position: | Body- worn Rear Side | Test Plot: | B7 |
|---|---|---|---|---|---|

Date:2016-09-28
Communication System: Customer System; Frequency: 836.6 MHz;Duty Cycle:1:1
Medium parameters used (interpolated): f=836.6 MHz; σ=0.97S/m; εr=55.10; ρ=1000 kg/m3
Phantom section: Flat Section

**DASY5 Configuration:**
•Probe: ES3DV3 - SN3292; ConvF(6.27, 6.27, 6.27); Calibrated: 02/09/2016;
•Sensor-Surface: 4mm (Mechanical Surface Detection)
•Electronics: DAE4 Sn1315; Calibrated: 26/07/2016
•Phantom: SAM 1; Type: SAM;
•Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6824)

**Area Scan (51x101x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) =0.650 W/kg

**Zoom Scan (5x5x6**)/Cube 0: Measurement grid: dx=7mm, dy=7mm, dz=5mm
Reference Value = 5.611 V/m; Power Drift = 0.00 dB
Peak SAR (extrapolated) = 0.950 mW/g
**SAR(1 g) = 0.594 mW/g; SAR(10 g) = 0.363 mW/g**
Maximum value of SAR (measured) = 0.650 W/kg




Body- worn Rear Side (LTE Band V Middle Channel)

| Test mode: | LTE Band 12 | Test Position: | Body- worn Rear Side | Test Plot: | B8 |
|---|---|---|---|---|---|

Date:2016-09-28
Communication System: Generic LTE; Frequency: 707.5 MHz;Duty Cycle: 1:1 Medium parameters used (interpolated): f = 707.5 MHz; σ = 0.86 mho/m; εr = 52.412; ρ = 1000 kg/m3
Phantom section: Flat Section

**DASY5 Configuration:**
•Probe: ES3DV3 - SN3292; ConvF(6.25,6.25,6.25); Calibrated: 02/09/2016;
•Sensor-Surface: 4mm (Mechanical Surface Detection)
•Electronics: DAE4 Sn1315; Calibrated: 26/07/2016
•Phantom: SAM 1; Type: SAM;
•Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6824)

**Area Scan (51x101x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.286 W/kg

**Zoom Scan (5x5x6**)/Cube 0: Measurement grid: dx=7mm, dy=7mm, dz=5mm
Reference Value = 6.167 V/m; Power Drift = -0.10 dB
Peak SAR (extrapolated) = 0.424 mW/g
**SAR(1 g) = 0.261 mW/g; SAR(10 g) = 0.158 mW/g**
Maximum value of SAR (measured) = 0.285 W/kg




Body- worn Rear Side (LTE Band 12 Middle Channel)

| Test mode: | WLAN 802.11b | Test Position: | Body- worn Rear Side | Test Plot: | B9 |
|---|---|---|---|---|---|

Date:2016-10-08
Communication System: Customer System; Frequency: 2437.0 MHz;Duty Cycle:1:1
Medium parameters used (interpolated): f= 2437.0 MHz; σ=1.93S/m; εr=52.65; ρ=1000 kg/m3
Phantom section : Flat Section

**DASY5 Configuration:**
•Probe: ES3DV3 - SN3292; ConvF(4.70,4.70,4.70); Calibrated: 02/09/2016;
•Sensor-Surface: 4mm (Mechanical Surface Detection)
•Electronics: DAE4 Sn1315; Calibrated: 26/07/2016
•Phantom: SAM 1; Type: SAM;
•Measurement SW: DASY52, Version 52.8 (2); SEMCAD X Version 14.6.6 (6824)

**Area Scan (51x101x1):** Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.171 W/kg

**Zoom Scan (5x5x6**)/Cube 0: Measurement grid: dx=7mm, dy=7mm, dz=5mm
Reference Value = 2.938 V/m; Power Drift = 0.17 dB
Peak SAR (extrapolated) = 0.254 mW/g
**SAR(1 g) = 0.157 mW/g; SAR(10 g) = 0.095 mW/g**

Maximum value of SAR (measured) = 0.170 W/kg




Body- worn Rear side (WLAN 802.11b Middle Channel)

# 16. Simultaneous Transmission analysis

| No. | Simultaneous Transmission Configurations | Head | Body-worn | Hotspot | Note |
|---|---|---|---|---|---|
| 1 | GSM(voice) + Bluetooth (data) | Yes | Yes | | |
| 2 | GSM(voice) + WIFI (data) | Yes | Yes | | |
| 3 | WCDMA(voice) + Bluetooth (data) | Yes | Yes | | |
| 4 | WCDMA(voice) + WIFI (data) | Yes | Yes | | |
| 5 | GPRS (data) + Bluetooth (data) | Yes | Yes | NA | |
| 6 | GPRS (data) + WIFI (data) | Yes | Yes | Yes | |
| 7 | WCDMA (data) + Bluetooth (data) | Yes | Yes | NA | |
| 8 | WCDMA (data) + WIFI (data) | Yes | Yes | Yes | |
| 9 | LTE + Bluetooth (data) | Yes | Yes | NA | |
| 10 | LTE + WIFI (data) | Yes | Yes | Yes | |

General note:

1. WLAN and Bluetooth share the same antenna, and cannot transmit simultaneously.
2. EUT will choose either GSM or WCDMA LTE according to the network signal condition; therefore, they will not operate simultaneously at any moment.
3. The reported SAR summation is calculated based on the same configuration and test position
4. Per FCC KDB Publication 616217 D04v01r02，Regardless of device dimensions, when next to the ear voice calls are supported the smart phone and phablets procedures in KDB 648474 must be applied.
5. Per FCC KDB Publication 648474 D04v01r03, this device is considered a "phablet".Therefore, phablet SAR tests are required whenwireless router mode does not apply or if wireless router 1g SAR > 1.2 W/kg. Phablet SAR was not evaluatedfor licensed technologies since wireless router 1g SAR was < 1.2 W/kg for these modes.
6. This device supports both LTE Band 12 and LTE Band 17. Since the supported frequency span for LTE Band17 falls completely within the supported frequency span for LTE Band 12, LTE Band 17 target power is lessthan or equal to LTE Band 12 target power, and both LTE bands share the same transmission path, SAR wasonly assessed for LTE Band 12.
7. For simultaneous transmission analysis, Bluetooth SAR is estimated per KDB 447498 D01 based on the formula below
   a) [(max. Power of channel, including tune-up tolerance, mW) / (min. test separation distance, mm)] * [√f(GHz)/x]W/kg for test separation distances ≦50mm; whetn x=7.5 for 1-g SAR, and x=18.75 for 10-g SAR.
   b) When the minimum separation distance is <5mm, the distance is used 5mm to determine SAR test exclusion
   c) 0.4 W/kg for 1-g SAR and 1.0W/kg for 10-g SAR, when the test separation distances is >50mm.

| Bluetooth Max power | Exposure position | Head | Hotspot | Body worn |
|---|---|---|---|---|
| | Test separation | 0mm | 0mm | 0mm |
| 3.0 dBm | Estimated SAR (W/kg) | 0.08W/kg | 0.08W/kg | 0.08W/kg |

## ***Maximum reported SAR value for Head***

| WWAN PCE +WIFI DTS | | | | | |
|---|---|---|---|---|---|
| WWAN Band | | Exposure Position | Max SAR (W/kg) | | Summed SAR (W/kg) |
| | | | WWAN PCS | WIFI DTS | |
| GSM | GSM850 | Left Cheek | 0.04 | 0.24 | 0.28 |
| | | Left Tilted | 0.03 | 0.20 | 0.23 |
| | | Right Cheek | 0.04 | 0.22 | 0.26 |
| | | Right Tilted | 0.03 | 0.19 | 0.22 |
| | PCS1900 | Left Cheek | 0.03 | 0.24 | 0.27 |
| | | Left Tilted | 0.02 | 0.20 | 0.22 |
| | | Right Cheek | 0.03 | 0.22 | 0.25 |
| | | Right Tilted | 0.02 | 0.19 | 0.21 |
| WCDMA | Band V | Left Cheek | 0.04 | 0.24 | 0.28 |
| | | Left Tilted | 0.04 | 0.20 | 0.24 |
| | | Right Cheek | 0.04 | 0.22 | 0.26 |
| | | Right Tilted | 0.03 | 0.19 | 0.22 |
| | Band II | Left Cheek | 0.05 | 0.24 | 0.29 |
| | | Left Tilted | 0.04 | 0.20 | 0.24 |
| | | Right Cheek | 0.05 | 0.22 | 0.27 |
| | | Right Tilted | 0.04 | 0.19 | 0.23 |
| LTE | Band II | Left Cheek | 0.08 | 0.24 | **0.32** |
| | | Left Tilted | 0.06 | 0.20 | 0.26 |
| | | Right Cheek | 0.07 | 0.22 | 0.29 |
| | | Right Tilted | 0.06 | 0.19 | 0.25 |
| | Band IV | Left Cheek | 0.06 | 0.24 | 0.30 |
| | | Left Tilted | 0.05 | 0.20 | 0.25 |
| | | Right Cheek | 0.06 | 0.22 | 0.28 |
| | | Right Tilted | 0.04 | 0.19 | 0.23 |
| | Band V | Left Cheek | 0.03 | 0.24 | 0.27 |
| | | Left Tilted | 0.02 | 0.20 | 0.22 |
| | | Right Cheek | 0.03 | 0.22 | 0.25 |
| | | Right Tilted | 0.01 | 0.19 | 0.20 |
| | Band XII | Left Cheek | 0.05 | 0.24 | 0.29 |
| | | Left Tilted | 0.04 | 0.20 | 0.24 |
| | | Right Cheek | 0.04 | 0.22 | 0.26 |
| | | Right Tilted | 0.03 | 0.19 | 0.22 |

| WWAN PCE + Bluetooth DSS | | | | | |
|---|---|---|---|---|---|
| WWAN Band | | Exposure Position | Max SAR (W/kg) | | Summed SAR (W/kg) |
| | | | WWAN PCS | BT DTS | |
| GSM | GSM850 | Left Cheek | 0.04 | 0.08 | 0.12 |
| | | Left Tilted | 0.03 | 0.08 | 0.11 |
| | | Right Cheek | 0.04 | 0.08 | 0.12 |
| | | Right Tilted | 0.03 | 0.08 | 0.11 |
| | PCS1900 | Left Cheek | 0.03 | 0.08 | 0.11 |
| | | Left Tilted | 0.02 | 0.08 | 0.10 |
| | | Right Cheek | 0.03 | 0.08 | 0.11 |
| | | Right Tilted | 0.02 | 0.08 | 0.10 |
| WCDMA | Band V | Left Cheek | 0.04 | 0.08 | 0.12 |
| | | Left Tilted | 0.04 | 0.08 | 0.12 |
| | | Right Cheek | 0.04 | 0.08 | 0.12 |
| | | Right Tilted | 0.03 | 0.08 | 0.11 |
| | Band II | Left Cheek | 0.05 | 0.08 | 0.13 |
| | | Left Tilted | 0.04 | 0.08 | 0.12 |
| | | Right Cheek | 0.05 | 0.08 | 0.13 |
| | | Right Tilted | 0.04 | 0.08 | 0.12 |
| LTE | Band II | Left Cheek | 0.08 | 0.08 | 0.16 |
| | | Left Tilted | 0.06 | 0.08 | 0.14 |
| | | Right Cheek | 0.07 | 0.08 | 0.15 |
| | | Right Tilted | 0.06 | 0.08 | 0.14 |
| | Band IV | Left Cheek | 0.06 | 0.08 | 0.14 |
| | | Left Tilted | 0.05 | 0.08 | 0.13 |
| | | Right Cheek | 0.06 | 0.08 | 0.14 |
| | | Right Tilted | 0.04 | 0.08 | 0.12 |
| | Band V | Left Cheek | 0.03 | 0.08 | 0.11 |
| | | Left Tilted | 0.02 | 0.08 | 0.10 |
| | | Right Cheek | 0.03 | 0.08 | 0.11 |
| | | Right Tilted | 0.01 | 0.08 | 0.09 |
| | Band XII | Left Cheek | 0.05 | 0.08 | 0.13 |
| | | Left Tilted | 0.04 | 0.08 | 0.12 |
| | | Right Cheek | 0.04 | 0.08 | 0.12 |
| | | Right Tilted | 0.03 | 0.08 | 0.11 |

## ***Maximum reported SAR value for Body***

| WWAN PCE + WIFI DTS | | | | | |
|---|---|---|---|---|---|
| WWAN Band | | Exposure Position | Max SAR (W/kg) | | Summed SAR (W/kg) |
| | | | WWAN PCS | WIFI DTS | |
| GSM | GSM850 | Front | 0.69 | 0.12 | 0.81 |
| | | Back | 1.04 | 0.19 | 1.23 |
| | PCS1900 | Front | 0.44 | 0.12 | 0.56 |
| | | Back | 0.67 | 0.19 | 0.86 |
| WCDMA | Band V | Front | 0.75 | 0.12 | 0.87 |
| | | Back | 1.05 | 0.19 | 1.24 |
| | Band II | Front | 0.74 | 0.12 | 0.86 |
| | | Back | **1.08** | 0.19 | **1.27** |
| LTE | Band II | Front | 0.61 | 0.12 | 0.73 |
| | | Back | 0.92 | 0.19 | 1.11 |
| | Band IV | Front | 0.61 | 0.12 | 0.73 |
| | | Back | 0.93 | 0.19 | 1.12 |
| | Band V | Front | 0.45 | 0.12 | 0.57 |
| | | Back | 0.63 | 0.19 | 0.82 |
| | Band XII | Front | 0.19 | 0.12 | 0.31 |
| | | Back | 0.28 | 0.19 | 0.47 |

| WWAN PCE + Bluetooth DSS | | | | | |
|---|---|---|---|---|---|
| WWAN Band | | Exposure Position | Max SAR (W/kg) | | Summed SAR (W/kg) |
| | | | WWAN PCS | Bleutooth DTS | |
| GSM | GSM850 | Front | 0.69 | 0.08 | 0.77 |
| | | Back | 1.04 | 0.08 | 1.12 |
| | PCS1900 | Front | 0.44 | 0.08 | 0.52 |
| | | Back | 0.67 | 0.08 | 0.75 |
| WCDMA | Band V | Front | 0.75 | 0.08 | 0.83 |
| | | Back | 1.05 | 0.08 | 1.13 |
| | Band II | Front | 0.74 | 0.08 | 0.82 |
| | | Back | 1.08 | 0.08 | 1.16 |
| LTE | Band II | Front | 0.61 | 0.08 | 0.69 |
| | | Back | 0.92 | 0.08 | 1.00 |
| | Band IV | Front | 0.61 | 0.08 | 0.69 |
| | | Back | 0.93 | 0.08 | 1.01 |
| | Band V | Front | 0.45 | 0.08 | 0.53 |
| | | Back | 0.63 | 0.08 | 0.71 |
| | Band XII | Front | 0.19 | 0.08 | 0.27 |
| | | Back | 0.28 | 0.08 | 0.36 |

# 17. TestSetup Photos



Liquid depth in the head phantom (750MHz)



Liquid depth in the body phantom (750MHz)



Liquid depth in the head phantom (835MHz)



Liquid depth in the body phantom (835MHz)



Liquid depth in the head phantom (1750MHz)



Liquid depth in the body phantom (1750MHz)

Liquid depth in the head phantom (1900MHz)



Liquid depth in the body phantom (1900MHz)



Liquid depth in the head phantom (2450MHz)



Liquid depth in the body phantom (2450MHz)



Left Head Touch



Right Head Touch



Left Head Tilt (15$^{o}$)



Right Head Tilt (15$^{o}$)

Body-worn Front Side (0mm)

Body-worn Rear Side (0mm)

Front Side (0mm) Rear Side (0mm)

Left Side (0mm) Right Side (0mm)

Bottom Side (0mm)

## 18. External and Internal Photos of the EUT

Please reference to the report No.: TRE1609005901

***---------End of Report----------***