

FCC RF EXPOSURE REPORT

FCC ID: 2AJZR-T605A00

Project No. : 1706185
Equipment : Premium Docking Station
Model : iSAPPOS 9A+, iSAPPOS 12A+
Applicant : iSAPPOS Systems Company Limited
**Address : Room 04, 6/F., Block A, Tonic Industrial Centre,
NO.26 Kai Cheung Road, Kowloon Bay, Hong
Kong**

**According: : FCC Guidelines for Human Exposure IEEE
C95.1 & KDB447498 D01**

B T L I N C .

B1, No. 37, Lane 365, YangGuang St., NeiHu District 114, Taipei, Taiwan
TEL: +886-2-2657-3299 FAX: +886-2-2657-3331

Table for Filed Antenna

Ant.	Manufacturer	Model Name	Antenna Type	Connector	Gain(dBi)
1	Flytech	T605	PCB	N/A	1.07

GENERAL CONCLUSION:

Maximum measured transmitter power:

OutputPower (dBm)	Output Power (mW)	Limit (mW)
0.92	1.236	10

According to FCC KDB447498 D01 V06, Appendix A, SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and ≤ 50 mm

The maximum measured output peak power of this EUT is 1.236mW, less than 10mW at 5mm distance.

Conclusion: No SAR evaluation required since transmitter power is below FCC threshold