

RF EXPOSURE Test Report

Product: ErgoDock

Trade Mark: KEESON

Model Number: ED01EN

FCC ID: 2AK23-ED01EN

Prepared for

Keeson Technology Corporation Limited
No.1508, Xiushui Road, WangJiangjing Town, Xiuzhou District, Jiaxing City,
Zhejiang Province,China

Prepared by

Shenzhen HongBiao Certification& Testing Co., Ltd
Room 102, 201, Building 2, Yuanwanggu RFID Industrial Park, Tongguan
Road, Tianliao Community, Yutang Street, Guangming District, Shenzhen,
China
Tel.: +86-755-2998 9321 Fax.: +86-755-2998 5110
Website: <http://www.sz-hongbiao.com>

Table of Contents

1	GENERAL DESCRIPTION	5
1.1	DESCRIPTION OF EUT	5
1.2	TEST MODE.....	5
1.3	TEST SETUP	6
1.4	ANCILLARY EQUIPMENT	6
2	TEST FACILITIES AND ACCREDITATIONS	7
2.1	TEST LABORATORY	7
2.2	ENVIRONMENTAL CONDITIONS	7
2.3	MEASUREMENT UNCERTAINTY	7
2.4	TEST SOFTWARE	7
3	LIST OF TEST EQUIPMENT	9
4	RF EXPOSURE.....	10
4.1	STANDALONE SAR TEST EXCLUSION CONSIDERATIONS.....	10
4.1.1.	<i>Limit</i>	10
4.1.2.	<i>Test Procedures</i>	10
4.1.3.	<i>Test Setup</i>	11
4.1.4.	<i>Test Result</i>	11
5	PHOTOGRAPHS OF THE TEST SETUP	14

TEST RESULT CERTIFICATION

Applicant's Name..... : Keeson Technology Corporation Limited
Address : No.1508, Xiushui Road, WangJiangjing Town, Xiuzhou District,
Jiaxing City, Zhejiang Province,China
Manufacturer's Name : Keeson Technology Corporation Limited
Address : No.1508, Xiushui Road, WangJiangjing Town, Xiuzhou District,
Jiaxing City, Zhejiang Province,China

Product description

Product name : ErgoDock
Model Number : ED01EN
Standards : FCC CFR 47 PART 1 , 1.1310
Test procedure..... : KDB 447498 D01 General RF Exposure Guidance v06
KDB 680106 D01 Wireless Power Transfer v04

This device described above has been tested by Shenzhen HongBiao Certification& Testing Co., Ltd and the test results show that the equipment under test (EUT) is in compliance with the EMC requirements. And it is applicable only to the tested sample identified in the report.

Date of Test..... :

Date (s) of performance of tests..... : July 20, 2026~July 29, 2026

Test Result..... : **Pass**

Testing Engineer :

Zoe Su

(Z o e S u)

Technical Manager :

Ming Liu

(M i n g L i u)

Authorized Signatory :

Leo Su

(L e o S u)

Revision History

[illegible]

1 General Description

1.1 Description of EUT

Product name:	ErgoDock
Model name:	ED01EN
Series Model:	N/A
Different of series model:	N/A
Operation frequency:	BLE: 2402-2480MHz Wireless Charge: 115-148kHz
Modulation type:	BLE: GFSK Wireless Charge: ASK
Bit Rate of transmitter:	BLE: 1 Mbps, 2Mbps Wireless Charge: N/A
Antenna type:	BLE: Ceramic Antenna Wireless Charge: Coil Antenna
Antenna gain:	BLE: 2dBi Wireless Charge: 0dBi
Max. output power:	BLE: 3.08dBm
Hardware version:	V1.0
Software version:	V1.0
Battery:	N/A
Power supply:	Input: 29V DC Wireless Output: 12W
Adapter information:	MODEL: GS05802900180 INPUT: 100-240V~ 50/60Hz 1.5A OUTPUT: 29.0V=1.8A, 52.2W

1.2 Test Mode

Pretest Test Mode	Description of Mode
1	Adapter + Wireless Output: 5W
2	Adapter + Wireless Output: 7.5W
3	Adapter + Wireless Output: 10W
4	Adapter + Wireless Output: 12W
5	BLE TX

1.3 Test Setup

See photographs of the test setup in the report for the actual setup and connections between EUT and support equipment.

1.4 Ancillary Equipment

Equipment	Model	S/N	Manufacturer
Phone	Pixel 9 Pro XL	CP2A.260705.006	Google LLC

2 Test Facilities and Accreditations

2.1 Test Laboratory

Test Site	Shenzhen HongBiao Certification& Testing Co., Ltd
Test Site Location	Room 102, 201, Building 2, Yuanwanggu RFID Industrial Park, Tongguan Road, Tianliao Community, Yutang Street, Guangming District, Shenzhen, China
Telephone:	(86-755) 2998 9321
Fax:	(86-755) 2998 5110
Designation Number:	848916
FCC Registration No.:	CN1341
A2LA Certificate No.:	6765.01

2.2 Environmental Conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15°C~35°C
Relative Humidity:	20%~75%
Air Pressure:	98kPa~101kPa

2.3 Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

The data and results quoted in this document are true and accurate values, and uncertainties are not involved in the calculations.

In addition, components and mass production processes that are similar to testing equipment may introduce additional deviations, and the manufacturer is solely responsible for the continued compliance of the equipment.

Measurement Frequency Range	U, (dB)	Note
RF frequency	2×10^{-5}	
RF power, conducted	± 0.57 dB	
E-field	± 2.5 dB	
H-field	± 4.2 dB	
Temperature	± 1 degree	
Humidity	± 5 %	

2.4 Test Software

Software name	Manufacturer	Model	Version
RF Test System	MWRF	MTS 8310	V2.0.0.0

EHP200-TS	Narda	EHP-200A	Rel 1.95
-----------	-------	----------	----------

3 List of Test Equipment

RF							
Item	Equipment No.	Equipment name	Manufacturer	Model	Serial No.	Calibration date	Due date
1	HB-E041	MXG Anaio Signal Generator	Agilent	N5181A	MY47070421	2026-04-27	2027-04-26
2	HB-E042	WIDEBAND RADIO COMMUNICATION TESTER	R&S	CMW500	132108	2026-04-27	2027-04-26
3	HB-E043	MXG Anaio Signal Generator	Agilent	N5182A	US46240335	2026-04-28	2027-04-27
4	HB-E044	Signal & spectrum Analyzer	R&S	FSV3044	101264	2026-04-28	2027-04-27
5	HB-E045	RF Control Box	Noyetec	NY100-R FCB	N/A	2026-04-28	2027-04-27
6	HB-E058	Thermometer Clock Humidity Monitor	N/A	HTC-1S	N/A	2026-04-30	2027-04-29
7	HB-E073	Electric and Magnetic Field Analyzer	Narda	EHP-200 A	180ZX11013	2026-04-30	2027-04-29

Note: the calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

4 RF Exposure

4.1 Standalone SAR test exclusion considerations

4.1.1. Limit

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b).

Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

MPE Calculation Method

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2)$

Where

P_d = Power density in mW/cm²

P_{out} = output power to antenna in mW

G = Numeric gain of the antenna relative to isotropic antenna

π = 3.1415926

R = distance between observation point and center of the radiator in cm (20cm)

P_d the limit of MPE, 1mW/cm².

If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.


4.1.2. Test Procedures

(wireless charging) E and H-field measurements should be made with the center of the probe at a distance of 20 cm surrounding the device and 20 cm above the top surface of the primary/client pair.

These measurements should be repeated for three different client battery levels, 1%, 50%, and 99%.

Record the test results.

4.1.3. Test Setup



4.1.4. Test Result

BLE:

Operation Frequency: 2402-2480MHz,
Power density limited: 1mW/ cm²

Antenna gain: 2dBi

R=20cm

mW=10^(dBm/10)

antenna gain Numeric=10^(dBi/10)= 10^(2/10)=1.58

BLE TX:

Channel Freq. (MHz)	modulation	conducted power	Tune-u p power (dBm)	Max		Antenna		Evaluation result	Power density Limits
		(dBm)		tune-up power		Gain		(mW/cm ²)	(mW/cm ²)
				(dBm)	(mW)	(dBi)	Nume ric		
2402	GFSK(1M)	2.86	3±1	4	1.259	2	1.58	0.0004	1
2440		2.78	3±1	4	1.259	2	1.58	0.0004	1
2480		3.08	3±1	4	1.259	2	1.58	0.0004	1
2402	GFSK(2M)	2.84	3±1	4	1.259	2	1.58	0.0004	1
2440		2.77	3±1	4	1.259	2	1.58	0.0004	1
2480		3.07	3±1	4	1.259	2	1.58	0.0004	1

Wireless charge:

Test condition: Mode 4 operating mode with client device (1 %, 50%, 99% battery status of client device)

Maximum permissible Exposure(Phone: 115-148kHz)				
Battery levels	Test sides	Test distance(cm)	E -field(V/m)	H-field(A/m)
<1%	Top	20	2.0873	0.0486
<1%	Left	20	1.2214	0.0478
<1%	Right	20	1.8525	0.0474
<1%	Front	20	1.3249	0.0482
<1%	Back	20	0.9471	0.0456
Limit			614	1.63
Margin Limit (%)			0.34%	2.98%

Maximum permissible Exposure(Phone: 115-148kHz)				
Battery levels	Test sides	Test distance(cm)	E -field(V/m)	H-field(A/m)
<50%	Top	20	2.0865	0.0477
<50%	Left	20	1.2202	0.0469
<50%	Right	20	1.8514	0.0454
<50%	Front	20	1.3236	0.0471
<50%	Back	20	0.9465	0.0448
Limit			614	1.63
Margin Limit (%)			0.34%	2.93%

Maximum permissible Exposure(Phone: 115-148kHz)				
Battery levels	Test sides	Test distance(cm)	E -field(V/m)	H-field(A/m)
<99%	Top	20	2.0851	0.0463
<99%	Left	20	1.2194	0.0461
<99%	Right	20	1.8502	0.0435
<99%	Front	20	1.3225	0.0462
<99%	Back	20	0.9451	0.0441
Limit			614	1.63
Margin Limit (%)			0.34%	2.84%

Results for transmit simultaneously

No.	Configurations	Maximum MPE Value			Limits
		Wireless Power Transfer($\sum (H_m / H_{RL})$ ^{Note)}	BLE	Transmit simultaneously	
1	Wireless Power Transfer + BLE	0.0298	0.0004	0.0302	1

No.	Configurations	Maximum MPE Value			Limits
		Wireless Power Transfer($\sum (E_m / E_{RL})$ ^{Note)}	BLE	Transmit simultaneously	
1	Wireless Power Transfer + BLE	0.0034	0.0004	0.0038	1

Note:

H_m = Measured magnetic field at a specific frequency.

H_{RL} = Reference level limit for the magnetic field at the measurement frequency.

According to KDB 447498 D01 General RF Exposure Guidance v06, At the transmit simultaneously calculation method is as follows:

Transmit simultaneously MPE = $\sum$ of MPE ratios

MPE ratios = Field strengths or power density / MPE limit at the test frequency

5 Photographs of the Test Setup

MPE



***** END OF REPORT *****