



## FCC PART 15.247


### TEST REPORT

For

#### FORMIKE ELECTRONIC CO.,LTD.

Flats 401-403, 4/F, iPARK Building, 26 DengLiang Rd.,  
NanShan District, Shenzhen, China

**FCC ID: 2AK44-KWH-88W8-80XX**

|                                           |                                                                                                                                                                                                |
|-------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Report Type:</b><br>Original Report    | <b>Product Name:</b><br>WiFi Module                                                                                                                                                            |
| <b>Test Engineer:</b> <u>Lorin Bian</u>   |                                                                                                           |
| <b>Report Number:</b> <u>RDG161219801</u> |                                                                                                                                                                                                |
| <b>Report Date:</b> <u>2017-03-06</u>     |                                                                                                                                                                                                |
| <b>Reviewed By:</b> <u>Henry Ding</u>     |                                                                                                            |
| <b>Test Laboratory:</b>                   | Bay Area Compliance Laboratories Corp. (Chengdu)<br>5040, HuiLongWan Plaza, No. 1, ShaWan Road,<br>JinNiu District, ChengDu, China<br>Tel: 028-65523123, Fax: 028-65525125<br>www.baclcorp.com |

**Note:** This test report was prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Chengdu). Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. This report was valid only with a valid digital signature.

## **TABLE OF CONTENTS**

|                                                                                              |           |
|----------------------------------------------------------------------------------------------|-----------|
| <b>GENERAL INFORMATION .....</b>                                                             | <b>4</b>  |
| PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....                                     | 4         |
| OBJECTIVE .....                                                                              | 4         |
| RELATED SUBMITTAL(S)/GRANT(S) .....                                                          | 4         |
| TEST METHODOLOGY .....                                                                       | 4         |
| TEST FACILITY .....                                                                          | 5         |
| <b>SYSTEM TEST CONFIGURATION .....</b>                                                       | <b>6</b>  |
| DESCRIPTION OF TEST CONFIGURATION .....                                                      | 6         |
| EQUIPMENT MODIFICATIONS .....                                                                | 6         |
| EUT EXERCISE SOFTWARE .....                                                                  | 6         |
| LOCAL SUPPORT EQUIPMENT LIST AND DETAILS .....                                               | 8         |
| SUPPORT CABLE LIST AND DETAILS .....                                                         | 8         |
| BLOCK DIAGRAM OF TEST SETUP .....                                                            | 9         |
| <b>SUMMARY OF TEST RESULTS .....</b>                                                         | <b>10</b> |
| <b>FCC §15.247 (i) &amp; §1.1310 &amp; §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE) .....</b> | <b>11</b> |
| APPLICABLE STANDARD .....                                                                    | 11        |
| <b>FCC §15.203 - ANTENNA REQUIREMENT .....</b>                                               | <b>12</b> |
| APPLICABLE STANDARD .....                                                                    | 12        |
| ANTENNA CONNECTOR CONSTRUCTION .....                                                         | 12        |
| <b>FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS .....</b>                                   | <b>13</b> |
| APPLICABLE STANDARD .....                                                                    | 13        |
| MEASUREMENT UNCERTAINTY .....                                                                | 13        |
| EUT SETUP .....                                                                              | 13        |
| EMI TEST RECEIVER SETUP .....                                                                | 14        |
| TEST PROCEDURE .....                                                                         | 14        |
| CORRECTED AMPLITUDE & MARGIN CALCULATION .....                                               | 14        |
| TEST EQUIPMENT LIST AND DETAILS .....                                                        | 15        |
| TEST DATA .....                                                                              | 15        |
| <b>FCC §15.209, §15.205 &amp; §15.247(d) - SPURIOUS EMISSIONS .....</b>                      | <b>18</b> |
| APPLICABLE STANDARD .....                                                                    | 18        |
| MEASUREMENT UNCERTAINTY .....                                                                | 18        |
| EUT SETUP .....                                                                              | 19        |
| EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP .....                                            | 20        |
| TEST PROCEDURE .....                                                                         | 20        |
| CORRECTED AMPLITUDE & MARGIN CALCULATION .....                                               | 20        |
| TEST EQUIPMENT LIST AND DETAILS .....                                                        | 21        |
| TEST DATA .....                                                                              | 21        |
| <b>FCC §15.247(d) - SPURIOUS EMISSIONS AT ANTENNA PORT .....</b>                             | <b>25</b> |
| APPLICABLE STANDARD .....                                                                    | 25        |
| TEST PROCEDURE .....                                                                         | 25        |
| TEST EQUIPMENT LIST AND DETAILS .....                                                        | 25        |
| TEST DATA .....                                                                              | 25        |
| <b>FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH .....</b>                                    | <b>31</b> |
| APPLICABLE STANDARD .....                                                                    | 31        |
| TEST PROCEDURE .....                                                                         | 31        |

|                                                                        |           |
|------------------------------------------------------------------------|-----------|
| TEST EQUIPMENT LIST AND DETAILS .....                                  | 31        |
| TEST DATA .....                                                        | 31        |
| <b>FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER .....</b>       | <b>37</b> |
| APPLICABLE STANDARD .....                                              | 37        |
| TEST PROCEDURE .....                                                   | 37        |
| TEST EQUIPMENT LIST AND DETAILS .....                                  | 37        |
| TEST DATA .....                                                        | 38        |
| <b>FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE .....</b> | <b>39</b> |
| APPLICABLE STANDARD .....                                              | 39        |
| TEST PROCEDURE .....                                                   | 39        |
| TEST EQUIPMENT LIST AND DETAILS .....                                  | 39        |
| TEST DATA .....                                                        | 40        |
| <b>CC §15.247(e) - POWER SPECTRAL DENSITY .....</b>                    | <b>44</b> |
| APPLICABLE STANDARD .....                                              | 44        |
| TEST PROCEDURE .....                                                   | 44        |
| TEST EQUIPMENT LIST AND DETAILS .....                                  | 44        |
| TEST DATA .....                                                        | 44        |

## GENERAL INFORMATION

---

### Product Description for Equipment under Test (EUT)

The **FORMIKE ELECTRONIC CO.,LTD.**'s product, model number: **KWH-88W8-802 (FCC ID: 2AK44-KWH-88W8-80XX)** (the "EUT") in this report was a **WiFi Module**, which was measured approximately: 1.32 cm (L) x 1.35 cm (W) x 0.15 cm (H), rated input voltage: DC3.3V.

*Note: The series product, model KWH-88W8-802, KWH-88W8-803, KWH-88W8-801 are electrically identical, the difference between them is the different model names, we selected KWH-88W8-802 for fully testing, the details was explained in the declaration letter.*

*\*All measurement and test data in this report was gathered from final production sample, serial number: 161219801 (assigned by the BACL, Chengdu). It may have deviation from any other sample. The EUT supplied by the applicant was received on 2016-12-21, and EUT conformed to test requirement.*

### Objective

This report is prepared on behalf of **FORMIKE ELECTRONIC CO.,LTD.** in accordance with Part 2, Subpart J, Part 15, Subparts A, B and C of the Federal Communications Commission's rules

The tests were performed in order to determine the compliance of the EUT with FCC Part 15-Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

### Related Submittal(s)/Grant(s)

N/A.

### Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Chengdu). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

The uncertainty of any RF tests which use conducted method measurement is  $\pm 3.17$  dB, the uncertainty of any radiation on emissions measurement is:

30M~200MHz:  $\pm 4.7$  dB;  
200M~1GHz:  $\pm 6.0$  dB;  
1G~6GHz:  $\pm 5.13$  dB;  
6G~25GHz:  $\pm 5.47$  dB;

And the uncertainty will not be taken into consideration for all test data recorded in the report.

## **Test Facility**

The test site used by BACL to collect test data is located in the 5040, HuiLongWan Plaza, No. 1, ShaWan Road, JinNiu District, ChengDu, China

Test site at BACL has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on April 24, 2015. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 560332. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

## SYSTEM TEST CONFIGURATION

---

### Description of Test Configuration

The system was configured for testing in testing mode, which was provided by manufacturer. For 2.4GHz band, 11 channels are provided:

| Channel | Frequency (MHz) | Channel | Frequency (MHz) |
|---------|-----------------|---------|-----------------|
| 1       | 2412            | 7       | 2442            |
| 2       | 2417            | 8       | 2447            |
| 3       | 2422            | 9       | 2452            |
| 4       | 2427            | 10      | 2457            |
| 5       | 2432            | 11      | 2462            |
| 6       | 2437            | /       | /               |

For 802.11b, 802.11g, and 802.11n ht20 modes were tested with channel 1, 6 and 11.

The worst-case data rates are determined to be as follows for each mode based upon investigations by measuring the average power and PSD across all data rates bandwidths, and modulations.

### Equipment Modifications

No modification was made to the EUT tested.


### EUT Exercise Software

The software "Dos Command" was used for testing, which was provided by manufacturer, and configured maximum power and duty cycle in default mode.

The duty cycle as below:


| Test Mode    | T <sub>on</sub> (ms) | T <sub>on+off</sub> (ms) | Duty Cycle (%) |
|--------------|----------------------|--------------------------|----------------|
| 802.11b      | 50                   | 50                       | 100%           |
| 802.11g      | 100                  | 100                      | 100%           |
| 802.11n ht20 | 100                  | 100                      | 100%           |

### 802.11b




Date: 17. JAN. 2017 22:01:04

### 802.11g



Date: 17. JAN. 2017 21:57:18

### 802.11n ht20



### Local Support Equipment List and Details

| Manufacturer | Description | Model     | Serial Number     |
|--------------|-------------|-----------|-------------------|
| IBM          | PC          | 8176      | 99Y7315           |
| DELL         | Display     | E157FPC   | 060229-11         |
| Lenovo       | Keyboard    | KB-US19EB | IMHYX011071016460 |
| Lenovo       | Mouse       | MO-5013U  | IMJS011041409259  |

### Support Cable List and Details

| Cable Description | Shielding Type | Ferrite Core | Length (m) | From Port           | To       |
|-------------------|----------------|--------------|------------|---------------------|----------|
| Mouse Cable       | yes            | No           | 1.4        | Parallel Port of PC | Mouse    |
| Keyboard Cable    | yes            | No           | 1.3        | USB Port of PC      | Keyboard |
| VGA Cable         | yes            | yes          | 1.2        | VGA port of PC      | Display  |



## **SUMMARY OF TEST RESULTS**

---

| <b>FCC Rules</b>                       | <b>Description of Test</b>                  | <b>Result</b> |
|----------------------------------------|---------------------------------------------|---------------|
| FCC §15.247 (i) & §1.1310<br>& §2.1091 | Maximum Permissible Exposure (MPE)          | Compliant     |
| §15.203                                | Antenna Requirement                         | Compliant     |
| §15.207 (a)                            | AC Line Conducted Emissions                 | Compliant     |
| §15.205, §15.209,<br>§15.247(d)        | Spurious Emissions                          | Compliant     |
| §15.247(d)                             | Spurious Emissions at antenna port          | Compliant     |
| §15.247 (a)(2)                         | 6 dB Emission Bandwidth                     | Compliant     |
| §15.247(b)(3)                          | Maximum conducted output power              | Compliant     |
| §15.247(d)                             | 100 kHz Bandwidth of Frequency Band<br>Edge | Compliant     |
| §15.247(e)                             | Power Spectral Density                      | Compliant     |

## FCC §15.247 (i) & §1.1310 & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

### Applicable Standard

According to subpart 15.247(i) and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

| (B) Limits for General Population/Uncontrolled Exposure |                               |                               |                                     |                          |
|---------------------------------------------------------|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| Frequency Range (MHz)                                   | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) | Power Density (mW/cm <sup>2</sup> ) | Averaging Time (minutes) |
| 0.3–1.34                                                | 614                           | 1.63                          | *(100)                              | 30                       |
| 1.34–30                                                 | 824/f                         | 2.19/f                        | *(180/f <sup>2</sup> )              | 30                       |
| 30–300                                                  | 27.5                          | 0.073                         | 0.2                                 | 30                       |
| 300–1500                                                | /                             | /                             | f/1500                              | 30                       |
| 1500–100,000                                            | /                             | /                             | 1.0                                 | 30                       |

f = frequency in MHz; \* = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

### Calculated Formulary:

Predication of MPE limit at a given distance

$S = PG/4\pi R^2$  = power density (in appropriate units, e.g. mW/cm<sup>2</sup>);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

### Calculated Data:

| Frequency (MHz) | Antenna Gain |           | Tune-up Power |        | Evaluation Distance (cm) | Power Density (mW/cm <sup>2</sup> ) | MPE Limit (mW/cm <sup>2</sup> ) |
|-----------------|--------------|-----------|---------------|--------|--------------------------|-------------------------------------|---------------------------------|
|                 | (dBi)        | (numeric) | (dBm)         | (mW)   |                          |                                     |                                 |
| 2412-2462       | 5            | 3.16      | 20            | 100.00 | 20.00                    | 0.0629                              | 1.0                             |

Note: The maximum tune-up power including tolerance is 20dBm, that declared by manufacturer.

**Result:** The device meet FCC MPE at 20 cm distance

## **FCC §15.203 - ANTENNA REQUIREMENT**

---

### **Applicable Standard**

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

### **Antenna Connector Construction**

The EUT have a PIFA antenna. The antenna permanently attached to the module. Maximum antenna gain is 5dBi. Please refer to the EUT photos.

**Result:** Compliance.

## FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

### Applicable Standard

FCC§15.207

### Measurement Uncertainty

Compliance or non-compliance with a disturbance limit shall be determined in the following manner:

If  $U_{lab}$  is less than or equal to  $U_{cisprr}$  of Table 1, then:

–compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;  
 –non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If  $U_{lab}$  is greater than  $U_{cisprr}$  of Table 1, then:


–compliance is deemed to occur if no measured disturbance level, increased by  $(U_{lab} - U_{cisprr})$ , exceeds the disturbance limit;  
 –non-compliance is deemed to occur if any measured disturbance level, increased by  $(U_{lab} - U_{cisprr})$ , exceeds the disturbance limit.

Based on CISPR 16-4-2:2011, measurement uncertainty of conducted disturbance at mains port using AMN at Bay Area Compliance Laboratories Corp. (Chengdu) is  $\pm 3.17$  dB (150 kHz to 30 MHz).

Table 1 – Values of  $U_{cisprr}$

| Measurement                                                       | $U_{cisprr}$ |
|-------------------------------------------------------------------|--------------|
| Conducted disturbance at mains port using AMN (150 kHz to 30 MHz) | 3.4 dB       |

### EUT Setup



Note: 1. Support units were connected to second LISN.  
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 30 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The PC was connected to an AC 120 V/60 Hz power source

### EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

| Frequency Range  | IF B/W |
|------------------|--------|
| 150 kHz – 30 MHz | 9 kHz  |

### Test Procedure

During the conducted emission test, the PC was connected to the first LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

### Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

$$C_f = A_C + VDF$$

Herein,

$V_C$  (cord. Reading): corrected voltage amplitude

$V_R$ : reading voltage amplitude

$A_C$ : attenuation caused by cable loss

VDF: voltage division factor of AMN

$C_f$ : Correction Factor

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

### Test Equipment List and Details

| Manufacturer    | Description       | Model   | Serial Number | Calibration Date | Calibration Due Date |
|-----------------|-------------------|---------|---------------|------------------|----------------------|
| Rohde & Schwarz | EMI Test Receiver | ESCS 30 | 836858/0016   | 2016-12-02       | 2017-12-01           |
| Rohde & Schwarz | L.I.S.N.          | ENV216  | 3560.6550.06  | 2016-12-02       | 2017-12-01           |
| Rohde & Schwarz | PULSE LIMITER     | ESH3Z2  | 357.8810.52   | 2016-10-31       | 2017-10-30           |
| N/A             | Conducted Cable   | NO.5    | N/A           | 2016-11-10       | 2017-11-09           |
| R&S             | Test Software     | EMC32   | Version8.53.0 | N/A              | N/A                  |

\* **Statement of Traceability:** BACL (Chengdu) attested that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

### Test Data


#### Environmental Conditions

|                           |           |
|---------------------------|-----------|
| <b>Temperature:</b>       | 25.6 °C   |
| <b>Relative Humidity:</b> | 48 %      |
| <b>ATM Pressure:</b>      | 101.1 kPa |

*The testing was performed by Lorin Bian on 2017-01-05.*

Test Mode: Transmitting


AC120 V, 60 Hz, Line:



| Frequency (MHz) | QuasiPeak (dB $\mu$ V) | Bandwidth (kHz) | Line | Corr. (dB) | Margin (dB) | Limit (dB $\mu$ V) | Comment    |
|-----------------|------------------------|-----------------|------|------------|-------------|--------------------|------------|
| 0.483938        | 44.6                   | 9.000           | L1   | 19.7       | 11.7        | 56.3               | Compliance |
| 0.499611        | 43.0                   | 9.000           | L1   | 19.7       | 13.0        | 56.0               | Compliance |
| 0.558572        | 43.0                   | 9.000           | L1   | 19.7       | 13.0        | 56.0               | Compliance |
| 0.619536        | 46.1                   | 9.000           | L1   | 19.7       | 9.9         | 56.0               | Compliance |
| 0.852094        | 43.5                   | 9.000           | L1   | 19.7       | 12.5        | 56.0               | Compliance |
| 0.967957        | 45.1                   | 9.000           | L1   | 19.7       | 10.9        | 56.0               | Compliance |

| Frequency (MHz) | Average (dB $\mu$ V) | Bandwidth (kHz) | Line | Corr. (dB) | Margin (dB) | Limit (dB $\mu$ V) | Comment    |
|-----------------|----------------------|-----------------|------|------------|-------------|--------------------|------------|
| 0.346296        | 43.7                 | 9.000           | L1   | 19.7       | 5.4         | 49.1               | Compliance |
| 0.483938        | 42.5                 | 9.000           | L1   | 19.7       | 3.8         | 46.3               | Compliance |
| 0.619536        | 41.0                 | 9.000           | L1   | 19.7       | 5.0         | 46.0               | Compliance |
| 0.852094        | 38.7                 | 9.000           | L1   | 19.7       | 7.3         | 46.0               | Compliance |
| 0.967957        | 39.2                 | 9.000           | L1   | 19.7       | 6.8         | 46.0               | Compliance |
| 1.108371        | 41.3                 | 9.000           | L1   | 19.7       | 4.7         | 46.0               | Compliance |

**AC120 V, 60 Hz, Neutral:**



| Frequency (MHz) | QuasiPeak (dB $\mu$ V) | Bandwidth (kHz) | Line | Corr. (dB) | Margin (dB) | Limit (dB $\mu$ V) | Comment    |
|-----------------|------------------------|-----------------|------|------------|-------------|--------------------|------------|
| 0.483938        | 44.6                   | 9.000           | N    | 19.6       | 11.7        | 56.3               | Compliance |
| 0.558572        | 42.7                   | 9.000           | N    | 19.6       | 13.3        | 56.0               | Compliance |
| 0.619536        | 46.0                   | 9.000           | N    | 19.6       | 10.0        | 56.0               | Compliance |
| 0.852094        | 43.4                   | 9.000           | N    | 19.6       | 12.6        | 56.0               | Compliance |
| 0.967957        | 45.1                   | 9.000           | N    | 19.7       | 10.9        | 56.0               | Compliance |
| 1.731709        | 42.9                   | 9.000           | N    | 19.7       | 13.1        | 56.0               | Compliance |

| Frequency (MHz) | Average (dB $\mu$ V) | Bandwidth (kHz) | Line | Corr. (dB) | Margin (dB) | Limit (dB $\mu$ V) | Comment    |
|-----------------|----------------------|-----------------|------|------------|-------------|--------------------|------------|
| 0.346296        | 43.7                 | 9.000           | N    | 19.6       | 5.4         | 49.1               | Compliance |
| 0.483938        | 42.7                 | 9.000           | N    | 19.6       | 3.6         | 46.3               | Compliance |
| 0.619536        | 40.8                 | 9.000           | N    | 19.6       | 5.2         | 46.0               | Compliance |
| 0.967957        | 38.8                 | 9.000           | N    | 19.7       | 7.2         | 46.0               | Compliance |
| 1.108371        | 40.9                 | 9.000           | N    | 19.7       | 5.1         | 46.0               | Compliance |
| 1.731709        | 38.9                 | 9.000           | N    | 19.7       | 7.1         | 46.0               | Compliance |

## **FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS**

### **Applicable Standard**

FCC §15.247 (d); §15.209; §15.205;

### **Measurement Uncertainty**

Compliance or non-compliance with a disturbance limit shall be determined in the following manner:

If  $U_{lab}$  is less than or equal to  $U_{cispr}$  of Table 2, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If  $U_{lab}$  is greater than  $U_{cispr}$  of Table 2, then:

- compliance is deemed to occur if no measured disturbance level, increased by  $(U_{lab} - U_{cispr})$ , exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level, increased by  $(U_{lab} - U_{cispr})$ , exceeds the disturbance limit.

Based on CISPR 16-4-2-2011, measurement uncertainty of radiated emission at a distance of 3m at Bay Area Compliance Laboratories Corp. (Chengdu) is:

30M~200MHz:  $\pm 4.7$  dB;

200M~1GHz:  $\pm 6.0$  dB;

1G~6GHz:  $\pm 5.13$  dB;


6G~25GHz:  $\pm 5.47$  dB;

Table 2 – Values of  $U_{cispr}$


| Measurement                                                                                | $U_{cispr}$ |
|--------------------------------------------------------------------------------------------|-------------|
| Radiated disturbance (electric field strength at an OATS or in a SAC) (30 MHz to 1000 MHz) | 6.3 dB      |
| Radiated disturbance (electric field strength in a FAR) (1 GHz to 6 GHz)                   | 5.2 dB      |
| Radiated disturbance (electric field strength in a FAR) (6 GHz to 18 GHz)                  | 5.5 dB      |

## EUT Setup

### Below 1GHz:



### Above 1GHz:



The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

## EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

30MHz-1000MHz:

| Detector | RBW     | Video B/W | IF B/W |
|----------|---------|-----------|--------|
| QP       | 120 kHz | 300 kHz   | 120kHz |

1GHz- 25GHz:

| Detector | Duty cycle | RBW  | Video B/W |
|----------|------------|------|-----------|
| PK       | Any        | 1MHz | 3 MHz     |
| Ave.     | >98%       | 1MHz | 10 Hz     |
|          | <98%       | 1MHz | 1/T       |

Note: T is minimum transmission duration

## Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

## Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Loss and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Loss} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

## Test Equipment List and Details

| Manufacturer          | Description           | Model       | Serial Number   | Calibration Date | Calibration Due Date |
|-----------------------|-----------------------|-------------|-----------------|------------------|----------------------|
| Agilent               | Amplifier             | 8447D       | 2944A10442      | 2016-12-02       | 2017-12-01           |
| Rohde & Schwarz       | EMI Test Receiver     | ESCI        | 100028          | 2016-12-02       | 2017-12-01           |
| Sunol Sciences        | Broadband Antenna     | JB3         | A101808         | 2016-04-10       | 2019-04-09           |
| Rohde & Schwarz       | Spectrum Analyzer     | FSEM30      | 100018          | 2016-12-02       | 2017-12-01           |
| ETS                   | Horn Antenna          | 3115        | 003-6076        | 2016-12-02       | 2017-12-01           |
| Ducommun Technologies | Horn Antenna          | ARH-4223-02 | 1007726-0113024 | 2014-06-16       | 2017-06-15           |
| Mini-circuits         | Amplifier             | ZVA-183-S+  | 771001215       | 2016-05-20       | 2017-05-19           |
| HP                    | Amplifier             | 8449B       | 3008A00277      | 2016-12-02       | 2017-12-01           |
| EMCT                  | Semi-Anechoic Chamber | 966         | N/A             | 2015-04-24       | 2018-04-23           |
| N/A                   | RF Cable (below 1GHz) | NO.1        | N/A             | 2016-11-10       | 2017-11-09           |
| N/A                   | RF Cable (below 1GHz) | NO.4        | N/A             | 2016-11-10       | 2017-11-09           |
| N/A                   | RF Cable (above 1GHz) | NO.2        | N/A             | 2016-11-10       | 2017-11-09           |
| WEINSCHL ENGINEERING  | Attenuator            | 1A10dB      | AA4135          | 2016-11-10       | 2017-11-09           |

\* **Statement of Traceability:** BACL (Chengdu) attested that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

## Test Data

### Environmental Conditions

|                           |           |
|---------------------------|-----------|
| <b>Temperature:</b>       | 24.2 °C   |
| <b>Relative Humidity:</b> | 49 %      |
| <b>ATM Pressure:</b>      | 101.8 kPa |

\* The testing was performed by Lorin Bian from 2017-03-04.

Test Mode: Transmitting

**30MHz-25GHz:**  
802.11b Mode

| Frequency<br>(MHz)       | Receiver          |                        | Rx Antenna     |                | Cable<br>loss<br>(dB) | Amplifier<br>Gain<br>(dB) | Corrected<br>Amplitude<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) |
|--------------------------|-------------------|------------------------|----------------|----------------|-----------------------|---------------------------|------------------------------------|-------------------|----------------|
|                          | Reading<br>(dBμV) | Detector<br>(PK/QP/AV) | Polar<br>(H/V) | Factor<br>(dB) |                       |                           |                                    |                   |                |
| Low Channel: 2412 MHz    |                   |                        |                |                |                       |                           |                                    |                   |                |
| 2412                     | 75.29             | PK                     | H              | 23.50          | 3.00                  | 0.00                      | 101.79                             | N/A               | N/A            |
| 2412                     | 72.1              | AV                     | H              | 23.50          | 3.00                  | 0.00                      | 98.60                              | N/A               | N/A            |
| 2412                     | 72.65             | PK                     | V              | 23.50          | 3.00                  | 0.00                      | 99.15                              | N/A               | N/A            |
| 2412                     | 68.74             | AV                     | V              | 23.50          | 3.00                  | 0.00                      | 95.24                              | N/A               | N/A            |
| 2390                     | 28.75             | PK                     | H              | 23.57          | 3.00                  | 0.00                      | 55.32                              | 74.00             | 18.68          |
| 2390                     | 17.48             | AV                     | H              | 23.57          | 3.00                  | 0.00                      | 44.05                              | 54.00             | 9.95           |
| 4824                     | 46.47             | PK                     | H              | 30.84          | 5.11                  | 26.87                     | 55.55                              | 74.00             | 18.45          |
| 4824                     | 40.28             | AV                     | H              | 30.84          | 5.11                  | 26.87                     | 49.36                              | 54.00             | 4.64           |
| 7236                     | 43.65             | PK                     | H              | 34.77          | 6.18                  | 26.36                     | 58.24                              | 74.00             | 15.76          |
| 7236                     | 30.18             | AV                     | H              | 34.77          | 6.18                  | 26.36                     | 44.77                              | 54.00             | 9.23           |
| 1732                     | 36.25             | PK                     | H              | 24.47          | 2.85                  | 26.56                     | 37.01                              | 74.00             | 36.99          |
| 1732                     | 20.18             | AV                     | H              | 24.47          | 2.85                  | 26.56                     | 20.94                              | 54.00             | 33.06          |
| 646.92                   | 38.09             | QP                     | V              | 20.25          | 1.93                  | 28.85                     | 31.42                              | 46.00             | 14.58          |
| 700.27                   | 36.8              | QP                     | V              | 20.80          | 1.93                  | 28.72                     | 30.81                              | 46.00             | 15.19          |
| Middle Channel: 2437 MHz |                   |                        |                |                |                       |                           |                                    |                   |                |
| 2437                     | 74.26             | PK                     | H              | 23.41          | 3.00                  | 0.00                      | 100.67                             | N/A               | N/A            |
| 2437                     | 70.04             | AV                     | H              | 23.41          | 3.00                  | 0.00                      | 96.45                              | N/A               | N/A            |
| 2437                     | 71.22             | PK                     | V              | 23.41          | 3.00                  | 0.00                      | 97.63                              | N/A               | N/A            |
| 2437                     | 67.49             | AV                     | V              | 23.41          | 3.00                  | 0.00                      | 93.90                              | N/A               | N/A            |
| 4874                     | 46.85             | PK                     | H              | 31.00          | 5.09                  | 26.87                     | 56.07                              | 74.00             | 17.93          |
| 4874                     | 40.52             | AV                     | H              | 31.00          | 5.09                  | 26.87                     | 49.74                              | 54.00             | 4.26           |
| 7311                     | 42.14             | PK                     | H              | 34.92          | 6.21                  | 26.40                     | 56.87                              | 74.00             | 17.13          |
| 7311                     | 30.68             | AV                     | H              | 34.92          | 6.21                  | 26.40                     | 45.41                              | 54.00             | 8.59           |
| 1539                     | 35.27             | PK                     | H              | 24.16          | 2.70                  | 26.37                     | 35.76                              | 74.00             | 38.24          |
| 1539                     | 22.56             | AV                     | H              | 24.16          | 2.70                  | 26.37                     | 23.05                              | 54.00             | 30.95          |
| 2264                     | 33.24             | PK                     | H              | 24.00          | 3.02                  | 26.86                     | 33.40                              | 74.00             | 40.60          |
| 2264                     | 21.06             | AV                     | H              | 24.00          | 3.02                  | 26.86                     | 21.22                              | 54.00             | 32.78          |
| 646.92                   | 38.63             | QP                     | V              | 20.25          | 1.93                  | 28.85                     | 31.96                              | 46.00             | 14.04          |
| 700.27                   | 37.19             | QP                     | V              | 20.80          | 1.93                  | 28.72                     | 31.20                              | 46.00             | 14.80          |
| High Channel: 2462 MHz   |                   |                        |                |                |                       |                           |                                    |                   |                |
| 2462                     | 74.25             | PK                     | H              | 23.33          | 2.99                  | 0.00                      | 100.57                             | N/A               | N/A            |
| 2462                     | 71.02             | AV                     | H              | 23.33          | 2.99                  | 0.00                      | 97.34                              | N/A               | N/A            |
| 2462                     | 71.26             | PK                     | V              | 23.33          | 2.99                  | 0.00                      | 97.58                              | N/A               | N/A            |
| 2462                     | 68.24             | AV                     | V              | 23.33          | 2.99                  | 0.00                      | 94.56                              | N/A               | N/A            |
| 2483.5                   | 28.22             | PK                     | H              | 23.26          | 2.99                  | 0.00                      | 54.47                              | 74.00             | 19.53          |
| 2483.5                   | 17.48             | AV                     | H              | 23.26          | 2.99                  | 0.00                      | 43.73                              | 54.00             | 10.27          |
| 4924                     | 48.74             | PK                     | H              | 31.16          | 5.07                  | 26.88                     | 58.09                              | 74.00             | 15.91          |
| 4924                     | 31.06             | AV                     | H              | 31.16          | 5.07                  | 26.88                     | 40.41                              | 54.00             | 13.59          |
| 7386                     | 43.22             | PK                     | H              | 35.07          | 6.25                  | 26.43                     | 58.11                              | 74.00             | 15.89          |
| 7386                     | 28.74             | AV                     | H              | 35.07          | 6.25                  | 26.43                     | 43.63                              | 54.00             | 10.37          |
| 2044                     | 33.19             | PK                     | H              | 24.75          | 3.04                  | 26.83                     | 34.15                              | 74.00             | 39.85          |
| 2044                     | 22.64             | AV                     | H              | 24.75          | 3.04                  | 26.83                     | 23.60                              | 54.00             | 30.40          |
| 646.92                   | 38.92             | QP                     | V              | 20.25          | 1.93                  | 28.85                     | 32.25                              | 46.00             | 13.75          |
| 700.27                   | 37.63             | QP                     | V              | 20.80          | 1.93                  | 28.72                     | 31.64                              | 46.00             | 14.36          |

802.11g Mode

| Frequency<br>(MHz)       | Receiver          |                        | Rx Antenna     |                | Cable<br>loss<br>(dB) | Amplifier<br>Gain<br>(dB) | Corrected<br>Amplitude<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) |
|--------------------------|-------------------|------------------------|----------------|----------------|-----------------------|---------------------------|------------------------------------|-------------------|----------------|
|                          | Reading<br>(dBμV) | Detector<br>(PK/QP/AV) | Polar<br>(H/V) | Factor<br>(dB) |                       |                           |                                    |                   |                |
| Low Channel: 2412 MHz    |                   |                        |                |                |                       |                           |                                    |                   |                |
| 2412                     | 72.14             | PK                     | H              | 23.50          | 3.00                  | 0.00                      | 98.64                              | N/A               | N/A            |
| 2412                     | 63.47             | AV                     | H              | 23.50          | 3.00                  | 0.00                      | 89.97                              | N/A               | N/A            |
| 2412                     | 70.25             | PK                     | V              | 23.50          | 3.00                  | 0.00                      | 96.75                              | N/A               | N/A            |
| 2412                     | 60.43             | AV                     | V              | 23.50          | 3.00                  | 0.00                      | 86.93                              | N/A               | N/A            |
| 2390                     | 25.36             | PK                     | H              | 23.57          | 3.00                  | 0.00                      | 51.93                              | 74.00             | 22.07          |
| 2390                     | 17.84             | AV                     | H              | 23.57          | 3.00                  | 0.00                      | 44.41                              | 54.00             | 9.59           |
| 4824                     | 45.95             | PK                     | H              | 30.84          | 5.11                  | 26.87                     | 55.03                              | 74.00             | 18.97          |
| 4824                     | 30.28             | AV                     | H              | 30.84          | 5.11                  | 26.87                     | 39.36                              | 54.00             | 14.64          |
| 7236                     | 42.66             | PK                     | H              | 34.77          | 6.18                  | 26.36                     | 57.25                              | 74.00             | 16.75          |
| 7236                     | 30.17             | AV                     | H              | 34.77          | 6.18                  | 26.36                     | 44.76                              | 54.00             | 9.24           |
| 1586                     | 35.44             | PK                     | H              | 24.24          | 2.74                  | 26.41                     | 36.01                              | 74.00             | 37.99          |
| 1586                     | 23.47             | AV                     | H              | 24.24          | 2.74                  | 26.41                     | 24.04                              | 54.00             | 29.96          |
| 646.92                   | 39.19             | QP                     | V              | 20.25          | 1.93                  | 28.85                     | 32.52                              | 46.00             | 13.48          |
| 700.27                   | 38.07             | QP                     | V              | 20.80          | 1.93                  | 28.72                     | 32.08                              | 46.00             | 13.92          |
| Middle Channel: 2437 MHz |                   |                        |                |                |                       |                           |                                    |                   |                |
| 2437                     | 72.54             | PK                     | H              | 23.41          | 3.00                  | 0.00                      | 98.95                              | N/A               | N/A            |
| 2437                     | 63.85             | AV                     | H              | 23.41          | 3.00                  | 0.00                      | 90.26                              | N/A               | N/A            |
| 2437                     | 70.74             | PK                     | V              | 23.41          | 3.00                  | 0.00                      | 97.15                              | N/A               | N/A            |
| 2437                     | 60.29             | AV                     | V              | 23.41          | 3.00                  | 0.00                      | 86.70                              | N/A               | N/A            |
| 4874                     | 45.28             | PK                     | H              | 31.00          | 5.09                  | 26.87                     | 54.50                              | 74.00             | 19.50          |
| 4874                     | 32.09             | AV                     | H              | 31.00          | 5.09                  | 26.87                     | 41.31                              | 54.00             | 12.69          |
| 7311                     | 42.58             | PK                     | H              | 34.92          | 6.21                  | 26.40                     | 57.31                              | 74.00             | 16.69          |
| 7311                     | 30.11             | AV                     | H              | 34.92          | 6.21                  | 26.40                     | 44.84                              | 54.00             | 9.16           |
| 1663                     | 35.47             | PK                     | H              | 24.36          | 2.79                  | 26.49                     | 36.13                              | 74.00             | 37.87          |
| 1663                     | 23.19             | AV                     | H              | 24.36          | 2.79                  | 26.49                     | 23.85                              | 54.00             | 30.15          |
| 646.92                   | 38.41             | QP                     | V              | 20.25          | 1.93                  | 28.85                     | 31.74                              | 46.00             | 14.26          |
| 700.27                   | 35.74             | QP                     | V              | 20.80          | 1.93                  | 28.72                     | 29.75                              | 46.00             | 16.25          |
| High Channel: 2462 MHz   |                   |                        |                |                |                       |                           |                                    |                   |                |
| 2462                     | 72.15             | PK                     | H              | 23.33          | 2.99                  | 0.00                      | 98.47                              | N/A               | N/A            |
| 2462                     | 63.22             | AV                     | H              | 23.33          | 2.99                  | 0.00                      | 89.54                              | N/A               | N/A            |
| 2462                     | 70.14             | PK                     | V              | 23.33          | 2.99                  | 0.00                      | 96.46                              | N/A               | N/A            |
| 2462                     | 60.38             | AV                     | V              | 23.33          | 2.99                  | 0.00                      | 86.70                              | N/A               | N/A            |
| 2483.5                   | 28.56             | PK                     | H              | 23.26          | 2.99                  | 0.00                      | 54.81                              | 74.00             | 19.19          |
| 2483.5                   | 17.49             | AV                     | H              | 23.26          | 2.99                  | 0.00                      | 43.74                              | 54.00             | 10.26          |
| 4924                     | 47.26             | PK                     | H              | 31.16          | 5.07                  | 26.88                     | 56.61                              | 74.00             | 17.39          |
| 4924                     | 33.61             | AV                     | H              | 31.16          | 5.07                  | 26.88                     | 42.96                              | 54.00             | 11.04          |
| 7386                     | 42.62             | PK                     | H              | 35.07          | 6.25                  | 26.43                     | 57.51                              | 74.00             | 16.49          |
| 7386                     | 30.67             | AV                     | H              | 35.07          | 6.25                  | 26.43                     | 45.56                              | 54.00             | 8.44           |
| 1576                     | 36.09             | PK                     | H              | 24.22          | 2.73                  | 26.40                     | 36.64                              | 74.00             | 37.36          |
| 1576                     | 24.64             | AV                     | H              | 24.22          | 2.73                  | 26.40                     | 25.19                              | 54.00             | 28.81          |
| 646.92                   | 38.95             | QP                     | V              | 20.25          | 1.93                  | 28.85                     | 32.28                              | 46.00             | 13.72          |
| 700.27                   | 36.13             | QP                     | V              | 20.80          | 1.93                  | 28.72                     | 30.14                              | 46.00             | 15.86          |

802.11 n ht20 Mode

| Frequency<br>(MHz)       | Receiver          |                        | Rx Antenna     |                | Cable<br>loss<br>(dB) | Amplifier<br>Gain<br>(dB) | Corrected<br>Amplitude<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) |
|--------------------------|-------------------|------------------------|----------------|----------------|-----------------------|---------------------------|------------------------------------|-------------------|----------------|
|                          | Reading<br>(dBμV) | Detector<br>(PK/QP/AV) | Polar<br>(H/V) | Factor<br>(dB) |                       |                           |                                    |                   |                |
| Low Channel: 2412 MHz    |                   |                        |                |                |                       |                           |                                    |                   |                |
| 2412                     | 72.15             | PK                     | H              | 23.50          | 3.00                  | 0.00                      | 98.65                              | N/A               | N/A            |
| 2412                     | 62.31             | AV                     | H              | 23.50          | 3.00                  | 0.00                      | 88.81                              | N/A               | N/A            |
| 2412                     | 70.18             | PK                     | V              | 23.50          | 3.00                  | 0.00                      | 96.68                              | N/A               | N/A            |
| 2412                     | 59.88             | AV                     | V              | 23.50          | 3.00                  | 0.00                      | 86.38                              | N/A               | N/A            |
| 2390                     | 28.74             | PK                     | H              | 23.57          | 3.00                  | 0.00                      | 55.31                              | 74.00             | 18.69          |
| 2390                     | 18.06             | AV                     | H              | 23.57          | 3.00                  | 0.00                      | 44.63                              | 54.00             | 9.37           |
| 4824                     | 47.84             | PK                     | H              | 30.84          | 5.11                  | 26.87                     | 56.92                              | 74.00             | 17.08          |
| 4824                     | 33.69             | AV                     | H              | 30.84          | 5.11                  | 26.87                     | 42.77                              | 54.00             | 11.23          |
| 7236                     | 44.65             | PK                     | H              | 34.77          | 6.18                  | 26.36                     | 59.24                              | 74.00             | 14.76          |
| 7236                     | 30.25             | AV                     | H              | 34.77          | 6.18                  | 26.36                     | 44.84                              | 54.00             | 9.16           |
| 2950                     | 36.21             | PK                     | H              | 24.10          | 3.39                  | 26.46                     | 37.24                              | 74.00             | 36.76          |
| 2950                     | 24.57             | AV                     | H              | 24.10          | 3.39                  | 26.46                     | 25.60                              | 54.00             | 28.40          |
| 646.92                   | 39.24             | QP                     | V              | 20.25          | 1.93                  | 28.85                     | 32.57                              | 46.00             | 13.43          |
| 700.27                   | 36.57             | QP                     | V              | 20.80          | 1.93                  | 28.72                     | 30.58                              | 46.00             | 15.42          |
| Middle Channel: 2437 MHz |                   |                        |                |                |                       |                           |                                    |                   |                |
| 2437                     | 72.19             | PK                     | H              | 23.41          | 3.00                  | 0.00                      | 98.60                              | N/A               | N/A            |
| 2437                     | 62.66             | AV                     | H              | 23.41          | 3.00                  | 0.00                      | 89.07                              | N/A               | N/A            |
| 2437                     | 70.18             | PK                     | V              | 23.41          | 3.00                  | 0.00                      | 96.59                              | N/A               | N/A            |
| 2437                     | 58.94             | AV                     | V              | 23.41          | 3.00                  | 0.00                      | 85.35                              | N/A               | N/A            |
| 4874                     | 48.79             | PK                     | H              | 31.00          | 5.09                  | 26.87                     | 58.01                              | 74.00             | 15.99          |
| 4874                     | 34.06             | AV                     | H              | 31.00          | 5.09                  | 26.87                     | 43.28                              | 54.00             | 10.72          |
| 7311                     | 44.66             | PK                     | H              | 34.92          | 6.21                  | 26.40                     | 59.39                              | 74.00             | 14.61          |
| 7311                     | 31.64             | AV                     | H              | 34.92          | 6.21                  | 26.40                     | 46.37                              | 54.00             | 7.63           |
| 1588                     | 35.84             | PK                     | H              | 24.24          | 2.74                  | 26.42                     | 36.40                              | 74.00             | 37.60          |
| 1588                     | 22.47             | AV                     | H              | 24.24          | 2.74                  | 26.42                     | 23.03                              | 54.00             | 30.97          |
| 646.92                   | 39.51             | QP                     | V              | 20.25          | 1.93                  | 28.85                     | 32.84                              | 46.00             | 13.16          |
| 700.27                   | 37.01             | QP                     | V              | 20.80          | 1.93                  | 28.72                     | 31.02                              | 46.00             | 14.98          |
| High Channel: 2462 MHz   |                   |                        |                |                |                       |                           |                                    |                   |                |
| 2462                     | 72.25             | PK                     | H              | 23.33          | 2.99                  | 0.00                      | 98.57                              | N/A               | N/A            |
| 2462                     | 62.67             | AV                     | H              | 23.33          | 2.99                  | 0.00                      | 88.99                              | N/A               | N/A            |
| 2462                     | 70.14             | PK                     | V              | 23.33          | 2.99                  | 0.00                      | 96.46                              | N/A               | N/A            |
| 2462                     | 69.28             | AV                     | V              | 23.33          | 2.99                  | 0.00                      | 95.60                              | N/A               | N/A            |
| 2483.5                   | 27.68             | PK                     | H              | 23.26          | 2.99                  | 0.00                      | 53.93                              | 74.00             | 20.07          |
| 2483.5                   | 18.96             | AV                     | H              | 23.26          | 2.99                  | 0.00                      | 45.21                              | 54.00             | 8.79           |
| 4924                     | 48.55             | PK                     | H              | 31.16          | 5.07                  | 26.88                     | 57.90                              | 74.00             | 16.10          |
| 4924                     | 33.59             | AV                     | H              | 31.16          | 5.07                  | 26.88                     | 42.94                              | 54.00             | 11.06          |
| 7386                     | 42.84             | PK                     | H              | 35.07          | 6.25                  | 26.43                     | 57.73                              | 74.00             | 16.27          |
| 7386                     | 29.98             | AV                     | H              | 35.07          | 6.25                  | 26.43                     | 44.87                              | 54.00             | 9.13           |
| 2950                     | 35.44             | PK                     | H              | 24.10          | 3.39                  | 26.46                     | 36.47                              | 74.00             | 37.53          |
| 2950                     | 21.69             | AV                     | H              | 24.10          | 3.39                  | 26.46                     | 22.72                              | 54.00             | 31.28          |
| 646.92                   | 37.84             | QP                     | V              | 20.25          | 1.93                  | 28.85                     | 31.17                              | 46.00             | 14.83          |
| 700.27                   | 35.69             | QP                     | V              | 20.80          | 1.93                  | 28.72                     | 29.70                              | 46.00             | 16.30          |


## FCC §15.247(d) - SPURIOUS EMISSIONS AT ANTENNA PORT

### Applicable Standard

FCC §15.247 (d)

### Test Procedure

- Set RBW = 1 MHz.
- Set the video bandwidth (VBW)  $\geq 3 \times$  RBW.
- Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Allow the trace to stabilize.
- Measure the emission from 30MHz to 25GHz.



### Test Equipment List and Details

| Manufacturer    | Description     | Model  | Serial Number | Calibration Date | Calibration Due Date |
|-----------------|-----------------|--------|---------------|------------------|----------------------|
| Rohde & Schwarz | Signal Analyzer | FSIQ26 | 831929/005    | 2016-09-21       | 2017-09-20           |
| N/A             | RF Cable        | N/A    | N/A           | Each Time        | /                    |

\* **Statement of Traceability:** BACL (Chengdu) attested that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

### Test Data


#### Environmental Conditions

|                    |          |
|--------------------|----------|
| Temperature:       | 26.8 °C  |
| Relative Humidity: | 41 %     |
| ATM Pressure:      | 99.3 kPa |


\* The testing was performed by Lorin Bian on 2017-01-19.

Test Results: Compliant, (All emission under the Average limit 54dBuV/m(EIRP -41.2dBm)) more than 5dB.


### 802.11b Low Channel




### 802.11b Middle Channel




### 802.11b High Channel




### 802.11g Low Channel




### 802.11g Middle Channel




### 802.11g High Channel




### 802.11n ht20 Low Channel



### 802.11n ht20 Middle Channel



### 802.11n ht20 High Channel




## FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH

### Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

### Test Procedure

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW)  $\geq 3 \times$  RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



### Test Equipment List and Details

| Manufacturer    | Description     | Model  | Serial Number | Calibration Date | Calibration Due Date |
|-----------------|-----------------|--------|---------------|------------------|----------------------|
| Rohde & Schwarz | Signal Analyzer | FSIQ26 | 831929/005    | 2016-09-21       | 2017-09-20           |
| N/A             | RF Cable        | N/A    | N/A           | Each Time        | /                    |

\* **Statement of Traceability:** BACL (Chengdu) attested that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

### Test Data

#### Environmental Conditions


|                    |                 |
|--------------------|-----------------|
| Temperature:       | 22.8~25.7 °C    |
| Relative Humidity: | 32~39 %         |
| ATM Pressure:      | 101.6~101.8 kPa |

\* The testing was performed by Lorin Bian from 2016-12-29 to 2017-01-17.


Test Mode: Transmitting

Test Result: Compliant. Please refer to the following table and plots.


| Test mode | Channel | Frequency (MHz) | 6 dB Bandwidth (MHz) | Limit (MHz) |
|-----------|---------|-----------------|----------------------|-------------|
| 802.11b   | Low     | 2412            | 9.78                 | ≥0.5        |
|           | Middle  | 2437            | 10.50                | ≥0.5        |
|           | High    | 2462            | 10.1                 | ≥0.5        |
| 802.11g   | Low     | 2412            | 16.51                | ≥0.5        |
|           | Middle  | 2437            | 16.51                | ≥0.5        |
|           | High    | 2462            | 16.59                | ≥0.5        |
| 802.11n20 | Low     | 2412            | 17.64                | ≥0.5        |
|           | Middle  | 2437            | 17.8                 | ≥0.5        |
|           | High    | 2462            | 17.72                | ≥0.5        |




### 802.11b Middle Channel




### 802.11b High Channel




### 802.11g Low Channel




### 802.11g Middle Channel




### 802.11g High Channel




### 802.11n ht20 Low Channel



### 802.11n ht20 Middle Channel



### 802.11n ht20 High Channel




## FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

### Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

### Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to test equipment.
3. Add a correction factor to the display.



### Test Equipment List and Details

| Manufacturer | Description           | Model  | Serial Number | Calibration Date | Calibration Due Date |
|--------------|-----------------------|--------|---------------|------------------|----------------------|
| Agilent      | Wideband Power Sensor | N1921A | MY54170074    | 2016-01-03       | 2017-01-03           |
| Agilent      | P-Series Power Meter  | N1912A | MY5000798     | 2016-01-03       | 2017-01-03           |
| N/A          | RF Cable              | N/A    | N/A           | Each Time        | /                    |

\* **Statement of Traceability:** BACL (Chengdu) attested that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

## Test Data

### Environmental Conditions

|                           |           |
|---------------------------|-----------|
| <b>Temperature:</b>       | 25.7 °C   |
| <b>Relative Humidity:</b> | 32 %      |
| <b>ATM Pressure:</b>      | 101.8 kPa |

*\* The testing was performed by Lorin Bian on 2016-12-29.*

*Test Mode: Transmitting*

*Test Result: Compliant. Please refer to the following table.*

| Test mode | Channel | Frequency (MHz) | Max Peak Conducted Output Power (dBm) | Limit (dBm) |
|-----------|---------|-----------------|---------------------------------------|-------------|
| 802.11b   | Low     | 2412            | 19.21                                 | 30          |
|           | Middle  | 2437            | 17.64                                 | 30          |
|           | High    | 2462            | 18.21                                 | 30          |
| 802.11g   | Low     | 2412            | 18.61                                 | 30          |
|           | Middle  | 2437            | 17.04                                 | 30          |
|           | High    | 2462            | 17.36                                 | 30          |
| 802.11n20 | Low     | 2412            | 17.11                                 | 30          |
|           | Middle  | 2437            | 15.74                                 | 30          |
|           | High    | 2462            | 16.06                                 | 30          |

## **FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE**

### **Applicable Standard**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### **Test Procedure**

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

### **Test Equipment List and Details**

| Manufacturer    | Description     | Model  | Serial Number | Calibration Date | Calibration Due Date |
|-----------------|-----------------|--------|---------------|------------------|----------------------|
| Rohde & Schwarz | Signal Analyzer | FSIQ26 | 831929/005    | 2016-09-21       | 2017-09-20           |
| N/A             | RF Cable        | N/A    | N/A           | Each Time        | /                    |

\* **Statement of Traceability:** BACL (Chengdu) attested that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

## Test Data


### Environmental Conditions

|                    |           |
|--------------------|-----------|
| Temperature:       | 25.7 °C   |
| Relative Humidity: | 32 %      |
| ATM Pressure:      | 101.8 kPa |


\* The testing was performed by Lorin Bian on 2016-12-29.

Test mode: Transmitting


Test Result: Compliant. Please refer to following plots.




### 802.11b: Band Edge, Right Side




### 802.11g: Band Edge, Left Side




### 802.11g: Band Edge, Right Side



### 802.11n ht20 Band Edge, Left Side



### 802.11n ht20 Band Edge, Right Side



## CC §15.247(e) - POWER SPECTRAL DENSITY

### Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

### Test Procedure

- a) Set analyzer center frequency to DTS channel center frequency.
- b) Set the span to 1.5 times the DTS bandwidth.
- c) Set the RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
- d) Set the VBW  $\geq 3 \times \text{RBW}$ .
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level within the RBW.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

### Test Equipment List and Details

| Manufacturer    | Description     | Model  | Serial Number | Calibration Date | Calibration Due Date |
|-----------------|-----------------|--------|---------------|------------------|----------------------|
| Rohde & Schwarz | Signal Analyzer | FSIQ26 | 831929/005    | 2016-09-21       | 2017-09-20           |
| N/A             | RF Cable        | N/A    | N/A           | Each Time        | /                    |

\* **Statement of Traceability:** BACL (Chengdu) attested that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

### Test Data

#### Environmental Conditions

|                    |                 |
|--------------------|-----------------|
| Temperature:       | 22.8~25.7 °C    |
| Relative Humidity: | 32~39 %         |
| ATM Pressure:      | 101.6~101.8 kPa |


\* The testing was performed by Lorin Bian from 2016-12-29 to 2017-01-17.

Test Mode: Transmitting


Test Result: Compliant. Please refer to the following table and plots

| Test mode | Channel | Frequency (MHz) | PSD (dBm/3kHz) | Limit (dBm/3kHz) |
|-----------|---------|-----------------|----------------|------------------|
| 802.11b   | Low     | 2412            | -11.77         | ≤8               |
|           | Middle  | 2437            | -12.92         | ≤8               |
|           | High    | 2462            | -12.72         | ≤8               |
| 802.11g   | Low     | 2412            | -13.72         | ≤8               |
|           | Middle  | 2437            | -15.47         | ≤8               |
|           | High    | 2462            | -15.34         | ≤8               |
| 802.11n20 | Low     | 2412            | -14.54         | ≤8               |
|           | Middle  | 2437            | -16.06         | ≤8               |
|           | High    | 2462            | -15.84         | ≤8               |


### Power Spectral Density, 802.11b Low Channel




### Power Spectral Density, 802.11b Middle Channel




### Power Spectral Density, 802.11b High Channel




### Power Spectral Density, 802.11g Low Channel



### Power Spectral Density, 802.11g Middle Channel




### Power Spectral Density, 802.11g High Channel




Date: 29.DEC.2016 18:14:17

### Power Spectral Density, 802.11n ht20 Low Channel




Date: 29.DEC.2016 17:40:12

### Power Spectral Density, 802.11n ht20 Middle Channel



Date: 29.DEC.2016 17:52:46

### Power Spectral Density, 802.11n ht20 High Channel



Date: 29.DEC.2016 17:58:34

\*\*\*\*\* END OF REPORT \*\*\*\*\*