

MaxLite®
 MODEL/MODÈLE: ML2LASABNU169CSEMMSV
 120-277V AC 50/60Hz 16W
 CONFORMS TO UL STD. 1598
 CONFORME À LA NORME UL1598
 CERTIFIED TO CSA STD. C22.2 No. 250.0
 CERTIFIÉ SELON LA NORME CSA C22.2 No. 250.0
 MADE IN CHINA/FABRIQUÉ EN CHINE
JA8-2019
 20F256101 KLD3001LS-EM-MSV



CAN ICES-005(B)/NMB-005(B)
 MIN 90 °C SUPPLY CONDUCTORS
 LES FILS D'ALIMENTATION 90 °C MIN
 SUITABLE FOR DAMP LOCATIONS
 CONVIENT AUX EMPLACEMENTS HUMIDES
 MAXIMUM AMBIENT OPERATING TEMPERATURE 40°C
 TEMPÉRATURE AMBIANTE MAXIMALE DE FONCTIONNEMENT 40°C
 CAUTION – RISK OF FIRE / ATTENTION – RISQUE D'INCENDIE

CLASS 1 CLASS 1 CÂBLAGE
 WIRING ONLY SEULEMENT

2700K
 3000K
 3500K
 4000K
 5000K

FCC ID: 2AK53ML2LAUMSV
 This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. Este dispositivo cumple con la Parte 15 de las Reglas de la FCC. La operación está sujeta a las dos siguientes condiciones: (1) Este dispositivo no provoca ninguna Interferencia perjudicial, (2) Este dispositivo aceptará cualquier interferencia que reciba, incluyendo aquellas que provoquen una operación no deseada.

MaxLite®
 MODEL/MODÈLE: ML2LAMABNU209CSEMMSV
 120-277V AC 50/60Hz 20W
 CONFORMS TO UL STD. 1598
 CONFORME À LA NORME UL1598
 CERTIFIED TO CSA STD. C22.2 No. 250.0
 CERTIFIÉ SELON LA NORME CSA C22.2 No. 250.0
 MADE IN CHINA/FABRIQUÉ EN CHINE
JA8-2019
 20F256101 KLD3001L-EM-MSV



CAN ICES-005(B)/NMB-005(B)
 MIN 90 °C SUPPLY CONDUCTORS
 LES FILS D'ALIMENTATION 90 °C MIN
 SUITABLE FOR DAMP LOCATIONS
 CONVIENT AUX EMPLACEMENTS HUMIDES
 MAXIMUM AMBIENT OPERATING TEMPERATURE 40°C
 TEMPÉRATURE AMBIANTE MAXIMALE DE FONCTIONNEMENT 40°C
 CAUTION – RISK OF FIRE / ATTENTION – RISQUE D'INCENDIE

CLASS 1 CLASS 1 CÂBLAGE
 WIRING ONLY SEULEMENT

2700K
 3000K
 3500K
 4000K
 5000K

FCC ID: 2AK53ML2LAUMSV
 This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. Este dispositivo cumple con la Parte 15 de las Reglas de la FCC. La operación está sujeta a las dos siguientes condiciones: (1) Este dispositivo no provoca ninguna Interferencia perjudicial, (2) Este dispositivo aceptará cualquier interferencia que reciba, incluyendo aquellas que provoquen una operación no deseada.

MaxLite®
 MODEL/MODÈLE: ML2LALABNU249CSEMMSV
 120-277V AC 50/60Hz 24W
 CONFORMS TO UL STD. 1598
 CONFORME À LA NORME UL1598
 CERTIFIED TO CSA STD. C22.2 No. 250.0
 CERTIFIÉ SELON LA NORME CSA C22.2 No. 250.0
 MADE IN CHINA/FABRIQUÉ EN CHINE
JA8-2019
 20F256101 KLD3001LL-EM-MSV



CAN ICES-005(B)/NMB-005(B)
 MIN 90 °C SUPPLY CONDUCTORS
 LES FILS D'ALIMENTATION 90 °C MIN
 SUITABLE FOR DAMP LOCATIONS
 CONVIENT AUX EMPLACEMENTS HUMIDES
 MAXIMUM AMBIENT OPERATING TEMPERATURE 40°C
 TEMPÉRATURE AMBIANTE MAXIMALE DE FONCTIONNEMENT 40°C
 CAUTION – RISK OF FIRE / ATTENTION – RISQUE D'INCENDIE

CLASS 1 CLASS 1 CÂBLAGE
 WIRING ONLY SEULEMENT

2700K
 3000K
 3500K
 4000K
 5000K

FCC ID: 2AK53ML2LAUMSV
 This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. Este dispositivo cumple con la Parte 15 de las Reglas de la FCC. La operación está sujeta a las dos siguientes condiciones: (1) Este dispositivo no provoca ninguna Interferencia perjudicial, (2) Este dispositivo aceptará cualquier interferencia que reciba, incluyendo aquellas que provoquen una operación no deseada.

