

TEST REPORT

Product : Beyond Tablet
Trade mark : Beyond Screen
Model/Type reference : BYM001
Serial Number : N/A
Report Number : EED32J00028401
FCC ID : 2AK5X-BM2897
Date of Issue : Mar. 30, 2017
Test Standards : 47 CFR Part 15 Subpart C (2015)
Test result : PASS

Prepared for:

Beyond Screen Limited
Suite 307, Building 6, Fulltech Plaza, No. 33 North Guangshun Street,
Beijing, 100102, China

Prepared by:

Centre Testing International Group Co., Ltd.
Hongwei Industrial Zone, Bao'an 70 District,
Shenzhen, Guangdong, China
TEL: +86-755-3368 3668
FAX: +86-755-3368 3385

Tested By:

Tom chen
Tom chen (Test Project)

Compiled by:

Ware xin
Ware xin (Project Engineer)

Reviewed by:

Kevin Yang
Kevin yang (Reviewer)

Approved by:

Sheek Luo
Sheek Luo (Lab supervisor)

Date:

Mar. 30, 2017



Check No.: 1022560588

2 Version

Version No.	Date	Description
00	Mar. 30, 2017	Original

3 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15 Subpart C Section 15.203/15.247 (c)	ANSI C63.10-2013	PASS
AC Power Line Conducted Emission	47 CFR Part 15 Subpart C Section 15.207	ANSI C63.10-2013	PASS
Conducted Peak Output Power	47 CFR Part 15 Subpart C Section 15.247 (b)(1)	ANSI C63.10-2013	PASS
20dB Occupied Bandwidth	47 CFR Part 15 Subpart C Section 15.247 (a)(1)	ANSI C63.10-2013	PASS
Carrier Frequencies Separation	47 CFR Part 15 Subpart C Section 15.247 (a)(1)	ANSI C63.10-2013	PASS
Hopping Channel Number	47 CFR Part 15 Subpart C Section 15.247 (b)	ANSI C63.10-2013	PASS
Dwell Time	47 CFR Part 15 Subpart C Section 15.247 (a)(1)	ANSI C63.10-2013	PASS
Pseudorandom Frequency Hopping Sequence	47 CFR Part 15 Subpart C Section 15.247(b)(4)&TCB Exclusion List (7 July 2002)	ANSI C63.10-2013	PASS
RF Conducted Spurious Emissions	47 CFR Part 15 Subpart C Section 15.247(d)	ANSI C63.10-2013	PASS
Radiated Spurious emissions	47 CFR Part 15 Subpart C Section 15.205/15.209	ANSI C63.10-2013	PASS

Remark:

Test according to ANSI C63.4-2014 & ANSI C63.10-2013.

The tested samples and the sample information are provided by the client.


4 Content

1 COVER PAGE	1
2 VERSION	2
3 TEST SUMMARY	3
4 CONTENT	3
5 TEST REQUIREMENT	5
5.1 TEST SETUP	5
5.1.1 For Conducted test setup	5
5.1.2 For Radiated Emissions test setup	5
5.1.3 For Conducted Emissions test setup	6
5.2 TEST ENVIRONMENT	6
5.3 TEST CONDITION	6
6 GENERAL INFORMATION	7
6.1 CLIENT INFORMATION	7
6.2 GENERAL DESCRIPTION OF EUT	7
6.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD	7
6.4 DESCRIPTION OF SUPPORT UNITS	8
6.5 TEST LOCATION	8
6.6 TEST FACILITY	8
6.7 DEVIATION FROM STANDARDS	9
6.8 ABNORMALITIES FROM STANDARD CONDITIONS	9
6.9 OTHER INFORMATION REQUESTED BY THE CUSTOMER	9
6.10 MEASUREMENT UNCERTAINTY (95% CONFIDENCE LEVELS, K=2)	10
7 EQUIPMENT LIST	11
8 RADIO TECHNICAL REQUIREMENTS SPECIFICATION	13
Appendix A): 20dB Occupied Bandwidth	14
Appendix B): Carrier Frequency Separation	18
Appendix C): Dwell Time	22
Appendix D): Hopping Channel Number	26
Appendix E): Conducted Peak Output Power	28
Appendix F): Band-edge for RF Conducted Emissions	32
Appendix G): RF Conducted Spurious Emissions	37
Appendix H): Pseudorandom Frequency Hopping Sequence	44
Appendix I): Antenna Requirement	45
Appendix J): AC Power Line Conducted Emission	46
Appendix K): Restricted bands around fundamental frequency (Radiated)	49
Appendix L): Radiated Spurious Emissions	57

5 Test Requirement

5.1 Test setup

5.1.1 For Conducted test setup



5.1.2 For Radiated Emissions test setup

Radiated Emissions setup:




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz





Figure 3. Above 1GHz

5.1.3 For Conducted Emissions test setup

Conducted Emissions setup



5.2 Test Environment

Operating Environment:	
Temperature:	24°C
Humidity:	54 % RH
Atmospheric Pressure:	1010mbar

5.3 Test Condition

Test Mode	Tx	RF Channel		
		Low(L)	Middle(M)	High(H)
GFSK/ $\pi/4$ DQPSK/ 8DPSK(DH1,DH3, DH5)	2402MHz ~2480 MHz	Channel 1	Channel 40	Channel79
		2402MHz	2441MHz	2480MHz

TX mode: The EUT transmitted the continuous modulation test signal at the specific channel(s).

Test mode:

Pre-scan under all rate at Lowest channel 1

Mode	GFSK		
packets	1-DH1	1-DH3	1-DH5
Power(dBm)	2.227	2.301	2.308

Mode	$\pi/4$ DQPSK		
packets	2-DH1	2-DH3	2-DH5
Power(dBm)	3.471	3.475	3.478

Mode	8DPSK		
packets	3-DH1	3-DH3	3-DH5
Power(dBm)	3.668	3.674	3.677

Through Pre-scan, 1-DH5 packet the power is the worst case of GFSK, 2-DH5 packet the power is the worst case of $\pi/4$ DQPSK, 3-DH5 packet the power is the worst case of 8DPSK.

6 General Information

6.1 Client Information

Applicant:	Beyond Screen Limited
Address of Applicant:	Suite 307, Building 6, Fulltech Plaza, No. 33 North Guangshun Street, Beijing, 100102, China
Manufacturer:	Beyond Screen Limited
Address of Manufacturer:	Suite 307, Building 6, Fulltech Plaza, No. 33 North Guangshun Street, Beijing, 100102, China
Factory:	Shenzhen Han-Shine Electronic Co., Ltd.
Address of Factory:	No. 2, Lane 3, 2nd Industrial Park, Yulv Village, Gongming Town, Guangming New District, Shenzhen City, Guangdong Province, 518132, China

6.2 General Description of EUT

Product Name:	Beyond Tablet
Model No.(EUT):	BYM001
Trade mark:	Beyond Screen
EUT Supports Radios application:	Wlan 2.4GHz 802.11b/g/n(HT20&HT40), Bluetooth V3.0+EDR, BT 4.0 NFC(13.56MHz)
Power Supply:	Adapter: MODEL: RS-200/120-S336 INPUT: 100-240VAC, 50/60Hz, 1.5A Max OUTPUT: DC 12V=2A
AC Adapter line:	137cm(Unshielded)
Sample Received Date:	Mar. 02, 2017
Sample tested Date:	Mar. 02, 2017 to Mar. 30, 2017

6.3 Product Specification subjective to this standard

Operation Frequency:	2402MHz~2480MHz						
Bluetooth Version:	3.0+EDR						
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)						
Modulation Type:	GFSK, $\pi/4$ DQPSK, 8DPSK						
Number of Channel:	79						
Hopping Channel Type:	Adaptive Frequency Hopping systems						
Hardware Version:	BY2.MB_V0.3 BY2.TB_V0.3 BY2.LRB V0.35 BY2.KB_V0.3 (manufacturer declare)						
Software Version:	V1.0(manufacturer declare)						
Test Power Grade:	3(manufacturer declare)						
Test Software of EUT:	SoFia RFTestTool V1.1 (manufacturer declare)						
Antenna Type:	PIFA Antenna						
Antenna Gain:	3.74dBi						
Test Voltage:	AC 120V, 60Hz						
Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402MHz	21	2422MHz	41	2442MHz	61	2462MHz
2	2403MHz	22	2423MHz	42	2443MHz	62	2463MHz

3	2404MHz	23	2424MHz	43	2444MHz	63	2464MHz
4	2405MHz	24	2425MHz	44	2445MHz	64	2465MHz
5	2406MHz	25	2426MHz	45	2446MHz	65	2466MHz
6	2407MHz	26	2427MHz	46	2447MHz	66	2467MHz
7	2408MHz	27	2428MHz	47	2448MHz	67	2468MHz
8	2409MHz	28	2429MHz	48	2449MHz	68	2469MHz
9	2410MHz	29	2430MHz	49	2450MHz	69	2470MHz
10	2411MHz	30	2431MHz	50	2451MHz	70	2471MHz
11	2412MHz	31	2432MHz	51	2452MHz	71	2472MHz
12	2413MHz	32	2433MHz	52	2453MHz	72	2473MHz
13	2414MHz	33	2434MHz	53	2454MHz	73	2474MHz
14	2415MHz	34	2435MHz	54	2455MHz	74	2475MHz
15	2416MHz	35	2436MHz	55	2456MHz	75	2476MHz
16	2417MHz	36	2437MHz	56	2457MHz	76	2477MHz
17	2418MHz	37	2438MHz	57	2458MHz	77	2478MHz
18	2419MHz	38	2439MHz	58	2459MHz	78	2479MHz
19	2420MHz	39	2440MHz	59	2460MHz	79	2480MHz
20	2421MHz	40	2441MHz	60	2461MHz		

6.4 Description of Support Units

The EUT has been tested independently.

6.5 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd.

Hongwei Industrial Zone, Bao'an 70 District, Shenzhen, Guangdong, China 518101

Telephone: +86 (0) 755 33683668 Fax: +86 (0) 755 33683385

No tests were sub-contracted.

6.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L1910

Centre Testing International Group Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories..

A2LA-Lab Cert. No. 3061.01

Centre Testing International Group Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC-Registration No.: 886427

Centre Testing International Group Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Registration 886427.

IC-Registration No.: 7408A-2

The 3m Alternate Test Site of Centre Testing International Group Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 7408A-2 .

IC-Registration No.: 7408B-1

The 10m Alternate Test Site of Centre Testing International Group Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 7408B-1.

NEMKO-Aut. No.: ELA503

Centre Testing International Group Co., Ltd. has been assessed the quality assurance system, the testing facilities, qualifications and testing practices of the relevant parts of the organization. The quality assurance system of the Laboratory has been validated against ISO/IEC 17025 or equivalent. The laboratory also fulfils the conditions described in Nemko Document NLA-10.

VCCI

The Radiation 3 &10 meters site of Centre Testing International Group Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-4096.

Main Ports Conducted Interference Measurement of Centre Testing International Group Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: C-4563.

Telecommunication Ports Conducted Disturbance Measurement of Centre Testing International Group Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: T-2146.

The Radiation 3 meters site of Centre Testing International Group Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-758

6.7 Deviation from Standards

None.

6.8 Abnormalities from Standard Conditions

None.

6.9 Other Information Requested by the Customer

None.

6.10 Measurement Uncertainty (95% confidence levels, k=2)

No.	Item	Measurement Uncertainty
1	Radio Frequency	7.9×10^{-8}
2	RF power, conducted	0.31dB (30MHz-1GHz)
		0.57dB (1GHz-18GHz)
3	Radiated Spurious emission test	4.5dB (30MHz-1GHz)
		4.8dB (1GHz-12.75GHz)
4	Conduction emission	3.6dB (9kHz to 150kHz)
		3.2dB (150kHz to 30MHz)
5	Temperature test	0.64°C
6	Humidity test	2.8%
7	DC power voltages	0.025%

7 Equipment List

RF test system					
Equipment	Manufacturer	Model No.	Serial Number	Cal. Date (mm-dd-yyyy)	Cal. Due date (mm-dd-yyyy)
Signal Generator	Keysight	E8257D	MY53401106	04-01-2016	03-31-2017
Spectrum Analyzer	Keysight	N9010A	MY54510339	04-01-2016	03-31-2017
Signal Generator	Keysight	N5182B	MY53051549	04-01-2016	03-31-2017
High-pass filter	Sinoscite	FL3CX03WG18 NM12-0398-002	TTF20120439	01-11-2017	01-10-2018
High-pass filter	MICRO-TRONICS	SPA-F-63029-4	003	01-11-2017	01-10-2018
DC Power	Keysight	E3642A	MY54436035	04-01-2016	03-31-2017
BT&WI-FI Automatic control	R&S	OSP120	101374	04-01-2016	03-31-2017
RF control unit	JS Tonscend	JS0806-2	158060006	04-01-2016	03-31-2017

Conducted disturbance Test					
Equipment	Manufacturer	Model No.	Serial Number	Cal. date (mm-dd-yyyy)	Cal. Due date (mm-dd-yyyy)
Receiver	R&S	ESCI	100009	06-16-2016	06-15-2017
Temperature/ Humidity Indicator	TAYLOR	1451	1905	04-27-2016	04-26-2017
LISN	R&S	ENV216	100098	06-16-2016	06-15-2017
LISN	schwarzbeck	NNLK8121	8121-529	06-16-2016	06-15-2017
Current Probe	R&S	EZ17	100106	06-16-2016	06-15-2017
ISN	TESEQ GmbH	ISN T800	30297	02-23-2017	02-22-2018

3M Semi/full-anechoic Chamber					
Equipment	Manufacturer	Model No.	Serial Number	Cal. date (mm-dd-yyyy)	Cal. Due date (mm-dd-yyyy)
3M Chamber & Accessory Equipment	TDK	SAC-3	TTE20130797	06-05-2016	06-05-2019
TRILOG Broadband Antenna	SCHWARZBEC K	VULB9163	9163-484	05-23-2016	05-22-2017
Microwave Preamplifier	Agilent	8449B	3008A02425	02-16-2017	02-15-2018
Horn Antenna	ETS-LINDGREN	3117	00057407	07-20-2015	07-18-2018
Loop Antenna	ETS	6502	00071730	07-30-2015	07-28-2017
Microwave Preamplifier	A.H.SYSTEMS	PAP-1840-60	6041.6042	06-30-2015	06-28-2018
Horn Antenna	A.H.SYSTEMS	SAS-574 374	374	06-30-2015	06-28-2018
Spectrum Analyzer	R&S	FSP40	100416	06-16-2016	06-15-2017
Receiver	R&S	ESCI	100435	06-16-2016	06-15-2017
LISN	schwarzbeck	NNBM8125	81251547	06-16-2016	06-15-2017
LISN	schwarzbeck	NNBM8125	81251548	06-16-2016	06-15-2017
Signal Generator	Agilent	E4438C	MY45095744	04-01-2016	03-31-2017
Signal Generator	Keysight	E8257D	MY53401106	04-01-2016	03-31-2017
Temperature/ Humidity Indicator	TAYLOR	1451	1905	04-27-2016	04-26-2017
Cable line	Fulai(7M)	SF106	5219/6A	01-11-2017	01-10-2018
Cable line	Fulai(6M)	SF106	5220/6A	01-11-2017	01-10-2018
Cable line	Fulai(3M)	SF106	5216/6A	01-11-2017	01-10-2018
Cable line	Fulai(3M)	SF106	5217/6A	01-11-2017	01-10-2018
High-pass filter	Sinoscite	FL3CX03WG18 NM12-0398-002	TTF20120439	01-11-2017	01-10-2018
High-pass filter	MICRO-TRONICS	SPA-F-63029-4	003	01-11-2017	01-10-2018
band rejection filter	Sinoscite	FL5CX01CA09 CL12-0395-001	TTF20120434	01-11-2017	01-10-2018
band rejection filter	Sinoscite	FL5CX01CA08 CL12-0393-001	TTF20120435	01-11-2017	01-10-2018
band rejection filter	Sinoscite	FL5CX02CA04 CL12-0396-002	TTF20120436	01-11-2017	01-10-2018
band rejection filter	Sinoscite	FL5CX02CA03 CL12-0394-001	TTF20120437	01-11-2017	01-10-2018

8 Radio Technical Requirements Specification

Reference documents for testing:

No.	Identity	Document Title
1	FCC Part15C (2015)	Subpart C-Intentional Radiators
2	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices

Test Results List:


Test requirement	Test method	Test item	Verdict	Note
Part15C Section 15.247 (a)(1)	ANSI 63.10	20dB Occupied Bandwidth	PASS	Appendix A)
Part15C Section 15.247 (a)(1)	ANSI 63.10	Carrier Frequencies Separation	PASS	Appendix B)
Part15C Section 15.247 (a)(1)	ANSI 63.10	Dwell Time	PASS	Appendix C)
Part15C Section 15.247 (b)	ANSI 63.10	Hopping Channel Number	PASS	Appendix D)
Part15C Section 15.247 (b)(1)	ANSI 63.10	Conducted Peak Output Power	PASS	Appendix E)
Part15C Section 15.247(d)	ANSI 63.10	Band-edge for RF Conducted Emissions	PASS	Appendix F)
Part15C Section 15.247(d)	ANSI 63.10	RF Conducted Spurious Emissions	PASS	Appendix G)
Part15C Section 15.247 (a)(1)	ANSI 63.10	Pseudorandom Frequency Hopping Sequence	PASS	Appendix H)
Part15C Section 15.203/15.247 (c)	ANSI 63.10	Antenna Requirement	PASS	Appendix I)
Part15C Section 15.207	ANSI 63.10	AC Power Line Conducted Emission	PASS	Appendix J)
Part15C Section 15.205/15.209	ANSI 63.10	Restricted bands around fundamental frequency (Radiated) Emission)	PASS	Appendix K)
Part15C Section 15.205/15.209	ANSI 63.10	Radiated Spurious Emissions	PASS	Appendix L)




Appendix A): 20dB Occupied Bandwidth




Test Result

Mode	Channel.	20dB Bandwidth [MHz]	99% OBW [MHz]	Verdict	Remark
GFSK	LCH	1.029	0.91701	PASS	Peak detector
GFSK	MCH	1.029	0.91611	PASS	
GFSK	HCH	1.029	0.91225	PASS	
$\pi/4$ DQPSK	LCH	1.261	1.1845	PASS	
$\pi/4$ DQPSK	MCH	1.289	1.1832	PASS	
$\pi/4$ DQPSK	HCH	1.288	1.1799	PASS	
8DPSK	LCH	1.292	1.1785	PASS	
8DPSK	MCH	1.288	1.1765	PASS	
8DPSK	HCH	1.286	1.1792	PASS	

Test Graph



$\pi/4$DQPSK/LCH	 Center Freq 2.402000000 GHz Ref Offset 19.08 dB Ref 19.08 dBm Center 2.402 GHz #Res BW 30 kHz #VBW 100 kHz Span 3 MHz Sweep 3.2 ms Occupied Bandwidth 1.1845 MHz Total Power 9.04 dBm Transmit Freq Error 180 Hz OBW Power 99.00 % x dB Bandwidth 1.261 MHz x dB -20.00 dB
$\pi/4$DQPSK/MCH	 Center Freq 2.441000000 GHz Ref Offset 19.02 dB Ref 19.02 dBm Center 2.441 GHz #Res BW 30 kHz #VBW 100 kHz Span 3 MHz Sweep 3.2 ms Occupied Bandwidth 1.1832 MHz Total Power 9.64 dBm Transmit Freq Error -475 Hz OBW Power 99.00 % x dB Bandwidth 1.289 MHz x dB -20.00 dB
$\pi/4$DQPSK/HCH	 Center Freq 2.480000000 GHz Ref Offset 19.05 dB Ref 19.05 dBm Center 2.48 GHz #Res BW 30 kHz #VBW 100 kHz Span 3 MHz Sweep 3.2 ms Occupied Bandwidth 1.1799 MHz Total Power 9.55 dBm Transmit Freq Error -527 Hz OBW Power 99.00 % x dB Bandwidth 1.288 MHz x dB -20.00 dB

8DPSK/LCH	
8DPSK/MCH	
8DPSK/HCH	




Appendix B): Carrier Frequency Separation


Result Table

Mode	Channel.	Carrier Frequency Separation [MHz]	Verdict
GFSK	LCH	1.022	PASS
GFSK	MCH	0.996	PASS
GFSK	HCH	1.120	PASS
$\pi/4$ DQPSK	LCH	1.106	PASS
$\pi/4$ DQPSK	MCH	0.920	PASS
$\pi/4$ DQPSK	HCH	1.088	PASS
8DPSK	LCH	1.060	PASS
8DPSK	MCH	1.150	PASS
8DPSK	HCH	1.002	PASS

Test Graph



$\pi/4$DQPSK/LCH	
$\pi/4$DQPSK/MCH	
$\pi/4$DQPSK/HCH	




Appendix C): Dwell Time


Result Table


Mode	Packet	Channel	Burst Width [ms/hop/ch]	Total Hops[hop*ch]	Dwell Time[s]	Duty Cycle [%]	Verdict
GFSK	DH1	LCH	0.363534	320	0.116	0.64	PASS
GFSK	DH1	MCH	0.362266	320	0.116	0.64	PASS
GFSK	DH1	HCH	0.363533	320	0.116	0.64	PASS
GFSK	DH3	LCH	1.62007	160	0.259	0.89	PASS
GFSK	DH3	MCH	1.6188	160	0.259	0.89	PASS
GFSK	DH3	HCH	1.62007	160	0.259	0.89	PASS
GFSK	DH5	LCH	2.86774	106.7	0.306	0.93	PASS
GFSK	DH5	MCH	2.86647	106.7	0.306	0.93	PASS
GFSK	DH5	HCH	2.86774	106.7	0.306	0.93	PASS

Remark : All modes are tested, only the worst mode GFSK is reported.

Test Graph









Appendix D): Hopping Channel Number

Result Table

Mode	Channel.	Number of Hopping Channel	Verdict
GFSK	Hop	79	PASS
$\pi/4$ DQPSK	Hop	79	PASS
8DPSK	Hop	79	PASS

Test Graph







Appendix E): Conducted Peak Output Power


Result Table

Mode	Channel.	Maximum Peak Output Power [dBm]	Verdict
GFSK	LCH	2.308	PASS
GFSK	MCH	2.149	PASS
GFSK	HCH	1.831	PASS
$\pi/4$ DQPSK	LCH	3.478	PASS
$\pi/4$ DQPSK	MCH	3.260	PASS
$\pi/4$ DQPSK	HCH	3.234	PASS
8DPSK	LCH	3.677	PASS
8DPSK	MCH	3.478	PASS
8DPSK	HCH	3.391	PASS

Test Graph










Appendix F): Band-edge for RF Conducted Emissions




Result Table




Mode	Channel	Carrier Frequency [MHz]	Carrier Power [dBm]	Frequency Hopping	Max Spurious Level [dBm]	Limit [dBm]	Verdict
GFSK	LCH	2402	1.868	Off	-61.121	-18.13	PASS
			0.917	On	-53.971	-19.08	PASS
GFSK	HCH	2480	1.406	Off	-58.462	-18.59	PASS
			0.668	On	-54.408	-19.33	PASS
$\pi/4$ DQPSK	LCH	2402	1.720	Off	-61.087	-18.28	PASS
			-1.933	On	-56.519	-21.93	PASS
$\pi/4$ DQPSK	HCH	2480	1.236	Off	-59.073	-18.76	PASS
			-2.381	On	-56.012	-22.38	PASS
8DPSK	LCH	2402	1.587	Off	-59.738	-18.41	PASS
			-0.193	On	-56.827	-20.19	PASS
8DPSK	HCH	2480	1.019	Off	-59.543	-18.98	PASS
			-3.063	On	-54.851	-23.06	PASS


Test Graph

Graphs

GFSK/LCH/No Hop	 <table><tr><th>NR</th><th>MODE</th><th>TRC</th><th>SQL</th><th>F</th><th>FUNCTION</th><th>FUNCTION WIDTH</th><th>FUNCTION VALUE</th></tr><tr><td>1</td><td>N</td><td>1</td><td>f</td><td>2.4021800 GHz</td><td></td><td></td><td>-1.868 dBm</td></tr><tr><td>2</td><td>N</td><td>1</td><td>f</td><td>2.4000000 GHz</td><td></td><td></td><td>-49.601 dBm</td></tr><tr><td>3</td><td>N</td><td>1</td><td>f</td><td>2.3900000 GHz</td><td></td><td></td><td>-63.501 dBm</td></tr><tr><td>4</td><td>N</td><td>1</td><td>f</td><td>2.3857325 GHz</td><td></td><td></td><td>-61.121 dBm</td></tr></table>	NR	MODE	TRC	SQL	F	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE	1	N	1	f	2.4021800 GHz			-1.868 dBm	2	N	1	f	2.4000000 GHz			-49.601 dBm	3	N	1	f	2.3900000 GHz			-63.501 dBm	4	N	1	f	2.3857325 GHz			-61.121 dBm
NR	MODE	TRC	SQL	F	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE																																		
1	N	1	f	2.4021800 GHz			-1.868 dBm																																		
2	N	1	f	2.4000000 GHz			-49.601 dBm																																		
3	N	1	f	2.3900000 GHz			-63.501 dBm																																		
4	N	1	f	2.3857325 GHz			-61.121 dBm																																		
GFSK/LCH/Hop	 <table><tr><th>NR</th><th>MODE</th><th>TRC</th><th>SQL</th><th>F</th><th>FUNCTION</th><th>FUNCTION WIDTH</th><th>FUNCTION VALUE</th></tr><tr><td>1</td><td>N</td><td>1</td><td>f</td><td>2.4019050 GHz</td><td></td><td></td><td>0.917 dBm</td></tr><tr><td>2</td><td>N</td><td>1</td><td>f</td><td>2.4000000 GHz</td><td></td><td></td><td>-55.012 dBm</td></tr><tr><td>3</td><td>N</td><td>1</td><td>f</td><td>2.3900000 GHz</td><td></td><td></td><td>-54.585 dBm</td></tr><tr><td>4</td><td>N</td><td>1</td><td>f</td><td>2.3890075 GHz</td><td></td><td></td><td>-53.971 dBm</td></tr></table>	NR	MODE	TRC	SQL	F	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE	1	N	1	f	2.4019050 GHz			0.917 dBm	2	N	1	f	2.4000000 GHz			-55.012 dBm	3	N	1	f	2.3900000 GHz			-54.585 dBm	4	N	1	f	2.3890075 GHz			-53.971 dBm
NR	MODE	TRC	SQL	F	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE																																		
1	N	1	f	2.4019050 GHz			0.917 dBm																																		
2	N	1	f	2.4000000 GHz			-55.012 dBm																																		
3	N	1	f	2.3900000 GHz			-54.585 dBm																																		
4	N	1	f	2.3890075 GHz			-53.971 dBm																																		
GFSK/HCH/No Hop	 <table><tr><th>NR</th><th>MODE</th><th>TRC</th><th>SQL</th><th>F</th><th>FUNCTION</th><th>FUNCTION WIDTH</th><th>FUNCTION VALUE</th></tr><tr><td>1</td><td>N</td><td>1</td><td>f</td><td>2.479991 GHz</td><td></td><td></td><td>1.406 dBm</td></tr><tr><td>2</td><td>N</td><td>1</td><td>f</td><td>2.483500 GHz</td><td></td><td></td><td>-61.201 dBm</td></tr><tr><td>3</td><td>N</td><td>1</td><td>f</td><td>2.500000 GHz</td><td></td><td></td><td>-61.897 dBm</td></tr><tr><td>4</td><td>N</td><td>1</td><td>f</td><td>2.484328 GHz</td><td></td><td></td><td>-58.462 dBm</td></tr></table>	NR	MODE	TRC	SQL	F	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE	1	N	1	f	2.479991 GHz			1.406 dBm	2	N	1	f	2.483500 GHz			-61.201 dBm	3	N	1	f	2.500000 GHz			-61.897 dBm	4	N	1	f	2.484328 GHz			-58.462 dBm
NR	MODE	TRC	SQL	F	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE																																		
1	N	1	f	2.479991 GHz			1.406 dBm																																		
2	N	1	f	2.483500 GHz			-61.201 dBm																																		
3	N	1	f	2.500000 GHz			-61.897 dBm																																		
4	N	1	f	2.484328 GHz			-58.462 dBm																																		

GFSK/HCH/Hop	 <table><tr><th>MNR</th><th>MODE</th><th>TRC</th><th>SCN</th><th>X</th><th>Y</th><th>FUNCTION</th><th>FUNCTION WIDTH</th><th>FUNCTION VALUE</th></tr><tr><td>1</td><td>N</td><td>1</td><td>f</td><td>2.479 931 GHz</td><td>0.668 dBm</td><td></td><td></td><td></td></tr><tr><td>2</td><td>N</td><td>1</td><td>f</td><td>2.483 500 GHz</td><td>-61.135 dBm</td><td></td><td></td><td></td></tr><tr><td>3</td><td>N</td><td>1</td><td>f</td><td>2.500 000 GHz</td><td>-55.535 dBm</td><td></td><td></td><td></td></tr><tr><td>4</td><td>N</td><td>1</td><td>f</td><td>2.497 991 GHz</td><td>-54.408 dBm</td><td></td><td></td><td></td></tr></table>	MNR	MODE	TRC	SCN	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE	1	N	1	f	2.479 931 GHz	0.668 dBm				2	N	1	f	2.483 500 GHz	-61.135 dBm				3	N	1	f	2.500 000 GHz	-55.535 dBm				4	N	1	f	2.497 991 GHz	-54.408 dBm			
MNR	MODE	TRC	SCN	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE																																						
1	N	1	f	2.479 931 GHz	0.668 dBm																																									
2	N	1	f	2.483 500 GHz	-61.135 dBm																																									
3	N	1	f	2.500 000 GHz	-55.535 dBm																																									
4	N	1	f	2.497 991 GHz	-54.408 dBm																																									
$\pi/4$ DQPSK/LCH/ No Hop	 <table><tr><th>MNR</th><th>MODE</th><th>TRC</th><th>SCN</th><th>X</th><th>Y</th><th>FUNCTION</th><th>FUNCTION WIDTH</th><th>FUNCTION VALUE</th></tr><tr><td>1</td><td>N</td><td>1</td><td>f</td><td>2.402 177 GHz</td><td>1.720 dBm</td><td></td><td></td><td></td></tr><tr><td>2</td><td>N</td><td>1</td><td>f</td><td>2.400 000 GHz</td><td>-54.652 dBm</td><td></td><td></td><td></td></tr><tr><td>3</td><td>N</td><td>1</td><td>f</td><td>2.380 000 GHz</td><td>-52.852 dBm</td><td></td><td></td><td></td></tr><tr><td>4</td><td>N</td><td>1</td><td>f</td><td>2.389 240 GHz</td><td>-51.087 dBm</td><td></td><td></td><td></td></tr></table>	MNR	MODE	TRC	SCN	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE	1	N	1	f	2.402 177 GHz	1.720 dBm				2	N	1	f	2.400 000 GHz	-54.652 dBm				3	N	1	f	2.380 000 GHz	-52.852 dBm				4	N	1	f	2.389 240 GHz	-51.087 dBm			
MNR	MODE	TRC	SCN	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE																																						
1	N	1	f	2.402 177 GHz	1.720 dBm																																									
2	N	1	f	2.400 000 GHz	-54.652 dBm																																									
3	N	1	f	2.380 000 GHz	-52.852 dBm																																									
4	N	1	f	2.389 240 GHz	-51.087 dBm																																									
$\pi/4$ DQPSK/LCH/ Hop	 <table><tr><th>MNR</th><th>MODE</th><th>TRC</th><th>SCN</th><th>X</th><th>Y</th><th>FUNCTION</th><th>FUNCTION WIDTH</th><th>FUNCTION VALUE</th></tr><tr><td>1</td><td>N</td><td>1</td><td>f</td><td>2.402 010 GHz</td><td>-1.933 dBm</td><td></td><td></td><td></td></tr><tr><td>2</td><td>N</td><td>1</td><td>f</td><td>2.400 000 GHz</td><td>-55.680 dBm</td><td></td><td></td><td></td></tr><tr><td>3</td><td>N</td><td>1</td><td>f</td><td>2.380 000 GHz</td><td>-59.716 dBm</td><td></td><td></td><td></td></tr><tr><td>4</td><td>N</td><td>1</td><td>f</td><td>2.388 832 GHz</td><td>-56.519 dBm</td><td></td><td></td><td></td></tr></table>	MNR	MODE	TRC	SCN	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE	1	N	1	f	2.402 010 GHz	-1.933 dBm				2	N	1	f	2.400 000 GHz	-55.680 dBm				3	N	1	f	2.380 000 GHz	-59.716 dBm				4	N	1	f	2.388 832 GHz	-56.519 dBm			
MNR	MODE	TRC	SCN	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE																																						
1	N	1	f	2.402 010 GHz	-1.933 dBm																																									
2	N	1	f	2.400 000 GHz	-55.680 dBm																																									
3	N	1	f	2.380 000 GHz	-59.716 dBm																																									
4	N	1	f	2.388 832 GHz	-56.519 dBm																																									

$\pi/4$ DQPSK/HCH/ No Hop	 <table><tr><th>MNR</th><th>MODE</th><th>TRF</th><th>SCL</th><th>X</th><th>Y</th><th>FUNCTION</th><th>FUNCTION WIDTH</th><th>FUNCTION VALUE</th></tr><tr><td>1</td><td>N</td><td>1</td><td>f</td><td>2.480178 GHz</td><td>-2.336 dBm</td><td></td><td></td><td></td></tr><tr><td>2</td><td>N</td><td>1</td><td>f</td><td>2.483500 GHz</td><td>-58.861 dBm</td><td></td><td></td><td></td></tr><tr><td>3</td><td>N</td><td>1</td><td>f</td><td>2.500000 GHz</td><td>-53.473 dBm</td><td></td><td></td><td></td></tr><tr><td>4</td><td>N</td><td>1</td><td>f</td><td>2.483503 GHz</td><td>-59.073 dBm</td><td></td><td></td><td></td></tr></table>	MNR	MODE	TRF	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE	1	N	1	f	2.480178 GHz	-2.336 dBm				2	N	1	f	2.483500 GHz	-58.861 dBm				3	N	1	f	2.500000 GHz	-53.473 dBm				4	N	1	f	2.483503 GHz	-59.073 dBm			
MNR	MODE	TRF	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE																																						
1	N	1	f	2.480178 GHz	-2.336 dBm																																									
2	N	1	f	2.483500 GHz	-58.861 dBm																																									
3	N	1	f	2.500000 GHz	-53.473 dBm																																									
4	N	1	f	2.483503 GHz	-59.073 dBm																																									
$\pi/4$ DQPSK/HCH/ Hop	 <table><tr><th>MNR</th><th>MODE</th><th>TRF</th><th>SCL</th><th>X</th><th>Y</th><th>FUNCTION</th><th>FUNCTION WIDTH</th><th>FUNCTION VALUE</th></tr><tr><td>1</td><td>N</td><td>1</td><td>f</td><td>2.480013 GHz</td><td>-2.381 dBm</td><td></td><td></td><td></td></tr><tr><td>2</td><td>N</td><td>1</td><td>f</td><td>2.483500 GHz</td><td>-59.855 dBm</td><td></td><td></td><td></td></tr><tr><td>3</td><td>N</td><td>1</td><td>f</td><td>2.490201 GHz</td><td>-56.012 dBm</td><td></td><td></td><td></td></tr></table>	MNR	MODE	TRF	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE	1	N	1	f	2.480013 GHz	-2.381 dBm				2	N	1	f	2.483500 GHz	-59.855 dBm				3	N	1	f	2.490201 GHz	-56.012 dBm												
MNR	MODE	TRF	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE																																						
1	N	1	f	2.480013 GHz	-2.381 dBm																																									
2	N	1	f	2.483500 GHz	-59.855 dBm																																									
3	N	1	f	2.490201 GHz	-56.012 dBm																																									
8DPSK/LCH/No Hop	 <table><tr><th>MNR</th><th>MODE</th><th>TRF</th><th>SCL</th><th>X</th><th>Y</th><th>FUNCTION</th><th>FUNCTION WIDTH</th><th>FUNCTION VALUE</th></tr><tr><td>1</td><td>N</td><td>1</td><td>f</td><td>2.402175 GHz</td><td>-1.587 dBm</td><td></td><td></td><td></td></tr><tr><td>2</td><td>N</td><td>1</td><td>f</td><td>2.400000 GHz</td><td>-50.481 dBm</td><td></td><td></td><td></td></tr><tr><td>3</td><td>N</td><td>1</td><td>f</td><td>2.390000 GHz</td><td>-82.284 dBm</td><td></td><td></td><td></td></tr><tr><td>4</td><td>N</td><td>1</td><td>f</td><td>2.387575 GHz</td><td>-59.738 dBm</td><td></td><td></td><td></td></tr></table>	MNR	MODE	TRF	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE	1	N	1	f	2.402175 GHz	-1.587 dBm				2	N	1	f	2.400000 GHz	-50.481 dBm				3	N	1	f	2.390000 GHz	-82.284 dBm				4	N	1	f	2.387575 GHz	-59.738 dBm			
MNR	MODE	TRF	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE																																						
1	N	1	f	2.402175 GHz	-1.587 dBm																																									
2	N	1	f	2.400000 GHz	-50.481 dBm																																									
3	N	1	f	2.390000 GHz	-82.284 dBm																																									
4	N	1	f	2.387575 GHz	-59.738 dBm																																									






Appendix G): RF Conducted Spurious Emissions



Result Table



Mode	Channel	Pref [dBm]	Puw[dBm]	Verdict
GFSK	LCH	1.164	<Limit	PASS
GFSK	MCH	1.475	<Limit	PASS
GFSK	HCH	1.245	<Limit	PASS
$\pi/4$ DQPSK	LCH	1.696	<Limit	PASS
$\pi/4$ DQPSK	MCH	1.418	<Limit	PASS
$\pi/4$ DQPSK	HCH	0.859	<Limit	PASS
8DPSK	LCH	1.566	<Limit	PASS
8DPSK	MCH	1.213	<Limit	PASS
8DPSK	HCH	1.029	<Limit	PASS



Test Graph


















Appendix H): Pseudorandom Frequency Hopping Sequence

Test Requirement:

47 CFR Part 15C Section 15.247 (a)(1) requirement:


Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

Alternatively, Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

EUT Pseudorandom Frequency Hopping Sequence


The pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONES; i.e. the shift register is initialized with nine ones.

- Number of shift register stages: 9
- Length of pseudo-random sequence: $2^9 - 1 = 511$ bits
- Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence

An example of Pseudorandom Frequency Hopping Sequence as follow:



Each frequency used equally on the average by each transmitter.

The system receivers have input bandwidths that match the hopping channel bandwidths of their Corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

The device does not have the ability to be coordinated with other FHSS systems in an effort to avoid the simultaneous occupancy of individual hopping frequencies by multiple transmitters.

Appendix I): Antenna Requirement

15.203 requirement:


An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:

The antenna is PIFA Antenna and no consideration of replacement. The best case gain of the antenna is 3.74dBi.



Appendix J): AC Power Line Conducted Emission

Test Procedure:	Test frequency range :150KHz-30MHz 1)The mains terminal disturbance voltage test was conducted in a shielded room. 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50Ω/50μH + 5Ω linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded. 3)The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane, 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2. 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.														
Limit:	<table><tr><th rowspan="2">Frequency range (MHz)</th><th colspan="2">Limit (dBμV)</th></tr><tr><th>Quasi-peak</th><th>Average</th></tr><tr><td>0.15-0.5</td><td>66 to 56*</td><td>56 to 46*</td></tr><tr><td>0.5-5</td><td>56</td><td>46</td></tr><tr><td>5-30</td><td>60</td><td>50</td></tr></table> * The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz. NOTE : The lower limit is applicable at the transition frequency	Frequency range (MHz)	Limit (dBμV)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
Frequency range (MHz)	Limit (dBμV)														
	Quasi-peak	Average													
0.15-0.5	66 to 56*	56 to 46*													
0.5-5	56	46													
5-30	60	50													


Measurement Data

An initial pre-scan was performed on the live and neutral lines with peak detector.

Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.

Live line:


80.0 dBuV



No.	Freq. MHz	Reading_Level (dBuV)			Correct Factor dB	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment
		Peak	QP	AVG		peak	QP	AVG	QP	AVG	QP	AVG		
1	0.1580	37.41	32.03	13.51	9.76	47.17	41.79	23.27	65.56	55.56	-23.77	-32.29	P	
2	0.5380	31.39	26.34	21.63	9.73	41.12	36.07	31.36	56.00	46.00	-19.93	-14.64	P	
3	0.9340	19.11	14.72	8.59	9.71	28.82	24.43	18.30	56.00	46.00	-31.57	-27.70	P	
4	3.1260	18.23	13.38	5.97	9.68	27.91	23.06	15.65	56.00	46.00	-32.94	-30.35	P	
5	12.7140	16.85	9.87	3.11	9.96	26.81	19.83	13.07	60.00	50.00	-40.17	-36.93	P	
6	29.6140	10.33	5.31	0.47	10.20	20.53	15.51	10.67	60.00	50.00	-44.49	-39.33	P	

Neutral line:

80.0 dBuV



No.	Freq. MHz	Reading_Level (dBuV)			Correct Factor dB	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment
		Peak	QP	AVG		peak	QP	AVG	QP	AVG	QP	AVG		
1	0.5420	30.75	25.14	20.82	9.73	40.48	34.87	30.55	56.00	46.00	-21.13	-15.45	P	
2	0.9220	19.24	14.38	3.57	9.72	28.96	24.10	13.29	56.00	46.00	-31.90	-32.71	P	
3	1.7060	18.26	13.67	5.98	9.69	27.95	23.36	15.67	56.00	46.00	-32.64	-30.33	P	
4	11.8660	38.65	9.45	-4.74	9.93	48.58	19.38	5.19	60.00	50.00	-40.62	-44.81	P	
5	11.8660	16.51	9.41	3.60	9.93	26.44	19.34	13.53	60.00	50.00	-40.66	-36.47	P	
6	23.9540	17.25	12.11	5.47	10.18	27.43	22.29	15.65	60.00	50.00	-37.71	-34.35	P	

Notes:


1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.

Appendix K): Restricted bands around fundamental frequency (Radiated)

Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	30MHz-1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average
Test Procedure:	Below 1GHz test procedure as below: - The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. - The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. - The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. - For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. - The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. - Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel Above 1GHz test procedure as below: - Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 meter to 1.5 meter(Above 18GHz the distance is 1 meter and table is 1.5 meter). b. Test the EUT in the lowest channel , the Highest channel - The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is worse case. - Repeat above procedures until all frequencies measured was complete.				
Limit:	Frequency	Limit (dBμV/m @3m)		Remark	
	30MHz-88MHz	40.0		Quasi-peak Value	
	88MHz-216MHz	43.5		Quasi-peak Value	
	216MHz-960MHz	46.0		Quasi-peak Value	
	960MHz-1GHz	54.0		Quasi-peak Value	
	Above 1GHz	54.0		Average Value	
		74.0		Peak Value	


Test plot as follows:

Worse case mode:	GFSK(1-DH5)		
Frequency: 2390.0MHz	Test channel: Lowest	Polarization: Horizontal	Remark: Peak




	Ant Freq	Cable Factor	Preamp Loss	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB		
1	2390.000	32.53	4.28	44.03	49.25	42.03	74.00	-31.97	Horizontal	
2 pp	2401.796	32.56	4.31	44.04	86.42	79.25	74.00	5.25	Horizontal	

Worse case mode:	GFSK(1-DH5)		
Frequency: 2390.0MHz	Test channel: Lowest	Polarization: Vertical	Remark: Peak




	Ant Freq	Cable Factor	Preamp Loss	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB		
1	2390.000	32.53	4.28	44.03	49.65	42.43	74.00	-31.57	Vertical	
2 pp	2401.796	32.56	4.31	44.04	80.37	73.20	74.00	-0.80	Vertical	

Worse case mode:	GFSK(1-DH5)		
Frequency: 2483.5MHz	Test channel: Highest	Polarization: Horizontal	Remark: Peak




	Ant Freq	Cable Factor	Preamp Loss	Factor	Read Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB	
1 pp	2479.797	32.71	4.50	44.14	84.44	77.51	74.00	3.51	Horizontal
2	2483.500	32.71	4.51	44.14	49.85	42.93	74.00	-31.07	Horizontal

Worse case mode:	GFSK(1-DH5)		
Frequency: 2483.5MHz	Test channel: Highest	Polarization: Vertical	Remark: Peak




	Ant Freq	Cable Factor	Preamp Loss	Factor	Read Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB	
1 pp	2479.819	32.71	4.50	44.14	78.11	71.18	74.00	-2.82	Vertical
2	2483.500	32.71	4.51	44.14	49.10	42.18	74.00	-31.82	Vertical

Worse case mode:	$\pi/4$ DQPSK(2-DH5)		
Frequency: 2390.0MHz	Test channel: Lowest	Polarization: Horizontal	Remark: Peak




	Ant Freq	Cable Factor	Preamp Loss	Read Level	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2390.000	32.53	4.28	44.03	48.90	41.68	74.00	-32.32	Horizontal
2 pp	2401.796	32.56	4.31	44.04	85.64	78.47	74.00	4.47	Horizontal

Worse case mode:	$\pi/4$ DQPSK(2-DH5)		
Frequency: 2390.0MHz	Test channel: Lowest	Polarization: Vertical	Remark: Peak




	Ant Freq	Cable Factor	Preamp Loss	Read Level	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2390.000	32.53	4.28	44.03	49.05	41.83	74.00	-32.17	Vertical
2 pp	2401.891	32.56	4.31	44.04	81.53	74.36	74.00	0.36	Vertical

Worse case mode:	$\pi/4$ DQPSK(2-DH5)		
Frequency: 2483.5MHz	Test channel: Highest	Polarization: Horizontal	Remark: Peak




	Ant Freq	Cable Factor	Preamp Loss	Read Level	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB	
1 pp	2479.797	32.71	4.50	44.14	85.86	78.93	74.00	4.93	Horizontal
2	2483.500	32.71	4.51	44.14	48.65	41.73	74.00	-32.27	Horizontal

Worse case mode:	$\pi/4$ DQPSK(2-DH5)		
Frequency: 2483.5MHz	Test channel: Highest	Polarization: Vertical	Remark: Peak




	Ant Freq	Cable Factor	Preamp Loss	Read Level	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB	
1 pp	2479.797	32.71	4.50	44.14	77.88	70.95	74.00	-3.05	Vertical
2	2483.500	32.71	4.51	44.14	49.18	42.26	74.00	-31.74	Vertical

Worse case mode:	8DPSK(3-DH5)		
Frequency: 2390.0MHz	Test channel: Lowest	Polarization: Horizontal	Remark: Peak




	Ant Freq	Cable Factor	Preamp Loss	Read Level	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2390.000	32.53	4.28	44.03	49.06	41.84	74.00	-32.16	Horizontal
2 pp	2401.891	32.56	4.31	44.04	86.47	79.30	74.00	5.30	Horizontal

Worse case mode:	8DPSK(3-DH5)		
Frequency: 2390.0MHz	Test channel: Lowest	Polarization: Vertical	Remark: Peak




	Ant Freq	Cable Factor	Preamp Loss	Read Level	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2390.000	32.53	4.28	44.03	49.37	42.15	74.00	-31.85	Vertical
2 pp	2401.987	32.56	4.31	44.04	80.44	73.27	74.00	-0.73	Vertical

Worse case mode:	8DPSK(3-DH5)		
Frequency: 2483.5MHz	Test channel: Highest	Polarization: Horizontal	Remark: Peak



		Ant Freq	Cable Factor	Preamp Loss	Read Level	Level	Limit Line	Over Limit	Pol/Phase	Remark
		MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB	
1	pp	2479.994	32.71	4.50	44.14	85.47	78.54	74.00	4.54	Horizontal
2		2483.500	32.71	4.51	44.14	49.70	42.78	74.00	-31.22	Horizontal

Worse case mode:	8DPSK(3-DH5)		
Frequency: 2483.5MHz	Test channel: Highest	Polarization: Vertical	Remark: Peak



		Ant Freq	Cable Factor	Preamp Loss	Read Level	Level	Limit Line	Over Limit	Pol/Phase	Remark
		MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB	
1	pp	2479.950	32.71	4.50	44.14	78.70	71.77	74.00	-2.23	Vertical
2		2483.500	32.71	4.51	44.14	48.26	41.34	74.00	-32.66	Vertical

Note:

1) Through Pre-scan transmitter mode with all kind of modulation and all kind of data type, find the 1-DH5 of data type is the worse case of GFSK modulation type, the 2-DH5 of data type is the worse case of $\pi/4$ DQPSK modulation type, the 3-DH5 of data type is the worse case of 8DPSK modulation type in charge + transmitter mode.

2) As shown in this section, the field strength limits are based on average limits. However, the peak field

strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak values are measured.

3) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading - Correct Factor

Correct Factor = Preamplifier Factor - Antenna Factor - Cable Factor


Appendix L): Radiated Spurious Emissions

Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
	0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
	0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average
Test Procedure:					
Below 1GHz test procedure as below:					
a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.					
Above 1GHz test procedure as below:					
g. Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 meter to 1.5 meter(Above 18GHz the distance is 1 meter and table is 1.5 meter). h. Test the EUT in the lowest channel ,the middle channel ,the Highest channel i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is worse case. j. Repeat above procedures until all frequencies measured was complete.					
Limit:	Frequency	Field strength (microvolt/meter)	Limit (dBµV/m)	Remark	Measurement distance (m)
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz-88MHz	100	40.0	Quasi-peak	3
	88MHz-216MHz	150	43.5	Quasi-peak	3
	216MHz-960MHz	200	46.0	Quasi-peak	3
	960MHz-1GHz	500	54.0	Quasi-peak	3
	Above 1GHz	500	54.0	Average	3
	Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.				

Radiated Spurious Emissions test Data: **Radiated Emission below 1GHz**


30MHz~1GHz (QP)

Test mode:	Transmitting	Horizontal
------------	--------------	------------



	Ant Freq	Cable Factor	Read Loss	Level Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	47.659	14.91	1.21	10.23	26.35	40.00	-13.65	Horizontal QP
2	71.080	10.19	1.46	12.99	24.64	40.00	-15.36	Horizontal QP
3	136.460	10.52	1.58	21.63	33.73	43.50	-9.77	Horizontal QP
4 pp	211.527	11.80	2.25	24.20	38.25	43.50	-5.25	Horizontal QP
5	364.260	15.25	2.74	21.32	39.31	46.00	-6.69	Horizontal QP
6	719.200	20.82	3.94	9.32	34.08	46.00	-11.92	Horizontal QP

Test mode:	Transmitting	Vertical
------------	--------------	----------



	Ant Freq	Cable Factor	Loss	Read Level	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		
1	47.659	14.91	1.21	14.01	30.13	40.00	-9.87	Vertical	QP
2 pp	65.343	11.92	1.44	21.43	34.79	40.00	-5.21	Vertical	QP
3	143.830	10.06	1.58	23.24	34.88	43.50	-8.62	Vertical	QP
4	214.514	11.85	2.25	23.17	37.27	43.50	-6.23	Vertical	QP
5	408.946	16.45	2.84	15.32	34.61	46.00	-11.39	Vertical	QP
6	721.726	20.83	3.94	13.21	37.98	46.00	-8.02	Vertical	QP

Transmitter Emission above 1GHz

Worse case mode:		GFSK(1-DH5)		Test channel:		Lowest	Remark: Peak		
Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Gain (dB)	Read Level (dBμV)	Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Result	Antenna Polaxis
1162.051	30.13	2.47	44.44	56.01	44.17	74.00	-29.83	Pass	H
3728.625	33.00	5.48	44.62	49.91	43.77	74.00	-30.23	Pass	H
4804.000	34.69	5.11	44.60	47.10	42.30	74.00	-31.70	Pass	H
5806.408	35.76	7.00	44.52	48.84	47.08	74.00	-26.92	Pass	H
7206.000	36.42	6.66	44.77	47.19	45.50	74.00	-28.50	Pass	H
9608.000	37.88	7.73	45.58	47.52	47.55	74.00	-26.45	Pass	H
1162.051	30.13	2.47	44.44	60.22	48.38	74.00	-25.62	Pass	V
3241.498	33.38	5.57	44.67	54.59	48.87	74.00	-25.13	Pass	V
4804.000	34.69	5.11	44.60	47.51	42.71	74.00	-31.29	Pass	V
5821.207	35.77	7.03	44.52	49.38	47.66	74.00	-26.34	Pass	V
7206.000	36.42	6.66	44.77	47.15	45.46	74.00	-28.54	Pass	V
9608.000	37.88	7.73	45.58	47.77	47.80	74.00	-26.20	Pass	V

Worse case mode:		GFSK(1-DH5)		Test channel:		Middle	Remark: Peak		
Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Gain (dB)	Read Level (dBμV)	Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Result	Antenna Polaxis
1198.095	30.22	2.51	44.39	53.16	41.50	74.00	-32.50	Pass	H
1759.638	31.33	3.05	43.72	56.56	47.22	74.00	-26.78	Pass	H
4882.000	34.85	5.08	44.60	46.85	42.18	74.00	-31.82	Pass	H
5986.509	35.89	7.40	44.50	48.80	47.59	74.00	-26.41	Pass	H
7323.000	36.43	6.77	44.87	47.35	45.68	74.00	-28.32	Pass	H
9764.000	38.05	7.60	45.55	47.75	47.85	74.00	-26.15	Pass	H
1201.149	30.23	2.52	44.38	56.61	44.98	74.00	-29.02	Pass	V
1904.119	31.56	3.16	43.59	59.26	50.39	74.00	-23.61	Pass	V
4882.000	34.85	5.08	44.60	47.34	42.67	74.00	-31.33	Pass	V
6412.427	36.12	7.02	44.54	48.96	47.56	74.00	-26.44	Pass	V
7323.000	36.43	6.77	44.87	48.99	47.32	74.00	-26.68	Pass	V
9764.000	38.05	7.60	45.55	48.74	48.84	74.00	-25.16	Pass	V

Worse case mode:		GFSK(1-DH5)		Test channel:		Highest	Remark: Peak		
Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Gain (dB)	Read Level (dBμV)	Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Result	Antenna Polaxis
1198.095	30.22	2.51	44.39	54.33	42.67	74.00	-31.33	Pass	H
1908.972	31.57	3.16	43.58	55.57	46.72	74.00	-27.28	Pass	H
4960.000	35.02	5.05	44.60	46.37	41.84	74.00	-32.16	Pass	H
6511.117	36.17	6.92	44.55	48.68	47.22	74.00	-26.78	Pass	H
7440.000	36.45	6.88	44.97	47.12	45.48	74.00	-28.52	Pass	H
9920.000	38.22	7.47	45.52	47.13	47.30	74.00	-26.70	Pass	H
1326.513	30.52	2.66	44.21	54.72	43.69	74.00	-30.31	Pass	V
3402.126	33.25	5.54	44.66	53.75	47.88	74.00	-26.12	Pass	V
4960.000	35.02	5.05	44.60	46.45	41.92	74.00	-32.08	Pass	V
6379.864	36.10	7.05	44.54	48.88	47.49	74.00	-26.51	Pass	V
7440.000	36.45	6.88	44.97	47.73	46.09	74.00	-27.91	Pass	V
9920.000	38.22	7.47	45.52	47.83	48.00	74.00	-26.00	Pass	V

Worse case mode:		π/4DQPSK(2-DH5)		Test channel:		Lowest	Remark: Peak		
Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Gain (dB)	Read Level (dBμV)	Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Result	Antenna Polaxis
1162.051	30.13	2.47	44.44	52.44	40.60	74.00	-33.40	Pass	H
1668.044	31.18	2.98	43.81	54.11	44.46	74.00	-29.54	Pass	H
4804.000	34.69	5.11	44.60	47.18	42.38	74.00	-31.62	Pass	H
5850.919	35.79	7.10	44.51	49.08	47.46	74.00	-26.54	Pass	H
7206.000	36.42	6.66	44.77	46.98	45.29	74.00	-28.71	Pass	H
9608.000	37.88	7.73	45.58	47.60	47.63	74.00	-26.37	Pass	H
1162.051	30.13	2.47	44.44	58.44	46.60	74.00	-27.40	Pass	V
1329.894	30.52	2.66	44.21	57.29	46.26	74.00	-27.74	Pass	V
4804.000	34.69	5.11	44.60	47.33	42.53	74.00	-31.47	Pass	V
6094.137	35.95	7.33	44.51	49.09	47.86	74.00	-26.14	Pass	V
7206.000	36.42	6.66	44.77	46.87	45.18	74.00	-28.82	Pass	V
9608.000	37.88	7.73	45.58	47.58	47.61	74.00	-26.39	Pass	V

Worse case mode:		$\pi/4$ DQPSK(2-DH5)		Test channel:		Middle	Remark: Peak		
Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Gain (dB)	Read Level (dB μ V)	Level (dB μ V/m)	Limit Line (dB μ V/m)	Over Limit (dB)	Result	Antenna Polaxis
1201.149	30.23	2.52	44.38	51.36	39.73	74.00	-34.27	Pass	H
1668.044	31.18	2.98	43.81	52.27	42.62	74.00	-31.38	Pass	H
3795.660	32.95	5.47	44.62	49.16	42.96	74.00	-31.04	Pass	H
4882.000	34.85	5.08	44.60	45.28	40.61	74.00	-33.39	Pass	H
7323.000	36.43	6.77	44.87	45.81	44.14	74.00	-29.86	Pass	H
9764.000	38.05	7.60	45.55	47.42	47.52	74.00	-26.48	Pass	H
1162.051	30.13	2.47	44.44	56.94	45.10	74.00	-28.90	Pass	V
1329.894	30.52	2.66	44.21	56.95	45.92	74.00	-28.08	Pass	V
4882.000	34.85	5.08	44.60	46.74	42.07	74.00	-31.93	Pass	V
5836.044	35.78	7.07	44.52	49.34	47.67	74.00	-26.33	Pass	V
7323.000	36.43	6.77	44.87	47.84	46.17	74.00	-27.83	Pass	V
9764.000	38.05	7.60	45.55	47.77	47.87	74.00	-26.13	Pass	V

Worse case mode:		$\pi/4$ DQPSK(2-DH5)		Test channel:		Highest	Remark: Peak		
Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Gain (dB)	Read Level (dB μ V)	Level (dB μ V/m)	Limit Line (dB μ V/m)	Over Limit (dB)	Result	Antenna Polaxis
1198.095	30.22	2.51	44.39	53.68	42.02	74.00	-31.98	Pass	H
1668.044	31.18	2.98	43.81	53.54	43.89	74.00	-30.11	Pass	H
1908.972	31.57	3.16	43.58	56.64	47.79	74.00	-26.21	Pass	H
4960.000	35.02	5.05	44.60	47.39	42.86	74.00	-31.14	Pass	H
7440.000	36.45	6.88	44.97	47.60	45.96	74.00	-28.04	Pass	H
9920.000	38.22	7.47	45.52	47.60	47.77	74.00	-26.23	Pass	H
1093.183	29.96	2.38	44.55	51.23	39.02	74.00	-34.98	Pass	V
1439.09	30.75	2.77	44.07	51.73	41.18	74.00	-32.82	Pass	V
4096.875	33.05	5.40	44.60	47.49	41.34	74.00	-32.66	Pass	V
4960.000	35.02	5.05	44.60	45.68	41.15	74.00	-32.85	Pass	V
7440.000	36.45	6.88	44.97	46.60	44.96	74.00	-29.04	Pass	V
9920.000	38.22	7.47	45.52	47.60	47.77	74.00	-26.23	Pass	V

Worse case mode:		8DPSK(3-DH5)		Test channel:		Lowest	Remark: Peak		
Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Gain (dB)	Read Level (dBμV)	Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Result	Antenna Polaxis
1162.051	30.13	2.47	44.44	53.51	41.67	74.00	-32.33	Pass	H
1668.044	31.18	2.98	43.81	53.34	43.69	74.00	-30.31	Pass	H
4804.000	34.69	5.11	44.60	46.97	42.17	74.00	-31.83	Pass	H
5791.646	35.74	6.97	44.52	49.07	47.26	74.00	-26.74	Pass	H
7206.000	36.42	6.66	44.77	46.78	45.09	74.00	-28.91	Pass	H
9608.000	37.88	7.73	45.58	49.33	49.36	74.00	-24.64	Pass	H
1162.051	30.13	2.47	44.44	57.30	45.46	74.00	-28.54	Pass	V
4086.459	33.02	5.40	44.60	49.24	43.06	74.00	-30.94	Pass	V
4804.000	34.69	5.11	44.60	47.65	42.85	74.00	-31.15	Pass	V
5821.207	35.77	7.03	44.52	49.07	47.35	74.00	-26.65	Pass	V
7206.000	36.42	6.66	44.77	46.74	45.05	74.00	-28.95	Pass	V
9608.000	37.88	7.73	45.58	47.91	47.94	74.00	-26.06	Pass	V

Worse case mode:		8DPSK(3-DH5)		Test channel:		Middle	Remark: Peak		
Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Gain (dB)	Read Level (dBμV)	Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Result	Antenna Polaxis
1198.095	30.22	2.51	44.39	53.21	41.55	74.00	-32.45	Pass	H
1668.044	31.18	2.98	43.81	54.46	44.81	74.00	-29.19	Pass	H
4882.000	34.85	5.08	44.60	46.51	41.84	74.00	-32.16	Pass	H
5747.586	35.71	6.87	44.52	49.18	47.24	74.00	-26.76	Pass	H
7323.000	36.43	6.77	44.87	47.89	46.22	74.00	-27.78	Pass	H
9764.000	38.05	7.60	45.55	48.33	48.43	74.00	-25.57	Pass	H
1162.051	30.13	2.47	44.44	59.71	47.87	74.00	-26.13	Pass	V
1529.749	30.93	2.85	43.96	52.69	42.51	74.00	-31.49	Pass	V
4882.000	34.85	5.08	44.60	46.77	42.10	74.00	-31.90	Pass	V
5971.290	35.88	7.37	44.50	49.07	47.82	74.00	-26.18	Pass	V
7323.000	36.43	6.77	44.87	47.33	45.66	74.00	-28.34	Pass	V
9764.000	38.05	7.60	45.55	48.45	48.55	74.00	-25.45	Pass	V

Worse case mode:		8DPSK(3-DH5)		Test channel:		Highest	Remark: Peak		
Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Gain (dB)	Read Level (dBμV)	Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Result	Antenna Polaxis
1198.095	30.22	2.51	44.39	52.91	41.25	74.00	-32.75	Pass	H
1741.812	31.30	3.04	43.74	53.17	43.77	74.00	-30.23	Pass	H
4960.000	35.02	5.05	44.60	46.14	41.61	74.00	-32.39	Pass	H
6577.752	36.20	6.86	44.56	49.53	48.03	74.00	-25.97	Pass	H
7440.000	36.45	6.88	44.97	47.55	45.91	74.00	-28.09	Pass	H
9920.000	38.22	7.47	45.52	48.08	48.25	74.00	-25.75	Pass	H
1159.096	30.13	2.47	44.44	58.26	46.42	74.00	-27.58	Pass	V
1823.477	31.43	3.10	43.66	56.59	47.46	74.00	-26.54	Pass	V
4960.000	35.02	5.05	44.60	46.37	41.84	74.00	-32.16	Pass	V
6396.125	36.11	7.03	44.54	49.05	47.65	74.00	-26.35	Pass	V
7440.000	36.45	6.88	44.97	47.38	45.74	74.00	-28.26	Pass	V
9920.000	38.22	7.47	45.52	47.33	47.50	74.00	-26.50	Pass	V

Note:

1) Through Pre-scan transmitter mode with all kind of modulation and all kind of data type, find the 1-DH5 of data type is the worse case of GFSK modulation type, the 2-DH5 of data type is the worse case of $\pi/4$ DQPSK modulation type, the 3-DH5 of data type is the worse case of 8DPSK modulation type in transmitter mode.

2) As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak values are measured.

3) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading - Correct Factor

Correct Factor = Preamplifier Factor - Antenna Factor - Cable Factor

4) Scan from 9kHz to 25GHz, the disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.

*** End of Report ***

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CTI, this report can't be reproduced except in full.