



MPE ESTIMATION

**Test report
On Behalf of
Control Technology China Co., LTD
For
Diagnose charge battery station
Model No.: DCBS**

**FCC ID: 2AK5Y-DCBS
IC ID: 25313-DCBS**

Prepared for : Control Technology China Co., LTD
No.98 Jianpeng Road, Jiuting Town, Shanghai, China

Prepared By : Shenzhen HUAK Testing Technology Co., Ltd.
1F, B2 Building, Junfeng Zhongcheng Zhizao Innovation Park, Fuhai Street,
Bao'an District, Shenzhen City, China

Date of Test: July 10, 2019 ~ Aug. 02, 2019

Date of Report: Aug. 02, 2019

Report Number: HK1907221811-3E

**BT**

Mode	Max PK Output power(dBm)	Tune Up Power(dBm)	Max Tune Up power(mW)	Antenna Gain(dBi)	Antenna Gain (linear)	MPE (mW/cm ²)
BT	3.62	3.62±1(4)	2.51	-0.54	0.883	0.00044

$$Pd = \frac{Pout * G}{4\pi r^2} ;$$

Note:

Note: The estimation distance is 20cm

Note:

PK Output power= conducted power.

Conducted power see the test report HK1907221811-2E, antenna gain=-0.54dBi

NOTE: WIFI 2.4GHz and BT cannot transmit simultaneously.

when the minimum test separation distance is >20 cm, a distance of 20 cm is applied to determine SAR test exclusion. The test exclusion threshold is 0.01256mW/cm² which is < 1.0mW/cm², SAR testing is not required.

-----The End-----