

S

T

S

L

A

B



FCC SAR TEST REPORT

Report No.: STS2003236H02

Issued for

Shanghai Unihertz E-Commerce Co., Ltd

Room 302, No. 5, Lane 59, Shennan Rd, Minhang district,
Shanghai, China 201108

Product Name:	Smart phone
Brand Name:	Unihertz
Model Name:	Atom XL
Series Model:	N/A
FCC ID:	2AK6CATOMXL
Test Standard:	ANSI/IEEE Std. C95.1
	FCC 47 CFR Part 2 (2.1093)
	IEEE 1528: 2013
Max. Report SAR (1g):	Head: 0.668 W/kg
	Body: 0.466 W/kg

Any reproduction of this document must be done in full. No single part of this document may be reproduced without permission from STS, All Test Data Presented in this report is only applicable to presented Test sample.

ShenZhen STS Test Services Co.,Ltd.

A 1/F, Building B, Zhuoke Science Park, No.190 Chongqing Road, HepingShequ, Fuyong Sub-District, Bao'an District, Shenzhen, Guang Dong, China

TEL: +86-755 3688 6288 FAX: +86-755 3688 6277 E-mail: sts@stsapp.com





Test Report Certification

Applicant's name : Shanghai Unihertz E-Commerce Co., Ltd
Address : Room 302, No. 5, Lane 59, Shennan Rd, Minhang district,
Shanghai, China 201108
Manufacture's Name : OBLUE Communication Technology Co.,Ltd.
Address : 7th floor, building B, dayou industrial and trade industrial park,
heping yonghe road,fuyong street,baoan district, Shenzhen,
China

Product description

Product name : Smart phone
Brand name : Unihertz
Model name : Atom XL
Series Model : N/A

Standards : ANSI/IEEE Std. C95.1-1992
FCC 47 CFR Part 2 (2.1093)
IEEE 1528: 2013

The device was tested by Shenzhen STS Test Services Co., Ltd. in accordance with the measurement methods and procedures specified in KDB 865664 The test results in this report apply only to the tested sample of the stated device/equipment. Other similar device/equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Date of Test :

Date (s) of performance of tests : 22 Apr. 2020~06 May 2020

Date of Issue : 07 May. 2020

Test Result : **Pass**

Testing Engineer :

Aaron Bu

(Aaron Bu)

Technical Manager :

Jason Lu

(Jason Lu)

Authorized Signatory :

Vita Li

(Vita Li)





Table of Contents

1. General Information	5
1.1 EUT Description	5
1.2 Test Environment	7
1.3 Test Factory	7
2. Test Standards and Limits	8
3. SAR Measurement System	9
3.1 Definition of Specific Absorption Rate (SAR)	9
3.2 SAR System	9
4. Tissue Simulating Liquids	12
4.1 Simulating Liquids Parameter Check	12
5. SAR System Validation	14
5.1 Validation System	14
5.2 Validation Result	14
6. SAR Evaluation Procedures	15
7. EUT Antenna Location Sketch	16
7.1 SAR test exclusion consider table	17
8. EUT Test Position	18
8.1 Define Two Imaginary Lines on the Handset	18
8.2 Hotspot mode exposure position condition	19
9. Uncertainty	20
9.1 Measurement Uncertainty	20
9.2 System validation Uncertainty	21
10. Conducted Power Measurement	22
10.1 Test Result	22
10.2 SAR Test Exclusions Applied	56
11. EUT and Test Setup Photo	58
11.1 EUT Photo	58
11.2 Setup Photo	61
12. SAR Result Summary	68
12.1 Head SAR	68
12.2 Body-worn and Hotspot SAR	73
13. Equipment List	83
Appendix A. System Validation Plots	84
Appendix B. SAR Test Plots	114
Appendix C. Probe Calibration and Dipole Calibration Report	153

**Revision History**

Rev.	Issue Date	Report No.	Effect Page	Contents
00	07 May. 2020	STS2003236H02	ALL	Initial Issue

Note: **Format version** of the report -V01





1. General Information

Environmental evaluation measurements of specific absorption rate (SAR) distributions in emulated human head and body tissues exposed to radio frequency (RF) radiation from wireless portable devices for compliance with the rules and regulations of the U.S. Federal Communications Commission (FCC).

1.1 EUT Description

Product Name	Smart phone
Brand Name	Unihertz
Model Name	Atom XL
Series Model	N/A
Model Difference	N/A
Battery	Rated Voltage: 3.85V Charge Limit: 4.4V Capacity: 4260mAh
Device Category	Portable
Product stage	Production unit
RF Exposure Environment	General Population / Uncontrolled
IMEI	11111111111111 22222222222222
Hardware Version	G63_V2.0
Software Version	Unihertz_Atom_XL_20200312
Frequency Range	Walkie-talkie mode: 400~406MHz, 406.1~480MHz GSM 850: 824.2~848.8MHz PCS1900: 1850.2~1909.8MHz WCDMA Band II: 1852.4~1907.6MHz WCDMA IV:1712.4~1752.6 MHz WCDMA Band V: 826.4~846.6MHz LTE Band 2: 1850.7~1909.3MHz LTE Band 4: 1710.7~1754.3MHz LTE Band 5: 824.7~848.3MHz LTE Band 7: 2502.5~2567.5MHz LTE Band 12:699.7~715.3MHz LTE Band 13:779.5~784.5MHz LTE Band 17: 706.5~713.5MHz LTE Band 25: 1850.7~1914.3MHz LTE Band 26: 814.7~848.3MHz LTE Band 38: 2570 MHz to 2620 MHz LTE Band 41: 2496MHz~2690 MHz LTE Band 66: 1710.7MHz~1779.3 MHz WLAN802.11b/g/n(HT20): 2412~2462MHz WLAN 802.11n(HT40): 2422~2452MHz 5GHz IEEE 802.11a/n/ac (20MHz): 5180 MHz to 5825MHz 5GHz IEEE 802.11n/ac (40MHz):5190 MHz to 5795MHz 5GHz IEEE 802.11ac (80MHz): 5210MHz, 5290MHz, 5530MHz to 5610MHz, 5775MHz Bluetooth: 2402~ 2480MHz



Max. Reported SAR(1g): (Limit: 1.6W/kg)	Band	Mode	Head (W/kg)	Body Worn and Hotspot(W/kg)
	PCE	GSM 850	0.246	0.431
	PCE	GSM 1900	0.262	0.466
	PCE	WCDMA Band II	0.149	0.368
	PCE	WCDMA Band IV	0.075	0.109
	PCE	WCDMA Band V	0.240	0.441
	PCE	LTE Band 2	0.261	0.317
	PCE	LTE Band 4	0.262	0.381
	PCE	LTE Band 5	0.186	0.307
	PCE	LTE Band 7	0.078	0.325
	PCE	LTE Band 12	0.059	0.263
	PCE	LTE Band 13	0.085	0.030
	PCE	LTE Band 17	0.083	0.291
	PCE	LTE Band 25	0.283	0.284
	PCE	LTE Band 26	0.205	0.436
	PCE	LTE Band 41	0.049	0.416
	PCE	LTE Band 66	0.179	0.358
	DTS	2.4G WLAN	0.150	0.046
	NII	5.2G WLAN ^{Note}	0.305	0.152
	NII	5.4G WLAN ^{Note}	0.308	0.154
	NII	5.6G WLAN ^{Note}	0.316	0.158
	NII	5.8G WLAN ^{Note}	0.668	0.203
	DTS	Bluetooth ^{Note}	0.334	0.167
1-g Sum SAR			0.951	0.669
Max. Reported SAR(1g):	Walkie talkie Mode			
	with 50% duty cycle		Front of face 0.147	Wrist 0.226
FCC Equipment Class	Licensed Portable Transmitter Held to Ear (PCE) Part 15 Spread Spectrum Transmitter (DSS) Digital Transmission System (DTS) Unlicensed National Information Infrastructure TX (NII)			
Operating Mode:	GSM: GSM Voice; GPRS; EGPRS Class 12 WCDMA: RMC, HSDPA, HSUPA Release 6 LTE: QPSK, 16QAM WLAN: 802.11 a/b/g/ac/n(HT20) /n(HT40) Bluetooth: 4.2+EDR (GFSK +π/4DQPSK+8DPSK) BLE			
Antenna Specification:	GSM, WCDMA, LTE: PIFA Antenna BT, WLAN: PIFA Antenna			
SIM Card	Support dual-SIM, dual standby, the multiple SIM card with two lines cannot transmitting at the same time			
Hotspot Mode	Support			
DTM Mode	Not Support			
Note: 1. Bluetooth, 5.2G WLAN, 5.4G WLAN, 5.6G WLAN and 5.8G WLAN Body SAR was estimated 2. The dual SIM card mobile has 2 SIM slots and supports dual SIM dual standby. The WWAN radio transmission will be enabled by either one SIM at a time (Single active) 3. After pre-scan two SIM cards power, we found test result of the SIM1 was the worse, so we chose SIM1 card to perform all tests. 4. The EUT battery must be fully charged and checked periodically during the test to ascertain uniform power				



1.2 Test Environment

Ambient conditions in the SAR laboratory:

Items	Required
Temperature (°C)	18-25
Humidity (%RH)	30-70

1.3 Test Factory

ShenZhen STS Test Services Co.,Ltd.

A 1/F, Building B, Zhuoke Science Park, No.190 Chongqing Road, HepingShequ, Fuyong Sub-District, Bao'an District, Shenzhen, Guang Dong, China

FCC test Firm Registration No.: 625569

IC Registration No.: 12108A

A2LA Certificate No.: 4338.01





2. Test Standards and Limits

No.	Identity	Document Title
1	47 CFR Part 2	Frequency Allocations and Radio Treaty Matters; General Rules and Regulations
2	ANSI/IEEE Std. C95.1-1992	IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz
3	IEEE Std. 1528-2013	Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques
4	FCC KDB 447498 D01 v06	Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies
5	FCC KDB 865664 D01 v01r04	SAR Measurement 100 MHz to 6 GHz
6	FCC KDB 865664 D02 v01r02	RF Exposure Reporting
7	FCC KDB 941225 D01 v03r01	SAR Measurement Procedures for 3G Devices
8	FCC KDB 941225 D05 v02r05	SAR for LTE Devices
9	FCC KDB 941225 D06 v02r01	Hotspot Mode SAR
10	FCC KDB 648474 D04 v01r03	SAR Evaluation Considerations for Wireless Handsets
11	FCC KDB 248227 D01 Wi-Fi SAR v02r02	SAR Considerations for 802.11 Devices
12	FCC KDB 643646 D01 v01r03	SAR Test for PTT Radios

(A). Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

(B). Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

NOTE: Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1 gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

Population/Uncontrolled Environments:

Are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure.

Occupational/Controlled Environments:

Are defined as locations where there is exposure that may be incurred by people who are aware of the potential for exposure, (i.e. as a result of employment or occupation).

NOTE

GENERAL POPULATION/UNCONTROLLED EXPOSURE

PARTIAL BODY LIMIT

1.6 W/kg

3. SAR Measurement System

3.1 Definition of Specific Absorption Rate (SAR)

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$


SAR is expressed in units of Watts per kilogram (W/kg) SAR measurement can be related to the electrical field in the tissue by

$$SAR = \frac{\sigma E^2}{\rho}$$

Where: σ is the conductivity of the tissue,
 ρ is the mass density of the tissue and E is the RMS electrical field strength.

3.2 SAR System

MVG SAR System Diagram:



COMOSAR is a system that is able to determine the SAR distribution inside a phantom of human being according to different standards. The COMOSAR system consists of the following items:

- Main computer to control all the system
- 6 axis robot
- Data acquisition system
- Miniature E-field probe
- Phone holder
- Head simulating tissue

The following figure shows the system.



The EUT under test operating at the maximum power level is placed in the phone holder, under the phantom, which is filled with head simulating liquid. The E-Field probe measures the electric field inside the phantom. The Open SAR software computes the results to give a SAR value in a 1g or 10g mass.

3.2.1 Probe

For the measurements the Specific Dosimetric E-Field Probe SN 41/18 EPG0334 with following specifications is used

- Probe Length: 330 mm
- Length of Individual Dipoles: 2 mm
- Maximum external diameter: 8 mm
- Probe Tip External Diameter: 2.5 mm
- Distance between dipole/probe extremity: 1 mm
- Dynamic range: 0.01-100 W/kg
- Probe linearity: 3%
- Axial Isotropy: < 0.10 dB
- Spherical Isotropy: < 0.10 dB
- Calibration range: 450 MHz to 6 GHz for head & body simulating liquid.
- Angle between probe axis (evaluation axis) and surface normal line: less than 30°



Figure 1-MVG COMOSAR Dosimetric E field Dipole

3.2.2 Phantom

For the measurements the Specific Anthropomorphic Mannequin (SAM) defined by the IEEE SCC-34/SC2 group is used. The phantom is a polyurethane shell integrated in a wooden table. The thickness of the phantom amounts to 2mm +/- 0.2mm. It enables the dosimetric evaluation of left and right phone usage and includes an additional flat phantom part for the simplified performance check. The phantom set-up includes a cover, which prevents the evaporation of the liquid.


SN 32/14 SAM115



SN 32/14 SAM116



3.2.3 Device Holder



The SAR in the phantom is approximately inversely proportional to the square of the distance between the source and the liquid surface. For a source at 5 mm distance, a positioning uncertainty of ± 0.5 mm would produce a SAR uncertainty of ± 20 %. Accurate device positioning is therefore crucial for accurate and repeatable measurements. The positions in which the devices must be measured are defined by the standards.

4. Tissue Simulating Liquids



4. Tissue Simulating Liquids

4.1 Simulating Liquids Parameter Check

The head tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 in P1528 have been incorporated in the following table. These head parameters are derived from planar layer models simulating the highest expected SAR for the dielectric properties and tissue thickness variations in a human head. Other head and body tissue parameters that have not been specified in P1528 are derived from the tissue dielectric parameters computed from the 4-Cole-Cole equations described in Reference [12] and extrapolated according to the head parameters specified in P1528.

Head Tissue

Frequency (MHz)	cellulose %	DGBE %	HEC %	NaCl %	Preventol %	Sugar %	X100 %	Water %	Conductivity σ	Permittivity ϵ_r
750	0.2	/	/	1.4	0.2	57.0	/	41.1	0.89	41.9
835	0.2	/	/	1.4	0.2	57.9	/	40.3	0.90	41.5
900	0.2	/	/	1.4	0.2	57.9	/	40.3	0.97	41.5
1800	/	44.5	/	0.3	/	/	30.45	55.2	1.4	40.0
1900	/	44.5	/	0.3	/	/	30.45	55.2	1.4	40.0
2000	/	44.5	/	0.3	/	/	/	55.2	1.4	40.0
2450	/	44.9	/	0.1	/	/	/	55.0	1.80	39.2
2600	/	45.0	/	0.1	/	/	/	54.9	1.96	39.0

Body Tissue

Frequency (MHz)	cellulose %	DGBE %	HEC %	NaCl %	Preventol %	Sugar %	X100 %	Water %	Conductivity σ	Permittivity ϵ_r
750	0.2	/	/	0.9	0.1	47.2	/	51.7	0.96	55.5
835	0.2	/	/	0.9	0.1	48.2	/	50.8	0.97	55.2
900	0.2	/	/	0.9	0.1	48.2	/	50.8	1.05	55.0
1800	/	29.4	/	0.4	/	/	30.45	70.2	1.52	53.3
1900	/	29.4	/	0.4	/	/	30.45	70.2	1.52	53.3
2000	/	29.4	/	0.4	/	/	/	70.2	1.52	53.3
2450	/	31.3	/	0.1	/	/	/	68.6	1.95	52.7
2600	/	31.7	/	0.1	/	/	/	68.2	2.16	52.3

Tissue dielectric parameters for head and body phantoms				
Frequency	ϵ_r		σ S/m	
	Head	Body	Head	Body
300	45.3	58.2	0.87	0.92
450	43.5	56.7	0.87	0.94
900	41.5	55.0	0.97	1.05
1450	40.5	54.0	1.20	1.30
1800	40.0	53.3	1.40	1.52
2450	39.2	52.7	1.80	1.95
3000	38.5	52.0	2.40	2.73
5800	35.3	48.2	5.27	6.00

**LIQUID MEASUREMENT RESULTS**

Date	Ambient condition		Head Simulating Liquid		Parameters	Target	Measured	Deviation [%]	Limited [%]
	Temp. [°C]	Humidity [%]	Frequency	Temp. [°C]					
2020-05-06	23.3	50	450 MHz	23.1	Permittivity:	43.50	42.87	-1.45	±5
					Conductivity	0.87	0.85	-2.30	±5
2020-04-22	23.0	50	750 MHz	22.7	Permittivity:	41.9	41.02	-2.10	±5
					Conductivity:	0.88	0.89	1.14	±5
2020-04-23	23.1	53	835 MHz	22.8	Permittivity:	41.5	40.68	-1.98	±5
					Conductivity:	0.9	0.92	2.22	±5
2020-04-26	23.5	50	1800 MHz	23.2	Permittivity:	40	40.31	0.78	±5
					Conductivity:	1.4	1.37	-2.14	±5
2020-04-27	23.2	48	1900 MHz	22.8	Permittivity:	40	40.67	1.68	±5
					Conductivity:	1.4	1.44	2.86	±5
2020-04-28	23.5	52	2450 MHz	23.2	Permittivity:	39.2	39.94	1.89	±5
					Conductivity:	1.8	1.76	-2.22	±5
2020-04-29	23.1	50	2600 MHz	22.9	Permittivity:	39	39.79	2.03	±5
					Conductivity:	1.96	1.93	-1.53	±5
2020-04-30	23.3	49	5800 MHz	23.0	Permittivity:	35.3	35.75	1.27	±5
					Conductivity:	5.27	5.25	-0.38	±5


Date	Ambient condition		Body Simulating Liquid		Parameters	Target	Measured	Deviation [%]	Limited [%]
	Temp. [°C]	Humidity [%]	Frequency	Temp. [°C]					
2020-05-06	23.3	50	450 MHz	23.0	Permittivity:	56.7	57.11	0.72	±5
					Conductivity:	0.94	0.96	2.13	±5
2020-04-22	23.0	50	750 MHz	22.7	Permittivity:	55.5	55.40	-0.18	±5
					Conductivity:	0.96	0.94	-2.08	±5
2020-04-23	23.1	53	835 MHz	22.9	Permittivity:	55.2	54.93	-0.49	±5
					Conductivity:	0.97	0.98	1.03	±5
2020-04-26	23.5	50	1800 MHz	22.3	Permittivity:	53.3	54.20	1.69	±5
					Conductivity:	1.52	1.55	1.97	±5
2020-04-27	23.2	48	1900 MHz	22.8	Permittivity:	53.3	53.96	1.24	±5
					Conductivity:	1.52	1.50	-1.32	±5
2020-04-28	23.5	52	2450 MHz	23.3	Permittivity:	52.7	52.89	0.36	±5
					Conductivity:	1.95	1.97	1.03	±5
2020-04-29	23.1	50	2600 MHz	22.8	Permittivity:	52.5	52.31	-0.36	±5
					Conductivity:	2.16	2.22	2.78	±5

5. SAR System Validation

5.1 Validation System

Each MVG system is equipped with one or more system validation kits. These units, together with the predefined measurement procedures within the MVG software, enable the user to conduct the system performance check and system validation. System kit includes a dipole, and dipole device holder.

The system check verifies that the system operates within its specifications. It's performed daily or before every SAR measurement. The system check uses normal SAR measurement in the flat section of the phantom with a matched dipole at a specified distance. The system validation setup is shown as below.



5.2 Validation Result

Comparing to the original SAR value provided by MVG, the validation data should be within its specification of 10 %.

Freq.(MHz)	Power(mW)	Tested Value (W/Kg)	Normalized SAR (W/kg/W)	Target (W/Kg/W)	Tolerance(%)	Date
450 Head	100	0.452	4.52	4.58	-1.31	2020-05-06
450 Body	100	0.467	4.67	4.58	1.97	2020-05-06
750 Head	100	0.882	8.82	8.49	3.89	2020-04-22
750 Body	100	0.809	8.09	8.49	-4.71	2020-04-22
835 Head	100	0.963	9.63	9.56	0.73	2020-04-23
835 Body	100	0.958	9.58	9.56	0.21	2020-04-23
1800 Head	100	3.843	38.43	38.4	0.08	2020-04-26
1800 Body	100	3.791	37.91	38.4	-1.28	2020-04-26
1900 Head	100	3.959	39.59	39.7	-0.28	2020-04-27
1900 Body	100	4.004	40.04	39.7	0.86	2020-04-27
2450 Head	100	5.231	52.31	52.4	-0.17	2020-04-28
2450 Body	100	5.204	52.04	52.4	-0.69	2020-04-28
2600 Head	100	5.495	54.95	55.3	-0.63	2020-04-29
2600 Body	100	5.518	55.18	55.3	-0.22	2020-04-29
5800 Head	100	18.147	181.47	181.2	0.15	2020-04-30

Note:

1. The tolerance limit of System validation $\pm 10\%$.
2. The dipole input power (forward power) was 100 mW.
3. The results are normalized to 1 W input power.



6. SAR Evaluation Procedures

The procedure for assessing the average SAR value consists of the following steps:

The following steps are used for each test position

- Establish a call with the maximum output power with a base station simulator. The connection between the mobile and the base station simulator is established via air interface
- Measurement of the local E-field value at a fixed location. This value serves as a reference value for calculating a possible power drift.
- Measurement of the SAR distribution with a grid of 8 to 16mm * 8 to 16 mm and a constant distance to the inner surface of the phantom. Since the sensors cannot directly measure at the inner phantom surface, the values between the sensors and the inner phantom surface are extrapolated. With these values the area of the maximum SAR is calculated by an interpolation scheme.
- Around this point, a cube of 30 * 30 * 30 mm or 32 * 32 * 32 mm is assessed by measuring 5 or 8 * 5 or 8*4 or 5 mm. With these data, the peak spatial-average SAR value can be calculated.


➤ Area Scan& Zoom Scan

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g. Area scan and zoom scan resolution setting follows KDB 865664 D01 quoted below.

When the 1-g SAR of the highest peak is within 2 dB of the SAR limit, additional zoom scans are required for other peaks within 2 dB of the highest peak that have not been included in any zoom scan to ensure there is no increase in SAR.

7. EUT Antenna Location Sketch

It is a Smart phone, support GSM/WCDMA/LTE/WIFI/BT mode.



 WWAN Antenna

 WLAN/BT Antenna

Note 1: The antenna information refer the manufacturer provide report, applicable only to the tested sample identified in the report.



7.1 SAR test exclusion consider table

According with FCC KDB 447498 D01, appendix A, <SAR test exclusion thresholds for 100MHz ~6GHz and ≤50mm> table, this device SAR test configurations consider as following:

Band	Test position configurations					
	Front	Back	Right edge	Left edge	Top edge	Bottom edge
WWAN	<5mm	<5mm	<5mm	<5mm	125mm	<5mm
	Yes	Yes	Yes	Yes	No	Yes
WLAN/BT	<5mm	<5mm	<5mm	55mm	<5mm	120mm
	Yes	Yes	No	Yes	Yes	No

Note:

- Maximum power is the source-based time-average power and represents the maximum RF output power among production units.
- Per KDB 447498 D01, for larger devices, the test separation distance of adjacent edge configuration is determined by the closest separation between the antenna and the user.
- per KDB 447498 D01, standalone SAR test exclusion threshold is applied; if the distance of the antenna to the user is <5mm, 5mm is user to determine SAR exclusion threshold
- per KDB 447498 D01, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distance ≤50mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, Mw}) / (\text{min. test separation distance, mm})] \cdot \sqrt{f(\text{GHz})} \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR}$$

$$f(\text{GHz}) \text{ is the RF channel transmit frequency in GHz. Power and distance are rounded to the nearest mW and mm before calculation. The result is rounded to one decimal place for comparison}$$

For <50mm distance, we just calculate mW of the exclusion threshold value(3.0)to do compare

- per KDB 447498 D01, at 100 MHz to 6GHz and for test separation distances >50mm, the SAR test exclusion threshold is determined according to the following
 - [threshold at 50mm in step 1]+(test separation distance -50mm)*(f (MHz)/150)]Mw, at 100 MHz to 1500 MHz
 - [threshold at 50mm in step1]+(test separation distance -50mm) *10]mW at > 1500MHz and ≤6GHz
- Per KDB 447498 D02, RMC 12.2kbps setting is used to evaluate SAR. If HSDPA/ HSUPA/DC-HSDPA output power is<0.25db higher than RMC 12.2Kbps,or reported SAR with RMC 12.2kbps setting is ≤1.2W/Kg, HSDPA/HSUPA/DC-HSDPA SAR evaluation can be excluded.
- Per KDB 248227 D01, choose the highest output power channel to test SAR and determine further SAR exclusion 8.for each frequency band, testing at higher data rates and higher order modulations is not required when the maximum average output power for each of each of these configurations is less than 1/4db higher than those measured at the lower data rate than 11b mode, thus the SAR can be excluded.

8. EUT Test Position


This EUT was tested in Right Cheek, Right Titled, Left Cheek, Left Titled, Front Face and Rear Face.

8.1 Define Two Imaginary Lines on the Handset

(1) The vertical centerline passes through two points on the front side of the handset the midpoint of the width w_t of the handset at the level of the acoustic output, and the midpoint of the width w_b of the handset.

(2) The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output. The horizontal line is also tangential to the face of the handset at point A.


(3) The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily to the front face of the handset, especially for clamshell handsets, handsets with flip covers, and other irregularly shaped handsets.



Cheek Position

1) To position the device with the vertical center line of the body of the device and the horizontal line crossing the center piece in a plane parallel to the sagittal plane of the phantom. While maintaining the device in this plane, align the vertical center line with the reference plane containing the ear and mouth reference point (M: Mouth, RE: Right Ear, and LE: Left Ear) and align the center of the ear piece with the line RE-LE.


2) To move the device towards the phantom with the ear piece aligned with the line LE-RE until the phone touched the ear. While maintaining the device in the reference plane and maintaining the phone contact with ear, move the bottom of the phone until any point on the front side is in contact with the cheek of the phantom or until contact with the ear is lost



Title Position


(1) To position the device in the "cheek" position described above.

(2) While maintaining the device in the reference plane described above and pivoting against the ear, moves it outward away from the mouth by an angle of 15 degrees or until with the ear is lost.




Body-worn Position Conditions:

Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in KDB Publication 447498 D01 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. When the same wireless transmission configuration is used for testing body-worn accessory and hotspot mode SAR, respectively, in voice and data mode, SAR results for the most conservative *test separation distance* configuration may be used to support both SAR conditions. When the *reported* SAR for a body-worn accessory, measured without a headset connected to the handset, is $> 1.2 \text{ W/kg}$, the highest *reported* SAR configuration for that wireless mode and frequency band should be repeated for the body-worn accessory with a headset attached to the handset.



8.2 Hotspot mode exposure position condition

For handsets that support hotspot mode operations, with wireless router capabilities and various web browsing function, the relevant hand and body exposure condition are tested according to the hotspot SAR procedures in KDB 941225. A test separation distance of 10 mm is required between the phantom and all surface and edges with a transmitting antenna located within 25 mm from that surface or edge. When form factor of a handset is smaller than 9cm x 5cm, a test separation distance of 5mm (instead of 10mm) is required for testing hotspot mode. When the separate distance required for body-worn accessory testing is larger than or equal to that tested for hotspot mode, in the same wireless mode and for the same surface of the phone, the hotspot mode SAR data may be used to support body-worn accessory SAR compliance for that particular configuration (surface).





9. Uncertainty

9.1 Measurement Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in IEEE 1528: 2013. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Uncertainty Component	Tol (+/- %)	Prob. Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (+/-%)	10g Ui (+/-%)	v_i
Measurement System								
Probe calibration	5.831	N	1	1	1	5.83	5.83	∞
Axial Isotropy	0.695	R	$\sqrt{3}$	$\sqrt{0.5}$	$\sqrt{0.5}$	0.28	0.28	∞
Hemispherical Isotropy	1.045	R	$\sqrt{3}$	$\sqrt{0.5}$	$\sqrt{0.5}$	0.43	0.43	∞
Boundary effect	1.0	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Linearity	0.685	R	$\sqrt{3}$	1	1	0.40	0.40	∞
System detection limits	1.0	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Modulation response	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	∞
Readout Electronics	0.021	N	1	1	1	0.021	0.021	∞
Response Time	0	R	$\sqrt{3}$	1	1	0	0	∞
Integration Time	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
RF ambient conditions-Noise	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	∞
RF ambient conditions-reflections	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	∞
Probe positioner mechanical tolerance	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Probe positioning with respect to phantom shell	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Post-processing	2.3	R	$\sqrt{3}$	1	1	1.33	1.33	∞
Test sample Related								
Test sample positioning	2.6	N	1	1	1	2.6	2.6	∞
Device holder uncertainty	3	N	1	1	1	3	3	∞
SAR drift measurement	5	R	$\sqrt{3}$	1	1	2.89	2.89	∞
SAR scaling	5	R	$\sqrt{3}$	1	1	2.89	2.89	∞
Phantom and tissue parameters								
Phantom uncertainty (shape and thickness uncertainty)	4	R	$\sqrt{3}$	1	1	2.31	2.31	∞
Uncertainty in SAR correction for deviations in permittivity and conductivity	1.9	N	1	1	0.84	1.90	1.60	∞
Liquid conductivity (temperature uncertainty)	2.5	R	$\sqrt{3}$	0.78	0.71	1.13	1.02	∞
Liquid conductivity (measured)	4	N	1	0.78	0.71	3.12	2.84	M
Liquid permittivity (temperature uncertainty)	2.5	R	$\sqrt{3}$	0.23	0.26	0.33	0.38	∞
Liquid permittivity (measured)	5	N	1	0.23	0.26	1.15	1.30	M
Combined Standard Uncertainty		RSS				9.79	9.59	
Expanded Uncertainty (95% Confidence interval)		K=2				19.58	19.18	



9.2 System validation Uncertainty

Uncertainty Component	Tol (+-%)	Prob. Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (+-%)	10g Ui (+-%)	vi
Measurement System								
Probe calibration	5.831	N	1	1	1	5.83	5.83	∞
Axial Isotropy	0.695	R	$\sqrt{3}$	1	1	0.40	0.40	∞
Hemispherical Isotropy	1.045	R	$\sqrt{3}$	0	0	0.00	0.00	∞
Boundary effect	1.0	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Linearity	0.685	R	$\sqrt{3}$	1	1	0.40	0.40	∞
System detection limits	1.0	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Modulation response	3.0	R	$\sqrt{3}$	0	0	0.00	0.00	∞
Readout Electronics	0.021	N	1	1	1	0.021	0.021	∞
Response Time	0.0	R	$\sqrt{3}$	0	0	0.00	0.00	∞
Integration Time	1.4	R	$\sqrt{3}$	0	0	0.00	0.00	∞
RF ambient conditions-Noise	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	∞
RF ambient conditions-reflections	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	∞
Probe positioner mechanical tolerance	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Probe positioning with respect to phantom shell	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Post-Processing	2.3	R	$\sqrt{3}$	1	1	1.33	1.33	∞
System validation source								
Deviation of experimental dipole from numerical dipole	5.0	N	1	1	1	5.00	5.00	∞
Input power and SAR drift measurement	5.0	R	$\sqrt{3}$	1	1	2.89	2.89	∞
Other source contribution Uncertainty	2.0	R	$\sqrt{3}$	1	1	1.15	1.15	∞
Phantom and set-up								
Phantom uncertainty (shape and thickness uncertainty)	4.0	R	$\sqrt{3}$	1	1	2.31	2.31	∞
Uncertainty in SAR correction for deviations in permittivity and conductivity	1.9	N	1	1	0.84	1.90	1.60	∞
Liquid conductivity (temperature uncertainty)	2.5	R	$\sqrt{3}$	0.78	0.71	1.13	1.02	∞
Liquid conductivity (measured)	4	N	1	0.78	0.71	3.12	2.84	M
Liquid permittivity (temperature uncertainty)	2.5	R	$\sqrt{3}$	0.23	0.26	0.33	0.38	∞
Liquid permittivity (measured)	5	N	1	0.23	0.26	1.15	1.30	M
Combined Standard Uncertainty		RSS				9.718	9.517	
Expanded Uncertainty (95% Confidence interval)		K=2				19.44	19.04	



10. Conducted Power Measurement

10.1 Test Result

Burst Average Power (dBm)						
Band	GSM 850			PCS 1900		
Channel	128	190	251	512	661	810
Frequency (MHz)	824.2	836.6	848.8	1850.2	1880.0	1909.8
GSM(GMSK, 1-Slot)	31.11	31.35	31.66	27.45	26.38	26.59
GPRS (GMSK, 1-Slot)	31.13	31.39	31.67	27.49	26.42	26.60
GPRS (GMSK, 2-Slot)	30.68	30.92	31.25	27.08	25.97	26.14
GPRS (GMSK, 3-Slot)	30.27	30.48	30.79	26.64	25.55	25.71
GPRS (GMSK, 4-Slot)	29.83	30.03	30.36	26.20	25.11	25.29
EGPRS(8PSK, 1-Slot)	27.55	27.84	28.00	25.71	26.27	26.74
EGPRS(8PSK, 2-Slot)	26.84	27.11	27.23	24.97	25.52	25.99
EGPRS(8PSK, 3-Slot)	26.12	26.34	26.43	24.18	24.81	25.23
EGPRS(8PSK, 4-Slot)	25.36	25.58	25.69	23.45	24.10	24.48
Remark: GPRS, CS4 coding scheme. EGPRS, MCS5 coding scheme. Multi-Slot Class 8, Support Max 4 downlink, 1 uplink, 5 working link Multi-Slot Class 10, Support Max 4 downlink, 2 uplink, 5 working link Multi-Slot Class 12, Support Max 4 downlink, 4 uplink, 5 working link						

Fram- Average Power(dBm)						
Band	GSM 850			PCS 1900		
Channel	128	190	251	512	661	810
Frequency (MHz)	824.2	836.6	848.8	1850.2	1880.0	1909.8
GSM(GMSK, 1-Slot)	22.08	22.32	22.63	18.42	17.35	17.56
GPRS (GMSK, 1-Slot)	22.10	22.36	22.64	18.46	17.39	17.57
GPRS (GMSK, 2-Slot)	24.66	24.90	25.23	21.06	19.95	20.12
GPRS (GMSK, 3-Slot)	26.01	26.22	26.53	22.38	21.29	21.45
GPRS (GMSK, 4-Slot)	26.82	27.02	27.35	23.19	22.10	22.28
EGPRS(8PSK, 1-Slot)	18.52	18.81	18.97	16.68	17.24	17.71
EGPRS(8PSK, 2-Slot)	20.82	21.09	21.21	18.95	19.50	19.97
EGPRS(8PSK, 3-Slot)	21.86	22.08	22.17	19.92	20.55	20.97
EGPRS(8PSK, 4-Slot)	22.35	22.57	22.68	20.44	21.09	21.47
Remark : 1. SAR testing was performed on the maximum frame-averaged power mode. 2. The frame-averaged power is linearly proportion to the slot number configured and it is linearly scaled the maximum Burst - averaged power based on time slots. The calculated method is shown as below: Frame-averaged power = Burst averaged power (1 TX Slot) – 9.03 dB Frame-averaged power = Burst averaged power (2 TX Slots) – 6.02 dB Frame-averaged power = Burst averaged power (3 TX Slots) - 4.26 dB Frame-averaged power = Burst averaged power (4 TX Slots) – 3.01 dB						

**WCDMA**

Band	WCDMA Band V			WCDMA Band IV			WCDMA Band II		
Channel	4132	4183	4233	1312	1413	1513	9262	9400	9538
Frequency (MHz)	826.4	836.6	846.6	1712.6	1740	1752.4	1852.4	1880.0	1907.6
AMR 12.2Kbps	21.04	20.87	20.99	21.59	21.37	21.14	20.84	20.75	20.97
RMC 12.2Kbps	21.07	20.89	21.02	21.61	21.39	21.17	20.94	20.76	21.00
HSDPA Subtest-1	19.83	19.84	19.87	21.45	21.15	20.87	18.53	18.45	18.58
HSDPA Subtest-2	19.38	19.42	19.41	20.96	20.68	20.46	18.06	18.02	18.16
HSDPA Subtest-3	19.04	18.99	18.95	20.49	20.23	19.96	17.68	17.56	17.82
HSDPA Subtest-4	18.64	18.64	18.60	20.11	19.91	19.53	17.32	17.16	17.39
HSUPA Subtest-1	19.79	19.74	19.70	21.22	20.95	20.79	18.51	18.36	18.59
HSUPA Subtest-2	18.86	18.81	18.76	20.38	20.01	19.83	17.57	17.40	17.68
HSUPA Subtest-3	18.69	18.35	18.42	20.33	19.58	19.47	17.43	16.94	17.37
HSUPA Subtest-4	18.36	17.95	18.12	20.01	19.13	19.10	16.96	16.47	17.07
HSUPA Subtest-5	16.87	16.46	16.71	18.61	17.67	17.68	15.48	15.05	15.57

According to 3GPP 25.101 sub-clause 6.2.2, the maximum output power is allowed to be reduced by following the table.

Table 6.1A: UE maximum output power with HS-DPCCH and E-DCH

UE Transmit Channel Configuration	CM(db)	MPR(db)
For all combinations of ,DPDCH,DPCCH HS-DPDCH,E-DPDCH and E-DPCCH	$0 \leq CM \leq 3.5$	MAX(CM-1,0)
Note: CM=1 for $\beta_c/\beta_d=12/15$, $\beta_{hs}/\beta_c=24/15$. For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.		

The device supports MPR to solve linearity issues (ACLR or SEM) due to the higher peak-to average ratios (PAR) of the HSUPA signal. This prevents saturating the full range of the TX DAC inside of device and provides a reduced power output to the RF transceiver chip according to the Cubic Metric (a function of the combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH).

When E-DPDCH channels are present the beta gains on those channels are reduced firsts to try to get the power under the allowed limit. If the beta gains are lowered as far as possible, then a hard limiting is applied at the maximum allowed level.

The SW currently recalculates the cubic metric every time the beta gains on the E-DPDCH are reduced. The cubic metric will likely get lower each time this is done .However, there is no reported reduction of maximum output power in the HSUPA mode since the device also provides a compensation for the power back-off by increasing the gain of TX_AGC in the transceiver (PA) device.

The end effect is that the DUT output power is identical to the case where there is no MPR in the device.

**WLAN**

Mode	Channel Number	Frequency (MHz)	Average Power (dBm)
802.11b	1	2412	13.91
	6	2437	13.72
	11	2462	13.78
802.11g	1	2412	4.27
	6	2437	4.40
	11	2462	4.56
802.11n(HT 20)	1	2412	1.77
	6	2437	1.99
	11	2462	2.09
802.11n(HT 40)	3	2422	2.09
	6	2437	1.89
	9	2452	1.98

WLAN (5.2Gband)

Mode	Channel Number	Frequency (MHz)	Output Power (dBm)
802.11a	36	5180	6.58
	40	5200	6.56
	48	5240	6.51
802.11 n-HT20	36	5180	2.76
	40	5200	2.72
	48	5240	2.74
802.11 n-HT40	38	5190	2.80
	46	5230	2.67
802.11 ac-VHT20	36	5180	2.50
	40	5200	2.55
	48	5240	2.51
802.11 ac-VHT40	38	5190	2.69
	46	5230	2.72
802.11 ac-VHT80	42	5210	2.66

**WLAN (5.3Gband)**

Mode	Channel Number	Frequency (MHz)	Output Power (dBm)
802.11a	52	5260	6.48
	60	5300	6.35
	64	5320	6.28
802.11 n-HT20	52	5260	3.01
	60	5300	2.93
	64	5320	2.71
802.11 n-HT40	54	5270	2.96
	62	5310	2.79
802.11 ac-VHT20	52	5260	2.25
	60	5300	2.15
	64	5320	2.00
802.11 ac-VHT40	54	5270	2.97
	62	5310	2.90
802.11 ac-VHT80	58	5290	3.40

WLAN (5.6Gband)

Mode	Channel Number	Frequency (MHz)	Output Power (dBm)
802.11a	100	5500	6.85
	116	5580	6.87
	140	5700	6.30
802.11 n-HT20	100	5500	2.84
	116	5580	2.26
	140	5700	1.67
802.11 n-HT40	102	5510	2.65
	110	5550	2.48
	134	5670	1.78
802.11 ac-VHT20	100	5500	2.90
	116	5580	2.32
	140	5700	1.67
802.11 ac-VHT40	102	5510	2.69
	110	5550	2.50
	134	5670	1.76
802.11 ac-VHT80	106	5530	0.45
	122	5610	0.46

**WLAN (5.8Gband)**

Mode	Channel Number	Frequency (MHz)	Output Power (dBm)
802.11a	149	5745	7.81
	157	5785	7.51
	165	5825	7.01
802.11 n-HT20	149	5745	3.92
	157	5785	3.62
	165	5825	3.18
802.11 n-HT40	151	5755	3.70
	159	5795	3.53
802.11 ac-VHT20	149	5745	2.91
	157	5785	2.65
	165	5825	2.41
802.11 ac-VHT40	151	5755	2.87
	159	5795	2.63
802.11 ac-VHT80	155	5775	3.32

Bluetooth

Mode	Channel Number	Frequency (MHz)	Average Power (dBm)
GFSK(1Mbps)	0	2402	8.48
	39	2441	8.40
	78	2480	8.57
$\pi/4$ -DQPSK(2Mbps)	0	2402	6.66
	39	2441	6.62
	78	2480	6.80
8DPSK(3Mbps)	0	2402	6.66
	39	2441	6.62
	78	2480	6.80

BLE

Mode	Channel Number	Frequency (MHz)	Average Power (dBm)
GFSK(1Mbps)	0	2402	2.47
	19	2440	2.57
	39	2480	2.71

**PTT****Analogue**

Mode	Frequency (MHz)	Average Power (dBm)
12.5KHz (Low Power)	450.0125	27.615
	460.0000	27.701
	469.9875	27.255
12.5KHz (High Power)	450.0125	32.162
	460.0000	32.152
	469.9875	32.033

Data

Mode	Frequency (MHz)	Average Power (dBm)
12.5KHz (Low Power)	450.0125	27.703
	460.0000	27.732
	469.9875	27.740
12.5KHz (High Power)	450.0125	32.616
	460.0000	32.190
	469.9875	32.069



LTE Conducted Power

General Note:

1. Anritsu CMW500 base station simulator was used to setup the connection with EUT; the frequency band, channel bandwidth, RB allocation configuration, modulation type are set in the base station simulator to configure EUT transmitting at maximum power and at different configurations which are requested to be reported to FCC, for conducted power measurement and SAR testing.
2. Per KDB 941225 D05, when a properly configured base station simulator is used for the SAR and power measurements, spectrum plots for each RB allocation and offset configuration is not required.
3. Per KDB 941225 D05, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
4. Per KDB 941225 D05, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
5. Per KDB 941225 D05, For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
6. Per KDB 941225 D05, 16QAM output power for each RB allocation configuration is $> \text{not } \frac{1}{2}$ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is ≤ 1.45 W/kg; Per KDB 941225 D05, 16QAM SAR testing is not required.
7. Per KDB 941225 D05, Smaller bandwidth output power for each RB allocation configuration is $> \text{not } \frac{1}{2}$ dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is ≤ 1.45 W/kg; Per KDB 941225 D05, smaller bandwidth SAR testing is not required.



LTE Band 2

LTE Band 2 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	21.96	21.93	21.84
1.4	1	2		21.74	21.72	21.62
1.4	1	5		21.52	21.43	21.35
1.4	3	0		21.31	21.17	21.13
1.4	3	1		21.04	20.96	20.85
1.4	3	2		20.75	20.71	20.65
1.4	6	0		20.46	20.45	20.42
1.4	1	0	16-QAM	21.70	21.73	21.61
1.4	1	2		21.43	21.44	21.36
1.4	1	5		21.20	21.15	21.16
1.4	3	0		20.93	20.88	20.91
1.4	3	1		20.70	20.64	20.65
1.4	3	2		20.46	20.37	20.39
1.4	6	0		20.23	20.08	20.18
3	1	0	QPSK	22.06	22.08	22.10
3	1	7		21.78	21.86	21.86
3	1	14		21.50	21.64	21.60
3	8	0		21.22	21.35	21.38
3	8	4		20.99	21.14	21.14
3	8	7		20.72	20.89	20.86
3	15	0		20.50	20.64	20.62
3	1	0	16-QAM	21.82	21.86	21.84
3	1	7		21.61	21.58	21.58
3	1	14		21.34	21.29	21.28
3	8	0		21.12	21.00	21.07
3	8	4		20.85	20.73	20.87
3	8	7		20.56	20.50	20.66
3	15	0		20.35	20.23	20.44



LTE BAND 2

LTE Band 2 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	21.75	21.98	21.97
5	1	12		21.49	21.71	21.75
5	1	24		21.23	21.45	21.54
5	12	0		20.98	21.23	21.33
5	12	6		20.68	20.98	21.08
5	12	11		20.47	20.76	20.80
5	25	0		20.19	20.48	20.55
5	1	0	16-QAM	21.52	21.69	21.74
5	1	12		21.24	21.48	21.47
5	1	24		20.99	21.19	21.19
5	12	0		20.76	20.96	20.90
5	12	6		20.50	20.73	20.65
5	12	11		20.29	20.50	20.39
5	25	0		20.05	20.25	20.18
10	1	0	QPSK	21.84	21.93	21.89
10	1	24		21.63	21.71	21.62
10	1	49		21.41	21.49	21.41
10	25	0		21.12	21.26	21.12
10	25	12		20.85	20.97	20.86
10	25	24		20.57	20.71	20.60
10	50	0		20.28	20.49	20.36
10	1	0	16-QAM	21.61	21.73	21.67
10	1	24		21.38	21.50	21.39
10	1	49		21.11	21.24	21.11
10	25	0		20.86	20.94	20.91
10	25	12		20.63	20.72	20.67
10	25	24		20.41	20.44	20.46
10	50	0		20.16	20.23	20.18



LTE BAND 2

LTE Band 2 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	22.19	22.13	22.15
15	1	37		21.95	21.91	21.89
15	1	74		21.74	21.68	21.65
15	36	0		21.49	21.44	21.37
15	36	18		21.20	21.22	21.16
15	36	39		20.97	21.01	20.88
15	75	0		20.70	20.81	20.61
15	1	0	16-QAM	21.90	21.89	21.92
15	1	38		21.63	21.59	21.63
15	1	75		21.36	21.33	21.36
15	36	0		21.15	21.09	21.15
15	36	18		20.93	20.84	20.89
15	36	39		20.69	20.56	20.68
15	75	0		20.41	20.29	20.45
20	1	0	QPSK	22.35	22.23	22.29
20	1	49		22.12	21.97	22.01
20	1	99		21.86	21.72	21.81
20	50	0		21.59	21.42	21.56
20	50	24		21.37	21.15	21.28
20	50	49		21.09	20.90	21.04
20	100	0		20.83	20.66	20.78
20	1	0	16-QAM	22.05	21.96	22.08
20	1	49		21.79	21.70	21.85
20	1	99		21.52	21.48	21.62
20	50	0		21.29	21.25	21.34
20	50	24		21.01	21.02	21.14
20	50	49		20.72	20.73	20.88
20	100	0		20.47	20.50	20.67



LTE BAND 4

LTE Band 4 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	21.73	21.74	21.81
1.4	1	2		21.44	21.47	21.51
1.4	1	5		21.16	21.19	21.22
1.4	3	0		20.92	20.93	20.96
1.4	3	1		20.69	20.64	20.67
1.4	3	2		20.42	20.43	20.45
1.4	6	0		20.17	20.22	20.17
1.4	1	0	16-QAM	21.45	21.53	21.52
1.4	1	2		21.16	21.25	21.26
1.4	1	5		20.88	21.03	21.04
1.4	3	0		20.65	20.83	20.76
1.4	3	1		20.39	20.62	20.53
1.4	3	2		20.16	20.40	20.27
1.4	6	0		19.93	20.14	20.03
3	1	0	QPSK	21.57	21.73	21.52
3	1	7		21.30	21.46	21.26
3	1	14		21.02	21.17	21.00
3	8	0		20.73	20.94	20.78
3	8	4		20.50	20.72	20.57
3	8	7		20.27	20.51	20.31
3	15	0		19.97	20.23	20.05
3	1	0	16-QAM	21.31	21.46	21.23
3	1	7		21.11	21.23	20.94
3	1	14		20.89	21.00	20.64
3	8	0		20.69	20.74	20.41
3	8	4		20.46	20.47	20.15
3	8	7		20.24	20.19	19.93
3	15	0		19.97	19.90	19.71



LTE BAND 4

LTE Band 4 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	21.50	21.59	21.56
5	1	12		21.22	21.33	21.28
5	1	24		20.95	21.11	20.99
5	12	0		20.74	20.82	20.79
5	12	6		20.51	20.61	20.52
5	12	11		20.24	20.39	20.29
5	25	0		20.01	20.13	20.07
5	1	0	16-QAM	21.30	21.32	21.29
5	1	12		21.09	21.03	21.00
5	1	24		20.82	20.80	20.70
5	12	0		20.58	20.58	20.41
5	12	6		20.37	20.31	20.18
5	12	11		20.12	20.03	19.90
5	25	0		19.84	19.79	19.63
10	1	0	QPSK	21.65	21.66	21.69
10	1	24		21.42	21.45	21.48
10	1	49		21.14	21.20	21.20
10	25	0		20.88	20.97	20.97
10	25	12		20.66	20.74	20.72
10	25	24		20.41	20.46	20.50
10	50	0		20.12	20.17	20.21
10	1	0	16-QAM	21.42	21.39	21.44
10	1	24		21.16	21.09	21.16
10	1	49		20.88	20.86	20.96
10	25	0		20.66	20.63	20.66
10	25	12		20.43	20.41	20.40
10	25	24		20.22	20.13	20.14
10	50	0		19.99	19.92	19.85



LTE BAND 4

LTE Band 4 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	21.88	21.76	21.73
15	1	37		21.66	21.53	21.47
15	1	74		21.39	21.28	21.23
15	36	0		21.09	20.99	20.93
15	36	18		20.81	20.76	20.66
15	36	39		20.53	20.54	20.39
15	75	0		20.28	20.27	20.16
15	1	0	16-QAM	21.67	21.54	21.49
15	1	38		21.40	21.31	21.22
15	1	75		21.20	21.05	21.00
15	36	0		20.96	20.82	20.76
15	36	18		20.67	20.59	20.47
15	36	39		20.43	20.35	20.21
15	75	0		20.15	20.15	19.99
20	1	0	QPSK	21.83	21.86	21.91
20	1	49		21.58	21.65	21.70
20	1	99		21.37	21.37	21.44
20	50	0		21.11	21.08	21.22
20	50	24		20.83	20.85	20.98
20	50	49		20.60	20.57	20.69
20	100	0		20.34	20.28	20.46
20	1	0	16-QAM	21.58	21.58	21.64
20	1	49		21.37	21.31	21.44
20	1	99		21.15	21.10	21.17
20	50	0		20.90	20.82	20.93
20	50	24		20.64	20.60	20.72
20	50	49		20.42	20.34	20.52
20	100	0		20.15	20.05	20.26



LTE BAND 5

LTE Band 5 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	23.43	23.40	23.50
1.4	1	2		23.19	23.11	23.24
1.4	1	5		22.97	22.88	23.00
1.4	3	0		22.70	22.58	22.71
1.4	3	1		22.44	22.32	22.42
1.4	3	2		22.19	22.08	22.17
1.4	6	0		21.93	21.80	21.91
1.4	1	0	16-QAM	23.13	23.19	23.22
1.4	1	2		22.87	22.91	23.00
1.4	1	5		22.58	22.63	22.79
1.4	3	0		22.38	22.41	22.57
1.4	3	1		22.17	22.16	22.35
1.4	3	2		21.91	21.88	22.07
1.4	6	0		21.68	21.61	21.84
3	1	0	QPSK	23.46	23.47	23.56
3	1	7		23.18	23.18	23.36
3	1	14		22.90	22.95	23.11
3	8	0		22.61	22.68	22.83
3	8	4		22.35	22.40	22.59
3	8	7		22.06	22.13	22.30
3	15	0		21.81	21.84	22.02
3	1	0	16-QAM	23.21	23.24	23.29
3	1	7		22.93	22.98	23.02
3	1	14		22.64	22.76	22.75
3	8	0		22.36	22.48	22.50
3	8	4		22.06	22.22	22.25
3	8	7		21.78	21.97	21.95
3	15	0		21.55	21.76	21.69



LTE BAND 5

LTE Band 5 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	23.35	23.38	23.43
5	1	12		23.12	23.12	23.15
5	1	24		22.84	22.91	22.92
5	12	0		22.57	22.68	22.69
5	12	6		22.33	22.45	22.47
5	12	11		22.06	22.17	22.19
5	25	0		21.85	21.91	21.90
5	1	0	16-QAM	23.12	23.16	23.16
5	1	12		22.86	22.88	22.90
5	1	24		22.64	22.67	22.69
5	12	0		22.34	22.43	22.45
5	12	6		22.12	22.20	22.23
5	12	11		21.88	21.99	22.03
5	25	0		21.58	21.75	21.80
10	1	0	QPSK	23.61	23.56	23.81
10	1	24		23.39	23.31	23.61
10	1	49		23.19	23.02	23.40
10	25	0		22.94	22.81	23.13
10	25	12		22.65	22.61	22.88
10	25	24		22.43	22.35	22.61
10	50	0		22.18	22.06	22.33
10	1	0	16-QAM	23.38	23.26	23.55
10	1	24		23.11	23.03	23.25
10	1	49		22.82	22.74	22.98
10	25	0		22.61	22.45	22.74
10	25	12		22.38	22.19	22.50
10	25	24		22.12	21.90	22.22
10	50	0		21.85	21.63	21.99



LTE BAND 7

LTE Band 7 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	20.11	20.12	20.28
5	1	12		19.91	19.85	20.07
5	1	24		19.67	19.64	19.85
5	12	0		19.43	19.36	19.57
5	12	6		19.16	19.09	19.30
5	12	11		18.93	18.79	19.02
5	25	0		18.73	18.56	18.75
5	1	0	16-QAM	19.89	19.86	20.02
5	1	12		19.60	19.63	19.82
5	1	24		19.39	19.41	19.58
5	12	0		19.13	19.18	19.30
5	12	6		18.86	18.95	19.10
5	12	11		18.56	18.66	18.82
5	25	0		18.33	18.40	18.61
10	1	0	QPSK	20.08	20.09	20.05
10	1	24		19.78	19.79	19.85
10	1	49		19.48	19.58	19.57
10	25	0		19.21	19.34	19.30
10	25	12		18.94	19.09	19.08
10	25	24		18.67	18.81	18.85
10	50	0		18.44	18.57	18.62
10	1	0	16-QAM	19.87	19.79	19.77
10	1	24		19.62	19.54	19.51
10	1	49		19.35	19.24	19.23
10	25	0		19.08	19.00	19.00
10	25	12		18.81	18.73	18.72
10	25	24		18.53	18.50	18.48
10	50	0		18.26	18.24	18.23



LTE BAND 7

LTE Band 7 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	20.07	20.18	20.14
15	1	37		19.79	19.96	19.86
15	1	74		19.51	19.73	19.61
15	36	0		19.29	19.45	19.38
15	36	18		19.08	19.23	19.12
15	36	39		18.88	19.01	18.89
15	75	0		18.62	18.75	18.61
15	1	0	16-QAM	19.85	19.89	19.93
15	1	38		19.62	19.62	19.70
15	1	75		19.38	19.36	19.43
15	36	0		19.15	19.09	19.20
15	36	18		18.91	18.83	18.98
15	36	39		18.62	18.58	18.71
15	75	0		18.32	18.31	18.45
20	1	0	QPSK	20.35	20.23	20.20
20	1	49		20.10	20.01	19.91
20	1	99		19.89	19.72	19.66
20	50	0		19.65	19.48	19.36
20	50	24		19.38	19.20	19.14
20	50	49		19.13	18.99	18.85
20	100	0		18.92	18.71	18.57
20	1	0	16-QAM	20.14	20.01	19.94
20	1	49		19.90	19.80	19.65
20	1	99		19.69	19.60	19.38
20	50	0		19.47	19.31	19.16
20	50	24		19.17	19.08	18.89
20	50	49		18.88	18.87	18.62
20	100	0		18.64	18.65	18.34



LTE BAND 12

LTE Band 12 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	23.56	23.48	23.36
1.4	1	2		23.36	23.25	23.07
1.4	1	5		23.13	22.96	22.77
1.4	3	0		22.91	22.72	22.53
1.4	3	1		22.61	22.45	22.24
1.4	3	2		22.40	22.20	22.00
1.4	6	0		22.15	21.94	21.74
1.4	1	0	16-QAM	23.30	23.20	23.15
1.4	1	2		23.03	22.97	22.95
1.4	1	5		22.76	22.71	22.74
1.4	3	0		22.56	22.50	22.46
1.4	3	1		22.27	22.23	22.20
1.4	3	2		22.02	21.96	22.00
1.4	6	0		21.79	21.70	21.73
3	1	0	QPSK	23.45	23.47	23.41
3	1	7		23.15	23.22	23.18
3	1	14		22.85	22.97	22.98
3	8	0		22.59	22.76	22.78
3	8	4		22.36	22.53	22.48
3	8	7		22.11	22.28	22.27
3	15	0		21.86	22.05	22.02
3	1	0	16-QAM	23.24	23.18	23.19
3	1	7		23.01	22.93	22.98
3	1	14		22.76	22.63	22.69
3	8	0		22.55	22.41	22.45
3	8	4		22.31	22.17	22.16
3	8	7		22.04	21.88	21.91
3	15	0		21.79	21.59	21.64



LTE Band 12 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	23.62	23.54	23.57
5	1	12		23.36	23.26	23.28
5	1	24		23.10	22.99	23.00
5	12	0		22.86	22.73	22.73
5	12	6		22.60	22.45	22.52
5	12	11		22.32	22.17	22.27
5	25	0		22.10	21.94	22.01
5	1	0	16-QAM	23.39	23.25	23.35
5	1	12		23.09	23.00	23.11
5	1	24		22.81	22.70	22.84
5	12	0		22.59	22.45	22.59
5	12	6		22.36	22.24	22.38
5	12	11		22.13	21.99	22.13
5	25	0		21.92	21.75	21.88
10	1	0	QPSK	23.52	23.69	23.83
10	1	24		23.24	23.46	23.56
10	1	49		22.96	23.25	23.31
10	25	0		22.71	22.96	23.07
10	25	12		22.47	22.73	22.83
10	25	24		22.24	22.46	22.55
10	50	0		21.97	22.23	22.27
10	1	0	16-QAM	23.23	23.42	23.60
10	1	24		23.00	23.19	23.38
10	1	49		22.79	22.99	23.16
10	25	0		22.55	22.71	22.94
10	25	12		22.27	22.46	22.73
10	25	24		22.07	22.20	22.44
10	50	0		21.83	21.91	22.18



LTE BAND 13

LTE Band 13 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	21.11	21.10	21.18
5	1	12		20.90	20.84	20.95
5	1	24		20.66	20.56	20.73
5	12	0		20.46	20.35	20.44
5	12	6		20.23	20.10	20.16
5	12	11		19.99	19.89	19.90
5	25	0		19.76	19.61	19.67
5	1	0	16-QAM	20.88	20.88	20.94
5	1	12		20.67	20.65	20.68
5	1	24		20.47	20.35	20.39
5	12	0		20.23	20.06	20.10
5	12	6		19.97	19.82	19.87
5	12	11		19.71	19.54	19.63
5	25	0		19.49	19.25	19.33
10	1	0	QPSK	N/A	21.24	N/A
10	1	24		N/A	21.02	N/A
10	1	49		N/A	20.82	N/A
10	25	0		N/A	20.52	N/A
10	25	12		N/A	20.24	N/A
10	25	24		N/A	19.96	N/A
10	50	0		N/A	19.72	N/A
10	1	0	16-QAM	N/A	21.00	N/A
10	1	24		N/A	20.71	N/A
10	1	49		N/A	20.43	N/A
10	25	0		N/A	20.17	N/A
10	25	12		N/A	19.91	N/A
10	25	24		N/A	19.66	N/A
10	50	0		N/A	19.37	N/A



LTE BAND 17

LTE Band 17 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	21.24	21.18	21.19
5	1	12		20.99	20.95	20.97
5	1	24		20.72	20.68	20.67
5	12	0		20.50	20.46	20.42
5	12	6		20.28	20.21	20.14
5	12	11		19.99	19.97	19.88
5	25	0		19.71	19.72	19.59
5	1	0	16-QAM	20.95	20.96	20.92
5	1	12		20.69	20.70	20.65
5	1	24		20.46	20.40	20.41
5	12	0		20.22	20.20	20.17
5	12	6		19.98	19.92	19.92
5	12	11		19.74	19.68	19.68
5	25	0		19.53	19.46	19.39
10	1	0	QPSK	21.19	21.37	21.28
10	1	24		20.97	21.13	21.02
10	1	49		20.71	20.91	20.78
10	25	0		20.51	20.68	20.55
10	25	12		20.30	20.42	20.33
10	25	24		20.07	20.18	20.05
10	50	0		19.80	19.94	19.83
10	1	0	16-QAM	20.99	21.08	21.07
10	1	24		20.74	20.84	20.85
10	1	49		20.48	20.58	20.63
10	25	0		20.19	20.37	20.40
10	25	12		19.91	20.10	20.11
10	25	24		19.69	19.84	19.87
10	50	0		19.48	19.58	19.60



LTE BAND 25

LTE Band 25 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	21.05	21.09	21.15
1.4	1	2		20.76	20.87	20.87
1.4	1	5		20.49	20.61	20.63
1.4	3	0		20.22	20.33	20.41
1.4	3	1		20.00	20.05	20.20
1.4	3	2		19.75	19.77	19.93
1.4	6	0		19.47	19.54	19.73
1.4	1	0	16-QAM	20.78	20.87	20.93
1.4	1	2		20.50	20.67	20.73
1.4	1	5		20.25	20.42	20.44
1.4	3	0		20.00	20.17	20.23
1.4	3	1		19.73	19.93	19.97
1.4	3	2		19.49	19.66	19.68
1.4	6	0		19.22	19.37	19.39
3	1	0	QPSK	20.96	20.83	20.94
3	1	7		20.75	20.57	20.65
3	1	14		20.53	20.28	20.44
3	8	0		20.32	20.04	20.24
3	8	4		20.05	19.77	20.02
3	8	7		19.77	19.53	19.78
3	15	0		19.56	19.24	19.56
3	1	0	16-QAM	20.73	20.56	20.73
3	1	7		20.45	20.27	20.49
3	1	14		20.21	20.00	20.27
3	8	0		19.92	19.71	20.00
3	8	4		19.67	19.42	19.73
3	8	7		19.39	19.17	19.51
3	15	0		19.16	18.97	19.25



LTE Band 25 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	20.94	20.95	20.97
5	1	12		20.67	20.72	20.71
5	1	24		20.46	20.45	20.43
5	12	0		20.25	20.18	20.21
5	12	6		19.98	19.91	19.95
5	12	11		19.69	19.61	19.71
5	25	0		19.40	19.37	19.51
5	1	0	16-QAM	20.71	20.67	20.68
5	1	12		20.42	20.47	20.39
5	1	24		20.17	20.23	20.14
5	12	0		19.97	19.94	19.88
5	12	6		19.75	19.71	19.65
5	12	11		19.52	19.51	19.42
5	25	0		19.29	19.25	19.15
10	1	0	QPSK	20.99	21.03	21.08
10	1	24		20.73	20.76	20.83
10	1	49		20.49	20.49	20.62
10	25	0		20.29	20.23	20.37
10	25	12		20.04	19.98	20.14
10	25	24		19.78	19.73	19.88
10	50	0		19.51	19.50	19.60
10	1	0	16-QAM	20.76	20.76	20.86
10	1	24		20.53	20.51	20.60
10	1	49		20.28	20.28	20.39
10	25	0		20.04	20.07	20.14
10	25	12		19.79	19.77	19.85
10	25	24		19.59	19.51	19.62
10	50	0		19.37	19.26	19.42



LTE Band 25 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	21.18	21.12	21.13
15	1	37		20.95	20.87	20.90
15	1	74		20.68	20.67	20.66
15	36	0		20.48	20.45	20.37
15	36	18		20.27	20.18	20.10
15	36	39		20.06	19.95	19.81
15	75	0		19.81	19.74	19.51
15	1	0	16-QAM	20.92	20.91	20.93
15	1	38		20.64	20.62	20.71
15	1	75		20.35	20.34	20.49
15	36	0		20.10	20.08	20.24
15	36	18		19.81	19.88	20.01
15	36	39		19.55	19.66	19.80
15	75	0		19.33	19.46	19.57
20	1	0	QPSK	21.28	21.39	21.21
20	1	49		21.06	21.11	20.96
20	1	99		20.82	20.86	20.70
20	50	0		20.52	20.59	20.44
20	50	24		20.27	20.31	20.20
20	50	49		20.05	20.09	19.93
20	100	0		19.79	19.81	19.63
20	1	0	16-QAM	21.05	21.12	21.00
20	1	49		20.79	20.91	20.71
20	1	99		20.58	20.68	20.42
20	50	0		20.29	20.42	20.15
20	50	24		20.01	20.12	19.88
20	50	49		19.78	19.83	19.61
20	100	0		19.54	19.62	19.38



LTE BAND 26(Part22)

LTE Band 26 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	23.68	23.69	23.74
1.4	1	2		23.40	23.49	23.52
1.4	1	5		23.13	23.19	23.29
1.4	3	0		22.89	22.95	23.02
1.4	3	1		22.65	22.68	22.74
1.4	3	2		22.43	22.40	22.49
1.4	6	0		22.23	22.17	22.24
1.4	1	0	16-QAM	23.46	23.40	23.45
1.4	1	2		23.19	23.18	23.23
1.4	1	5		22.95	22.90	22.98
1.4	3	0		22.71	22.67	22.76
1.4	3	1		22.44	22.46	22.51
1.4	3	2		22.17	22.25	22.28
1.4	6	0		21.92	21.98	22.01
3	1	0	QPSK	23.61	23.57	23.50
3	1	7		23.41	23.27	23.30
3	1	14		23.17	23.05	23.08
3	8	0		22.90	22.77	22.87
3	8	4		22.68	22.56	22.57
3	8	7		22.47	22.32	22.31
3	15	0		22.25	22.04	22.10
3	1	0	16-QAM	23.39	23.33	23.24
3	1	7		23.17	23.04	22.97
3	1	14		22.91	22.81	22.69
3	8	0		22.65	22.59	22.47
3	8	4		22.42	22.30	22.19
3	8	7		22.18	22.01	21.90
3	15	0		21.92	21.76	21.65



LTE Band 26 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	23.85	23.85	23.88
5	1	12		23.64	23.57	23.67
5	1	24		23.35	23.37	23.44
5	12	0		23.10	23.10	23.20
5	12	6		22.81	22.80	22.94
5	12	11		22.51	22.54	22.74
5	25	0		22.31	22.26	22.51
5	1	0	16-QAM	23.55	23.57	23.67
5	1	12		23.34	23.28	23.40
5	1	24		23.06	23.01	23.18
5	12	0		22.81	22.80	22.92
5	12	6		22.53	22.51	22.71
5	12	11		22.27	22.25	22.46
5	25	0		22.00	21.96	22.18
10	1	0	QPSK	23.90	23.91	23.87
10	1	24		23.65	23.66	23.63
10	1	49		23.38	23.43	23.42
10	25	0		23.08	23.20	23.13
10	25	12		22.84	22.90	22.91
10	25	24		22.59	22.62	22.65
10	50	0		22.37	22.37	22.44
10	1	0	16-QAM	23.60	23.61	23.62
10	1	24		23.34	23.41	23.40
10	1	49		23.11	23.16	23.17
10	25	0		22.89	22.95	22.89
10	25	12		22.60	22.75	22.66
10	25	24		22.30	22.53	22.45
10	50	0		22.06	22.23	22.22



LTE Band 26 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	24.08	24.02	24.12
15	1	37		23.8	23.81	23.92
15	1	74		23.57	23.56	23.65
15	36	0		23.28	23.35	23.43
15	36	18		23.01	23.06	23.19
15	36	39		22.75	22.77	22.9
15	75	0		22.53	22.53	22.62
15	1	0	16-QAM	23.87	23.8	23.85
15	1	38		23.57	23.55	23.63
15	1	75		23.35	23.25	23.35
15	36	0		23.06	23.04	23.15
15	36	18		22.77	22.79	22.85
15	36	39		22.54	22.55	22.58
15	75	0		22.3	22.31	22.33



LTE BAND 26(Part90)

LTE Band 26 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	23.57	23.52	23.50
1.4	1	2		23.30	23.28	23.28
1.4	1	5		23.05	23.05	23.08
1.4	3	0		22.78	22.79	22.82
1.4	3	1		22.48	22.55	22.59
1.4	3	2		22.22	22.26	22.30
1.4	6	0		21.97	21.99	22.06
1.4	1	0	16-QAM	23.31	23.30	23.26
1.4	1	2		23.07	23.07	23.02
1.4	1	5		22.83	22.78	22.81
1.4	3	0		22.60	22.50	22.51
1.4	3	1		22.34	22.29	22.24
1.4	3	2		22.07	22.07	22.01
1.4	6	0		21.80	21.78	21.79
3	1	0	QPSK	23.46	23.49	23.55
3	1	7		23.22	23.21	23.31
3	1	14		22.96	23.01	23.09
3	8	0		22.67	22.72	22.88
3	8	4		22.45	22.50	22.62
3	8	7		22.17	22.25	22.32
3	15	0		21.90	22.02	22.10
3	1	0	16-QAM	23.17	23.26	23.27
3	1	7		22.90	23.04	23.02
3	1	14		22.66	22.82	22.76
3	8	0		22.38	22.52	22.53
3	8	4		22.12	22.25	22.24
3	8	7		21.82	21.98	21.98
3	15	0		21.58	21.77	21.74



LTE Band 26 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	23.63	23.59	23.61
5	1	12		23.41	23.31	23.36
5	1	24		23.20	23.02	23.13
5	12	0		22.99	22.78	22.85
5	12	6		22.70	22.55	22.61
5	12	11		22.44	22.28	22.36
5	25	0		22.24	21.98	22.09
5	1	0	16-QAM	23.35	23.34	23.40
5	1	12		23.06	23.07	23.16
5	1	24		22.84	22.80	22.88
5	12	0		22.60	22.56	22.59
5	12	6		22.39	22.31	22.34
5	12	11		22.18	22.02	22.10
5	25	0		21.89	21.76	21.83
10	1	0	QPSK	N/A	23.75	N/A
10	1	24		N/A	23.50	N/A
10	1	49		N/A	23.21	N/A
10	25	0		N/A	22.94	N/A
10	25	12		N/A	22.69	N/A
10	25	24		N/A	22.48	N/A
10	50	0		N/A	22.28	N/A
10	1	0	16-QAM	N/A	23.54	N/A
10	1	24		N/A	23.26	N/A
10	1	49		N/A	22.98	N/A
10	25	0		N/A	22.68	N/A
10	25	12		N/A	22.43	N/A
10	25	24		N/A	22.20	N/A
10	50	0		N/A	21.91	N/A



LTE BAND 38

SAR for LTE Band 38 (Frequency range: 2570-2620 MHz) is covered by LTE Band 41 (Frequency range: 2496-2690 MHz) due to overlapping frequency range, same maximum tune-up limit and same channel bandwidth

LTE BAND 41

LTE Band 41 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	20.55	20.61	20.68
5	1	12		20.32	20.39	20.42
5	1	24		20.11	20.11	20.13
5	12	0		19.90	19.82	19.92
5	12	6		19.66	19.59	19.63
5	12	11		19.41	19.29	19.33
5	25	0		19.13	19.00	19.11
5	1	0	16-QAM	20.29	20.34	20.42
5	1	12		20.00	20.10	20.16
5	1	24		19.80	19.81	19.90
5	12	0		19.54	19.53	19.66
5	12	6		19.33	19.32	19.45
5	12	11		19.04	19.03	19.19
5	25	0		18.76	18.79	18.97
10	1	0	QPSK	20.77	20.63	20.59
10	1	24		20.52	20.36	20.31
10	1	49		20.29	20.14	20.09
10	25	0		20.01	19.86	19.82
10	25	12		19.77	19.60	19.60
10	25	24		19.48	19.40	19.39
10	50	0		19.24	19.14	19.10
10	1	0	16-QAM	20.48	20.38	20.30
10	1	24		20.20	20.18	20.08
10	1	49		20.00	19.91	19.84
10	25	0		19.77	19.70	19.55
10	25	12		19.51	19.46	19.34
10	25	24		19.22	19.17	19.07
10	50	0		18.96	18.95	18.86



LTE Band 41 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	20.95	20.83	20.84
15	1	37		20.73	20.58	20.58
15	1	74		20.43	20.34	20.37
15	36	0		20.20	20.05	20.15
15	36	18		19.99	19.82	19.87
15	36	39		19.70	19.59	19.62
15	75	0		19.44	19.31	19.38
15	1	0	16-QAM	20.74	20.54	20.61
15	1	38		20.50	20.25	20.32
15	1	75		20.27	20.00	20.10
15	36	0		20.00	19.73	19.90
15	36	18		19.72	19.53	19.67
15	36	39		19.51	19.33	19.43
15	75	0		19.24	19.08	19.23
20	1	0	QPSK	21.00	21.05	21.01
20	1	49		20.75	20.83	20.80
20	1	99		20.54	20.58	20.52
20	50	0		20.27	20.30	20.32
20	50	24		20.00	20.04	20.07
20	50	49		19.73	19.82	19.79
20	100	0		19.53	19.56	19.51
20	1	0	16-QAM	20.72	20.79	20.77
20	1	49		20.47	20.56	20.51
20	1	99		20.20	20.28	20.29
20	50	0		19.93	20.01	20.09
20	50	24		19.64	19.80	19.82
20	50	49		19.36	19.54	19.52
20	100	0		19.08	19.32	19.24



LTE BAND 66

LTE Band 66 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	22.57	22.49	22.43
1.4	1	2		22.31	22.23	22.15
1.4	1	5		22.06	22.00	21.94
1.4	3	0		21.79	21.79	21.74
1.4	3	1		21.54	21.58	21.50
1.4	3	2		21.26	21.36	21.25
1.4	6	0		21.00	21.07	20.96
1.4	1	0	16-QAM	22.34	22.20	22.14
1.4	1	2		22.05	22.00	21.85
1.4	1	5		21.76	21.72	21.58
1.4	3	0		21.46	21.46	21.36
1.4	3	1		21.18	21.20	21.14
1.4	3	2		20.98	20.90	20.87
1.4	6	0		20.72	20.62	20.58
3	1	0	QPSK	22.63	22.59	22.56
3	1	7		22.41	22.39	22.30
3	1	14		22.19	22.11	22.01
3	8	0		21.98	21.85	21.80
3	8	4		21.73	21.62	21.60
3	8	7		21.47	21.32	21.34
3	15	0		21.22	21.12	21.12
3	1	0	16-QAM	22.42	22.39	22.36
3	1	7		22.13	22.16	22.06
3	1	14		21.92	21.88	21.84
3	8	0		21.63	21.63	21.55
3	8	4		21.43	21.36	21.33
3	8	7		21.19	21.09	21.09
3	15	0		20.97	20.79	20.81



LTE Band 66 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	22.41	22.37	22.51
5	1	12		22.12	22.11	22.25
5	1	24		21.88	21.87	22.04
5	12	0		21.62	21.58	21.77
5	12	6		21.38	21.29	21.48
5	12	11		21.17	21.08	21.23
5	25	0		20.90	20.83	20.98
5	1	0	16-QAM	22.19	22.12	22.23
5	1	12		21.91	21.90	21.98
5	1	24		21.67	21.68	21.78
5	12	0		21.40	21.41	21.50
5	12	6		21.18	21.15	21.26
5	12	11		20.89	20.95	21.04
5	25	0		20.61	20.71	20.80
10	1	0	QPSK	22.40	22.44	22.43
10	1	24		22.13	22.14	22.19
10	1	49		21.90	21.94	21.93
10	25	0		21.62	21.73	21.69
10	25	12		21.33	21.50	21.39
10	25	24		21.03	21.28	21.10
10	50	0		20.79	21.05	20.83
10	1	0	16-QAM	22.10	22.17	22.14
10	1	24		21.89	21.96	21.85
10	1	49		21.68	21.75	21.61
10	25	0		21.45	21.53	21.39
10	25	12		21.22	21.29	21.17
10	25	24		20.97	21.09	20.90
10	50	0		20.73	20.89	20.60



LTE Band 66 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	22.59	22.55	22.53
15	1	37		22.33	22.29	22.27
15	1	74		22.08	22.02	22.00
15	36	0		21.83	21.74	21.77
15	36	18		21.58	21.53	21.50
15	36	39		21.33	21.33	21.28
15	75	0		21.11	21.04	21.04
15	1	0	16-QAM	22.30	22.27	22.32
15	1	38		22.08	22.01	22.03
15	1	75		21.78	21.80	21.80
15	36	0		21.53	21.53	21.50
15	36	18		21.32	21.31	21.26
15	36	39		21.11	21.02	21.06
15	75	0		20.83	20.76	20.86
20	1	0	QPSK	22.67	22.73	22.65
20	1	49		22.39	22.44	22.41
20	1	99		22.19	22.16	22.21
20	50	0		21.93	21.94	21.99
20	50	24		21.64	21.66	21.72
20	50	49		21.39	21.46	21.44
20	100	0		21.15	21.25	21.22
20	1	0	16-QAM	22.37	22.49	22.44
20	1	49		22.16	22.22	22.16
20	1	99		21.88	21.97	21.95
20	50	0		21.66	21.69	21.71
20	50	24		21.45	21.42	21.47
20	50	49		21.24	21.19	21.18
20	100	0		21.03	20.91	20.91



10.2 SAR Test Exclusions Applied

Per FCC KDB 447498D01, the 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

$$\frac{\text{Max Power of Channel (mW)}}{\text{Test Separation Dist (mm)}} * \sqrt{\text{Frequency (GHz)}} \leq 3.0$$

Based on the maximum conducted power of **Bluetooth Head** (rounded to the nearest mW) and the antenna to user separation distance,

Bluetooth Head SAR was not required; $[(7.943/5) * \sqrt{2.480}] = 2.50 < 3.0$.

Based on the maximum conducted power of **Bluetooth Body** (rounded to the nearest mW) and the antenna to user separation distance,

Bluetooth Body SAR was not required; $[(7.943/10) * \sqrt{2.480}] = 1.25 < 3.0$.

Based on the maximum conducted power of **2.4 GHz WLAN Head** (rounded to the nearest mW) and the antenna to user separation distance,

2.4 GHz WLAN SAR was required; $[(25.119/5) * \sqrt{2.462}] = 7.88 > 3.0$.

Based on the maximum conducted power of **2.4 GHz WLAN Body** (rounded to the nearest mW) and the antenna to user separation distance,

2.4 GHz WLAN SAR was required; $[(25.119/10) * \sqrt{2.462}] = 3.94 > 3.0$.

Based on the maximum conducted power of **5.2 GHz WLAN Head** (rounded to the nearest mW) and the antenna to user separation distance,

5.2 GHz WLAN SAR was not required; $[(5.012/5) * \sqrt{5.200}] = 2.29 < 3.0$.

Based on the maximum conducted power of **5.2 GHz WLAN Body** (rounded to the nearest mW) and the antenna to user separation distance,

5.2 GHz WLAN SAR was not required; $[(5.012/10) * \sqrt{5.200}] = 1.14 < 3.0$.

Based on the maximum conducted power of **5.3 GHz WLAN Head** (rounded to the nearest mW) and the antenna to user separation distance,

5.4 GHz WLAN SAR was not required; $[(5.012/5) * \sqrt{5.300}] = 2.31 < 3.0$.

Based on the maximum conducted power of **5.3 GHz WLAN Body** (rounded to the nearest mW) and the antenna to user separation distance,

5.4 GHz WLAN SAR was not required; $[(5.012/10) * \sqrt{5.300}] = 1.15 < 3.0$.



Based on the maximum conducted power of **5.6 GHz WLAN Head** (rounded to the nearest mW) and the antenna to user separation distance,

5.6 GHz WLAN SAR was not required; $[(5.012/5)^* \sqrt{5.600}] = 2.37 < 3.0$.

Based on the maximum conducted power of **5.6 GHz WLAN Body** (rounded to the nearest mW) and the antenna to user separation distance,

5.6 GHz WLAN SAR was not required; $[(5.012/10)^* \sqrt{5.600}] = 1.19 < 3.0$.

Based on the maximum conducted power of **5.8 GHz WLAN Head** (rounded to the nearest mW) and the antenna to user separation distance,

5.8 GHz WLAN SAR was required; $[(6.310/5)^* \sqrt{5.800}] = 3.04 > 3.0$.

Based on the maximum conducted power of **5.8 GHz WLAN Body** (rounded to the nearest mW) and the antenna to user separation distance,

5.8 GHz WLAN SAR was not required; $[(5.012/10)^* \sqrt{5.800}] = 1.52 < 3.0$.



11. EUT and Test Setup Photo

11.1 EUT Photo

Front side




Back side




Top side




Bottom side



Left side




Right side




11.2 Setup Photo


Right Touch




Right Tilt




Left Touch




Left Tilt




Body Front side(separation distance is 10mm)



Body Back side(separation distance is 10mm)



Left Edge(separation distance is 10mm)



Right Edge(separation distance is 10mm)




Top Edge(separation distance is 10mm)



Bottom Edge(separation distance is 10mm)




Walkie-talkie mode Front of face(separation distance is 25mm)



Walkie-talkie mode Limbs(separation distance is 0mm)



Liquid depth (15 cm)





12. SAR Result Summary

12.1 Head SAR

Band	Mode	Test Position	Ch.	Result 1g (W/Kg)	Power Drift(%)	Max.Turn-up Power(dBm)	Meas.Output Power(dBm)	Scaled SAR (W/Kg)	Meas. No.
GSM 850	GPRS Data-4 Slot	Right Cheek	251	0.212	-0.81	31	30.36	0.246	1
		Right Tilt	251	0.138	3.31	31	30.36	0.160	/
		Left Cheek	251	0.175	2.56	31	30.36	0.203	/
		Left Tilt	251	0.093	-2.76	31	30.36	0.108	/
GSM1900	GPRS Data-4 Slot	Right Cheek	512	0.218	3.27	27	26.20	0.262	3
		Right Tilt	512	0.130	1.45	27	26.20	0.156	/
		Left Cheek	512	0.187	-3.66	27	26.20	0.225	/
		Left Tilt	512	0.114	-2.23	27	26.20	0.137	/
WCDMA II	RMC	Right Cheek	9538	0.133	3.86	21.5	21	0.149	5
		Right Tilt	9538	0.070	0.64	21.5	21	0.079	/
		Left Cheek	9538	0.114	-3.24	21.5	21	0.128	/
		Left Tilt	9538	0.062	-3.33	21.5	21	0.070	/
WCDMA IV	RMC	Right Cheek	1312	0.069	-2.20	22	21.61	0.075	7
		Right Tilt	1312	0.035	2.25	22	21.61	0.038	/
		Left Cheek	1312	0.052	2.83	22	21.61	0.057	/
		Left Tilt	1312	0.027	2.94	22	21.61	0.030	/
WCDMA V	RMC	Right Cheek	4132	0.194	0.25	22	21.07	0.240	9
		Right Tilt	4132	0.107	0.70	22	21.07	0.133	/
		Left Cheek	4132	0.162	-3.42	22	21.07	0.201	/
		Left Tilt	4132	0.085	3.47	22	21.07	0.105	/



Band	Mode	Test Position	Ch.	Result 1g (W/Kg)	Power Drift(%)	Max.Turn-up Power(dBm)	Meas.Output Power(dBm)	Duty cycle(%)	Scaled SAR (W/Kg)	Meas. No.
2.4G WLAN	802.11b	Right Cheek	1	0.147	-0.92	14	13.91	100	0.150	11
		Right Tilt	1	0.124	2.01	14	13.91	100	0.127	/
		Left Cheek	1	0.130	-3.67	14	13.91	100	0.133	/
		Left Tilt	1	0.116	-0.34	14	13.91	100	0.118	/
5.8G WLAN	802.11a	Right Cheek	149	0.639	-3.07	8	7.81	100	0.668	35
		Right Tilt	149	0.614	-2.78	8	7.81	100	0.641	/
		Left Cheek	149	0.586	1.23	8	7.81	100	0.612	/
		Left Tilt	149	0.532	0.68	8	7.81	100	0.556	/

Note:

- Per KDB 447498 D01, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
 - Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
 - For WWAN: Scaled SAR(W/kg)= Measured SAR(W/kg)*Tune-up Scaling Factor
- Per KDB 248227- When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg. (The highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power was 0.017W/Kg for Head)
- Per KDB865664 D01, Repeated measurement is not required when the original highest measured SAR is <0.80 W/kg



Band	BW (MHz)	Mod.	RB Size	RB offset	Test Position	Ch.	Result 1g (W/Kg)	Power Drift(%)	Max. Turn-up Power(dBm)	Meas. Output Power(dBm)	Scaled SAR (W/Kg)	Meas. No.
LTE Band 2	20M	QPSK	1	0	Right Cheek	18700	0.225	-2.43	23	22.35	0.261	13
			50	0	Right Cheek	18700	0.187	-0.46	22	21.59	0.206	/
			1	0	Right Tilt	18700	0.141	0.38	23	22.35	0.164	/
			50	0	Right Tilt	18700	0.112	-2.52	22	21.59	0.123	/
			1	0	Left Cheek	18700	0.198	3.83	23	22.35	0.230	/
			50	0	Left Cheek	18700	0.126	0.99	22	21.59	0.138	/
			1	0	Left Tilt	18700	0.113	-0.69	23	22.35	0.131	/
			50	0	Left Tilt	18700	0.057	0.23	22	21.59	0.063	/
LTE Band 4	20M	QPSK	1	0	Right Cheek	20300	0.257	-1.30	22	21.91	0.262	15
			50	0	Right Cheek	20300	0.204	3.65	22	21.22	0.244	/
			1	0	Right Tilt	20300	0.138	1.01	22	21.91	0.141	/
			50	0	Right Tilt	20300	0.113	-3.15	22	21.22	0.135	/
			1	0	Left Cheek	20300	0.225	0.28	22	21.91	0.230	/
			50	0	Left Cheek	20300	0.173	-0.94	22	21.22	0.207	/
			1	0	Left Tilt	20300	0.131	2.32	22	21.91	0.134	/
			50	0	Left Tilt	20300	0.095	1.58	22	21.22	0.114	/
LTE Band 5	10M	QPSK	1	0	Right Cheek	20600	0.178	-0.42	24	23.81	0.186	17
			25	0	Right Cheek	20600	0.125	-1.65	24	23.13	0.153	/
			1	0	Right Tilt	20600	0.081	-1.90	24	23.81	0.085	/
			25	0	Right Tilt	20600	0.063	-3.85	24	23.13	0.077	/
			1	0	Left Cheek	20600	0.145	-2.99	24	23.81	0.151	/
			25	0	Left Cheek	20600	0.089	1.04	24	23.13	0.109	/
			1	0	Left Tilt	20600	0.070	3.85	24	23.81	0.073	/
			25	0	Left Tilt	20600	0.041	2.74	24	23.13	0.050	/
LTE Band 7	20M	QPSK	1	0	Right Cheek	20850	0.067	0.47	21	20.35	0.078	19
			50	0	Right Cheek	20850	0.044	2.31	20	19.65	0.048	/
			1	0	Right Tilt	20850	0.036	-0.22	21	20.35	0.042	/
			50	0	Right Tilt	20850	0.028	-2.39	20	19.65	0.030	/
			1	0	Left Cheek	20850	0.055	-2.65	21	20.35	0.064	/
			50	0	Left Cheek	20850	0.031	3.94	20	19.65	0.034	/
			1	0	Left Tilt	20850	0.027	2.53	21	20.35	0.031	/
			50	0	Left Tilt	20850	0.015	2.41	20	19.65	0.016	/
LTE Band 12	10M	QPSK	1	0	Right Cheek	23130	0.057	3.36	24	23.83	0.059	21
			25	0	Right Cheek	23130	0.039	-1.80	24	23.07	0.048	/
			1	0	Right Tilt	23130	0.026	3.52	24	23.83	0.027	/
			25	0	Right Tilt	23130	0.020	2.28	24	23.07	0.025	/
			1	0	Left Cheek	23130	0.043	2.11	24	23.83	0.045	/
			25	0	Left Cheek	23130	0.030	1.21	24	23.07	0.037	/
			1	0	Left Tilt	23130	0.027	-0.40	24	23.83	0.028	/
			25	0	Left Tilt	23130	0.021	-2.60	24	23.07	0.026	/



LTE Band 13	10M	QPSK	1	0	Right Cheek	23230	0.071	3.82	22	21.24	0.085	23
			25	0	Right Cheek	23230	0.053	-3.55	21	20.52	0.059	/
			1	0	Right Tilt	23230	0.045	3.95	22	21.24	0.054	/
			25	0	Right Tilt	23230	0.030	-2.41	21	20.52	0.034	/
			1	0	Left Cheek	23230	0.063	-2.59	22	21.24	0.075	/
			25	0	Left Cheek	23230	0.038	-3.77	21	20.52	0.042	/
			1	0	Left Tilt	23230	0.035	-3.12	22	21.24	0.042	/
			25	0	Left Tilt	23230	0.020	1.60	21	20.52	0.022	/
LTE Band 17	10M	QPSK	1	0	Right Cheek	23790	0.072	2.56	22	21.37	0.083	25
			25	0	Right Cheek	23790	0.045	3.81	21	20.68	0.048	/
			1	0	Right Tilt	23790	0.057	-3.51	22	21.37	0.066	/
			25	0	Right Tilt	23790	0.032	0.90	21	20.68	0.034	/
			1	0	Left Cheek	23790	0.065	-3.93	22	21.37	0.075	/
			25	0	Left Cheek	23790	0.043	2.07	21	20.68	0.046	/
			1	0	Left Tilt	23790	0.030	3.39	22	21.37	0.035	/
			25	0	Left Tilt	23790	0.019	0.33	21	20.68	0.020	/
LTE Band 25	20M	QPSK	1	0	Right Cheek	26365	0.246	-1.14	22	21.39	0.283	27
			50	0	Right Cheek	26365	0.183	1.47	21	20.59	0.201	/
			1	0	Right Tilt	26365	0.118	-1.88	22	21.39	0.136	/
			50	0	Right Tilt	26365	0.095	2.57	21	20.59	0.104	/
			1	0	Left Cheek	26365	0.214	-0.13	22	21.39	0.246	/
			50	0	Left Cheek	26365	0.157	-2.16	21	20.59	0.173	/
			1	0	Left Tilt	26365	0.102	3.96	22	21.39	0.117	/
			50	0	Left Tilt	26365	0.088	3.89	21	20.59	0.097	/
LTE Band 26	15M (part22)	QPSK	1	0	Right Cheek	26965	0.167	-0.55	25	24.12	0.205	29
			36	0	Right Cheek	26965	0.115	2.43	24	23.43	0.131	/
			1	0	Right Tilt	26965	0.078	3.02	25	24.12	0.096	/
			36	0	Right Tilt	26965	0.047	3.25	24	23.43	0.054	/
			1	0	Left Cheek	26965	0.133	1.56	25	24.12	0.163	/
			36	0	Left Cheek	26965	0.096	-0.51	24	23.43	0.109	/
			1	0	Left Tilt	26965	0.053	-1.43	25	24.12	0.065	/
			36	0	Left Tilt	26965	0.038	-0.67	24	23.43	0.043	/
	10M (part90)	QPSK	1	0	Right Cheek	26865	0.143	-3.23	24	23.75	0.151	/
			50	0	Right Cheek	26865	0.105	2.86	23	22.94	0.106	/
			1	0	Right Tilt	26865	0.077	1.82	24	23.75	0.082	/
			50	0	Right Tilt	26865	0.054	3.50	23	22.94	0.055	/
			1	0	Left Cheek	26865	0.116	0.14	24	23.75	0.123	/
			50	0	Left Cheek	26865	0.072	0.65	23	22.94	0.073	/
			1	0	Left Tilt	26865	0.074	-0.16	24	23.75	0.078	/
			50	0	Left Tilt	26865	0.041	1.84	23	22.94	0.042	/



LTE Band 41	20M	QPSK	1	0	Right Cheek	40620	0.039	-0.04	22	21.05	0.049	31
			50	0	Right Cheek	41490	0.024	-2.78	21	20.32	0.028	/
			1	0	Right Tilt	40620	0.026	-0.96	22	21.05	0.032	/
			50	0	Right Tilt	41490	0.013	1.36	21	20.32	0.015	/
			1	0	Left Cheek	40620	0.031	-2.58	22	21.05	0.039	/
			50	0	Left Cheek	41490	0.020	-2.04	21	20.32	0.023	/
			1	0	Left Tilt	40620	0.015	-1.69	22	21.05	0.019	/
			50	0	Left Tilt	41490	0.009	0.39	21	20.32	0.011	/
LTE Band 66	20M	QPSK	1	0	Right Cheek	132322	0.168	2.70	23	22.73	0.179	33
			50	0	Right Cheek	132572	0.115	1.08	22	21.99	0.115	/
			1	0	Right Tilt	132322	0.092	1.54	23	22.73	0.098	/
			50	0	Right Tilt	132572	0.066	-1.24	22	21.99	0.066	/
			1	0	Left Cheek	132322	0.143	-2.01	23	22.73	0.152	/
			50	0	Left Cheek	132572	0.089	-2.56	22	21.99	0.089	/
			1	0	Left Tilt	132322	0.077	2.07	23	22.73	0.082	/
			50	0	Left Tilt	132572	0.045	0.75	22	21.99	0.045	/



12.2 Body-worn and Hotspot SAR

Band	Mode	Test Position	Ch.	Result 1g (W/Kg)	Power Drift(%)	Max.Turn-up Power(dBm)	Meas.Output Power(dBm)	Scaled SAR (W/Kg)	Meas. No.
GSM 850	GPRS Data-4 Slot	Front side	251	0.194	2.45	31	30.36	0.225	/
		Back side	251	0.372	-1.18	31	30.36	0.431	2
		Left side	251	0.235	-1.39	31	30.36	0.272	/
		Right side	251	0.113	-0.68	31	30.36	0.131	/
		Bottom side	251	0.066	-3.38	31	30.36	0.076	/
GSM1900	GPRS Data-4 Slot	Front side	512	0.345	3.82	27	26.20	0.415	/
		Back side	512	0.388	0.15	27	26.20	0.466	4
		Left side	512	0.226	3.73	27	26.20	0.272	/
		Right side	512	0.057	0.01	27	26.20	0.069	/
		Bottom side	512	0.271	-0.60	27	26.20	0.326	/
WCDMA II	RMC	Front side	9538	0.183	-4.00	21.5	21	0.205	/
		Back side	9538	0.328	2.09	21.5	21	0.368	6
		Left side	9538	0.211	-2.70	21.5	21	0.237	/
		Right side	9538	0.056	2.72	21.5	21	0.063	/
		Bottom side	9538	0.189	-1.35	21.5	21	0.212	/
WCDMA IV	RMC	Front side	1312	0.075	1.46	22	21.61	0.082	/
		Back side	1312	0.100	-1.24	22	21.61	0.109	8
		Left side	1312	0.032	-1.90	22	21.61	0.035	/
		Right side	1312	0.067	-2.20	22	21.61	0.073	/
		Bottom side	1312	0.054	-0.73	22	21.61	0.059	/
WCDMA V	RMC	Front side	4132	0.281	-0.18	22	21.07	0.348	/
		Back side	4132	0.356	2.24	22	21.07	0.441	10
		Left side	4132	0.079	3.66	22	21.07	0.098	/
		Right side	4132	0.203	-3.41	22	21.07	0.251	/
		Bottom side	4132	0.118	-2.27	22	21.07	0.146	/



Band	Mode	Test Position	Ch.	Result 1g (W/Kg)	Power Drift(%)	Max.Turn-up Power(dBm)	Meas.Output Power(dBm)	Duty cycle(%)	Scaled SAR (W/Kg)	Meas. No.
WLAN	802.11b	Front side	1	0.028	1.38	14	13.91	100	0.029	/
		Back side	1	0.045	2.36	14	13.91	100	0.046	12
		Right side	1	0.021	0.24	14	13.91	100	0.021	/
		Top side	1	0.034	-0.75	14	13.91	100	0.035	/

Note:

1. The test separation of all above table is 10mm.
2. Per KDB 447498 D01, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
 - a. Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
 - b. For WWAN: Scaled SAR(W/kg)= Measured SAR(W/kg)*Tune-up Scaling Factor
3. Per KDB 248227- When the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg. (The highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power was 0.005 W/Kg for Body)
4. When the user enables the personal Wireless router functions for the handsets, actual operations include simultaneous transmission of both the Wi-Fi transmitting frequency and thus cannot be evaluated for SAR under actual use conditions. The "Portable Hotspot" feature on the handset was NOT activated, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal.



Band	BW (MHz)	Mod.	RB Size	RB offset	Test Position	Ch.	Result 1g (W/Kg)	Power Drift(%)	Max. Turn-up Power(dBm)	Meas. Output Power(dBm)	Scaled SAR (W/Kg)	Meas. No.
LTE Band 2	20M	QPSK	1	0	Front side	18700	0.239	3.83	23	22.35	0.278	/
			50	0	Front side	18700	0.187	-2.51	22	21.59	0.206	/
			1	0	Back Side	18700	0.273	-3.56	23	22.35	0.317	14
			50	0	Back Side	18700	0.222	-0.86	22	21.59	0.244	/
			1	0	Left Side	18700	0.068	-3.31	23	22.35	0.079	/
			50	0	Left Side	18700	0.035	1.92	22	21.59	0.038	/
			1	0	Right Side	18700	0.211	2.22	23	22.35	0.245	/
			50	0	Right Side	18700	0.154	0.11	22	21.59	0.169	/
			1	0	Bottom Side	18700	0.177	2.84	23	22.35	0.206	/
			50	0	Bottom Side	18700	0.132	2.41	22	21.59	0.145	/
LTE Band 4	20M	QPSK	1	0	Front side	20300	0.326	3.95	22	21.91	0.333	/
			50	0	Front side	20300	0.281	0.83	22	21.22	0.336	/
			1	0	Back Side	20300	0.373	3.89	22	21.91	0.381	16
			50	0	Back Side	20300	0.308	-1.39	22	21.22	0.369	/
			1	0	Left Side	20300	0.112	-3.75	22	21.91	0.114	/
			50	0	Left Side	20300	0.085	-2.91	22	21.22	0.102	/
			1	0	Right Side	20300	0.257	1.43	22	21.91	0.262	/
			50	0	Right Side	20300	0.192	-0.72	22	21.22	0.230	/
			1	0	Bottom Side	20300	0.267	1.30	22	21.91	0.273	/
			50	0	Bottom Side	20300	0.213	1.71	22	21.22	0.255	/
LTE Band 5	10M	QPSK	1	0	Front side	20600	0.228	1.13	24	23.81	0.238	/
			25	0	Front side	20600	0.161	-0.77	24	23.13	0.197	/
			1	0	Back Side	20600	0.294	-2.39	24	23.81	0.307	18
			25	0	Back Side	20600	0.237	2.65	24	23.13	0.290	/
			1	0	Left Side	20600	0.071	0.85	24	23.81	0.074	/
			25	0	Left Side	20600	0.046	-2.32	24	23.13	0.056	/
			1	0	Right Side	20600	0.183	3.57	24	23.81	0.191	/
			25	0	Right Side	20600	0.135	2.84	24	23.13	0.165	/
			1	0	Bottom Side	20600	0.231	1.45	24	23.81	0.241	/
			25	0	Bottom Side	20600	0.156	-1.40	24	23.13	0.191	/
LTE Band 7	20M	QPSK	1	0	Front side	20850	0.232	-2.57	21	20.35	0.269	/
			50	0	Front side	20850	0.185	0.94	20	19.65	0.201	/
			1	0	Back Side	20850	0.280	-1.31	21	20.35	0.325	20
			50	0	Back Side	20850	0.217	-0.69	20	19.65	0.235	/
			1	0	Left Side	20850	0.089	2.52	21	20.35	0.103	/
			50	0	Left Side	20850	0.051	-3.25	20	19.65	0.055	/
			1	0	Right Side	20850	0.148	-0.11	21	20.35	0.172	/
			50	0	Right Side	20850	0.093	2.53	20	19.65	0.101	/
			1	0	Bottom Side	20850	0.169	-3.02	21	20.35	0.196	/
			50	0	Bottom Side	20850	0.115	-0.38	20	19.65	0.125	/



LTE Band 12	10M	QPSK	1	0	Front side	23130	0.223	-1.92	24	23.83	0.232	/
			25	0	Front side	23130	0.178	0.21	24	23.07	0.221	/
			1	0	Back Side	23130	0.253	2.36	24	23.83	0.263	22
			25	0	Back Side	23130	0.217	3.06	24	23.07	0.269	/
			1	0	Left Side	23130	0.085	2.29	24	23.83	0.088	/
			25	0	Left Side	23130	0.056	1.52	24	23.07	0.069	/
			1	0	Right Side	23130	0.198	1.74	24	23.83	0.206	/
			25	0	Right Side	23130	0.152	-2.87	24	23.07	0.188	/
			1	0	Bottom Side	23130	0.147	-0.88	24	23.83	0.153	/
			25	0	Bottom Side	23130	0.094	1.74	24	23.07	0.116	/
LTE Band 13	10M	QPSK	1	0	Front side	23230	0.016	2.45	22	21.24	0.019	/
			25	0	Front side	23230	0.009	3.89	21	20.52	0.010	/
			1	0	Back Side	23230	0.025	-3.23	22	21.24	0.030	24
			25	0	Back Side	23230	0.017	-1.22	21	20.52	0.019	/
			1	0	Left Side	23230	0.009	-1.17	22	21.24	0.011	/
			25	0	Left Side	23230	0.005	3.20	21	20.52	0.006	/
			1	0	Right Side	23230	0.011	-1.95	22	21.24	0.013	/
			25	0	Right Side	23230	0.007	-1.00	21	20.52	0.008	/
			1	0	Bottom Side	23230	0.019	-1.63	22	21.24	0.023	/
			25	0	Bottom Side	23230	0.014	1.10	21	20.52	0.016	/
LTE Band 17	10M	QPSK	1	0	Front side	23790	0.211	-2.53	22	21.37	0.244	/
			25	0	Front side	23790	0.168	1.58	21	20.68	0.181	/
			1	0	Back Side	23790	0.252	-1.87	22	21.37	0.291	26
			25	0	Back Side	23790	0.187	2.86	21	20.68	0.201	/
			1	0	Left Side	23790	0.043	-0.24	22	21.37	0.050	/
			25	0	Left Side	23790	0.028	3.81	21	20.68	0.030	/
			1	0	Right Side	23790	0.155	0.87	22	21.37	0.179	/
			25	0	Right Side	23790	0.112	-3.05	21	20.68	0.121	/
			1	0	Bottom Side	23790	0.127	3.69	22	21.37	0.147	/
			25	0	Bottom Side	23790	0.085	-3.94	21	20.68	0.091	/
LTE Band 25	20M	QPSK	1	0	Front side	26365	0.172	2.70	22	21.39	0.198	/
			50	0	Front side	26365	0.120	0.15	21	20.59	0.132	/
			1	0	Back Side	26365	0.247	3.89	22	21.39	0.284	28
			50	0	Back Side	26365	0.183	-1.33	21	20.59	0.201	/
			1	0	Left Side	26365	0.057	3.70	22	21.39	0.066	/
			50	0	Left Side	26365	0.035	-2.60	21	20.59	0.038	/
			1	0	Right Side	26365	0.161	-1.31	22	21.39	0.185	/
			50	0	Right Side	26365	0.118	-3.06	21	20.59	0.130	/
			1	0	Bottom Side	26365	0.163	0.53	22	21.39	0.188	/
			50	0	Bottom Side	26365	0.125	-0.08	21	20.59	0.137	/



LTE Band 26	15M (Part22)	QPSK	1	0	Front side	26965	0.314	0.49	25	24.12	0.385	/
			36	0	Front side	26965	0.249	-1.66	24	23.43	0.284	/
			1	0	Back Side	26965	0.356	-0.09	25	24.12	0.436	30
			36	0	Back Side	26965	0.283	-3.06	24	23.43	0.323	/
			1	0	Left Side	26965	0.128	3.20	25	24.12	0.157	/
			36	0	Left Side	26965	0.093	-2.35	24	23.43	0.106	/
			1	0	Right Side	26965	0.236	-2.87	25	24.12	0.289	/
			36	0	Right Side	26965	0.181	3.68	24	23.43	0.206	/
			1	0	Bottom Side	26965	0.277	2.75	25	24.12	0.339	/
			36	0	Bottom Side	26965	0.223	-1.44	24	23.43	0.254	/
	10M (Part90)	QPSK	1	0	Front side	26865	0.276	3.74	24	23.75	0.292	/
			50	0	Front side	26865	0.223	3.04	23	22.94	0.226	/
			1	0	Back Side	26865	0.314	1.52	24	23.75	0.333	/
			50	0	Back Side	26865	0.228	-3.76	23	22.94	0.231	/
			1	0	Left Side	26865	0.073	0.97	24	23.75	0.077	/
			50	0	Left Side	26865	0.045	-0.57	23	22.94	0.046	/
			1	0	Right Side	26865	0.143	-1.23	24	23.75	0.151	/
			50	0	Right Side	26865	0.088	3.37	23	22.94	0.089	/
			1	0	Bottom Side	26865	0.125	1.53	24	23.75	0.132	/
			50	0	Bottom Side	26865	0.078	3.53	23	22.94	0.079	/
LTE Band 41	20M	QPSK	1	0	Front side	40620	0.274	0.52	22	21.05	0.341	/
			50	0	Front side	41490	0.211	3.38	21	20.32	0.247	/
			1	0	Back Side	40620	0.334	-1.36	22	21.05	0.416	32
			50	0	Back Side	41490	0.276	2.17	21	20.32	0.323	/
			1	0	Left Side	40620	0.098	-3.29	22	21.05	0.122	/
			50	0	Left Side	41490	0.055	1.28	21	20.32	0.064	/
			1	0	Right Side	40620	0.212	2.38	22	21.05	0.264	/
			50	0	Right Side	41490	0.137	3.46	21	20.32	0.160	/
			1	0	Bottom Side	40620	0.150	-0.39	22	21.05	0.187	/
			50	0	Bottom Side	41490	0.096	2.30	21	20.32	0.112	/
LTE Band 66	20M	QPSK	1	0	Front side	132322	0.283	-0.93	23	22.73	0.301	/
			50	0	Front side	132572	0.199	-2.63	22	21.99	0.199	/
			1	0	Back Side	132322	0.336	3.90	23	22.73	0.358	34
			50	0	Back Side	132572	0.251	0.69	22	21.99	0.252	/
			1	0	Left Side	132322	0.133	1.74	23	22.73	0.142	/
			50	0	Left Side	132572	0.076	-0.46	22	21.99	0.076	/
			1	0	Right Side	132322	0.218	2.07	23	22.73	0.232	/
			50	0	Right Side	132572	0.143	-1.52	22	21.99	0.143	/
			1	0	Bottom Side	132322	0.277	0.64	23	22.73	0.295	/
			50	0	Bottom Side	132572	0.189	-0.99	22	21.99	0.189	/

LTE BAND 38

SAR for LTE Band 38 (Frequency range: 2570-2620 MHz) is covered by LTE Band 41 (Frequency range: 2496-2690 MHz) due to overlapping frequency range, same maximum tune-up limit and same channel bandwidth

**Analogue**

Phantom Configurations	Frequency (MHz)	Channel	Power Drift(%)	SAR 1g with 100% duty cycle (W/Kg)	SAR 1g with 50% duty cycle (W/Kg)	Max. Turn-up Power (dBm)	Meas. Output Power (dBm)	Scaled SAR (W/Kg)	Meas. No.
Front of face	450.0125	1	1.34	0.242	0.121	33	32.162	0.147	36
Limbs	450.0125	1	-0.57	0.371	0.186	33	32.162	0.226	37

Data

Phantom Configurations	Frequency (MHz)	Channel	Power Drift(%)	SAR 1g with 100% duty cycle (W/Kg)	SAR 1g with 50% duty cycle (W/Kg)	Max. Turn-up Power (dBm)	Meas. Output Power (dBm)	Scaled SAR (W/Kg)	Meas. No.
Front of face	450.0125	1	1.89	0.225	0.113	33	32.616	0.123	38
Limbs	450.0125	1	-1.15	0.384	0.192	33	32.616	0.210	39



**Simultaneous Multi-band Transmission Evaluation:**

Application Simultaneous Transmission information:

Position	Simultaneous State
Head	1. GSM + WLAN
	2. GSM + Bluetooth
	3. WCDMA + WLAN
	4. WCDMA + Bluetooth
	5. LTE + WLAN
	6. LTE + Bluetooth
Body	1. GSM + WLAN
	2. GSM + Bluetooth
	3. WCDMA + WLAN
	4. WCDMA + Bluetooth
	5. LTE + WLAN
	6. LTE + Bluetooth

NOTE:

1. Bluetooth and WLAN can't simultaneous transmission at the same time.
2. For simultaneous transmission at head and body exposure position, 2 transmitters simultaneous transmission was the worst state.
3. Based upon KDB 447498 D01, BT SAR is excluded as below table.
4. If the test separation distance is <5mm, 5mm is used for excluded SAR calculation.
5. For minimum test separation distance $\leq 50\text{mm}$, Bluetooth standalone SAR is excluded according to $[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f} (\text{GHz}) / x] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR
6. The reported SAR summation is calculated based on the same configuration and test position.
7. KDB 447498 / 4.3.2 (2) when standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:
 - a) $(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm}) \cdot [\sqrt{f} (\text{GHz}) / x] \text{ W/kg}$ for test separation distances $\leq 50 \text{ mm}$;
Where $x = 7.5$ for 1-g SAR, and $x = 18.75$ for 10-g SAR.
 - b) 0.4W/Kg for 1-g SAR and 1.0W/Kg for 10-g SAR, when the separation distance is $>50\text{mm}$.

Estimated SAR		Maximum Power		Antenna to user(mm)	Frequency(GHz)	Stand alone SAR(1g) [W/kg]
		dBm	mW			
BT	Head	9	7.943	5	2.480	0.334
	Body			10	2.480	0.167



Estimated SAR		Maximum Power		Antenna to user(mm)	Frequency(GHz)	Stand Alone SAR(1g) [W/kg]
		dBm	mW			
5.2G WLAN	Head	7	5.012	5	5.200	0.305
	Body			10	5.200	0.152
5.3G WLAN	Head	7	5.012	5	5.300	0.308
	Body			10	5.300	0.154
5.6G WLAN	Head	7	5.012	5	5.600	0.316
	Body			10	5.600	0.158
5.8G WLAN	Body	8	6.310	5	5.800	0.203



Simultaneous Mode	Position	Mode	Max. 1-g SAR (W/kg)	1-g Sum SAR (W/kg)
GSM + 2.4GHz WLAN	Head	GSM	0.262	0.412
		2.4GHz WLAN	0.150	
	Body	GSM	0.466	0.512
		2.4GHz WLAN	0.046	
WCDMA + 2.4GHz WLAN	Head	WCDMA	0.240	0.390
		2.4GHz WLAN	0.150	
	Body	WCDMA	0.368	0.414
		2.4GHz WLAN	0.046	
LTE + 2.4GHz WLAN	Head	LTE	0.283	0.433
		2.4GHz WLAN	0.150	
	Body	LTE	0.436	0.482
		2.4GHz WLAN	0.046	
GSM + Bluetooth	Head	GSM	0.262	0.596
		Bluetooth	0.334	
	Body	GSM	0.466	0.633
		Bluetooth	0.167	
WCDMA + Bluetooth	Head	WCDMA	0.240	0.574
		Bluetooth	0.334	
	Body	WCDMA	0.441	0.608
		Bluetooth	0.167	
LTE + Bluetooth	Head	LTE	0.283	0.617
		Bluetooth	0.334	
	Body	LTE	0.436	0.603
		Bluetooth	0.167	
GSM + 5.2GHz WLAN	Head	GSM	0.262	0.567
		5.2GHz WLAN	0.305	
	Body	GSM	0.466	0.618
		5.2GHz WLAN	0.152	
WCDMA + 5.2GHz WLAN	Head	WCDMA	0.240	0.545
		5.2GHz WLAN	0.305	
	Body	WCDMA	0.441	0.877
		5.2GHz WLAN	0.436	
LTE + 5.2GHz WLAN	Head	LTE	0.283	0.588
		5.2GHz WLAN	0.305	
	Body	LTE	0.436	0.872
		5.2GHz WLAN	0.436	
GSM + 5.3GHz WLAN	Head	GSM	0.262	0.570
		5.3GHz WLAN	0.308	
	Body	GSM	0.466	0.620
		5.3GHz WLAN	0.154	
WCDMA RMC+ 5.3GHz WLAN	Head	WCDMA	0.240	0.548
		5.3GHz WLAN	0.308	
	Body	WCDMA	0.441	0.595
		5.3GHz WLAN	0.154	
LTE + 5.3GHz WLAN	Head	LTE	0.283	0.591
		5.3GHz WLAN	0.308	
	Body	LTE	0.436	0.590
		5.3GHz WLAN	0.154	



Simultaneous Mode	Position	Mode	Max. 1-g SAR (W/kg)	1-g Sum SAR (W/kg)
GSM + 5.6GHz WLAN	Head	GSM	0.262	0.578
		5.6GHz WLAN	0.316	
	Body	GSM	0.466	0.624
		5.6GHz WLAN	0.158	
WCDMA + 5.6GHz WLAN	Head	WCDMA	0.240	0.556
		5.6GHz WLAN	0.316	
	Body	WCDMA	0.441	0.599
		5.6GHz WLAN	0.158	
LTE + 5.6GHz WLAN	Head	LTE	0.283	0.599
		5.6GHz WLAN	0.316	
	Body	LTE	0.436	0.594
		5.6GHz WLAN	0.158	
GSM + 5.8GHz WLAN	Head	GSM	0.262	0.930
		5.8GHz WLAN	0.668	
	Body	GSM	0.466	0.669
		5.8GHz WLAN	0.203	
WCDMA RMC+ 5.8GHz WLAN	Head	WCDMA	0.240	0.908
		5.8GHz WLAN	0.668	
	Body	WCDMA	0.441	0.644
		5.8GHz WLAN	0.203	
LTE + 5.8GHz WLAN	Head	LTE	0.283	0.951
		5.8GHz WLAN	0.668	
	Body	LTE	0.436	0.639
		5.8GHz WLAN	0.203	

Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneous transmitting antenna.

When the sum of SAR 1g of all simultaneously transmitting antennas in an operating mode and exposure condition combination is within the SAR limit (SAR-1g 1.6 W/kg), the simultaneous transmission SAR is not required. When the sum of SAR 1g is greater than the SAR limit (SAR-1g 1.6 W/kg), SAR test exclusion is determined by the SPLSR.



13. Equipment List

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last Calibration	Calibrated Until
450MHz Dipole	MVG	SID450	SN 30/14 DIP0G750-330	2017.08.15	2020.08.14
750MHz Dipole	MVG	SID750	SN 30/14 DIP0G750-331	2017.08.15	2020.08.14
835MHz Dipole	MVG	SID835	SN 30/14 DIP0G835-332	2017.08.15	2020.08.14
1800MHz Dipole	MVG	SID1800	SN 30/14 DIP1G800-329	2017.08.15	2020.08.14
1900MHz Dipole	MVG	SID1900	SN 30/14 DIP1G900-333	2017.08.15	2020.08.14
2450MHzDipole	MVG	SID2450	SN 30/14 DIP2G450-335	2017.08.15	2020.08.14
2600MHz Dipole	MVG	SID2600	SN 30/14 DIP2G600-336	2017.08.15	2020.08.14
E-Field Probe	MVG	SSE2	SN 41/18 EPGO334	2019.06.04	2020.06.03
Dielectric Probe Kit	MVG	SCLMP	SN 32/14 OCPG67	2019.11.25	2020.11.24
Antenna	MVG	ANTA3	SN 07/13 ZNTA52	N/A	N/A
Phantom1	MVG	SAM	SN 32/14 SAM115	N/A	N/A
Phantom2	MVG	SAM	SN 32/14 SAM116	N/A	N/A
Phone holder	MVG	N/A	SN 32/14 MSH97	N/A	N/A
Laptop holder	MVG	N/A	SN 32/14 LSH29	N/A	N/A
Attenuator	Agilent	99899	DC-18GHz	N/A	N/A
Directional coupler	Narda	4226-20	3305	N/A	N/A
Network Analyzer	Agilent	8753ES	US38432810	2019.10.11	2020.10.10
Multi Meter	Keithley	Multi Meter 2000	4050073	2019.10.11	2020.10.10
Signal Generator	Agilent	N5182A	MY50140530	2019.10.09	2020.10.08
Wireless Communication Test Set	Agilent	8960-E5515C	MY48360751	2019.10.09	2020.10.08
Wireless Communication Test Set	R&S	CMW500	117239	2019.10.09	2020.10.08
Power Amplifier	DESAY	ZHL-42W	9638	2019.10.09	2020.10.08
Power Meter	R&S	NRP	100510	2019.10.16	2020.10.15
Power Meter	Agilent	E4419B	QB43312265	2019.10.12	2020.10.11
Power Sensor	R&S	NRP-Z11	101919	2019.10.12	2020.10.11
Power Sensor	HP	E9300A	US39210170	2019.10.09	2020.10.08
Temperature hygrometer	SuWei	SW-108	N/A	2019.10.13	2020.10.12
Thermograph	Elitech	RC-4	S/N EF7176501537	2019.10.11	2020.10.10

Note:

Per KDB 865664 D01, Dipole SAR Validation Verification, STS LAB has adopted 3 years calibration intervals. On annual basis, every measurement dipole has been evaluated and is in compliance with the following criteria:

1. There is no physical damage on the dipole
2. System validation with specific dipole is within 10% of calibrated value

Return-loss in within 20% of calibrated measurement



Appendix A. System Validation Plots

System Performance Check Data (450MHz Head)

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2020-05-06

Experimental conditions.




Probe	
Phantom	Validation plane
Device Position	-
Band	450MHz
Channels	-
Signal	CW
Frequency (MHz)	450MHz
Relative permittivity	42.87
Conductivity (S/m)	0.85
Power drift (%)	-0.53
Probe	SN 41/18 EPGO334
ConvF:	1.42
Crest factor:	1:1



Maximum location: X=2.00, Y=0.00

SAR 10g (W/Kg)	0.311847
SAR 1g (W/Kg)	0.452179

Z Axis Scan





System Performance Check Data (450MHz Body)

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2020-05-06

Experimental conditions.




Probe	
Phantom	Validation plane
Device Position	-
Band	450MHz
Channels	-
Signal	CW
Frequency (MHz)	450MHz
Relative permittivity	57.11
Conductivity (S/m)	0.96
Power drift (%)	2.91
Probe	SN 41/18 EPG0334
ConvF:	1.45
Crest factor:	1:1



Maximum location: X=3.00, Y=0.00

SAR 10g (W/Kg)	0.320625
SAR 1g (W/Kg)	0.466534

Z Axis Scan





System Performance Check Data (750MHz Head)

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm, dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2020-04-22

Experimental conditions




Phantom	Validation plane
Device Position	-
Band	750MHz
Channels	-
Signal	CW
Frequency (MHz)	750MHz
Relative permittivity	41.02
Conductivity (S/m)	0.89
Power drift (%)	1.35
Probe	SN 41/18 EPG0334
ConvF	1.43
Crest factor	1:1



Maximum location: X=2.00, Y=1.00

SAR 10g (W/Kg)	0.579864
SAR 1g (W/Kg)	0.881638

Z Axis Scan





System Performance Check Data (750MHz Body)

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm, dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2020-04-22

Experimental conditions.




Probe	
Phantom	Validation plane
Device Position	-
Band	750MHz
Channels	-
Signal	CW
Frequency (MHz)	750MHz
Relative permittivity	55.40
Conductivity (S/m)	0.94
Power drift (%)	-1.19
Probe	SN 41/18 EPG0334
ConvF:	1.49
Crest factor:	1:1



Maximum location: X=1.00, Y=-1.00

SAR 10g (W/Kg)	0.571165
SAR 1g (W/Kg)	0.809412

Z Axis Scan





System Performance Check Data (835MHz Head)

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm, dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2020-04-23

Experimental conditions




Phantom	Validation plane
Device Position	-
Band	835MHz
Channels	-
Signal	CW
Frequency (MHz)	835MHz
Relative permittivity	40.68
Conductivity (S/m)	0.92
Power drift (%)	2.25
Probe	SN 41/18 EPG0334
ConvF:	1.48
Crest factor:	1:1



Maximum location: X=-7.00, Y=-1.00

SAR 10g (W/Kg)	0.611878
SAR 1g (W/Kg)	0.962954

Z Axis Scan





System Performance Check Data (835MHz Body)

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm, dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2020-04-23

Experimental conditions.




Probe	
Phantom	Validation plane
Device Position	-
Band	835MHz
Channels	-
Signal	CW
Frequency (MHz)	835MHz
Relative permittivity	54.93
Conductivity (S/m)	0.98
Power drift (%)	-3.13
Probe	SN 41/18 EPG0334
ConvF:	1.53
Crest factor:	1:1



Maximum location: X=-7.00, Y=-1.00

SAR 10g (W/Kg)	0.609465
SAR 1g (W/Kg)	0.957627

Z Axis Scan





System Performance Check Data(1800MHz Head)

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm, dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2020-04-26

Experimental conditions.




Phantom	Validation plane
Device Position	-
Band	1800MHz
Channels	-
Signal	CW
Frequency (MHz)	1800MHz
Relative permittivity	40.31
Conductivity (S/m)	1.37
Power drift (%)	-0.72
Probe	SN 41/18 EPGO334
ConvF	1.60
Crest factor:	1:1



Maximum location: X=5.00, Y=1.00

SAR 10g (W/Kg)	2.107615
SAR 1g (W/Kg)	3.842689

Z Axis Scan



**System Performance Check Data(1800MHz Body)**

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm, dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2020-04-26




Experimental conditions.

Phantom	Validation plane
Device Position	-
Band	1800MHz
Channels	-
Signal	CW
Frequency (MHz)	1800MHz
Relative permittivity	54.20
Conductivity (S/m)	1.55
Power drift (%)	-0.21
Probe	SN 41/18 EPG0334
ConvF	1.66
Crest factor:	1:1

**Maximum location: X=-3.00, Y=-2.00**

SAR 10g (W/Kg)	1.885943
SAR 1g (W/Kg)	3.790811

Z Axis Scan





System Performance Check Data (1900MHz Head)

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm, dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2020-04-27

Experimental conditions.




Phantom	Validation plane
Device Position	-
Band	1900MHz
Channels	-
Signal	CW
Frequency (MHz)	1900MHz
Relative permittivity	40.67
Conductivity (S/m)	1.44
Power drift (%)	0.58
Probe	SN 41/18 EPG0334
ConvF	1.84
Crest factor:	1:1



Maximum location: X=3.00, Y=-2.00

SAR 10g (W/Kg)	2.147140
SAR 1g (W/Kg)	3.958965

Z Axis Scan





System Performance Check Data (1900MHz Body)

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm, dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2020-04-27

Experimental conditions.




Device Position	-
Band	1900MHz
Channels	-
Signal	CW
Frequency (MHz)	1900
Relative permittivity	53.96
Conductivity (S/m)	1.50
Power drift (%)	0.87
Probe	SN 41/18 EPGO334
ConvF:	1.88
Crest factor:	1:1



Maximum location: X=-3.00, Y=-2.00

SAR 10g (W/Kg)	2.054625
SAR 1g (W/Kg)	4.003693

Z Axis Scan



System Performance Check Data (2450MHz Head)

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm, dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2020-04-28

Experimental conditions.




Device Position	Validation plane
Band	2450 MHz
Channels	-
Signal	CW
Frequency (MHz)	2450
Relative permittivity	39.94
Conductivity (S/m)	1.76
Power drift (%)	0.32
Probe	SN 41/18 EPG0334
ConvF	1.97
Crest factor:	1:1



Maximum location: X=1.00, Y=0.00

SAR 10g (W/Kg)	2.381508
SAR 1g (W/Kg)	5.231192

Z Axis Scan



**System Performance Check Data (2450MHz Body)**

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm, dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2020-04-28




Experimental conditions.

Device Position	Validation plane
Band	2450 MHz
Channels	-
Signal	CW
Frequency (MHz)	2450
Relative permittivity	52.89
Conductivity (S/m)	1.97
Power drift (%)	2.32
Probe	SN 41/18 EPGO334
ConvF	2.02
Crest factor:	1:1

**Maximum location: X=1.00, Y=0.00**

SAR 10g (W/Kg)	2.222486
SAR 1g (W/Kg)	5.204367

Z Axis Scan





System Performance Check Data(2600MHz Head)

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm, dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2020-04-29

Experimental conditions.




Device Position	Validation plane
Band	2600 MHz
Channels	-
Signal	CW
Frequency (MHz)	2600
Relative permittivity	39.31
Conductivity (S/m)	1.93
Power drift (%)	1.68
Probe	SN 41/18 EPGO334
ConvF	1.85
Crest factor:	1:1



Maximum location: X=1.00, Y=0.00

SAR 10g (W/Kg)	2.348551
SAR 1g (W/Kg)	5.495319

Z Axis Scan



System Performance Check Data (2600MHz Body)

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm, dy=8mm

Zoom scan resolution: dx=8mm, dy=8mm, dz=5mm

Date of measurement: 2020-04-29

Experimental conditions.




Device Position	Validation plane
Band	2600 MHz
Channels	-
Signal	CW
Frequency (MHz)	2600
Relative permittivity	52.31
Conductivity (S/m)	2.22
Power drift (%)	0.97
Probe	SN 41/18 EPG0334
ConvF	1.92
Crest factor:	1:1



Maximum location: X=3.00, Y=1.00

SAR 10g (W/Kg)	2.453644
SAR 1g (W/Kg)	5.518366

Z Axis Scan



**System Performance Check Data(5800MHz Head)**

Type: Phone measurement (Complete)


Area scan resolution: dx=8mm,dy=8mm

Zoom scan resolution: dx=4mm, dy=4mm, dz=2mm

Date of measurement: 2020-04-30




Experimental conditions.

Device Position	Validation plane
Band	5800 MHz
Channels	-
Signal	CW
Frequency (MHz)	5800
Relative permittivity	35.75
Conductivity (S/m)	5.25
Power drift (%)	1.75
Probe	SN 41/18 EPGO334
ConvF	2.09
Crest factor:	1:1

**Maximum location: X=7.00, Y=2.00**

SAR 10g (W/Kg)	6.110752
SAR 1g (W/Kg)	18.147283

Z Axis Scan



Appendix B. SAR Test Plots


Plot 1: DUT: Smart phone; EUT Model: Atom XL

Test Date	2020-04-22
Probe	SN 41/18 EPGO334
ConvF	1.48
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Right head
Device Position	Cheek
Band	GPRS 850
Channels	High
Signal	Duty Cycle: 2.00 (Crest factor: 2.0)
Frequency (MHz)	848.8
Relative permittivity (real part)	40.68
Conductivity (S/m)	0.92

Maximum location: X=-47.00, Y=-21.00

SAR Peak: 0.27 W/kg

SAR 10g (W/Kg)	0.153466
SAR 1g (W/Kg)	0.211717




Plot 2: DUT: Smart phone; EUT Model: Atom XL

Test Date	2020-04-22
Probe	SN 41/18 EPG0334
ConvF	1.53
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Back Side
Band	GPRS 850
Channels	High
Signal	Duty Cycle: 2.00 (Crest factor: 2.0)
Frequency (MHz)	848.8
Relative permittivity (real part)	54.93
Conductivity (S/m)	0.98

Maximum location: X=6.00, Y=29.00

SAR Peak: 0.51 W/kg

SAR 10g (W/Kg)	0.270881
SAR 1g (W/Kg)	0.372007




Plot 3: DUT: Smart phone; EUT Model: Atom XL

Test Date	2020-04-27
Probe	SN 41/18 EPGO334
ConvF	1.84
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Right head
Device Position	Cheek
Band	GPRS 1900
Channels	Low
Signal	Duty Cycle: 1:2.00 (Crest factor: 2.0)
Frequency (MHz)	1850.2
Relative permittivity (real part)	40.67
Conductivity (S/m)	1.44

Maximum location: X=-63.00, Y=-15.00

SAR Peak: 0.35 W/kg

SAR 10g (W/Kg)	0.120835
SAR 1g (W/Kg)	0.217863




Plot 4: DUT: Smart phone; EUT Model: Atom XL

Test Date	2020-04-27
Probe	SN 41/18 EPG0334
ConvF	1.88
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Back Side
Band	GPRS 1900
Channels	Low
Signal	Duty Cycle: 1:2.00 (Crest factor: 2.0)
Frequency (MHz)	1850.2
Relative permittivity (real part)	53.96
Conductivity (S/m)	1.50

Maximum location: X=25.00, Y=-15.00

SAR Peak: 0.62 W/kg

SAR 10g (W/Kg)	0.218496
SAR 1g (W/Kg)	0.388098




Plot 5: DUT: Smart phone; EUT Model: Atom XL

Test Date	2020-04-27
Probe	SN 41/18 EPG0334
ConvF	1.84
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Right head
Device Position	Cheek
Band	WCDMA II
Channels	High
Signal	WCDMA (Crest factor: 1.0)
Frequency (MHz)	1907.6
Relative permittivity (real part)	40.67
Conductivity (S/m)	1.44

Maximum location: X=-62.00, Y=-15.00

SAR Peak: 0.21 W/kg

SAR 10g (W/Kg)	0.074224
SAR 1g (W/Kg)	0.132838




Plot 6: DUT: Smart phone; EUT Model: Atom XL

Test Date	2020-04-27
Probe	SN 41/18 EPGO334
ConvF	1.88
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Back Side
Band	WCDMA II
Channels	High
Signal	WCDMA (Crest factor: 1.0)
Frequency (MHz)	1907.6
Relative permittivity (real part)	53.96
Conductivity (S/m)	1.50

Maximum location: X=13.00, Y=-8.00

SAR Peak: 0.54 W/kg

SAR 10g (W/Kg)	0.176884
SAR 1g (W/Kg)	0.327569




Plot 7: DUT: Smart phone; EUT Model: Atom XL

Test Date	2020-04-26
Probe	SN 41/18 EPG0334
ConvF	1.60
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Right head
Device Position	Cheek
Band	WCDMA VI
Channels	Low
Signal	WCDMA (Crest factor: 1.0)
Frequency (MHz)	1712.6
Relative permittivity (real part)	40.31
Conductivity (S/m)	1.37

Maximum location: X=-49.00, Y=-54.00

SAR Peak: 0.12 W/kg

SAR 10g (W/Kg)	0.035393
SAR 1g (W/Kg)	0.068987




Plot 8: DUT: Smart phone; EUT Model: Atom XL

Test Date	2020-04-26
Probe	SN 41/18 EPGO334
ConvF	1.66
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Back Side
Band	WCDMA VI
Channels	Low
Signal	WCDMA (Crest factor: 1.0)
Frequency (MHz)	1712.6
Relative permittivity (real part)	54.20
Conductivity (S/m)	1.55

Maximum location: X=-17.00, Y=-13.00

SAR Peak: 0.16 W/kg

SAR 10g (W/Kg)	0.057468
SAR 1g (W/Kg)	0.100090




Plot 9: DUT: Smart phone; EUT Model: Atom XL

Test Date	2020-04-22
Probe	SN 41/18 EPGO334
ConvF	1.48
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Right head
Device Position	Cheek
Band	WCDMA V
Channels	Low
Signal	WCDMA (Crest factor: 1.0)
Frequency (MHz)	826.4
Relative permittivity (real part)	40.68
Conductivity (S/m)	0.92

Maximum location: X=-47.00, Y=-34.00

SAR Peak: 0.25 W/kg

SAR 10g (W/Kg)	0.137465
SAR 1g (W/Kg)	0.194183




Plot 10: DUT: Smart phone; EUT Model: Atom XL

Test Date	2020-04-22
Probe	SN 41/18 EPGO334
ConvF	1.53
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Back Side
Band	WCDMA V
Channels	Low
Signal	WCDMA (Crest factor: 1.0)
Frequency (MHz)	826.4
Relative permittivity (real part)	54.93
Conductivity (S/m)	0.98

Maximum location: X=2.00, Y=32.00

SAR Peak: 0.44 W/kg

SAR 10g (W/Kg)	0.264839
SAR 1g (W/Kg)	0.356257



Plot 11: DUT: Smart phone; EUT Model: Atom XL


Test Date	2020-04-28
Probe	SN 41/18 EPGO334
ConvF	1.97
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Right head
Device Position	Cheek
Band	IEEE 802.11b ISM
Channels	Low
Signal	IEEE802.b (Crest factor: 1.0)
Frequency (MHz)	2412
Relative permittivity (real part)	39.94
Conductivity (S/m)	1.76

Maximum location: X=-7.00, Y=-7.00


SAR Peak: 0.27 W/kg

SAR 10g (W/Kg)	0.068505
SAR 1g (W/Kg)	0.146621


SURFACE SAR




VOLUME SAR



3D



Z Axis Scan




Plot 12: DUT: Smart phone; EUT Model: Atom XL

Test Date	2020-04-28
Probe	SN 41/18 EPGO334
ConvF	2.02
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Back Side
Band	IEEE 802.11b ISM
Channels	Low
Signal	IEEE802.b (Crest factor: 1.0)
Frequency (MHz)	2412
Relative permittivity (real part)	52.89
Conductivity (S/m)	1.97

Maximum location: X=9.00, Y=0.00

SAR Peak: 0.09 W/kg

SAR 10g (W/Kg)	0.018219
SAR 1g (W/Kg)	0.045241




Plot 13: DUT: Smart phone; EUT Model: Atom XL

Test Date	2020-04-27
Probe	SN 41/18 EPG0334
ConvF	1.84
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Right head
Device Position	Cheek
Band	LTE Band 2 (RB 1)
Channels	Low
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	1860
Relative permittivity (real part)	40.67
Conductivity (S/m)	1.44

Maximum location: X=-58.00, Y=-16.00

SAR Peak: 0.34 W/kg

SAR 10g (W/Kg)	0.129431
SAR 1g (W/Kg)	0.225078




Plot 14: DUT: Smart phone; EUT Model: Atom XL

Test Date	2020-04-27
Probe	SN 41/18 EPGO334
ConvF	1.88
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Back Side
Band	LTE Band 2(RB 1)
Channels	Low
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	1860
Relative permittivity (real part)	53.96
Conductivity (S/m)	1.50

Maximum location: X=14.00, Y=-10.00

SAR Peak: 0.45 W/kg

SAR 10g (W/Kg)	0.147780
SAR 1g (W/Kg)	0.272909




Plot 15: DUT: Smart phone; EUT Model: Atom XL

Test Date	2020-04-26
Probe	SN 41/18 EPGO334
ConvF	1.60
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Right head
Device Position	Cheek
Band	LTE Band 4 (RB 1)
Channels	High
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	1745
Relative permittivity (real part)	40.31
Conductivity (S/m)	1.37

Maximum location: X=-65.00, Y=-19.00

SAR Peak: 0.38 W/kg

SAR 10g (W/Kg)	0.150731
SAR 1g (W/Kg)	0.256798




Plot 16: DUT: Smart phone; EUT Model: Atom XL

Test Date	2020-04-26
Probe	SN 41/18 EPGO334
ConvF	1.66
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Back Side
Band	LTE Band 4 (RB 1)
Channels	High
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	1745
Relative permittivity (real part)	54.20
Conductivity (S/m)	1.55

Maximum location: X=15.00, Y=-1.00

SAR Peak: 0.60 W/kg

SAR 10g (W/Kg)	0.210851
SAR 1g (W/Kg)	0.372864




Plot 17: DUT: Smart phone; EUT Model: Atom XL

Test Date	2020-04-22
Probe	SN 41/18 EPG0334
ConvF	1.48
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Right head
Device Position	Cheek
Band	LTE Band 5 (RB 1)
Channels	High
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	844.0
Relative permittivity (real part)	40.68
Conductivity (S/m)	0.92

Maximum location: X=-47.00, Y=-37.00

SAR Peak: 0.23 W/kg

SAR 10g (W/Kg)	0.123982
SAR 1g (W/Kg)	0.177894




Plot 18: DUT: Smart phone; EUT Model: Atom XL

Test Date	2020-04-22
Probe	SN 41/18 EPGO334
ConvF	1.53
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Back Side
Band	LTE Band 5 (RB 1)
Channels	High
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	844.0
Relative permittivity (real part)	54.93
Conductivity (S/m)	0.98

Maximum location: X=-8.00, Y=22.00

SAR Peak: 0.37 W/kg

SAR 10g (W/Kg)	0.214411
SAR 1g (W/Kg)	0.293618




Plot 19: DUT: Smart phone; EUT Model: Atom XL

Test Date	2020-04-29
Probe	SN 41/18 EPG0334
ConvF	1.85
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Right head
Device Position	Cheek
Band	LTE Band 7 (RB 1)
Channels	Low
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	2510
Relative permittivity (real part)	39.79
Conductivity (S/m)	1.93

Maximum location: X=-48.00, Y=-8.00

SAR Peak: 0.13 W/kg

SAR 10g (W/Kg)	0.028357
SAR 1g (W/Kg)	0.067035




Plot 20: DUT: Smart phone; EUT Model: Atom XL

Test Date	2020-04-29
Probe	SN 41/18 EPGO334
ConvF	1.92
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Back Side
Band	LTE Band 7 (RB 1)
Channels	Low
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	2510
Relative permittivity (real part)	52.31
Conductivity (S/m)	2.22

Maximum location: X=-17.00, Y=11.00

SAR Peak: 0.51 W/kg

SAR 10g (W/Kg)	0.125101
SAR 1g (W/Kg)	0.279887




Plot 21: DUT: Smart phone; EUT Model: Atom XL

Test Date	2020-04-22
Probe	SN 41/18 EPG0334
ConvF	1.43
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Right head
Device Position	Cheek
Band	LTE Band 12 (RB 1)
Channels	High
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	711
Relative permittivity (real part)	41.02
Conductivity (S/m)	0.89

Maximum location: X=-49.00, Y=-33.00

SAR Peak: 0.08 W/kg

SAR 10g (W/Kg)	0.039523
SAR 1g (W/Kg)	0.057410




Plot 22: DUT: Smart phone; EUT Model: Atom XL

Test Date	2020-04-22
Probe	SN 41/18 EPGO334
ConvF	1.49
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Back Side
Band	LTE Band 12 (RB 1)
Channels	High
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	711
Relative permittivity (real part)	55.50
Conductivity (S/m)	0.96

Maximum location: X=6.00, Y=15.00

SAR Peak: 0.32 W/kg

SAR 10g (W/Kg)	0.183428
SAR 1g (W/Kg)	0.253239




Plot 23: DUT: Smart phone; EUT Model: Atom XL

Test Date	2020-04-22
Probe	SN 41/18 EPG0334
ConvF	1.43
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Right head
Device Position	Cheek
Band	LTE Band 13 (RB 1)
Channels	Middle
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	782
Relative permittivity (real part)	41.02
Conductivity (S/m)	0.89

Maximum location: X=-49.00, Y=-34.00

SAR Peak: 0.09 W/kg

SAR 10g (W/Kg)	0.050619
SAR 1g (W/Kg)	0.071242




Plot 24: DUT: Smart phone; EUT Model: Atom XL

Test Date	2020-04-22
Probe	SN 41/18 EPGO334
ConvF	1.49
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Back Side
Band	LTE Band 13 (RB 1)
Channels	Middle
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	782
Relative permittivity (real part)	55.40
Conductivity (S/m)	0.94

Maximum location: X=1.00, Y=17.00

SAR Peak: 0.03 W/kg

SAR 10g (W/Kg)	0.016262
SAR 1g (W/Kg)	0.024765




Plot 25: DUT: Smart phone; EUT Model: Atom XL

Test Date	2020-04-22
Probe	SN 41/18 EPGO334
ConvF	1.43
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Right head
Device Position	Cheek
Band	LTE Band 17 (RB 1)
Channels	Middle
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	710
Relative permittivity (real part)	41.02
Conductivity (S/m)	0.89

Maximum location: X=-48.00, Y=-32.00

SAR Peak: 0.09 W/kg

SAR 10g (W/Kg)	0.050422
SAR 1g (W/Kg)	0.071576




Plot 26: DUT: Smart phone; EUT Model: Atom XL

Test Date	2020-04-22
Probe	SN 41/18 EPGO334
ConvF	1.49
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Back Side
Band	LTE Band 17 (RB 1)
Channels	Middle
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	710
Relative permittivity (real part)	55.40
Conductivity (S/m)	0.94

Maximum location: X=7.00, Y=14.00

SAR Peak: 0.32 W/kg

SAR 10g (W/Kg)	0.182567
SAR 1g (W/Kg)	0.251540




Plot 27: DUT: Smart phone; EUT Model: Atom XL

Test Date	2020-04-27
Probe	SN 41/18 EPGO334
ConvF	1.84
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Right head
Device Position	Cheek
Band	LTE Band 25 (RB 1)
Channels	Middle
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	1882.5
Relative permittivity (real part)	40.67
Conductivity (S/m)	1.44

Maximum location: X=-60.00, Y=-17.00

SAR Peak: 0.37 W/kg

SAR 10g (W/Kg)	0.140916
SAR 1g (W/Kg)	0.245549




Plot 28: DUT: Smart phone; EUT Model: Atom XL

Test Date	2020-04-27
Probe	SN 41/18 EPGO334
ConvF	1.88
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Back Side
Band	LTE Band 25 (RB 1)
Channels	Middle
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	1882.5
Relative permittivity (real part)	53.96
Conductivity (S/m)	1.50

Maximum location: X=14.00, Y=-6.00

SAR Peak: 0.40 W/kg

SAR 10g (W/Kg)	0.133609
SAR 1g (W/Kg)	0.247272




Plot 29: DUT: Smart phone; EUT Model: Atom XL

Test Date	2020-04-22
Probe	SN 41/18 EPGO334
ConvF	1.48
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Right head
Device Position	Cheek
Band	LTE Band 26 (RB 1)
Channels	High
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	841.5
Relative permittivity (real part)	41.02
Conductivity (S/m)	0.89

Maximum location: X=-48.00, Y=-38.00

SAR Peak: 0.22 W/kg

SAR 10g (W/Kg)	0.116550
SAR 1g (W/Kg)	0.167158




Plot 30: DUT: Smart phone; EUT Model: Atom XL

Test Date	2020-04-22
Probe	SN 41/18 EPGO334
ConvF	1.53
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Back Side
Band	LTE Band 26 (RB 1)
Channels	High
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	841.5
Relative permittivity (real part)	55.40
Conductivity (S/m)	0.94

Maximum location: X=-7.00, Y=20.00

SAR Peak: 0.46 W/kg

SAR 10g (W/Kg)	0.261736
SAR 1g (W/Kg)	0.356277




Plot 31: DUT: Smart phone; EUT Model: Atom XL

Test Date	2020-04-29
Probe	SN 41/18 EPGO334
ConvF	1.85
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Right head
Device Position	Cheek
Band	LTE Band 41 (RB 1)
Channels	Middle
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	2593
Relative permittivity (real part)	39.79
Conductivity (S/m)	1.93

Maximum location: X=-48.00, Y=-6.00

SAR Peak: 0.08 W/kg

SAR 10g (W/Kg)	0.016086
SAR 1g (W/Kg)	0.038509




Plot 32: DUT: Smart phone; EUT Model: Atom XL

Test Date	2020-04-29
Probe	SN 41/18 EPGO334
ConvF	1.92
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Back Side
Band	LTE Band 41 (RB 1)
Channels	Middle
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	2593
Relative permittivity (real part)	52.31
Conductivity (S/m)	2.22

Maximum location: X=17.00, Y=-14.00

SAR Peak: 0.63 W/kg

SAR 10g (W/Kg)	0.148371
SAR 1g (W/Kg)	0.334269




Plot 33: DUT: Smart phone; EUT Model: Atom XL

Test Date	2020-04-26
Probe	SN 41/18 EPGO334
ConvF	1.60
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Right head
Device Position	Cheek
Band	LTE Band 66 (RB 1)
Channels	Middle
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	1745
Relative permittivity (real part)	40.31
Conductivity (S/m)	1.37

Maximum location: X=-53.00, Y=-3.00

SAR Peak: 0.27 W/kg

SAR 10g (W/Kg)	0.090409
SAR 1g (W/Kg)	0.167778




Plot 34: DUT: Smart phone; EUT Model: Atom XL

Test Date	2020-04-26
Probe	SN 41/18 EPGO334
ConvF	1.66
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Back Side
Band	LTE Band 66 (RB 1)
Channels	Middle
Signal	LTE (Crest factor: 1.0)
Frequency (MHz)	1745
Relative permittivity (real part)	54.20
Conductivity (S/m)	1.55

Maximum location: X=-5.00, Y=-16.00

SAR Peak: 0.53 W/kg

SAR 10g (W/Kg)	0.195841
SAR 1g (W/Kg)	0.335576




Plot 35: DUT: Smart phone; EUT Model: Atom XL

Test Date	2020-04-30
Probe	SN 41/18 EPGO334
ConvF	2.16
Area Scan	dx=8mm dy=8mm, h= 5.00 mm
Zoom Scan	7x7x12,dx=4mm dy=4mm dz=2mm, Complete/ndx=8mm dy=8mm, h= 5.00 mm
Phantom	Right head
Device Position	Cheek
Band	IEEE 802.11a ISM
Channels	149
Signal	IEEE802.a (Crest factor: 1.0)
Frequency (MHz)	5745
Relative permittivity (real part)	35.75
Conductivity (S/m)	5.25

Maximum location: X=3.00, Y=-21.00

SAR Peak: 1.54 W/kg

SAR 10g (W/Kg)	0.173660
SAR 1g (W/Kg)	0.638859




Plot 36: DUT: Smart phone; EUT Model: Atom XL

Test Date	2020-05-06
Probe	SN 41/18 EPGO334
ConvF	1.42
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Front of face
Channels	CH 1
Signal	Crest factor: 1.0
Frequency (MHz)	450.0125
Relative permittivity (real part)	42.87
Conductivity (S/m)	0.85

Maximum location: X=2.00, Y=-16.00

SAR Peak: 0.30 W/kg

SAR 10g (W/Kg)	0.184132
SAR 1g (W/Kg)	0.241761




Plot 37: DUT: Smart phone; EUT Model: Atom XL

Test Date	2020-05-06
Probe	SN 41/18 EPGO334
ConvF	1.45
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Limbs
Channels	CH 1
Signal	Crest factor: 1.0
Frequency (MHz)	450.0125
Relative permittivity (real part)	57.11
Conductivity (S/m)	0.96

Maximum location: X=8.00, Y=0.00

SAR Peak: 0.48 W/kg

SAR 10g (W/Kg)	0.269851
SAR 1g (W/Kg)	0.370947




Plot 38: DUT: Smart phone; EUT Model: Atom XL

Test Date	2020-05-06
Probe	SN 41/18 EPGO334
ConvF	1.42
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Front of face
Channels	CH 1
Signal	Crest factor: 1.0
Frequency (MHz)	450.0125
Relative permittivity (real part)	42.87
Conductivity (S/m)	0.85

Maximum location: X=10.00, Y=-1.00

SAR Peak: 0.28 W/kg

SAR 10g (W/Kg)	0.171219
SAR 1g (W/Kg)	0.224998




Plot 39: DUT: Smart phone; EUT Model: Atom XL

Test Date	2020-05-06
Probe	SN 41/18 EPGO334
ConvF	1.45
Area Scan	dx=8mm, dy=8mm, h= 5.00 mm
Zoom Scan	5x5x7, dx=8mm, dy=8mm, dz=5mm, Complete/ndx=8mm, dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Limbs
Channels	CH 1
Signal	Crest factor: 1.0
Frequency (MHz)	450.0125
Relative permittivity (real part)	57.11
Conductivity (S/m)	0.96

Maximum location: X=7.00, Y=1.00

SAR Peak: 0.55 W/kg

SAR 10g (W/Kg)	0.261038
SAR 1g (W/Kg)	0.384116





Appendix C. Probe Calibration and Dipole Calibration Report

Refer the appendix Calibration Report.

※※※※END OF THE REPORT※※※※

