

工业56寸

预留不干胶
空白位置
($\geq 1.8 \times 2.8 \text{cm}$)

HALO: H7ICAT/ICT/T/ICATNB/ICTNB/TNB/TCP/H7UICAT/
UICAT,H7RT/RICT/RICAT,H27ICAT/ICT/T/RICAT/RICT/
RT,H2750ICAT,H750ICAT/T/TD010/TCP/TCPD010/
RICAT/RINTD010/RTD010,H51CAT/RICAT/T/RT/TM,
H251CAT,H550ICAT/RICAT,ML7BXRfk/E26Rfk

Smart LED Lamp Assembly
Intelligent assemblage d'ampoule DEL
Inteligente asamblea de lámpara LED
RL56129BLE40AWH

SUITABLE FOR WET LOCATIONS COVERED
CEILING ONLY / CONVIENT AUX
ENDROITS HUMIDES AVEC UN PLAFOND
COUVERT / ADECUADO PARA LUGARES
HUMEDOS CON UN TECHO CUBIERTO

FCC ID: 2AKCY-RL56HLBLE
IC: 4706A-RL56HLBLE
Patent: www.eaton.com/patents
LL5182003ML

2700K-5000K 14.2Watts



HALO
AC INPUT:
120 VAC ~.120A
60HZ PF>.9



EAT•N
1121 HIGHWAY 74 SOUTH
PEACHTREE CITY, GA 30269

See the instruction sheet or website to view the most recent list of approved housings. / Consultez la feuille d'instructions ou le site d'approved pour obtenir la liste récente des boîtiers approuvés. / Consulte la lista más reciente de alojamiento aprobados en la hoja de instrucciones o el sitio web.

UL Certified to use with the following non-Halo and non-Alt-Pro recessed luminaires / Certifié UL pour une utilisation avec la suivante non-Halo et non-Alt-Pro luminaires encastrés. / Certificado UL para su uso con las siguientes organizaciones no Halo / no Alt-Pro de luminarias empotrables.

John: W22.1/W.S/C22.0/W21.1/W21.2/W20.0/W25.0/W.S/W20.0
Lighthouse: Thomas W.S/S2C.0/W.S/S2C.0/W.S/S2C.0/W.S/S2C.0
Capri: W11.1/W11.0/W.S/C11.0/W.S/C11.0/W.S/C11.0/W.S/C11.0
Thomas: W11.1/W.S/C11.0/W.S/C11.0/W.S/C11.0/W.S/C11.0
Progress: W11.1/W.S/C11.0/W.S/C11.0/W.S/C11.0/W.S/C11.0
Commercial Electric: W11.1/W.S/C11.0/W.S/C11.0/W.S/C11.0/W.S/C11.0