



MPE ESTIMATION

Test report
On Behalf of
Shenzhen Inpor Cloud Computing CO.,Ltd.
For
Meet Mini Portable All-in-One Video Conferencing Device
Model No.: MM1

FCC ID: 2AKHL-MM1

Prepared for : **Shenzhen Inpor Cloud Computing CO.,Ltd.**
916 Room, Block B, Building 9, Tech and Ecology Park, Shenzhen Bay, Nanshan District, Shenzhen, China

Prepared By : **Shenzhen HUAK Testing Technology Co., Ltd.**
1F, B2 Building, Junfeng Zhongcheng Zhizao Innovation Park, Fuhai Street, Bao'an District, Shenzhen City, China

Date of Test: **Apr. 17, 2019 ~ Apr. 26, 2019**

Date of Report: **Apr. 26, 2019**

Report Number: **HK1904170865-4E**

**5.2G WIFI**

Mode	Max PK Output power(dBm)	Tune Up Power(dBm)	Max Tune Up power(mW)	Antenna Gain(dBi)	Antenna Gain (linear)	MPE (mW/cm ²)
11a	11.29	11±1(12)	15.85	1	1.2589	0.00379
11n(HT20)	10.99	10±1(11)	12.59	1	1.2589	0.00315
11n(HT40)	9.85	9±1(10)	10.00	1	1.2589	0.00251
11ac(HT20)	9.74	9±1(10)	10.00	1	1.2589	0.00251
11ac(HT40)	8.77	8±1(9)	7.94	1	1.2589	0.00199
11ac(HT80)	8.65	8±1(9)	7.94	1	1.2589	0.00199

$$Pd = \frac{P_{out} * G}{4\pi r^2};$$

Note:

Note: The estimation distance is 20cm

Note:

PK Output power= conducted power.

Conducted power see the test report HK1904170865-3E, antenna gain=1dBi

5.8G WIFI

Mode	Max PK Output power(dBm)	Tune Up Power(dBm)	Max Tune Up power(mW)	Antenna Gain(dBi)	Antenna Gain (linear)	MPE (mW/cm ²)
11a	11.56	11±1(12)	15.85	1	1.2589	0.00379
11n(HT20)	10.58	10±1(11)	12.59	1	1.2589	0.00315
11n(HT40)	9.84	9±1(10)	10.00	1	1.2589	0.00251
11ac(HT20)	9.38	9±1(10)	10.00	1	1.2589	0.00251
11ac(HT40)	9.45	9±1(10)	10.00	1	1.2589	0.00251
11ac(HT80)	9.14	9±1(10)	10.00	1	1.2589	0.00251

$$Pd = \frac{P_{out} * G}{4\pi r^2};$$

Note:

Note: The estimation distance is 20cm

Note:

PK Output power= conducted power.

Conducted power see the test report HK1904170865-3E, antenna gain=1dBi



Note: the device could not transmit simultaneously in 2.4G and 5G.

when the minimum test separation distance is >20 cm, a distance of 20 cm is applied to determine SAR test exclusion. The test exclusion threshold is 0.00629mW/cm^2 which is $< 1.0\text{mW/cm}^2$, SAR testing is not required.

-----The End-----