

TEST REPORT

Reference No...... : WTX25X09259866W002
FCC ID..... : 2AKIT-DBC03
Applicant..... : Lumi United Technology Co., Ltd
Address..... : B1, Chongwen Park, Nanshan iPark, Liuxian Avenue, Taoyuan Residential District, Nanshan District, Shenzhen, China
Manufacturer..... : The same as Applicant
Address..... : The same as Applicant
Product Name..... : Doorbell Camera G400 (Wired) , Doorbell Camera G400 Select (Wired)
Model No...... : DB-C03E
Standards..... : FCC Part 15.247
Date of Receipt sample..... : 2025-09-27
Date of Test..... : 2025-11-05 to 2025-12-29
Date of Issue..... : 2026-01-07
Test Report Form No...... : WTX_Part 15_247W
Test Result..... : **Pass**

Remarks:


The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of approver.

Prepared By:

Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road,
Block 70 Bao'an District, Shenzhen, Guangdong, China
Tel.: +86-755-33663308 Fax.: +86-755-33663309 Email: sem@waltek.com.cn

Tested by:



Dashan Chen/Project Engineer

Approved by:



Jason Su/Manager

TABLE OF CONTENTS

1. GENERAL INFORMATION	4
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
1.2 TEST STANDARDS	5
1.3 TEST METHODOLOGY	5
1.4 TEST FACILITY	5
1.5 EUT SETUP AND TEST MODE	6
1.6 MEASUREMENT UNCERTAINTY	7
1.7 TEST EQUIPMENT LIST AND DETAILS	8
2. SUMMARY OF TEST RESULTS	12
3. ANTENNA REQUIREMENT	13
3.1 STANDARD APPLICABLE	13
3.2 EVALUATION INFORMATION	13
4. POWER SPECTRAL DENSITY	14
4.1 STANDARD APPLICABLE	14
4.2 TEST SETUP BLOCK DIAGRAM	14
4.3 TEST PROCEDURE	14
4.4 SUMMARY OF TEST RESULTS/PLOTS	14
5. DTS BANDWIDTH	15
5.1 STANDARD APPLICABLE	15
5.2 TEST SETUP BLOCK DIAGRAM	15
5.3 TEST PROCEDURE	15
5.4 SUMMARY OF TEST RESULTS/PLOTS	15
6. RF OUTPUT POWER	16
6.1 STANDARD APPLICABLE	16
6.2 TEST SETUP BLOCK DIAGRAM	16
6.3 TEST PROCEDURE	16
6.4 SUMMARY OF TEST RESULTS/PLOTS	16
7. FIELD STRENGTH OF SPURIOUS EMISSIONS	17
7.1 STANDARD APPLICABLE	17
7.2 TEST PROCEDURE	17
7.3 CORRECTED AMPLITUDE & MARGIN CALCULATION	19
7.4 SUMMARY OF TEST RESULTS/PLOTS	19
8. OUT OF BAND EMISSIONS	28
8.1 STANDARD APPLICABLE	28
8.2 TEST PROCEDURE	28
8.3 SUMMARY OF TEST RESULTS/PLOTS	29
9. CONDUCTED EMISSIONS	38
9.1 TEST PROCEDURE	38
9.2 BASIC TEST SETUP BLOCK DIAGRAM	38
9.3 TEST RECEIVER SETUP	38
9.4 SUMMARY OF TEST RESULTS/PLOTS	38
APPENDIX SUMMARY	41
APPENDIX A: DTS BANDWIDTH	42
APPENDIX B: OCCUPIED CHANNEL BANDWIDTH	49
APPENDIX C: MAXIMUM CONDUCTED OUTPUT POWER	56
APPENDIX D: MAXIMUM POWER SPECTRAL DENSITY	57
APPENDIX F: BAND EDGE MEASUREMENTS	64
APPENDIX G: CONDUCTED SPURIOUS EMISSION	69
APPENDIX PHOTOGRAPHS	82

Report version

Version No.	Date of issue	Description
Rev.00	2026-01-07	Original
/	/	/

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

General Description of EUT	
Product Name:	Doorbell Camera G400 (Wired), Doorbell Camera G400 Select (Wired)
Trade Name:	Aqara
Model No.:	DB-C03E
Adding Model(s):	DB-C03D
Rated Voltage:	Doorbell Camera: PoE Input: IEEE 802.3af(48V) Power Input: 8-24V AC or 8-24V DC Chime: Power Input:5V
Battery Capacity:	/
Power Adapter Model:	/
<i>Note: The test data is gathered from a production sample provided by the manufacturer. The appearance of others models listed in the report is different from main-test model DB-C03E, but the circuit and the electronic construction do not change, declared by the manufacturer.</i>	

Technical Characteristics of EUT	
Support Standards:	802.11b, 802.11g, 802.11n, 802.11ax
Frequency Range:	2412-2462MHz for 802.11b/g/n/ax(HT/HE20) 2422-2452MHz for 802.11n/ax(HT/HE40)
RF Output Power:	15.59dBm (Conducted)
Type of Modulation:	CCK, OFDM, QPSK, BPSK, 16QAM, 64QAM, 256QAM, 1024QAM
Quantity of Channels:	11 for 802.11b/g/n/ax(HT/HE20); 7 for 802.11n/ax(HT/HE40)
Channel Separation:	5MHz
Type of Antenna:	FPC Antenna
Antenna Gain:	2.61dBi
<i>Note The Antenna Gain is provided by the customer and can affect the validity of results.</i>	

1.2 Test Standards

The tests were performed according to following standards:

FCC Rules Part 15.247: Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928MHz, 2400-2483.5MHz, and 5725-5850MHz.

558074 D01 15.247 Meas Guidance v05r02: Guidance for Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid System Devices Operating under section 15.247 of the FCC rules.

ANSI C63.10-2020: American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which results in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2020, KDB 558074 D01 15.247 Meas Guidance v05r02.

The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted accordingly in reference to the Operating Instructions.

1.4 Test Facility

Address of the test laboratory

Laboratory: Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road, Block 70 Bao'an District, Shenzhen, Guangdong, China

FCC – Registration No.: 125990

Waltek Testing Group (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. The Designation Number is CN5010, and Test Firm Registration Number is 125990.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Waltek Testing Group (Shenzhen) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A and the CAB identifier is CN0057.

1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, with a duty cycle equal to 100%, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	802.11b	Low:2412MHz, Middle:2437MHz,High:2462MHz
TM2	802.11g	Low:2412MHz, Middle:2437MHz,High:2462MHz
TM3	802.11n-HT20/802.11ax-HE20	Low:2412MHz, Middle:2437MHz,High:2462MHz
TM4	802.11n-HT40/802.11ax-HE40	Low:2422MHz, Middle:2437MHz,High:2452MHz

Test Conditions	
Temperature:	22~25 °C
Relative Humidity:	50~55 %.
ATM Pressure:	1019 mbar

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
Type-C Cable	1.0	Unshielded	Without Ferrite

Special Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
Router	Xiaomi	R4A	/
Wireless Router	MERCURY	MS08CP	/
Adapter	Ri Hui	RHDA240200	/
Adapter	Multicomp	SAW36-240-1500G	/

1.6 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	$\pm 0.57\text{dB}$
Occupied Bandwidth	Conducted	$\pm 0.015\text{MHz}$
Power Spectral Density	Conducted	$\pm 1.8\text{dB}$
Conducted Spurious Emission	Conducted	$\pm 2.17\text{dB}$
Conducted Emission 1#	Conducted	@9kHz to 150kHz: $\pm 3.74\text{dB}$
		@150kHz to 30MHz: $\pm 3.34\text{dB}$
Conducted Emission 2#	Conducted	@9kHz to 150kHz: $\pm 3.74\text{dB}$
		@150kHz to 30MHz: $\pm 3.34\text{dB}$
Transmitter Spurious Emissions chamber A	Radiated	@9kHz to 30MHz: $\pm 3.0\text{dB}$
		@30MHz to 1GHz: $\pm 5.70\text{dB}$
		@1GHz to 6GHz: $\pm 5.88\text{dB}$
		@6GHz to 18GHz: $\pm 5.96\text{dB}$
Transmitter Spurious Emissions chamber B	Radiated	@30MHz to 1GHz: $\pm 5.36\text{dB}$
Transmitter Spurious Emissions chamber C	Radiated	@9kHz to 30MHz: $\pm 3.0\text{dB}$
		@30MHz to 1GHz: $\pm 5.28\text{dB}$
		@1GHz to 6GHz: $\pm 5.56\text{dB}$
		@6GHz to 18GHz: $\pm 5.72\text{dB}$

1.7 Test Equipment List and Details

Fixed asset Number	Description	Manufacturer	Model	Serial No.	Cal Date	Due. Date
WTXE1041A 1001	Communication Tester	Rohde & Schwarz	CMW500	148650	2025-02-23	2026-02-22
WTXE1005A 1005	Spectrum Analyzer	Agilent	N9020A	US471401 02	2025-02-23	2026-02-22
WTXE1084A 1001	Spectrum Analyzer	Agilent	N9020A	MY543205 48	2025-02-23	2026-02-22
WTXE1005A 1006	Spectrum Analyzer	Rohde & Schwarz	FSP40	100612	2025-02-23	2026-02-22
WTXE1051A 1001	Power Sensor	Agilent	U2021XA	MY551600 07	2025-02-23	2026-02-22
WTXE1051A 1002	Power Sensor	Agilent	U2021XA	MY542400 01	2025-02-23	2026-02-22
WTXW1105A 1010	Spectrum Analyzer	KEYSIGHT	N9020A	MY512856 77	2025-02-23	2026-02-22
WTXE1105A 1008	RF Control Unit	Tonscend	JS0806-2	24F80620 870	2025-02-23	2026-02-22
WTXE1103A 1003	Attenuator	Pasternack	PE4007-4	/	2025-02-23	2026-02-22
WTXE1003A 1-005	Coaxial Cable	/	0M4RFC	/	2025-02-23	2026-02-22
☐ Chamber A: Below 1GHz						
WTXE1005A 1003	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/03 5	2025-02-23	2026-02-22
WTXE1001A 1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2025-02-23	2026-02-22
WTXE1007A 1002	Amplifier	HP	8447F	2805A034 75	2025-02-23	2026-02-22
WTXE1010A 1007	Loop Antenna	Schwarz beck	FMZB 1516	9773	2024-02-26	2026-02-25
WTXE1010A 1006	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2025-02-23	2026-02-22
WTXE1104A 1032-1	Coaxial Cable	/	RC_6G-N-M	/	2025-02-23	2026-02-22
WTXE1104A 1032-2	Coaxial Cable	/	RC_6G-N-M	/	2025-02-23	2026-02-22
WTXE1104A 1032-3	Coaxial Cable	/	RC_6G-N-M	/	2025-02-23	2026-02-22
☐ Chamber A: Above 1GHz						

WTXE1005A 1003	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/03 5	2025-02-23	2026-02-22
WTXE1001A 1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2025-02-23	2026-02-22
WTXE1065A 1001	Amplifier	C&D	PAP-1.0G18	14918	2025-02-23	2026-02-22
WTXE1010A 1005	Horn Antenna	ETS	3117	00086197	2025-02-23	2026-02-22
WTXE1010A 1010	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2024-03-17	2026-03-16
WTXE1003A 1001	Pre-amplifier	Schwarzbeck	BBV 9721	9721-031	2025-02-23	2026-02-22
WTXE1104A 1033-1	Coaxial Cable	/	C16-07-07	/	2025-02-23	2026-02-22
WTXE1104A 1033-2	Coaxial Cable	/	C16-07-07	/	2025-02-23	2026-02-22
WTXE1104A 1033-3	Coaxial Cable	/	C16-07-07	/	2025-02-23	2026-02-22
☐ Chamber B:Below 1GHz						
WTXE1010A 1006	Trilog Broadband Antenna	Schwarz beck	VULB9163(B)	9163-635	2024-03-17	2027-03-16
WTXE1038A 1001	Amplifier	Agilent	8447D	2944A104 57	2025-02-23	2026-02-22
WTXE1001A 1002	EMI Test Receiver	Rohde & Schwarz	ESPI	101391	2025-02-23	2026-02-22
WTXE1104A 1031-1	Coaxial Cable	/	1.5MRFC-LWB3	/	2025-02-23	2026-02-22
WTXE1104A 1031-2	Coaxial Cable	/	RG 316	/	2025-02-23	2026-02-22
WTXE1104A 1031-3	Coaxial Cable	/	RG 316	/	2025-02-23	2026-02-22
☒ Chamber C:Below 1GHz						
WTXE1093A 1001	EMI Test Receiver	Rohde & Schwarz	ESIB 26	100401	2025-02-23	2026-02-22
WTXE1010A 1013-1	Trilog Broadband Antenna	Schwarz beck	VULB 9168	1194	2024-04-18	2027-04-17
WTXE1010A 1007	Loop Antenna	Schwarz beck	FMZB 1516	9773	2024-02-26	2026-02-25
WTXE1007A 1003	Amplifier	HP	8447F	2944A038 69	2025-02-23	2026-02-22

WTXE1104A 1034-1	Coaxial Cable	/	RC_6G-N-M	/	2025-02-23	2026-02-22
WTXE1104A 1034-2	Coaxial Cable	/	RC_6G-N-M	/	2025-02-23	2026-02-22
WTXE1104A 1034-3	Coaxial Cable	/	RC_6G-N-M	/	2025-02-23	2026-02-22
☒ Chamber C: Above 1GHz						
WTXE1093A 1001	EMI Test Receiver	Rohde & Schwarz	ESIB 26	100401	2025-02-23	2026-02-22
WTXE1103A 1005	Horn Antenna	POAM	RTF-118A	1820	2025-06-13	2027-06-12
WTXE1103A 1006	Amplifier	Tonscend	TAP01018050	AP22E806 235	2025-02-23	2026-02-22
WTXE1010A 1010	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2024-03-17	2026-03-16
WTXE1003A 1001	Pre-amplifier	Schwarzbeck	BBV 9721	9721-031	2025-02-23	2026-02-22
WTXE1104A 1035-1	Coaxial Cable	/	RC-18G-N-M	/	2025-02-23	2026-02-22
WTXE1104A 1035-2	Coaxial Cable	/	RC-18G-N-M	/	2025-02-23	2026-02-22
WTXE1104A 1035-3	Coaxial Cable	/	RC-18G-N-M	/	2025-02-23	2026-02-22
☐ Conducted Room 1#						
WTXE1104A 1029	EMI Test Receiver	Rohde & Schwarz	ESCI	100525	2024-12-08	2025-12-07
					2025-11-25	2026-11-24
WTXE1002A 1001	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2025-02-23	2026-02-22
WTXE1003A 1001	AC LISN	Schwarz beck	NSLK8126	8126-279	2025-02-23	2026-02-22
WTXE1104A 1036	Coaxial Cable	/	RG 316	/	2025-02-23	2026-02-22
WTXE1104A 1038	Coaxial Cable	/	6MRFC-DP	/	2025-02-23	2026-02-22
☒ Conducted Room 2#						
WTXE1001A 1004	EMI Test Receiver	Rohde & Schwarz	ESPI	101259	2025-02-23	2026-02-22
WTXE1003A 1003	LISN	Rohde & Schwarz	ENV 216	100097	2025-02-23	2026-02-22
WTXE1104A 1037	Coaxial Cable	/	RG 316	/	2025-02-23	2026-02-22

Software List			
Description	Manufacturer	Model	Version
EMI Test Software/EZ-EMC (Radiated Emission A)	Farad	RA-03A1	1.1.4.2
EMI Test Software/EZ-EMC (Radiated Emission B)	Farad	RA-03A1	1.1.4.2
EMI Test Software/EZ-EMC (Radiated Emission C)	Farad	RA-03A1-2	1.1.4.2
EMI Test Software/EZ-EMC (Conducted Emission Room 1#)	Farad	3A1*CE-RE	1.1.4.3
EMI Test Software/EZ-EMC (Conducted Emission Room 2#)	Farad	3A1*CE-RE	1.1.4.3
RF Test System	Tonscend	JS1120-3	V3.5.39

*Remark: indicates software version used in the compliance certification testing.

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§15.203; §15.247(b)(4)(i)	Antenna Requirement	Compliant
§15.205	Restricted Band of Operation	Compliant
§15.207(a)	Conducted Emission	Compliant
§15.247(e)	Power Spectral Density	Compliant
§15.247(a)(2)	DTS Bandwidth	Compliant
§15.247(b)(3)	RF Output Power	Compliant
§15.209(a)	Radiated Emission	Compliant
§15.247(d)	Band Edge (Out of Band Emissions)	Compliant

N/A: Not applicable.

3. Antenna Requirement

3.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.2 Evaluation Information


This product has a FPC antenna, fulfill the requirement of this section.

4. Power Spectral Density

4.1 Standard Applicable

According to 15.247(e), for digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.

4.2 Test Setup Block Diagram



4.3 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.4 and ANSI C63.10-2020 Subclause 11.10.3, such specifications require that the same method as used to determine the conducted output power shall also be used to determine the power spectral density. The test method of power spectral density as below:

- Set instrument center frequency to DTS channel center frequency.
- Set span to at least 1.5 times the OBW.
- Set RBW to: $3\text{kHz} \leq \text{RBW} \leq 100\text{kHz}$.
- Set VBW $\geq 3 \times \text{RBW}$.
- Detector = power averaging (RMS) or sample detector (when RMS not available).
- Ensure that the number of measurement points in the sweep $\geq 2 \times \text{span}/\text{RBW}$.
- Sweep time = auto couple.
- Employ trace averaging (RMS) mode over a minimum of 100 traces.
- Use the peak marker function to determine the maximum amplitude level.
- If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span in order to meet the minimum measurement point requirement as the RBW is reduced).

4.4 Summary of Test Results/Plots


Please refer to Appendix D

5. DTS Bandwidth

5.1 Standard Applicable

According to 15.247(a)(2), systems using digital modulation techniques may operate in the 902–928MHz, 2400–2483.5MHz, and 5725–5850MHz bands. The minimum 6 dB bandwidth shall be at least 500kHz.

5.2 Test Setup Block Diagram



5.3 Test Procedure

According to the KDB 558074 D01 v05r02 Subclause 8.2 and ANSI C63.10-2020 Subclause 11.8.1, the test method of DTS Bandwidth as below:

Option 1:

The steps for the first option are as follows:

- Set RBW = shall be in the range of 1% to 5% of the OBW but not less than 100 kHz.
- Set the VBW $\geq [3 \times \text{RBW}]$.
- Detector = peak.
- Trace mode = max-hold.
- Sweep = No faster than coupled (auto) time.
- Allow the trace to stabilize.
- Measure the maximum width of the emission by placing two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-6 dB down amplitude”. If a marker is below this “-6 dB downamplitude” value, then it shall be as close as possible to this value.

Option 2:

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described in ANSI C63.10-2020 Subclause 11.8.1 (i.e., RBW = 100 kHz, VBW $\geq 3 \times \text{RBW}$, and peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥ 6 dB

5.4 Summary of Test Results/Plots

Please refer to Appendix A&B

6. RF Output Power

6.1 Standard Applicable

According to 15.247(b)(3), for systems using digital modulation in the 902–928MHz, 2400–2483.5MHz, and 5725–5850MHz bands: 1 Watt.

6.2 Test Setup Block Diagram



6.3 Test Procedure

The EUT was directly connected to the Power meter.

6.4 Summary of Test Results/Plots

Please refer to Appendix C

7. Field Strength of Spurious Emissions

7.1 Standard Applicable

According to §15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30dB instead of 20dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).


The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

7.2 Test Procedure


The setup of EUT is according with per ANSI C63.10-2020 measurement procedure. The specification used was with the FCC Part 15.205 15.247(a) and FCC Part 15.209 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40cm long in the middle. The spacing between the peripherals was 10cm.


The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30MHz to 1GHz.



The test setup for emission measurement above 1GHz.



Frequency :9kHz-30MHz	Frequency :30MHz-1GHz	Frequency :Above 1GHz
RBW=10kHz,	RBW=120kHz,	RBW=1MHz,
VBW =30kHz	VBW=300kHz	VBW=3MHz(Peak), 10Hz(AV)
Sweep time= Auto	Sweep time= Auto	Sweep time= Auto
Trace = max hold	Trace = max hold	Trace = max hold
Detector function = peak	Detector function = peak, QP	Detector function = peak, AV

7.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dB μ V means the emission is 6dB μ V below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$


7.4 Summary of Test Results/Plots

Note: 1.This EUT was tested in 3 orthogonal positions and the worst case position data was reported.

All test modes (different data rate and different modulation) are performed, but only the worst case(802.11b_11Mbps) is recorded in this report.


➤ Spurious Emissions Below 1GHz

802.11b_11Mbps			
Test Channel	Low(worst case)	Polarity:	Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	34.5269	26.04	-9.57	16.47	40.00	-23.53	-	-	peak
2	70.2095	27.50	-10.48	17.02	40.00	-22.98	-	-	peak
3	120.6117	27.83	-10.25	17.58	43.50	-25.92	-	-	peak
4	263.1154	28.48	-9.61	18.87	46.00	-27.13	-	-	peak
5	442.5721	30.38	-4.97	25.41	46.00	-20.59	-	-	peak
6	776.4848	28.65	1.45	30.10	46.00	-15.90	-	-	peak

802.11b_11Mbps			
Test Channel	Low(worst case)	Polarity:	Vertical




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	43.2332	26.09	-8.52	17.57	40.00	-22.43	-	-	peak
2	74.2696	29.27	-11.23	18.04	40.00	-21.96	-	-	peak
3	148.9173	33.26	-8.57	24.69	43.50	-18.81	-	-	peak
4	257.6266	28.36	-9.77	18.59	46.00	-27.41	-	-	peak
5	464.8867	28.76	-4.44	24.32	46.00	-21.68	-	-	peak
6	776.4848	29.36	1.45	30.81	46.00	-15.19	-	-	peak

Remark: '-' Means the test Degree and Height are not recorded by the test software and only show the worst case in the test report.


- Spurious Emissions Above 1GHz
- Test Mode: 802.11b_11Mbps (worst case)

Test Channel	Low	Polarity:	Horizontal
--------------	-----	-----------	------------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	4824.000	54.00	-11.92	42.08	74.00	-31.92	-	-	peak
2	7236.000	54.53	-6.41	48.12	74.00	-25.88	-	-	peak

Test Channel	Low	Polarity:	Vertical
--------------	-----	-----------	----------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	4824.000	54.30	-11.92	42.38	74.00	-31.62	-	-	peak
2	7236.000	54.37	-6.41	47.96	74.00	-26.04	-	-	peak

➤ Test Channel	Middle	Polarity:	Horizontal
----------------	--------	-----------	------------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	4874.000	53.70	-11.79	41.91	74.00	-32.09	-	-	peak
2	7311.000	52.32	-4.97	47.35	74.00	-26.65	-	-	peak

Test Channel	Middle	Polarity:	Vertical
--------------	--------	-----------	----------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	4874.000	52.03	-11.79	40.24	74.00	-33.76	-	-	peak
2	7311.000	50.85	-4.97	45.88	74.00	-28.12	-	-	peak

➤ Test Channel	High	Polarity:	Horizontal
----------------	------	-----------	------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	4924.000	53.80	-12.33	41.47	74.00	-32.53	-	-	peak
2	7386.000	53.08	-6.00	47.08	74.00	-26.92	-	-	peak

Test Channel	High	Polarity:	Vertical
--------------	------	-----------	----------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	4924.000	53.80	-12.33	41.47	74.00	-32.53	-	-	peak
2	7386.000	53.08	-6.00	47.08	74.00	-26.92	-	-	peak

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Conducted Spurious Emission Please refer to Appendix F

8. Out of Band Emissions

8.1 Standard Applicable

According to §15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30dB instead of 20dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

8.2 Test Procedure

According to the KDB 558074D01 v05r02 Subclause 8.4 and ANSI C63.10-2020 Subclause 11.11, the Emissions in nonrestricted frequency bands test method as follows:

- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the RBW = 100kHz.
- c) Set the VBW $\geq [3 \times \text{RBW}]$.
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

According to the KDB 558074 D01 v05r02 Subclause 8.5 and ANSI C63.10-2020 Subclause 11.12, the Emissions in restricted frequency bands test method as follows:

A. Radiated emission measurements:

Set span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation (2310MHz to 2420MHz for low bandedge, 2460MHz to 2500MHz for the high bandedge)

RBW = 1MHz, VBW = 1MHz for peak value measured

RBW = 1MHz, VBW = 10Hz for average value measured

Sweep = auto; Detector function = peak/average; Trace = max hold

All the trace to stabilize, set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. Those emission

must comply with the 15.209 limit for fall in the restricted bands listed in section 15.205. Note that the method of measurement KDB publication number: 913591 may be used for the radiated bandedge measurements.

B. Antenna-port conducted measurements

Peak emission levels are measured by setting the instrument as follows:

- a) RBW = as specified in Table 9.
- b) VBW $\geq [3 \times \text{RBW}]$.
- c) Detector = peak.
- d) Sweep time = auto.
- e) Trace mode = max hold.
- f) Allow sweeps to continue until the trace stabilizes. (Note that the required measurement time may be lengthened for low-duty-cycle applications.)

Table 9—RBW as a function of frequency

Frequency	RBW
9 kHz to 150 kHz	200 Hz to 300 Hz
0.15 MHz to 30 MHz	9 kHz to 10 kHz
30 MHz to 1000 MHz	100 kHz to 120 kHz
>1000 MHz	1 MHz

If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in section 8.1. Report the three highest emissions relative to the limit.

8.3 Summary of Test Results/Plots


➤ Radiated test

802.11b_11Mbps			
Test Channel	Low	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	42.76	0.50	43.26	54.00	-10.74	Average Detector
	2310.000	56.45	0.50	56.95	74.00	-17.05	Peak Detector
2	2390.000	43.57	0.69	44.26	54.00	-9.74	Average Detector
	2390.000	56.74	0.69	57.43	74.00	-16.57	Peak Detector
3	2400.000	51.30	0.71	52.01	Delta=50.8dBc		Average Detector
4	2411.084	102.07	0.74	102.81			Average Detector

802.11b_11Mbps			
Test Channel	High	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2461.234	101.23	0.85	102.08	/	/	Average Detector
	2462.929	106.03	0.86	106.89	/	/	Peak Detector
2	2483.500	43.25	0.91	44.16	54.00	-9.84	Average Detector
	2483.500	56.31	0.91	57.22	74.00	-16.78	Peak Detector
3	2500.000	42.94	0.95	43.89	54.00	-10.11	Average Detector
	2500.000	55.62	0.95	56.57	74.00	-17.43	Peak Detector

802.11g_54Mbps			
Test Channel	Low	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	42.82	0.50	43.32	54.00	-10.68	Average Detector
	2310.000	55.42	0.50	55.92	74.00	-18.08	Peak Detector
2	2390.000	45.71	0.69	46.40	54.00	-7.60	Average Detector
	2390.000	68.99	0.69	69.68	74.00	-4.32	Peak Detector

802.11g_54Mbps			
Test Channel	High	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2460.836	95.29	0.85	96.14	/	/	Average Detector
	2463.827	109.10	0.86	109.96	/	/	Peak Detector
2	2483.500	47.08	0.91	47.99	54.00	-6.01	Average Detector
	2483.500	66.22	0.91	67.13	74.00	-6.87	Peak Detector
3	2500.000	42.96	0.95	43.91	54.00	-10.09	Average Detector
	2500.000	56.08	0.95	57.03	74.00	-16.97	Peak Detector

802.11n-HT20_MCS7			
Test Channel	Low	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	42.82	0.50	43.32	54.00	-10.68	Average Detector
	2310.000	56.33	0.50	56.83	74.00	-17.17	Peak Detector
2	2390.000	45.70	0.69	46.39	54.00	-7.61	Average Detector
	2390.000	68.31	0.69	69.00	74.00	-5.00	Peak Detector

802.11n-HT20_MCS7			
Test Channel	High	Polarity:	Horizontal(worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2461.035	92.87	0.85	93.72	/	/	Average Detector
	2463.128	107.01	0.86	107.87	/	/	Peak Detector
2	2483.500	44.88	0.91	45.79	54.00	-8.21	Average Detector
	2483.500	67.06	0.91	67.97	74.00	-6.03	Peak Detector
3	2500.000	42.82	0.95	43.77	54.00	-10.23	Average Detector
	2500.000	56.21	0.95	57.16	74.00	-16.84	Peak Detector

802.11n-HT40_MCS7			
Test Channel	Low	Polarity:	Horizontal(worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	42.87	0.50	43.37	54.00	-10.63	Average Detector
	2310.000	56.10	0.50	56.60	74.00	-17.40	Peak Detector
2	2390.000	50.06	0.69	50.75	54.00	-3.25	Average Detector
	2390.000	68.46	0.69	69.15	74.00	-4.85	Peak Detector

802.11n-HT40_MCS7			
Test Channel	High	Polarity:	Horizontal(worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2454.044	87.59	0.84	88.43	/	/	Average Detector
	2449.718	105.69	0.83	106.52	/	/	Peak Detector
2	2483.500	49.31	0.91	50.22	54.00	-3.78	Average Detector
	2483.500	66.04	0.91	66.95	74.00	-7.05	Peak Detector
3	2500.000	43.45	0.95	44.40	54.00	-9.60	Average Detector
	2500.000	55.82	0.95	56.77	74.00	-17.23	Peak Detector

➤ Conducted test
Please refer to Appendix D&E


9. Conducted Emissions

9.1 Test Procedure

The setup of EUT is according with per ANSI C63.10-2020 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40cm long in the middle. The spacing between the peripherals was 10cm.

9.2 Basic Test Setup Block Diagram




9.3 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency.....	150kHz
Stop Frequency.....	30MHz
Sweep Speed.....	Auto
IF Bandwidth.....	10kHz
Quasi-Peak Adapter Bandwidth.....	9kHz
Quasi-Peak Adapter Mode.....	Normal


9.4 Summary of Test Results/Plots

Test Mode	Communication	AC120V 60Hz	Polarity:	Neutral
-----------	---------------	-------------	-----------	---------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1780	40.77	9.54	50.31	64.57	-14.26	QP
2	0.1780	26.44	9.54	35.98	54.57	-18.59	AVG
3	0.2779	33.11	9.63	42.74	60.88	-18.14	QP
4	0.2779	20.58	9.63	30.21	50.88	-20.67	AVG
5	0.6060	33.85	9.69	43.54	56.00	-12.46	QP
6	0.6300	23.89	9.70	33.59	46.00	-12.41	AVG
7	2.2740	27.33	9.37	36.70	56.00	-19.30	QP
8	3.0100	13.81	9.40	23.21	46.00	-22.79	AVG
9	6.5500	31.41	9.74	41.15	60.00	-18.85	QP
10	8.5659	17.89	9.80	27.69	50.00	-22.31	AVG
11	26.4860	37.47	9.55	47.02	60.00	-12.98	QP
12*	29.2340	30.55	9.55	40.10	50.00	-9.90	AVG

Test Mode	Communication	AC120V 60Hz	Polarity:	Line
-----------	---------------	-------------	-----------	------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.1780	41.72	9.54	51.26	64.57	-13.31	QP
2	0.1780	28.83	9.54	38.37	54.57	-16.20	AVG
3	0.6180	37.63	9.70	47.33	56.00	-8.67	QP
4*	0.6300	30.12	9.70	39.82	46.00	-6.18	AVG
5	1.3300	15.73	9.63	25.36	46.00	-20.64	AVG
6	1.4740	33.09	9.57	42.66	56.00	-13.34	QP
7	4.3380	16.27	9.49	25.76	46.00	-20.24	AVG
8	5.2100	33.90	9.59	43.49	60.00	-16.51	QP
9	6.5700	34.68	9.75	44.43	60.00	-15.57	QP
10	6.5700	18.49	9.75	28.24	50.00	-21.76	AVG
11	25.6940	38.10	9.55	47.65	60.00	-12.35	QP
12	27.1580	30.55	9.55	40.10	50.00	-9.90	AVG

APPENDIX SUMMARY


Project No.	WTX25X09259866W002	Test Engineer	BAldi Zhong
Start date	2025/11/5	Finish date	2025/12/29
Temperature	22.6℃	Humidity	57%
RF specifications	2.4G-WiFi		

APPENDIX	Description of Test Item	Result
A	DTS Bandwidth	Compliant
B	Occupied Channel Bandwidth	Compliant
C	Maximum conducted output power	Compliant
D	Maximum power spectral density	Compliant
E	Band edge measurements	Compliant
F	Conducted Spurious Emission	Compliant

Appendix A: DTS Bandwidth**Test Result**

TestMode	Antenna	Frequency[MHz]	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	9.040	2407.480	2416.520	0.5	PASS
11B	Ant1	2437	8.600	2432.960	2441.560	0.5	PASS
11B	Ant1	2462	9.080	2457.480	2466.560	0.5	PASS
11G	Ant1	2412	16.000	2403.880	2419.880	0.5	PASS
11G	Ant1	2437	16.320	2428.840	2445.160	0.5	PASS
11G	Ant1	2462	15.640	2454.120	2469.760	0.5	PASS
11N20SISO	Ant1	2412	16.680	2403.840	2420.520	0.5	PASS
11N20SISO	Ant1	2437	17.040	2428.520	2445.560	0.5	PASS
11N20SISO	Ant1	2462	16.640	2453.520	2470.160	0.5	PASS
11N40SISO	Ant1	2422	34.960	2404.560	2439.520	0.5	PASS
11N40SISO	Ant1	2437	35.120	2419.480	2454.600	0.5	PASS
11N40SISO	Ant1	2452	35.120	2434.480	2469.600	0.5	PASS
11AX20SISO	Ant1	2412	17.840	2403.000	2420.840	0.5	PASS
11AX20SISO	Ant1	2437	18.200	2427.880	2446.080	0.5	PASS
11AX20SISO	Ant1	2462	16.680	2453.160	2469.840	0.5	PASS
11AX40SISO	Ant1	2422	36.080	2403.440	2439.520	0.5	PASS
11AX40SISO	Ant1	2437	36.320	2418.200	2454.520	0.5	PASS
11AX40SISO	Ant1	2452	36.000	2433.600	2469.600	0.5	PASS


Test Graphs



11B-Ant1-2412-PASS




11B-Ant1-2437-PASS




11B-Ant1-2462-PASS



11G-Ant1-2412-PASS




11G-Ant1-2437-PASS




11G-Ant1-2462-PASS







11N40SISO-Ant1-2422-PASS




11N40SISO-Ant1-2437-PASS




11N40SISO-Ant1-2452-PASS




11AX20SISO-Ant1-2412-PASS




11AX20SISO-Ant1-2437-PASS




11AX20SISO-Ant1-2462-PASS



11AX40SISO-Ant1-2422-PASS



11AX40SISO-Ant1-2437-PASS



11AX40SISO-Ant1-2452-PASS

Appendix B: Occupied Channel Bandwidth


Test Result

TestMode	Antenna	Channel Frequency[MHz]	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	13.281	2405.4136	2418.6946	---	---
11B	Ant1	2437	13.284	2430.4055	2443.6895	---	---
11B	Ant1	2462	13.355	2455.3579	2468.7129	---	---
11G	Ant1	2412	17.276	2403.3418	2420.6178	---	---
11G	Ant1	2437	17.298	2428.3018	2445.5998	---	---
11G	Ant1	2462	17.332	2453.2851	2470.6171	---	---
11N20SISO	Ant1	2412	18.366	2402.7985	2421.1645	---	---
11N20SISO	Ant1	2437	18.417	2427.7913	2446.2083	---	---
11N20SISO	Ant1	2462	18.471	2452.7564	2471.2274	---	---
11N40SISO	Ant1	2422	36.719	2403.5789	2440.2979	---	---
11N40SISO	Ant1	2437	36.911	2418.5019	2455.4129	---	---
11N40SISO	Ant1	2452	36.754	2433.6108	2470.3648	---	---
11AX20SISO	Ant1	2412	19.272	2402.3564	2421.6284	---	---
11AX20SISO	Ant1	2437	19.300	2427.3560	2446.6560	---	---
11AX20SISO	Ant1	2462	19.227	2452.3903	2471.6173	---	---
11AX40SISO	Ant1	2422	37.849	2403.0953	2440.9443	---	---
11AX40SISO	Ant1	2437	38.067	2417.9666	2456.0336	---	---
11AX40SISO	Ant1	2452	38.031	2432.9676	2470.9986	---	---


Test Graphs




11B-Ant1-2412




11B-Ant1-2437



11B-Ant1-2462




11G-Ant1-2412




11G-Ant1-2437



11G-Ant1-2462



11N20SISO-Ant1-2412



11N20SISO-Ant1-2437



11N20SISO-Ant1-2462