



REPORT No.: SZ16120062W03

FCC RF TEST REPORT

APPLICANT : Beijing LLVision Technology Co., Ltd

PRODUCT NAME : Smart Glass Host

MODEL NAME : GLXSS Pro

TRADE NAME : GLXSS

BRAND NAME : GLXSS

FCC ID : 2AKLNG20A1

STANDARD(S) : 47 CFR Part 15 Subpart C

ISSUE DATE : 2017-02-08



SHENZHEN MORLAB COMMUNICATIONS TECHNOLOGY Co., Ltd.

NOTE: This document is issued by MORLAB, the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

MORLAB GROUP

FL1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China

Tel: 86-755-36698555
Http://www.morlab.com

Fax: 86-755-36698525
E-mail: service@morlab.cn



DIRECTORY

TEST REPORT DECLARATION.....4

1. TECHNICAL INFORMATION5

1.1 APPLICANT INFORMATION5

1.2 EQUIPMENT UNDER TEST (EUT) DESCRIPTION5

1.2.1 IDENTIFICATION OF ALL USED EUTS6

1.3 TEST STANDARDS AND RESULTS6

1.3.1 TEST ENVIRONMENT CONDITIONS6

2. 47 CFR PART 15C REQUIREMENTS.....7

2.1 ANTENNA REQUIREMENT7

2.1.1 APPLICABLE STANDARD7

2.1.2 RESULT: COMPLIANT7

2.2 PEAK OUTPUT POWER.....7

2.2.1 REQUIREMENT7

2.2.2 TEST DESCRIPTION7

2.2.3 TEST RESULT.....8

2.3 BANDWIDTH10

2.3.1 REQUIREMENT 10

2.3.2 TEST DESCRIPTION 10

2.3.3 TEST RESULT..... 10

2.4 CONDUCTED SPURIOUS EMISSIONS AND BAND EDGE19

2.4.1 REQUIREMENT 19

2.4.2 TEST DESCRIPTION 19

2.4.3 TEST RESULT..... 19

2.5 POWER SPECTRAL DENSITY (PSD)32

2.5.1 REQUIREMENT..... 32

2.5.2 TEST DESCRIPTION 32

2.5.3 TEST RESULT..... 33

2.6 RESTRICTED FREQUENCY BANDS41

2.6.1 REQUIREMENT..... 41

2.6.2 TEST DESCRIPTION 41

2.6.3 TEST RESULT..... 42



REPORT No.: SZ16120062W03

2.7	CONDUCTED EMISSION	53
2.7.1	REQUIREMENT	53
2.7.2	TEST DESCRIPTION	53
2.1.1	TEST RESULT	54
2.8	RADIATED EMISSION	56
2.8.1	REQUIREMENT	56
2.8.2	TEST DESCRIPTION	57
2.8.3	TEST RESULT	59
ANNEX A GENERAL INFORMATION		72

Change History		
Issue	Date	Reason for change
1.0	2017-02-08	First edition



REPORT No.: SZ16120062W03

TEST REPORT DECLARATION

Applicant	Beijing LLVision Technology Co., Ltd
Applicant Address	Room903, Unit A, The Spaces International Center, No.8 Dongdaqiao Road, Chaoyang District, Beijing, P.R. China
Manufacturer Address	Huizhou BYD Electronic Company Limited
Manufacturer	Xiang shui River Daya Bay Economic Development Zone Huizhou Guangdong
Product Name	Smart Glass Host
Model Name	GLXSS Pro
Brand Name	GLXSS
HW Version	B2
SW Version	G20A_V03.1201
Test Standards	47 CFR Part 15 Subpart C
Test Date	2016-12-20 to 2016-12-31
Test Result	PASS

Tested by : Li Jingzong
Li Jingzong

Reviewed by : Qiu Xiaojun
Qiu Xiaojun

Approved by : Peng Huarui
Peng Huarui



1. TECHNICAL INFORMATION

Note: Provide by applicant.

1.1 Applicant Information

Company:	Beijing LLVision Technology Co., Ltd
Address	Room903, Unit A, The Spaces International Center, No.8 Dongdaqiao Road, Chaoyang District, Beijing, P.R. China

1.2 Equipment under Test (EUT) Description

Brand Name:	GLXSS
Trade Name:	GLXSS
Model Name:	GLXSS Pro
Frequency Range:	802.11b/g/n-20MHz: 2.412GHz - 2.462GHz 802.11n-40MHz: 2.422GHz - 2.452GHz
Channel Number:	802.11b/g/n-20MHz: 11 802.11n-40MHz: 7
Modulation Type:	DSSS, OFDM
Antenna Type:	Ceramic Antenna
Antenna Gain:	1.66 dBi

NOTE:

1. The EUT is a Smart Glass Host, it's operating at 2.4GHz ISM; it supports 802.11b, 802.11g, 802.11n and they are all tested in this report.
For 802.11b/g/n-20MHz (2.4GHz band), the frequencies allocated is $F \text{ (MHz)} = 2412 + 5 * (n - 1)$ ($1 \leq n \leq 11$). The lowest, middle, highest channel numbers of the EUT used and tested in this report are separately 1 (2412MHz), 6 (2437MHz) and 11 (2462MHz).
For 802.11n-40MHz, the frequencies allocated is $F \text{ (MHz)} = 2412 + 5 * (n - 1)$ ($3 \leq n \leq 9$). The lowest, middle, highest channel numbers of the EUT used and tested in this report are separately 3 (2422MHz), 6 (2437MHz) and 9 (2452MHz).
2. The EUT connected to the serial port of the computer with a serial communication cable, we use the dedicated software to control the EUT continuous transmission. And the duty cycle is 100%.
3. For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.



1.2.1 Identification of all used EUTs

The EUT identity consists of numerical and letter characters, the letter character indicates the test sample, and the following two numerical characters indicate the software version of the test sample.

EUT Identity	Hardware Version	Software Version
A01	B2	G20A_V03.1201

1.3 Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart C (Bluetooth, 2.4GHz ISM band radiators) for the EUT FCC ID Certification:

No.	Identity	Document Title
1	47 CFR Part 15 (10-1-15 Edition)	Radio Frequency Devices

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Test Date	Result
1	15.203	Antenna Requirement	N.A	<u>PASS</u>
2	15.247(b)	Peak Output Power	Dec 25, 2016	<u>PASS</u>
3	15.247(a)	Bandwidth	Dec 25, 2016	<u>PASS</u>
4	15.247(d)	Conducted Spurious Emission and Band Edge	Dec 25, 2016	<u>PASS</u>
5	15.247(d)	Restricted Frequency Bands	Dec 28, 2016	<u>PASS</u>
6	15.207	Conducted Emission	Dec 28, 2016	<u>PASS</u>
7	15.209 ,15.247(d)	Radiated Emission	Dec 28, 2016	<u>PASS</u>
8	15.247(e)	Power spectral density (PSD)	Dec 25, 2016	<u>PASS</u>

The tests of Conducted Emission and Radiated Emission were performed according to the method of measurements prescribed in ANSI C63.10 2013 and KDB558074 D01 v03r05 (04/08/2016).

1.3.1 Test Environment Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15 - 35
Relative Humidity (%):	30 -60
Atmospheric Pressure (kPa):	86-106

2. 47 CFR PART 15C REQUIREMENTS

2.1 Antenna requirement

2.1.1 Applicable Standard

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

2.1.2 Result: Compliant

The EUT has a permanently and irreplaceable attached antenna. Please refer to the EUT internal photos.

2.2 Peak Output Power

2.2.1 Requirement

According to FCC section 15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: The maximum peak conducted output power of the intentional radiator shall not exceed 1 Watt.

2.2.2 Test Description

The measured output power was calculated by the reading of the USB Wideband Power Sensor and calibration.

A. Test Setup:



The EUT (Equipment under the test) which is coupled to the USB Wideband Power Sensor; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading, all test result in power meter.

B. Equipments List:

Please reference ANNEX A(1.5).



2.2.3 Test Result

The lowest, middle and highest channels are selected to perform testing to verify the conducted RF output peak power of the Module.

2.2.3.1 802.11b Test Mode

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
1	2412	16.75	0.0473	30	1	PASS
6	2437	16.81	0.0480			PASS
11	2462	17.04	0.0506			PASS

Channel	Frequency (MHz)	Measured Output Average Power		Limit		Verdict
		dBm	W	dBm	W	
1	2412	13.27	0.0212	30	1	PASS
6	2437	13.36	0.0217			PASS
11	2462	13.52	0.0225			PASS

2.2.3.2 802.11g Test mode

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
1	2412	21.75	0.1496	30	1	PASS
6	2437	21.84	0.1528			PASS
11	2462	22.12	0.1629			PASS

Channel	Frequency (MHz)	Measured Output Average Power		Limit		Verdict
		dBm	W	dBm	W	
1	2412	11.46	0.0140	30	1	PASS
6	2437	11.66	0.0147			PASS
11	2462	11.75	0.0150			PASS

**2.2.3.3 802.11n-20MHz Test mode**

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
1	2412	20.52	0.1127	30	1	PASS
6	2437	20.73	0.1183			PASS
11	2462	20.85	0.1216			PASS

Channel	Frequency (MHz)	Measured Output Average Power		Limit		Verdict
		dBm	W	dBm	W	
1	2412	8.90	0.0078	30	1	PASS
6	2437	8.99	0.0079			PASS
11	2462	9.25	0.0084			PASS

2.2.3.4 802.11n-40MHz Test mode

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
3	2422	19.87	0.0971	30	1	PASS
6	2437	19.29	0.0849			PASS
9	2452	19.22	0.0836			PASS

Channel	Frequency (MHz)	Measured Output Average Power		Limit		Verdict
		dBm	W	dBm	W	
3	2422	7.99	0.0063	30	1	PASS
6	2437	8.12	0.0065			PASS
9	2452	8.15	0.0065			PASS




2.3 Bandwidth

2.3.1 Requirement

According to FCC section 15.247(a) (2), Systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

2.3.2 Test Description

A. Test Set:



The EUT is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

KDB 558074 Section 8.1 Option 1 was used in order to prove compliance.

B. Equipments List:

Please reference ANNEX A(1.5).

2.3.3 Test Result

The lowest, middle and highest channels are selected to perform testing to record the 6 dB bandwidth of the Module.




REPORT No.: SZ16120062W03

2.3.3.1 802.11b Test mode

A. Test Verdict:

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limits(kHz)	Result
1	2412	8.355	≥ 500	PASS
6	2437	8.361	≥ 500	PASS
11	2462	7.926	≥ 500	PASS


B. Test Plots




(Channel 1: 2412MHz @ 802.11b)



REPORT No.: SZ16120062W03



(Channel 6: 2437 MHz @ 802.11b)



(Channel 11: 2462MHz @ 802.11b)




REPORT No.: SZ16120062W03

2.3.3.2 802.11g Test mode

A. Test Verdict:

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limits (kHz)	Result
1	2412	16.474	≥ 500	PASS
6	2437	16.472	≥ 500	PASS
11	2462	16.486	≥ 500	PASS


B. Test Plots:




(Channel 1: 2412MHz @ 802.11g)



REPORT No.: SZ16120062W03



(Channel 6: 2437MHz @ 802.11g)



(Channel 11: 2462MHz @ 802.11g)




REPORT No.: SZ16120062W03

2.3.3.3 802.11n-20 Test mode

A. Test Verdict:

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limits (kHz)	Result
1	2412	17.694	≥500	PASS
6	2437	17.690	≥500	PASS
11	2462	17.721	≥500	PASS


B. Test Plots:




(Channel 1: 2412MHz @ 802.11n-20)



REPORT No.: SZ16120062W03



(Channel 6: 2437MHz @ 802.11n-20)



(Channel 11: 2462MHz @ 802.11n-20)




REPORT No.: SZ16120062W03

2.3.3.4 802.11n-40 Test mode

A. Test Verdict:

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limits (kHz)	Result
3	2422	36.443	≥500	PASS
6	2437	36.465	≥500	PASS
9	2452	36.494	≥500	PASS


B. Test Plots:




(Channel 3: 2422Mz @ 802.11n-40)



REPORT No.: SZ16120062W03



(Channel 6: 2437MHz @ 802.11n-40)



(Channel 9: 2452MHz @ 802.11n-40)


2.4 Conducted Spurious Emissions and Band Edge

2.4.1 Requirement

According to FCC section 15.247(c), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

2.4.2 Test Description

A. Test Set:



The EUT is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

KDB 558074 Section 11.0 was used in order to prove compliance.

B. Equipments List:

Please reference ANNEX A(1.5).

2.4.3 Test Result

The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions.



REPORT No.: SZ16120062W03


2.4.3.1 802.11b Test mode

A. Test Verdict:

Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
			Carrier Level	Calculated -20dBc Limit	
1	2412	-40.64	4.19	-15.81	PASS
6	2437	-40.19	4.33	-15.67	PASS
11	2462	-41.28	4.62	-15.38	PASS

B. Test Plots:


Note: the power of the Module transmitting frequency should be ignored.




(Channel = 1, 30MHz to 25GHz)



REPORT No.: SZ16120062W03




(Band Edge @ Channel = 1)




(Channel = 6, 30MHz to 25GHz)



REPORT No.: SZ16120062W03



(Channel = 11, 30MHz to 25GHz)



(Band Edge @ Channel = 11)



REPORT No.: SZ16120062W03


2.4.3.2 802.11g Test mode

A. Test Verdict:

Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
			Carrier Level	Calculated -20dBc Limit	
1	2412	-45.63	2.70	-17.30	PASS
6	2437	-45.63	2.48	-17.52	PASS
11	2462	-46.12	2.75	-17.25	PASS

B. Test Plots:


Note: the power of the Module transmitting frequency should be ignored.




(Channel = 1, 30MHz to 25GHz)



REPORT No.: SZ16120062W03




(Band Edge @ Channel = 1)




(Channel = 6, 30MHz to 25GHz)



REPORT No.: SZ16120062W03



(Channel = 11, 30MHz to 25GHz)



(Band Edge @ Channel = 11)




REPORT No.: SZ16120062W03

2.4.3.3 802.11n -20MHz Test mode**A. Test Verdict:**

Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
			Carrier Level	Calculated -20dBc Limit	
1	2412	-41.00	0.22	-19.78	PASS
6	2437	-40.03	0.40	-19.60	PASS
11	2462	-41.14	0.26	-19.74	PASS

B. Test Plots:


Note: the power of the Module transmitting frequency should be ignored.




(Channel = 1, 30MHz to 25GHz)



REPORT No.: SZ16120062W03




(Band Edge @ Channel = 1)




(Channel = 6, 30MHz to 25GHz)



REPORT No.: SZ16120062W03



(Channel = 11, 30MHz to 25GHz)



(Band Edge @ Channel = 11)




REPORT No.: SZ16120062W03

2.4.3.4 802.11n -40MHz Test mode**A. Test Verdict:**

Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
			Carrier Level	Calculated -20dBc Limit	
3	2422	-40.89	-2.31	-22.31	PASS
6	2437	-40.49	-2.47	-22.47	PASS
9	2452	-39.67	-1.95	-21.95	PASS

B. Test Plots:


Note: the power of the Module transmitting frequency should be ignored.




(Channel = 3, 30MHz to 25GHz)



REPORT No.: SZ16120062W03




(Band Edge @ Channel = 3)




(Channel = 6, 30MHz to 25GHz)



REPORT No.: SZ16120062W03



(Channel = 9, 30MHz to 25GHz)



(Band Edge @ Channel = 9)

2.5 Power spectral density (PSD)

2.5.1 Requirement

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.


2.5.2 Test Description

A. Test procedure

The measured power spectral density was calculated by the reading of the spectrum analyzer and calibration. Following is the test procedure for PSD test:

- Set analyzer center frequency to channel center frequency.
- Set the span to 30MHz
- Set the RBW to 3 kHz
- Set the VBW to 10KHz
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level within the RBW.

B. Test Set:



The EUT is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

KDB 558074 Section 10.2 was used in order to prove compliance.

C. Equipments List:

Please reference ANNEX A(1.5).



REPORT No.: SZ16120062W03


2.5.3 Test Result

2.5.3.1 802.11b Test mode

A. Test Verdict:

Spectral power density (dBm/3kHz)				
Channel	Frequency (MHz)	Measured PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
1	2412	-9.00	8	PASS
6	2437	-9.12	8	PASS
11	2462	-7.66	8	PASS
Measurement uncertainty: ± 1.3 dB				


B. Test Plots:




(Channel = 1 @ 802.11b)



REPORT No.: SZ16120062W03



(Channel = 6 @ 802.11b)



(Channel = 11 @ 802.11b)




REPORT No.: SZ16120062W03

2.5.3.2 802.11g Test mode

A. Test Verdict:

Spectral power density (dBm/3kHz)				
Channel	Frequency (MHz)	Measured PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
1	2412	-12.84	8	PASS
6	2437	-12.99	8	PASS
11	2462	-12.82	8	PASS
Measurement uncertainty: ± 1.3 dB				


B. Test Plots:




(Channel = 1 @ 802.11g)



REPORT No.: SZ16120062W03



(Channel = 6 @ 802.11g)



(Channel = 11 @ 802.11g)




REPORT No.: SZ16120062W03

2.5.3.3 802.11n-20MHz Test mode

A. Test Verdict:

Spectral power density (dBm/3kHz)				
Channel	Frequency (MHz)	Measured PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
1	2412	-14.47	8	PASS
6	2437	-14.09	8	PASS
11	2462	-14.19	8	PASS
Measurement uncertainty: ± 1.3 dB				


B. Test Plots:




(Channel = 1 @ 802.11n-20MHz)



REPORT No.: SZ16120062W03



(Channel = 6 @ 802.11n-20MHz)



(Channel = 11 @ 802.11n-20MHz)




REPORT No.: SZ16120062W03

2.5.3.4 802.11n-40MHz Test mode

A. Test Verdict:

Spectral power density (dBm/3kHz)				
Channel	Frequency (MHz)	Measured PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
3	2422	-17.52	8	PASS
6	2437	-17.25	8	PASS
9	2452	-16.61	8	PASS
Measurement uncertainty: ± 1.3 dB				


B. Test Plots:




(Channel = 3 @ 802.11n-40MHz)



REPORT No.: SZ16120062W03



(Channel = 6 @ 802.11n-40MHz)



(Channel = 9 @ 802.11n-40MHz)


2.6 Restricted Frequency Bands

2.6.1 Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in 15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

2.6.2 Test Description

A. Test Setup



The EUT is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading.

For the Test Antenna:

Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength.

KDB 558074 Section 12.1 was used in order to prove compliance.

B. Equipments List:

Please reference ANNEX A(1.5).



2.6.3 Test Result

The lowest and highest channels are tested to verify Restricted Frequency Bands.

The measurement results are obtained as below:

$$E \text{ [dB}\mu\text{V/m]} = U_R + A_T + A_{\text{Factor}} \text{ [dB]}; A_T = L_{\text{Cable loss}} \text{ [dB]} - G_{\text{preamp}} \text{ [dB]}$$

A_T : Total correction Factor except Antenna

U_R : Receiver Reading

G_{preamp} : Preamplifier Gain

A_{Factor} : Antenna Factor at 3m

Note: Restricted Frequency Bands were performed when antenna was at vertical and horizontal polarity, and only the worse test condition (vertical) was recorded in this test report.

2.6.3.1 802.11b Test mode

The lowest and highest channels are tested to verify the band edge emissions.

A. Test Verdict:

Channel	Frequency (MHz)	Detector	Receiver Reading U_R (dBuV)	A_T (dB)	A_{Factor} (dB@3m)	Max. Emission E (dB μ V/m)	Limit (dB μ V/m)	Verdict
		PK/ AV						
1	2384.45	PK	46.65	-33.63	32.56	45.58	74	Pass
1	2387.92	AV	32.74	-33.63	32.56	31.67	54	Pass
11	2484.53	PK	48.73	-33.18	32.5	48.05	74	Pass
11	2484.15	AV	33.51	-33.18	32.5	32.83	54	Pass


B. Test Plots:



REPORT No.: SZ16120062W03



(Plot A1: Channel = 1 PEAK @ 802.11b)



(Plot A2: Channel = 1 AVG @ 802.11b)



REPORT No.: SZ16120062W03



(Plot B1: Channel = 11 PEAK @ 802.11b)



(Plot B2: Channel = 11 AVG @ 802.11b)



2.6.3.2 802.11g Test mode

The lowest and highest channels are tested to verify the band edge emissions.

A. Test Verdict:

Channel	Frequency (MHz)	Detector	Receiver Reading U_R (dBuV)	A_T (dB)	A_{Factor} (dB@3m)	Max. Emission E (dBμV/m)	Limit (dBμV/m)	Verdict
		PK/ AV						
1	2388.93	PK	54.88	-33.63	32.56	53.81	74	Pass
1	2389.49	AV	37.76	-33.63	32.56	36.69	54	Pass
11	2483.70	PK	55.17	-33.18	32.5	54.49	74	Pass
11	2483.81	AV	37.67	-33.18	32.5	36.99	54	Pass


B. Test Plots:



(Plot C1: Channel = 1 PEAK @ 802.11g)




REPORT No.: SZ16120062W03



(Plot C2: Channel = 1 AVG @ 802.11g)



(Plot D1: Channel = 11 PEAK @ 802.11g)



(Plot D2: Channel = 11 AVG @ 802.11g)

2.6.3.3 802.11n-20MHz Test mode

The lowest and highest channels are tested to verify the band edge emissions.


A. Test Verdict:

Channel	Frequency (MHz)	Detector	Receiver Reading U_R (dBμV)	A_T (dB)	A_{Factor} (dB@3m)	Max. Emission E (dBμV/m)	Limit (dBμV/m)	Verdict
		PK/ AV						
1	2389.26	PK	54.96	-33.63	32.56	53.89	74	Pass
1	2389.49	AV	36.56	-33.63	32.56	35.49	54	Pass
11	2484.76	PK	56.88	-33.18	32.5	56.2	74	Pass
11	2484.04	AV	37.62	-33.18	32.5	36.94	54	Pass


B. Test Plots:



REPORT No.: SZ16120062W03



(Plot E1: Channel = 1 PEAK @ 802.11n-20)



(Plot E2: Channel = 1 AVG @ 802.11n-20)



REPORT No.: SZ16120062W03



(Plot F1: Channel = 11 PEAK @ 802.11n-20)



(Plot F2: Channel = 11 AVG @ 802.11n-20)



2.6.3.4 802.11n-40MHz Test mode

The lowest and highest channels are tested to verify the band edge emissions.

A. Test Verdict:

Channel	Frequency (MHz)	Detector	Receiver Reading U_R (dBuV)	A_T (dB)	A_{Factor} (dB@3m)	Max. Emission E (dBuV/m)	Limit (dBuV/m)	Verdict
		PK/ AV						
3	2383.22	PK	59.57	-33.63	32.56	58.5	74	Pass
3	2389.26	AV	36.10	-33.63	32.56	35.03	54	Pass
9	2485.10	PK	57.46	-33.18	32.5	56.78	74	Pass
9	2484.34	AV	36.94	-33.18	32.5	36.26	54	Pass


B. Test Plots:




(Plot E1: Channel = 3 PEAK @ 802.11n-40)



REPORT No.: SZ16120062W03




(Plot E2: Channel = 3 AVG @ 802.11n-40)



(Plot F1: Channel = 9 PEAK @ 802.11n-40)



REPORT No.: SZ16120062W03



(Plot F2: Channel = 9 AVG @ 802.11n-40)

2.7 Conducted Emission

2.7.1 Requirement

According to FCC section 15.207, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).


Frequency range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

NOTE:

- The lower limit shall apply at the band edges.
- The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

2.7.2 Test Description

A. Test Setup:



The Table-top EUT was placed upon a non-metallic table 0.8m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.10 2013.



B. Equipments List:

Please reference ANNEX A(1.5).

2.1.1 Test Result


The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.

A. Test setup:

The EUT configuration of the emission tests is EUT + Link.


Note: The test voltage is AC 120V/60Hz.

B. Test Plots:



(Plot A: L Phase)

NO.	Fre. (MHz)	Emission Level (dBμV)		Limit (dBμV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.15	46.71	28.06	66	56	Line	PASS
2	0.64	39.88	28.48	56	46		PASS
3	1.615	39.87	26.18	56	46		PASS
4	12.695	33.37	21.76	60	50		PASS
5	15.08	34.34	21.71	60	50		PASS
6	16.37	38.11	26.38	60	50		PASS



(Plot B: N Phase)

NO.	Fre. (MHz)	Emission Level (dBμV)		Limit (dBμV)		Power- line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.15	59.00	32.12	66	56	Neutral	PASS
2	0.66	44.41	34.35	56	46		PASS
3	1.195	44.21	35.32	56	46		PASS
4	1.965	48.95	40.78	56	46		PASS
5	4.125	41.77	35.00	56	46		PASS
6	16.735	41.22	23.46	60	50		PASS



2.8 Radiated Emission

2.8.1 Requirement

According to FCC section 15.247(d), radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V/m}$)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note:

For Above 1000MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.


For above 1000MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK)

In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), also should comply with the radiated emission limits specified in Section 15.209(a)(above table)


2.8.2 Test Description

A. Test Setup:


- 1) For radiated emissions from 9kHz to 30MHz



- 2) For radiated emissions from 30MHz to 1GHz



3) For radiated emissions above 1GHz



The RF absorbing material used on the reference ground plane and on the turntable have a maximum height (thickness) of 30 cm (12 in) and have a minimum-rated attenuation of 20 dB at all frequencies from 1 GHz to 18 GHz. Test site have a minimum area of the ground plane covered with RF absorbing material as specified in Figure 6 of ANSI C63.4: 2014.

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4dB according to the standards: ANSI C63.10 (2013). For radiated emissions below or equal to 1GHz, The EUT was set-up on insulator 80cm above the Ground Plane, For radiated emissions above 1GHz, The EUT was set-up on insulator 150cm above the Ground Plane. The set-up and test methods were according to ANSI C63.10

For the radiated emission test above 1GHz:

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

The EUT is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of



the site as factors are calculated to correct the reading

For the Test Antenna:

- (a) In the frequency range of 9kHz to 30MHz, magnetic field is measured with Loop Test Antenna. The Test Antenna is positioned with its plane vertical at 1m distance from the EUT. The center of the Loop Test Antenna is 1m above the ground. During the measurement the Loop Test Antenna rotates about its vertical axis for maximum response at each azimuth about the EUT.
- (b) In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 1GHz) and Horn Test Antenna (above 1GHz) are used. Place the test antenna at 3m away from area of the EUT, while keeping the test antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The test antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final test antenna elevation shall be that which maximizes the emissions. The test antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane. The emission levels at both horizontal and vertical polarizations should be tested.

B. Equipments List:

Please reference ANNEX A(1.5).

2.8.3 Test Result

According to ANSI C63.10, because of peak detection will yield amplitudes equal to or greater than amplitudes measured with the quasi-peak (or average) detector, the measurement data from a spectrum analyzer peak detector will represent the worst-case results, if the peak measured value complies with the quasi-peak limit, it is unnecessary to perform an quasi-peak measurement.

The measurement results are obtained as below:

$$E \text{ [dB}\mu\text{V/m]} = U_R + A_T + A_{\text{Factor}} \text{ [dB]}; A_T = L_{\text{Cable loss}} \text{ [dB]} - G_{\text{preamp}} \text{ [dB]}$$

A_T : Total correction Factor except Antenna

U_R : Receiver Reading

G_{preamp} : Preamplifier Gain

A_{Factor} : Antenna Factor at 3m

During the test, the total correction Factor A_T and A_{Factor} were built in test software.

The low frequency, which started from 9KHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

**2.8.3.1 802.11b Test mode****A. Test Plots for the Whole Measurement Frequency Range:**

Plots for Channel = 1



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
54.280	18.16	N.A	N.A	N.A	40.00	N.A	Horizontal	PASS
170.826	26.67	N.A	N.A	N.A	43.50	N.A	Horizontal	PASS
2377.831	44.92	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
3618.367	46.19	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
8987.198	48.72	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
16820.476	50.42	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
32.428	30.69	N.A	N.A	N.A	40.00	N.A	Vertical	PASS
184.180	20.82	N.A	N.A	N.A	43.50	N.A	Vertical	PASS
2368.227	45.74	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
3618.367	46.51	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
12135.988	50.16	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
18380.615	51.00	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)



REPORT No.: SZ16120062W03

Plot for Channel = 6



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
54.280	17.95	N.A	N.A	N.A	40.00	N.A	Horizontal	PASS
180.538	26.51	N.A	N.A	N.A	43.50	N.A	Horizontal	PASS
2512.925	49.55	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
3655.028	46.84	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
12294.854	49.46	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
18453.937	50.76	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
32.428	31.10	N.A	N.A	N.A	40.00	N.A	Vertical	PASS
184.180	20.15	N.A	N.A	N.A	43.50	N.A	Vertical	PASS
2511.004	49.49	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
3655.028	46.30	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
10302.928	48.23	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
18498.745	51.67	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)




REPORT No.: SZ16120062W03

Plot for Channel = 11



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
54.280	18.32	N.A	N.A	N.A	40.00	N.A	Horizontal	PASS
182.966	24.91	N.A	N.A	N.A	43.50	N.A	Horizontal	PASS
2462.985	55.33	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
3691.689	46.19	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
10359.956	48.02	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
18519.113	50.43	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
32.428	30.85	N.A	N.A	N.A	40.00	N.A	Vertical	PASS
283.730	23.14	N.A	N.A	N.A	46.00	N.A	Vertical	PASS
2462.345	55.06	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
3695.763	45.93	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
9427.132	47.75	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
18392.835	51.31	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)

**2.8.3.2 802.11g Test mode****A. Test Plots for the Whole Measurement Frequency Range:**

Plots for Channel = 1



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
49.424	17.43	N.A	N.A	N.A	40.00	N.A	Horizontal	PASS
181.752	23.32	N.A	N.A	N.A	43.50	N.A	Horizontal	PASS
2381.700	55.07	49.01	36.97	74.0	N.A	54.0	Horizontal	PASS
5622.513	47.39	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
12156.356	48.08	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
16563.848	50.92	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
54.280	18.90	N.A	N.A	N.A	40.00	N.A	Vertical	PASS
284.944	24.23	N.A	N.A	N.A	46.00	N.A	Vertical	PASS
2385.514	53.14	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
5382.179	46.37	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
10188.871	48.47	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
16087.252	50.58	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)



REPORT No.: SZ16120062W03

Plot for Channel = 6



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
54.280	17.69	N.A	N.A	N.A	40.00	N.A	Horizontal	PASS
181.752	29.23	N.A	N.A	N.A	43.50	N.A	Horizontal	PASS
2379.112	48.63	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
5655.101	47.86	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
10359.956	47.38	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
18559.847	50.72	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
82.203	18.36	N.A	N.A	N.A	40.00	N.A	Vertical	PASS
283.730	22.65	N.A	N.A	N.A	46.00	N.A	Vertical	PASS
2510.364	49.64	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
5663.248	47.29	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
12127.841	48.71	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
18563.921	51.13	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)



REPORT No.: SZ16120062W03

Plot for Channel = 11



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
54.280	19.98	N.A	N.A	N.A	40.00	N.A	Horizontal	PASS
180.538	19.31	N.A	N.A	N.A	43.50	N.A	Horizontal	PASS
2467.467	53.72	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
5655.101	47.01	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
9027.932	48.02	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
18551.700	50.54	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
33.642	34.76	N.A	N.A	N.A	40.00	N.A	Vertical	PASS
288.586	24.64	N.A	N.A	N.A	46.00	N.A	Vertical	PASS
599.374	25.50	N.A	N.A	N.A	46.00	N.A	Vertical	PASS
2462.985	42.83	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
5716.203	47.54	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
16193.162	51.45	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)

**2.8.3.3 802.11n-20MHz Test mode****A. Test Plots for the Whole Measurement Frequency Range:**

Plots for Channel = 1



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
54.280	16.50	N.A	N.A	N.A	40.00	N.A	Horizontal	PASS
182.966	23.67	N.A	N.A	N.A	43.50	N.A	Horizontal	PASS
2382.313	49.69	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
4331.224	45.24	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
8596.145	47.60	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
16115.767	50.93	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
54.280	20.77	N.A	N.A	N.A	40.00	N.A	Vertical	PASS
284.944	23.78	N.A	N.A	N.A	46.00	N.A	Vertical	PASS
2384.234	51.33	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
5675.468	47.79	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
9333.442	48.26	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
16462.011	51.10	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)



REPORT No.: SZ16120062W03

Plot for Channel = 6



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
54.280	17.06	N.A	N.A	N.A	40.00	N.A	Horizontal	PASS
186.608	24.08	N.A	N.A	N.A	43.50	N.A	Horizontal	PASS
2510.364	48.52	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
5642.881	46.54	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
11753.082	47.76	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
18335.807	50.42	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
59.136	23.86	N.A	N.A	N.A	40.00	N.A	Vertical	PASS
190.250	28.48	N.A	N.A	N.A	43.50	N.A	Vertical	PASS
447.622	29.88	N.A	N.A	N.A	46.00	N.A	Vertical	PASS
2235.054	47.99	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
5606.219	48.10	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
18519.113	51.05	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)



REPORT No.: SZ16120062W03

Plot for Channel = 11



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
37.284	24.68	N.A	N.A	N.A	40.00	N.A	Horizontal	PASS
181.752	23.59	N.A	N.A	N.A	43.50	N.A	Horizontal	PASS
2464.266	51.18	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
4534.897	46.01	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
11744.935	48.32	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
18531.333	51.26	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(Antenna Horizontal, 30MHz to 25GHz)




Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
61.564	27.10	N.A	N.A	N.A	40.00	N.A	Vertical	PASS
189.036	30.41	N.A	N.A	N.A	43.50	N.A	Vertical	PASS
2193.437	46.91	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
2464.266	50.44	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
5541.044	47.57	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
18262.484	51.22	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Antenna Vertical, 30MHz to 25GHz)

**2.8.3.4 802.11n-40MHz Test mode****A. Test Plots for the Whole Measurement Frequency Range:**

Plots for Channel = 3



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
54.280	18.56	N.A	N.A	N.A	40.00	N.A	Horizontal	PASS
282.516	23.44	N.A	N.A	N.A	46.00	N.A	Horizontal	PASS
2378.800	61.08	51.00	37.90	74.0	N.A	54.0	Horizontal	PASS
4648.954	46.22	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
11789.744	48.64	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
18555.774	51.46	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(Plot A.2: Antenna Horizontal, 30MHz to 25GHz)



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
32.428	33.44	N.A	N.A	N.A	40.00	N.A	Vertical	PASS
504.681	25.80	N.A	N.A	N.A	46.00	N.A	Vertical	PASS
2382.500	60.96	51.38	38.10	74.0	N.A	54.0	Vertical	PASS
4710.056	46.91	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
10229.605	47.65	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
18580.215	51.59	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Plot A.3: Antenna Vertical, 30MHz to 25GHz)



REPORT No.: SZ16120062W03

Plots for Channel = 6



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
54.280	18.66	N.A	N.A	N.A	40.00	N.A	Horizontal	PASS
182.966	25.18	N.A	N.A	N.A	43.50	N.A	Horizontal	PASS
2387.435	50.28	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
4188.652	46.08	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
9060.520	48.07	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
18506.892	50.45	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(Plot B.2: Antenna Horizontal, 30MHz to 25GHz)



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
32.428	33.57	N.A	N.A	N.A	40.00	N.A	Vertical	PASS
184.180	19.49	N.A	N.A	N.A	43.50	N.A	Vertical	PASS
2514.206	50.06	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
4547.118	46.08	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
8970.904	48.41	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
18547.627	51.10	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Plot B.3: Antenna Vertical, 30MHz to 25GHz)



Plots for Channel = 9



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
49.424	17.79	N.A	N.A	N.A	40.00	N.A	Horizontal	PASS
182.966	24.45	N.A	N.A	N.A	43.50	N.A	Horizontal	PASS
2503.962	51.91	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
5667.321	47.07	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
12140.062	48.42	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS
18421.349	50.90	N.A	N.A	74.0	N.A	54.0	Horizontal	PASS

(Plot C.2: Antenna Horizontal, 30MHz to 25GHz)



Fre. (MHz)	Pk (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
32.428	33.38	N.A	N.A	N.A	40.00	N.A	Vertical	PASS
283.730	21.29	N.A	N.A	N.A	46.00	N.A	Vertical	PASS
2505.242	52.13	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
4742.644	46.00	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
9023.859	47.27	N.A	N.A	74.0	N.A	54.0	Vertical	PASS
18580.215	50.31	N.A	N.A	74.0	N.A	54.0	Vertical	PASS

(Plot C.3: Antenna Vertical, 30MHz to 25GHz)



ANNEX A GENERAL INFORMATION

1.1 Identification of the Responsible Testing Laboratory

Company Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Department:	Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Responsible Test Lab Manager:	Mr. Su Feng
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525

1.2 Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

1.3 Facilities and Accreditations

Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L3572.

All measurement facilities used to collect the measurement data are located at FL.1, Building A, FeiYang Science Park, Block 67, BaoAn District, Shenzhen, 518101 P. R. China. The test site is constructed in conformance with the requirements of ANSI C63.10 2013 and CISPR Publication 22; the FCC registration number is 695796.

1.4 Maximum measurement uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for test performed on the EUT as specified in CISPR 16-1-2:

Test items	Uncertainty
Peak Output Power	$\pm 2.22\text{dB}$
Power spectral density (PSD)	$\pm 2.22\text{dB}$
Bandwidth	$\pm 5\%$
Conducted Spurious Emission	$\pm 2.77\text{ dB}$
Restricted Frequency Bands	$\pm 5\%$
Radiated Emission	$\pm 2.95\text{dB}$
Conducted Emission	$\pm 2.44\text{dB}$



REPORT No.: SZ16120062W03

This uncertainty represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2

1.5 Test Equipments Utilized

1.5.1 Conducted Test Equipments

Conducted Test Equipment						
No.	Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Cal. Due
1	Spectrum Analyzer	MY45101810	E4407B	Agilent	2016.06.02	2017.06.01
2	Power Splitter	NW521	1506A	Weinschel	2016.06.02	2017.06.01
3	Attenuator 1	(N/A.)	10dB	Resnet	2016.06.02	2017.06.01
4	Attenuator 2	(N/A.)	3dB	Resnet	2016.06.02	2017.06.01
5	EXA Signal Analyzer	MY53470836	N9010A	Agilent	2016.12.07	2017.12.06
6	RF cable (30MHz-26GHz)	CB01	RF01	Morlab	N/A	N/A
7	Coaxial cable	CB02	RF02	Morlab	N/A	N/A
8	SMA connector	CN01	RF03	HUBER-SUHNER	N/A	N/A

1.5.2 Conducted Emission Test Equipments

Conducted Emission Test Equipments						
No.	Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Cal. Due
1	Receiver	US44210471	E7405A	Agilent	2016.06.02	2017.06.01
2	LISN	812744	NSLK 8127	Schwarzbeck	2016.06.02	2017.06.01
3	Service Supplier	100448	CMU200	R&S	2016.06.02	2017.06.01
4	Pulse Limiter (20dB)	9391	VTSD 9561-D	Schwarzbeck	2016.06.02	2017.06.01
5	Coaxial cable(BNC) (30MHz-26GHz)	CB01	EMC01	Morlab	N/A	N/A

1.5.3 Auxiliary Test Equipment

Auxiliary Test Equipment						
No.	Equipment Name	Model No.	Brand Name	Manufacturer	Cal.Date	Cal.Due Date
1	Computer	T430i	Think Pad	Lenovo	N/A	N/A



REPORT No.: SZ16120062W03

1.5.4 Radiated Test Equipments

Radiated Test Equipments						
No.	Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Cal.Due Date
1	System Simulator	GB45360846	8960-E5515C	Agilent	2016.06.02	2017.06.01
2	Receiver	MY54130016	N9038A	Agilent	2016.06.02	2017.06.01
3	Test Antenna - Bi-Log	N/A	VULB9163	Schwarzbeck	2016.07.05	2017.07.04
4	Test Antenna - Horn	9170C-531	BBHA9170	Schwarzbeck	2016.07.05	2017.07.04
5	Test Antenna - Loop	1519-022	FMZB1519	Schwarzbeck	2016.07.05	2017.07.04
6	Test Antenna - Horn	71688	BBHA 9120D	Schwarzbeck	2016.07.05	2017.07.04
7	Coaxial cable (N male) (9KHz-30MHz)	CB04	EMC04	Morlab	N/A	N/A
8	Coaxial cable (N male) (30MHz-26GHz)	CB02	EMC02	Morlab	N/A	N/A
9	Coaxial cable(N male) (30MHz-26GHz)	CB03	EMC03	Morlab	N/A	N/A
10	1-18GHz pre-Amplifier	MA02	TS-PR18	Rohde& Schwarz	2016.07.05	2017.07.04
11	18-26.5GHz pre-Amplifier	MA03	TS-PR18	Rohde& Schwarz	2016.07.05	2017.07.04

1.5.5 Climate Chamber

Climate Chamber						
No.	Equipment Name	Serial No.	Type	Manufacturer	Cal.Date	Cal.Due Date
1	Climate Chamber	2004012	HL4003T	Yinhe	2016.03.25	2017.03.24

1.5.6 Vibration Table

Vibration Table						
No.	Equipment Name	Serial No.	Type	Manufacturer	Cal.Date	Cal.Due Date
1	Vibration Table	N/A	ACT2000-S015L	CMI-COM	2016.03.25	2017.03.24

1.5.7 Anechoic Chamber

Anechoic Chamber						
No.	Equipment Name	Serial No.	Type	Manufacturer	Cal.Date	Cal.Due Date
1	Anechoic Chamber	N/A	9m*6m*6m	Changning	2016.03.25	2017.03.24

***** END OF REPORT *****