

BT FPC Antenna (HA-A110T-R-V4)

1. Explanation of Product Number

S	2	B	4	B	B	1	F	1	B	0	0	0	4	3
(1)				(2)		(3)	(4)		(5)					



Product Description:

- (1) Product Categories:
B:BT Antenna
- (2) Dimensions:
B1: 26.86*8.56*0.15 (mm)
- (3) Material:
F: FPC
- (4) Working Frequencies:
1B: 2.4G-2.5G
- (5) Antenna Series:
01: Serial number

Tolerances (Unless otherwise specified)
X : ± 1 X.X : ± 0.1 X.XX : ± 0.01
Angle : ± Hole Dia. : ±



深圳市迎丰天线技术有限公司

SHEN ZHEN YINGFENG ANTENNA TECHNOLOGY CO., LTD

Scale :	Unit: mm
Drawn By : Andy	Checked By : Simon
Designed By : Simon	Approved By : Simon

THIS SPECIFICATION IS THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED IN ALL CIRCUMSTANCES WITHOUT WRITTEN PERMISSION

TITLE: BT FPC Antenna(HA-A110T-R-V4)	PART NO.	S2B4BB1F1B00043	REV.
			A

2. Features

- *Stable and reliable in performances
- *RoHS compliance
- *Low cost

3. Applications

*BT

4. Description

* YINGFENG FPC antenna series are specially designed for 2.4G-2.5G band application. Based on YINGFENG proprietary designs and processes, this FPC antenna has excellent stability and sensitivity to consistently provide high signal reception efficiency.

5. Antenna Electrical Specifications :

Characteristics	Specifications			Unit
Outline Dimensions	26.86*8.56*0.15			mm
Frequency	2400~2500			MHz
Impedance	50			Ω
Polarization	Linear Polarization			
Return Loss Table	Return Loss			
Freq.Band	2.4G Hz	2.45G Hz	2.5G Hz	
dB	-15.55	-27.39	-20.79	
VSWR Table	VSWR			
Freq.Band	2.4G Hz	2.45G Hz	2.5G Hz	
	1.40	1.08	1.20	
GAIN Table	Total Gain = Xpol + Ppol			
Freq.Band	2400MHz	2450MHz	2480MHz	2500MHz
Peak Gain(dBi)	1.38	1.68	1.52	1.46

Tolerances (Unless otherwise specified)

X : ± 1 X.X : ± 0.1 X.XX : ± 0.01

Angle : $\pm$

Hole Dia. : $\pm$



深圳市迎丰天线技术有限公司

SHEN ZHEN YINGFENG ANTENNA TECHNOLOGY CO., LTD

Scale :

Unit: mm

Drawn By : Andy

Checked By : Simon

Designed By : Simon

Approved By : Simon

THIS SPECIFICATION IS THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED IN ALL CIRCUMSTANCES WITHOUT WRITTEN PERMISSION

TITLE: BT FPC Antenna(HA-A110T-R-V4)


PART
NO.

S2B4BB1F1B00043

REV.
A


6. Dimensions (unit: mm)

blic errand: ±0.2mm



7. Measurement Characteristics:

(1) Return Loss



(2) VSWR

Tolerances (Unless otherwise specified)
X : ± 1 X.X : ± 0.1 X.XX : ± 0.01
Angle : ± Hole Dia. : ±




深圳市迎丰天线技术有限公司
SHEN ZHEN YINGFENG ANTENNA TECHNOLOGYCO.,LTD


Scale : Unit: mm
Drawn By : Andy Checked By : Simon
Designed By :Simon Approved By :Simon

THIS SPECIFICATION IS THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED IN ALL CIRCUMSTANCES WITHOUT WRITTEN PERMISSION

TITLE: BT FPC Antenna(HA-A110T-R-V4)	PART NO.	S2B4BB1F1B00043	REV.
			A



8. Three D Radiation Pattern measurements



Tolerances (Unless otherwise specified)
X : ± 1 X.X : ± 0.1 X.XX : ± 0.01

Angle : ± Hole Dia. : ±



深圳市迎丰天线技术有限公司

SHEN ZHEN YINGFENG ANTENNA TECHNOLOGYCO.,LTD


Scale :	Unit: mm
Drawn By : Andy	Checked By : Simon
Designed By :Simon	Approved By :Simon

THIS SPECIFICATION IS THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED IN ALL CIRCUMSTANCES WITHOUT WRITTEN PERMISSION

TITLE: BT FPC Antenna(HA-A110T-R-V4)	PART NO.	S2B4BB1F1B00043	REV.
			A

9.Radiation Pattern

9-1.3D Gain Pattern (Radiation Pattern at 2450 MHz)



Tolerances (Unless otherwise specified)
X : ± 1 X.X : ± 0.1 X.XX : ± 0.01
Angle : ± Hole Dia. : ±



深圳市迎丰天线技术有限公司

SHEN ZHEN YINGFENG ANTENNA TECHNOLOGYCO.,LTD

Scale :	Unit: mm
Drawn By : Andy	Checked By : Simon
Designed By :Simon	Approved By :Simon


THIS SPECIFICATION IS THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED IN ALL CIRCUMSTANCES WITHOUT WRITTEN PERMISSION

TITLE: BT FPC Antenna(HA-A110T-R-V4)	PART NO.	S2B4BB1F1B00043	REV.
			A

9-3.complete machine Efficiency Table

Frequency(MHz)	2400	2450	2480	2500
Efficiency (%)	35.07	38.25	38.00	36.66
Gain (dBi)	1.38	1.68	1.52	1.46

10-1 产品包装 Product packaging

版本 edition:: V4.0	页码 Page: 1/1
1.产品排版: 32*4=128PCS	2.离型纸隔层摆放保护天线 Barrier paper protection products
	
3.密封袋封装效果 Sealing bag packaging effect	4.纸箱封箱效果(贴出货标签和 ROHS 标签) Carton sealing effect
	

10-2.Revision Control:

Revision	Date	Content	Remark
A	2025-09-19	New Issued.	N/A

10-3.Technology and Materials:

1. Technology (工艺) :油墨 优力哑黑 白色字符 沉金 1U 半切离型膜出货

2.Materials (材料) : 电解铜一对半 背胶 3M9471

Tolerances (Unless otherwise specified)

X : ± 1 X.X : ± 0.1 X.XX : ± 0.01 Angle : $\pm$ Hole Dia. : $\pm$ 

深圳市迎丰天线技术有限公司

SHEN ZHEN YINGFENG ANTENNA TECHNOLOGY CO.,LTD

Scale :

Unit: mm

Drawn By : Andy

Checked By : Simon

Designed By : Simon

Approved By : Simon

THIS SPECIFICATION IS THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED IN ALL CIRCUMSTANCES WITHOUT WRITTEN PERMISSION

TITLE: BT FPC Antenna(HA-A110T-R-V4)

PART
NO.

S2B4BB1F1B00043

REV.

A