FCC RF Exposure

EUT Description: **GAME PAD**
Model No.: **SB914539, SB909375, SB914850, SB913709, SB912757, SB914522, SB912726, SB912733, SB912740, SB914881**
FCC ID: **2AKMJ-SB914539**

1. Limits

According to KDB 447498 D01 General RF Exposure Guidance v06 The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤50 mm are determined by:
[(max power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]·[√f(GHz)]≤3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR,

Where:
Result=P/D*√F
F= the RF channel transmit frequency in GHz
P=Maximum turn-up power in mw
D=Min. test separation distance in mm

2. Test Result of RF Exposure Evaluation

2.4G

	Transmit frequency	Output power （dBm）	Tune Up Power （dBm）	Max Tune Up power dBm/mW	Min test separation distance mm	Result	Limit (mW/cm^2)	SAR Test Exclusion
EDR	2480	0.942	0±1	1/ 1.259	5	0.397	3.0	Pass
Note: PK Output power= conducted power. Conducted power see the test report HK1911152895-E, antenna gain=0dBi								

Per KDB 447498 D01, when the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion. The test exclusion threshold is 0.397 which is<= 3, SAR testing is not required.

Note: Exclusion Thresholds Results=[(*max. power of channel, including tune-up tolerance, mW*)/(*min. test separation distance, mm*)] ·[$\sqrt{f_{(GHz)}}$]

$f_{(GHz)}$ is the RF channel transmit frequency in GHz

Distance=5mm