


RF Exposure Evaluation Report

APPLICANT : NUVIZ Inc.
EQUIPMENT : NUVIZ Controller
BRAND NAME : NUVIZ
MODEL NAME : C-101
FCC ID : 2AKND-C101
STANDARD : 47 CFR Part 2.1093
FCC KDB 447498 D01 v06

We, SPORTON INTERNATIONAL INC., would like to declare that the device has been evaluated in accordance with 47 CFR Part 2.1093, and pass the limit. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.



Reviewed by: Eric Huang / Manager



Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL INC.

No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Taoyuan City, Taiwan (R.O.C.)



Table of Contents

1.	Administration Data	3
2.	General Information	4
2.1	Description of Device Under Test (DUT)	4
3.	Maximum RF output power among production units(Unit: dBm).....	4
4.	RF Exposure Evaluation	5

Revision History

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FA690301-01	Rev. 01	Initial issue of report	Mar. 24, 2017

**1. Administration Data**

Testing Laboratory	
Test Site	SPORTON INTERNATIONAL INC.
Test Site Location	No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978

Applicant	
Company Name	NUVIZ Inc.
Address	1620 5th Ave., Suite 550, San Diego, CA 92101

Manufacturer	
Company Name	NUVIZ Inc.
Address	1620 5th Ave., Suite 550, San Diego, CA 92101

2. General Information

2.1 Description of Device Under Test (DUT)

Product Feature & Specification	
DUT Type	NUVIZ Controller
Brand Name	NUVIZ
Model Name	C-101
FCC ID	2AKND-C101
Wireless Technology and Frequency Range	Bluetooth: 2402 MHz ~ 2480 MHz
Mode	Bluetooth LE
Antenna Gain	3.38dBi
Antenna Type	Metal Ring Antenna
HW Version	2000
SW Version	Street: 17090
DUT Stage	Production Unit

Remark: The above DUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

3. Maximum RF output power among production units(Unit: dBm)

Mode / Band	Bluetooth
	LE
	(GFSK)
2.4GHz Bluetooth	0

**4. RF Exposure Evaluation**

Bluetooth Max Power (dBm)	mW	Separation Distance (mm)	Frequency (GHz)	Exclusion Thresholds
0	1.00	5	2.48	0.31

Note:

1. Per KDB 447498 D01v06 the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

Conclusion: Per KDB 447498 D01v06, when the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine hand SAR test exclusion. The test exclusion threshold is 0.31 which is ≤ 7.5 , hand SAR testing is not required.