FCC Report (WIFI)

Applicant:	CanDo International, Inc.
Address of Applicant:	138 E Lemon Ave, Monrovia, California 91016, United States
Manufacturer	SHENZHEN FCAR TECHNOLOGY CO.,LTD
Address of Manufacturer:	8th floor, Chuangyi Building, No. 3025 Nanhai Ave., Nanshan, Shenzhen, Guangdong, China 518060
Factory:	SHENZHEN FCAR TECHNOLOGY CO.,LTD
Address of Factory:	West 1st Floor, Building B, Hengchao Industrial Park, Tangtou North Ave., Bao'an, Shenzhen, Guangdong, China 518108

Equipment Under Test (EUT)

Product Name:	AUTO DIAGNOSTIC SYSTEM
Model No.:	C-Pro
Trade Mark:	CanDo
FCC ID:	2AKNY-IDSCPRO
Applicable standards:	FCC CFR Title 47 Part 15 Subpart C Section 15.247
Date of sample receipt:	November 19, 2018
Date of Test:	November 20, 2018-December 05, 2018
Date of report issued:	December 06, 2018
Test Result :	PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

Robinson Lo
Laboratory Manager

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

2 Version

Version No.	Date	Description
00	*December 06, 2018*	*Original*

Prepared By:	Bill. Yuan	***Date:***	*December 06, 2018*
	Project Engineer		
Check By:	Robinson Lo	***Date:***	*December 06, 2018*
	Reviewer		

3 Contents

Page

1 COVER PAGE 1

2 VERSION 2

3 CONTENTS 3

4 TEST SUMMARY 4

5 GENERAL INFORMATION 5

5.1 GENERAL DESCRIPTION OF EUT 5
5.2 TEST MODE 7
5.3 DESCRIPTION OF SUPPORT UNITS 7
5.4 TEST FACILITY 7
5.5 TEST LOCATION 7

6 TEST INSTRUMENTS LIST 8

7 TEST RESULTS AND MEASUREMENT DATA 10

7.1 ANTENNA REQUIREMENT 10
7.2 CONDUCTED EMISSIONS 11
7.3 CONDUCTED PEAK OUTPUT POWER 14
7.4 CHANNEL BANDWIDTH 15
7.5 POWER SPECTRAL DENSITY 19
7.6 BAND EDGES 23
7.6.1 Conducted Emission Method 23
7.6.2 Radiated Emission Method 25
7.7 SPURIOUS EMISSION 29
7.7.1 Conducted Emission Method 29
7.7.2 Radiated Emission Method 33

8 TEST SETUP PHOTO 47

9 EUT CONSTRUCTIONAL DETAILS 49

4 Test Summary

Test Item	Section in CFR 47	Result
Antenna requirement	15.203/15.247 (c)	Pass
AC Power Line Conducted Emission	15.207	Pass
Conducted Peak Output Power	15.247 (b)(3)	Pass
Channel Bandwidth	15.247 (a)(2)	Pass
Power Spectral Density	15.247 (e)	Pass
Band Edge	15.247(d)	Pass
Spurious Emission	15.205/15.209	Pass

Remark: Test according to ANSI C63.10:2013.

Pass: The EUT complies with the essential requirements in the standard.

Measurement Uncertainty

Test Item	Frequency Range	Measurement Uncertainty	Notes
Radiated Emission	9kHz ~ 30MHz	± 4.54dB	(1)
Radiated Emission	30MHz ~ 1000MHz	± 5.34dB	(1)
Radiated Emission	1GHz ~ 26.5GHz	± 5.34dB	(1)
AC Power Line Conducted Emission	0.15MHz ~ 30MHz	± 3.44dB	(1)
Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.			

5 General Information

5.1 General Description of EUT

Product Name:	AUTO DIAGNOSTIC SYSTEM
Model No.:	C-Pro
Test sample(s) ID:	GTS201811000124-1
Sample(s) Status:	Engineer sample
Serial No.:	CD01-1808-318S-0001
Hardware version:	V1.1
Software version:	V1.1
Operation Frequency:	2412MHz~2462MHz(802.11b/802.11g/802.11n(HT20))
Channel numbers:	802.11b/802.11g /802.11n(HT20): 11
Channel separation:	5MHz
Modulation technology:	802.11b: Direct Sequence Spread Spectrum (DSSS) 802.11g/802.11n(H20): Orthogonal Frequency Division Multiplexing (OFDM)
Antenna Type:	Integral Antenna
Antenna gain:	2.0dBi(declare by applicant)
Power supply:	Adapter: Model:GME36A-120300FDS Input:AC 100-240V, 50/60Hz, 1.2A Output:DC 12V, 3A Or Battery:DC 3.7V, 5000mAh, 18.5Wh

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Test channel	**Frequency (MHz)**
	802.11b/802.11g/802.11n(HT20)
Lowest channel	2412MHz
Middle channel	2437MHz
Highest channel	2462MHz

5.2 Test mode

Transmitting mode	Keep the EUT in continuously transmitting mode

Remark: During the test, the dutycycle >98%, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.

We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:

Pre-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.

Mode	802.11b	802.11g	802.11n(HT20)
Data rate	1Mbps	6Mbps	6.5Mbps

5.3 Description of Support Units

None.

5.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

● **FCC —Registration No.: 381383**

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. Registration 381383, January 08, 2018.

● **Industry Canada (IC) —Registration No.: 9079A-2**

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 9079A-2, August 15, 2016.

5.5 Test Location

All tests were performed at:

Global United Technology Services Co., Ltd.
Address: No. 301-309, 3/F., Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102
Tel: 0755-27798480
Fax: 0755-27798960

6 Test Instruments list

Radiated Emission:						
Item	**Test Equipment**	**Manufacturer**	**Model No.**	**Inventory No.**	**Cal.Date (mm-dd-yy)**	**Cal.Due date (mm-dd-yy)**
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	July. 03 2015	July. 02 2020
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	June. 27 2018	June. 26 2019
4	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	GTS214	June. 27 2018	June. 26 2019
5	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120 D	GTS208	June. 27 2018	June. 26 2019
6	Horn Antenna	ETS-LINDGREN	3160	GTS217	June. 27 2018	June. 26 2019
7	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
8	Coaxial Cable	GTS	N/A	GTS213	June. 27 2018	June. 26 2019
9	Coaxial Cable	GTS	N/A	GTS211	June. 27 2018	June. 26 2019
10	Coaxial cable	GTS	N/A	GTS210	June. 27 2018	June. 26 2019
11	Coaxial Cable	GTS	N/A	GTS212	June. 27 2018	June. 26 2019
12	Amplifier(100kHz-3GHz)	HP	8347A	GTS204	June. 27 2018	June. 26 2019
13	Amplifier(2GHz-20GHz)	HP	84722A	GTS206	June. 27 2018	June. 26 2019
14	Amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	June. 27 2018	June. 26 2019
15	Band filter	Amindeon	82346	GTS219	June. 27 2018	June. 26 2019
16	Power Meter	Anritsu	ML2495A	GTS540	June. 27 2018	June. 26 2019
17	Power Sensor	Anritsu	MA2411B	GTS541	June. 27 2018	June. 26 2019
18	Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	GTS575	June. 27 2018	June. 26 2019
19	Splitter	Agilent	11636B	GTS237	June. 27 2018	June. 26 2019
20	Loop Antenna	ZHINAN	ZN30900A	GTS534	June. 27 2018	June. 26 2019

Conducted Emission						
Item	**Test Equipment**	**Manufacturer**	**Model No.**	**Inventory No.**	**Cal.Date (mm-dd-yy)**	**Cal.Due date (mm-dd-yy)**
1	Shielding Room	ZhongYu Electron	7.3(L)x3.1(W)x2.9(H)	GTS252	May.16 2014	May.15 2019
2	EMI Test Receiver	R&S	ESCI 7	GTS552	June. 27 2018	June. 26 2019
3	Coaxial Switch	ANRITSU CORP	MP59B	GTS225	June. 27 2018	June. 26 2019
4	Artificial Mains Network	SCHWARZBECK MESS	NSLK8127	GTS226	June. 27 2018	June. 26 2019
5	Coaxial Cable	GTS	N/A	GTS227	N/A	N/A
6	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
7	Thermo meter	KTJ	TA328	GTS233	June. 27 2018	June. 26 2019
8	Absorbing clamp	Elektronik-Feinmechanik	MDS21	GTS229	June. 27 2018	June. 26 2019

Conducted:						
Item	**Test Equipment**	**Manufacturer**	**Model No.**	**Serial No.**	**Cal.Date (mm-dd-yy)**	**Cal.Due date (mm-dd-yy)**
1	MXA Signal Analyzer	Agilent	N9020A	GTS566	June. 27 2018	June. 26 2019
2	EMI Test Receiver	R&S	ESCI 7	GTS552	June. 27 2018	June. 26 2019
3	Spectrum Analyzer	Agilent	E4440A	GTS533	June. 27 2018	June. 26 2019
4	MXG vector Signal Generator	Agilent	N5182A	GTS567	June. 27 2018	June. 26 2019
5	ESG Analog Signal Generator	Agilent	E4428C	GTS568	June. 27 2018	June. 26 2019
6	USB RF Power Sensor	DARE	RPR3006W	GTS569	June. 27 2018	June. 26 2019
7	RF Switch Box	Shongyi	RFSW3003328	GTS571	June. 27 2018	June. 26 2019
8	EMI Test Receiver	R&S	ESCI 7	GTS552	June. 27 2018	June. 26 2019
9	Programmable Constant Temp & Humi Test Chamber	WEWON	WHTH-150L-40-880	GTS572	June. 27 2018	June. 26 2019

General used equipment:						
Item	**Test Equipment**	**Manufacturer**	**Model No.**	**Inventory No.**	**Cal.Date (mm-dd-yy)**	**Cal.Due date (mm-dd-yy)**
1	Humidity/ Temperature Indicator	KTJ	TA328	GTS243	June. 27 2018	June. 26 2019
2	Barometer	ChangChun	DYM3	GTS255	June. 27 2018	June. 26 2019

7 Test results and Measurement Data

7.1 Antenna requirement

Standard requirement:	FCC Part15 C Section 15.203 /247(c)

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(c) (1)(i) requirement:

(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

EUT Antenna:

The antenna is integral antenna, the best case gain of the antennas are 2.0dBi.



7.2 Conducted Emissions

Test Requirement:	FCC Part15 C Section 15.207
Test Method:	ANSI C63.10:2013
Test Frequency Range:	150KHz to 30MHz
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto
Limit:	

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

Test setup:



Remark:
E.U.T: Equipment Under Test
LISN: Line Impedence Stabilization Network
Test table height=0.8m

Test procedure:

1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment.
2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs).
3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2013 on conducted measurement.

Test Instruments:	Refer to section 6.0 for details.
Test mode:	Refer to section 5.2 for details.
Test voltage:	AC 120V, 60Hz
Test results:	Pass

Remark: Both high and low voltages have been tested to show only the worst low voltage test data.

Measurement data

Mode:	**Transmitting mode**	**Test by:**	**Bill**
Temp./Hum.(%H):	**26℃/56%RH**	**Probe:**	**Line**



Freq MHz	Reading level dBuV	LISN/ISN factor dB/m	Cable loss dB	Level dBuV	Limit level dBuV	Over limit dB	Remark
0.15	48.88	0.40	0.07	49.35	66.00	-16.65	QP
0.15	32.66	0.40	0.07	33.13	56.00	-22.87	Average
0.32	35.95	0.39	0.10	36.44	59.80	-23.36	QP
0.32	29.27	0.39	0.10	29.76	49.80	-20.04	Average
0.47	37.21	0.33	0.11	37.65	56.58	-18.93	QP
0.47	28.20	0.33	0.11	28.64	46.58	-17.94	Average
0.63	32.33	0.28	0.12	32.73	56.00	-23.27	QP
0.63	24.80	0.28	0.12	25.20	46.00	-20.80	Average
5.53	30.62	0.20	0.17	30.99	60.00	-29.01	QP
5.53	21.77	0.20	0.17	22.14	50.00	-27.86	Average
13.13	36.32	0.20	0.21	36.73	60.00	-23.27	QP
13.13	28.41	0.20	0.21	28.82	50.00	-21.18	Average

Mode:	**Transmitting mode**	**Test by:**	**Bill**
Temp./Hum.(%H):	**26℃/56%RH**	**Probe:**	**Neutral**



Freq MHz	Reading level dBuV	LISN/ISN factor dB/m	Cable loss dB	Level dBuV	Limit level dBuV	Over limit dB	Remark
0.15	49.26	0.40	0.07	49.73	66.00	-16.27	QP
0.15	32.14	0.40	0.07	32.61	56.00	-23.39	Average
0.32	33.69	0.39	0.10	34.18	59.80	-25.62	QP
0.32	27.75	0.39	0.10	28.24	49.80	-21.56	Average
0.63	31.86	0.28	0.12	32.26	56.00	-23.74	QP
0.63	24.21	0.28	0.12	24.61	46.00	-21.39	Average
1.48	26.49	0.20	0.16	26.85	56.00	-29.15	QP
1.48	15.97	0.20	0.16	16.33	46.00	-29.67	Average
5.59	32.21	0.20	0.17	32.58	60.00	-27.42	QP
5.59	20.82	0.20	0.17	21.19	50.00	-28.81	Average
12.92	34.82	0.20	0.21	35.23	60.00	-24.77	QP
12.92	27.09	0.20	0.21	27.50	50.00	-22.50	Average

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level =Receiver Read level + LISN Factor + Cable Loss
4. *If the average limit is met when using a quasi-peak detector receiver, the EUT shall be deemed to meet both limits and measurement with the average detector receiver is unnecessary.*

7.3 Conducted Peak Output Power

Test Requirement:	FCC Part15 C Section 15.247 (b)(3)
Test Method:	KDB558074 D01 DTS Meas Guidance V05
Limit:	30dBm
Test setup:	
Test Instruments:	Refer to section 6.0 for details.
Test mode:	Refer to section 5.2 for details.
Test results:	Pass

Measurement Data

Test CH	Peak Output Power (dBm)			Limit(dBm)	Result
	802.11b	802.11g	802.11n(HT20)		
Lowest	16.64	15.98	15.00	30.00	Pass
Middle	16.88	15.38	15.66		
Highest	16.83	16.48	15.64		

Test CH	Average Output Power (dBm)			Limit(dBm)	Result
	802.11b	802.11g	802.11n(HT20)		
Lowest	14.31	13.73	13.07	30.00	Pass
Middle	14.38	13.76	13.21		
Highest	14.35	13.95	13.18		

7.4 Channel Bandwidth

Test Requirement:	FCC Part15 C Section 15.247 (a)(2)
Test Method:	KDB558074 D01 DTS Meas Guidance V05
Limit:	>500KHz
Test setup:	
Test Instruments:	Refer to section 6.0 for details.
Test mode:	Refer to section 5.2 for details.
Test results:	Pass

Measurement Data

Test CH	Channel Bandwidth (MHz)			Limit(KHz)	Result
	802.11b	802.11g	802.11n(HT20)		
Lowest	9.086	15.172	15.132	>500	Pass
Middle	8.607	15.141	15.108		
Highest	8.108	15.161	15.162		

Test plot as follows:

Test mode:	802.11b



Lowest channel



Middle channel



Highest channel

Test mode:	802.11g



Lowest channel



Middle channel



Highest channel

Test mode:	802.11n(HT20)



Lowest channel



Middle channel



Highest channel

7.5 Power Spectral Density

Test Requirement:	FCC Part15 C Section 15.247 (e)
Test Method:	KDB558074 D01 DTS Meas Guidance V05
Limit:	8dBm/3kHz
Test setup:	
Test Instruments:	Refer to section 6.0 for details.
Test mode:	Refer to section 5.2 for details.
Test results:	Pass

Measurement Data

Test CH	Power Spectral Density (dBm)			Limit (dBm/3kHz)	Result
	802.11b	802.11g	802.11n(HT20)		
Lowest	-8.58	-12.42	-13.32	8.00	Pass
Middle	-8.58	-12.48	-13.10		
Highest	-8.37	-11.11	-12.76		

Test plot as follows:

Test mode:	802.11b



Lowest channel



Middle channel



Highest channel

Test mode:	802.11g



Lowest channel



Middle channel



Highest channel

Test mode:	802.11n(HT20)



Lowest channel



Middle channel



Highest channel

7.6 Band edges

7.6.1 Conducted Emission Method

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	KDB558074 D01 DTS Meas Guidance V05
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	
Test Instruments:	Refer to section 6.0 for details.
Test mode:	Refer to section 5.2 for details.
Test results:	Pass

Test plot as follows:

Test mode:	802.11b



Lowest channel



Highest channel

Test mode:	802.11g



Lowest channel



Highest channel

Test mode:	802.11n(HT20)



Lowest channel



Highest channel

7.6.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209 and 15.205
Test Method:	ANSI C63.10:2013
Test Frequency Range:	All of the restrict bands were tested, only the worst band's (2310MHz to 2500MHz) data was showed.
Test site:	Measurement Distance: 3m
Receiver setup:	

Frequency	Detector	RBW	VBW	Value
Above 1GHz	Peak	1MHz	3MHz	Peak
	Average	1MHz	3MHz	Average

Limit:

Frequency	Limit (dBuV/m @3m)	Value
Above 1GHz	54.00	Average
	74.00	Peak

Test setup:



Test Procedure:

1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
7. The radiation measurements are performed in X, Y, Z axis positioning. And found the Y axis positioning which it is worse case, only the test worst case mode is recorded in the report.

Test Instruments:	Refer to section 6.0 for details.
Test mode:	Refer to section 5.2 for details.

Test results:	Pass

Measurement data:

Test mode:	802.11b	Test channel:	Lowest

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	50.37	27.59	5.38	34.01	49.33	74.00	-24.67	Horizontal
2400.00	58.95	27.58	5.39	34.01	57.91	74.00	-16.09	Horizontal
2390.00	51.96	27.59	5.38	34.01	50.92	74.00	-23.08	Vertical
2400.00	60.40	27.58	5.39	34.01	59.36	74.00	-14.64	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	37.50	27.59	5.38	34.01	36.46	54.00	-17.54	Horizontal
2400.00	45.65	27.58	5.39	34.01	44.61	54.00	-9.39	Horizontal
2390.00	39.21	27.59	5.38	34.01	38.17	54.00	-15.83	Vertical
2400.00	46.68	27.58	5.39	34.01	45.64	54.00	-8.36	Vertical

Test mode:	802.11b	Test channel:	Highest

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	50.47	27.53	5.47	33.92	49.55	74.00	-24.45	Horizontal
2500.00	46.71	27.55	5.49	29.93	49.82	74.00	-24.18	Horizontal
2483.50	52.47	27.53	5.47	33.92	51.55	74.00	-22.45	Vertical
2500.00	48.98	27.55	5.49	29.93	52.09	74.00	-21.91	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	37.67	27.53	5.47	33.92	36.75	54.00	-17.25	Horizontal
2500.00	34.01	27.55	5.49	29.93	37.12	54.00	-16.88	Horizontal
2483.50	39.50	27.53	5.47	33.92	38.58	54.00	-15.42	Vertical
2500.00	35.84	27.55	5.49	29.93	38.95	54.00	-15.05	Vertical

Remarks:

1. *Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
2. *The emission levels of other frequencies are very lower than the limit and not show in test report.*
3. *Remark: The pre-test were performed on lowest, middle and highest frequencies, only the worst case's (lowest and highest frequencies) data was showed.*

Test mode:	802.11g	Test channel:	Lowest

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	50.03	27.59	5.38	34.01	48.99	74.00	-25.01	Horizontal
2400.00	58.50	27.58	5.39	34.01	57.46	74.00	-16.54	Horizontal
2390.00	51.60	27.59	5.38	34.01	50.56	74.00	-23.44	Vertical
2400.00	59.86	27.58	5.39	34.01	58.82	74.00	-15.18	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	37.26	27.59	5.38	34.01	36.22	54.00	-17.78	Horizontal
2400.00	45.37	27.58	5.39	34.01	44.33	54.00	-9.67	Horizontal
2390.00	38.95	27.59	5.38	34.01	37.91	54.00	-16.09	Vertical
2400.00	46.37	27.58	5.39	34.01	45.33	54.00	-8.67	Vertical

Test mode:	802.11g	Test channel:	Highest

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	49.99	27.53	5.47	33.92	49.07	74.00	-24.93	Horizontal
2500.00	46.33	27.55	5.49	29.93	49.44	74.00	-24.56	Horizontal
2483.50	51.91	27.53	5.47	33.92	50.99	74.00	-23.01	Vertical
2500.00	48.54	27.55	5.49	29.93	51.65	74.00	-22.35	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	37.37	27.53	5.47	33.92	36.45	54.00	-17.55	Horizontal
2500.00	33.79	27.55	5.49	29.93	36.90	54.00	-17.10	Horizontal
2483.50	39.18	27.53	5.47	33.92	38.26	54.00	-15.74	Vertical
2500.00	35.60	27.55	5.49	29.93	38.71	54.00	-15.29	Vertical

Remarks:

1. *Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
2. *The emission levels of other frequencies are very lower than the limit and not show in test report.*
3. *Remark: The pre-test were performed on lowest, middle and highest frequencies, only the worst case's (lowest and highest frequencies) data was showed.*

Test mode:	802.11n(HT20)	Test channel:	Lowest

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	50.08	27.59	5.38	34.01	49.04	74.00	-24.96	Horizontal
2400.00	58.56	27.58	5.39	34.01	57.52	74.00	-16.48	Horizontal
2390.00	51.65	27.59	5.38	34.01	50.61	74.00	-23.39	Vertical
2400.00	59.94	27.58	5.39	34.01	58.90	74.00	-15.10	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	37.29	27.59	5.38	34.01	36.25	54.00	-17.75	Horizontal
2400.00	45.42	27.58	5.39	34.01	44.38	54.00	-9.62	Horizontal
2390.00	38.99	27.59	5.38	34.01	37.95	54.00	-16.05	Vertical
2400.00	46.42	27.58	5.39	34.01	45.38	54.00	-8.62	Vertical

Test mode:	802.11n(HT20)	Test channel:	Highest

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	50.06	27.53	5.47	33.92	49.14	74.00	-24.86	Horizontal
2500.00	46.39	27.55	5.49	29.93	49.50	74.00	-24.50	Horizontal
2483.50	52.00	27.53	5.47	33.92	51.08	74.00	-22.92	Vertical
2500.00	48.60	27.55	5.49	29.93	51.71	74.00	-22.29	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	37.42	27.53	5.47	33.92	36.50	54.00	-17.50	Horizontal
2500.00	33.82	27.55	5.49	29.93	36.93	54.00	-17.07	Horizontal
2483.50	39.22	27.53	5.47	33.92	38.30	54.00	-15.70	Vertical
2500.00	35.64	27.55	5.49	29.93	38.75	54.00	-15.25	Vertical

Remarks:

1. *Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
2. *The emission levels of other frequencies are very lower than the limit and not show in test report.*
3. *Remark: The pre-test were performed on lowest, middle and highest frequencies, only the worst case's (lowest and highest frequencies) data was showed.*

7.7 Spurious Emission

7.7.1 Conducted Emission Method

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	KDB558074 D01 DTS Meas Guidance V05
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	
Test Instruments:	Refer to section 6.0 for details.
Test mode:	Refer to section 5.2 for details.
Test results:	Pass

Test plot as follows:

Test mode:	802.11b

Lowest channel



30MHz~25GHz

Middle channel



30MHz~25GHz

Highest channel



30MHz~25GHz

Test mode:	802.11g

Lowest channel



30MHz~25GHz

Middle channel



30MHz~25GHz

Highest channel



30MHz~25GHz

Test mode:	802.11n(HT20)

Lowest channel



30MHz~25GHz

Middle channel



30MHz~25GHz

Highest channel



30MHz~25GHz

7.7.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209
Test Method:	ANSI C63.10:2013
Test Frequency Range:	9kHz to 25GHz
Test site:	Measurement Distance: 3m

Receiver setup:

Frequency	Detector	RBW	VBW	Value
9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak
Above 1GHz	Peak	1MHz	3MHz	Peak
	Peak	1MHz	10Hz	Average

Limit:

Frequency	Limit (uV/m)	Value	Measurement Distance
0.009MHz-0.490MHz	2400/F(KHz)	QP	300m
0.490MHz-1.705MHz	24000/F(KHz)	QP	300m
1.705MHz-30MHz	30	QP	30m
30MHz-88MHz	100	QP	3m
88MHz-216MHz	150	QP	
216MHz-960MHz	200	QP	
960MHz-1GHz	500	QP	
Above 1GHz	500	Average	
	5000	Peak	

Test setup:

For radiated emissions from 9kHz to 30MHz



For radiated emissions from 30MHz to1GHz



For radiated emissions above 1GHz



Test Procedure:

1. The EUT was placed on the top of a rotating table (0.8m for below 1G and 1.5m for above 1G) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. If the emission level of the EUT in peak mode was 10dB lower than the

	limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
Test Instruments:	Refer to section 6.0 for details.
Test mode:	Refer to section 5.2 for details.
Test voltage:	AC 120V 60Hz
Test results:	Pass

Remark:

Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis which it is worse case.

Measurement data:

- **9kHz~30MHz**

The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

■ **Below 1GHz**

Mode:	**Transmitting mode**	**Test by:**	**Bill**
Temp./Hum.(%H):	**26℃/56%RH**	**Polarziation:**	**Horizontal**



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
88.964	44.84	10.32	1.10	36.63	19.63	43.50	-23.87	QP
181.283	56.76	9.07	1.75	37.24	30.34	43.50	-13.16	QP
330.195	48.53	14.18	2.52	37.45	27.78	46.00	-18.22	QP
396.242	55.28	15.25	2.83	37.52	35.84	46.00	-10.16	QP
663.473	43.67	19.56	3.96	37.60	29.59	46.00	-16.41	QP
796.183	43.30	21.34	4.45	37.62	31.47	46.00	-14.53	QP

Mode:	**Transmitting mode**	**Test by:**	**Bill**
Temp./Hum.(%H):	**26℃/56%RH**	**Polarziation:**	**Vertical**



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
43.353	50.15	12.24	0.70	35.85	27.24	40.00	-12.76	QP
84.110	52.52	8.80	1.06	36.59	25.79	40.00	-14.21	QP
181.283	56.95	9.07	1.75	37.24	30.53	43.50	-12.97	QP
331.355	48.15	14.20	2.53	37.45	27.43	46.00	-18.57	QP
396.242	55.86	15.25	2.83	37.52	36.42	46.00	-9.58	QP
691.987	45.34	19.59	4.06	37.62	31.37	46.00	-14.63	QP

■ **Above 1GHz**

Test mode:	802.11b	Test channel:	Lowest

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	40.01	31.79	8.62	32.10	48.32	74.00	-25.68	Vertical
7236.00	34.04	36.19	11.68	31.97	49.94	74.00	-24.06	Vertical
9648.00	32.59	38.07	14.16	31.56	53.26	74.00	-20.74	Vertical
12060.00	*					74.00		Vertical
14472.00	*					74.00		Vertical
16884.00	*					74.00		Vertical
4824.00	38.72	31.79	8.62	32.10	47.03	74.00	-26.97	Horizontal
7236.00	33.81	36.19	11.68	31.97	49.71	74.00	-24.29	Horizontal
9648.00	32.17	38.07	14.16	31.56	52.84	74.00	-21.16	Horizontal
12060.00	*					74.00		Horizontal
14472.00	*					74.00		Horizontal
16884.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	29.12	31.79	8.62	32.10	37.43	54.00	-16.57	Vertical
7236.00	22.91	36.19	11.68	31.97	38.81	54.00	-15.19	Vertical
9648.00	22.94	38.07	14.16	31.56	43.61	54.00	-10.39	Vertical
12060.00	*					54.00		Vertical
14472.00	*					54.00		Vertical
16884.00	*					54.00		Vertical
4824.00	28.28	31.79	8.62	32.10	36.59	54.00	-17.41	Horizontal
7236.00	22.40	36.19	11.68	31.97	38.30	54.00	-15.70	Horizontal
9648.00	21.93	38.07	14.16	31.56	42.60	54.00	-11.40	Horizontal
12060.00	*					54.00		Horizontal
14472.00	*					54.00		Horizontal
16884.00	*					54.00		Horizontal

Remarks:

1. *Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
2. *"*", means this data is the too weak instrument of signal is unable to test.*

Test mode:	802.11b	Test channel:	Middle

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	39.12	31.85	8.66	32.12	47.51	74.00	-26.49	Vertical
7311.00	34.14	36.37	11.71	31.91	50.31	74.00	-23.69	Vertical
9748.00	33.63	38.27	14.25	31.56	54.59	74.00	-19.41	Vertical
12185.00	*					74.00		Vertical
14622.00	*					74.00		Vertical
17059.00	*					74.00		Vertical
4874.00	39.63	31.85	8.66	32.12	48.02	74.00	-25.98	Horizontal
7311.00	32.80	36.37	11.71	31.91	48.97	74.00	-25.03	Horizontal
9748.00	33.52	38.27	14.25	31.56	54.48	74.00	-19.52	Horizontal
12185.00	*					74.00		Horizontal
14622.00	*					74.00		Horizontal
17059.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	29.99	31.85	8.66	32.12	38.38	54.00	-15.62	Vertical
7311.00	22.46	36.37	11.71	31.91	38.63	54.00	-15.37	Vertical
9748.00	22.88	38.27	14.25	31.56	43.84	54.00	-10.16	Vertical
12185.00	*					54.00		Vertical
14622.00	*					54.00		Vertical
17059.00	*					54.00		Vertical
4874.00	29.76	31.85	8.66	32.12	38.15	54.00	-15.85	Horizontal
7311.00	21.89	36.37	11.71	31.91	38.06	54.00	-15.94	Horizontal
9748.00	23.24	38.27	14.25	31.56	44.20	54.00	-9.80	Horizontal
12185.00	*					54.00		Horizontal
14622.00	*					54.00		Horizontal
17059.00	*					54.00		Horizontal

Remarks:

1. *Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
2. *"*", means this data is the too weak instrument of signal is unable to test.*

Test mode:	802.11b	Test channel:	Highest

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	44.47	31.90	8.70	32.15	52.92	74.00	-21.08	Vertical
7386.00	34.71	36.49	11.76	31.83	51.13	74.00	-22.87	Vertical
9848.00	36.85	38.62	14.31	31.77	58.01	74.00	-15.99	Vertical
12310.00	*					74.00		Vertical
14772.00	*					74.00		Vertical
17234.00	*					74.00		Vertical
4924.00	43.84	31.90	8.70	32.15	52.29	74.00	-21.71	Horizontal
7386.00	33.64	36.49	11.76	31.83	50.06	74.00	-23.94	Horizontal
9848.00	33.03	38.62	14.31	31.77	54.19	74.00	-19.81	Horizontal
12310.00	*					74.00		Horizontal
14772.00	*					74.00		Horizontal
17234.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	35.42	31.90	8.70	32.15	43.87	54.00	-10.13	Vertical
7386.00	24.63	36.49	11.76	31.83	41.05	54.00	-12.95	Vertical
9848.00	25.35	38.62	14.31	31.77	46.51	54.00	-7.49	Vertical
12310.00	*					54.00		Vertical
14772.00	*					54.00		Vertical
17234.00	*					54.00		Vertical
4924.00	34.23	31.90	8.70	32.15	42.68	54.00	-11.32	Horizontal
7386.00	23.04	36.49	11.76	31.83	39.46	54.00	-14.54	Horizontal
9848.00	22.30	38.62	14.31	31.77	43.46	54.00	-10.54	Horizontal
12310.00	*					54.00		Horizontal
14772.00	*					54.00		Horizontal
17234.00	*					54.00		Horizontal

Remarks:

1. *Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
2. *"*", means this data is the too weak instrument of signal is unable to test.*

Test mode:	802.11g	Test channel:	lowest

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	39.62	31.79	8.62	32.10	47.93	74.00	-26.07	Vertical
7236.00	33.79	36.19	11.68	31.97	49.69	74.00	-24.31	Vertical
9648.00	32.41	38.07	14.16	31.56	53.08	74.00	-20.92	Vertical
12060.00	*					74.00		Vertical
14472.00	*					74.00		Vertical
16884.00	*					74.00		Vertical
4824.00	38.39	31.79	8.62	32.10	46.70	74.00	-27.30	Horizontal
7236.00	33.59	36.19	11.68	31.97	49.49	74.00	-24.51	Horizontal
9648.00	32.01	38.07	14.16	31.56	52.68	74.00	-21.32	Horizontal
12060.00	*					74.00		Horizontal
14472.00	*					74.00		Horizontal
16884.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	28.75	31.79	8.62	32.10	37.06	54.00	-16.94	Vertical
7236.00	22.67	36.19	11.68	31.97	38.57	54.00	-15.43	Vertical
9648.00	22.77	38.07	14.16	31.56	43.44	54.00	-10.56	Vertical
12060.00	*					54.00		Vertical
14472.00	*					54.00		Vertical
16884.00	*					54.00		Vertica
4824.00	27.97	31.79	8.62	32.10	36.28	54.00	-17.72	Horizontal
7236.00	22.19	36.19	11.68	31.97	38.09	54.00	-15.91	Horizontal
9648.00	21.77	38.07	14.16	31.56	42.44	54.00	-11.56	Horizontal
12060.00	*					54.00		Horizontal
14472.00	*					54.00		Horizontal
16884.00	*					54.00		Horizontal

Remarks:

1. *Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
2. *"*", means this data is the too weak instrument of signal is unable to test.*

Test mode:	802.11g	Test channel:	Middle

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	38.79	31.85	8.66	32.12	47.18	74.00	-26.82	Vertical
7311.00	33.94	36.37	11.71	31.91	50.11	74.00	-23.89	Vertical
9748.00	33.48	38.27	14.25	31.56	54.44	74.00	-19.56	Vertical
12185.00	*					74.00		Vertical
14622.00	*					74.00		Vertical
17059.00	*					74.00		Vertical
4874.00	39.36	31.85	8.66	32.12	47.75	74.00	-26.25	Horizontal
7311.00	32.62	36.37	11.71	31.91	48.79	74.00	-25.21	Horizontal
9748.00	33.39	38.27	14.25	31.56	54.35	74.00	-19.65	Horizontal
12185.00	*					74.00		Horizontal
14622.00	*					74.00		Horizontal
17059.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	29.69	31.85	8.66	32.12	38.08	54.00	-15.92	Vertical
7311.00	22.26	36.37	11.71	31.91	38.43	54.00	-15.57	Vertical
9748.00	22.74	38.27	14.25	31.56	43.70	54.00	-10.30	Vertical
12185.00	*					54.00		Vertical
14622.00	*					54.00		Vertical
17059.00	*					54.00		Vertical
4874.00	29.50	31.85	8.66	32.12	37.89	54.00	-16.11	Horizontal
7311.00	21.72	36.37	11.71	31.91	37.89	54.00	-16.11	Horizontal
9748.00	23.11	38.27	14.25	31.56	44.07	54.00	-9.93	Horizontal
12185.00	*					54.00		Horizontal
14622.00	*					54.00		Horizontal
17059.00	*					54.00		Horizontal

Remarks:

1. *Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
2. *"*", means this data is the too weak instrument of signal is unable to test.*

Test mode:	802.11g	Test channel:	Highest

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	43.92	31.90	8.70	32.15	52.37	74.00	-21.63	Vertical
7386.00	34.36	36.49	11.76	31.83	50.78	74.00	-23.22	Vertical
9848.00	36.59	38.62	14.31	31.77	57.75	74.00	-16.25	Vertical
12310.00	*					74.00		Vertical
14772.00	*					74.00		Vertical
17234.00	*					74.00		Vertical
4924.00	43.37	31.90	8.70	32.15	51.82	74.00	-22.18	Horizontal
7386.00	33.33	36.49	11.76	31.83	49.75	74.00	-24.25	Horizontal
9848.00	32.80	38.62	14.31	31.77	53.96	74.00	-20.04	Horizontal
12310.00	*					74.00		Horizontal
14772.00	*					74.00		Horizontal
17234.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	34.91	31.90	8.70	32.15	43.36	54.00	-10.64	Vertical
7386.00	24.29	36.49	11.76	31.83	40.71	54.00	-13.29	Vertical
9848.00	25.11	38.62	14.31	31.77	46.27	54.00	-7.73	Vertical
12310.00	*					54.00		Vertical
14772.00	*					54.00		Vertical
17234.00	*					54.00		Vertical
4924.00	33.79	31.90	8.70	32.15	42.24	54.00	-11.76	Horizontal
7386.00	22.74	36.49	11.76	31.83	39.16	54.00	-14.84	Horizontal
9848.00	22.07	38.62	14.31	31.77	43.23	54.00	-10.77	Horizontal
12310.00	*					54.00		Horizontal
14772.00	*					54.00		Horizontal
17234.00	*					54.00		Horizontal

Remarks:

1. *Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
2. *"*", means this data is the too weak instrument of signal is unable to test.*

Test mode:	802.11n(HT20)	Test channel:	Lowest

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	39.05	31.79	8.62	32.10	47.36	74.00	-26.64	Vertical
7236.00	33.43	36.19	11.68	31.97	49.33	74.00	-24.67	Vertical
9648.00	32.15	38.07	14.16	31.56	52.82	74.00	-21.18	Vertical
12060.00	*					74.00		Vertical
14472.00	*					74.00		Vertical
16884.00	*					74.00		Vertical
4824.00	37.91	31.79	8.62	32.10	46.22	74.00	-27.78	Horizontal
7236.00	33.28	36.19	11.68	31.97	49.18	74.00	-24.82	Horizontal
9648.00	31.77	38.07	14.16	31.56	52.44	74.00	-21.56	Horizontal
12060.00	*					74.00		Horizontal
14472.00	*					74.00		Horizontal
16884.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4824.00	28.23	31.79	8.62	32.10	36.54	54.00	-17.46	Vertical
7236.00	22.32	36.19	11.68	31.97	38.22	54.00	-15.78	Vertical
9648.00	22.52	38.07	14.16	31.56	43.19	54.00	-10.81	Vertical
12060.00	*					54.00		Vertical
14472.00	*					54.00		Vertical
16884.00	*					54.00		Vertical
4824.00	27.51	31.79	8.62	32.10	35.82	54.00	-18.18	Horizontal
7236.00	21.88	36.19	11.68	31.97	37.78	54.00	-16.22	Horizontal
9648.00	21.54	38.07	14.16	31.56	42.21	54.00	-11.79	Horizontal
12060.00	*					54.00		Horizontal
14472.00	*					54.00		Horizontal
16884.00	*					54.00		Horizontal

Remarks:

1. *Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
2. *"*", means this data is the too weak instrument of signal is unable to test.*

Test mode:	802.11n(HT20)	Test channel:	Middle

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	38.32	31.85	8.66	32.12	46.71	74.00	-27.29	Vertical
7311.00	33.64	36.37	11.71	31.91	49.81	74.00	-24.19	Vertical
9748.00	33.27	38.27	14.25	31.56	54.23	74.00	-19.77	Vertical
12185.00	*					74.00		Vertical
14622.00	*					74.00		Vertical
17059.00	*					74.00		Vertical
4874.00	38.96	31.85	8.66	32.12	47.35	74.00	-26.65	Horizontal
7311.00	32.36	36.37	11.71	31.91	48.53	74.00	-25.47	Horizontal
9748.00	33.19	38.27	14.25	31.56	54.15	74.00	-19.85	Horizontal
12185.00	*					74.00		Horizontal
14622.00	*					74.00		Horizontal
17059.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874.00	29.25	31.85	8.66	32.12	37.64	54.00	-16.36	Vertical
7311.00	21.98	36.37	11.71	31.91	38.15	54.00	-15.85	Vertical
9748.00	22.54	38.27	14.25	31.56	43.50	54.00	-10.50	Vertical
12185.00	*					54.00		Vertical
14622.00	*					54.00		Vertical
17059.00	*					54.00		Vertical
4874.00	29.12	31.85	8.66	32.12	37.51	54.00	-16.49	Horizontal
7311.00	21.47	36.37	11.71	31.91	37.64	54.00	-16.36	Horizontal
9748.00	22.92	38.27	14.25	31.56	43.88	54.00	-10.12	Horizontal
12185.00	*					54.00		Horizontal
14622.00	*					54.00		Horizontal
17059.00	*					54.00		Horizontal

Remarks:

1. *Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
2. *"*", means this data is the too weak instrument of signal is unable to test.*

Test mode:	802.11n(HT20)	Test channel:	Highest

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	43.10	31.90	8.70	32.15	51.55	74.00	-22.45	4924.00
7386.00	33.84	36.49	11.76	31.83	50.26	74.00	-23.74	7386.00
9848.00	36.22	38.62	14.31	31.77	57.38	74.00	-16.62	9848.00
12310.00	*					74.00		Vertical
14772.00	*					74.00		Vertical
17234.00	*					74.00		Vertical
4924.00	42.68	31.90	8.70	32.15	51.13	74.00	-22.87	Horizontal
7386.00	32.88	36.49	11.76	31.83	49.30	74.00	-24.70	Horizontal
9848.00	32.46	38.62	14.31	31.77	53.62	74.00	-20.38	Horizontal
12310.00	*					74.00		Horizontal
14772.00	*					74.00		Horizontal
17234.00	*					74.00		Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924.00	34.16	31.90	8.70	32.15	42.61	54.00	-11.39	Vertical
7386.00	23.80	36.49	11.76	31.83	40.22	54.00	-13.78	Vertical
9848.00	24.76	38.62	14.31	31.77	45.92	54.00	-8.08	Vertical
12310.00	*					54.00		Vertical
14772.00	*					54.00		Vertical
17234.00	*					54.00		Vertical
4924.00	33.14	31.90	8.70	32.15	41.59	54.00	-12.41	Horizontal
7386.00	22.30	36.49	11.76	31.83	38.72	54.00	-15.28	Horizontal
9848.00	21.74	38.62	14.31	31.77	42.90	54.00	-11.10	Horizontal
12310.00	*					54.00		Horizontal
14772.00	*					54.00		Horizontal
17234.00	*					54.00		Horizontal

Remarks:

1 Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor

2 "", means this data is the too weak instrument of signal is unable to test.*

8 Test Setup Photo

Radiated Emission





Conducted Emission

9 EUT Constructional Details






XBY201805 79
WIFI/BT ANT










SAMSUNG 546
K3PE8E000M-CGC2
EXJX009B


Rockchip
RK3288


ZS 626696 5000mAh 3.7V
18.5Wh 2018-11-02

GME SWITCHING POWER ADAPTER
MODEL:GME36A-120300FDS
INPUT:100-240V~50-60Hz 1.2A
OUTPUT:12V 3A
A.V. POWER SUPPLY
Efficiency Level: VI
LISTED
E251844
23EZ
MADE IN CHINA
1606- 0000549

------End------