

FCC Measurement/Technical Report on

LC8 DASHBOARD

FCC ID: 2AKP9-LC8CLUSTER1
IC: 22273-LC8CLUSTER1

Test Report Reference: MDE_BOSCH_1629_FCCb_rev1

Test Laboratory:

7layers GmbH
Borsigstrasse 11
40880 Ratingen
Germany



Note:

The following test results relate only to the devices specified in this document. This report shall not be reproduced in parts without the written approval of the test laboratory.

7layers GmbH

Borsigstraße 11
40880 Ratingen, Germany
T +49 (0) 2102 749 0
F +49 (0) 2102 749 350

Geschäftsführer/

Managing Directors:

Frank Spiller
Bernhard Retka
Alexandre Norré-Oudard

Registergericht/registered:

Düsseldorf HRB 75554
USt-Id.-Nr./VAT-No. DE203159652
Steuer-Nr./TAX-No. 147/5869/0385

*a Bureau Veritas
Group Company*

www.7layers.com

Table of Contents

1	Applied Standards and Test Summary	4
1.1	Applied Standards	4
1.2	FCC-IC Correlation Table	5
1.3	Measurement Summary / Signatures	6
2	Administrative Data	11
2.1	Testing Laboratory	11
2.2	Project Data	11
2.3	Applicant Data	11
3	Test object Data	12
3.1	General EUT Description	12
3.2	EUT Main components	13
3.3	Ancillary Equipment	14
3.4	Auxiliary Equipment	14
3.5	EUT Setups	14
3.6	Operating Modes	15
3.7	Product labelling	15
4	Test Results	16
4.1	Occupied Bandwidth (20 dB)	16
4.2	Peak Power Output	19
4.3	Spurious RF Conducted Emissions	22
4.4	Transmitter Spurious Radiated Emissions	25
4.5	Band Edge Compliance Conducted	33
4.6	Band Edge Compliance Radiated	36
4.7	Channel Separation	39
4.8	Dwell Time	41
4.9	Number of Hopping Frequencies	43
5	Test Equipment	45
6	Antenna Factors, Cable Loss and Sample Calculations	48
6.1	LISN R&S ESH3-Z5 (150 kHz – 30 MHz)	48
6.2	Antenna R&S HFH2-Z2 (9 kHz – 30 MHz)	49
6.3	Antenna R&S HL562 (30 MHz – 1 GHz)	50
6.4	Antenna R&S HF907 (1 GHz – 18 GHz)	51
6.5	Antenna EMCO 3160-09 (18 GHz – 26.5 GHz)	52
7	Setup Drawings	53
8	Measurement Uncertainties	54

9 Photo Report

54

1 APPLIED STANDARDS AND TEST SUMMARY

1.1 APPLIED STANDARDS

Type of Authorization

Certification for an Intentional Radiator.

Applicable FCC Rules

Prepared in accordance with the requirements of FCC Rules and Regulations as listed in 47 CFR Ch.1 Parts 2 and 15 (10-1-15 Edition). The following subparts are applicable to the results in this test report.

Part 2, Subpart J - Equipment Authorization Procedures, Certification

Part 15, Subpart C – Intentional Radiators

§ 15.201 Equipment authorization requirement

§ 15.207 Conducted limits

§ 15.209 Radiated emission limits; general requirements

§ 15.247 Operation within the bands 902-928 MHz, 2400-2483.5 MHz

Note 1: (FHSS Equipment)

The tests were selected and performed with reference to the FCC Public Notice DA 00-705, released March 30, 2000. Instead of applying ANSI C63.4-1992 which is referenced in the FCC Public Note, the newer ANSI C63.10-2013 is applied.

Summary Test Results:

The EUT complied with all performed tests as listed in chapter 1.3 Measurement Summary / Signatures.

1.2 FCC-IC CORRELATION TABLE

Correlation of measurement requirements for FHSS (e.g. Bluetooth®) equipment from FCC and IC

FHSS equipment

Measurement	FCC reference	IC reference
Conducted emissions on AC Mains	§ 15.207	RSS-Gen Issue 4: 8.8
Occupied bandwidth	§ 15.247 (a) (1)	RSS-247 Issue 1: 5.1 (2)
Peak conducted output power	§ 15.247 (b) (1), (4)	RSS-247 Issue 1: 5.4 (2)
Transmitter spurious RF conducted emissions	§ 15.247 (d)	RSS-Gen Issue 4: 6.13/8.9/8.10; RSS-247 Issue 1: 5.5
Transmitter spurious radiated emissions	§ 15.247 (d); § 15.209 (a)	RSS-Gen Issue 4: 6.13 / 8.9/8.10; RSS-247 Issue 1: 5.5
Band edge compliance	§ 15.247 (d)	RSS-247 Issue 1: 5.5
Dwell time	§ 15.247 (a) (1) (iii)	RSS-247 Issue 1: 5.1 (4)
Channel separation	§ 15.247 (a) (1)	RSS-247 Issue 1: 5.1 (2)
No. of hopping frequencies	§ 15.247 (a) (1) (iii)	RSS-247 Issue 1: 5.1 (4)
Hybrid systems (only)	§ 15.247 (f); § 15.247 (e)	RSS-247 Issue 1: 5.3
Antenna requirement	§ 15.203 / 15.204	RSS-Gen Issue 4: 8.3
Receiver spurious emissions	-	-

1.3 MEASUREMENT SUMMARY / SIGNATURES

47 CFR CHAPTER I FCC PART 15 Subpart C §15.247

§ 15.247 (a) (1)

Occupied Bandwidth (20 dB)

The measurement was performed according to ANSI C63.10

Final Result

OP-Mode

Radio Technology, Operating Frequency

Bluetooth BDR, high

Setup

S01_AD01

FCC

Passed

IC

Passed

Bluetooth BDR, low

S01_AD01

Passed

Passed

Bluetooth BDR, mid

S01_AD01

Passed

Passed

Bluetooth EDR 2, high

S01_AD01

Passed

Passed

Bluetooth EDR 2, low

S01_AD01

Passed

Passed

Bluetooth EDR 2, mid

S01_AD01

Passed

Passed

Bluetooth EDR 3, high

S01_AD01

Passed

Passed

Bluetooth EDR 3, low

S01_AD01

Passed

Passed

Bluetooth EDR 3, mid

S01_AD01

Passed

Passed

47 CFR CHAPTER I FCC PART 15 Subpart C §15.247

§ 15.247 (b) (1)

Peak Power Output

The measurement was performed according to ANSI C63.10

Final Result

OP-Mode

Operating Frequency, Measurement method

Bluetooth BDR, high, conducted

Setup

S01_AD01

FCC

Passed

IC

Passed

S01_AO01

Passed

Passed

Bluetooth BDR, low, conducted

S01_AD01

Passed

Passed

S01_AO01

Passed

Passed

Bluetooth BDR, mid, conducted

S01_AD01

Passed

Passed

S01_AO01

Passed

Passed

Bluetooth EDR 2, high, conducted

S01_AD01

Passed

Passed

S01_AO01

Passed

Passed

Bluetooth EDR 2, low, conducted

S01_AD01

Passed

Passed

S01_AO01

Passed

Passed

Bluetooth EDR 2, mid, conducted

S01_AD01

Passed

Passed

S01_AO01

Passed

Passed

Bluetooth EDR 3, high, conducted

S01_AD01

Passed

Passed

S01_AO01

Passed

Passed

Bluetooth EDR 3, low, conducted

S01_AD01

Passed

Passed

S01_AO01

Passed

Passed

Bluetooth EDR 3, mid, conducted

S01_AD01

Passed

Passed

S01_AO01

Passed

Passed

47 CFR CHAPTER I FCC PART 15 Subpart C
§15.247

§ 15.247 (d)

Spurious RF Conducted Emissions

The measurement was performed according to ANSI C63.10

Final Result

OP-Mode

Radio Technology, Operating Frequency

Bluetooth BDR, high

Bluetooth BDR, low

Bluetooth BDR, mid

Bluetooth EDR 2, high

Bluetooth EDR 2, low

Bluetooth EDR 2, mid

Bluetooth EDR 3, high

Bluetooth EDR 3, low

Bluetooth EDR 3, mid

Setup

FCC

IC

S01_AD01

Passed

Passed

S01_AD01

Passed

Passed

S01_AD01

Passed

Passed

S01_AD01

Passed

Passed

S01_AD01

Passed

Passed

S01_AD01

Passed

Passed

S01_AD01

Passed

Passed

S01_AD01

Passed

Passed

S01_AD01

Passed

Passed

47 CFR CHAPTER I FCC PART 15 Subpart C
§15.247

§ 15.247 (d)

Transmitter Spurious Radiated Emissions

The measurement was performed according to ANSI C63.10

Final Result

OP-Mode

Radio Technology, Operating Frequency, Measurement range

Bluetooth BDR, high, 1 GHz - 26 GHz

Remark: BT+WLAN module tested in range 1 - 8 GHz only

Bluetooth BDR, high, 30 MHz - 1 GHz

Remark: Tested only with BT only module.

Bluetooth BDR, low, 1 GHz - 26 GHz

Remark: BT+WLAN module tested in range 1 - 8 GHz only

Bluetooth BDR, low, 30 MHz - 1 GHz

Remark: Tested only with BT only module.

Bluetooth BDR, mid, 1 GHz - 26 GHz

Remark: BT+WLAN module tested in range 1 - 8 GHz only

Bluetooth BDR, mid, 30 MHz - 1 GHz

Remark: Tested only with BT only module.

Bluetooth BDR, mid, 9 kHz - 30 MHz

Remark: Tested only with BT only module.

Bluetooth EDR 2, high, 1 GHz - 26 GHz

Remark: tested in range 1 - 8 GHz only

Bluetooth EDR 2, low, 1 GHz - 26 GHz

Remark: tested in range 1 - 8 GHz only

Bluetooth EDR 2, mid, 1 GHz - 26 GHz

Remark: tested in range 1 - 8 GHz only

Bluetooth EDR 3, high, 1 GHz - 26 GHz

Remark: BT only module tested in range 1 - 8 GHz only

Bluetooth EDR 3, high, 30 MHz - 1 GHz

Remark: Tested only with WLAN+BT module.

Bluetooth EDR 3, low, 1 GHz - 26 GHz

Remark: BT only module tested in range 1 - 8 GHz only

Setup

FCC

IC

S01_AF01

Passed

Passed

S01_AO01

Passed

Passed

S01_AF01

Passed

Passed

S01_AO01

Passed

Passed

S01_AF01

Passed

Passed

S01_AF01

Passed

Passed

S01_AF01

Passed

Passed

S01_AF01

Passed

Passed

S01_AF01

Passed

Passed

S01_AF01

Passed

Passed

S01_AF01

Passed

Passed

S01_AF01

Passed

Passed

S01_AF01

Passed

Passed

S01_AF01

Passed

Passed

S01_AO01

Passed

Passed

S01_AF01

Passed

Passed

Bluetooth EDR 3, low, 30 MHz - 1 GHz
Remark: Tested only with WLAN+BT module.

S01_AF01	Passed	Passed
S01_AO01	Passed	Passed

Bluetooth EDR 3, mid, 1 GHz - 26 GHz
Remark: BT only module tested in range 1 - 8 GHz only

S01_AF01	Passed	Passed
----------	--------	--------

Bluetooth EDR 3, mid, 30 MHz - 1 GHz
Remark: Tested only with WLAN+BT module.

S01_AF01	Passed	Passed
S01_AO01	Passed	Passed

Bluetooth BDR, mid, 9 kHz - 30 MHz
Remark: Tested only with WLAN+BT module.

S01_AF01	Passed	Passed
----------	--------	--------

47 CFR CHAPTER I FCC PART 15 Subpart C §15.247

§ 15.247 (d)

Band Edge Compliance Conducted

The measurement was performed according to ANSI C63.10

Final Result

OP-Mode

Radio Technology, Operating Frequency, Band Edge

Bluetooth BDR, high, high

Setup	FCC	IC
S01_AD01	Passed	Passed

Bluetooth BDR, hopping, high

S01_AD01	Passed	Passed
----------	--------	--------

Bluetooth BDR, hopping, low

S01_AD01	Passed	Passed
----------	--------	--------

Bluetooth BDR, low, low

S01_AD01	Passed	Passed
----------	--------	--------

Bluetooth EDR 2, high, high

S01_AD01	Passed	Passed
----------	--------	--------

Bluetooth EDR 2, hopping, high

S01_AD01	Passed	Passed
----------	--------	--------

Bluetooth EDR 2, hopping, low

S01_AD01	Passed	Passed
----------	--------	--------

Bluetooth EDR 2, low, low

S01_AD01	Passed	Passed
----------	--------	--------

Bluetooth EDR 3, high, high

S01_AD01	Passed	Passed
----------	--------	--------

Bluetooth EDR 3, hopping, high

S01_AD01	Passed	Passed
----------	--------	--------

Bluetooth EDR 3, hopping, low

S01_AD01	Passed	Passed
----------	--------	--------

Bluetooth EDR 3, low, low

S01_AD01	Passed	Passed
----------	--------	--------

47 CFR CHAPTER I FCC PART 15 Subpart C §15.247

§ 15.247 (d)

Band Edge Compliance Radiated

The measurement was performed according to ANSI C63.10

Final Result

OP-Mode

Radio Technology, Operating Frequency, Band Edge

Bluetooth BDR, high, high

Setup	FCC	IC
S01_AF01	Passed	Passed

Bluetooth EDR 2, high, high

S01_AO01	Passed	Passed
----------	--------	--------

Bluetooth EDR 3, high, high

S01_AF01	Passed	Passed
S01_AO01	Passed	Passed
S01_AF01	Passed	Passed
S01_AO01	Passed	Passed

47 CFR CHAPTER I FCC PART 15 Subpart C
§15.247

§ 15.247 (a) (1)

Channel Separation

The measurement was performed according to ANSI C63.10

Final Result

OP-Mode

Radio Technology

Bluetooth BDR

Setup

S01_AD01

FCC

Passed

IC

Passed

47 CFR CHAPTER I FCC PART 15 Subpart C
§15.247

§ 15.247 (a) (1) (iii)

Dwell Time

The measurement was performed according to ANSI C63.10

Final Result

OP-Mode

Radio Technology

Bluetooth BDR

Setup

S01_AD01

FCC

Passed

IC

Passed

47 CFR CHAPTER I FCC PART 15 Subpart C
§15.247

§ 15.247 (a) (1) (iii)

Number of Hopping Frequencies

The measurement was performed according to ANSI C63.10

Final Result

OP-Mode

Radio Technology

Bluetooth BDR

Setup

S01_AD01

FCC

Passed

IC

Passed

N/A: Not applicable

N/P: Not performed

After initial testing was complete, the Hard- and Software of the EUT was modified by the applicant. According to the applicant, there were no changes in relation to the transmitter hardware. See additional document "LC8 DASHBOARD HW502toHW602.pdf" for changes made.

Due to this only Spot Checks have been performed with the modified version of the EUT for test cases Peak Power Output, Transmitter Spurious Radiated Emissions and Band Edge Compliance Radiated. Since the conducted Peak Power results showed similar signal shape and similar power, no further conducted testing was performed.

Revision History

Report version control			
Version	Release date	Change Description	Version validity
initial	2017-01-23	--	invalid
rev1	2017-02-08	Changed name and type of EUT, corrected postcode of applicant, corrected test period, changed product description, changed note in regards to HW change	valid

M. Kullik MARCO KULLIK
2017.02.08
18:44:23 +01'00'

(responsible for accreditation scope)
Dipl.-Ing. Marco Kullik

D. Gall DANIEL GALL
2017.02.08
18:39:53 +01'00'

(responsible for testing and report)
Dipl.-Ing. Daniel Gall

2 ADMINISTRATIVE DATA

2.1 TESTING LABORATORY

Company Name: 7layers GmbH
Address: Borsigstr. 11
40880 Ratingen
Germany

This facility has been fully described in a report submitted to the FCC and accepted under the registration number 96716.

This facility has been fully described in a report submitted to the IC and accepted under the registration number: Site# 3699A-1.

The test facility is also accredited by the following accreditation organisation:

Laboratory accreditation no: DAkkS D-PL-12140-01-00
Responsible for accreditation scope: Dipl.-Ing. Marco Kullik
Report Template Version: 2016-06-07

2.2 PROJECT DATA

Responsible for testing and report: Dipl.-Ing. Daniel Gall
Employees who performed the tests: documented internally at 7Layers
Date of Report: 2017-02-08
Testing Period: 2016-11-15 to 2017-01-18

2.3 APPLICANT DATA

Company Name: Robert Bosch GmbH
Address: Daimlerstraße 6
71229 Leonberg
Germany
Contact Person: Mr. Daniel Beurer

2.4 MANUFACTURER DATA

Company Name: KTM AG
Address: Stallhofner Straße 3
5230 Mattighofen
Austria
Contact Person: Mr. Roeck Vitalis

3 TEST OBJECT DATA

3.1 GENERAL EUT DESCRIPTION

Kind of Device product description	Motorbike dashboard with integrated WLAN and Bluetooth.
Product name	LC8 DASHBOARD
Type	LC8 DASHBOARD
Declared EUT data by the supplier	
Voltage Type	DC
Voltage Level	DC 13.0 V
Tested Modulation Type	BT both modules: GFSK Modulation, 1-DHx packets π/4 DQPSK Modulation, 2-DHx packets 8-DPSK Modulation, 3-DHx packets
General product description	The EUT is a motorbike dashboard with integrated BT and WLAN
Specific product description for the EUT	The EUT is equipped with two modules. One module with Bluetooth technology only and one with Bluetooth and WLAN technology. The device will support WLAN modes b/g/n 20MHz bandwidth on channels 1 to 11 and Bluetooth classic. There are no changes in this regard between the two tested HW and SW versions.
The EUT provides the following ports:	Enclosure Cable Harness consisting of: USB shielded, Handlebar switch unshielded, ELOCK LED unshielded, DC supply unshielded, CAN unshielded, Ignition switch unshielded, Security alarm unshielded, MIL indicator unshielded, Ambient temperature sensor unshielded. length during testing: 1.92 m
Tested datarates	BT both modules: 1Mbps (DHx packets) 2Mbps (2-DHx packets) 3Mbps (3-DHx packets) All tests were performed in local TX mode, set with a special software provided by the applicant.

The main components of the EUT are listed and described in chapter 3.2 EUT Main components.

3.2 EUT MAIN COMPONENTS

Sample Name	Sample Code	Description
DE1050009ad01	ad01	Sample for conducted testing
Sample Parameter	Value	
Integral Antenna	deactivated	
Serial No.	#004	
HW Version	HW 502	
SW Version	SWP 032.35	
Comment		

Sample Name	Sample Code	Description
DE1050009af01	af01	Sample for radiated testing
Sample Parameter	Value	
Integral Antenna	BT only module: 3.01 dBi, BT+WLAN module: 2.42 dBi	
Serial No.	#006	
HW Version	HW 502	
SW Version	SWP 032.35	
Comment		

Sample Name	Sample Code	Description
DE1050009an02	an02	Sample modified Hard- and Software for radiated testing
Sample Parameter	Value	
Integral Antenna	BT only module: 3.01 dBi, BT+WLAN module: 2.42 dBi	
Serial No.	#011	
HW Version	HW 602	
SW Version	SWP 033.33	
Comment		

Sample Name	Sample Code	Description
DE1050009ao02	ao02	Sample modified Hard- and Software for conducted testing
Sample Parameter	Value	
Integral Antenna	deactivated	
Serial No.	#010	
HW Version	HW 602	
SW Version	SWP 033.33	
Comment		

NOTE: The short description is used to simplify the identification of the EUT in this test report.

3.3 ANCILLARY EQUIPMENT

For the purposes of this test report, ancillary equipment is defined as equipment which is used in conjunction with the EUT to provide operational and control features to the EUT. It is necessary to configure the system in a typical fashion, as a customer would normally use it. But nevertheless Ancillary Equipment can influence the test results.

Device	Details (Manufacturer, Type Model, OUT Code)	Description
-	-	-

3.4 AUXILIARY EQUIPMENT

For the purposes of this test report, auxiliary equipment is defined as equipment which is used temporarily to enable operational and control features especially used for the tests of the EUT which is not used during normal operation or equipment that is used during the tests in combination with the EUT but is not subject of this test report. It is necessary to configure the system in a typical fashion, as a customer would normally use it. But nevertheless Auxiliary Equipment can influence the test results.

Device	Details (Manufacturer, HW, SW, S/N)	Description
DE1050009AE01	Drew Technologies, -, -, 002241	USB - CAN Adapter
DE1050009AE04	Robert Bosch Elektronik GmbH, -, -, 3217	Control Box KTM

3.5 EUT SETUPS

This chapter describes the combination of EUTs and equipment used for testing. The rationale for selecting the EUTs, ancillary and auxiliary equipment and interconnecting cables, is to test a representative configuration meeting the requirements of the referenced standards.

Setup	Combination of EUTs	Description and Rationale
S01_AD01	DE1050009ad01, DE1050009AE04, DE1050009AE01,	Conducted Setup #01
S01_AF01	DE1050009af01, DE1050009AE04, DE1050009AE01,	Radiated Setup #01
S01_AN01	DE1050009an02, DE1050009AE04	Radiated Setup for changed HW / SW
S01_AO01	DE1050009ao02, DE1050009AE04, DE1050009AE01	Conducted Setup for changed HW / SW

3.6 OPERATING MODES

This chapter describes the operating modes of the EUTs used for testing.

3.6.1 TEST CHANNELS

BT Test Channels:
Channel:
Frequency [MHz]

2.4 GHz ISM 2400 - 2483.5 MHz		
low	mid	high
0	39	78
2402	2441	2480

3.7 PRODUCT LABELLING

3.7.1 FCC ID LABEL

Please refer to the documentation of the applicant.

3.7.2 LOCATION OF THE LABEL ON THE EUT

Please refer to the documentation of the applicant.

4 TEST RESULTS

4.1 OCCUPIED BANDWIDTH (20 DB)

Standard **FCC Part 15 Subpart C**

The test was performed according to:
ANSI C63.10

4.1.1 TEST DESCRIPTION

The Equipment Under Test (EUT) was set up to perform the occupied bandwidth measurements.

The reference level is the level of the highest amplitude signal observed from the transmitter at either the fundamental frequency or first-order modulation products in all typical modes of operation, including the unmodulated carrier, even if atypical.

The results recorded were measured with the modulation which produce the worst-case (widest) emission bandwidth.

The EUT was connected to spectrum analyzer via a short coax cable with a known loss.

Analyzer settings:

- Resolution Bandwidth (RBW): 1% to 5 % of the OBW
- Video Bandwidth (VBW): 3 x RBW
- Span: 2 to 5 times the OBW
- Trace: Maxhold
- Sweeps: 2000
- Sweep time: 8.5 ms
- Detector: Peak

The technology depending measurement parameters can be found in the measurement plot.

4.1.2 TEST REQUIREMENTS / LIMITS

FCC Part 15, Subpart C, §15.247 (a) (2)

For the band: 902 – 928 MHz

FCC Part 15, Subpart C, §15.247 (a) (1) (i)

The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz

For the band: 5725 – 5850 MHz

FCC Part 15, Subpart C, §15.247 (a) (1) (ii)

The maximum allowed 20 dB bandwidth of the hopping channel is 1 MHz

For the frequency band 2400 – 2483.5 MHz:

FCC Part 15, Subpart C, §15.247 (a) (1) (iii)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

Implication by the test laboratory:

Since the Bluetooth technology defines a fixed channel separation of 1 MHz this design parameter defines the maximum allowed occupied bandwidth depending on the EUT's output power:

1. Under the provision that the system operates with an output power not greater than 125 mW (21.0 dBm):

Implicit Limit: Max. 20 dB BW = $1.0 \text{ MHz} / 2/3 = 1.5 \text{ MHz}$

2. If the system output power exceeds 125 mW (21.0 dBm):

Implicit Limit: Max. 20 dB BW = 1.0 MHz

Used conversion factor: Output power (dBm) = $10 \log (\text{Output power (W)} / 1\text{mW})$

The measured output power of the system is below 125 mW (21.0 dBm). For the results, please refer to the related chapter of this report.

Therefore the limit is determined as 1.5 MHz.

4.1.3 TEST PROTOCOL

Ambient temperature: 23°C
Air Pressure: 1017hPa
Humidity: 43%
BT GFSK (1-DH1)

Module	Channel No.	Frequency [MHz]	20 dB Bandwidth [kHz]	Limit [kHz]	Margin to Limit [kHz]
BT/WLAN	0	2402	1046.4	1500	453.6
BT	0	2402	1052.4	1500	447.6
BT/WLAN	39	2441	1040.4	1500	459.6
BT	39	2441	1046.4	1500	453.6
BT/WLAN	78	2480	1046.4	1500	453.6
BT	78	2480	1046.4	1500	453.6

BT π/4 DQPSK (2-DH1)

Module	Channel No.	Frequency [MHz]	20 dB Bandwidth [kHz]	Limit [kHz]	Margin to Limit [kHz]
BT/WLAN	0	2402	1130.4	1500	369.6
BT	0	2402	1130.4	1500	369.6
BT/WLAN	39	2441	1130.4	1500	369.6
BT	39	2441	1130.4	1500	369.6
BT/WLAN	78	2480	1130.4	1500	369.6
BT	78	2480	1130.4	1500	369.6


BT 8-DPSK (3-DH1)

Module	Channel No.	Frequency [MHz]	20 dB Bandwidth [kHz]	Limit [kHz]	Margin to Limit [kHz]
BT/WLAN	0	2402	1227.6	1500	272.4
BT	0	2402	1221.6	1500	278.4
BT/WLAN	39	2441	1233.6	1500	266.4
BT	39	2441	1221.6	1500	278.4
BT/WLAN	78	2480	1233.6	1500	266.4
BT	78	2480	1215.6	1500	284.4

Remark: Please see next sub-clause for the measurement plot.

4.1.4 MEASUREMENT PLOT (SHOWING THE HIGHEST VALUE, "WORST CASE")

Radio Technology = Bluetooth EDR 3, Operating Frequency = mid



Title: 20dB Bandwidth
 Comment A: CH M: 2441 MHz; 20dB bandwidth (kHz):1233.6
 Date: 17.NOV.2016 11:30:58

BT + WLAN module

4.1.5 TEST EQUIPMENT USED

Regulatory Bluetooth RF Test Solution

4.2 PEAK POWER OUTPUT

Standard **FCC Part 15 Subpart C**

The test was performed according to:
ANSI C63.10

4.2.1 TEST DESCRIPTION

DTS EQUIPMENT:

The Equipment Under Test (EUT) was set up to perform the output power measurements. The results recorded were measured with the modulation which produces the worst-case (highest) output power. The reference level of the spectrum analyzer was set higher than the output power of the EUT.

The EUT was connected to the spectrum analyzer via a short coax cable with a known loss.

Analyzer settings:

- Resolution Bandwidth (RBW): 1 MHz
- Video Bandwidth (VBW): 3 MHz
- Trace: Maxhold
- Sweeps: 2000
- Sweeptime: 5 ms
- Detector: Peak

The channel power function of the spectrum analyser was used (Used channel bandwidth = DTS bandwidth)

FHSS EQUIPMENT:

The Equipment Under Test (EUT) was set up to perform the output power measurements. The results recorded were measured with the modulation which produces the worst-case (highest) output power. The reference level of the spectrum analyzer was set higher than the output power of the EUT.

The EUT was connected to the spectrum analyzer via a short coax cable with a known loss.

Analyzer settings:

- Resolution Bandwidth (RBW): 3 MHz
- Video Bandwidth (VBW): 3 MHz
- Trace: Maxhold
- Sweeps: 2000
- Sweeptime: 5 ms
- Detector: Peak

4.2.2 TEST REQUIREMENTS / LIMITS

DTS devices:

FCC Part 15, Subpart C, §15.247 (b) (3)

For systems using digital modulation techniques in the 902-928 MHz, 2400-2483.5 MHz and 5725-5850 MHz bands: 1 watt.

==> Maximum conducted peak output power: 30 dBm (excluding antenna gain, if antennas with directional gains that do not exceed 6 dBi are used).

Frequency Hopping Systems:

FCC Part 15, Subpart C, §15.247 (b) (1)

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

FCC Part 15, Subpart C, §15.247 (b) (2)

For frequency hopping systems operating in the 902-928 MHz band: 1 watt for systems employing at least 50 hopping channels; and, 0.25 watts for systems employing less than 50 hopping channels, but at least 25 hopping channels, as permitted under paragraph (a)(1)(i) of this section.

Used conversion factor: Limit (dBm) = 10 log (Limit (W)/1mW)

4.2.3 TEST PROTOCOL

Ambient temperature: 23°C
Air Pressure: 1017hPa
Humidity: 43%

Results Setup S01_AD01
BT GFSK (1-DH1)

Module	Channel No.	Frequency [MHz]	Peak Power Hardware HW 502 [dBm]	Limit [dBm]	Margin to Limit [dB]
BT/WLAN	0	2402	-2.3	21.0	23.3
BT	0	2402	-0.6	21.0	21.6
BT/WLAN	39	2441	-1.9	21.0	22.9
BT	39	2441	0.1	21.0	20.9
BT/WLAN	78	2480	-2.4	21.0	23.4
BT	78	2480	0.2	21.0	20.8

Results Setup S01_AO01

Peak Power Hardware HW 602 [dBm]	Margin to Limit [dB]
-3.2	24.2
-1.1	22.1
-2.8	23.8
0.2	20.8
-2.4	23.4
-0.4	21.4

BT n/4 DQPSK (2-DH1)

Module	Channel No.	Frequency [MHz]	Peak Power Hardware HW 502 [dBm]	Limit [dBm]	Margin to Limit [dB]
BT/WLAN	0	2402	0.2	21.0	20.8
BT	0	2402	-1.2	21.0	22.2
BT/WLAN	39	2441	0.6	21.0	20.4
BT	39	2441	-0.4	21.0	21.4
BT/WLAN	78	2480	0.7	21.0	20.3
BT	78	2480	-0.2	21.0	21.2

Peak Power Hardware HW 602 [dBm]	Margin to Limit [dB]
-1.0	22.0
-1.0	22.0
-0.3	21.3
0.3	20.7
0.3	20.7
-0.3	21.3

BT 8-DPSK (3-DH1)


Module	Channel No.	Frequency [MHz]	Peak Power Hardware HW 502 [dBm]	Limit [dBm]	Margin to Limit [dB]
BT/WLAN	0	2402	0.2	21.0	20.8
BT	0	2402	-1.2	21.0	22.2
BT/WLAN	39	2441	0.6	21.0	20.4
BT	39	2441	-0.5	21.0	21.5
BT/WLAN	78	2480	0.7	21.0	20.3
BT	78	2480	-0.4	21.0	21.4

Peak Power Hardware HW 602 [dBm]	Margin to Limit [dB]
-0.4	21.4
-0.6	21.6
0.2	20.8
0.5	20.5
0.7	20.3
-0.7	21.7


Remark: Please see next sub-clause for the measurement plot.

4.2.4 MEASUREMENT PLOT (SHOWING THE HIGHEST VALUE, "WORST CASE")

Radio Technology = Bluetooth EDR 3, Operating Frequency = high, Measurement method = conducted



Setup S01_AD01, BT + WLAN module



Setup S01_A001, BT + WLAN module

4.2.5 TEST EQUIPMENT USED

Regulatory Bluetooth RF Test Solution

4.3 SPURIOUS RF CONDUCTED EMISSIONS

Standard **FCC Part 15 Subpart C**

The test was performed according to:
ANSI C63.10

4.3.1 TEST DESCRIPTION

The Equipment Under Test (EUT) was set up to perform the spurious emissions measurements. The EUT was connected to spectrum analyzer via a short coax cable with a known loss.

Analyzer settings:

- Frequency range: 30 – 25000 MHz
- Resolution Bandwidth (RBW): 100 kHz
- Video Bandwidth (VBW): 300 kHz
- Trace: Maxhold
- Sweeps: 2
- Sweep Time: 330 s
- Detector: Peak

The reference value for the measurement of the spurious RF conducted emissions is determined during the test "band edge compliance conducted". This value is used to calculate the 20 dBc limit.

4.3.2 TEST REQUIREMENTS / LIMITS

FCC Part 15, Subpart C, §15.247 (c)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

4.3.3 TEST PROTOCOL

Ambient temperature: 23°C
 Air Pressure: 1017hPa
 Humidity: 43%
 BT GFSK (1-DH1)

Module	Channel No	Channel Center Freq. [MHz]	Spurious Freq. [MHz]	Spurious Level [dBm]	Detector	RBW [kHz]	Ref. Level [dBm]	Limit [dBm]	Margin to Limit [dB]
BT/WLAN	0	2402	- - -	- - -	PEAK	100	-2.5	-22.5	>20
BT	0	2402	- - -	- - -	PEAK	100	-2.5	-22.5	>20
BT/WLAN	39	2441	- - -	- - -	PEAK	100	-2.0	-22.0	>20
BT	39	2441	- - -	- - -	PEAK	100	-2.0	-22.0	>20
BT/WLAN	78	2480	- - -	- - -	PEAK	100	-2.6	-22.6	>20
BT	78	2480	- - -	- - -	PEAK	100	-2.6	-22.6	>20

BT $\pi/4$ DQPSK (2-DH1)

Module	Channel No	Channel Center Freq. [MHz]	Spurious Freq. [MHz]	Spurious Level [dBm]	Detector	RBW [kHz]	Ref. Level [dBm]	Limit [dBm]	Margin to Limit [dB]
BT/WLAN	0	2402	- - -	- - -	PEAK	100	-2.3	-22.3	>20
BT	0	2402	- - -	- - -	PEAK	100	-2.3	-22.3	>20
BT/WLAN	39	2441	- - -	- - -	PEAK	100	-1.6	-21.6	>20
BT	39	2441	- - -	- - -	PEAK	100	-1.6	-21.6	>20
BT/WLAN	78	2480	- - -	- - -	PEAK	100	-1.7	-21.7	>20
BT	78	2480	- - -	- - -	PEAK	100	-1.7	-21.7	>20


BT 8-DPSK (3-DH1)

Module	Channel No	Channel Center Freq. [MHz]	Spurious Freq. [MHz]	Spurious Level [dBm]	Detector	RBW [kHz]	Ref. Level [dBm]	Limit [dBm]	Margin to Limit [dB]
BT/WLAN	0	2402	- - -	- - -	PEAK	100	-2.2	-22.2	>20
BT	0	2402	- - -	- - -	PEAK	100	-2.2	-22.2	>20
BT/WLAN	39	2441	- - -	- - -	PEAK	100	-1.6	-21.6	>20
BT	39	2441	- - -	- - -	PEAK	100	-1.6	-21.6	>20
BT/WLAN	78	2480	- - -	- - -	PEAK	100	-1.9	-21.9	>20
BT	78	2480	- - -	- - -	PEAK	100	-1.9	-21.9	>20

Remark: No peaks closer 20 dB to the limit were found.
 Please see next sub-clause for the measurement plot.

4.3.4 MEASUREMENT PLOT (SHOWING THE HIGHEST VALUE, "WORST CASE")

Radio Technology = Bluetooth EDR 3, Operating Frequency = mid



Title: spurious emissions
Comment A: CH M: 2441 MHz
Date: 18.NOV.2016 11:17:39

BT only module

4.3.5 TEST EQUIPMENT USED

Regulatory Bluetooth RF Test Solution

4.4 TRANSMITTER SPURIOUS RADIATED EMISSIONS

Standard **FCC Part 15 Subpart C**

The test was performed according to:
ANSI C63.10

4.4.1 TEST DESCRIPTION

The test set-up was made in accordance to the general provisions of ANSI C63.10 in a typical installation configuration. The Equipment Under Test (EUT) was set up on a non-conductive table 1.0 x 2.0 m² in the semi-anechoic chamber. The influence of the EUT support table that is used between 30–1000 MHz was evaluated.

The measurement procedure is implemented into the EMI test software EMC32 from R&S. Exploratory tests are performed at 3 orthogonal axes to determine the worst-case orientation of a body-worn or handheld EUT. The final test on all kind of EUTs is also performed at 3 axes. A pre-check is performed while the EUT is powered from a DC power source.

1. Measurement up to 30 MHz

The Loop antenna HFH2-Z2 is used.

Step 1: pre measurement

- Anechoic chamber
- Antenna distance: 3 m
- Detector: Peak-Maxhold
- Frequency range: 0.009 - 0.15 MHz and 0.15 - 30 MHz
- Frequency steps: 0.05 kHz and 2.25 kHz
- IF-Bandwidth: 0.2 kHz and 9 kHz
- Measuring time / Frequency step: 100 ms (FFT-based)

Intention of this step is, to determine the radiated EMI-profile of the EUT. Afterwards the relevant emissions for the final measurement are identified.

Step 2: final measurement

For the relevant emissions determined in step 1, an additional measurement with the following settings will be performed. Intention of this step is to find the maximum emission level.

- Open area test side
- Antenna distance: according to the Standard
- Detector: Quasi-Peak
- Frequency range: 0.009 - 30 MHz
- Frequency steps: measurement at frequencies detected in step 1
- IF-Bandwidth: 0.2 - 10 kHz
- Measuring time / Frequency step: 1 s

2. Measurement above 30 MHz and up to 1 GHz

Step 1: Preliminary scan

This is a preliminary test to identify the highest amplitudes relative to the limit.

Settings for step 1:

- Antenna distance: 3 m
- Detector: Peak-Maxhold / Quasipeak (FFT-based)
- Frequency range: 30 - 1000 MHz

- Frequency steps: 30 kHz
- IF-Bandwidth: 120 kHz
- Measuring time / Frequency step: 100 ms
- Turntable angle range: -180° to 90°
- Turntable step size: 90°
- Height variation range: 1 – 3 m
- Height variation step size: 2 m
- Polarisation: Horizontal + Vertical

Intention of this step is, to determine the radiated EMI-profile of the EUT. Afterwards the relevant emissions for the final measurement are identified.

Step 2: Adjustment measurement

In this step the accuracy of the turntable azimuth and antenna height will be improved. This is necessary to find out the maximum value of every frequency.

For each frequency, which was determined the turntable azimuth and antenna height will be adjusted. The turntable azimuth will slowly vary by $\pm 45^{\circ}$ around this value. During this action, the value of emission is continuously measured. The turntable azimuth at the highest emission will be recorded and adjusted. In this position, the antenna height will also slowly vary by ± 100 cm around the antenna height determined. During this action, the value of emission is also continuously measured. The antenna height of the highest emission will also be recorded and adjusted.

- Detector: Peak – Maxhold
- Measured frequencies: in step 1 determined frequencies
- IF – Bandwidth: 120 kHz
- Measuring time: 100 ms
- Turntable angle range: $\pm 45^{\circ}$ around the determined value
- Height variation range: ± 100 cm around the determined value
- Antenna Polarisation: max. value determined in step 1

Step 3: Final measurement with QP detector

With the settings determined in step 3, the final measurement will be performed:

EMI receiver settings for step 4:

- Detector: Quasi-Peak (< 1 GHz)
- Measured frequencies: in step 1 determined frequencies
- IF – Bandwidth: 120 kHz
- Measuring time: 1 s

After the measurement a plot will be generated which contains a diagram with the results of the preliminary scan and a chart with the frequencies and values of the results of the final measurement.

3. Measurement above 1 GHz

The following modifications apply to the measurement procedure for the frequency range above 1 GHz:

Step 1:

The Equipment Under Test (EUT) was set up on a non-conductive support (tilt device) at 1.5 m height in the fully-anechoic chamber.

All steps were performed with one height (1.5 m) of the receiving antenna only.

The EUT is turned during the preliminary measurement across the elevation axis, with a step size of 90° .

The turn table step size (azimuth angle) for the preliminary measurement is 45° .

Step 2:

Due to the fact, that in this frequency range the test is performed in a fully anechoic room, the height scan of the receiving antenna instep 2 is omitted. Instead of this, a maximum search with a step size $\pm 45^{\circ}$ for the elevation axis is performed.

The turn table azimuth will slowly vary by $\pm 22.5^\circ$.

The elevation angle will slowly vary by $\pm 45^\circ$

EMI receiver settings (for all steps):

- Detector: Peak, Average
- IF Bandwidth = 1 MHz

Step 3:

Spectrum analyser settings for step 3:

- Detector: Peak / Average
- Measured frequencies: in step 1 determined frequencies
- IF – Bandwidth: 1 MHz
- Measuring time: 1 s

4.4.2 TEST REQUIREMENTS / LIMITS

FCC Part 15, Subpart C, §15.247 (d)

... In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

FCC Part 15, Subpart C, §15.209, Radiated Emission Limits

Frequency in MHz	Limit ($\mu\text{V}/\text{m}$)	Measurement distance (m)	Limits ($\text{dB}\mu\text{V}/\text{m}$)
0.009 – 0.49	2400/F(kHz)@300m	3	(48.5 – 13.8)@300m
0.49 – 1.705	24000/F(kHz)@30m	3	(33.8 – 23.0)@30m
1.705 – 30	30@30m	3	29.5@30m

The measured values are corrected with an inverse linear distance extrapolation factor (40 dB/decade) according FCC 15.31 (2).

Frequency in MHz	Limit ($\mu\text{V}/\text{m}$)	Measurement distance (m)	Limits ($\text{dB}\mu\text{V}/\text{m}$)
30 – 88	100@3m	3	40.0@3m
88 – 216	150@3m	3	43.5@3m
216 – 960	200@3m	3	46.0@3m
960 – 26000	500@3m	3	54.0@3m
26000 – 40000	500@3m	1	54.0@3m

The measured values above 26 GHz are corrected with an inverse linear distance extrapolation factor (20 dB/decade).

§15.35(b) ..., there is also a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit....

Used conversion factor: $\text{Limit (dB}\mu\text{V}/\text{m)} = 20 \log (\text{Limit } (\mu\text{V}/\text{m})/1\mu\text{V}/\text{m})$

4.4.3 TEST PROTOCOL

Ambient temperature: 22-24 °C
 Air Pressure: 989-1015 hPa
 Humidity: 39-43 %
 BT GFSK (1-DH1)

Module	Ch. Center Freq. [MHz]	Spurious Freq. [MHz]	Spurious Level [dBμV/m]	Detector	RBW [kHz]	Limit [dBμV/m]	Margin to Limit [dB]	Limit Type
Setup S01 AF01 (Hardware HW 502)								
BT/WLAN	2402	---	---	---	---	---	---	RB
BT	2402	---	---	---	---	---	---	RB
BT/WLAN	2441	---	---	---	---	---	---	RB
BT	2441	---	---	---	---	---	---	RB
BT/WLAN	2480	---	---	---	---	---	---	RB
BT	2480	---	---	---	---	---	---	RB
Setup S01 AN01 (Hardware HW 602)								
BT	2480	---	---	---	---	---	---	RB

BT π/4 DQPSK (2-DH1)

Module	Ch. Center Freq. [MHz]	Spurious Freq. [MHz]	Spurious Level [dBμV/m]	Detector	RBW [kHz]	Limit [dBμV/m]	Margin to Limit [dB]	Limit Type
Setup S01 AF01 (Hardware HW 502)								
BT/WLAN	2402	---	---	---	---	---	---	RB
BT	2402	---	---	---	---	---	---	RB
BT/WLAN	2441	---	---	---	---	---	---	RB
BT	2441	---	---	---	---	---	---	RB
BT/WLAN	2480	---	---	---	---	---	---	RB
BT	2480	---	---	---	---	---	---	RB

BT 8-DPSK (3-DH1)


Module	Ch. Center Freq. [MHz]	Spurious Freq. [MHz]	Spurious Level [dBμV/m]	Detector	RBW [kHz]	Limit [dBμV/m]	Margin to Limit [dB]	Limit Type
Setup S01 AF01 (Hardware HW 502)								
BT/WLAN	2402	---	---	---	---	---	---	RB
BT	2402	---	---	---	---	---	---	RB
BT/WLAN	2441	---	---	---	---	---	---	RB
BT	2441	---	---	---	---	---	---	RB
BT/WLAN	2480	---	---	---	---	---	---	RB
BT	2480	---	---	---	---	---	---	RB
Setup S01 AN01 (Hardware HW 602)								
BT/WLAN	2480	---	---	---	---	---	---	RB

Remark: Peaks with a peak detector value more than 20dB from the limit (10 dB for range up to 1GHz) may not be listed in the table above.
 Please see next sub-clause for the measurement plot.

4.4.4 MEASUREMENT PLOT (SHOWING THE HIGHEST VALUE, "WORST CASE")

Radio Technology = Bluetooth BDR, Operating Frequency = low, Measurement range = 1 GHz - 8 GHz


Setup S01_AF01:



BT + WLAN module

Radio Technology = Bluetooth EDR 3, Operating Frequency = low, Measurement range = 1 GHz - 26 GHz


Setup S01_AF01:



BT + WLAN module

Radio Technology = Bluetooth EDR 3, Operating Frequency = high, Measurement range = 1 GHz - 26 GHz

Setup S01_AN01:




Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	CAverage (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Elevation (deg)
1006.000000	---	31.12	54.00	22.88	1000.0	1000.000	150.0	V	-96.0	74.8
1008.040000	50.37	---	74.00	23.63	1000.0	1000.000	150.0	H	-89.0	74.9
2483.582500	---	36.57	54.00	17.43	1000.0	1000.000	150.0	V	26.0	13.1
2483.665000	50.03	---	74.00	23.98	1000.0	1000.000	150.0	V	-49.0	-11.9


Radio Technology = Bluetooth BDR, Operating Frequency = mid, Measurement range = 30 MHz - 1 GHz

Setup S01_AF01:




BT only Module

Setup S01_AN01:



BT only Module

Radio Technology = Bluetooth BDR, Operating Frequency = mid, Measurement range = 9 kHz - 30 MHz



BT only module

4.4.5 TEST EQUIPMENT USED

Radiated Emissions

4.5 BAND EDGE COMPLIANCE CONDUCTED

Standard **FCC Part 15 Subpart C**

The test was performed according to:
ANSI C63.10

4.5.1 TEST DESCRIPTION

For the conducted measurement, the Equipment Under Test (EUT) is placed in a shielded room. The reference power was measured in the test case "Spurious RF Conducted Emissions". The EUT was connected to the spectrum analyzer via a short coax cable with a known loss.

Analyzer settings:

- Frequency Range 2397 MHz – 2403 MHz and 2479 MHz – 2485 MHz
- Detector: Peak
- Resolution Bandwidth (RBW): 100 kHz
- Video Bandwidth (VBW): 300 kHz
- Sweptime: coupled
- Trace: Maxhold

4.5.2 TEST REQUIREMENTS / LIMITS

FCC Part 15.247 (d)

"In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. ...

If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c))."

For the conducted measurement the RF power at the band edge shall be "at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power..."

4.5.3 TEST PROTOCOL

Ambient temperature: 23°C
 Air Pressure: 1017hPa
 Humidity: 43%
 BT GFSK (1-DH1)

Module	Channel No.	Channel Center Frequency [MHz]	Band Edge Freq. [MHz]	Spurious Level [dBm]	Detector	RBW [kHz]	Ref. Level [dBm]	Limit [dBm]	Margin to Limit [dB]
BT/WLAN	0	2402	2400.0	-62.4	PEAK	100	-2.3	-22.3	40.1
BT	0	2402	2400.0	-52.2	PEAK	100	-2.3	-22.3	29.9
BT/WLAN	78	2480	2483.5	-63.0	PEAK	100	-2.5	-22.5	40.4
BT	78	2480	2483.5	-63.1	PEAK	100	-2.5	-22.5	40.6
BT/WLAN	hopping	hopping	2400.0	-56.9	PEAK	100	-1.9	-21.9	35.0
BT	hopping	hopping	2400.0	-52.1	PEAK	100	-1.9	-21.9	30.2
BT/WLAN	hopping	hopping	2483.5	-55.9	PEAK	100	-1.6	-21.6	34.3
BT	hopping	hopping	2483.5	-62.7	PEAK	100	-1.6	-21.6	41.1

BT π/4 QPSK (2-DH1)

Module	Channel No.	Channel Center Frequency [MHz]	Band Edge Freq. [MHz]	Spurious Level [dBm]	Detector	RBW [kHz]	Ref. Level [dBm]	Limit [dBm]	Margin to Limit [dB]
BT/WLAN	0	2402	2400.0	-57.9	PEAK	100	-2.2	-22.2	35.7
BT	0	2402	2400.0	-42.9	PEAK	100	-2.2	-22.2	20.8
BT/WLAN	78	2480	2483.5	-63.2	PEAK	100	-1.6	-21.6	41.6
BT	78	2480	2483.5	-64.0	PEAK	100	-1.6	-21.6	42.4
BT/WLAN	hopping	hopping	2400.0	-57.3	PEAK	100	-1.8	-21.8	35.5
BT	hopping	hopping	2400.0	-44.3	PEAK	100	-1.8	-21.8	22.5
BT/WLAN	hopping	hopping	2483.5	-60.8	PEAK	100	-1.4	-21.4	39.4
BT	hopping	hopping	2483.5	-62.0	PEAK	100	-1.4	-21.4	40.6


BT 8-DPSK (3-DH1)

Module	Channel No.	Channel Center Frequency [MHz]	Band Edge Freq. [MHz]	Spurious Level [dBm]	Detector	RBW [kHz]	Ref. Level [dBm]	Limit [dBm]	Margin to Limit [dB]
BT/WLAN	0	2402	2400.0	-54.6	PEAK	100	-2.3	-22.3	32.4
BT	0	2402	2400.0	-43.0	PEAK	100	-2.3	-22.3	20.8
BT/WLAN	78	2480	2483.5	-60.0	PEAK	100	-1.6	-21.6	38.4
BT	78	2480	2483.5	-62.9	PEAK	100	-1.6	-21.6	41.3
BT/WLAN	hopping	hopping	2400.0	-54.9	PEAK	100	-1.9	-21.9	33.0
BT	hopping	hopping	2400.0	-43.3	PEAK	100	-1.9	-21.9	21.4
BT/WLAN	hopping	hopping	2483.5	-59.5	PEAK	100	-1.6	-21.6	37.9
BT	hopping	hopping	2483.5	-61.3	PEAK	100	-1.6	-21.6	39.7


Remark: Please see next sub-clause for the measurement plot.

4.5.4 MEASUREMENT PLOT (SHOWING THE HIGHEST VALUE, "WORST CASE")

Radio Technology = Bluetooth EDR 3, Operating Frequency = low, Band Edge = low



Radio Technology = Bluetooth EDR 3, Operating Frequency = hopping, Band Edge = low



4.5.5 TEST EQUIPMENT USED

Regulatory Bluetooth RF Test Solution

4.6 BAND EDGE COMPLIANCE RADIATED

Standard **FCC Part 15 Subpart C**

The test was performed according to:
ANSI C63.10

4.6.1 TEST DESCRIPTION

Please see test description for the test case "Spurious Radiated Emissions"

4.6.2 TEST REQUIREMENTS / LIMITS

For band edges connected to a restricted band, the limits are specified in Section 15.209(a)

FCC Part 15, Subpart C, §15.209, Radiated Emission Limits

Frequency in MHz	Limit (µV/m)	Measurement distance (m)	Limits (dBµV/m)
0.009 – 0.49	2400/F(kHz)@300m	3	(48.5 – 13.8)@300m
0.49 – 1.705	24000/F(kHz)@30m	3	(33.8 – 23.0)@30m
1.705 – 30	30@30m	3	29.5@30m

The measured values are corrected with an inverse linear distance extrapolation factor (40 dB/decade) according FCC 15.31 (2).

Frequency in MHz	Limit (µV/m)	Measurement distance (m)	Limits (dBµV/m)
30 – 88	100@3m	3	40.0@3m
88 – 216	150@3m	3	43.5@3m
216 – 960	200@3m	3	46.0@3m
960 – 26000	500@3m	3	54.0@3m
26000 – 40000	500@3m	1	54.0@3m

The measured values above 26 GHz are corrected with an inverse linear distance extrapolation factor (20 dB/decade).

§15.35(b) ..., there is also a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit....

Used conversion factor: $\text{Limit (dBµV/m)} = 20 \log (\text{Limit (µV/m)}/1\mu\text{V/m})$

4.6.3 TEST PROTOCOL

Ambient temperature: 22-24 °C
 Air Pressure: 989-1015 hPa
 Humidity: 39-43 %
 BT GFSK (1-DH1)

Module	Ch. Center Freq. [MHz]	Band Edge Freq. [MHz]	Spurious Level [dBμV/m]	Detector	RBW [kHz]	Limit [dBμV/m]	Margin to Limit [dB]	Limit Type
Setup S01 AF01 (Hardware HW 502)								
BT/WLAN	2480	2483.5	49.5	PEAK	1000	74.0	24.5	BE
BT/WLAN	2480	2483.5	46.7	AV	1000	54.0	7.3	BE
BT	2480	2483.5	50.3	PEAK	1000	74.0	23.7	BE
BT	2480	2483.5	46.6	AV	1000	54.0	7.4	BE
Setup S01 AN01 (Hardware HW 602)								
BT/WLAN	2480	2483.5	49.1	PEAK	1000	74.0	24.9	BE
BT/WLAN	2480	2483.5	46.7	AV	1000	54.0	7.3	BE
BT	2480	2483.5	50.3	PEAK	1000	74.0	23.7	BE
BT	2480	2483.5	46.8	AV	1000	54.0	7.2	BE

BT n/4 DQPSK (2-DH1)

Module	Ch. Center Freq. [MHz]	Band Edge Freq. [MHz]	Spurious Level [dBμV/m]	Detector	RBW [kHz]	Limit [dBμV/m]	Margin to Limit [dB]	Limit Type
Setup S01 AF01 (Hardware HW 502)								
BT/WLAN	2480	2483.5	49.2	PEAK	1000	74.0	24.8	BE
BT/WLAN	2480	2483.5	46.7	AV	1000	54.0	7.3	BE
BT	2480	2483.5	49.4	PEAK	1000	74.0	24.6	BE
BT	2480	2483.5	46.7	AV	1000	54.0	7.3	BE
Setup S01 AN01 (Hardware HW 602)								
BT/WLAN	2480	2483.5	49.6	PEAK	1000	74.0	24.4	BE
BT/WLAN	2480	2483.5	46.8	AV	1000	54.0	7.2	BE
BT	2480	2483.5	49.5	PEAK	1000	74.0	24.5	BE
BT	2480	2483.5	46.8	AV	1000	54.0	7.2	BE

BT 8-DPSK (3-DH1)

Module	Ch. Center Freq. [MHz]	Band Edge Freq. [MHz]	Spurious Level [dBμV/m]	Detector	RBW [kHz]	Limit [dBμV/m]	Margin to Limit [dB]	Limit Type
Setup S01 AF01 (Hardware HW 502)								
BT/WLAN	2480	2483.5	49.8	PEAK	1000	74.0	24.2	BE
BT/WLAN	2480	2483.5	46.7	AV	1000	54.0	7.3	BE
BT	2480	2483.5	49.7	PEAK	1000	74.0	24.3	BE
BT	2480	2483.5	46.7	AV	1000	54.0	7.3	BE
Setup S01 AN01 (Hardware HW 602)								
BT/WLAN	2480	2483.5	50.0	PEAK	1000	74.0	24.0	BE
BT/WLAN	2480	2483.5	46.7	AV	1000	54.0	7.3	BE
BT	2480	2483.5	51.1	PEAK	1000	74.0	22.9	BE
BT	2480	2483.5	46.8	AV	1000	54.0	7.2	BE


Remark: Applied duty cycle correction (AV) [dB]:10.1

For the "lower band edge" (nearest, lower restricted band to the 2.4 GHz ISM band) the measurement values are reported in section 4.5 "TRANSMITTER SPURIOUS RADIATED EMISSIONS" in case that the margin to the compliance limit is less than 20 dB.

Please see next sub-clause for the measurement plot.

4.6.4 MEASUREMENT PLOT (SHOWING THE HIGHEST VALUE, "WORST CASE")

Radio Technology = Bluetooth BDR, Operating Frequency = high, Band Edge = high
Setup S01_AF01:




Final Result

Frequency (MHz)	MaxPeak (dBµV/m)	CAverage (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Elevation (deg)
2483.830000	---	36.51	54.00	17.49	1000.0	1000.000	150.0	H	128.0	104.0
2483.830000	50.31	---	74.00	23.69	1000.0	1000.000	150.0	V	142.0	77.0

BT only module

Radio Technology = Bluetooth EDR 3, Operating Frequency = high, Band Edge = high
Setup S01_AN01:



Final Result

Frequency (MHz)	MaxPeak (dBµV/m)	CAverage (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Elevation (deg)
2483.510000	---	36.69	---	---	1000.0	1000.000	150.0	H	123.0	86.0
2483.510000	51.07	---	74.00	22.93	1000.0	1000.000	150.0	H	-157.0	104.9

4.6.5 TEST EQUIPMENT USED

Radiated Emissions

4.7 CHANNEL SEPARATION

Standard **FCC Part 15 Subpart C**

The test was performed according to:
ANSI C63.10

4.7.1 TEST DESCRIPTION

The Equipment Under Test (EUT) was set up to perform the channel separation measurements. The channel separation is independent from the modulation pattern.

The EUT was connected to the spectrum analyzer via a short coax cable with a known loss.

Analyzer settings:

- Detector: Peak
- Trace: Maxhold
- Span: appr. 3 x OBW
- Centre Frequency: a mid frequency of the used band
- Resolution Bandwidth (RBW): appr. 3 % of channel spacing
- Video Bandwidth (VBW): 3 x RBW
- Sweep Time: 5 ms
- Sweeps: 2000

The technology depending measurement parameters can be found in the measurement plot.

4.7.2 TEST REQUIREMENTS / LIMITS

FCC Part 15, Subpart C, §15.247 (a) (1)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

4.7.3 TEST PROTOCOL


Ambient temperature: 23°C
Air Pressure: 1017hPa
Humidity: 43%

Module	Radio Technology	Channel Separation [kHz]	Limit [kHz]	Margin to Limit [kHz]
BT/WLAN	BT GFSK (1-DH1)	1000.0	697.600	302.400
BT	BT GFSK (1-DH1)	1000.0	701.600	298.400

Remark: Please see next sub-clause for the measurement plot.

4.7.4 MEASUREMENT PLOT (SHOWING THE HIGHEST VALUE, "WORST CASE")

Radio Technology = Bluetooth BDR



Title: Channel separation
Comment A: CH H: Hopping
Date: 17.NOV.2016 13:12:21
BT only module

4.7.5 TEST EQUIPMENT USED

Regulatory Bluetooth RF Test Solution

4.8 DWELL TIME

Standard **FCC Part 15 Subpart C**

The test was performed according to:
ANSI C63.10

4.8.1 TEST DESCRIPTION

The Equipment Under Test (EUT) was set up to perform the dwell time measurements. The dwell time is independent from the modulation pattern. The dwell time is calculated by:

The EUT was connected to the spectrum analyzer via a short coax cable with a known loss.

Dwell time = time slot length * hop rate / number of hopping channels * 31.6 s

with:

- hop rate = $1600 * 1/s$ for DH1 packets = $1600 s^{-1}$
- hop rate = $1600/3 * 1/s$ for DH3 packets = $533.33 s^{-1}$
- hop rate = $1600/5 * 1/s$ for DH5 packets = $320 s^{-1}$
- number of hopping channels = 79
- $31.6 s = 0.4$ seconds multiplied by the number of hopping channels = $0.4 s * 79$

The highest value of the dwell time is reported.

Analyzer settings:

- Center Frequency: mid channel frequency
- Span: Zero span
- Detector: Peak
- Trace: Maxhold
- Resolution Bandwidth (RBW): $\leq$ channel separation
- Trigger: Video

4.8.2 TEST REQUIREMENTS / LIMITS

For the band: 902 – 928 MHz
FCC Part 15, Subpart C, §15.247 (a) (1) (i)

If the 20 dB bandwidth of the hopping channel is less than 250 kHz the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period. If the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period.

For the band: 5725 – 5850 MHz
FCC Part 15, Subpart C, §15.247 (a) (1) (ii)

The average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 30 second period.

For the frequency band 2400 – 2483.5 MHz:
FCC Part 15, Subpart C, §15.247 (a) (1) (iii)

...The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Since the Bluetooth technology uses 79 channels this period is calculated to be 31.6 seconds.

4.8.3 TEST PROTOCOL


Ambient temperature: 23°C
Air Pressure: 1017hPa
Humidity: 43%

Module	Radio Technology	Time Slot Length [ms]	Dwell Time [ms]	Limit [s]	Margin to Limit [ms]
BT/WLAN	BT GFSK (1-DH1)	2.9	372.480	0.4	27.5
BT	BT GFSK (1-DH1)	2.9	372.480	0.4	27.5

Remark: Please see next sub-clause for the measurement plot.

4.8.4 MEASUREMENT PLOT (SHOWING THE HIGHEST VALUE, "WORST CASE")

Radio Technology = Bluetooth BDR



Title: Dwell time
Comment A: CH M: 2441 MHz
Date: 18.NOV.2016 10:48:27

BT only module

4.8.5 TEST EQUIPMENT USED

Regulatory Bluetooth RF Test Solution

4.9 NUMBER OF HOPPING FREQUENCIES

Standard **FCC Part 15 Subpart C**

The test was performed according to:
ANSI C63.10

4.9.1 TEST DESCRIPTION

The Equipment Under Test (EUT) was set up to perform the number of hopping frequencies measurement. The number of hopping frequencies is independent from the modulation pattern.

The EUT was connected to the spectrum analyzer via a short coax cable with a known loss.

Analyzer settings:

- Detector: Peak
- Trace: Maxhold
- Centre frequency: 2442 MHz
- Frequency span: Frequency band of operation
- Resolution Bandwidth (RBW): < 30 % of channel spacing or 20 dB bandwidth (whichever is maller)
- Video Bandwidth (VBW): 3 x RBW
- Sweep Time: 5 ms
- Sweeps: 2000

The technology depending measurement parameters can be found in the measurement plot.

4.9.2 TEST REQUIREMENTS / LIMITS

For the band: 902 – 928 MHz
FCC Part 15, Subpart C, §15.247 (a) (1) (i)

If the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies.

If the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies

For the band: 5725 – 5850 MHz
FCC Part 15, Subpart C, §15.247 (a) (1) (ii)

Frequency hopping systems operating in the 5725-5850 MHz band shall use at least 75 hopping frequencies.

For the band: 2400 – 2483.5 MHz
FCC Part 15, Subpart C, §15.247 (a) (1) (iii)

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

4.9.3 TEST PROTOCOL


Ambient temperature: 23°C
 Air Pressure: 1017hPa
 Humidity: 43%

Module	Radio Technology	Number of Hopping Frequencies	Limit	Margin to Limit
BT/WLAN	BT GFSK (1-DH1)	79	15	64
BT	BT GFSK (1-DH1)	79	15	64

Remark: Please see next sub-clause for the measurement plot.

4.9.4 MEASUREMENT PLOT (SHOWING THE HIGHEST VALUE, "WORST CASE")

Radio Technology = Bluetooth BDR



Title: Number of hopping frequencies
 Comment A: CH H: Hopping
 Date: 18.NOV.2016 13:03:51

BT only module

4.9.5 TEST EQUIPMENT USED

Regulatory Bluetooth RF Test Solution

5 TEST EQUIPMENT

- 1 Radiated Emissions
Lab to perform radiated emission tests

Ref.No.	Device Name	Description	Manufacturer	Serial Number	Last Calibration	Calibration Due
1.1	3160-09	Standard Gain / Pyramidal Horn Antenna 26.5 GHz	EMCO Elektronik GmbH	00083069		
1.2	WHKX 7.0/18G-8SS	High Pass Filter	Wainwright	09		
1.3	5HC3500/1800 0-1.2-KK	High Pass Filter	Trilithic	200035008		
1.4	Datum MFS	Rubidium Frequency Normal MFS	Datum GmbH	002	2016-09	2017-09
1.5	Fully Anechoic Room	8.80m x 4.60m x 4.05m (l x w x h)	Albatross Projects	P26971-647-001-PRB		
1.6	AM 4.0	Antenna mast	Maturo GmbH	AM4.0/180/1192 0513		
1.7	ESR 7	EMI Receiver / Spectrum Analyzer	Rohde & Schwarz	101424	2016-11	2018-11
1.8	TT 1.5 WI	Turn Table	Maturo GmbH	-		
1.9	Anechoic Chamber	10.58 x 6.38 x 6.00 m ³	Frankonia	none	2014-01	2017-01
1.10	Fluke 177	Digital Multimeter 03 (Multimeter)	Fluke Europe B.V.	86670383	2016-02	2018-02
1.11	ESIB 26	Spectrum Analyzer	Rohde & Schwarz	830482/004	2015-12	2017-12
1.12	Tilt device Maturo (Rohacell)	Antrieb TD1.5-10kg	Maturo GmbH	TD1.5-10kg/024/37907 09		
1.13	5HC2700/1275 0-1.5-KK	High Pass Filter	Trilithic	9942012		
1.14	AS 620 P	Antenna mast	HD GmbH	620/37		
1.15	NRV-Z1	Sensor Head A	Rohde & Schwarz	827753/005	2016-05	2017-05
1.16	4HC1600/1275 0-1.5-KK	High Pass Filter	Trilithic	9942011		
1.17	ASP 1.2/1.8-10 kg	Antenna Mast	Maturo GmbH	-		

Ref.No.	Device Name	Description	Manufacturer	Serial Number	Last Calibration	Calibration Due
1.18	JS4-18002600-32-5P	Broadband Amplifier 18 GHz - 26 GHz	Miteq	849785		
1.19	JS4-00101800-35-5P	Broadband Amplifier 30 MHz - 18 GHz	Miteq	896037		
1.20	HL 562	Ultralog new biconicals	Rohde & Schwarz	830547/003	2015-06	2018-06
1.21	Opus10 THI (8152.00)	ThermoHygro Datalogger 12 (Environ)	Lufft Mess- und Regeltechnik GmbH	12482	2015-03	2017-03
1.22	JS4-00102600-42-5A	Broadband Amplifier 30 MHz - 26 GHz	Miteq	619368		
1.23	HFH2-Z2	Loop Antenna	Rohde & Schwarz	829324/006	2014-11	2017-11
1.24	FSW 43	Spectrum Analyzer	Rohde & Schwarz	103779	2016-11	2018-11
1.25	Opus10 TPR (8253.00)	ThermoAirpressure Datalogger 13 (Environ)	Lufft Mess- und Regeltechnik GmbH	13936	2015-02	2017-02
1.26	Chroma 6404	AC Power Source	Chroma ATE INC.	64040001304		
1.27	3160-10	Standard Gain / Pyramidal Horn Antenna 40 GHz	EMCO Elektronik GmbH	00086675		
1.28	HL 562 Ultralog	Log.-per. Antenna	Rohde & Schwarz	100609	2016-04	2019-04
1.29	PAS 2.5 - 10 kg	Antenna Mast	Maturo GmbH	-		
1.30	HF 907	Double-ridged horn	Rohde & Schwarz	102444	2015-05	2018-05

2 Regulatory Bluetooth RF Test Solution Regulatory Bluetooth RF Tests

Ref.No.	Device Name	Description	Manufacturer	Serial Number	Last Calibration	Calibration Due
2.1	CBT	IL BT RF Test Solution	Rohde & Schwarz	100302	2016-02	2017-02
2.2	EX520	Digital Multimeter 12 (Multimeter)	Extech Instruments Corp	05157876	2016-02	2018-02
2.3	SMIQ03B	Signal Generator	Rohde & Schwarz	832870/017	2016-06	2019-06

Ref.No.	Device Name	Description	Manufacturer	Serial Number	Last Calibration	Calibration Due
2.4	Datum MFS	Rubidium Frequency Normal MFS	Datum GmbH	002	2016-09	2017-09
2.5	FSIQ26	Signal Analyser	Rohde & Schwarz	832695/007	2016-09	2018-09
2.6	NRVD	Powermeter	Rohde & Schwarz	832025/059	2016-08	2017-08
2.7	TOCT Switching Unit		7layers, Inc.	040107		
2.8	SMP03	Signal Generator 2 GHz - 27 GHz	Rohde & Schwarz	833680/003		
2.9	Opus10 THI (8152.00)	T/H Logger 15	Lufft Mess- und Regeltechnik GmbH	13985	2015-03	2017-03
2.10	NRV Z1 A	Power Sensor	Rohde & Schwarz	832279/013	2016-09	2017-08
2.11	ADU 200 Relay Box 7	used for automated testing (EMMI) only	Ontrak Control Systems Inc	A04380		
2.12	R&S CBT	Bluetooth Signalling Unit	Rohde & Schwarz	100589	2015-01	2018-01
2.13	KWP 120/70	Temperature Chamber Weiss 01	Weiss	59226012190010	2016-03	2018-03
2.14	NGSM 32/10	Power Supply	Rohde & Schwarz	2725	2015-06	2017-06
2.15	SMP02	Signal Generator SMP	Rohde & Schwarz	833286/0014	2016-05	2019-05

The calibration interval is the time interval between "Last Calibration" and "Calibration Due"

6 ANTENNA FACTORS, CABLE LOSS AND SAMPLE CALCULATIONS

This chapter contains the antenna factors with their corresponding path loss of the used measurement path for all antennas as well as the insertion loss of the LISN.

6.1 LISN R&S ESH3-Z5 (150 KHZ – 30 MHZ)

Frequency		Corr.	LISN insertion loss ESH3- Z5	cable loss (incl. 10 dB atten- uator)
MHz		dB	dB	dB
0.15		10.1	0.1	10.0
5		10.3	0.1	10.2
7		10.5	0.2	10.3
10		10.5	0.2	10.3
12		10.7	0.3	10.4
14		10.7	0.3	10.4
16		10.8	0.4	10.4
18		10.9	0.4	10.5
20		10.9	0.4	10.5
22		11.1	0.5	10.6
24		11.1	0.5	10.6
26		11.2	0.5	10.7
28		11.2	0.5	10.7
30		11.3	0.5	10.8

Sample calculation

$$U_{\text{LISN}} (\text{dB } \mu\text{V}) = U (\text{dB } \mu\text{V}) + \text{Corr. (dB)}$$

U = Receiver reading

LISN Insertion loss = Voltage Division Factor of LISN

Corr. = sum of single correction factors of used LISN, cables, switch units (if used)

Linear interpolation will be used for frequencies in between the values in the table.

6.2 ANTENNA R&S HFH2-Z2 (9 KHZ – 30 MHZ)

Frequency MHz	AF HFH-Z2) dB (1/m)	Corr. dB	cable loss 1 (inside chamber) dB	cable loss 2 (outside chamber) dB	cable loss 3 (switch unit) dB	cable loss 4 (to receiver) dB	distance corr. (-40 dB/ decade) dB	d _{Limit} (meas. distance (limit) m	d _{used} (meas. distance (used) m
0.009	20.50	-79.6	0.1	0.1	0.1	0.1	-80	300	3
0.01	20.45	-79.6	0.1	0.1	0.1	0.1	-80	300	3
0.015	20.37	-79.6	0.1	0.1	0.1	0.1	-80	300	3
0.02	20.36	-79.6	0.1	0.1	0.1	0.1	-80	300	3
0.025	20.38	-79.6	0.1	0.1	0.1	0.1	-80	300	3
0.03	20.32	-79.6	0.1	0.1	0.1	0.1	-80	300	3
0.05	20.35	-79.6	0.1	0.1	0.1	0.1	-80	300	3
0.08	20.30	-79.6	0.1	0.1	0.1	0.1	-80	300	3
0.1	20.20	-79.6	0.1	0.1	0.1	0.1	-80	300	3
0.2	20.17	-79.6	0.1	0.1	0.1	0.1	-80	300	3
0.3	20.14	-79.6	0.1	0.1	0.1	0.1	-80	300	3
0.49	20.12	-79.6	0.1	0.1	0.1	0.1	-80	300	3
0.490001	20.12	-39.6	0.1	0.1	0.1	0.1	-40	30	3
0.5	20.11	-39.6	0.1	0.1	0.1	0.1	-40	30	3
0.8	20.10	-39.6	0.1	0.1	0.1	0.1	-40	30	3
1	20.09	-39.6	0.1	0.1	0.1	0.1	-40	30	3
2	20.08	-39.6	0.1	0.1	0.1	0.1	-40	30	3
3	20.06	-39.6	0.1	0.1	0.1	0.1	-40	30	3
4	20.05	-39.5	0.2	0.1	0.1	0.1	-40	30	3
5	20.05	-39.5	0.2	0.1	0.1	0.1	-40	30	3
6	20.02	-39.5	0.2	0.1	0.1	0.1	-40	30	3
8	19.95	-39.5	0.2	0.1	0.1	0.1	-40	30	3
10	19.83	-39.4	0.2	0.1	0.2	0.1	-40	30	3
12	19.71	-39.4	0.2	0.1	0.2	0.1	-40	30	3
14	19.54	-39.4	0.2	0.1	0.2	0.1	-40	30	3
16	19.53	-39.3	0.3	0.1	0.2	0.1	-40	30	3
18	19.50	-39.3	0.3	0.1	0.2	0.1	-40	30	3
20	19.57	-39.3	0.3	0.1	0.2	0.1	-40	30	3
22	19.61	-39.3	0.3	0.1	0.2	0.1	-40	30	3
24	19.61	-39.3	0.3	0.1	0.2	0.1	-40	30	3
26	19.54	-39.3	0.3	0.1	0.2	0.1	-40	30	3
28	19.46	-39.2	0.3	0.1	0.3	0.1	-40	30	3
30	19.73	-39.1	0.4	0.1	0.3	0.1	-40	30	3

Sample calculation

$E \text{ (dB } \mu\text{V/m)} = U \text{ (dB } \mu\text{V)} + AF \text{ (dB 1/m)} + Corr. \text{ (dB)}$

U = Receiver reading

AF = Antenna factor

Corr. = sum of single correction factors of used cables, switch unit, distance correction, amplifier (if applicable)

distance correction = $-40 * \text{LOG} (d_{\text{Limit}} / d_{\text{used}})$

Linear interpolation will be used for frequencies in between the values in the table.

Table shows an extract of values

6.3 ANTENNA R&S HL562 (30 MHz – 1 GHz)

($d_{\text{Limit}} = 3 \text{ m}$)

Frequency	AF R&S HL562	Corr.
MHz	dB (1/m)	dB
30	18.6	0.6
50	6.0	0.9
100	9.7	1.2
150	7.9	1.6
200	7.6	1.9
250	9.5	2.1
300	11.0	2.3
350	12.4	2.6
400	13.6	2.9
450	14.7	3.1
500	15.6	3.2
550	16.3	3.5
600	17.2	3.5
650	18.1	3.6
700	18.5	3.6
750	19.1	4.1
800	19.6	4.1
850	20.1	4.4
900	20.8	4.7
950	21.1	4.8
1000	21.6	4.9

cable loss 1 (inside chamber)	cable loss 2 (outside chamber)	cable loss 3 (switch unit)	cable loss 4 (to receiver)	distance corr. (-20 dB/ decade)	d_{Limit} (meas. distance (limit))	d_{used} (meas. distance (used))
dB	dB	dB	dB	dB	m	m
0.29	0.04	0.23	0.02	0.0	3	3
0.39	0.09	0.32	0.08	0.0	3	3
0.56	0.14	0.47	0.08	0.0	3	3
0.73	0.20	0.59	0.12	0.0	3	3
0.84	0.21	0.70	0.11	0.0	3	3
0.98	0.24	0.80	0.13	0.0	3	3
1.04	0.26	0.89	0.15	0.0	3	3
1.18	0.31	0.96	0.13	0.0	3	3
1.28	0.35	1.03	0.19	0.0	3	3
1.39	0.38	1.11	0.22	0.0	3	3
1.44	0.39	1.20	0.19	0.0	3	3
1.55	0.46	1.24	0.23	0.0	3	3
1.59	0.43	1.29	0.23	0.0	3	3
1.67	0.34	1.35	0.22	0.0	3	3
1.67	0.42	1.41	0.15	0.0	3	3
1.87	0.54	1.46	0.25	0.0	3	3
1.90	0.46	1.51	0.25	0.0	3	3
1.99	0.60	1.56	0.27	0.0	3	3
2.14	0.60	1.63	0.29	0.0	3	3
2.22	0.60	1.66	0.33	0.0	3	3
2.23	0.61	1.71	0.30	0.0	3	3

($d_{\text{Limit}} = 10 \text{ m}$)

30	18.6	-9.9
50	6.0	-9.6
100	9.7	-9.2
150	7.9	-8.8
200	7.6	-8.6
250	9.5	-8.3
300	11.0	-8.1
350	12.4	-7.9
400	13.6	-7.6
450	14.7	-7.4
500	15.6	-7.2
550	16.3	-7.0
600	17.2	-6.9
650	18.1	-6.9
700	18.5	-6.8
750	19.1	-6.3
800	19.6	-6.3
850	20.1	-6.0
900	20.8	-5.8
950	21.1	-5.6
1000	21.6	-5.6

0.29	0.04	0.23	0.02	-10.5	10	3
0.39	0.09	0.32	0.08	-10.5	10	3
0.56	0.14	0.47	0.08	-10.5	10	3
0.73	0.20	0.59	0.12	-10.5	10	3
0.84	0.21	0.70	0.11	-10.5	10	3
0.98	0.24	0.80	0.13	-10.5	10	3
1.04	0.26	0.89	0.15	-10.5	10	3
1.18	0.31	0.96	0.13	-10.5	10	3
1.28	0.35	1.03	0.19	-10.5	10	3
1.39	0.38	1.11	0.22	-10.5	10	3
1.44	0.39	1.20	0.19	-10.5	10	3
1.55	0.46	1.24	0.23	-10.5	10	3
1.59	0.43	1.29	0.23	-10.5	10	3
1.67	0.34	1.35	0.22	-10.5	10	3
1.67	0.42	1.41	0.15	-10.5	10	3
1.87	0.54	1.46	0.25	-10.5	10	3
1.90	0.46	1.51	0.25	-10.5	10	3
1.99	0.60	1.56	0.27	-10.5	10	3
2.14	0.60	1.63	0.29	-10.5	10	3
2.22	0.60	1.66	0.33	-10.5	10	3
2.23	0.61	1.71	0.30	-10.5	10	3

Sample calculation

$E \text{ (dB } \mu\text{V/m)} = U \text{ (dB } \mu\text{V)} + AF \text{ (dB 1/m)} + \text{Corr. (dB)}$

U = Receiver reading

AF = Antenna factor

Corr. = sum of single correction factors of used cables, switch unit, distance correction, amplifier (if applicable)

distance correction = $-20 * \text{LOG} (d_{\text{Limit}} / d_{\text{used}})$

Linear interpolation will be used for frequencies in between the values in the table.

Tables show an extract of values.

6.4 ANTENNA R&S HF907 (1 GHZ – 18 GHZ)

Frequency	AF R&S HF907	Corr.
MHz	dB (1/m)	dB
1000	24.4	-19.4
2000	28.5	-17.4
3000	31.0	-16.1
4000	33.1	-14.7
5000	34.4	-13.7
6000	34.7	-12.7
7000	35.6	-11.0

cable loss 1 (relay + cable inside chamber)	cable loss 2 (outside chamber)	cable loss 3 (switch unit, atten- uator & pre-amp)	cable loss 4 (to receiver)		
dB	dB	dB	dB		
0.99	0.31	-21.51	0.79		
1.44	0.44	-20.63	1.38		
1.87	0.53	-19.85	1.33		
2.41	0.67	-19.13	1.31		
2.78	0.86	-18.71	1.40		
2.74	0.90	-17.83	1.47		
2.82	0.86	-16.19	1.46		

Frequency	AF R&S HF907	Corr.
MHz	dB (1/m)	dB
3000	31.0	-23.4
4000	33.1	-23.3
5000	34.4	-21.7
6000	34.7	-21.2
7000	35.6	-19.8

cable loss 1 (relay inside chamber)	cable loss 2 (inside chamber)	cable loss 3 (outside chamber)	cable loss 4 (switch unit, atten- uator & pre-amp)	cable loss 5 (to receiver)	used for FCC 15.247
dB	dB	dB	dB	dB	
0.47	1.87	0.53	-27.58	1.33	
0.56	2.41	0.67	-28.23	1.31	
0.61	2.78	0.86	-27.35	1.40	
0.58	2.74	0.90	-26.89	1.47	
0.66	2.82	0.86	-25.58	1.46	

Frequency	AF R&S HF907	Corr.
MHz	dB (1/m)	dB
7000	35.6	-57.3
8000	36.3	-56.3
9000	37.1	-55.3
10000	37.5	-56.2
11000	37.5	-55.3
12000	37.6	-53.7
13000	38.2	-53.5
14000	39.9	-56.3
15000	40.9	-54.1
16000	41.3	-54.1
17000	42.8	-54.4
18000	44.2	-54.7

cable loss 1 (relay inside chamber)	cable loss 2 (High Pass)	cable loss 3 (pre- amp)	cable loss 4 (inside chamber)	cable loss 5 (outside chamber)	cable loss 6 (to receiver)
dB	dB	dB	dB	dB	dB
0.56	1.28	-62.72	2.66	0.94	1.46
0.69	0.71	-61.49	2.84	1.00	1.53
0.68	0.65	-60.80	3.06	1.09	1.60
0.70	0.54	-61.91	3.28	1.20	1.67
0.80	0.61	-61.40	3.43	1.27	1.70
0.84	0.42	-59.70	3.53	1.26	1.73
0.83	0.44	-59.81	3.75	1.32	1.83
0.91	0.53	-63.03	3.91	1.40	1.77
0.98	0.54	-61.05	4.02	1.44	1.83
1.23	0.49	-61.51	4.17	1.51	1.85
1.36	0.76	-62.36	4.34	1.53	2.00
1.70	0.53	-62.88	4.41	1.55	1.91

Sample calculation

$E \text{ (dB } \mu\text{V/m)} = U \text{ (dB } \mu\text{V)} + AF \text{ (dB 1/m)} + Corr. \text{ (dB)}$

U = Receiver reading

AF = Antenna factor

Corr. = sum of single correction factors of used cables, switch unit, distance correction, amplifier (if applicable)

Linear interpolation will be used for frequencies in between the values in the table.

Tables show an extract of values.

6.5 ANTENNA EMCO 3160-09 (18 GHZ – 26.5 GHZ)

Frequency	AF EMCO 3160-09	Corr.	cable loss 1 (inside chamber)	cable loss 2 (pre- amp)	cable loss 3 (inside chamber)	cable loss 4 (switch unit)	cable loss 5 (to receiver)
MHz	dB (1/m)	dB	dB	dB	dB	dB	dB
18000	40.2	-23.5	0.72	-35.85	6.20	2.81	2.65
18500	40.2	-23.2	0.69	-35.71	6.46	2.76	2.59
19000	40.2	-22.0	0.76	-35.44	6.69	3.15	2.79
19500	40.3	-21.3	0.74	-35.07	7.04	3.11	2.91
20000	40.3	-20.3	0.72	-34.49	7.30	3.07	3.05
20500	40.3	-19.9	0.78	-34.46	7.48	3.12	3.15
21000	40.3	-19.1	0.87	-34.07	7.61	3.20	3.33
21500	40.3	-19.1	0.90	-33.96	7.47	3.28	3.19
22000	40.3	-18.7	0.89	-33.57	7.34	3.35	3.28
22500	40.4	-19.0	0.87	-33.66	7.06	3.75	2.94
23000	40.4	-19.5	0.88	-33.75	6.92	3.77	2.70
23500	40.4	-19.3	0.90	-33.35	6.99	3.52	2.66
24000	40.4	-19.8	0.88	-33.99	6.88	3.88	2.58
24500	40.4	-19.5	0.91	-33.89	7.01	3.93	2.51
25000	40.4	-19.3	0.88	-33.00	6.72	3.96	2.14
25500	40.5	-20.4	0.89	-34.07	6.90	3.66	2.22
26000	40.5	-21.3	0.86	-35.11	7.02	3.69	2.28
26500	40.5	-21.1	0.90	-35.20	7.15	3.91	2.36

Sample calculation

$E \text{ (dB } \mu\text{V/m)} = U \text{ (dB } \mu\text{V)} + AF \text{ (dB 1/m)} + Corr. \text{ (dB)}$

U = Receiver reading


AF = Antenna factor

Corr. = sum of single correction factors of used cables, switch unit, distance correction, amplifier (if applicable)


Linear interpolation will be used for frequencies in between the values in the table.

Table shows an extract of values.

7 SETUP DRAWINGS



Drawing 1: Setup in the Anechoic chamber. For measurements below 1 GHz the ground was replaced by a conducting groundplane.



Drawing 2: Setup for conducted radio tests.

8 MEASUREMENT UNCERTAINTIES

Test Case	Parameter	Uncertainty
AC Power Line	Power	± 3.4 dB
Field Strength of spurious radiation	Power	± 5.5 dB
6 dB / 26 dB / 99% Bandwidth	Power Frequency	± 2.9 dB ± 11.2 kHz
Conducted Output Power	Power	± 2.2 dB
Band Edge Compliance	Power Frequency	± 2.2 dB ± 11.2 kHz
Frequency Stability	Frequency	± 25 Hz
Power Spectral Density	Power	± 2.2 dB

9 PHOTO REPORT

Please see separate photo report.