FCC- TEST REPORT

Report Number	:	**64.912.17.00059.01**	Date of Issue:	June 19, 2017

Model	:	IRC-01
Product Type	:	Universal Remote
Applicant	:	Smart iBlue Technology Limited
Manufacturer	:	Smart iBlue Technology Limited
Address	:	Unit 12, 10/F., Hong Man Industrial Centre, 2 Hong Man Street, Chai Wan, HONG KONG

Test Result	:	■ **Positive**	☐ **Negative**
Total pages including Appendices	:	27	

TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch is a subcontractor to TÜV SÜD Product Service GmbH according to the principles outlined in ISO 17025.

TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch reports apply only to the specific samples tested under stated test conditions. Construction of the actual test samples has been documented. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. The manufacturer/importer is responsible to the Competent Authorities in Europe for any modifications made to the production units which result in non-compliance to the relevant regulations. TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch shall have no liability for any deductions, inferences or generalizations drawn by the client or others from TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch issued reports.

This report is the confidential property of the client. As a mutual protection to our clients, the public and ourselves, extracts from the test report shall not be reproduced except in full without our written approval.

1 Table of Contents

1 Table of Contents 2
2 Details about the Test Laboratory 3
3 Description of the Equipment under Test 4
4 Summary of Test Standards 5
5 Summary of Test Results 6
6 General Remarks 7
7 Test Setups 8
8 Systems test configuration 9
9 Technical Requirement 10
9.1 Conducted Emission 10
9.2 Conducted peak output power 11
9.3 6dB bandwidth and 99% Occupied Bandwidth 13
9.4 Power spectral density 15
9.5 Spurious RF conducted emissions 17
9.6 Band edge 21
9.7 Spurious radiated emissions for transmitter 23
10 Test Equipment List 26
11 System Measurement Uncertainty 27

2 Details about the Test Laboratory

Details about the Test Laboratory
Test Site 1

Company name:	TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch Building 12&13, Zhiheng Wisdomland Business Park, Nantou Checkpoint Road 2, Nanshan District, Shenzhen City, 518052, P. R. China
FCC Registration Number:	502708
IC Registration Number:	10320A-1
Telephone:	86 755 8828 6998
Fax:	86 755 828 5299

3 Description of the Equipment under Test

Product: Universal Remote

Model no.: IRC-01

FCC ID: 2AKSEIRC-01

Rating: DC 5V

RF Transmission Frequency: 2402MHz to 2480MHz

Modulation: GFSK

Antenna Type: Integrated Antenna

Antenna Gain: 0dBi

Description of the EUT:
The EUT is a remote which can be controlled by connecting Bluetooth.

4 Summary of Test Standards

Test Standards	
FCC Part 15 Subpart C 10-1-2015 Edition	PART 15 - RADIO FREQUENCY DEVICES Subpart C - Intentional Radiators

All the test methods were according to KDB558074 D01 DTS Meas Guidance v04 and ANSI C63.10 (2013).

5 Summary of Test Results

Technical Requirements				
FCC Part 15 Subpart C				
Test Condition		Pages	Test Result	Test Site
§15.247(b)(1)	Conducted peak output power	11	Pass	Site 1
§15.247(e)	Power spectral density	15	Pass	Site 1
§15.247(a)(2)	6dB bandwidth	13	Pass	Site 1
§15.247(d)	Spurious RF conducted emissions	17	Pass	Site 1
§15.247(d)	Band edge	21	Pass	Site 1
§15.247(d) & §15.209 &	Spurious radiated emissions for transmitter and receiver	23	Pass	Site 1
§15.203	Antenna requirement	See note 1	Pass	--

Note 1: The EUT uses an Integrated Antenna, which gain is 0dBi. According to §15.203, it is considered sufficiently to comply with the provisions of this section.

6 General Remarks

Remarks

This submittal(s) (test report) is intended for FCC ID: 2AKSEIRC-01 complies with Section 15.207, 15.247 of the FCC Part 15, Subpart C.
This report is for the BLE part.

SUMMARY:

All tests according to the regulations cited on page 5 were

■ - Performed

☐ - **Not** Performed

The Equipment under Test

■ - **Fulfills** the general approval requirements.

☐ - **Does not** fulfill the general approval requirements.

Sample Received Date: January 5, 2017

Testing Start Date: January 6, 2017

Testing End Date: January 19, 2017

- TÜV SÜD Certification and Testing (China) Co., Ltd. Guangzhou Branch -

Reviewed by:

Peter Jia

Prepared by:

Matt Zhang

7 Test Setups

7.1 AC Power Line Conducted Emission test setups



7.2 Radiated test setups

Below 1GHz



Above 1GHz



7.3 Conducted RF test setups



8 Systems test configuration

Auxiliary Equipment Used during Test:

DESCRIPTION	MANUFACTURER	MODEL NO.(SHIELD)	S/N(LENGTH)
Mobile Phone	SAMSUNG	SAMSUNG Note2	---

9 Technical Requirement

9.1 Conducted Emission

Test Method

1. The EUT was placed on a table, which is 0.8m above ground plane
2. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.).
3. Maximum procedure was performed to ensure EUT compliance
4. A EMI test receiver is used to test the emissions from both sides of AC line

Limit

Frequency MHz	QP Limit dBµV	AV Limit dBµV
0.150-0.500	66-56*	56-46*
0.500-5	56	46
5-30	60	50

* Decreasing linear

Result: Not Applicable

9.2 Conducted peak output power

Test Method

1. Use the following spectrum analyzer settings:
   RBW > the 6 dB bandwidth of the emission being measured, VBW≥3RBW, Span≥3RBW
   Sweep = auto, Detector function = peak, Trace = max hold.
2. Add a correction factor to the display.
3. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power.

Limits

Frequency Range MHz	Limit W	Limit dBm
2400-2483.5	≤1	≤30

Test result as below table

Frequency MHz	Conducted Peak Output Power dBm	Result
Low channel 2402MHz	4.63	Pass
Middle channel 2440MHz	5.10	Pass
High channel 2480MHz	4.83	Pass

2402MHz



Date: 16.JAN.2017 10:38:59

2440MHz



Date: 16.JAN.2017 10:39:54

2480MHz



Date: 16.JAN.2017 10:40:19

9.3 6dB bandwidth and 99% Occupied Bandwidth

Test Method

1. Use the following spectrum analyzer settings:
   RBW=100K, VBW≥3RBW, Sweep = auto, Detector function = peak, Trace = max hold
2. Use the automatic bandwidth measurement capability of an instrument, may be employed using the X dB bandwidth mode with X set to 6 dB, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥ 6 dB.
3. Allow the trace to stabilize, record the X dB Bandwidth value.

Limit

Limit [kHz]
≥500

Test result

Frequency MHz	6dB bandwidth kHz	**99% Bandwidth kHz**	Result
Top channel 2402MHz	690.3	1037.626	Pass
Middle channel 2440MHz	664.3	1041.968	Pass
Bottom channel 2480MHz	707.7	1041.968	Pass

2402MHz



Date: 16.JAN.2017 10:32:30

2440MHz



Date: 16.JAN.2017 10:31:28

2480MHz



Date: 16.JAN.2017 10:29:31

9.4 Power spectral density

Test Method

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance:

1. Set analyzer center frequency to DTS channel center frequency. RBW=3kHz,VBW≥3RBW,Span=1.5 times DTS bandwidth, Detector=Peak, Sweep=auto, Trace= max hold.
2. Allow trace to fully stabilize, use the peak marker function to determine the maximum amplitude level within the RBW.
3. Repeat above procedures until other frequencies measured were completed.

Limit

Limit [dBm]
≤8

Test result

Frequency MHz	Power spectral density dBm	Result
Top channel 2402MHz	-11.19	Pass
Middle channel 2440MHz	-10.77	Pass
Bottom channel 2480MHz	-10.62	Pass

2402MHz



Date: 16.JAN.2017 10:42:14

2440MHz



Date: 16.JAN.2017 10:41:51

2480MHz



Date: 16.JAN.2017 10:41:23

9.5 Spurious RF conducted emissions

Test Method

1. Establish a reference level by using the following procedure:
   a. Set RBW=100 kHz. VBW≥3RBW. Detector =peak, Sweep time = auto couple, Trace mode = max hold.
   b. Allow trace to fully stabilize, use the peak marker function to determine the maximum PSD level.
2. Use the maximum PSD level to establish the reference level.
   a. Set the center frequency and span to encompass frequency range to be measured.
   b. Use the peak marker function to determine the maximum amplitude level. Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements, report the three highest emissions relative to the limit.
3. Repeat above procedures until other frequencies measured were completed.

Limit

Frequency Range MHz	Limit (dBc)
30-25000	-20

Spurious RF conducted emissions

2402MHz



Date: 16.JAN.2017 10:53:41



Date: 16.JAN.2017 10:53:03

2440MHz



Date: 16.JAN.2017 10:52:03



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.441 GHz	4.52 dBm		
M2		1	4.873 GHz	-48.95 dBm		
M3		1	7.304 GHz	-47.81 dBm		

Date: 16.JAN.2017 10:51:31

2480MHz



Date: 16.JAN.2017 10:50:19



Date: 16.JAN.2017 10:49:42

9.6 Band edge

Test Method

1 Use the following spectrum analyzer settings:
Span = wide enough to capture the peak level of the in-band emission and all spurious
RBW = 100 kHz, VBW⩾RBW, Sweep = auto, Detector function = peak, Trace = max hold.
2 Allow the trace to stabilize, use the peak and delta measurement to record the result.
3 The level displayed must comply with the limit specified in this Section.

Limit

In any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a) (see Section 15.205(c)).

Test result

2402MHz



Date: 16.JAN.2017 10:46:08

Band edge

2480MHz



Date: 16.JAN.2017 10:47:59

9.7 Spurious radiated emissions for transmitter

Test Method

1: The EUT was place on a turn table which is 1.5m above ground plane for above 1GHz and 0.8m above ground for below 1GHz at 3-meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.

2: The EUT was set 3 meters away from the interference – receiving antenna, which was mounted on the top of a variable – height antenna tower.

3: The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

4: For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

5: Use the following spectrum analyzer settings According to C63.10:

For Above 1GHz

Span = wide enough to capture the peak level of the in-band emission and all spurious RBW = 1MHz, VBW≥RBW for peak measurement and VBW = 10Hz for average measurement, Sweep = auto, Detector function = peak, Trace = max hold.

For Below 1GHz

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious RBW = 100 KHz, VBW≥RBW for peak measurement, Sweep = auto, Detector function = peak, Trace = max hold.

Note:

1: The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 KHz for Quasi-peak detection (QP) at frequency below 1GHz.

2: The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for peak detection (PK) at frequency above 1GHz.

3: The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for RMS Average ((duty cycle < 98%) for Average detection (AV) at frequency above 1GHz, then the measurement results was added to a correction factor (20log(1/duty cycle)).

4: The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz (duty cycle > 98%) for Average detection (AV) at frequency above 1GHz.

Limit

The radio emission outside the operating frequency band shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. Radiated emissions which fall in the restricted bands, as defined in section15.205, must comply with the radiated emission limits specified in section 15.209.

Frequency MHz	Field Strength uV/m	Field Strength dBµV/m	Detector
30-88	100	40	QP
88-216	150	43.5	QP
216-960	200	46	QP
960-1000	500	54	QP
Above 1000	500	54	AV
Above 1000	5000	74	PK

Spurious radiated emissions for transmitter

According to C63.10, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement, so AV emission value did not show in below table if the peak value complies with average limit.

Transmitting spurious emission test result as below:

2402MHz (30MHz – 1GHz)

Frequency	Emission Level	Polarization	Limit	Detector	Result
MHz	dBuV/m		dBµV/m		
839.62	23.76	Horizontal	46.00	QP	Pass
204.97	28.19	Vertical	43.50	QP	Pass

2402MHz (Above 1GHz)

Frequency	Emission Level	Polarization	Limit	Detector	Result
MHz	dBuV/m		dBµV/m		
4803.28	41.86	Horizontal	74.00	PK	Pass
4803.28	36.44	Vertical	74.00	PK	Pass

2440MHz (Above 1GHz)

Frequency	Emission Level	Polarization	Limit	Detector	Result
MHz	dBuV/m		dBµV/m		
4879.21	38.14	Horizontal	74	PK	Pass
4880.15	40.49	Vertical	74	PK	Pass

2480MHz (Above 1GHz)

Frequency	Emission Level	Polarization	Limit	Detector	Result
MHz	dBuV/m		dBµV/m		
4959.37	38.89	Horizontal	74.00	PK	Pass
4859.37	42.08	Vertical	74.00	PK	Pass

10 Test Equipment List

List of Test Instruments

	DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	CAL. DUE DATE
C	Signal Generator	Rohde & Schwarz	SMB100A	108272	2017-7-24
	Signal Analyzer	Rohde & Schwarz	FSV40	101030	2017-7-24
	Vector Signal Generator	Rohde & Schwarz	SMU 200A	105324	2017-7-24
	RF Switch Module	Rohde & Schwarz	OSP120/OSP-B157	101226/100851	2017-7-24
	Test software	Rohde & Schwarz	EMC32	Version 9.22.00	N/A
	EMI Test Receiver	Rohde & Schwarz	ESR 3	101782	2017-7-15
	LISN	Rohde & Schwarz	ENV216	100326	2017-7-15
RE	Signal Analyzer	Rohde & Schwarz	FSV40	101031	2017-8-17
	Trilog Super Broadband Test Antenna	Schwarzbeck	VULB 9163	708	2017-8-17
	Horn Antenna	Rohde & Schwarz	HF907	102295	2017-8-17
	Wideband Horn Antenna	Q-PAR	QWH-SL-18-40-K-SG	12827	2017-8-17
	Pre-amplifier	Rohde & Schwarz	SCU 18	102230	2017-8-17
	Pre-amplifier	Rohde & Schwarz	SCU 40A	100432	2017-8-17
	Fully Anechoic Chamber	TDK	8X4X4	--	2019-8-29

C - Conducted RF tests

- Conducted peak output power
- 6dB bandwidth
- Power spectral density*
- Spurious RF conducted emissions
- Band edge
- Conducted emission AC power port

RE - Radiated RF tests

- Spurious radiated emissions for transmitter

11 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 were:

System Measurement Uncertainty	
Items	**Extended Uncertainty**
Uncertainty for Radiated Emission in 3m chamber 30MHz-1000MHz	Horizontal: 4.83dB; Vertical: 4.91dB;
Uncertainty for Radiated Emission in 3m chamber 1000MHz-18000MHz	Horizontal: 4.89dB; Vertical: 4.88dB;
Uncertainty for Conducted RF test	2.04dB