

FCC Radio Test Report

FCC ID: 2AKU3SWSC-580W

Original Grant

Report No. : TB-FCC151105
Applicant : Shenzhen Dexin Industrial Co., Ltd.
Equipment Under Test (EUT)
EUT Name : Wireless network HD camera
Model No. : WSC-580W
Series No. : WSC-590W, WSC-588, WSC-588H, WSC-589, WSC-589H,
WSC-599, WSC-599H, WSC-578W
Brand Name : **Haier**
Receipt Date : 2016-12-28
Test Date : 2016-12-29 to 2017-01-05
Issue Date : 2017-01-06
Standards : FCC Part 15, Subpart C (15.247:2016)
Test Method : ANSI C63.10: 2013
Conclusions : **PASS**

In the configuration tested, the EUT complied with the standards specified above,
The EUT technically complies with the FCC and IC requirements

Test/Witness Engineer :

Ivan Su

**Approved &
Authorized**

:

Long Ha



This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in the report.

Contents

CONTENTS.....	2
1. GENERAL INFORMATION ABOUT EUT	4
1.1 Client Information.....	4
1.2 General Description of EUT (Equipment Under Test)	4
1.3 Block Diagram Showing the Configuration of System Tested.....	5
1.4 Description of Support Units	5
1.5 Description of Test Mode.....	6
1.6 Description of Test Software Setting	7
1.7 Measurement Uncertainty	8
1.7 Test Facility.....	8
2. TEST SUMMARY.....	9
3. TEST EQUIPMENT.....	10
4. CONDUCTED EMISSION TEST	12
4.1 Test Standard and Limit.....	12
4.2 Test Setup.....	12
4.3 Test Procedure.....	12
4.4 EUT Operating Mode	13
4.5 Test Data.....	13
5. RADIATED EMISSION TEST	22
5.1 Test Standard and Limit.....	22
5.2 Test Setup.....	23
5.3 Test Procedure.....	24
5.4 EUT Operating Condition	25
5.5 Test Data.....	25
6. RESTRICTED BANDS REQUIREMENT	53
6.1 Test Standard and Limit.....	53
6.2 Test Setup.....	53
6.3 Test Procedure.....	53
6.4 EUT Operating Condition	54
6.5 Test Data.....	54
7. BANDWIDTH TEST.....	79
7.1 Test Standard and Limit.....	79
7.2 Test Setup.....	79
7.3 Test Procedure.....	79
7.4 EUT Operating Condition	79

7.5 Test Data.....	80
8. PEAK OUTPUT POWER TEST.....	92
8.1 Test Standard and Limit.....	92
8.2 Test Setup.....	92
8.3 Test Procedure.....	92
8.4 EUT Operating Condition	92
8.5 Test Data.....	93
9. POWER SPECTRAL DENSITY TEST	97
9.1 Test Standard and Limit.....	97
9.2 Test Setup.....	97
9.3 Test Procedure.....	97
9.4 EUT Operating Condition	97
9.5 Test Data.....	98
10. ANTENNA REQUIREMENT.....	110
10.1 Standard Requirement.....	110
10.2 Antenna Connected Construction	110

1. General Information about EUT

1.1 Client Information

Applicant	: Shenzhen Dexin Industrial Co., Ltd.
Address	: 3 Floor, E Building, Yunfeng Road, No.23, Guanghao Industrial Zones, Longhua District, Shenzhen, China.
Manufacturer	: Shenzhen Jieshilian Industrial Co., Ltd.
Address	: 2 Floor, No.270 Buiding, Dashuikengjuling Industrial Zone, Guanlan, Longhua Diserict, Shenzhen, China.

1.2 General Description of EUT (Equipment Under Test)

EUT Name	:	Wireless network HD camera	
Models No.	:	WSC-580W, WSC-590W, WSC-588, WSC-588H, WSC-589, WSC-589H, WSC-599, WSC-599H, WSC-578W	
Model Difference	:	All models are identical in the same PCB layout interior structure and electrical circuits, The only difference is model name for commercial purpose.	
Product Description	:	Operation Frequency:	802.11b/g/n(HT20): 2412MHz~2462MHz 802.11n(HT40): 2422MHz~2452MHz
	:	Number of Channel:	802.11b/g/n(HT20):11 channels <i>see note(3)</i> 802.11n(HT40): 7 channels <i>see note(3)</i>
	:	RF Output Power:	802.11b: 18.36 dBm 802.11g: 15.99 dBm 802.11n (HT20): 15.06 dBm 802.11n (HT40): 15.02 dBm
	:	Antenna Gain:	3.5 dBi Dipole Antenna
	:	Modulation Type:	802.11b: DSSS(CCK, QPSK, BPSK) 802.11g: OFDM 802.11n: OFDM
	:	Bit Rate of Transmitter:	802.11b: 11/5.5/2/1 Mbps 802.11g: 54/48/36/24/18/12/9/6 Mbps 802.11n:up to 150Mbps
	:		
Power Supply	:	DC Voltage by the Host System. DC Voltage Supply from AC/DC Adapter	
Power Rating	:	DC 5.0 by the Host System. Input: AC 100-240 V~50/60Hz—0.3 A Output: DC 5.0 V—1500mA	

Connecting I/O Port(S) : Please refer to the User's Manual

Note:

- (1) This Test Report is FCC Part 15.247 for 802.11b/g/n, the test procedure follows the FCC KDB 558074 D01 DTS Meas Guidance v03r05.
- (2) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.
- (3) Channel List:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2412	05	2432	09	2452
02	2417	06	2437	10	2457
03	2422	07	2442	11	2462
04	2427	08	2447		

Note: CH 01~CH 11 for 802.11b/g/n(HT20)


CH 03~CH 09 for 802.11n(HT40)

(4) Antenna information

Antenna	Brand	Model Name	Type	Antenna Gain(dBi)
ANT1	N/A	N/A	Dipole	3.5

1.3 Block Diagram Showing the Configuration of System Tested

TX Mode



1.4 Description of Support Units

The EUT has been test as an independent unit

1.5 Description of Test Mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned follow was evaluated respectively.

For Conducted Test	
Final Test Mode	Description
Mode 1	TX B Mode

For Radiated Test	
Final Test Mode	Description
Mode 2	TX Mode B Mode Channel 01/06/11
Mode 3	TX Mode G Mode Channel 01/06/11
Mode 4	TX Mode N(HT20) Mode Channel 01/06/11
Mode 5	TX Mode N(HT40) Mode Channel 03/06/09

Note:

- (1) For all test, we have verified the construction and function in typical operation. And all the test modes were carried out with the EUT in transmitting operation in maximum power with all kinds of data rate.

According to ANSI C63.10 standards, the measurements are performed at the highest, middle, lowest available channels, and the worst case data rate as follows:

- 802.11b Mode: CCK (1 Mbps)
- 802.11g Mode: OFDM (6 Mbps)
- 802.11n (HT20) Mode: MCS 0 (6.5 Mbps)
- 802.11n (HT40) Mode: MCS 0 (13 Mbps)

- (2) During the testing procedure, the continuously transmitting with the maximum power mode was programmed by the customer.
- (3) The EUT is considered a fixed unit; in normal use it was positioned on X-plane. The worst case was found positioned on X-plane. Therefore only the test data of this X-plane was used for radiated emission measurement test.

1.6 Description of Test Software Setting

During testing channel& Power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of WLAN.

Test Software: MT7601USB			
Test Mode: Continuously transmitting			
Mode	Data Rate	Channel	Parameters
			ANT
802.11b	CCK/ 1Mbps	01	DEF
	CCK/ 1Mbps	06	DEF
	CCK/ 1Mbps	11	DEF
802.11g	OFDM/ 6Mbps	01	DEF
	OFDM/ 6Mbps	06	DEF
	OFDM/ 6Mbps	11	DEF
802.11n(20)	MCS 0	01	DEF
	MCS 0	06	DEF
	MCS 0	11	DEF
802.11n(40)	MCS 0	03	DEF
	MCS 0	06	DEF
	MCS 0	09	DEF

1.7 Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

Test Item	Parameters	Expanded Uncertainty (U_{Lab})
Conducted Emission	Level Accuracy: 9kHz~150kHz 150kHz to 30MHz	± 3.42 dB ± 3.42 dB
Radiated Emission	Level Accuracy: 9kHz to 30 MHz	± 4.60 dB
Radiated Emission	Level Accuracy: 30MHz to 1000 MHz	± 4.40 dB
Radiated Emission	Level Accuracy: Above 1000MHz	± 4.20 dB

1.7 Test Facility

The testing report were performed by the Shenzhen Toby Technology Co., Ltd., in their facilities located at 1A/F., Bldg.6, Yusheng Industrial Zone, The National Road No.107 Xixiang Section 467, Xixiang, Bao'an, Shenzhen, Guangdong, China. At the time of testing, the following bodies accredited the Laboratory:

CNAS (L5813)

The Laboratory has been accredited by CNAS to ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories for the competence in the field of testing. And the Registration No.: CNAS L5813.

FCC List No.: (811562)

The Laboratory is listed in the United States of American Federal Communications Commission (FCC), and the registration number is 811562.

IC Registration No.: (11950A-1)

The Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing. The site registration: Site# 11950A-1.

2. Test Summary

FCC Part 15 Subpart C(15.247)/ RSS 247 Issue 1				
Standard Section		Test Item	Judgment	Remark
FCC	IC			
15.203	/	Antenna Requirement	PASS	N/A
15.207	RSS-GEN 7.2.4	Conducted Emission	PASS	N/A
15.205	RSS-GEN 7.2.2	Restricted Bands	PASS	N/A
15.247(a)(2)	RSS 247 5.2 (1)	6dB Bandwidth	PASS	N/A
15.247(b)	RSS 247 5.4 (4)	Peak Output Power	PASS	N/A
15.247(e)	RSS 247 5.2 (2)	Power Spectral Density	PASS	N/A
15.247(d)	RSS 247 5.5	Band Edge	PASS	N/A
15.247(d)& 15.209	RSS 247 5.5	Transmitter Radiated Spurious Emission	PASS	N/A
Note: "/" for no requirement for this test item. N/A is an abbreviation for Not Applicable.				

3. Test Equipment

Conducted Emission Test					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
EMI Test Receiver	Rohde & Schwarz	ESCI	100321	Jul. 22, 2016	Jul. 21, 2017
RF Switching Unit	Compliance Direction Systems Inc	RSU-A4	34403	Jul. 22, 2016	Jul. 21, 2017
AMN	SCHWARZBECK	NNBL 8226-2	8226-2/164	Jul. 22, 2016	Jul. 21, 2017
LISN	Rohde & Schwarz	ENV216	101131	Jul. 22, 2016	Jul. 21, 2017
Radiation Emission Test					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Jul. 22, 2016	Jul. 21, 2017
EMI Test Receiver	Rohde & Schwarz	ESPI	100010/007	Jul. 22, 2016	Jul. 21, 2017
Bilog Antenna	ETS-LINDGREN	3142E	00117537	Mar. 20, 2016	Mar. 19, 2017
Bilog Antenna	ETS-LINDGREN	3142E	00117542	Mar. 20, 2016	Mar. 19, 2017
Horn Antenna	ETS-LINDGREN	3117	00143207	Mar. 19, 2016	Mar. 18, 2017
Horn Antenna	ETS-LINDGREN	3117	00143209	Mar. 19, 2016	Mar. 18, 2017
Pre-amplifier	Sonoma	310N	185903	Mar. 20, 2016	Mar. 19, 2017
Pre-amplifier	HP	8447B	3008A00849	Mar. 26, 2016	Mar. 25, 2017
Loop Antenna	Laplace instrument	RF300	0701	Mar. 19, 2016	Mar. 18, 2017
Cable	HUBER+SUHNER	100	SUCOFLEX	Mar. 26, 2016	Mar. 25, 2017
Positioning Controller	ETS-LINDGREN	2090	N/A	N/A	N/A
Antenna Conducted Emission					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Jul. 22, 2016	Jul. 21, 2017
Spectrum Analyzer	Rohde & Schwarz	ESCI	100321	Jul. 22, 2016	Jul. 21, 2017
Power Meter	Anritsu	ML2495A	25406005	Jul. 22, 2016	Jul. 21, 2017

Power Sensor	Anritsu	ML2411B	25406005	Jul. 22, 2016	Jul. 21, 2017
--------------	---------	---------	----------	---------------	---------------

4. Conducted Emission Test

4.1 Test Standard and Limit

4.1.1 Test Standard
FCC Part 15.207

4.1.2 Test Limit


Conducted Emission Test Limit

Frequency	Maximum RF Line Voltage (dB μ V)	
	Quasi-peak Level	Average Level
150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
500kHz~5MHz	56	46
5MHz~30MHz	60	50

Notes:

- (1) *Decreasing linearly with logarithm of the frequency.
- (2) The lower limit shall apply at the transition frequencies.
- (3) The limit decrease in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

4.2 Test Setup



4.3 Test Procedure

The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.

Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.

I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.

LISN at least 80 cm from nearest part of EUT chassis.

The bandwidth of EMI test receiver is set at 9kHz, and the test frequency band is from 0.15MHz to 30MHz.


4.4 EUT Operating Mode

Please refer to the description of test mode.

4.5 Test Data


Please see the next page.

EUT:	Wireless network HD camera	Model Name :	WSC-580W
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Terminal:	Line		
Test Mode:	TX B Mode		
Remark:	Only worse case is reported		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1		0.1500	31.47	10.12	41.59	65.99	-24.40	QP
2		0.1500	16.02	10.12	26.14	55.99	-29.85	AVG
3		0.4660	30.39	10.03	40.42	56.58	-16.16	QP
4		0.4660	16.57	10.03	26.60	46.58	-19.98	AVG
5		0.9340	30.10	10.13	40.23	56.00	-15.77	QP
6		0.9340	18.47	10.13	28.60	46.00	-17.40	AVG
7		1.0780	31.04	10.15	41.19	56.00	-14.81	QP
8		1.0780	21.49	10.15	31.64	46.00	-14.36	AVG
9	*	2.2260	34.97	10.06	45.03	56.00	-10.97	QP
10		2.2260	21.33	10.06	31.39	46.00	-14.61	AVG
11		27.0020	36.72	10.10	46.82	60.00	-13.18	QP
12		27.0020	26.48	10.10	36.58	50.00	-13.42	AVG

Emission Level= Read Level+ Correct Factor




Emission Level= Read Level+ Correct Factor



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1		0.1500	35.53	10.12	45.65	65.99	-20.34	QP
2		0.1500	19.72	10.12	29.84	55.99	-26.15	AVG
3		0.2900	30.53	10.09	40.62	60.52	-19.90	QP
4		0.2900	18.76	10.09	28.85	50.52	-21.67	AVG
5		0.5180	32.32	10.02	42.34	56.00	-13.66	QP
6	*	0.5180	23.49	10.02	33.51	46.00	-12.49	AVG
7		0.9820	32.08	10.15	42.23	56.00	-13.77	QP
8		0.9820	18.83	10.15	28.98	46.00	-17.02	AVG
9		2.4020	31.96	10.06	42.02	56.00	-13.98	QP
10		2.4020	19.87	10.06	29.93	46.00	-16.07	AVG
11		23.3740	24.45	10.06	34.51	60.00	-25.49	QP
12		23.3740	7.47	10.06	17.53	50.00	-32.47	AVG

Emission Level= Read Level+ Correct Factor

EUT:	Wireless network HD camera	Model Name :	WSC-580W
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 240V/60 Hz		
Terminal:	Neutral		
Test Mode:	TX B Mode		
Remark:	Only worse case is reported		



No. Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
	MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1	0.1499	10.35	9.92	20.27	66.00	-45.73	QP
2	0.1499	5.59	9.92	15.51	56.00	-40.49	AVG
3	0.5060	38.82	10.02	48.84	56.00	-7.16	QP
4	0.5060	33.13	10.02	43.15	46.00	-2.85	AVG
5	1.4460	34.16	10.06	44.22	56.00	-11.78	QP
6	1.4460	30.24	10.06	40.30	46.00	-5.70	AVG
7	2.3620	33.67	10.05	43.72	56.00	-12.28	QP
8	2.3620	25.41	10.05	35.46	46.00	-10.54	AVG
9	5.9499	30.11	10.01	40.12	60.00	-19.88	QP
10	5.9499	13.70	10.01	23.71	50.00	-26.29	AVG
11 *	27.0020	47.44	10.20	57.64	60.00	-2.36	QP
12	27.0020	36.12	10.20	46.32	50.00	-3.68	AVG

Emission Level= Read Level+ Correct Factor

5. Radiated Emission Test

5.1 Test Standard and Limit

5.1.1 Test Standard

FCC Part 15.209

5.1.2 Test Limit

Radiated Emission Limits (9kHz~1000MHz)

Frequency (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3


Radiated Emission Limit (Above 1000MHz)

Frequency (MHz)	Distance Meters(at 3m)	
	Peak (dBuV/m)	Average (dBuV/m)
Above 1000	74	54


Note:

- (1) The tighter limit applies at the band edges.
- (2) Emission Level (dBuV/m)=20log Emission Level(uV/m)


5.2 Test Setup



Below 30MHz Test Setup



Below 1000MHz Test Setup



Above 1GHz Test Setup

5.3 Test Procedure

- (1) Measurements at frequency above 1GHz. The EUT was placed on a rotating 1.5m high above the ground. RF absorbers covered the ground plane with a minimum area of 3.0m by 3.0m between the EUT and measurement receiver antenna. The RF absorber shall not exceed 30cm in high above the conducting floor. The table was rotated 360 degrees to determine the position of the highest radiation.
- (2) The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.
- (3) The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- (4) If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit Bellow 1 GHz, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed. But the Peak Value and average value both need to comply with applicable limit above 1 GHz.
- (5) Testing frequency range below 1GHz the measuring instrument use VBW=120 kHz with Quasi-peak detection.
- (6) Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.

(7) For the actual test configuration, please see the test setup photo.

5.4 EUT Operating Condition

The Equipment Under Test was set to Continual Transmitting in maximum power.

5.5 Test Data

Remark: During testing above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.

Test data please refer the following pages.


9 KHz~30 MHz

From 9 KHz to 30 MHz: Conclusion: PASS

Note: The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

30MHz~1GHz

EUT:	Wireless network HD camera	Model:	WSC-580W
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX B Mode 2412MHz		
Remark:	Only worse case is reported		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		30.3171	47.62	-14.34	33.28	40.00	-6.72	peak
2	!	92.4624	61.00	-22.52	38.48	43.50	-5.02	peak
3	!	216.0240	60.44	-19.29	41.15	46.00	-4.85	peak
4	*	270.3747	59.38	-17.26	42.12	46.00	-3.88	peak
5	!	406.0880	54.18	-12.36	41.82	46.00	-4.18	peak
6	!	729.3582	48.14	-6.08	42.06	46.00	-3.94	peak

*:Maximum data x:Over limit !:over margin

Emission Level= Read Level+ Correct Factor

EUT:	Wireless network HD camera	Model:	WSC-580W
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Vertical		
Test Mode:	TX B Mode 2412MHz		
Remark:	Only worse case is reported		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	!	80.9274	58.95	-23.28	35.67	40.00	-4.33	peak
2	!	135.0319	61.54	-21.96	39.58	43.50	-3.92	peak
3	!	189.0741	58.43	-20.53	37.90	43.50	-5.60	peak
4	!	270.3747	59.95	-17.26	42.69	46.00	-3.31	peak
5	!	459.1143	53.70	-11.66	42.04	46.00	-3.96	peak
6	*	952.0937	46.01	-3.25	42.76	46.00	-3.24	peak

*:Maximum data x:Over limit !:over margin

Emission Level= Read Level+ Correct Factor

Above 1GHz


EUT:	Wireless network HD camera	Model:	WSC-580W
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX B Mode 2412MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4823.157	46.98	13.56	60.54	74.00	-13.46	peak
2	*	4824.698	35.35	13.56	48.91	54.00	-5.09	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Wireless network HD camera	Model:	WSC-580W
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Vertical		
Test Mode:	TX B Mode 2412MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4822.998	36.05	13.55	49.60	54.00	-4.40	AVG
2		4824.519	47.69	13.56	61.25	74.00	-12.75	peak

Emission Level= Read Level+ Correct Factor


EUT:	Wireless network HD camera	Model:	WSC-580W
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX B Mode 2437MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4874.157	45.80	13.86	59.66	74.00	-14.34	peak
2	*	4874.321	34.45	13.86	48.31	54.00	-5.69	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Wireless network HD camera	Model:	WSC-580W
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Vertical		
Test Mode:	TX B Mode 2437MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4873.512	36.45	13.86	50.31	54.00	-3.69	AVG
2		4874.251	46.39	13.86	60.25	74.00	-13.75	peak

Emission Level= Read Level+ Correct Factor


EUT:	Wireless network HD camera	Model:	WSC-580W
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX B Mode 2462MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4924.002	45.88	14.15	60.03	74.00	-13.97	peak
2	*	4924.424	35.51	14.15	49.66	54.00	-4.34	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Wireless network HD camera	Model:	WSC-580W
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Vertical		
Test Mode:	TX B Mode 2462MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4924.215	34.82	14.15	48.97	54.00	-5.03	AVG
2		4924.620	44.93	14.15	59.08	74.00	-14.92	peak

Emission Level= Read Level+ Correct Factor


EUT:	Wireless network HD camera	Model:	WSC-580W
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX G Mode 2412MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB Detector
1		4824.166	45.41	13.56	58.97	74.00	-15.03 peak
2	*	4824.278	36.05	13.56	49.61	54.00	-4.39 AVG

Emission Level= Read Level+ Correct Factor


EUT:	Wireless network HD camera	Model:	WSC-580W
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Vertical		
Test Mode:	TX G Mode 2412MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4823.619	36.09	13.56	49.65	54.00	-4.35	AVG
2		4824.621	45.52	13.56	59.08	74.00	-14.92	peak

Emission Level= Read Level+ Correct Factor


EUT:	Wireless network HD camera	Model:	WSC-580W
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX G Mode 2437MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4874.255	47.46	13.86	61.32	74.00	-12.68	peak
2	*	4875.651	36.29	13.87	50.16	54.00	-3.84	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Wireless network HD camera	Model:	WSC-580W
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Vertical		
Test Mode:	TX G Mode 2437MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4874.258	47.73	13.86	61.59	74.00	-12.41	peak
2	*	4874.698	36.83	13.86	50.69	54.00	-3.31	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Wireless network HD camera	Model:	WSC-580W
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX G Mode 2462MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4924.058	33.46	14.15	47.61	54.00	-6.39	AVG
2		4924.518	45.46	14.15	59.61	74.00	-14.39	peak

Emission Level= Read Level+ Correct Factor


EUT:	Wireless network HD camera	Model:	WSC-580W
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Vertical		
Test Mode:	TX G Mode 2462MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4923.991	32.76	14.15	46.91	54.00	-7.09	AVG
2		4924.612	45.03	14.15	59.18	74.00	-14.82	peak

Emission Level= Read Level+ Correct Factor


EUT:	Wireless network HD camera	Model:	WSC-580W
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX N(HT20) Mode 2412MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4822.985	34.54	13.55	48.09	54.00	-5.91	AVG
2		4824.667	43.49	13.56	57.05	74.00	-16.95	peak

Emission Level= Read Level+ Correct Factor


EUT:	Wireless network HD camera	Model:	WSC-580W
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Vertical		
Test Mode:	TX N(HT20) Mode 2412MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4823.009	45.10	13.56	58.66	74.00	-15.34	peak
2	*	4824.615	35.35	13.56	48.91	54.00	-5.09	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Wireless network HD camera	Model:	WSC-580W
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX N(HT20) Mode 2437MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4874.598	45.78	13.86	59.64	74.00	-14.36	peak
2	*	4874.624	35.32	13.86	49.18	54.00	-4.82	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Wireless network HD camera	Model:	WSC-580W
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Vertical		
Test Mode:	TX N(HT20) Mode 2437MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4874.665	45.80	13.86	59.66	74.00	-14.34	peak
2	*	4875.698	35.74	13.87	49.61	54.00	-4.39	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Wireless network HD camera	Model:	WSC-580W
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX N(HT20) Mode 2462MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4924.054	35.46	14.15	49.61	54.00	-4.39	AVG
2		4924.516	44.00	14.15	58.15	74.00	-15.85	peak

Emission Level= Read Level+ Correct Factor


EUT:	Wireless network HD camera	Model:	WSC-580W
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Vertical		
Test Mode:	TX N(HT20) Mode 2462MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4923.058	35.94	14.15	50.09	54.00	-3.91	AVG
2		4924.612	46.16	14.15	60.31	74.00	-13.69	peak

Emission Level= Read Level+ Correct Factor


EUT:	Wireless network HD camera	Model:	WSC-580W
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX N(HT40) Mode 2422MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4843.215	36.45	13.68	50.13	54.00	-3.87	AVG
2		4844.012	48.63	13.68	62.31	74.00	-11.69	peak

Emission Level= Read Level+ Correct Factor


EUT:	Wireless network HD camera	Model:	WSC-580W
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Vertical		
Test Mode:	TX N(HT40) Mode 2422MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4843.751	35.93	13.68	49.61	54.00	-4.39	AVG
2		4844.651	47.61	13.68	61.29	74.00	-12.71	peak

Emission Level= Read Level+ Correct Factor


EUT:	Wireless network HD camera	Model:	WSC-580W
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX N(HT40) Mode 2437MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4873.512	46.27	13.86	60.13	74.00	-13.87	peak
2	*	4874.615	35.80	13.86	49.66	54.00	-4.34	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Wireless network HD camera	Model:	WSC-580W
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Vertical		
Test Mode:	TX N(HT40) Mode 2437MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4823.698	47.47	13.56	61.03	74.00	-12.97	peak
2	*	4824.336	36.05	13.56	49.61	54.00	-4.39	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Wireless network HD camera	Model:	WSC-580W
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX N(HT40) Mode 2452MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	4903.165	35.64	14.03	49.67	54.00	-4.33	AVG
2		4904.658	46.28	14.03	60.31	74.00	-13.69	peak

Emission Level= Read Level+ Correct Factor

EUT:	Wireless network HD camera	Model:	WSC-580W
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Vertical		
Test Mode:	TX N(HT40) Mode 2452MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4905.612	34.94	14.05	48.99	54.00	-5.01	AVG
2		4905.664	46.26	14.05	60.31	74.00	-13.69	peak

Emission Level= Read Level+ Correct Factor

6. Restricted Bands Requirement

6.1 Test Standard and Limit


6.1.1 Test Standard

FCC Part 15.209 FCC Part 15.205

6.1.2 Test Limit

Restricted Frequency Band (MHz)	Distance Meters(at 3m)	
	Peak (dBuV/m)	Average (dBuV/m)
2310 ~2390	74	54
2483.5 ~2500	74	54

6.2 Test Setup



6.3 Test Procedure

- (1) The measuring distance of 3m shall be used for measurements at frequency up to 1GHz and above 1 GHz. The EUT was placed on a rotating 0.8m high above ground, the table was rotated 360 degrees to determine the position of the highest radiation.
- (2) Measurements at frequency above 1GHz. The EUT was placed on a rotating 1.5m high above the ground. RF absorbers covered the ground plane with a minimum area of 3.0m by 3.0m between the EUT and measurement receiver antenna. The RF absorber shall not

exceed 30cm in high above the conducting floor. The table was rotated 360 degrees to determine the position of the highest radiation.

- (3) The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.
- (4) The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- (5) If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit Bellow 1 GHz, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed. But the Peak Value and average value both need to comply with applicable limit above 1 GHz.
- (6) Testing frequency range below 1GHz the measuring instrument use VBW=120 kHz with Quasi-peak detection.
- (7) Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.
- (8) For the actual test configuration, please see the test setup photo.

6.4 EUT Operating Condition


The Equipment Under Test was set to Continual Transmitting in maximum power.

6.5 Test Data

Please see the next page.

(1) Radiation Test


EUT:	Wireless network HD camera	Model:	WSC-580W
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX B Mode 2412MHz		
Remark:	N/A		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB Detector
1		2390.000	42.13	0.77	42.90	74.00	-31.10 peak
2		2390.000	32.83	0.77	33.60	54.00	-20.40 AVG
3	X	2410.006	98.56	0.85	99.41	Fundamental Frequency peak	
4	*	2410.012	94.09	0.85	94.94	Fundamental Frequency AVG	

Emission Level= Read Level+ Correct Factor


EUT:	Wireless network HD camera	Model:	WSC-580W
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Vertical		
Test Mode:	TX B Mode 2412MHz		
Remark:	N/A		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		2390.000	50.25	0.77	51.02	74.00	-22.98	peak
2		2390.000	40.68	0.77	41.45	54.00	-12.55	AVG
3	X	2410.900	109.07	0.86	109.93	Fundamental Frequency		peak
4	*	2411.300	104.94	0.86	105.80	Fundamental Frequency		AVG


Emission Level= Read Level+ Correct Factor

EUT:	Wireless network HD camera	Model:	WSC-580W
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX B Mode 2462MHz		
Remark:	N/A		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB Detector
1	X	2460.900	109.36	1.06	110.42	Fundamental Frequency	peak
2	*	2461.200	104.81	1.07	105.88	Fundamental Frequency	AVG
3		2483.500	49.70	1.17	50.87	74.00	-23.13 peak
4		2483.500	40.41	1.17	41.58	54.00	-12.42 AVG

Emission Level= Read Level+ Correct Factor




EUT:	Wireless network HD camera	Model:	WSC-580W
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX G Mode 2412MHz		
Remark:	N/A		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		2390.000	50.93	0.77	51.70	74.00	-22.30	peak
2		2390.000	39.73	0.77	40.50	54.00	-13.50	AVG
3	X	2410.400	101.51	0.85	102.36	Fundamental Frequency		peak
4	*	2410.800	91.18	0.86	92.04	Fundamental Frequency		AVG


Emission Level= Read Level+ Correct Factor

EUT:	Wireless network HD camera	Model:	WSC-580W
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Vertical		
Test Mode:	TX G Mode 2412MHz		
Remark:	N/A		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		2390.000	55.19	0.77	55.96	74.00	-18.04	peak
2		2390.000	44.27	0.77	45.04	54.00	-8.96	AVG
3	X	2407.400	106.30	0.85	107.15	Fundamental Frequency		peak
4	*	2410.300	95.88	0.85	96.73	Fundamental Frequency		AVG

Emission Level= Read Level+ Correct Factor




EUT:	Wireless network HD camera	Model:	WSC-580W
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Vertical		
Test Mode:	TX G Mode 2462MHz		
Remark:	N/A		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	2462.800	88.82	1.08	89.90	Fundamental Frequency		AVG
2	X	2463.500	98.28	1.08	99.36	Fundamental Frequency		peak
3		2483.500	49.65	1.17	50.82	74.00	-23.18	peak
4		2483.500	37.94	1.17	39.11	54.00	-14.89	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Wireless network HD camera	Model:	WSC-580W
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX N(HT20) Mode 2412MHz		
Remark:	N/A		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		2390.000	53.93	0.77	54.70	74.00	-19.30	peak
2		2390.000	43.11	0.77	43.88	54.00	-10.12	AVG
3	X	2411.100	104.44	0.86	105.30	Fundamental Frequency		peak
4	*	2413.400	94.34	0.86	95.20	Fundamental Frequency		AVG

Emission Level= Read Level+ Correct Factor


EUT:	Wireless network HD camera	Model:	WSC-580W
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Vertical		
Test Mode:	TX N(HT20) Mode 2412MHz		
Remark:	N/A		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		2390.000	57.86	0.77	58.63	74.00	-15.37	peak
2		2390.000	46.17	0.77	46.94	54.00	-7.06	AVG
3	X	2410.600	105.97	0.86	106.83	Fundamental Frequency		peak
4	*	2410.600	96.01	0.86	96.87	Fundamental Frequency		AVG

Emission Level= Read Level+ Correct Factor


EUT:	Wireless network HD camera	Model:	WSC-580W
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX N(HT20) Mode 2462MHz		
Remark:	N/A		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	X	2460.300	105.44	1.06	106.50	Fundamental Frequency		peak
2	*	2460.500	95.43	1.06	96.49	Fundamental Frequency		AVG
3		2483.500	58.53	1.17	59.70	74.00	-14.30	peak
4		2483.500	44.40	1.17	45.57	54.00	-8.43	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Wireless network HD camera	Model:	WSC-580W
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Vertical		
Test Mode:	TX N(HT20) Mode 2462MHz		
Remark:	N/A		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	X	2460.500	104.48	1.06	105.54	Fundamental Frequency		peak
2	*	2463.400	94.20	1.08	95.28	Fundamental Frequency		AVG
3		2483.500	55.97	1.17	57.14	74.00	-16.86	peak
4		2483.500	42.94	1.17	44.11	54.00	-9.89	AVG


Emission Level= Read Level+ Correct Factor

EUT:	Wireless network HD camera	Model:	WSC-580W
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX N(HT40) Mode 2422MHz		
Remark:	N/A		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		2390.000	62.82	0.77	63.59	74.00	-10.41	peak
2		2390.000	48.34	0.77	49.11	54.00	-4.89	AVG
3	X	2420.200	103.17	0.89	104.06	Fundamental Frequency		peak
4	*	2420.300	94.29	0.89	95.18	Fundamental Frequency		AVG

Emission Level= Read Level+ Correct Factor




EUT:	Wireless network HD camera	Model:	WSC-580W
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX N(HT40) Mode 2452MHz		
Remark:	N/A		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	X	2450.200	103.89	1.02	104.91	Fundamental Frequency		peak
2	*	2450.400	93.91	1.02	94.93	Fundamental Frequency		AVG
3		2483.500	63.22	1.17	64.39	74.00	-9.61	peak
4		2483.500	49.87	1.17	51.04	54.00	-2.96	AVG

Emission Level= Read Level+ Correct Factor

EUT:	Wireless network HD camera	Model:	WSC-580W
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Vertical		
Test Mode:	TX N(HT40) Mode 2452MHz		
Remark:	N/A		





No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	2453.500	92.33	1.04	93.37	Fundamental Frequency		AVG
2	X	2453.600	101.81	1.04	102.85	Fundamental Frequency		peak
3		2483.500	64.73	1.17	65.90	74.00	-8.10	peak
4		2483.500	49.51	1.17	50.68	54.00	-3.32	AVG


Emission Level= Read Level+ Correct Factor


(2) Conducted Test(Band Edge)


EUT:	Wireless network HD camera	Model:	WSC-580W
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Test Mode:	TX B Mode 2412MHz / TX B Mode 2462MHz		
Remark:	The EUT is programed in continuously transmitting mode		




















7. Bandwidth Test

7.1 Test Standard and Limit


7.1.1 Test Standard

FCC Part 15.247 (a)(2)

7.1.2 Test Limit

FCC Part 15 Subpart C(15.247)/RSS-210		
Test Item	Limit	Frequency Range(MHz)
Bandwidth	≥ 500 KHz (6dB bandwidth)	2400~2483.5

7.2 Test Setup



7.3 Test Procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) The bandwidth is measured at an amplitude level reduced 6dB from the reference level. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst –case (i.e the widest) bandwidth.
- (3) Measure the channel separation the spectrum analyzer was set to Resolution Bandwidth:100 kHz, and Video Bandwidth:300 kHz, Detector: Peak, Sweep Time set auto.

7.4 EUT Operating Condition


The EUT was set to continuously transmitting in each mode and low, middle and high channel for the test.

7.5 Test Data

EUT:	Wireless network HD camera		Model:	WSC-580W
Temperature:	25 °C		Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz			
Test Mode:	TX 802.11B Mode			
Channel frequency (MHz)	6dB Bandwidth (MHz)		99% Bandwidth (MHz)	Limit (MHz)
2412	9.603		12.9197	>=0.5
2437	9.595		12.7508	
2462	9.193		12.5575	


802.11B Mode

2412 MHz




802.11B Mode

2437 MHz





802.11B Mode


2462 MHz




EUT:	Wireless network HD camera	Model:	WSC-580W
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Test Mode:	TX 802.11G Mode		
Channel frequency (MHz)	6dB Bandwidth (MHz)	99% Bandwidth (MHz)	Limit (MHz)
2412	15.623	16.3873	>=0.5
2437	15.410	16.3863	
2462	15.148	16.3937	
802.11G Mode			
2412 MHz			









EUT:	Wireless network HD camera	Model:	WSC-580W
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Test Mode:	TX 802.11N(HT20) Mode		
Channel frequency (MHz)	6dB Bandwidth (MHz)	99% Bandwidth (MHz)	Limit (MHz)
2412	16.208	17.5277	>=0.5
2437	16.093	17.5324	
2462	15.269	17.5031	
802.11N(HT20) Mode			
2412 MHz			







EUT:	Wireless network HD camera	Model:	WSC-580W
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Test Mode:	TX 802.11N(HT40) Mode		
Channel frequency (MHz)	6dB Bandwidth (MHz)	99% Bandwidth (MHz)	Limit (MHz)
2422	35.495	35.7218	>=0.5
2437	35.560	35.7609	
2452	35.475	35.7344	
802.11N(HT40) Mode			
2422 MHz			

Agilent08:17:45 Jan 5, 2017

Ref 15 dBm

Atten 25 dB

#Peak

Log

10

dB/

Offst

1

dB

Center

2.422000000 GHz

Center 2.422 GHz

#Res BW 100 kHz

#VBW 300 kHz

Sweep 8.288 ms (401 pts)

Span 80 MHz

Occupied Bandwidth

35.7218 MHz

Occ BW % Pwr99.00 %


x dB-6.00 dB


Transmit Freq Error

-16.308 kHz

x dB Bandwidth

35.495 MHz





8. Peak Output Power Test

8.1 Test Standard and Limit


8.1.1 Test Standard

FCC Part 15.247 (b)

8.1.2 Test Limit

FCC Part 15 Subpart C(15.247)/RSS-210		
Test Item	Limit	Frequency Range(MHz)
Peak Output Power	1 Watt or 30 dBm	2400~2483.5

8.2 Test Setup



8.3 Test Procedure

The measurement is according to section 9.1.2 of KDB 558074 D01 DTS Meas Guidance v03r05.


The EUT was connected to RF power meter via a broadband power sensor as show the block above. The power sensor video bandwidth is greater or equal to the DTS bandwidth of the equipment.


8.4 EUT Operating Condition


The EUT was set to continuously transmitting in the max power during the test.

8.5 Test Data

EUT:	Wireless network HD camera	Model:	WSC-580W
Temperature:	25 ℃	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Mode	Channel frequency (MHz)	Test Result (dBm)	Limit (dBm)
802.11b	2412	17.80	30
	2437	17.60	
	2462	18.36	
802.11g	2412	15.81	
	2437	15.98	
	2462	15.99	
802.11n (HT20)	2412	14.82	
	2437	14.73	
	2462	15.06	
802.11n (HT40)	2422	14.85	
	2437	14.70	
	2452	15.02	
Result: PASS			







9. Power Spectral Density Test


9.1 Test Standard and Limit

9.1.1 Test Standard
FCC Part 15.247 (e)

9.1.2 Test Limit

FCC Part 15 Subpart C(15.247)		
Test Item	Limit	Frequency Range(MHz)
Power Spectral Density	8dBm(in any 3 kHz)	2400~2483.5

9.2 Test Setup



9.3 Test Procedure

The EUT was directly connected to the Spectrum Analyzer and antenna output port as show in the block diagram above. The measurement according to section 10.2 of KDB 558074 D01 DTS Meas Guidance v03r05.

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Set analyser center frequency to DTS channel center frequency.
- (3) Set the span to 1.5 times the DTS bandwidth.
- (4) Set the RBW to: 3 kHz
- (5) Set the VBW to: 10 kHz
- (6) Detector: peak
- (7) Sweep time: auto
- (8) Allow trace to fully stabilize. Then use the peak marker function to determine the maximum amplitude level.

9.4 EUT Operating Condition

The EUT was set to continuously transmitting in each mode and low, middle and high channel for the test.

9.5 Test Data

EUT:	Wireless network HD camera	Model:	WSC-580W
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Test Mode:	TX 802.11B Mode		
Channel Frequency (MHz)	Power Density (3 kHz/dBm)	Limit (dBm)	
2412	-5.688	8	
2437	-5.571		
2462	-4.873		
802.11B Mode			
2412 MHz			

Agilent

09:07:47 Jan 5, 2017

Ref 15 dBm

Atten 25 dB

Mkr1 2.4129000 GHz

-5.688 dBm

Peak

Log

10

dB/

Offst

1

dB

Marker

2.412900000 GHz

-5.688 dBm

M1 S2

S3 FC

AA


Center 2.412 GHz


#Res BW 3 kHz


#VBW 10 kHz


Sweep 1.715 s (401 pts)


Span 15 MHz





























10. Antenna Requirement

10.1 Standard Requirement

10.1.1 Standard

FCC Part 15.203

10.1.2 Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

10.2 Antenna Connected Construction

The directional gains of the antenna used for transmitting is 3.5 dBi, and the antenna de-signed with permanent attachment and no consideration of replacement. Please see the EUT photo for details.

Result

The EUT antenna is a dipole Antenna. It complies with the standard requirement.

Antenna Type
☐ Permanent attached antenna
☒ Unique connector antenna
☐ Professional installation antenna

-----END OF REPORT-----