

Label

DynaScan

Model Code : *****

P/N Code : 9G*****

Model Name : 3E64450

Rating : 100-240V ~ 50/60Hz 3 A

S/N Code





Contains FCC ID: 2AKWY-FBP207



Contains IC: 35225-FBP207
CAN ICES(A) / NMB(A)



CONFORMS TO
UL STD. 62368-1
CERTIFIED TO
CSA STD. C22.2
NO. 62368-1



*****株式会社

Intertek
5022047

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: 1) This device may not cause harmful interference, and 2) this device must accept any interference received, including interference that may cause undesired operation.

WARNING
This apparatus shall be connected to a socket-outlet with earthing connection. Apparatus stikprop skal tilsluttes en stikkontakt med jord som giver forbindelse til stikproppens jord.
Laite on liitettävä suojakoskettimilla varustettuun pistorasiaan.
Apparatet må tilkoples jordet stikkontakt.
Apparaten skall anslutas till jordat uttag.

AVERTISSEMENT
Cet appareil doit être relié à la terre. N'enlevez jamais les moins qualifié de le faire.

Stability Hazard
The display set may fall, causing serious personal injury or death. To prevent injury, this display must be securely attached to the floor/wall in accordance with the installation instructions.

DynaScan Technology Corp. 6F, No. 88, Wenmao Rd., Guishan Dist., Taoyuan City 333001, Taiwan Made in Taiwan

Label location

