



RF MEASUREMENT REPORT

FCC ID: 2AKWY-FBP207
IC: 35225-FBP207
Applicant: Dynascan Technology Corp.
Product: SE3 Wi-Fi 6 Radio Module
Model No.: SKI.WB800D80U.5
Brand Name: DynaScan
FCC Classification: Digital Transmission System (DTS)
FCC Rule Part(s): Part 15 Subpart C (Section 15.247)
ISED Rule(s): RSS-247 Issue 4, RSS-GEN Issue 5
Result: Complies
Received Date: 2026-06-25
Test Date: 2026-07-17~2026-07-31

Reviewed By:


Paddy Chen

Paddy Chen

Approved By:

Chenz Ker

Chenz Ker



The test results relate only to the samples tested.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report. Testing was performed in accordance with the applicable measurement procedures. The test results reported herein apply only to the specific item(s) tested.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Taiwan) Co., Ltd.

Revision History

Report No.	Version	Description	Issue Date	Note
2606TW6702-U2	V1.0	Original Report	2026-09-17	Valid

Report Reference: 2606TW6701-U1 (Original)

(FCC Grant Date: 09/15/2026, FCC ID: 2AKWY-FBP207)

(ISED Grant Date: 09/15/2026, IC: 35225-FBP207)

Update Scope: Addition of host product

Details of Modifications: Addition of host product, Product Name: Display, Model No.: 3E64450.

Therefore, based on the evaluation and the worst-case configuration determined from the original report data, conducted output power testing was performed, and radiated spurious emission / band edge tests were performed for verification.

This product includes two SKUs. SKU 1 was used as the main test configuration, while SKU 2 was evaluated by verification testing. All corresponding test data are included in this report.

CONTENTS

Description	Page
1. General Information	5
1.1. Applicant	5
1.2. Manufacturer	5
1.3. Testing Facility	5
1.4. Product Information	6
1.5. Radio Specification under Test	7
1.6. Working Frequencies	8
1.7. Antenna Details	9
2. Test Configuration	10
2.1. Test Mode	10
2.2. Test System Connection Diagram	11
2.3. Test Software	11
2.4. Applied Standards	12
2.5. Test Environment Condition	12
3. Antenna Requirements	13
4. Measuring Instrument	14
5. Decision Rules and Measurement Uncertainty	15
5.1. Decision Rules	15
5.2. Measurement Uncertainty	15
6. Test Result	16
6.1. Summary	16
6.2. 6 dB & 99% Bandwidth Measurement	17
6.2.1. Test Limit	17
6.2.2. Test Procedure	17
6.2.3. Test Setting	17
6.2.4. Test Setup	17
6.2.5. Test Result	18
6.3. Output Power and EIRP Measurement	19
6.3.1. Test Limit	19
6.3.2. Test Procedure	19
6.3.3. Test Setting	19
6.3.4. Test Setup	19
6.3.5. Test Result	19
6.4. Power Spectral Density Measurement	20
6.4.1. Test Limit	20

6.4.2.	Test Procedure	20
6.4.3.	Test Setting	20
6.4.4.	Test Setup	20
6.4.5.	Test Result	21
6.5.	Conducted Band Edge and Out-of-Band Emissions Measurement	22
6.5.1.	Test Limit	22
6.5.2.	Test Procedure	22
6.5.3.	Test Setting	22
6.5.4.	Test Setup	22
6.5.5.	Test Result	23
6.6.	Radiated Spurious Emissions Measurement.....	24
6.6.1.	Test Limit	24
6.6.2.	Test Procedure	25
6.6.3.	Test Setting	25
6.6.4.	Test Setup	27
6.6.5.	Test Result	29
6.7.	Radiated Restricted Band Edge Measurement	30
6.7.1.	Test Limit	30
6.7.2.	Test Procedure	32
6.7.3.	Test Setting	32
6.7.4.	Test Setup	33
6.7.5.	Test Result	33
6.8.	AC Conducted Emissions Measurement	34
6.8.1.	Test Limit	34
6.8.2.	Test Setup	34
6.8.3.	Test Result	34
Appendix A - Test Result.....		35
A.1	Output Power Test Result	35
A.2	EIRP Test Result	37
A.3	Radiated Spurious Emissions Test Result	39
A.4	Radiated Restricted Band Edge Test Result.....	47
Appendix B - Test Setup Photograph		59
Appendix C - External Photograph		59
Appendix D - Internal Photograph		59

1. General Information

1.1. Applicant

Dynascan Technology Corp.

6F, No.88, Wenmao Rd., Guishan Dist., Taoyuan City 333001, Taiwan

1.2. Manufacturer

Dynascan Technology Corp.

6F, No.88, Wenmao Rd., Guishan Dist., Taoyuan City 333001, Taiwan

1.3. Testing Facility

☒	Test Site 1 - MRT Taiwan Laboratory
	Laboratory Location No. 38, Fuxing 2nd Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)
	Laboratory Accreditations
	TAF: 3261 FCC: 291082, TW3261 ISED: TW3261
☐	Test Site 2 - MRT Taiwan Laboratory
	Laboratory Location No. 64, Wenming Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)
	Laboratory Accreditations
	TAF: 3261 FCC: 933489, TW0041 ISED: TW3261

1.4. Product Information

Product Name	SE3 Wi-Fi 6 Radio Module
Model No.	SKI.WB800D80U.5
Wi-Fi Specification	802.11a/b/g/n/ac/ax
Antenna Information	Refer to section 1.7
Operating Temperature	0 ~ 45 °C
Operating Environment	Indoor Use
Power Type	AC Input
Note: The information of the EUT (Equipment Under Test) was provided by the manufacturer. The accuracy, completeness, and validity of the information are solely the responsibility of the manufacturer.	

Note:

SKU Difference Explanation	
SKU 1	The outer casing of the mechanism is a metal back plate with no openings.
SKU 2	The outer shell of the mechanism is a metal back plate with openings.

1.5. Radio Specification under Test

Frequency Range	2400 ~ 2483.5 MHz	
Channel Number	802.11b/g/n-HT20/ax-HE20: 11 802.11n-HT40/ax-HE40: 7	
Type of Modulation	802.11b: DSSS 802.11g/n: OFDM 802.11ax: OFDMA	
Data Rate	802.11b: 1/2/5.5/11 Mbps 802.11g: 6/9/12/18/24/36/48/54 Mbps 802.11n: up to 300 Mbps 802.11ax: up to 573.6 Mbps	
Channel Puncturing Function	☐ Supported	☒ Unsupported
Support RU	☒ Full RU	☐ Partial RU

1.6. Working Frequencies

802.11b/g/n-HT20/ax-HE20

Channel	Frequency	Channel	Frequency	Channel	Frequency
01	2412 MHz	02	2417 MHz	03	2422 MHz
04	2427 MHz	05	2432 MHz	06	2437 MHz
07	2442 MHz	08	2447 MHz	09	2452 MHz
10	2457 MHz	11	2462 MHz	--	--

802.11n-HT40/ax-HE40

Channel	Frequency	Channel	Frequency	Channel	Frequency
03	2422 MHz	04	2427 MHz	05	2432 MHz
06	2437 MHz	07	2442 MHz	08	2447 MHz
09	2452 MHz	--	--	--	--

1.7. Antenna Details

Technology	Frequency Range (MHz)	Antenna Type	Max Peak Gain (dBi)
2.4GHz Wi-Fi	2412 ~ 2472	Metal Antenna	-3.04
5GHz Wi-Fi	5180 ~ 5825		-2.31

Note: The antenna gain is from antenna data sheet provided by the manufacturer.


2. Test Configuration

2.1. Test Mode

Mode 1: Transmit by 802.11b (1 Mbps)
Mode 2: Transmit by 802.11g (6 Mbps)
Mode 3: Transmit by 802.11n-HT20 (MCS0)
Mode 4: Transmit by 802.11n-HT40 (MCS0)
Mode 5: Transmit by 802.11ax-HE20 (MCS0)
Mode 6: Transmit by 802.11ax-HE40 (MCS0)
Note 1: All modes of operation and data rates were investigated, so all RF test requirements shall be executed at the worst data rate which power is the greatest.

2.2. Test System Connection Diagram

The device was tested per the guidance ANSI C63.10-2020 was used to reference the appropriate EUT setup for radiated emissions testing and AC conducted emissions testing.



2.3. Test Software

The test utility software used during testing was “adb.exe”.

2.4. Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15.247
- RSS-247 Issue 4
- RSS-GEN Issue 5
- KDB 558074 D01 v05r02
- KDB 662911 D01 v02r01
- ANSI C63.10-2020
- ANSI C63.10-2020/Cor1-2023
- ANSI C63.10a-2024

2.5. Test Environment Condition

Ambient Temperature	15 ~ 35 °C
Relative Humidity	20 ~ 75%RH

3. Antenna Requirements

Excerpt from §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antenna of the device is **permanently attached**.
- There are no provisions for connection to an external antenna.

Conclusion:

The unit complies with the requirement of §15.203.

4. Measuring Instrument

Instrument	Manufacturer	Model No.	Asset No.	Cali. Interval	Cali. Due Date	Test Site
Active Loop Antenna	SCHWARZBECK	FMZB 1519B	MRTTWA00002	1 year	2027/4/15	TW-AC1
Broadband TRILOG Antenna	SCHWARZBECK	VULB 9162	MRTTWA00086	1 year	2026/11/13	TW-AC1
Broadband Hornantenna	RFSPIN	DRH18-E	MRTTWA00106	1 year	2027/3/4	TW-AC1
Broadband Preamplifier	EMC Instruments corporation	EMC118A45SEE	MRTTWA00107	1 year	2027/3/4	TW-AC1
Breitband Hornantenna	SCHWARZBECK	BBHA 9170	MRTTWA00004	1 year	2027/3/25	TW-AC1
Broadband Amplifier	SCHWARZBECK	BBV 9721	MRTTWA00006	1 year	2027/3/24	TW-AC1
EMI Test Receiver	R&S	ESR3	MRTTWA00009	1 year	2027/3/4	TW-AC1
Signal Analyzer	R&S	FSV40	MRTTWA00007	1 year	2027/3/12	TW-AC1
EXA Signal Analyzer	KEYSIGHT	N9010A	MRTTWA00012	1 year	2026/10/20	TW-SR7
EXA Signal Analyzer	KEYSIGHT	N9010B	MRTTWA00074	1 year	2027/7/13	TW-SR7
X-Series USB Peak and Average Power Sensor	KEYSIGHT	U2021XA	MRTTWA00014	1 year	2027/4/14	TW-SR7
X-Series USB Peak and Average Power Sensor	KEYSIGHT	U2021XA	MRTTWA00015	1 year	2027/3/10	TW-SR7

Software	Version	Function
e3	9.160520a	EMI Test Software

5. Decision Rules and Measurement Uncertainty

5.1. Decision Rules

The Decision Rule is based on Simple Acceptance in accordance with ISO Guide 98-4: 2012 Clause 8.2.

(Measurement uncertainty is not taken into account when stating conformity with a specified requirement.)

5.2. Measurement Uncertainty

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.

AC Conducted Emission Measurement
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): 150kHz~30MHz: $\pm 2.53\text{dB}$
Radiated Emission Measurement
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): 9kHz ~ 1GHz: $\pm 4.25\text{dB}$ 1GHz ~ 40GHz: $\pm 4.45\text{dB}$
Conducted Power (Carrier Power / Power Density)
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): $\pm 0.84\text{dB}$
Conducted Spurious Emission
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): $\pm 2.65\text{ dB}$
Occupied Bandwidth
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): $\pm 3.3\%$
Temp. / Humidity
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): $\pm 0.82^\circ\text{C} / \pm 3\%$
Frequency Error
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$): $\pm 78.4\text{Hz}$

6. Test Result

6.1. Summary

FCC Section(s)	RSS Section(s)	Test Description	Test Condition	Verdict
15.247(a)(2)	RSS-247 [6.3.1]	6 dB Bandwidth	Conducted	N/A
--	RSS-Gen [6.7]	99% Bandwidth		N/A
15.247(b)(3)	RSS-247 [6.3.2]	Output Power and EIRP		Pass
15.247(e)	RSS-247 [6.3.1]	Power Spectral Density		N/A
15.247(d)	RSS-247 [6.6]	Band Edge / Out-of-Band Emissions		N/A
15.205 15.209	RSS-Gen [8.9], [8.10]	General Field Strength (Restricted Bands and Radiated Emissions)	Radiated	Pass
15.207	RSS-Gen [8.8]	AC Conducted Emissions 150 kHz - 30 MHz	Line Conducted	N/A

Notes:

1. The analyzer plots shown in this section were captured using a correction table to account for cable and attenuator losses in the system connecting the EUT to the analyzer across relevant frequencies.

6.2. 6 dB & 99% Bandwidth Measurement

6.2.1. Test Limit

The minimum 6 dB bandwidth shall be at least 500 kHz.

6.2.2. Test Procedure

ANSI C63.10a-2024 - Section 6.9.3 (99% Bandwidth)

ANSI C63.10-2020 - Section 11.8 (6 dB Bandwidth)

6.2.3. Test Setting

6 dB Bandwidth


1. The Spectrum's automatic bandwidth measurement capability was used to perform the 6 dB bandwidth measurement. The "X" dB bandwidth parameter was set to $X = 6$. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1% to 5% of the OBW, but not less than 100 kHz
3. VBW $\geq 3 \times$ RBW
4. Detector = Peak
5. Trace mode = Max hold
6. Sweep = Auto couple
7. Allow the trace to stabilize

99% Bandwidth

1. Span = 1.5 times to 5 times the OBW
2. RBW = 1% to 5% the OBW, without going below 10 kHz.
3. VBW $\geq 3 \times$ RBW
4. Detector = Peak
5. Trace mode = Max hold
6. Sweep = Auto couple
7. Allow the trace to stabilize

6.2.4. Test Setup

Spectrum Analyzer



6.2.5. Test Result

N/A.

6.3. Output Power and EIRP Measurement

6.3.1. Test Limit

FCC Part15C:

The maximum output power shall be less 1 Watt (30 dBm).

The conducted output power limit specified in paragraph FCC Part 15.247(b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs FCC Part 15.247(b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

IC RSS-247:

The maximum conducted output power shall not exceed 1 Watt (30 dBm) and the EIRP shall not exceed 4 Watt (36 dBm).

6.3.2. Test Procedure


ANSI C63.10-2020 - Section 11.9.2.3.2

6.3.3. Test Setting

Average Power Measurement

Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter.

6.3.4. Test Setup



6.3.5. Test Result

Refer to Appendix A.1& A.2.

6.4. Power Spectral Density Measurement

6.4.1. Test Limit

The maximum permissible power spectral density is 8 dBm in any 3 kHz band.

The same method of determining the conducted output power shall be used to determine the power spectral density.

6.4.2. Test Procedure


ANSI C63.10-2020 - Section 11.10.5

6.4.3. Test Setting

1. Measure the duty cycle (x) of the transmitter output signal
2. Set instrument center frequency to DTS channel center frequency
3. Span > 1.5 times the OBW
4. RBW = 10 kHz
5. VBW $\geq 3 \times$ RBW
6. Detector = RMS
7. Ensure that the number of measurement points in the sweep $\geq 2 \times$ Span/RBW
8. Sweep time = Auto couple
9. Don't use sweep triggering; Allow sweep to "free run".
10. Employ trace averaging (RMS) mode over a minimum of 100 traces
11. Use the peak marker function to determine the maximum amplitude level
12. If duty cycle < 98%, add $10\log(1/x)$, where x is the duty cycle measured in step 1, to the measured PSD to compute the average PSD during the actual transmission time. If duty cycle $\geq 98\%$, no need to add $10\log(1/x)$.
13. If measured value exceeds requirement specified by regulatory agency, then reduce RBW (but no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span to meet the minimum measurement point requirement as the RBW is reduced).

6.4.4. Test Setup

Spectrum Analyzer



6.4.5. Test Result

N/A.

6.5. Conducted Band Edge and Out-of-Band Emissions Measurement

6.5.1. Test Limit

The limit for out-of-band spurious emissions at the band edge is 30 dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100 kHz bandwidth per the PSD procedure.

6.5.2. Test Procedure

ANSI C63.10-2020 - Section 11.11

6.5.3. Test Setting


Reference level measurement

1. Set instrument center frequency to DTS channel center frequency
2. Span ≥ 1.5 times the DTS bandwidth
3. RBW = 100 kHz
4. VBW $\geq 3 \times$ RBW
5. Detector = Peak
6. Sweep time = Auto couple
7. Trace mode = Max hold
8. Allow trace to fully stabilize

Emission level measurement

1. Set the center frequency and span to encompass frequency range to be measured
2. RBW = 100 kHz
3. VBW $\geq 3 \times$ RBW
4. Detector = Peak
5. Trace mode = Max hold
6. Sweep time = Auto couple
7. The trace was allowed to stabilize

6.5.4. Test Setup



6.5.5. Test Result

N/A.

6.6. Radiated Spurious Emissions Measurement

6.6.1. Test Limit

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table per Section 15.209.

FCC Part 15 Subpart C Paragraph 15.209		
Frequency [MHz]	Field Strength [$\mu\text{V/m}$]	Measured Distance [Meters]
0.009 - 0.490	2400/F (kHz)	300
0.490 - 1.705	24000/F (kHz)	30
1.705 - 30	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3
18000 - 40000	1500	1

All out of band emissions appearing in a restricted band as specified in Section 8.10 of the RSS-Gen Issue 5 must not exceed the limits shown in Table per Section 8.9.

RSS-Gen Section 8.9		
Frequency [MHz]	Field Strength [$\mu\text{A/m}$]	Measured Distance [Meters]
0.009 - 0.490	6.37/F (kHz)	300
0.490 - 1.705	63.7/F (kHz)	30
1.705 - 30	0.08	30
Frequency [MHz]	Field Strength [$\mu\text{V/m}$]	Measured Distance [Meters]
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3
18000 - 40000	1500	1

Note: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

6.6.2. Test Procedure

ANSI C63.10-2020 - Section 11.11 & 11.12

ANSI C63.10-2020 - Section 6.3 (General Requirements)

ANSI C63.10-2020 - Section 6.4 (Standard test method below 30 MHz)

ANSI C63.10-2020 - Section 6.5 (Standard test method above 30 MHz to 1 GHz)

ANSI C63.10-2020 - Section 6.6 (Standard test method above 1 GHz)

6.6.3. Test Setting

Table 1 - RBW as a function of frequency

Frequency	RBW
9 ~ 150 kHz	200 ~ 300 Hz
0.15 ~ 30 MHz	9 ~ 10 kHz
30 ~ 1000 MHz	100 ~ 120 kHz
> 1000 MHz	1 MHz

Quasi-Peak Measurements below 1 GHz

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. Span was set greater than 1 MHz
3. RBW = as specified in Table 1
4. VBW $\geq 3 \times$ RBW
5. Detector = CISPR quasi-peak
6. Sweep time = Auto couple
7. Trace was allowed to stabilize

Peak Measurements above 1 GHz

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1 MHz
3. VBW $\geq 3 \times$ RBW
4. Detector = Peak
5. Sweep time = Auto couple
6. Trace mode = Max hold
7. Trace was allowed to stabilize


Average Measurements above 1 GHz (Method VB)

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest


2. RBW = 1 MHz
3. VBW; if the EUT is configured to transmit with duty cycle $\geq 98\%$, set VBW = 10 Hz
If the EUT duty cycle is $< 98\%$, set VBW $\geq 1/T$. T is the minimum transmission duration.
4. As an alternative, the instrument may be set to linear detector mode. Ensure that video filtering is applied in linear voltage domain (rather than in a log or dB domain). Some instruments require linear display mode in order to accomplish this. Others have a setting for Average-VBW Type, which can be set to "Voltage" regardless of the display mode
5. Detector = Peak
6. Sweep time = Auto
7. Trace mode = Max hold
8. Trace was allowed to stabilize

6.6.4. Test Setup


Below 30 MHz Test Setup:




Below 1 GHz Test Setup:



Above 1 GHz Test Setup:



18GHz-40GHz Test Setup:



6.6.5. Test Result

Refer to Appendix A.3.

6.7. Radiated Restricted Band Edge Measurement

6.7.1. Test Limit

For 15.205 requirement:

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a) of FCC part 15, must also comply with the radiated emission limits specified in Section 15.209(a).

Frequency (MHz)	Frequency (MHz)	Frequency (MHz)	Frequency (GHz)
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)
13.36 - 13.41	--	--	--

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table per Section 15.209.

FCC Part 15 Subpart C Paragraph 15.209		
Frequency [MHz]	Field Strength [μV/m]	Measured Distance [Meters]
0.009 - 0.490	2400/F (kHz)	300
0.490 - 1.705	24000/F (kHz)	30
1.705 - 30	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

For RSS-Gen Section 8.10 requirement:

Radiated emissions which fall in the restricted bands, as defined in Section 8.10 of RSS-Gen, must also comply with the radiated emission limits specified in Section 8.9.

Frequency (MHz)	Frequency (MHz)	Frequency (GHz)
0.090 - 0.110	149.9 - 150.05	9.0 - 9.2
0.495 - 0.505	156.52475 - 156.52525	9.3 - 9.5
2.1735 - 2.1905	156.7 - 156.9	10.6 - 12.7
3.020 - 3.026	162.0125 - 167.17	13.25 - 13.4
4.125 - 4.128	167.72 - 173.2	14.47 - 14.5
4.17725 - 4.17775	240 - 285	15.35 - 16.2
4.20725 - 4.20775	322 - 335.4	17.7 - 21.4
5.677 - 5.683	399.9 - 410	22.01 - 23.12
6.215 - 6.218	608 - 614	23.6 - 24.0
6.26775 - 6.26825	960 - 1427	31.2 - 31.8
6.31175 - 6.31225	1435 - 1626.5	36.43 - 36.5
8.291 - 8.294	1645.5 - 1646.5	Above 38.6
8.362 - 8.366	1660 - 1710	* Certain frequency bands listed in table 7 and in bands above 38.6 GHz are designated for license exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.
8.37625 - 8.38675	1718.8 - 1722.2	
8.41425 - 8.41475	2200 - 2300	
12.29 - 12.293	2310 - 2390	
12.51975 - 12.52025	2483.5 - 2500	
12.57675 - 12.57725	2655 - 2900	
13.36 - 13.41	3260 - 3267	
16.42 - 16.423	3332 - 3339	
16.69475 - 16.69525	3345.8 - 3358	
16.80425 - 16.80475	3500 - 4400	
25.5 - 25.67	4500 - 5150	
37.5 - 38.25	5350 - 5460	
73 - 74.6	7250 - 7750	
74.8 - 75.2	8025 - 8500	
108 - 138	--	

All out of band emissions appearing in a restricted band as specified in Section 8.10 of the RSS-Gen must not exceed the limits shown in Table per Section 8.9.

RSS-Gen Section 8.9		
Frequency [MHz]	Field Strength [$\mu\text{A/m}$]	Measured Distance [Meters]
0.009 - 0.490	6.37/F (kHz)	300
0.490 - 1.705	63.7/F (kHz)	30
1.705 - 30	0.08	30
Frequency [MHz]	Field Strength [$\mu\text{V/m}$]	Measured Distance [Meters]
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3
Note: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.		

6.7.2. Test Procedure

ANSI C63.10-2020 - Section 6.3 & 6.6 & 11.12

6.7.3. Test Setting

Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1 MHz
3. VBW $\geq 3 \times$ RBW
4. Detector = Peak
5. Sweep time = Auto couple
6. Trace mode = Max hold
7. Trace was allowed to stabilize


Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1 MHz
3. VBW; If the EUT is configured to transmit with duty cycle $\geq 98\%$, set VBW = 10 Hz.

If the EUT duty cycle is $< 98\%$, set VBW $\geq 1/T$. T is the minimum transmission duration.

4. As an alternative, the instrument may be set to linear detector mode. Ensure that video filtering is applied in linear voltage domain (rather than in a log or dB domain). Some instruments require linear display mode in order to accomplish this. Others have a setting for Average-VBW Type, which can be set to "Voltage" regardless of the display mode
5. Detector = Peak
6. Sweep time = Auto
7. Trace mode = Max hold
8. Allow max hold to run for at least 50 times (1/duty cycle) traces

6.7.4. Test Setup



6.7.5. Test Result

Refer to Appendix A.4.

6.8. AC Conducted Emissions Measurement


6.8.1. Test Limit

FCC Part 15 Subpart C Paragraph 15.207 / RSS-Gen Issue 5 Section 8.8 Limits		
Frequency (MHz)	QP (dB μ V)	AV (dB μ V)
0.15 - 0.50	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30	60	50

Note 1: The lower limit shall apply at the transition frequencies.

Note 2: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

6.8.2. Test Setup



6.8.3. Test Result

N/A.

Appendix A - Test Result

A.1 Output Power Test Result

Test Site	SR7	Test Engineer	Wen
Test Date	2026-07-17		

SKU1

Test Mode	Data Rate / MCS	Channel No.	Freq. (MHz)	Average Power (dBm)	Limit (dBm)
11b	1 Mbps	01	2412	19.04	≤ 30.00
11b	1 Mbps	06	2437	19.02	≤ 30.00
11b	1 Mbps	11	2462	18.93	≤ 30.00
11g	6 Mbps	01	2412	17.28	≤ 30.00
11g	6 Mbps	06	2437	19.44	≤ 30.00
11g	6 Mbps	11	2462	16.92	≤ 30.00
11n-HT20	MCS0	01	2412	16.92	≤ 30.00
11n-HT20	MCS0	06	2437	19.77	≤ 30.00
11n-HT20	MCS0	11	2462	17.53	≤ 30.00
11n-HT40	MCS0	03	2422	16.39	≤ 30.00
11n-HT40	MCS0	06	2437	17.20	≤ 30.00
11n-HT40	MCS0	09	2452	16.06	≤ 30.00
11ax-HE20	MCS0	01	2412	16.63	≤ 30.00
11ax-HE20	MCS0	06	2437	19.58	≤ 30.00
11ax-HE20	MCS0	11	2462	17.46	≤ 30.00
11ax-HE40	MCS0	03	2422	16.44	≤ 30.00
11ax-HE40	MCS0	06	2437	17.13	≤ 30.00
11ax-HE40	MCS0	09	2452	16.01	≤ 30.00

Test Site	SR7	Test Engineer	Wen
Test Date	2026-07-17		

SKU2

Test Mode	Data Rate / MCS	Channel No.	Freq. (MHz)	Average Power (dBm)	Limit (dBm)
11ax-HE20	MCS0	01	2412	16.32	≤ 30.00
11ax-HE20	MCS0	06	2437	19.18	≤ 30.00
11ax-HE20	MCS0	11	2462	17.31	≤ 30.00

A.2 EIRP Test Result

Test Site	SR7	Test Engineer	Wen
Test Date	2026-07-17		

SKU1

Test Mode	Data Rate/ MCS	Channel No.	Freq. (MHz)	Average Power (dBm)	EIRP (dBm)	Limit (dBm)
11b	1 Mbps	01	2412	19.04	16.00	≤ 36.00
11b	1 Mbps	06	2437	19.02	15.98	≤ 36.00
11b	1 Mbps	11	2462	18.93	15.89	≤ 36.00
11g	6 Mbps	01	2412	17.28	14.24	≤ 36.00
11g	6 Mbps	06	2437	19.44	16.40	≤ 36.00
11g	6 Mbps	11	2462	16.92	13.88	≤ 36.00
11n-HT20	MCS0	01	2412	16.92	13.88	≤ 36.00
11n-HT20	MCS0	06	2437	19.77	16.73	≤ 36.00
11n-HT20	MCS0	11	2462	17.53	14.49	≤ 36.00
11n-HT40	MCS0	03	2422	16.39	13.35	≤ 36.00
11n-HT40	MCS0	06	2437	17.20	14.16	≤ 36.00
11n-HT40	MCS0	09	2452	16.06	13.02	≤ 36.00
11ax-HE20	MCS0	01	2412	16.63	13.59	≤ 36.00
11ax-HE20	MCS0	06	2437	19.58	16.54	≤ 36.00
11ax-HE20	MCS0	11	2462	17.46	14.42	≤ 36.00
11ax-HE40	MCS0	03	2422	16.44	13.40	≤ 36.00
11ax-HE40	MCS0	06	2437	17.13	14.09	≤ 36.00
11ax-HE40	MCS0	09	2452	16.01	12.97	≤ 36.00

Note: EIRP (dBm) = Average Power (dBm) + Antenna Gain (dBi).



Test Site	SR7	Test Engineer	Wen
Test Date	2026-07-17		


SKU2

Test Mode	Data Rate/ MCS	Channel No.	Freq. (MHz)	Average Power (dBm)	EIRP (dBm)	Limit (dBm)
11ax-HE20	MCS0	01	2412	16.32	13.28	≤ 36.00
11ax-HE20	MCS0	06	2437	19.18	16.14	≤ 36.00
11ax-HE20	MCS0	11	2462	17.31	14.27	≤ 36.00

Note: EIRP (dBm) = Average Power (dBm) + Antenna Gain (dBi).

A.3 Radiated Spurious Emissions Test Result

EUT	Display	Date of Test	2026-07-24
Factor	DRH18-E & BBHA 9170	Temp. / Humidity	25°C /50%
Polarity	Horizontal	Site / Test Engineer	AC1 / Todd
Test Mode	802.11ax-20MHz_TX_CH 1_ANT 0_SKU 1	Test Voltage	AC 120V/60Hz
Limit	FCC Part15C_1GHz-40GHz		




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	* 4824.000	46.21	3.54	49.75	-24.25	74.00	100	71	Peak
2	7236.000	40.43	8.22	48.65	-25.35	74.00	100	60	Peak
3	9648.000	40.25	7.32	47.58	-26.42	74.00	100	312	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Display	Date of Test	2026-07-24
Factor	DRH18-E & BBHA 9170	Temp. / Humidity	25°C /50%
Polarity	Vertical	Site / Test Engineer	AC1 / Todd
Test Mode	802.11ax-20MHz_TX_CH 1_ANT 0_SKU 1	Test Voltage	AC 120V/60Hz
Limit	FCC Part15C_1GHz-40GHz		




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4824.000	44.30	3.54	47.84	-26.16	74.00	100	360	Peak
2	7236.000	39.25	8.22	47.47	-26.53	74.00	100	360	Peak
3	* 9648.000	40.87	7.32	48.19	-25.81	74.00	100	332	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Display	Date of Test	2026-07-24
Factor	DRH18-E & BBHA 9170	Temp. / Humidity	25°C /50%
Polarity	Horizontal	Site / Test Engineer	AC1 / Todd
Test Mode	802.11ax-20MHz_TX_CH 6_ANT 0_SKU 1	Test Voltage	AC 120V/60Hz
Limit	FCC Part15C_1GHz-40GHz		




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4874.000	42.21	3.50	45.71	-28.29	74.00	100	82	Peak
2	* 7311.000	43.41	8.36	51.78	-22.22	74.00	100	82	Peak
3	9748.000	42.10	7.46	49.56	-24.44	74.00	100	54	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Display	Date of Test	2026-07-24
Factor	DRH18-E & BBHA 9170	Temp. / Humidity	25°C /50%
Polarity	Vertical	Site / Test Engineer	AC1 / Todd
Test Mode	802.11ax-20MHz_TX_CH 6_ANT 0_SKU 1	Test Voltage	AC 120V/60Hz
Limit	FCC Part15C_1GHz-40GHz		




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4874.000	42.10	3.50	45.60	-28.40	74.00	100	0	Peak
2	7311.000	39.63	8.36	47.99	-26.01	74.00	100	354	Peak
3	* 9748.000	42.30	7.46	49.76	-24.24	74.00	100	273	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Display	Date of Test	2026-07-24
Factor	DRH18-E & BBHA 9170	Temp. / Humidity	25°C /50%
Polarity	Horizontal	Site / Test Engineer	AC1 / Todd
Test Mode	802.11ax-20MHz_TX_CH 11_ANT 0_SKU 1	Test Voltage	AC 120V/60Hz
Limit	FCC Part15C_1GHz-40GHz		




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4924.000	42.34	3.61	45.95	-28.05	74.00	100	75	Peak
2	7386.000	39.06	8.12	47.18	-26.82	74.00	100	75	Peak
3	* 9848.000	41.39	8.11	49.50	-24.50	74.00	100	260	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Display	Date of Test	2026-07-24
Factor	DRH18-E & BBHA 9170	Temp. / Humidity	25°C /50%
Polarity	Vertical	Site / Test Engineer	AC1 / Todd
Test Mode	802.11ax-20MHz_TX_CH 11_ANT 0_SKU 1	Test Voltage	AC 120V/60Hz
Limit	FCC Part15C_1GHz-40GHz		




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4924.000	43.92	3.61	47.53	-26.47	74.00	100	10	Peak
2	7386.000	39.32	8.12	47.44	-26.56	74.00	100	349	Peak
3	* 9848.000	41.26	8.11	49.36	-24.64	74.00	100	69	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Display	Date of Test	2026-07-31
Factor	DRH18-E & BBHA 9170	Temp. / Humidity	25°C /52%
Polarity	Horizontal	Site / Test Engineer	AC1 / Todd
Test Mode	802.11ax-20MHz_TX_CH 1_ANT 0_SKU 2	Test Voltage	AC 120V/60Hz
Limit	FCC Part15C_1GHz-40GHz		




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	4824.000	45.35	3.54	48.89	-25.11	74.00	100	63	Peak
2	* 7236.000	41.96	8.22	50.18	-23.82	74.00	100	57	Peak
3	9648.000	41.96	7.32	49.28	-24.72	74.00	100	3	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Display	Date of Test	2026-07-31
Factor	DRH18-E & BBHA 9170	Temp. / Humidity	25°C /52%
Polarity	Vertical	Site / Test Engineer	AC1 / Todd
Test Mode	802.11ax-20MHz_TX_CH 1_ANT 0_SKU 2	Test Voltage	AC 120V/60Hz
Limit	FCC Part15C_1GHz-40GHz		




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	* 4824.000	45.89	3.54	49.43	-24.57	74.00	100	0	Peak
2	7236.000	39.18	8.22	47.39	-26.61	74.00	100	125	Peak
3	9648.000	40.91	7.32	48.23	-25.77	74.00	100	52	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB) – Preamplifier(dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

A.4 Radiated Restricted Band Edge Test Result

EUT	Display	Date of Test	2026-07-24
Factor	DRH18-E	Temp. / Humidity	25°C /50%
Polarity	Horizontal	Site / Test Engineer	AC1 / Todd
Test Mode	802.11ax-20MHz_TX_CH 1_ANT 0_SKU 1	Test Voltage	AC 120V/60Hz
Limit	FCC Part15C_1GHz-40GHz		




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	* 2385.000	36.17	31.59	67.76	-6.24	74.00	120	70	Peak
2	2390.000	35.10	31.60	66.70	-7.30	74.00	120	70	Peak
3	2408.250	78.15	31.65	109.80	N/A	N/A	120	70	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Display	Date of Test	2026-07-28
Factor	DRH18-E	Temp. / Humidity	25°C /50%
Polarity	Horizontal	Site / Test Engineer	AC1 / Todd
Test Mode	802.11ax-20MHz_TX_CH 1_ANT 0_SKU 1	Test Voltage	AC 120V/60Hz
Limit	FCC Part15C_1GHz-40GHz		




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2387.375	19.88	31.59	51.47	-2.53	54.00	120	70	Average
2	* 2390.000	21.56	31.60	53.16	-0.84	54.00	120	70	Average
3	2410.250	67.39	31.66	99.05	N/A	N/A	120	70	Average

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Display	Date of Test	2026-07-24
Factor	DRH18-E	Temp. / Humidity	25°C /50%
Polarity	Vertical	Site / Test Engineer	AC1 / Todd
Test Mode	802.11ax-20MHz_TX_CH 1_ANT 0_SKU 1	Test Voltage	AC 120V/60Hz
Limit	FCC Part15C_1GHz-40GHz		




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	* 2384.500	29.85	31.59	61.44	-12.56	74.00	145	360	Peak
2	2390.000	29.34	31.60	60.95	-13.05	74.00	145	360	Peak
3	2408.250	71.65	31.65	103.30	N/A	N/A	145	360	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Display	Date of Test	2026-07-28
Factor	DRH18-E	Temp. / Humidity	25°C /50%
Polarity	Vertical	Site / Test Engineer	AC1 / Todd
Test Mode	802.11ax-20MHz_TX_CH 1_ANT 0_SKU 1	Test Voltage	AC 120V/60Hz
Limit	FCC Part15C_1GHz-40GHz		




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2384.875	14.75	31.59	46.34	-7.66	54.00	145	360	Average
2	* 2390.000	15.50	31.60	47.10	-6.90	54.00	145	360	Average
3	2414.625	60.99	31.67	92.66	N/A	N/A	145	360	Average

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Display	Date of Test	2026-07-24
Factor	DRH18-E	Temp. / Humidity	25°C /50%
Polarity	Horizontal	Site / Test Engineer	AC1 / Todd
Test Mode	802.11ax-20MHz_TX_CH 11_ANT 0_SKU 1	Test Voltage	AC 120V/60Hz
Limit	FCC Part15C_1GHz-40GHz		




No	Frequency (MHz)	Reading (dBUV)	C.F (dB/m)	Measurement (dBUV/m)	Margin (dB)	Limit (dBUV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2458.310	77.46	31.78	109.24	N/A	N/A	125	65	Peak
2	2483.500	31.83	31.83	63.66	-10.34	74.00	125	65	Peak
3	* 2487.130	34.08	31.84	65.92	-8.08	74.00	125	65	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB).
3. Measurement (dBUV/m) = Reading(dBUV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Display	Date of Test	2026-07-28
Factor	DRH18-E	Temp. / Humidity	25°C /50%
Polarity	Horizontal	Site / Test Engineer	AC1 / Todd
Test Mode	802.11ax-20MHz_TX_CH 11_ANT 0_SKU 1	Test Voltage	AC 120V/60Hz
Limit	FCC Part15C_1GHz-40GHz		




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2460.180	67.14	31.78	98.92	N/A	N/A	125	65	Average
2	* 2483.500	21.25	31.83	53.09	-0.91	54.00	125	65	Average
3	2484.820	19.75	31.84	51.58	-2.42	54.00	125	65	Average

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Display	Date of Test	2026-07-24
Factor	DRH18-E	Temp. / Humidity	25°C /50%
Polarity	Vertical	Site / Test Engineer	AC1 / Todd
Test Mode	802.11ax-20MHz_TX_CH 11_ANT 0_SKU 1	Test Voltage	AC 120V/60Hz
Limit	FCC Part15C_1GHz-40GHz		




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2458.310	71.94	31.78	103.72	N/A	N/A	150	55	Peak
2	2483.500	28.10	31.83	59.94	-14.06	74.00	150	55	Peak
3	* 2487.570	30.02	31.84	61.86	-12.14	74.00	150	55	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Display	Date of Test	2026-07-28
Factor	DRH18-E	Temp. / Humidity	25°C /50%
Polarity	Vertical	Site / Test Engineer	AC1 / Todd
Test Mode	802.11ax-20MHz_TX_CH 11_ANT 0_SKU 1	Test Voltage	AC 120V/60Hz
Limit	FCC Part15C_1GHz-40GHz		




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2456.275	61.62	31.77	93.39	N/A	N/A	150	55	Average
2	* 2483.500	16.74	31.83	48.57	-5.43	54.00	150	55	Average
3	2487.020	15.95	31.84	47.80	-6.20	54.00	150	55	Average

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Display	Date of Test	2026-07-31
Factor	DRH18-E	Temp. / Humidity	25°C /52%
Polarity	Horizontal	Site / Test Engineer	AC1 / Todd
Test Mode	802.11ax-20MHz_TX_CH 1_ANT 0_SKU 2	Test Voltage	AC 120V/60Hz
Limit	FCC Part15C_1GHz-40GHz		




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	* 2384.625	35.00	31.59	66.59	-7.41	74.00	120	65	Peak
2	2390.000	32.26	31.60	63.86	-10.14	74.00	120	65	Peak
3	2408.375	78.07	31.65	109.72	N/A	N/A	120	65	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Display	Date of Test	2026-07-31
Factor	DRH18-E	Temp. / Humidity	25°C /52%
Polarity	Horizontal	Site / Test Engineer	AC1 / Todd
Test Mode	802.11ax-20MHz_TX_CH 1_ANT 0_SKU 2	Test Voltage	AC 120V/60Hz
Limit	FCC Part15C_1GHz-40GHz		




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2387.875	20.26	31.60	51.86	-2.14	54.00	120	65	Average
2	* 2390.000	21.82	31.60	53.42	-0.58	54.00	120	65	Average
3	2417.250	67.40	31.67	99.08	N/A	N/A	120	65	Average

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Display	Date of Test	2026-07-31
Factor	DRH18-E	Temp. / Humidity	25°C /52%
Polarity	Vertical	Site / Test Engineer	AC1 / Todd
Test Mode	802.11ax-20MHz_TX_CH 1_ANT 0_SKU 2	Test Voltage	AC 120V/60Hz
Limit	FCC Part15C_1GHz-40GHz		




No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	* 2383.875	28.37	31.58	59.95	-14.05	74.00	145	355	Peak
2	2390.000	27.75	31.60	59.35	-14.65	74.00	145	355	Peak
3	2408.375	71.42	31.65	103.07	N/A	N/A	145	355	Peak

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

EUT	Display	Date of Test	2026-07-31
Factor	DRH18-E	Temp. / Humidity	25°C /52%
Polarity	Vertical	Site / Test Engineer	AC1 / Todd
Test Mode	802.11ax-20MHz_TX_CH 1_ANT 0_SKU 2	Test Voltage	AC 120V/60Hz
Limit	FCC Part15C_1GHz-40GHz		



No	Frequency (MHz)	Reading (dBuV)	C.F (dB/m)	Measurement (dBuV/m)	Margin (dB)	Limit (dBuV/m)	Height (cm)	Angle (deg)	Remark (QP/PK/AV)
1	2388.000	13.61	31.60	45.21	-8.79	54.00	145	355	Average
2	* 2390.000	14.32	31.60	45.93	-8.07	54.00	145	355	Average
3	2410.250	60.89	31.66	92.54	N/A	N/A	145	355	Average

Note:

1. " *", means this data is the worst emission level.
2. C.F (Correction Factor) = Antenna Factor (dB/m) + Cable Loss (dB).
3. Measurement (dBuV/m) = Reading(dBuV) + C.F (Correction Factor).
4. The emission levels of other frequencies are very lower than the limit and not show in test report.

Appendix B - Test Setup Photograph

Refer to “2606TW6702-UT” file.

Appendix C - External Photograph

Refer to “2606TW6702-UE” file.

Appendix D - Internal Photograph

Refer to “2606TW6702-UI” file.

_____ The End _____