

**FCC RF EXPOSURE REPORT**

EUT	Building Automation System
Frequency band (Operating)	☒ WLAN: 2.412GHz ~ 2.462GHz ☒ WLAN: 2.422GHz ~ 2.452GHz ☐ WLAN: 5.180GHz ~ 5.240GHz ☐ WLAN: 5.190GHz ~ 5.230GHz
Device category	☐ Portable (<20cm separation) ☒ Mobile (>20cm separation)
Exposure classification	☐ Occupational/Controlled exposure (S = 5mW/cm ²) ☒ General Population/Uncontrolled exposure (S=1mW/cm ²)
Antenna diversity	☐ Single antenna ☒ Multiple antennas ☐ Tx diversity ☐ Rx diversity ☒ Tx/Rx diversity
Max. output power	26.98dBm (498.884mW)
Antenna gain (Max)	2dBi(Numeric gain:1.58)
Evaluation applied	☒ MPE Evaluation* ☐ SAR Evaluation ☐ N/A

Note:

1. The maximum output power is 26.98dBm (498.884mW) at 2422MHz (with numeric 1.58 antenna gain.)
2. DTS device is not subject to routine RF evaluation; MPE estimate is used to justify the compliance.
3. For mobile or fixed location transmitters, no SAR consideration applied. The maximum power density is 1.0 mW/cm² even if the calculation indicates that the power density would be larger.

**TEST RESULTS**

No non-compliance noted.

Calculation

Given $E = \frac{\sqrt{30 \times P \times G}}{d}$ & $S = \frac{E^2}{3770}$

Where E = Field strength in Volts / meter
 P = Power in Watts
 G = Numeric antenna gain
 d = Distance in meters
 S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{3770 d^2}$$

Changing to units of mW and cm, using:

$$P \text{ (mW)} = P \text{ (W)} / 1000 \text{ and}$$

$$d \text{ (cm)} = d \text{ (m)} / 100$$

Yields

$$S = \frac{30 \times (P/1000) \times G}{3770 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \text{Equation 1}$$

Where d = Distance in cm
 P = Power in mW
 G = Numeric antenna gain
 S = Power density in mW / cm²

Maximum Permissible Exposure

Modulation Mode	Frequency band (MHz)	Peak output power(dBm)	Peak output power(mW)	Antenna Gain (dBi)	Antenna gain (Numeric)	Distance (cm)	Power density (mW/cm2)	Limit (mW/cm2)
802.11b	2412-2462	19.66	92.4698174	2	1.58489319	20	0.0291644	1
802.11g	2412-2462	25.55	358.921935	2	1.58489319	20	0.11320173	1
802.11n HT20	2412-2462	26.47	443.608644	2	1.58489319	20	0.13991139	1
802.11n HT40	2422-2452	26.98	498.884487	2	1.58489319	20	0.15734505	1