


RF EXPOSURE REPORT

Applicant:	Clear Touch Interactive Inc		
Address:	1100 Thousand Oaks Blvd, Greenville, SC 29607, United States		
Manufacturer:	Clear Touch Interactive Inc		
Address:	1100 Thousand Oaks Blvd, Greenville, SC 29607, United States		
Product Description:	Command Studio Microphone Set		
Brand Name:	Clear Touch		
Tested Model/HVIN:	CTI-CMST01-MIC		
FCC ID:	2AL27-CMSTMIC		
Report No.:	JCF250916082-002		
Received Date:	Sep. 22, 2025		
Tested Date:	Sep. 22, 2025 - Dec. 09, 2025		
Issued Date:	Dec. 09, 2025		
Test Standards:	KDB 447498 D01 General RF Exposure Guidance v06		
Test Result:	Pass		
Prepared By:			
			
<u>Kennys Zhang/Engineer</u>		Date: Dec. 09, 2025	
Reviewed By:			
			
<u>Roger Li/Engineer</u>		Date: Dec. 09, 2025	
Approved By:			
			
<u>Talent Zhang/Engineer</u>		Date: Dec. 09, 2025	

Note: The test results in this report apply exclusively to the tested model / sample. Without written approval of Guangzhou Jingce Testing Technology Co., Ltd. the test report shall not be reproduced except in full.

Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Dec. 09, 2025	Original Report	/



Table of Contents

1. Test Report Declare 4

2. Equipment Under Test 5

 2.1. Description of EUT 5

 2.2. Description of Available Antennas 5

3. Test Laboratory 5

4. RF Exposure Measurement 6

 4.1. Requirement 6

 4.2. Limits for Maximum Permissible Exposure (MPE) 6

 4.3. Conducted Power 6

5. RF Exposure Calculation 6



1. Test Report Declare

Applicant:	Clear Touch Interactive Inc
Address:	1100 Thousand Oaks Blvd, Greenville, SC 29607, United States
Manufacturer:	Clear Touch Interactive Inc
Address:	1100 Thousand Oaks Blvd, Greenville, SC 29607, United States
Product Name	Command Studio Microphone Set
Brand Name:	Clear Touch
Model Name:	CTI-CMST01-MIC
Difference Description:	N/A

We Declare:

The equipment described above is tested by Guangzhou Jingce Testing Technology Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Guangzhou Jingce Testing Technology Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests except as provided information by clients.

用章
Service

2. Equipment Under Test

2.1. Description of EUT

EUT* Name:	Command Studio Microphone Set
Model Number:	CTI-CMST01-MIC
EUT Function Description:	Please refer to user manual of this device
Power Supply:	Input: 5V $\pm$ 2A, Output: 5V $\pm$ 0.7A
Sample No.	250916082-01-01
Hardware Version:	N/A
Software Version:	N/A
Radio Specification:	SRD 2.4G
Operation Frequency:	2.4G SRD: 2406MHz—2474MHz
Modulation:	GFSK
Antenna Type:	PCB Antenna, MAX. Gain: 2.4 dBi
Product Type:	☒ Portable device ☐ Mobile device ☐ Fixed device

Note 1: EUT is the ab. of equipment under test.

Note 2: The antenna gain is declared by the customer and the laboratory is not responsible for the accuracy of the antenna gain.

2.2. Description of Available Antennas

Test Mode	Transmit and Receive Mode	Description
2.4G SRD	☒ 1TX, 1RX	ANT 1 can be used as transmitting/receiving antenna.

3. Test Laboratory

Guangzhou Jingce Testing Technology Co., Ltd.

Add.: No.10, Hefeng No.1 street, Huangpu District, Guangzhou, Guangdong, People's Republic of China

Association for Laboratory Accreditation(A2LA). Certificate Number: 6594.03

FCC Designation Number: CN1381. Test Firm Registration Number: 486550

IC Test Firm Registration Number: 31808

Conformity Assessment Body identifier: CN0173

4. RF Exposure Measurement

4.1. Requirement

According to 447498 D01 General RF Exposure Guidance v06 The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by: $[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where: $f(\text{GHz})$ is the RF channel transmit frequency in GHz Power and distance are rounded to the nearest mW and mm before calculation The result is rounded to one decimal place for comparison

4.2. Limits for Maximum Permissible Exposure (MPE)

Band	Channel Frequency (MHz)	Limit (mW)	Limit (dBm)
BLE	2442	9.60	9.82

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$

Limit = $[3.0 \cdot (\text{min. test separation distance, mm})] / [\sqrt{f(\text{GHz})}] = (3 \cdot 5) / [\sqrt{2.442(\text{GHz})}] = 9.60\text{mW}$

4.3. Conducted Power

Band	Channel Frequency (MHz)	Average Power (dBm)
BLE	2440	1.07

5. RF Exposure Calculation

We used the maximum power between the conducted power and ERP/EIRP to perform RF exposure exemption evaluation.

Band	Channel Frequency (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	PASS/FAIL
BLE	2440	1.07	2.4	3.47	9.82	PASS

Then SAR evaluation is not required.

--END--