



Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640
Fax: +86-755-26648637
Website: www.cqa-cert.com

Report Template Version: V03
Report Template Revision Date: Mar.1st, 2017

RF Exposure Evaluation Report

Report No. : CQASZ20190600466E-02
Applicant: ShenZhen Doctors of Intelligence & Technology Co.,Ltd.
Address of Applicant: 4F,Building 2,Science & Technology Industrial Park,Pingshan Xili, Nanshan District, Shenzhen, China
Equipment Under Test (EUT):
Product: Smart Light
Model No.: DT-light
Brand Name: DoHome
FCC ID: 2AL3B-DT-LIGHT
Standards: 47 CFR Part 1.1307
47 CFR Part 1.1310
KDB447498D01 General RF Exposure Guidance v06
Date of Receipt: 2019-06-13
Date of Test: 2019-06-13 to 2019-06-16
Date of Issue: 2019-06-27
Test Result : PASS*

Tested By:

Daisy Qin

(Daisy Qin)

Reviewed By:

Aaron Ma

(Aaron Ma)

Approved By:

Jack Ai

(Jack Ai)



* In the configuration tested, the EUT complied with the standards specified above.

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CQA, this report can't be reproduced except in full.

1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20190600466E-02	Rev.01	Initial report	2019-06-27

2 Contents

	Page
1 VERSION	2
2 CONTENTS	3
3 GENERAL INFORMATION.....	4
3.1 CLIENT INFORMATION.....	4
3.2 GENERAL DESCRIPTION OF EUT	4
4 RF EXPOSURE EVALUATION	5
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT	5
4.1.1 Limits	5
4.1.2 Test Procedure.....	5
4.2 1.1.3 EUT RF EXPOSURE EVALUATION	6

3 General Information

3.1 Client Information

Applicant:	ShenZhen Doctors of Intelligence & Technology Co.,Ltd.
Address of Applicant:	4F,Building 2,Science & Technology Industrial Park,Pingshan Xili, Nanshan District, Shenzhen, China
Manufacturer:	ShenZhen Doctors of Intelligence & Technology Co.,Ltd.
Address of Manufacturer:	4F,Building 2,Science & Technology Industrial Park,Pingshan Xili, Nanshan District, Shenzhen, China

3.2 General Description of EUT

Product Name:	Smart Light
Model No.:	DT-light
Trade Mark:	DoHome
Hardware version:	V1.4
Software version:	V1.5
Operation Frequency:	IEEE 802.11b/g/n(HT20): 2412MHz to 2462MHz
Channel Numbers:	IEEE 802.11b/g, IEEE 802.11n HT20: 11 Channels
Channel Separation:	5MHz
Type of Modulation:	IEEE for 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE for 802.11g : OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11n(HT20) : OFDM (64QAM, 16QAM, QPSK,BPSK)
Transfer Rate:	IEEE for 802.11b: 1Mbps/2Mbps/5.5Mbps/11Mbps IEEE for 802.11g : 6Mbps/9Mbps/12Mbps/18Mbps/24Mbps/36Mbps/48Mbps/54Mbps IEEE for 802.11n(HT20) : 6.5Mbps/13Mbps/19.5Mbps/26Mbps/39Mbps/52Mbps/58.5Mbps/65Mbps
Product Type:	☐ Mobile ☐ Portable ☒ Fix Location
Test Software of EUT:	RF test (manufacturer declare)
Antenna Type:	PCB antenna
Antenna Gain:	0dBi
Power Supply:	AC120V/60Hz

4 RF Exposure Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

4.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

4.2 1.1.3 EUT RF Exposure Evaluation

1) For WIFI

ANT1:

Antenna Gain: 0dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.0 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Measurement Data

802.11b mode				
Test channel	Average Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2412MHz)	12.63	12.5±1	13.5	22.387
Middle(2437MHz)	13.15	13.0±1	14.0	25.119
Highest(2462MHz)	13.46	13.0±1	14.0	25.119
802.11g mode				
Test channel	Average Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2412MHz)	12.37	12.0±1.0	13.0	19.953
Middle(2437MHz)	12.56	12.5±1.0	13.5	22.387
Highest(2462MHz)	13.1	13.0±1.0	14.0	25.119
802.11n(HT20)mode				
Test channel	Average Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2412MHz)	12.45	12.0±1.0	13.0	19.953
Middle(2437MHz)	12.79	12.5±1.0	13.5	22.387
Highest(2462MHz)	12.54	12.5±1.0	13.5	22.387

The worst case:

Maximum tune-up Power (mW)	Antenna Gain (dBi)	Power Density at R = 20 cm (mW/cm ²)	Limit	Result
25.119	0	0.005	1.0	PASS

Note: 1) Refer to report No. CQASZ20190600466E-01 for EUT test Max Conducted average Output Power value.

$$2) P_d = (P_{out} * G) / (4 * \pi * R^2) = (25.119 * 1.0) / (4 * 3.1416 * 20^2) = 0.005$$