



RADIO TEST REPORT

Applicant	:	SELVAS Healthcare, Inc.
Address of Applicant	:	155, Sinseong-ro, Yuseong-gu, Daejeon, Republic of Korea
Manufacturer	:	SELVAS Healthcare, Inc.
Address of Manufacturer	:	155, Sinseong-ro, Yuseong-gu, Daejeon, Republic of Korea
Equipment under Test	:	BrailleSense 7-32
Model No.	:	H732B, H720B
FCC ID	:	2AL4D-H732B
Test Standard(s)	:	FCC Rules and Regulations Part 15 Subpart C, ANSI C63.10-2020+Cor.1-2023
Report No.	:	DDT-RE26040120-1E07
Issue Date	:	2026/09/01
Issue By	:	Guangdong Dongdian Testing Service Co., Ltd. Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808

REPORT

Table of Contents

1.	Summary of Test Results	7
2.	General Test Information.....	8
2.1.	Description of EUT	8
2.2.	Accessories of EUT	8
2.3.	Block diagram of EUT configuration for test.....	8
2.4.	Decision of final test mode	9
2.5.	Deviations of test standard	9
2.6.	Test environment conditions	9
2.7.	Test laboratory	10
2.8.	Measurement uncertainty	10
3.	Equipment Used During Conductive Test	11
4.	6dB Bandwidth	12
4.1.	Block diagram of test setup	12
4.2.	Limits	12
4.3.	Test procedure	12
4.4.	Test result.....	13
4.5.	Test graphs	14
5.	99% Bandwidth	22
5.1.	Block diagram of test setup	22
5.2.	Limits	22
5.3.	Test procedure	22
5.4.	Test result.....	23
5.5.	Test graphs	24
6.	Conducted Output Power	32
6.1.	Block diagram of test setup	32
6.2.	Limits	32
6.3.	Test procedure	32
6.4.	Test result average.....	33
7.	Power Spectral Density	34
7.1.	Block diagram of test setup	34
7.2.	Limits	34
7.3.	Test procedure	34
7.4.	Test result.....	35
7.5.	Test graphs	36
8.	Band Edge Compliance (Conducted Method).....	44
8.1.	Block diagram of test setup	44

8.2.	Limits	44
8.3.	Test procedure	44
8.4.	Test result.....	45
8.5.	Test graphs	46
9.	RF Conducted Spurious Emissions.....	52
9.1.	Block diagram of test setup	52
9.2.	Limits	52
9.3.	Test procedure	52
9.4.	Test result.....	53
9.5.	Test graphs	54
10.	Duty Cycle	78
10.1.	Block diagram of test setup	78
10.2.	Limit.....	78
10.3.	Test procedure	78
10.4.	Test result.....	79
10.5.	Test graphs	80
11.	Antenna Requirements.....	88
11.1.	Limit.....	88
11.2.	Result	88
12.	Radiated Emission	89
12.1.	Test equipment.....	89
12.2.	Block diagram of test setup	90
12.3.	Limits	91
12.4.	Assistant equipment used for test	92
12.5.	Test procedure	92
12.6.	Test result.....	94
12.7.	Test data	95
13.	Band Edge Compliance.....	107
13.1.	Test equipment.....	107
13.2.	Block diagram of test setup	107
13.3.	Limits	108
13.4.	Assistant equipment used for test	108
13.5.	Test procedure	108
13.6.	Test result.....	108
13.7.	Test data	109
14.	Power Line Conducted Emissions.....	133
14.1.	Test equipment.....	133
14.2.	Block diagram of test setup	133

14.3. Limits133

14.4. Assistant equipment used for test133

14.5. Test procedure133

14.6. Test result.....134

14.7. Test data135

15. Test Setup Photograph139

16. Photos of the EUT144

Test Report Declare

Applicant	:	SELVAS Healthcare, Inc.
Address of Applicant	:	155, Sinseong-ro, Yuseong-gu, Daejeon, Republic of Korea
Equipment under Test	:	BrailleSense 7-32
Model No.	:	H732B, H720B
Manufacturer	:	SELVAS Healthcare, Inc.
Address of Manufacturer	:	155, Sinseong-ro, Yuseong-gu, Daejeon, Republic of Korea

Test Standard Used:

FCC Rules and Regulations Part 15 Subpart C,
ANSI C63.10-2020+Cor.1-2023

We Declare:

The equipment described above is tested by Guangdong Dongdian Testing Service Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Guangdong Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

Report No.:	DDT-RE26040120-1E07		
Date of Receipt:	2026/06/04	Date of Test:	2026/06/04 - 2026/08/22

Created: Johnson Huang	Reviewed: Tiger Mo	Approved: Ella Gong
		
2026/08/17	2026/09/01	2026/09/01

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Guangdong Dongdian Testing Service Co., Ltd.

Revision History

Version	Revision Content	Issue Date	Approved
V0	Initial issue	2026/09/01	Ella Gong

1. Summary of Test Results

No.	Test Parameter	Clause No.	Condition	Result
1	6 dB Bandwidth and 99% Bandwidth	47 CFR Part 15 15.247(a)(2)	/	Pass
2	Peak Output Power	47 CFR Part 15 15.247(b)(3)	/	Pass
3	Power Spectral Density	47 CFR Part 15 15.247(e)	/	Pass
4	RF Conducted Spurious Emissions	47 CFR Part 15 15.247(d)	/	Pass
5	Radiated Emission	47 CFR Part 15 15.205, 47 CFR Part 15 15.209, 47 CFR Part 15 15.247(d)	/	Pass
6	Band Edge Compliance	47 CFR Part 15 15.205, 47 CFR Part 15 15.209, 47 CFR Part 15 15.247(d)	/	Pass
7	Antenna Requirement	47 CFR Part 15 15.203	/	Pass
8	Power Line Conducted Emissions	47 CFR Part 15 15.207(a)	/	Pass
Note: N/A is an abbreviation for Not Applicable, and means this item is not applicable for this device or no need to test according to standard.				

2. General Test Information

2.1. Description of EUT

EUT Name	: BrailleSense 7-32
Model Number	: H732B, H720B
Difference of model number	: Above models are identical in schematic, structure, only the Model Number, keyboard is different for all the models, therefore the whole test performed on the model H732B. The emissions below 1G for testing, to verify that the H720B meets the standard requirements.
EUT Function Description	: Please reference user manual of this device
Power Supply	: Powered by DC 5V external adapter or built-in battery.
Antenna Type	: FPC
Max Antenna Gain(dBi)	: Ant1:1.6dBi, Ant2:0.39dBi

Radio Technology	: IEEE 802.11b/g/n
Operation frequency	: IEEE 802.11b: 2412MHz to 2462MHz IEEE 802.11g: 2412MHz to 2462MHz IEEE 802.11n HT20: 2412MHz to 2462MHz IEEE 802.11n HT40: 2422MHz to 2452MHz
Modulation	: IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK)

Channel information					
CH	Frequency (MHz)	CH	Frequency (MHz)	CH	Frequency (MHz)
1	2412	5	2432	9	2452
2	2417	6	2437	10	2457
3	2422	7	2442	11	2462
4	2427	8	2447	/	/

Note: The above EUT information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications or User's Manual. The above Antenna information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

“☒” means to be chosen or applicable; “☐” means don't to be chosen or not applicable; This note applies to entire report.

2.2. Accessories of EUT

Accessories	Manufacturer	Model number	Description
/	/	/	/

2.3. Block diagram of EUT configuration for test

EUT

2.4. Decision of final test mode

According pre-test, the worst test modes were reported as below:

Test software: EngineerMode.exe

The test software was used to control EUT work in Continuous Tx mode and select test channel, wireless mode as below table.

The pathloss of external cable: 0.5dB (According to the manufacturer's claims)

Tested mode, Tx Power Setting, Data rate, Channel, and Frequency					
Tested mode	Tx Power Setting		Data rate (Mbps) (see Note)	Test Channel	Frequency (MHz)
	ANT1	ANT2			
IEEE 802.11b	14	14	1	LCH: CH1	2412
	14	14	1	MCH: CH6	2437
	14	14	1	HCH: CH11	2462
IEEE 802.11g	14	14	6	LCH: CH1	2412
	14	14	6	MCH: CH6	2437
	14	14	6	HCH: CH11	2462
IEEE 802.11n HT20	14	14	MCS 8	LCH: CH1	2412
	14	14	MCS 8	MCH: CH6	2437
	14	14	MCS 8	HCH: CH11	2462
IEEE 802.11n HT40	14	14	MCS 8	LCH: CH3	2422
	14	14	MCS 8	MCH: CH6	2437
	14	14	MCS 8	HCH: CH9	2452
Note: According exploratory test, EUT will have maximum output power in those data rate, so those data rate were used for all test.					

2.5. Deviations of test standard

No deviation.

2.6. Test environment conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature range:	+15°C to +35 °C
Humidity range:	20% to 75%
Pressure range:	86 kPa to106 kPa

Note: The specific temperature and humidity information of each test item refers to the temperature and humidity record in the corresponding test data.

2.7. Test laboratory

Guangdong Dongdian Testing Service Co., Ltd.

Add.: Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808.

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: ddt@dgddt.com.

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, R-20240, G-20118

2.8. Measurement uncertainty


Test Item	Uncertainty
Bandwidth	1.9%
Peak Output Power (Conducted) (Spectrum analyzer)	0.98 dB
Peak Output Power (Conducted) (Power Sensor)	1.18 dB
Power Spectral Density (Base EIRP)	1.51 dB
Power Spectral Density (Spectrum analyzer)	0.98 dB
Frequencies Stability	1.9 kHz
Conducted spurious emissions	1.21 dB ($9\text{ kHz} \leq f < 7\text{ GHz}$);
	3.31 dB ($7\text{ GHz} \leq f < 40\text{ GHz}$)
Uncertainty for radio frequency (RBW < 20 kHz)	5.5×10^{-8}
Time	0.11%
Temperature	0.3 °C
Humidity	2 %
Uncertainty for Radiation Emission test (9 kHz – 30 MHz)	3.44 dB
Uncertainty for Radiation Emission test (30 MHz - 1 GHz)	4.28 dB (Antenna Polarize: V)
Uncertainty for Radiation Emission test (1 GHz - 40 GHz)	4.14 dB (Antenna Polarize: H)
	4.22 dB (1 - 6 GHz)
	4.52 dB (6 GHz - 18 GHz)
Uncertainty for Power line conduction emission test	4.58 dB (18 GHz - 40 GHz)
	3.32dB (150KHz-30MHz)
	3.72dB (9KHz-150KHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

3. Equipment Used During Conductive Test

Equipment	Manufacturer	Model No.	Serial Number	Due Date
☒ RF Connected Test (RF Measurement System 3#)				
SIGNAL ANALYZER	R&S	FSV40	101407	2027/07/10
Wideband Radio Communication Tester	R&S	CMW500	120259	2027/07/10
EXG Analog Signal Generator	KEYSIGHT	N5173B	MY62153058	2027/06/21
MXG Vector Signal Generator	Agilent	N5182A	MY48180912	2027/02/27
RF Control Unit	Tonscend	JS0806-2	20C8060230	2027/03/17
TEMP&HUMI Programmable Chamber	ZHIXIANG	ZXGDJS-150L	ZX170110-A	2027/02/27
Test Software	Tonscend	JS1120-3	V3.6.21	N/A

4. 6dB Bandwidth

4.1. Block diagram of test setup



4.2. Limits

For direct sequence systems, the minimum 6 dB bandwidth shall be at least 500 kHz

4.3. Test procedure

- (1) The test according to ANSI C63.10 clause 11.8.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously
- (4) Use the following spectrum analyzer settings for 6 dB Bandwidth:
 - RBW: 100 kHz
 - VBW: $\geq [3 \times \text{RBW}]$
 - Detector Mode: peak
 - Sweep time: auto
 - Trace mode max hold

Allow the trace to stabilize, measure the 6 dB bandwidth of signal, and record the results in the report


4.4. Test result


Test Engineer:	Tan Shaofeng	Test Site:	RF Measurement System 3#
Ambient Condition:	24.5-26.1℃,37.2-42.9%RH	Test Date:	2026.7.8-2026.8.10
Test Power Supply:	DC 5V	Sample Number:	S26040120-036

Test Mode	Antenna	Frequency [MHz]	DTS BW [MHz]	FL [MHz]	FH [MHz]	Limit [MHz]	Verdict
11B	Ant1	2412	8.04	2408.48	2416.52	0.5	PASS
	Ant2	2412	8.04	2408.00	2416.04	0.5	PASS
	Ant1	2437	7.56	2433.00	2440.56	0.5	PASS
	Ant2	2437	8.04	2433.00	2441.04	0.5	PASS
	Ant1	2462	7.56	2458.00	2465.56	0.5	PASS
	Ant2	2462	8.08	2457.96	2466.04	0.5	PASS
11G	Ant1	2412	16.32	2403.88	2420.20	0.5	PASS
	Ant2	2412	16.04	2404.12	2420.16	0.5	PASS
	Ant1	2437	15.88	2428.88	2444.76	0.5	PASS
	Ant2	2437	16.04	2429.12	2445.16	0.5	PASS
	Ant1	2462	15.52	2454.24	2469.76	0.5	PASS
	Ant2	2462	15.96	2453.84	2469.80	0.5	PASS
11N20MI MO	Ant1	2412	17.56	2403.24	2420.80	0.5	PASS
	Ant2	2412	17.56	2403.24	2420.80	0.5	PASS
	Ant1	2437	16.28	2428.88	2445.16	0.5	PASS
	Ant2	2437	16.96	2428.84	2445.80	0.5	PASS
	Ant1	2462	15.16	2454.44	2469.60	0.5	PASS
	Ant2	2462	16.32	2453.24	2469.56	0.5	PASS
11N40MI MO	Ant1	2422	35.28	2404.48	2439.76	0.5	PASS
	Ant2	2422	35.68	2404.48	2440.16	0.5	PASS
	Ant1	2437	35.84	2419.08	2454.92	0.5	PASS
	Ant2	2437	35.36	2419.40	2454.76	0.5	PASS
	Ant1	2452	35.84	2434.08	2469.92	0.5	PASS
	Ant2	2452	35.12	2434.48	2469.60	0.5	PASS


4.5. Test graphs









11G Ant2 2412




11G Ant1 2437




11G Ant2 2437




11G Ant1_2462




11G Ant2_2462




11N20MIMO_Ant1_2412




11N20MIMO_Ant2_2412




11N20MIMO_Ant1_2437




11N20MIMO_Ant2_2437




11N20MIMO_Ant1_2462




11N20MIMO_Ant2_2462




11N40MIMO_Ant1_2422




11N40MIMO_Ant2_2422




11N40MIMO_Ant1_2437




11N40MIMO_Ant2_2437



11N40MIMO_Ant1_2452




11N40MIMO_Ant2_2452



5. 99% Bandwidth

5.1. Block diagram of test setup



5.2. Limits

Just for Report.

5.3. Test procedure

- (1) The test according to ANSI C63.10 clause 6.9.3.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously
- (4) Use the following spectrum analyzer settings for the 99% Bandwidth:

RBW:	1% to 5% of the OBW
VBW:	approximately three times RBW
Span:	between 1.5 times and 5.0 times the OBW
Detector Mode:	peak
Sweep time:	auto
Trace mode	max hold

Allow the trace to stabilize, measure the 99% bandwidth of signal, and record the results in the report.


5.4. Test result


Test Engineer:	Tan Shaofeng	Test Site:	RF Measurement System 3#
Ambient Condition:	24.5-26.1℃,37.2-42.9%RH	Test Date:	2026.7.8-2026.8.10
Test Power Supply:	DC 5V	Sample Number:	S26040120-036

TestMode	Antenna	Channel Frequency[MHz]	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	12.787	2405.7662	2418.5534	---	---
	Ant2	2412	12.747	2405.6464	2418.3936	---	---
	Ant1	2437	12.827	2430.5664	2443.3936	---	---
	Ant2	2437	12.787	2430.6464	2443.4336	---	---
	Ant1	2462	12.707	2455.6863	2468.3936	---	---
	Ant2	2462	12.747	2455.5664	2468.3137	---	---
11G	Ant1	2412	18.621	2403.2887	2421.9101	---	---
	Ant2	2412	17.982	2403.3287	2421.3107	---	---
	Ant1	2437	17.183	2428.3686	2445.5514	---	---
	Ant2	2437	17.183	2428.4486	2445.6314	---	---
	Ant1	2462	17.902	2453.0490	2470.9510	---	---
	Ant2	2462	17.822	2453.0090	2470.8312	---	---
11N20MI MO	Ant1	2412	19.381	2402.8092	2422.1898	---	---
	Ant2	2412	18.342	2403.0490	2421.3906	---	---
	Ant1	2437	18.262	2427.8492	2446.1109	---	---
	Ant2	2437	17.862	2428.0889	2445.9510	---	---
	Ant1	2462	18.781	2452.6094	2471.3906	---	---
	Ant2	2462	18.422	2452.6893	2471.1109	---	---
11N40MI MO	Ant1	2422	36.923	2403.8581	2440.7812	---	---
	Ant2	2422	37.083	2403.8581	2440.9411	---	---
	Ant1	2437	37.562	2418.3786	2455.9411	---	---
	Ant2	2437	37.243	2418.3786	2455.6214	---	---
	Ant1	2452	37.642	2432.8991	2470.5415	---	---
	Ant2	2452	37.003	2433.2987	2470.3017	---	---


5.5. Test graphs









11G Ant2 2412




11G Ant1 2437




11G Ant2 2437




11G Ant1_2462




11G Ant2_2462




11N20MIMO_Ant1_2412




11N20MIMO_Ant2_2412




11N20MIMO_Ant1_2437




11N20MIMO_Ant2_2437




11N20MIMO_Ant1_2462




11N20MIMO_Ant2_2462




11N40MIMO_Ant1_2422




11N40MIMO_Ant2_2422



11N40MIMO_Ant1_2437




11N40MIMO_Ant2_2437



6. Conducted Output Power

6.1. Block diagram of test setup



6.2. Limits

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

6.3. Test procedure

- (1) The test according to ANSI C63.10 clause 11.9.2.3.
- (2) Connect EUT's antenna output to RF power meter by RF cable, the path loss was compensated to the results.
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously, If the transmitter does not transmit continuously, measure the duty cycle, D, of the transmitter output signal.
- (4) Measure the average power of the transmitter. This measurement is an average over both the ON and OFF periods of the transmitter.
- (5) Adjust the measurement in dBm by adding $[10 \log (1 / D)]$, where D is the duty cycle.
- (6) Record the RF average power of each antenna port.

6.4. Test result average


Test Engineer:	Tan Shaofeng	Test Site:	RF Measurement System 3#
Ambient Condition:	24.5-26.1℃,37.2-42.9%RH	Test Date:	2026.7.8-2026.8.10
Test Power Supply:	DC 5V	Sample Number:	S26040120-036

Test Mode	Antenna	Frequency [MHz]	Average power [dBm]	Duty Cycle [%]	DC Factor [dB]	Result [dBm]	Limit [dBm]	EIRP [dBm]	EIRP Limit [dBm]	Verdict
11B	Ant1	2412	8.82	99.64	0.02	8.84	≤30.00	10.44	≤36.00	PASS
	Ant2	2412	8.93	99.64	0.02	8.95	≤30.00	9.34	≤36.00	PASS
	Ant1	2437	8.72	99.64	0.02	8.74	≤30.00	10.34	≤36.00	PASS
	Ant2	2437	9.42	99.53	0.02	9.44	≤30.00	9.83	≤36.00	PASS
	Ant1	2462	9.07	99.52	0.02	9.09	≤30.00	10.69	≤36.00	PASS
	Ant2	2462	9.10	99.41	0.03	9.13	≤30.00	9.52	≤36.00	PASS
11G	Ant1	2412	9.40	96.53	0.15	9.55	≤30.00	11.15	≤36.00	PASS
	Ant2	2412	9.21	96.53	0.15	9.36	≤30.00	9.75	≤36.00	PASS
	Ant1	2437	9.61	96.53	0.15	9.76	≤30.00	11.36	≤36.00	PASS
	Ant2	2437	10.00	96.53	0.15	10.15	≤30.00	10.54	≤36.00	PASS
	Ant1	2462	9.42	97.22	0.12	9.54	≤30.00	11.14	≤36.00	PASS
	Ant2	2462	9.26	96.53	0.15	9.41	≤30.00	9.80	≤36.00	PASS
11N20MI MO	Ant1	2412	9.45	93.06	0.31	9.76	≤30.00	11.36	≤36.00	PASS
	Ant2	2412	9.21	93.06	0.31	9.52	≤30.00	9.91	≤36.00	PASS
	total	2412	---	---	---	12.65	≤30.00	13.71	≤36.00	PASS
	Ant1	2437	9.42	94.37	0.25	9.67	≤30.00	11.27	≤36.00	PASS
	Ant2	2437	9.85	94.37	0.25	10.10	≤30.00	10.49	≤36.00	PASS
	total	2437	---	---	---	12.90	≤30.00	13.91	≤36.00	PASS
	Ant1	2462	9.38	94.37	0.25	9.63	≤30.00	11.23	≤36.00	PASS
	Ant2	2462	9.06	94.37	0.25	9.31	≤30.00	9.70	≤36.00	PASS
11N40MI MO	total	2462	---	---	---	12.48	≤30.00	13.54	≤36.00	PASS
	Ant1	2422	9.58	89.74	0.47	10.05	≤30.00	11.65	≤36.00	PASS
	Ant2	2422	8.89	87.18	0.60	9.49	≤30.00	9.88	≤36.00	PASS
	total	2422	---	---	---	12.79	≤30.00	13.86	≤36.00	PASS
	Ant1	2437	9.26	89.74	0.47	9.73	≤30.00	11.33	≤36.00	PASS
	Ant2	2437	9.55	87.18	0.60	10.15	≤30.00	10.54	≤36.00	PASS
	total	2437	---	---	---	12.96	≤30.00	13.96	≤36.00	PASS
	Ant1	2452	9.53	89.47	0.48	10.01	≤30.00	11.61	≤36.00	PASS
	Ant2	2452	9.58	87.18	0.60	10.18	≤30.00	10.57	≤36.00	PASS
	total	2452	---	---	---	13.11	≤30.00	14.13	≤36.00	PASS

Note: EIRP (dBm)=Conducted Output Power (dBm)+ Antenna Gain (dBi)

7. Power Spectral Density

7.1. Block diagram of test setup



7.2. Limits

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

7.3. Test procedure

- (1) The test according to ANSI C63.10 clause 11.10.5.
- (2) Connect EUT’s antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results.
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously.
- (4) Use the following spectrum analyzer settings for Power Spectral Density measurement:

Center frequency	DTS Channel center frequency
RBW:	$3\text{ kHz} \leq \text{RBW} \leq 100\text{ kHz}$
VBW:	$\geq 3\text{RBW}$
Span	1.5 times the DTS bandwidth
Detector Mode:	RMS
Sweep time:	auto
Trace mode	max hold
	Employ trace averaging (rms)
Trace	mode over a minimum of 100 traces.

- (5) Add $[10 \log (1 / D)]$, where D is the duty cycle measured in step a), to the measured PSD to compute the average PSD during the actual transmission time.
If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

7.4. Test result

Test Engineer:	Tan Shaofeng	Test Site:	RF Measurement System 3#
Ambient Condition:	24.5-26.1℃,37.2-42.9%RH	Test Date:	2026.7.8-2026.8.10
Test Power Supply:	DC 5V	Sample Number:	S26040120-036


Test Mode	Antenna	Frequency [MHz]	Result[dBm/3-100kHz]	Limit[dBm/3kHz]	Verdict
11B	Ant1	2412	-23.45	≤8.00	PASS
	Ant2	2412	-23.58	≤8.00	PASS
	Ant1	2437	-23.68	≤8.00	PASS
	Ant2	2437	-22.86	≤8.00	PASS
	Ant1	2462	-23.02	≤8.00	PASS
	Ant2	2462	-22.55	≤8.00	PASS
11G	Ant1	2412	-26.08	≤8.00	PASS
	Ant2	2412	-25.78	≤8.00	PASS
	Ant1	2437	-25.39	≤8.00	PASS
	Ant2	2437	-24.93	≤8.00	PASS
	Ant1	2462	-24.99	≤8.00	PASS
	Ant2	2462	-25.33	≤8.00	PASS
11N20MIMO	Ant1	2412	-25.68	≤8.00	PASS
	Ant2	2412	-25.30	≤8.00	PASS
	total	2412	-22.48	≤8.00	PASS
	Ant1	2437	-25.51	≤8.00	PASS
	Ant2	2437	-24.65	≤8.00	PASS
	total	2437	-22.05	≤8.00	PASS
	Ant1	2462	-25.09	≤8.00	PASS
	Ant2	2462	-24.98	≤8.00	PASS
	total	2462	-22.02	≤8.00	PASS
11N40MIMO	Ant1	2422	-27.50	≤8.00	PASS
	Ant2	2422	-27.65	≤8.00	PASS
	total	2422	-24.56	≤8.00	PASS
	Ant1	2437	-28.52	≤8.00	PASS
	Ant2	2437	-27.42	≤8.00	PASS
	total	2437	-24.92	≤8.00	PASS
	Ant1	2452	-28.33	≤8.00	PASS
	Ant2	2452	-27.03	≤8.00	PASS
	total	2452	-24.62	≤8.00	PASS

Note: The Duty Cycle Factor is compensated in the graph.


7.5. Test graphs









11G Ant2 2412




11G Ant1 2437




11G Ant2 2437




11G Ant1_2462




11G Ant2_2462




11N20MIMO_Ant1_2412



11N20MIMO_Ant2_2412



11N20MIMO_Ant1_2437



11N20MIMO_Ant2_2437