verify No.043962015824

위변조방지/진위확인
www.docuqr.com

TEST REPORT

KCTL Inc.
65, Sinwon-ro, Yeongtong-gu,
Suwon-si, Gyeonggi-do, 16677, Korea
TEL: 82-31-285-0894 FAX: 82-505-299-8311
www.kctl.co.kr

KCTL

1. Client

- Name : SELVAS Healthcare,Inc.
- Address : 174 Gajung-ro, Yuseong-gu Daejeon South Korea
- Date of Receipt : 2018-03-20

2. Use of Report : -

3. Name of Product and Model : BrailleSense Polaris MINI / H520B

4. Manufacturer and Country of Origin : SELVAS Healthcare,Inc. / Korea

5. FCC ID : 2AL4DH520B

6. Date of Test : 2018-05-01 to 2018-05-08

7. Test Standards : FCC Part 15 Subpart C, 15.247

8. Test Results : Refer to the test result in the test report

Affirmation	Tested by Name : Euijung Kim (Signature)	Technical Manager Name : Jongha Choi (Signature)

2018-05-10

KCTL Inc.

As a test result of the sample which was submitted from the client, this report does not guarantee the whole product quality. This test report should not be used and copied without a written agreement by KCTL Inc.

REPORT REVISION HISTORY

Date	Revision	Page No
2018-05-10	Originally issued	-

This report shall not be reproduced except in full, without the written approval of KCTL Inc. This document may be altered or revised by KCTL Inc. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by KCTL Inc. will constitute fraud and shall nullify the document.

[Contents]

1. Client information 4

2. Laboratory information 5

3. Description of E.U.T. 6

3.1 Basic description 6

3.2 General description 6

3.3 Test frequency 8

3.4 Test Voltage 8

4. Summary of test results 9

4.1 Standards & results 9

4.2 Uncertainty 9

5. Test results 10

5.1 Antenna Requirement 10

5.2 Maximum Peak Output Power 11

5.3 Peak Power Spectral Density 23

5.4 6 dB Bandwidth(DTS Channel Bandwidth) 31

5.5 Spurious Emission, Band Edge, and Restricted bands 45

5.6 Conducted Emission 73

6. Test equipment used for test 75

This test report shall not be reproduced, except in full, without the written approval

1. Client information

Applicant:	SELVAS Healthcare,Inc.
Address:	174 Gajung-ro, Yuseong-gu Daejeon South Korea
Telephone number:	+82 42 864 4460
Contact person:	Hyeondong Jeong / flynn.h.jeong@selvas.com

Manufacturer:	SELVAS Healthcare,Inc.
Address:	155, Sinseong-ro, Yuseong-gu, Daejeon, Republic of Korea

KCTL

2. Laboratory information

Address

KCTL Inc.

65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea

Telephone Number: +82 31 285 0894

Facsimile Number: +82 505 299 8311

FCC Site Designation No: KR0040, FCC Site Registration No: 687132

VCCI Registration No. : R-3327, G-198, C-3706, T-1849

Industry Canada Registration No. : 8035A-2

KOLAS NO.: KT231

SITE MAP



3. Description of E.U.T.

3.1 Basic description

Applicant	SELVAS Healthcare,Inc.
Address of Applicant	174 Gajung-ro, Yuseong-gu Daejeon South Korea
Manufacturer	SELVAS Healthcare,Inc.
Address of Manufacturer	155, Sinseong-ro, Yuseong-gu, Daejeon, Republic of Korea
Type of equipment	BrailleSense Polaris MINI
Basic Model	H520B
Serial number	N/A

3.2 General description

Frequency Range	2 412 ㎒ ~ 2 462 ㎒ (802.11b/g/n HT20) 2 422 ㎒ ~ 2 452 ㎒ (802.11n HT40) 5 180 ㎒ ~ 5 240 ㎒ (802.11ac VHT20) 5 745 ㎒ ~ 5 825 ㎒ (802.11ac VHT20) 2 402 ㎒ ~ 2 480 ㎒ (Bluetooth, Bluetooth Low Energy)
Type of Modulation	802.11b : DSSS, 802.11g/n/ac : OFDM, Bluetooth : GFSK, π/4DQPSK, 8DPSK Bluetooth Low Energy : GFSK
The number of channels	2.4 ㎓: 11 ch (802.11b/g/n HT20), 7 ch (802.11n HT40), 79 ch (Bluetooth), 40 ch (Bluetooth Low Energy) 5 ㎓: 5 150 ㎒ Band: 4 (802.11ac VHT20) 5 725 ㎒ Band: 5 (802.11ac VHT20)
Type of Antenna	FPCB Antenna
Antenna Gain	2.4 ㎓: -0.97 ㏈i (WiFi) 2.45 ㏈i (Bluetooth, Bluetooth Low Energy) 5 ㎓: 1.99 ㏈i (5 150 ㎒ ~ 5 250 ㎒) -0.49 ㏈i (5 725 ㎒ ~ 5 850 ㎒)

Transmit Power	9.46 dBm
Power supply	DC 3.70 V
Product SW/HW version	V0.3 / 5.32.15.25468
Radio SW/HW version	V5.32.01 / V6.1
Test SW Version	Dut labtool 2.0.0.89
RF power setting in TEST SW	15(802.11b/g/n HT20/n HT40)

Note : The above EUT information was declared by the manufacturer.

This test report shall not be reproduced, except in full, without the written approval

3.3 Test frequency

	802.11b/g/n HT20	802.11n HT40
Lowest frequency	2 412 ㎒	2 422 ㎒
Middle frequency	2 437 ㎒	2 437 ㎒
Highest frequency	2 462 ㎒	2 452 ㎒

3.4 Test Voltage

Mode	Voltage
Nominal Voltage	DC 3.70 V

This test report shall not be reproduced, except in full, without the written approval

4. Summary of test results

4.1 Standards & results

FCC Rule Reference	Parameter	Report Section	Test Result
15.203, 15.247(b)(4)	Antenna Requirement	5.1	C
15.247(b)(3)	Maximum Peak Output Power	5.2	C
15.247(e)	Peak Power Spectral Density	5.3	C
15.247(a)(2)	6 dB Channel Bandwidth	5.4	C
-	Occupied Bandwidth	5.4	C
15.247(d), 15.205(a), 15.209(a)	Spurious Emission, Band Edge and Restricted bands	5.5	C
15.207(a)	Conducted Emissions	5.6	C
Note: C = Complies, NC = Not Complies, NT = Not Tested, NA = Not Applicable			

4.2 Uncertainty

Measurement Item	Expanded Uncertainty U = *k*Uc (*k* = 2)	
Conducted RF power	1.42 dB	
Conducted Spurious Emissions	1.58 dB	
Radiated Spurious Emissions	30 MHz ~ 300 MHz:	+4.94 dB, -5.06 dB
		+4.93 dB, -5.05 dB
	300 MHz ~ 1 000 MHz:	+4.97 dB, -5.08 dB
		+4.84 dB, -4.96 dB
	1 GHz ~ 25 GHz:	+6.03 dB, -6.05 dB
Conducted Emissions	9 kHz ~ 150 kHz:	3.75 dB
	150 kHz ~ 30 MHz:	3.36 dB

5. Test results

5.1 Antenna Requirement

5.1.1 Regulation

According to §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

And according to §15.247(b)(4), the conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

5.1.2 Result

-Complied

The transmitter has permanently attached FPCB Antenna (internal antenna) on board.

5.2 Maximum Peak Output Power

5.2.1 Regulation

According to §15.247(b)(3), For systems using digital modulation in the 902-928 ㎒, 2 400-2 483.5 ㎒, and 5 725-5 850 ㎒ bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

According to §15.247(b)(4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 ㏈i. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 ㏈i are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in ㏈ that the directional gain of the antenna exceeds 6 ㏈i.

5.2.2 Measurement Procedure

These test measurement settings are specified in section 9.0 of 558074 D01 DTS Meas Guidance.

5.2.2.1 Maximum conducted (average) output power

5.2.2.1.1 General

§15.247 permits the maximum conducted (average) output power to be measured as an alternative to the maximum peak conducted output power for demonstrating compliance to the limit. When this option is exercised, the measured power is to be referenced to the OBW rather than the DTS bandwidth (see ANSI C63.10 for measurement guidance).
When using a spectrum analyzer or EMI receiver to perform these measurements, it shall be capable of utilizing a number of measurement points in each sweep that is greater than or equal to twice the span/RBW to set a bin-to-bin spacing of ≤ RBW/2 so that narrowband signals are not lost between frequency bins.

If possible, configure or modify the operation of the EUT so that it transmits continuously at its maximum power control level. The intent is to test at 100 % duty cycle; however a small reduction in duty cycle (to no lower than 98 %) is permitted, if required by the EUT for amplitude control purposes. Manufacturers are expected to provide software to the test lab to permit such continuous operation.
If continuous transmission (or at least 98 % duty cycle) cannot be achieved due to hardware limitations (e.g., overheating), the EUT shall be operated at its maximum power control level, with the transmit duration as long as possible, and the duty cycle as high as possible during which sweep triggering/signal gating techniques may be used to perform the measurement over the transmission duration.

5.2.2.1.2 Measurement using a spectrum analyzer (SA)

5.2.2.1.2.1 Method AVGSA-1 (trace averaging with the EUT transmitting at full power throughout each sweep)

a) Set span to at least 1.5 times the OBW.
b) Set RBW = 1-5% of the OBW, not to exceed 1 MHz.
c) Set VBW ≥ 3 x RBW.
d) Number of points in sweep ≥ 2 × span / RBW. (This gives bin-to-bin spacing ≤ RBW/2, so that narrowband signals are not lost between frequency bins.)
e) Sweep time = auto.
f) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.
g) If transmit duty cycle < 98 %, use a sweep trigger with the level set to enable triggering only on full power pulses. The transmitter shall operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle ≥ 98 %, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to “free run”.
h) Trace average at least 100 traces in power averaging (i.e., RMS) mode.
i) Compute power by integrating the spectrum across the OBW of the signal using the instrument’s band power measurement function, with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.

5.2.2.1.2.2 Method AVGSA-2 (trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction)

a)Measure the duty cycle, x, of the transmitter output signal as described in 6.0.
b) Set span to at least 1.5 times the OBW.
c) Set RBW = 1-5% of the OBW, not to exceed 1 ㎒.
d) Set VBW ≥ 3 x RBW.
e) Number of points in sweep ≥ 2 × span / RBW. (This gives bin-to-bin spacing ≤ RBW/2, so that narrowband signals are not lost between frequency bins.)
f) Sweep time = auto.
g) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.
h) Do not use sweep triggering. Allow the sweep to “free run”.
i) Trace average at least 100 traces in power averaging (i.e., RMS) mode; however, the number of traces to be averaged shall be increased above 100 as needed such that the average accurately represents the true average over the on and off periods of the transmitter.
j) Compute power by integrating the spectrum across the OBW of the signal using the instrument’s band power measurement function with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.
k) Add 10 log (1/x), where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times (because the measurement represents an average over both the on and off times of the transmission). For example, add 10 log (1/0.25) = 6 ㏈ if the duty cycle is 25 %.

- Duty Cycle Correction Factor

- 802.11b



Note1) : period : 1 000.10 ms, On time : 996.50 ms
Note2) : DCCF = 10 log(1 / x) = 10 log(996.50 / 1 000.10) = 0.02, x = 0.996
Note3) : 802.11b is a continuous transmission (duty cycle >=98 %)"

- 802.11g



Note1) : period : 1 000.10 ms, On time : 995.75 ms
Note2) : DCCF = 10 log(1 / x) = 10 log(995.75 / 1 000.10) = 0.02, x = 0.996
Note3) : 802.11g is a continuous transmission (duty cycle >=98 %)"

- 802.11n HT20



Note1) : period : 1 000.10 ms, On time : 995.90 ms
Note2) : DCCF = 10 log(1 / x) = 10 log(995.90 / 1 000.10) = 0.03, x = 0.996
Note3) : 802.11n HT20 is a continuous transmission (duty cycle >=98 %)"

- 802.11n HT40



Note1) : period : 1 000.10 ms, On time : 995.90 ms
Note2) : DCCF = 10 log(1 / x) = 10 log(995.90 / 1 000.10) = 0.02, x = 0.996
Note3) : 802.11n HT20 is a continuous transmission (duty cycle >=98 %)"

5.2.3 Test Result

- Complied

- 802.11b

Channel	Frequency [㎒]	Average power [dBm]	D.C.C.F [dB]	Result [dBm]	Limit [dBm]	Margin [dB]
Lowest	2 412	9.20	0.02	9.22	30.00	20.78
Middle	2 437	9.44	0.02	9.46	30.00	20.54
Highest	2 462	9.17	0.02	9.19	30.00	20.81

- 802.11g

Channel	Frequency [㎒]	Average power [dBm]	D.C.C.F [dB]	Result [dBm]	Limit [dBm]	Margin [dB]
Lowest	2 412	7.42	0.02	7.44	30.00	22.56
Middle	2 437	7.96	0.02	7.98	30.00	22.02
Highest	2 462	7.54	0.02	7.56	30.00	22.44

- 802.11n HT20

Channel	Frequency [㎒]	Average power [dBm]	D.C.C.F [dB]	Result [dBm]	Limit [dBm]	Margin [dB]
Lowest	2 412	7.83	0.02	7.85	30.00	22.15
Middle	2 437	7.92	0.02	7.94	30.00	22.06
Highest	2 462	7.62	0.02	7.64	30.00	22.36

- 802.11n HT40

Channel	Frequency [㎒]	Average power [dBm]	D.C.C.F [dB]	Result [dBm]	Limit [dBm]	Margin [dB]
Lowest	2 422	6.83	0.02	6.85	30.00	23.15
Middle	2 437	7.08	0.02	7.10	30.00	22.90
Highest	2 452	6.67	0.02	6.69	30.00	23.31

NOTE:
1. We took the insertion loss of the cable loss into consideration within the measuring instrument.

5.2.4 Test Plot

Figure 1. Plot of Maximum Peak Output Power

- 802.11b

Lowest Channel (2 412 ㎒)



Middle Channel (2 437 ㎒)



Highest Channel (2 462 ㎒)



- 802.11g

Lowest Channel (2 412 ㎒)



Middle Channel (2 437 ㎒)



Highest Channel (2 462 ㎒)



- 802.11n HT20

Lowest Channel (2 412 ㎒)



Middle Channel (2 437 ㎒)



Highest Channel (2 462 ㎒)



- 802.11n HT40

Lowest Channel (2 422 ㎒)



Middle Channel (2 437 ㎒)



Highest Channel (2 452 ㎒)



5.3 Peak Power Spectral Density

5.3.1 Regulation

According to §15.247(e), for digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

5.3.2 Measurement Procedure

These test measurement settings are specified in section 10.0 of 558074 D01 DTS Meas Guidance.

5.3.2.1 Method AVGPSD-1 (trace averaging with EUT transmitting at full power throughout each sweep)

This procedure may be used when the maximum (average) conducted output power was used to demonstrate compliance to the output power limit. This is the baseline method for determining the maximum (average) conducted PSD level. If the instrument has an RMS power averaging detector, it must be used; otherwise, use the sample detector. The EUT must be configured to transmit continuously (duty cycle ≥ 98 %); otherwise sweep triggering/signal gating must be implemented to ensure that measurements are made only when the EUT is transmitting at its maximum power control level (no transmitter off time is to be considered).

1) Set instrument center frequency to DTS channel center frequency.

2) Set span to at least 1.5 x OBW.

3) Set RBW to: 3 kHz ≤ RBW ≤ 100 kHz.

4) Set VBW ≥ 3 x RBW.

5) Detector = power averaging (RMS) or sample detector (when RMS not available).

6) Ensure that the number of measurement points in the sweep ≥ 2 x span/RBW.

7) Sweep time = auto couple.

8) Employ trace averaging (RMS) mode over a minimum of 100 traces.

9) Use the peak marker function to determine the maximum amplitude level.

5.3.3 Test Result

- Complied

- 802.11b

Channel	Measured PSD [dBm/3 ㎑]	Duty Factor [dB]	Result [dBm/3 ㎑]	Limit [dBm/3 ㎑]	Margin [dB]
Lowest	-22.89	0.02	-22.87	8.00	30.87
Middle	-22.96	0.02	-22.94	8.00	30.94
Highest	-23.30	0.02	-23.28	8.00	31.28

- 802.11g

Channel	Measured PSD [dBm/3 ㎑]	Duty Factor [dB]	Result [dBm/3 ㎑]	Limit [dBm/3 ㎑]	Margin [dB]
Lowest	-26.95	0.02	-26.93	8.00	34.93
Middle	-26.44	0.02	-26.42	8.00	34.42
Highest	-26.94	0.02	-26.92	8.00	34.92

- 802.11n HT20

Channel	Measured PSD [dBm/3 ㎑]	Duty Factor [dB]	Result [dBm/3 ㎑]	Limit [dBm/3 ㎑]	Margin [dB]
Lowest	-26.59	0.02	-26.57	8.00	34.57
Middle	-26.21	0.02	-26.19	8.00	34.19
Highest	-26.54	0.02	-26.52	8.00	34.52

- 802.11n HT40

Channel	Measured PSD [dBm/3 ㎑]	Duty Factor [dB]	Result [dBm/3 ㎑]	Limit [dBm/3 ㎑]	Margin [dB]
Lowest	-31.20	0.02	-31.18	8.00	39.18
Middle	-30.92	0.02	-30.90	8.00	38.90
Highest	-30.80	0.02	-30.78	8.00	38.78

-NOTE:

1. We took the insertion loss of the cable loss into consideration within the measuring instrument.

5.3.4 Test Plot

Figure 2. Plot of the Power Density

- 802.11b

Lowest Channel (2 412 ㎒)



Middle Channel (2 437 ㎒)



Highest Channel (2 462 ㎒)



- 802.11g

Lowest Channel (2 412 ㎒)



Middle Channel (2 437 ㎒)



Highest Channel (2 462 ㎒)



- 802.11n HT20

Lowest Channel (2 412 ㎒)



Middle Channel (2 437 ㎒)



Highest Channel (2 462 ㎒)



- 802.11n HT40

Lowest Channel (2 422 ㎒)



Middle Channel (2 437 ㎒)



Highest Channel (2 452 ㎒)



5.4 6 dB Bandwidth(DTS Channel Bandwidth)

5.4.1 Regulation

According to §15.247(a)(2) Systems using digital modulation techniques may operate in the 902–928 ㎒, 2 400–2 483.5 ㎒, and 5 725–5 850 ㎒ bands. The minimum 6 ㏈ bandwidth shall be at least 500 ㎑.

5.4.2 Measurement Procedure

These test measurement settings are specified in section 8.0 of 558074 D01 DTS Meas Guidance.

5.4.2.1 DTS Channel Bandwidth-Option 1

1) Set RBW = 100 ㎑.
2) Set the video bandwidth (VBW) ≥ 3 x RBW.
3) Detector = Peak.
4) Trace mode = max hold.
5) Sweep = auto couple.
6) Allow the trace to stabilize.
7) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 ㏈ relative to the maximum level measured in the fundamental emission.

5.4.2.2 DTS Channel Bandwidth Measurement Procedure-Option 2

The automatic bandwidth measurement capability of an instrument may be employed using the X ㏈ bandwidth mode with X set to 6 ㏈, if the functionality described above (i.e., RBW = 100 ㎑, VBW ≥ 3 x RBW, peak detector with maximum hold) is implemented by the instrumentation function.
When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥ 6 ㏈.

5.4.3 Test Result

- Complied

- 802.11b

Channel	Frequency [MHz]	6 dB Bandwidth [MHz]	Min. Limit [MHz]	Occupied Bandwidth (99 % BW) [MHz]
Lowest	2 412	10.11	0.50	13.07
Middle	2 437	10.11	0.50	13.03
Highest	2 462	10.11	0.50	13.03

- 802.11g

Channel	Frequency [MHz]	6 dB Bandwidth [MHz]	Min. Limit [MHz]	Occupied Bandwidth (99 % BW) [MHz]
Lowest	2 412	16.58	0.50	16.50
Middle	2 437	16.58	0.50	16.50
Highest	2 462	16.58	0.50	16.50

- 802.11n HT20

Channel	Frequency [MHz]	6 dB Bandwidth [MHz]	Min. Limit [MHz]	Occupied Bandwidth (99 % BW) [MHz]
Lowest	2 412	17.78	0.50	17.58
Middle	2 437	17.78	0.50	17.58
Highest	2 462	17.78	0.50	17.58

- 802.11n HT40

Channel	Frequency [MHz]	6 dB Bandwidth [MHz]	Min. Limit [MHz]	Occupied Bandwidth (99 % BW) [MHz]
Lowest	2 422	36.52	0.50	36.04
Middle	2 437	36.52	0.50	36.04
Highest	2 452	36.52	0.50	36.04

NOTE:
1. We took the insertion loss of the cable loss into consideration within the measuring instrument.

5.4.4 Test Plot

Figure 3. Plot of the 6 ㏈ Bandwidth & Occupied Bandwidth

- 802.11b_6 ㏈ Bandwidth

Lowest Channel (2 412 ㎒)



Middle Channel (2 437 ㎒)



Highest Channel (2 462 ㎒)



- 802.11g_6 ㏈ Bandwidth

Lowest Channel (2 412 ㎒)



Middle Channel (2 437 ㎒)



Highest Channel (2 462 ㎒)



- 802.11n HT20_6 dB Bandwidth

Lowest Channel (2 412 MHz)



Middle Channel (2 437 MHz)



Highest Channel (2 462 ㎒)



- 802.11n HT40_6 ㏈ Bandwidth

Lowest Channel (2 422 ㎒)



Middle Channel (2 437 ㎒)



Highest Channel (2 452 ㎒)



- 802.11b_Occupied Bandwidth

Lowest Channel (2 412 ㎒)

Middle Channel (2 437 ㎒)



Highest Channel (2 462 ㎒)



- 802.11g_Occupied Bandwidth

Lowest Channel (2 412 ㎒)



Middle Channel (2 437 ㎒)



Highest Channel (2 462 ㎒)



- 802.11n HT20_Occupied Bandwidth

Lowest Channel (2 412 ㎒)



Middle Channel (2 437 ㎒)



Highest Channel (2 462 ㎒)



- 802.11n HT40_Occupied Bandwidth

Lowest Channel (2 422 ㎒)



Middle Channel (2 437 ㎒)



Highest Channel (2 452 ㎒)



5.5 Spurious Emission, Band Edge, and Restricted bands

5.5.1 Regulation

According to §15.247(d), in any 100 ㎑ bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 ㏈ below that in the 100 ㎑ bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 ㏈ instead of 20 ㏈. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

According to §15.209(a), Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall notexceed the field strength levels specified in the following table:

Frequency (㎒)	Field strength (㎛/m)	Measurement distance (m)
0.009 - 0.490	2 400/F(㎑)	300
0.490 - 1.705	24 000/F(㎑)	30
1.705 - 30	30	30
30 - 88	100**	3
88 - 216	150**	3
216 - 960	200**	3
Above 960	500	3

**Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54–72 ㎒, 76–88 ㎒, 174–216 ㎒ or 470–806 ㎒. However, operation within these frequency bands is permItted under other sections of this part, e.g., §§15.231 and 15.241.

According to § 15.205(a) and (b), only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.009 - 0.110 0.495 - 0.505 2.173 5 - 2.190 5 4.125 - 4.128 4.177 25 - 4.177 75 4.207 25 - 4.207 75 6.215 - 6.218 6.267 75 - 6.268 25 6.311 75 - 6.312 25 8.291 - 8.294 8.362 - 8.366 8.376 25 - 8.386 75 8.414 25 - 8.414 75 12.29 - 12.293 12.519 75 - 12.520 25 12.576 75 - 12.577 25 13.36 - 13.41	16.42 - 16.423 16.694 75 - 16.695 25 16.804 25 - 16.804 75 25.5 - 25.67 37.5 - 38.25 73 - 74.6 74.8 - 75.2 108 - 121.94 123 - 138 149.9 - 150.05 156.524 75 - 156.525 25 156.7 - 156.9 162.012 5 - 167.17 167.72 - 173.2 240 - 285 322 - 335.4	399.9 - 410 608 - 614 960 – 1 240 1 300 – 1 427 1 435 – 1 626.5 1 645.5 – 1 646.5 1 660 – 1 710 1 718.8 – 1 722.2 2 200 – 2 300 2 310 – 2 390 2 483.5 – 2 500 2 690 – 2 900 3 260 – 3 267 3 332 – 3 339 3 345.8 – 3 358 3 600 – 4 400	4.5 - 5.15 5.35 - 5.46 7.25 - 7.75 8.025 - 8.5 9.0 - 9.2 9.3 - 9.5 10.6 - 12.7 13.25 - 13.4 14.47 - 14.5 15.35 - 16.2 17.7 - 21.4 22.01 - 23.12 23.6 - 24.0 31.2 - 31.8 36.43 - 36.5 Above 38.6

The field strength of emissions appearing within these frequency bands shall not exceed the limits shown in §15.209. At frequencies equal to or less than 1 000 MHz, compliance with the limits in §15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1 000 MHz, compliance with the emission limits in §15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in §15.35 apply to these measurements.

5.5.2Measurement Procedure

5.5.2.1 Band-edge Compliance of RF Conducted Emissions

5.5.2.1.1 Reference Level Measurement

Establish a reference level by using the following procedure:

1) Set instrument center frequency to DTS channel center frequency.
2) Set the span to ≥ 1.5 times the DTS bandwidth.
3) Set the RBW = 100 ㎑.
4) Set the VBW ≥ 3 x RBW.
5) Detector = peak.
6) Sweep time = auto couple.
7) Trace mode = max hold.
8) Allow trace to fully stabilize.
9) Use the peak marker function to determine the maximum PSD level.

5.5.2.1.2 Emissions Level Measurement

1) Set the center frequency and span to encompass frequency range to be measured.
2) Set the RBW = 100 ㎑.
3) Set the VBW ≥ 3 x RBW.
4) Detector = peak.
5) Ensure that the number of measurement points ≥ span/RBW
6) Sweep time = auto couple.
7) Trace mode = max hold.
8) Allow trace to fully stabilize.
9) Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in 11.1 a) or 11.1 b). Report the three highest emissions relative to the limit.

5.5.2.2 Conducted Spurious Emissions

Set the spectrum analyzer as follows:

1) Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic.
   Typically, several plots are required to cover this entire span.
2) RBW = 100 ㎑
3) VBW ≥ RBW
4) Sweep = auto
5) Detector function = peak
6) Trace = max hold
7) Allow the trace to stabilize. Set the marker on the peak of any spurious emission recorded.
8) Each frequency found during preliminary measurements was re-examined and investigated. The test-receiver system was set up to average, peak, and quasi-peak detector function with specified bandwidth.

5.5.2.3 Radiated Spurious Emissions

1) The preliminary and final rdiated measurements were performed to determine the frequency producing the maximum emissions in at a 10m anechoic chamber. The EUT was tested at a distance 3 meters.
2) The EUT was placed on the top of the 0.8-meter height, 1 × 1.5 meter non-metallic table. To find the maximum emission levels, the height of a measuring antenna was changed and the turntable was rotated 360˚.
3) The antenna polarization was also changed from vertical to horizontal. The spectrum was scanned from 9 ㎑ to 30 ㎒ using the loop antenna, and from 30 to 1 000 ㎒ using the TRILOG broadband antenna, and from 1 000 ㎒ to 26 500 ㎒ using the horn antenna.
4) Each frequency found during preliminary measurements was re-examined and investigated. The test-receiver system was set up to average, peak, and quasi-peak detector function with specified bandwidth.
5) The 0.8m height is for below 1 G testing, and 1.5m is for above 1G testing.

Note

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 ㎑ for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1 ㎓.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 ㎒ for Peak detection and frequency above 1 ㎓.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 ㎒ and the video bandwidth is 3 ㎒ for Average detection (AV) at frequency above 1 ㎓. (Detector = RMS, Averaging type = power)
   In case of duty cycle less than 98%, a duty cycle correction factor has to be added to the measurement result.

5.5.3 Test Result

- Complied

1. Band edge & Conducted Spurious Emissions was shown in figure 3 & 4.
   Note: We took the insertion loss of the cable into consideration within the measuring instrument.
2. Measured value of the Field strength of spurious Emissions (Radiated)
3. It tested x,y and z – 3 axis each, mentioned only worst case data at this report.

※ Noise was not measured. (Margin was more than 20 ㏈)

- Below 1 ㎓ data (worst-case: 802.11b)

Middle channel (2 412 ㎒)

Frequency [㎒]	Receiver Bandwidth [㎑]	Pol. [V/H]	Reading [㏈(㎶)]	Cable Loss [㏈]	Amp Gain [㏈]	Antenna Factor [㏈]	Factor [㏈]	Result [㏈(㎶/m)]	Limit [㏈(㎶/m)]	Margin [㏈]
Quasi-Peak DATA. Emissions below 30 ㎒										
6.12	9	V	40.90	0.89	-32.69	19.70	-12.10	28.80	69.50	40.70
27.75	9	H	42.10	1.75	-32.69	19.04	-11.90	30.20	69.50	39.30
Quasi-Peak DATA. Emissions below 1 ㎓										
44.91	120	V	38.20	1.37	-31.61	16.45	-13.79	24.41	40.00	15.59
66.38	120	V	33.70	1.70	-30.95	12.43	-16.82	16.88	40.00	23.12
119.97	120	H	52.10	2.36	-37.61	18.30	-16.95	35.15	43.50	8.35
203.99	120	H	49.00	3.15	-33.80	15.53	-15.12	33.88	43.50	9.62
300.02	120	H	49.90	3.88	-35.15	19.20	-12.07	37.83	46.00	8.17
845.65	120	V	37.80	6.79	-34.16	26.07	-1.30	36.50	46.00	9.50

NOTE 1. Factor = Cable loss + Amp. Gain + Antenna factor
NOTE 2. Although these tests were performed other than open field test site, adequate comparison measurements were confirmed against 30 m open field test site.
Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

- Above 1 ㎓ data

802.11b_Lowest channel (2 412 ㎒)

Frequency [㎒]	Receiver Bandwidth [㎑]	Pol. [V/H]	Reading [dB(㎶)]	Cable Loss [dB]	Amp Gain [dB]	Antenna Factor [dB]	Factor [dB]	DCCF [dB]	Result [dB(㎶/m)]	Limit [dB(㎶/m)]	Margin [dB]
Peak DATA. Emissions above 1 ㎓											
1 286.80	1 000	V	72.53	2.74	-60.89	24.95	-33.20	-	39.33	74.00	34.67
2 389.00[1)]	1 000	H	55.02	3.70	-34.34	28.54	-2.10	-	52.93	74.00	21.07
3 010.70	1 000	H	76.01	4.14	-59.47	29.73	-25.60	-	50.41	74.00	23.59
3 982.68[1)]	1 000	V	68.61	4.77	-60.74	32.36	-23.61	-	45.00	74.00	29.00
5 908.41[1)]	1 000	V	71.18	6.04	-59.85	34.26	-19.55	-	51.62	74.00	22.38
5 990.83	1 000	V	72.10	6.09	-60.02	34.39	-19.54	-	52.55	74.00	21.45
21 538.66	1 000	V	48.06	12.00	-49.48	45.00	7.52	-	55.58	74.00	18.42
25 434.84	1 000	H	47.53	13.20	-47.11	45.40	11.49	-	59.03	74.00	14.97
Average DATA. Emissions above 1 ㎓											
2 389.00[1)]	1 000	H	44.02	3.70	-34.34	28.54	-2.10	-	41.92	54.00	12.08
3 982.68[1)]	1 000	V	57.32	4.77	-60.74	32.36	-23.61	-	33.71	54.00	20.29
5 908.41[1)]	1 000	V	67.99	6.04	-59.85	34.26	-19.55	-	48.44	54.00	5.56

[1)] Restricted band

802.11b_Middle channel (2 437 ㎒)

Frequency [㎒]	Receiver Bandwidth [㎑]	Pol. [V/H]	Reading [dB(㎶)]	Cable Loss [dB]	Amp Gain [dB]	Antenna Factor [dB]	Factor [dB]	DCCF [dB]	Result [dB(㎶/m)]	Limit [dB(㎶/m)]	Margin [dB]
Peak DATA. Emissions above 1 ㎓											
1 288.52	1 000	H	73.71	2.74	-60.93	24.95	-33.24	-	40.47	74.00	33.53
3 097.34	1 000	V	75.66	4.20	-59.70	29.96	-25.54	-	50.11	74.00	23.89
3 982.03[1)]	1 000	V	69.17	4.77	-60.74	32.35	-23.62	-	45.55	74.00	28.45
4 488.72	1 000	V	68.01	5.12	-60.09	32.64	-22.33	-	45.68	74.00	28.32
4 873.91[1)]	1 000	H	69.05	5.39	-59.84	32.84	-21.61	-	47.44	74.00	26.56
5 908.36	1 000	V	71.67	6.04	-59.85	34.26	-19.55	-	52.12	74.00	21.88
21 622.86	1 000	V	48.64	12.00	-49.47	45.00	7.53	-	56.18	74.00	17.82
25 899.69	1 000	V	47.01	13.60	-46.72	45.70	12.58	-	59.59	74.00	14.41
Average DATA. Emissions above 1 ㎓											
3 982.03[1)]	1 000	V	59.66	4.77	-60.74	32.35	-23.62	-	36.04	54.00	17.96
4 873.91[1)]	1 000	H	66.09	5.39	-59.84	32.84	-21.61	-	44.48	54.00	9.52

[1)] Restricted band

802.11b_Highest channel (2 462 MHz)

Frequency [MHz]	Receiver Bandwidth [kHz]	Pol. [V/H]	Reading [dB(μV)]	Cable Loss [dB]	Amp Gain [dB]	Antenna Factor [dB]	Factor [dB]	DCCF [dB]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]
Peak DATA. Emissions above 1 GHz											
1 259.77	1 000	H	74.49	2.72	-60.84	24.84	-33.28	-	41.21	74.00	32.79
2 484.00[1)]	1 000	H	55.80	3.77	-34.84	28.72	-2.35	-	53.45	74.00	20.55
3 062.58	1 000	H	77.66	4.18	-59.60	29.87	-25.55	-	52.11	74.00	21.89
4 923.88[1)]	1 000	H	71.47	5.42	-59.82	32.86	-21.54	-	49.94	74.00	24.06
5 908.81	1 000	V	71.52	6.04	-59.85	34.26	-19.55	-	51.97	74.00	22.03
5 989.47	1 000	V	69.84	6.09	-60.01	34.38	-19.54	-	50.30	74.00	23.70
21 579.30	1 000	V	47.83	12.00	-49.47	45.00	7.53	-	55.36	74.00	18.64
25 911.38	1 000	V	45.72	13.60	-46.70	45.70	12.60	-	58.32	74.00	15.68
Average DATA. Emissions above 1 GHz											
2 484.00[1)]	1 000	H	44.81	3.77	-34.84	28.72	-2.35	-	42.46	54.00	11.54
4 923.88[1)]	1 000	H	66.20	5.42	-59.82	32.86	-21.54	-	44.66	54.00	9.34

[1)] Restricted band

802.11g_Lowest channel (2 412 MHz)

Frequency [MHz]	Receiver Bandwidth [kHz]	Pol. [V/H]	Reading [dB(μV)]	Cable Loss [dB]	Amp Gain [dB]	Antenna Factor [dB]	Factor [dB]	DCCF [dB]	Result [dB(μV/m)]	Limit [dB(μV/m)]	Margin [dB]
Peak DATA. Emissions above 1 GHz											
1 287.66	1 000	H	74.27	2.74	-60.93	24.95	-33.24	-	41.03	74.00	32.97
2 389.01[1)]	1 000	H	57.39	3.70	-34.34	28.54	-2.10	-	55.29	74.00	18.71
3 186.64	1 000	V	75.92	4.26	-59.81	30.20	-25.35	-	50.57	74.00	23.43
3 982.76[1)]	1 000	V	68.75	4.77	-60.74	32.35	-23.62	-	45.12	74.00	28.88
5 908.36	1 000	V	73.98	6.04	-59.85	34.26	-19.55		54.43	74.00	19.57
21 594.97	1 000	V	47.96	12.00	-49.47	45.00	7.53	-	55.49	74.00	18.51
26 119.36	1 000	V	45.60	13.70	-46.68	45.70	12.72	-	58.32	74.00	15.68
Average DATA. Emissions above 1 GHz											
2 389.01[1)]	1 000	H	39.47	3.70	-34.34	28.54	-2.10	-	37.37	54.00	16.63
3 982.76[1)]	1 000	V	54.77	4.77	-60.74	32.35	-23.62	-	31.15	54.00	54.77

[1)] Restricted band

802.11g_Middle channel (2 437 ㎒)

Frequency [㎒]	Receiver Bandwidth [㎑]	Pol. [V/H]	Reading [dB(㎶)]	Cable Loss [dB]	Amp Gain [dB]	Antenna Factor [dB]	Factor [dB]	DCCF [dB]	Result [dB(㎶/m)]	Limit [dB(㎶/m)]	Margin [dB]
Peak DATA. Emissions above 1 ㎓											
1 288.20	1 000	V	73.73	2.74	-60.93	24.95	-33.24	-	40.49	74.00	33.51
3 009.53	1 000	V	77.22	4.14	-59.43	29.73	-25.56	-	51.66	74.00	22.34
5 908.36	1 000	V	71.12	6.04	-59.85	34.26	-19.55	-	51.57	74.00	22.43
15 732.11	1 000	V	59.17	10.03	-54.39	38.25	-6.11	-	53.05	74.00	20.95
21 637.73	1 000	V	47.61	12.00	-49.46	45.00	7.54	-	55.15	74.00	18.85
26 448.73	1 000	V	45.94	13.70	-46.83	45.60	12.47	-	58.41	74.00	15.59
Average DATA. Emissions above 1 ㎓											
Not detected											

802.11g_Highest channel (2 462 ㎒)

Frequency [㎒]	Receiver Bandwidth [㎑]	Pol. [V/H]	Reading [dB(㎶)]	Cable Loss [dB]	Amp Gain [dB]	Antenna Factor [dB]	Factor [dB]	DCCF [dB]	Result [dB(㎶/m)]	Limit [dB(㎶/m)]	Margin [dB]
Peak DATA. Emissions above 1 ㎓											
1 293.67	1 000	H	74.70	2.75	-60.95	24.97	-33.23	-	41.47	74.00	32.53
2 483.90[1)]	1 000	V	55.36	3.77	-34.84	28.72	-2.35	-	53.02	74.00	20.98
3 086.17	1 000	H	76.39	4.19	-59.67	29.93	-25.55	-	50.84	74.00	23.16
4 495.06	1 000	V	67.47	5.12	-60.08	32.65	-22.31	-	45.16	74.00	28.84
5 907.91	1 000	V	72.90	6.04	-59.85	34.26	-19.55	-	53.34	74.00	20.66
5 994.91	1 000	V	71.00	6.10	-60.03	34.39	-19.54	-	51.46	74.00	22.54
21 699.36	1 000	H	47.27	12.00	-49.45	45.00	7.55	-	54.81	74.00	19.19
26 135.56	1 000	V	45.89	13.70	-46.69	45.70	12.71	-	58.60	74.00	15.40
Average DATA. Emissions above 1 ㎓											
2 483.90[1)]	1 000	V	36.08	3.77	-34.84	28.72	-2.35	-	33.73	54.00	20.27

[1)] Restricted band

802.11n HT20_Lowest channel (2 412 ㎒)

Frequency [㎒]	Receiver Bandwidth [㎑]	Pol. [V/H]	Reading [dB(㎶)]	Cable Loss [dB]	Amp Gain [dB]	Antenna Factor [dB]	Factor [dB]	DCCF [dB]	Result [dB(㎶/m)]	Limit [dB(㎶/m)]	Margin [dB]
Peak DATA. Emissions above 1 ㎓											
1 273.36	1 000	V	74.22	2.73	-60.88	24.89	-33.26	-	40.96	74.00	33.04
2 389.44[1)]	1 000	V	61.02	3.70	-34.34	28.54	-2.10	-	58.93	74.00	15.07
3 142.97	1 000	H	77.32	4.23	-59.77	30.09	-25.45	-	51.87	74.00	22.13
3 984.96[1)]	1 000	V	69.07	4.77	-60.74	32.36	-23.61	-	45.46	74.00	28.54
5 907.91	1 000	H	72.51	6.04	-59.85	34.26	-19.55	-	52.96	74.00	21.04
21 619.41	1 000	V	48.48	12.00	-49.47	45.00	7.53	-	56.01	74.00	17.99
25 974.06	1 000	V	46.20	13.60	-46.55	45.70	12.75	-	58.95	74.00	15.05
Average DATA. Emissions above 1 ㎓											
2 389.44[1)]	1 000	V	46.49	3.70	-34.34	28.54	-2.10	-	44.39	54.00	9.61
3 984.96[1)]	1 000	V	58.16	4.77	-60.74	32.36	-23.61	-	34.55	54.00	19.45

[1)] Restricted band

802.11n HT20_Middle channel (2 437 ㎒)

Frequency [㎒]	Receiver Bandwidth [㎑]	Pol. [V/H]	Reading [dB(㎶)]	Cable Loss [dB]	Amp Gain [dB]	Antenna Factor [dB]	Factor [dB]	DCCF [dB]	Result [dB(㎶/m)]	Limit [dB(㎶/m)]	Margin [dB]
Peak DATA. Emissions above 1 ㎓											
1 271.95	1 000	H	75.67	2.73	-60.89	24.89	-33.27	-	42.40	74.00	31.60
3 154.61	1 000	V	76.11	4.24	-59.78	30.12	-25.42	-	50.69	74.00	23.31
3 985.03[1)]	1 000	V	70.25	4.77	-60.73	32.36	-23.60	-	46.64	74.00	27.36
5 908.36	1 000	V	73.30	6.04	-59.85	34.26	-19.55	-	53.75	74.00	20.25
21 684.22	1 000	V	48.08	12.00	-49.46	45.00	7.54	-	55.63	74.00	18.37
26 101.56	1 000	H	45.59	13.70	-46.67	45.70	12.73	-	58.32	74.00	15.68
Average DATA. Emissions above 1 ㎓											
3 985.03[1)]	1 000	V	58.79	4.77	-60.73	32.36	-23.60	-	35.19	54.00	18.81

[1)] Restricted band

802.11n HT20_Highest channel (2 462 ㎒)

Frequency [㎒]	Receiver Bandwidth [㎑]	Pol. [V/H]	Reading [dB(㎶)]	Cable Loss [dB]	Amp Gain [dB]	Antenna Factor [dB]	Factor [dB]	DCCF [dB]	Result [dB(㎶/m)]	Limit [dB(㎶/m)]	Margin [dB]
Peak DATA. Emissions above 1 ㎓											
1 271.64	1 000	H	73.87	2.73	-60.89	24.89	-33.27	-	40.60	74.00	33.40
2 487.38[1)]	1 000	V	55.66	3.77	-34.86	28.73	-2.36	-	53.31	74.00	20.69
3 054.84	1 000	V	76.59	4.17	-59.57	29.85	-25.55	-	51.04	74.00	22.96
5 907.91	1 000	V	73.29	6.04	-59.85	34.26	-19.55	-	53.74	74.00	20.26
5 990.83	1 000	V	74.20	6.09	-60.02	34.39	-19.54	-	54.66	74.00	19.34
15 159.36	1 000	H	57.87	9.82	-56.18	39.85	-6.51	-	51.37	74.00	22.63
21 598.16	1 000	V	47.99	12.00	-49.47	45.00	7.53	-	55.52	74.00	18.48
25 824.52	1 000	V	46.03	13.50	-46.70	45.60	12.40	-	58.43	74.00	15.57
Average DATA. Emissions above 1 ㎓											
2 487.38[1)]	1 000	V	35.62	3.77	-34.86	28.73	-2.36	-	33.26	54.00	20.74

[1)] Restricted band

802.11n HT40_Lowest channel (2 422 ㎒)

Frequency [㎒]	Receiver Bandwidth [㎑]	Pol. [V/H]	Reading [dB(㎶)]	Cable Loss [dB]	Amp Gain [dB]	Antenna Factor [dB]	Factor [dB]	DCCF [dB]	Result [dB(㎶/m)]	Limit [dB(㎶/m)]	Margin [dB]
Peak DATA. Emissions above 1 ㎓											
1 278.91	1 000	V	74.26	2.73	-60.90	24.92	-33.25	-	41.01	74.00	32.99
2 388.82[1)]	1 000	V	61.80	3.70	-34.34	28.54	-2.10	-	59.71	74.00	14.29
3 198.44	1 000	V	76.79	4.27	-59.83	30.24	-25.32	-	51.47	74.00	22.53
4 490.53	1 000	V	68.64	5.12	-60.09	32.65	-22.32	-	46.32	74.00	27.68
5 908.36	1 000	V	71.82	6.04	-59.85	34.26	-19.55	-	52.26	74.00	21.74
21 644.11	1 000	V	48.00	12.00	-49.46	45.00	7.54	-	55.53	74.00	18.47
26 128.66	1 000	H	45.73	13.70	-46.69	45.70	12.71	-	58.44	74.00	15.56
Average DATA. Emissions above 1 ㎓											
2 388.82[1)]	1 000	V	41.03	3.70	-34.34	28.54	-2.10	-	38.93	54.00	15.07

[1)] Restricted band

802.11n HT40_Middle channel (2 437 ㎒)

Frequency [㎒]	Receiver Bandwidth [㎑]	Pol. [V/H]	Reading [dB(㎶)]	Cable Loss [dB]	Amp Gain [dB]	Antenna Factor [dB]	Factor [dB]	DCCF [dB]	Result [dB(㎶/m)]	Limit [dB(㎶/m)]	Margin [dB]
Peak DATA. Emissions above 1 ㎓											
1 288.13	1 000	H	74.65	2.74	-60.93	24.95	-33.24	-	41.41	74.00	32.59
3 044.22	1 000	V	76.50	4.17	-59.54	29.82	-25.55	-	50.95	74.00	23.05
5 907.91	1 000	V	72.24	6.04	-59.85	34.26	-19.55	-	52.69	74.00	21.31
15 262.67	1 000	H	58.63	9.85	-55.97	39.56	-6.56	-	52.07	74.00	21.93
21 587.27	1 000	V	48.00	12.00	-49.47	45.00	7.53	-	55.53	74.00	18.47
25 455.30	1 000	V	46.78	13.20	-47.06	45.40	11.54	-	58.32	74.00	15.68
Average DATA. Emissions above 1 ㎓											
Not detected											

802.11n HT40_Highest channel (2 452 ㎒)

Frequency [㎒]	Receiver Bandwidth [㎑]	Pol. [V/H]	Reading [dB(㎶)]	Cable Loss [dB]	Amp Gain [dB]	Antenna Factor [dB]	Factor [dB]	DCCF [dB]	Result [dB(㎶/m)]	Limit [dB(㎶/m)]	Margin [dB]
Peak DATA. Emissions above 1 ㎓											
1 269.92	1 000	H	74.01	2.73	-60.88	24.88	-33.27	-	40.75	74.00	33.25
2 484.04[1)]	1 000	V	58.64	3.77	-34.84	28.72	-2.35	-	56.30	74.00	17.70
3 288.20	1 000	H	79.16	4.32	-60.01	30.48	-25.21	-	53.95	74.00	20.05
5 907.91	1 000	V	71.05	6.04	-59.85	34.26	-19.55	-	51.50	74.00	22.50
5 998.98	1 000	V	67.67	6.10	-60.04	34.40	-19.54	-	48.13	74.00	25.87
14 417.59	1 000	H	58.86	9.66	-57.65	40.71	-7.28	-	51.58	74.00	22.42
21 558.05	1 000	H	48.28	12.00	-49.48	45.00	7.52	-	55.80	74.00	18.20
26 254.30	1 000	V	46.18	13.70	-46.68	45.60	12.62	-	58.80	74.00	15.20
Average DATA. Emissions above 1 ㎓											
2 484.04[1)]	1 000	V	38.75	3.77	-34.84	28.72	-2.35	-	36.40	54.00	17.60

[1)] Restricted band

5.5.4 Test Plot

Figure 4. Plot of the Band-edge & Conducted Spurious Emissions

- 802.11b

Lowest Channel (2 412 ㎒)

Reference



Band-edge



- Result of 2 400.0 ㎒

Conducted Spurious Emissions



Middle Channel (2 437 ㎒)

Reference



Conducted Spurious Emissions



Highest Channel (2 462 ㎒)

Reference



Band-edge



- Result of 2 483.5 ㎒

Conducted Spurious Emissions



- 802.11g

Lowest Channel (2 412 ㎒)

Reference



Band-edge



- Result of 2 400.0 ㎒

Conducted Spurious Emissions



Middle Channel (2 437 ㎒)

Reference



Conducted Spurious Emissions



Highest Channel (2 462 ㎒)

Reference



Band-edge



- Result of 2 483.5 ㎒

Conducted Spurious Emissions



- 802.11n HT20

Lowest Channel (2 412 ㎒)

Reference



Band-edge



- Result of 2 400.0 ㎒

Conducted Spurious Emissions



Middle Channel (2 437 ㎒)

Reference



Conducted Spurious Emissions



Highest Channel (2 462 ㎒)

Reference



Band-edge



- Result of 2 483.5 ㎒

Conducted Spurious Emissions



- 802.11n HT40

Lowest Channel (2 422 ㎒)

Reference



Band-edge



- Result of 2 400.0 ㎒

Conducted Spurious Emissions



Middle Channel (2 437 ㎒)

Reference



Conducted Spurious Emissions



Highest Channel (2 452 ㎒)

Reference



Band-edge



- Result of 2 483.5 ㎒

Conducted Spurious Emissions



5.6 Conducted Emission

5.6.1 Regulation

According to §15.207(a), for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 ㎑ to 30 ㎒, shall not exceed the limits in the following table, as measured using a 50 μH/50 Ω line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency of emission (㎒)	Conducted limit (㏈㎶)	
	Qausi-peak	Average
0.15 – 0.5	66 to 56 *	56 to 46 *
0.5 – 5	56	46
5 – 30	60	50

* Decreases with the logarithm of the frequency.

According to §15.107(a), for unintentional device, except for Class A digital devices, line conducted emission limits are the same as the above table.

5.6.2 Measurement Procedure

1) The EUT was placed on a wooden table of size, 1 m by 1.5 m, raised 80 ㎝ in which is located 40 ㎝ away from the vertical wall and 1.5m away from the side wall of the shielded room.

2) Each current-carrying conductor of the EUT power cord was individually connected through a 50Ω/50μH LISN, which is an input transducer to a Spectrum Analyzer or an EMI/Field Intensity Meter, to the input power source.

3) Exploratory measurements were made to identify the frequency of the emission that had the highest amplitude relative to the limit by operating the EUT in a range of typical modes of operation, cable position, and with a typical system equipment configuration and arrangement. Based on the exploratory tests of the EUT, the one EUT cable configuration and arrangement and mode of operation that had produced the emission with the highest amplitude relative to the limit was selected for the final measurement.

4) The final test on all current-carrying conductors of all of the power cords to the equipment that comprises the EUT (but not the cords associated with other non-EUT equipment is the system) was then performed over the frequency range of 0.15 ㎒ to 30 ㎒.

5) The measurements were made with the detector set to PEAK amplitude within a bandwidth of 10 ㎑ or to QUASI-PEAK and AVERAGE within a bandwidth of 9 ㎑. The EUT was in transmitting mode during the measurements.

5.6.3 Test Result

- Complied

Figure 6. plot of Conducted Emission

- Conducted worst-case data: 802.11b_Lowest channel (2 412 ㎒)



Final Result

--- N_A Phase ---

No.	Frequency [MHz]	Reading QP [dB(uV)]	Reading CAV [dB(uV)]	c.f [dB]	Result QP [dB(uV)]	Result CAV [dB(uV)]	Limit QP [dB(uV)]	Limit AV [dB(uV)]	Margin QP [dB]	Margin CAV [dB]
1	0.16526	33.9	16.8	10.2	44.1	27.0	65.2	55.2	21.1	28.2
2	0.19858	35.3	17.2	10.0	45.3	27.2	63.7	53.7	18.4	26.5
3	0.27138	30.7	12.6	9.7	40.4	22.3	61.1	51.1	20.7	28.8
4	0.32692	26.6	9.3	9.8	36.4	19.1	59.5	49.5	23.1	30.4
5	0.40942	21.4	4.2	10.0	31.4	14.2	57.7	47.7	26.3	33.5
6	0.63014	20.9	6.3	10.0	30.9	16.3	56.0	46.0	25.1	29.7

--- L1_A Phase ---

No.	Frequency [MHz]	Reading QP [dB(uV)]	Reading CAV [dB(uV)]	c.f [dB]	Result QP [dB(uV)]	Result CAV [dB(uV)]	Limit QP [dB(uV)]	Limit AV [dB(uV)]	Margin QP [dB]	Margin CAV [dB]
1	0.71869	29.5	21.8	10.0	39.5	31.8	56.0	46.0	16.5	14.2
2	1.12795	21.0	12.8	10.1	31.1	22.9	56.0	46.0	24.9	23.1
3	1.48374	24.5	18.5	10.2	34.7	28.7	56.0	46.0	21.3	17.3
4	2.47367	23.3	16.8	10.1	33.4	26.9	56.0	46.0	22.6	19.1
5	2.97211	23.3	16.6	10.1	33.4	26.7	56.0	46.0	22.6	19.3
6	8.12314	18.1	9.9	10.1	28.2	20.0	60.0	50.0	31.8	30.0

6. Test equipment used for test

	Equipment Name	Manufacturer	Model No.	Serial No.	Next Cal. Date
■	Spectrum Analyzer	R & S	FSV30	100807	18.08.01
■	Spectrum Analyzer	R & S	FSV40	100988	19.01.05
■	Wideband Power Sensor	R & S	NRP-Z81	102398	19.01.31
■	DC Power Supply	AGILENT	E3632A	MY40016393	18.12.21
■	ATTENUATOR	R & S	DNF Dämpfungsglied 10 dB in N-50 Ohm	31212	18.05.15
■	EMI TEST RECEIVER	R & S	ESCI	100732	18.08.24
■	Bi-Log Antenna	SCHWARZBECK	VULB 9163	552	18.05.10
■	Amplifier	SONOMA INSTRUMENT	310N	186280	19.04.05
■	Amplifier	SONOMA INSTRUMENT	310N	284608	18.08.24
■	ATTENUATOR	Weinschel ENGINEERING	1	AE7348	18.05.15
■	Horn antenna	ETS.lindgren	3116	00086632	19.04.20
■	Horn antenna	ETS.lindgren	3117	155787	18.10.20
■	AMPLIFIER	L-3 Narda-MITEQ	AMF-7D-01001800-22-10P	2003683	18.06.12
■	AMPLIFIER	L-3 Narda-MITEQ	JS44-18004000-33-8P	2000997	18.08.09
■	LOOP Antenna	R & S	HFH2-Z2	892665/035	19.01.25
■	Antenna Mast	Innco Systems	MA4640-XP-ET	-	-
■	Turn Table	Innco Systems	DT2000	79	-
■	Antenna Mast	Innco Systems	MA4000-EP	303	-
■	Turn Table	Innco Systems	DT2000	79	-
■	Highpass Filter	WT	WT-A1698-HS	WT160411001	18.05.15
■	Vector Signal Generator	R & S	SMBV100A	257566	19.01.05
■	Signal Generator	R & S	SMR40	100007	18.05.15
■	Cable Assembly	RadiAll	2301761768000 PJ	17.30.38	-
■	Cable Assembly	gigalane	RG-400	-	-
■	Cable Assembly	HUER+SUHNER	SUCOFLEX 104	MY4342/4	-

This test report shall not be reproduced, except in full, without the written approval