

AXENT Intelligence Inc.

RF TEST REPORT

Report Type:

FCC Part 15.247 RF report

Model:

E600-E2

REPORT NUMBER:

2509B2401SHA-001

ISSUE DATE:

February 9, 2026

DOCUMENT CONTROL NUMBER:

TTRF15.247-02_V1 © 2018 Intertek



Applicant: AXENT Intelligence Inc.
3 Musick Irvine, CA 92618 US

Manufacturer: AXENT Intelligence Inc.
3 Musick Irvine, CA 92618 US

Manufacturer Site: Xiamen AXENT Corporation Limited.
No. 2 East Xiafei Road, Xinyang Street, Haicang District, Xiamen,

Product Name: Intelligent Toilet

Type/Model: E600-E2

FCC ID: 2AL4G-008

SUMMARY:

The equipment complies with the requirements according to the following standard(s) or Specification:

47CFR Part 15 (2024): Radio Frequency Devices (Subpart C)

ANSI C63.10 (2020): American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices

PREPARED BY:



Project Engineer
Dylan Tang

REVIEWED BY:



Reviewer
Wakeyou Wang

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

TEST REPORT

Content

REVISION HISTORY.....	5
MEASUREMENT RESULT SUMMARY	6
1 GENERAL INFORMATION	7
1.1 DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)	7
1.2 TECHNICAL SPECIFICATION.....	7
1.3 DESCRIPTION OF TEST FACILITY.....	8
2 TEST SPECIFICATIONS.....	9
2.1 STANDARDS OR SPECIFICATION	9
2.2 MODE OF OPERATION DURING THE TEST.....	9
2.3 TEST SOFTWARE LIST	10
2.4 TEST PERIPHERALS LIST.....	10
2.5 TEST ENVIRONMENT CONDITION:.....	10
2.6 INSTRUMENT LIST	11
2.7 MEASUREMENT UNCERTAINTY.....	12
3 MINIMUM 6DB BANDWIDTH.....	13
3.1 LIMIT	13
3.2 MEASUREMENT PROCEDURE	13
3.3 TEST CONFIGURATION	13
3.4 TEST RESULTS OF MINIMUM 6DB BANDWIDTH.....	13
4 MAXIMUM CONDUCTED OUTPUT POWER AND E.I.R.P.....	14
4.1 LIMIT	14
4.2 MEASUREMENT PROCEDURE	14
4.3 TEST CONFIGURATION	15
4.4 TEST RESULTS OF MAXIMUM CONDUCTED OUTPUT POWER.....	15
5 POWER SPECTRUM DENSITY	16
5.1 LIMIT	16
5.2 MEASUREMENT PROCEDURE	16
5.3 TEST CONFIGURATION	17
5.4 TEST RESULTS OF POWER SPECTRUM DENSITY	17
6 EMISSION OUTSIDE THE FREQUENCY BAND	18
6.1 LIMIT	18
6.2 MEASUREMENT PROCEDURE	18
6.3 TEST CONFIGURATION	19
6.4 THE RESULTS OF EMISSION OUTSIDE THE FREQUENCY BAND.....	19
7 RADIATED EMISSIONS IN RESTRICTED FREQUENCY BANDS.....	20
7.1 LIMIT	20
7.2 MEASUREMENT PROCEDURE	20
7.3 TEST CONFIGURATION	22
7.4 TEST RESULTS OF RADIATED EMISSIONS	24
8 POWER LINE CONDUCTED EMISSION.....	27
8.1 LIMIT	27
8.2 TEST CONFIGURATION	27
8.3 MEASUREMENT PROCEDURE	28

TEST REPORT

8.4	TEST RESULTS OF POWER LINE CONDUCTED EMISSION	29
9	OCCUPIED BANDWIDTH	31
9.1	LIMIT	31
9.2	MEASUREMENT PROCEDURE	31
9.3	TEST CONFIGURATION	31
9.4	THE RESULTS OF OCCUPIED BANDWIDTH	31
10	ANTENNA REQUIREMENT	32

Revision History

Report No.	Version	Description	Issued Date
2509B2401SHA-001	Rev. 01	Initial issue of report	February 9, 2026

Measurement result summary

TEST ITEM	FCC REFERENCE	RESULT
Minimum 6dB Bandwidth	15.247(a)(2)	Pass
Maximum conducted output power and e.i.r.p.	15.247(b)(3)	Pass
Power spectrum density	15.247(e)	Pass
Emission outside the frequency band	15.247(d)	Pass
Radiated Emissions in restricted frequency bands	15.247(d), 15.205&15.209	Pass
Power line conducted emission	15.207(a)	Pass
Occupied bandwidth	-	Tested
Antenna requirement	15.203	Pass

Notes: 1: NA =Not Applicable

TEST REPORT

1 GENERAL INFORMATION

1.1 Description of Equipment Under Test (EUT)

Product name:	Intelligent Toilet
Type/Model:	E600-E2
Description of EUT:	The EUT is Intelligent Toilet, it has only one model.
Rating:	120V~60Hz,750W
Category of EUT:	Class B
EUT type:	☐ Table top ☒ Floor standing
Software Version:	290003291103
Hardware Version:	V1.3
Sample received date:	October 9, 2025
Date of test:	October 10, 2025 ~ January 20, 2026

1.2 Technical Specification

Frequency Range:	2402-2480MHz
Type of Modulation:	GFSK
Channel Number:	3
Data Rate:	1Mbps
Antenna Information:	3dBi, PCB antenna

1.3 Description of Test Facility

Name:	Intertek Testing Services (Shanghai FTZ) Co., Ltd.
Address:	Building 86, No. 1198 Qinzhou Road(North), Shanghai 200233, P.R. China
Telephone:	86 21 61278200
Telefax:	86 21 54262353

The test facility is recognized, certified, or accredited by these organizations:	CNAS Accreditation Lab Registration No. CNAS L21189
	FCC Accredited Lab Designation Number: CN0175
	IC Registration Lab CAB identifier.: CN0014
	VCCI Registration Lab Registration No.: R-4243, G-845, C-4723, T-2252
	NVLAP Accreditation Lab NVLAP LAB CODE: 200849-0
	A2LA Accreditation Lab Certificate Number: 3309.02

2 TEST SPECIFICATIONS

2.1 Standards or specification

47CFR Part 15 (2024)

ANSI C63.10 (2020)

KDB 558074 (v05r02)

2.2 Mode of operation during the test

The lowest, middle and highest channel were tested as representatives.

Frequency Band (MHz)				2402 ~ 2480			
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

Data rate VS Power:

The test setting software is offered by the manufactory. The pre-scan for the conducted power with all rates in each modulation and bands was used, and the worst case was found and used in all test cases.

Test software and Power Setting parameter			
Test Software	SSCOM V5.13.1		
Working Mode	BLE		
Test Channel	2402MHz	2426MHz	2480MHz
Power Setting	default	default	default

TEST REPORT

While testing transmitting mode of EUT, the internal modulation and continuously transmission was applied.

Radiated test mode: EUT transmitted signal with BT antenna;

Conducted test mode: EUT transmitted signal from BT RF port connected to SPA directly;

2.3 Test software list

Test Items	Software	Manufacturer	Version
Conducted emission	ESxS-K1	R&S	V2.1.0
Radiated emission	ES-K1	R&S	V1.71

2.4 Test peripherals list

Item No.	Name	Band and Model	Description
-	-	-	-

2.5 Test environment condition:

Test items	Temperature	Humidity
Minimum 6dB Bandwidth	23°C	52% RH
Maximum conducted output power and e.i.r.p.		
Power spectrum density		
Emission outside the frequency band		
Occupied bandwidth		
Radiated Emissions in restricted frequency bands	22°C	55% RH
Power line conducted emission	21°C	52% RH

TEST REPORT

2.6 Instrument list

Conducted Emission					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
☒	Test Receiver	R&S	ESR7	EC 6194	2026-02-17
☒	A.M.N.	R&S	ESH2-Z5	EC 3119	2026-07-22
☐	A.M.N.	R&S	ENV4200	EC 3558	2026-06-04
☒	Attenuator	Hua Xiang	Ts5-10db-6g	EC 6194-1	2026-01-14
☒	Shielded room	Zhongyu	-	EC 2838	2027-01-08
Radiated Emission					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
☒	Test Receiver	R&S	ESIB 26	EC 3045	2026-08-05
☒	Bilog Antenna	TESEQ	CBL 6112B	EC 6411	2026-09-27
☐	Pre-amplifier	R&S	AFS42-00101800-25-S-42	EC 5262	2026-11-06
☒	Pre-amplifier	Tonscend	tap01018050	EC 6432-1	2026-12-03
☒	Horn antenna	Tonscend	bha9120d	EC 6432-2	2026-04-10
☐	Horn antenna	ETS	3116c	EC 5955	2026-08-24
☒	Semi-anechoic chamber	Albatross project	-	EC 3048	2026-07-11
RF test					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
☒	PXA Signal Analyzer	Keysight	N9030A	EC 5338	2026-05-25
☒	PXA Signal Analyzer	Keysight	N9030B	EC 6078	2026-03-25
☒	Vector Signal Generator	Agilent	N5182B	EC 5175	2026-03-11
☒	MXG Analog Signal Generator	Agilent	N5181A	EC 5338-2	2026-03-11
☒	Test Receiver	R&S	ESCI 7	EC 4501	2026-03-04
☐	Universal Radio Communication Tester	R&S	CMW500	EC 6209	2027-01-14
☐	Universal Radio Communication Tester	R&S	CMW500	EC5944	2027-03-11
☒	Signal generator	Agilent	N5182A	EC 6172	2026-08-05
☒	Signal generator	Agilent	N5181A	EC 6171	2026-08-05
☒	Climate chamber	GWS	MT3065	EC 6021	2026-03-07
Additional instrument					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
☒	Therom-Hygrograph	Testo	175h1	EC 6640	2026-08-03
☒	Pressure meter	YM3	Shanghai Mengde	EC 3320	2026-08-04

TEST REPORT

2.7 Measurement uncertainty

The measurement uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.


Test item	Measurement uncertainty
Maximum peak output power	$\pm 0.74\text{dB}$
Radiated Emissions in restricted frequency bands below 1GHz	$\pm 4.90\text{dB}$
Radiated Emissions in restricted frequency bands above 1GHz	$\pm 5.02\text{dB}$
Emission outside the frequency band	$\pm 2.89\text{dB}$

TEST REPORT**3 Minimum 6dB bandwidth****Test result: Pass****3.1 Limit**

For systems using digital modulation techniques that may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz and 5725 - 5850 MHz bands, the minimum 6 dB bandwidth shall be at least 500 kHz.

3.2 Measurement Procedure

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

3.3 Test Configuration**3.4 Test Results of Minimum 6dB bandwidth**

Please refer to Appendix A

TEST REPORT

4 Maximum conducted output power and e.i.r.p.

Test result: Pass

4.1 Limit

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 W. (The e.i.r.p. shall not exceed 4 W)

If the transmitting antenna of directional gain greater than 6dBi is used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi. If there have a beam forming type, the limit should be the minimum of 30dBm and 30+ (6 –antenna gain-beam forming gain).

4.2 Measurement Procedure

- a) Set the RBW $\geq$ DTS bandwidth.
- b) Set VBW $\geq 3 \times$ RBW.
- c) Set span $\geq 3 \times$ RBW
- d) Sweep time = auto couple.
- e) Detector = peak.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use peak marker function to determine the peak amplitude level.

TEST REPORT

4.3 Test Configuration



4.4 Test Results of Maximum conducted output power

Please refer to Appendix A

TEST REPORT

5 Power spectrum density

Test result: Pass

5.1 Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.

If the transmitting antenna of directional gain greater than 6dBi is used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi. If there have a beam forming type, the limit should be the minimum of 8dBm/MHz and $8 + (6 - \text{antenna gain-beam forming gain})$.

5.2 Measurement Procedure

- a) Set analyzer center frequency to DTS channel center frequency.
- b) Set the span to 1.5 times the DTS bandwidth.
- c) Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- d) Set the VBW $\geq 3 \times \text{RBW}$.
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level within the RBW.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

TEST REPORT

5.3 Test Configuration



5.4 Test Results of Power spectrum density

Please refer to Appendix A

TEST REPORT

6 Emission outside the frequency band

Test result: Pass

6.1 Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

6.2 Measurement Procedure

Reference level measurement

Establish a reference level by using the following procedure:

- a) Set instrument center frequency to DTS channel center frequency.
- b) Set the span to ≥ 1.5 times the DTS bandwidth.
- c) Set the RBW = 100 kHz.
- d) Set the VBW $\geq 3 \times$ RBW.
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum PSD level.

Emission level measurement

- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the RBW = 100 kHz.
- c) Set the VBW $\geq 3 \times$ RBW.
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in 11.1 a) or 11.1 b). Report the three highest emissions relative to the limit.

TEST REPORT

6.3 Test Configuration



6.4 The results of Emission outside the frequency band

Please refer to Appendix A

TEST REPORT

7 Radiated Emissions in restricted frequency bands

Test result: Pass

7.1 Limit

The radiated emissions which fall in the restricted bands, must also comply with the radiated emission limits specified showed as below:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

7.2 Measurement Procedure

For Radiated emission below 30MHz:

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- Both X and Y axes of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

NOTE:

- The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

For Radiated emission above 30MHz:

TEST REPORT

- a) The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b) The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c) The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d) For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e) The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f) The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.


Note:

- 1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
- 2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
- 3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is $\geq 1/T$ (Duty cycle < 98%) or 3 x RBW (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.
- 4. All modes of operation were investigated and the worst-case emissions are reported


TEST REPORT

7.3 Test Configuration

For Radiated emission below 30MHz:




For Radiated emission 30MHz to 1GHz:



TEST REPORT

For Radiated emission above 1GHz:





TEST REPORT

7.4 Test Results of Radiated Emissions

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

The worst waveform from 30MHz to 1000MHz is listed as below:



TEST REPORT

Test data below 1GHz

Antenna	Frequency (MHz)	Corrected Reading (dBuV/m)	Correct Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector
H	32.910	25.4	13.3	40.0	14.6	QP
H	95.960	25.8	9.6	43.5	17.7	QP
H	135.924	27.7	13.8	43.5	15.8	QP
H	167.64	35.6	14.1	43.5	7.9	QP
H	263.867	33.1	14.2	46.0	12.9	QP
H	335.550	32.4	16.1	46.0	13.6	QP
V	31.552	36.0	13.2	40.0	4.0	QP
V	42.707	24.3	14.1	40.0	15.7	QP
V	95.960	27.1	9.6	43.5	16.4	QP
V	137.282	25.9	13.9	43.5	17.6	QP
V	253.391	25.8	13.8	46.0	20.2	QP
V	959.648	32.6	27.0	46.0	13.4	QP

Test result above 1GHz:

The emission was conducted from 1GHz to 25GHz

1M

CH	Antenna	Frequency (MHz)	Corrected Reading (dBuV/m)	Correct Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector
L	H	2402.00	91.48	31.73	Fundamental	/	PK
	V	2402.00	94.10	31.73	Fundamental	/	PK
	H	2390.00	35.00	31.71	74.00	39.0	PK
	V	2390.00	35.40	31.71	74.00	38.6	PK
	H	4804.00	33.00	-13.92	74.00	41.0	PK
	H	7206.00	37.40	-8.96	74.00	36.6	PK
	H	9608.00	40.60	-4.97	74.00	33.4	PK
	V	4804.00	33.00	-13.92	74.00	41.0	PK
	V	7206.00	36.80	-8.96	74.00	37.2	PK
	V	9608.00	40.20	-4.97	74.00	33.8	PK
M	H	4852.00	34.40	-13.68	74.00	39.6	PK
	H	7278.00	37.00	-8.88	74.00	37.0	PK

TEST REPORT

	H	9760.00	40.60	-4.78	74.00	33.4	PK
	V	4852.00	32.10	-13.68	74.00	41.9	PK
	V	7278.00	36.80	-8.88	74.00	37.2	PK
	V	9760.00	41.00	-4.78	74.00	33.0	PK
H	H	2480.00	89.22	31.87	Fundamental	/	PK
	V	2480.00	86.38	31.87	Fundamental	/	PK
	H	2483.50	59.00	31.88	74.00	15.0	PK
	H	2483.50	46.90	31.88	54.00	7.1	AV
	V	2483.50	59.30	31.88	74.00	14.7	PK
	V	2483.50	46.80	31.88	54.00	7.2	AV
	H	4960.00	44.80	-13.43	74.00	29.2	PK
	H	7440.00	37.40	-8.91	74.00	36.6	PK
	H	9920.00	40.20	-4.97	74.00	33.8	PK
	V	4960.00	42.80	-13.43	74.00	31.2	PK
	V	7440.00	47.00	-8.91	74.00	27.0	PK
	V	9920.00	40.40	-4.97	74.00	33.6	PK

- Remark: 1. Correct Factor = Antenna Factor + Cable Loss (- Amplifier, for higher than 1GHz), the value was added to Original Receiver Reading by the software automatically.
 2. Corrected Reading = Original Receiver Reading + Correct Factor
 3. Margin = Limit - Corrected Reading
 4. If the PK Corrected Reading is lower than AV limit, the AV test can be elided.

Example: Assuming Antenna Factor = 30.20dB/m, Cable Loss = 2.00dB,
 Gain of Preamplifier = 32.00dB, Original Receiver Reading = 10.00dBuV,
 Limit = 40.00dBuV/m.
 Then Correct Factor = 30.20 + 2.00 – 32.00 = 0.20dB/m;
 Corrected Reading = 10dBuV + 0.20dB/m = 10.20dBuV/m;
 Margin = 40.00dBuV/m - 10.20dBuV/m = 29.80dB.


8 Power line conducted emission

Test result: Pass

8.1 Limit

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	QP	AV
0.15-0.5	66 to 56*	56 to 46 *
0.5-5	56	46
5-30	60	50
* Decreases with the logarithm of the frequency.		

8.2 Test Configuration



8.3 Measurement Procedure


Measured levels of ac power-line conducted emission shall be the emission voltages from the voltage probe, where permitted, or across the 50 Ω LISN port (to which the EUT is connected), where permitted, terminated into a 50 Ω measuring instrument. All emission voltage and current measurements shall be made on each current-carrying conductor at the plug end of the EUT power cord by the use of mating plugs and receptacles on the LISN, if used. Equipment shall be tested with power cords that are normally supplied or recommended by the manufacturer and that have electrical and shielding characteristics that are the same as those cords normally supplied or recommended by the manufacturer. For those measurements using a LISN, the 50 Ω measuring port is terminated by a measuring instrument having 50 Ω input impedance. All other ports are terminated in 50 Ω loads.

Tabletop devices shall be placed on a platform of nominal size 1 m by 1.5 m, raised 80 cm above the reference ground plane. The vertical conducting plane or wall of an RF-shielded (screened) room shall be located 40 cm to the rear of the EUT. Floor-standing devices shall be placed either directly on the reference ground-plane or on insulating material as described in ANSI C63.4. All other surfaces of tabletop or floor-standing EUTs shall be at least 80 cm from any other grounded conducting surface, including the case or cases of one or more LISNs.


The bandwidth of the test receiver is set at 9 kHz.

8.4 Test Results of Power line conducted emission

L Line



N Line



TEST REPORT

Test Data:

No.	Frequency	Limit dBuV	Level dBuV	Margin dB	Reading dBuV	Factor dB	Detector	Phase
1	177.000kHz	64.63	43.87	20.76	33.67	10.20	QP	L1
2	222.000kHz	62.74	39.77	22.97	29.57	10.20	QP	L1
3	280.500kHz	60.80	33.42	27.38	23.22	10.20	QP	L1
4	348.000kHz	59.01	41.96	17.05	31.76	10.20	QP	L1
5	519.000kHz	56.00	35.14	20.86	24.94	10.20	QP	L1
6	6.833MHz	60.00	14.90	45.10	4.20	10.70	QP	L1
7	172.500kHz	64.84	44.70	20.14	34.60	10.10	QP	N
8	249.000kHz	61.79	37.29	24.50	27.19	10.10	QP	N
9	316.500kHz	59.80	28.99	30.81	18.89	10.10	QP	N
10	523.500kHz	56.00	30.62	25.38	20.42	10.20	QP	N
11	4.767MHz	56.00	15.95	40.05	5.35	10.60	QP	N
12	15.986MHz	60.00	14.77	45.23	3.47	11.30	QP	N
13	181.500kHz	54.42	17.67	36.75	7.47	10.20	AV	L1
14	222.000kHz	52.74	15.50	37.24	5.30	10.20	AV	L1
15	280.500kHz	50.80	17.47	33.33	7.27	10.20	AV	L1
16	357.000kHz	48.80	7.20	41.60	-3.00	10.20	AV	L1
17	442.500kHz	47.01	8.49	38.52	-1.71	10.20	AV	L1
18	523.500kHz	46.00	15.40	30.60	5.20	10.20	AV	L1
19	195.000kHz	53.82	22.40	31.42	12.30	10.10	AV	N
20	244.500kHz	51.94	12.78	39.16	2.68	10.10	AV	N
21	339.000kHz	49.23	7.56	41.67	-2.54	10.10	AV	N
22	474.000kHz	46.44	7.60	38.84	-2.60	10.20	AV	N
23	523.500kHz	46.00	13.15	32.85	2.95	10.20	AV	N
24	4.520MHz	46.00	3.27	42.73	-7.33	10.60	AV	N

Remark: 1. Correct Factor = LISN Factor + Cable Loss, the value was added to Original Receiver Reading by the software automatically.

2. Level = Reading + Factor

3. Margin = Limit - Level

4. If the PK Corrected Reading is lower than AV limit, the AV test can be elided.

9 Occupied Bandwidth

Test result: Tested

9.1 Limit

None


9.2 Measurement Procedure

The occupied bandwidth per RSS-Gen was measured using the Spectrum Analyzer.

The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts.

The resolution bandwidth (RBW) shall be in the range of 1% to 5% of the occupied bandwidth (OBW) and video bandwidth (VBW) shall be approximately 3x RBW.

9.3 Test Configuration



9.4 The results of Occupied Bandwidth

Please refer to Appendix A

TEST REPORT

10 Antenna requirement

Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

Result:

EUT uses permanently attached antenna to the intentional radiator, so it can comply with the provisions of this section.

***** END *****