

FCC §1.1310 & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to 1.1310, 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Averaging Time (minutes)
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	/	/	f/1500	30
1500–100,000	/	/	1.0	30

f = frequency in MHz;

* = Plane-wave equivalent power density;

MPE Calculation

Prediction of power density at the distance of the applicable MPE limit

$$S = PG/4\pi R^2$$

Where: S = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_i \frac{S_i}{S_{Limit,i}} \leq 1$$

Calculated Data:

Module	Frequency (MHz)	Antenna Gain		Tune-up Power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
		(dBi)	(numeric)	(dBm)	(mW)			
2.4G	2402-2480	3	2.00	15	31.62	20.00	0.0126	1.0
	2412-2462	3	2.00	15	31.62	20.00	0.0126	1.0
DSRC	5860-5920	5	3.14	0	1.0	20.00	0.0006	1.0

Note: The maximum tune-up power including tolerance was declared by manufacturer.

The WLAN or Bluetooth can transmit simultaneously with DSRC:

$$\sum_i \frac{S_i}{S_{Limit,i}}$$

$$\begin{aligned}
 &= S_{2.4}/S_{limit-2.4} + S_{DSRC}/S_{limit-DSRC} \\
 &= 0.0126/1 + 0.0006/1 \\
 &= 0.0132 \\
 &< 1.0
 \end{aligned}$$

Result: The device meet FCC MPE at 20 cm distance