

## RF Exposure Requirements

---

Product Description: Panorama Camera

Model No.: Hi720, Hi720 ProC, C720, Ball720

FCC ID: 2AL5FHI720

According to the KDB 447498 D01 v06 section 4.3.1, for 100 MHz to 6 GHz and test separation distances  $\leq 50$  mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

-  $f(\text{GHz})$  is the RF channel transmit frequency in GHz

- Power and distance are rounded to the nearest mW and mm before calculation<sup>17</sup>

- The result is rounded to one decimal place for comparison

### Wi-Fi

Tx frequency range: 2412~2462MHz

Maximum Tx channel: 2412MHz

Min. test separation distance: 5mm

Maximum Conducted Output Power: 9.06dBm

Tune-Up output power: 9.5dBm

Calculate result: 2.8

Limit: 3.0

The exclusion thresholds is  $2.8 < 3.0$ , so the transmitter complies with the RF exposure requirements and the SAR is not required.