

Test Report for FCC

FCC ID :2AL6N-IOFITGP

Report Number		ESTRFC1804-007		
Applicant	Company name	Salted Venture Co., Ltd.		
	Address	06227 340, Nonhyeon-ro, Gangnam-gu, Seoul, Republic of Korea		
	Telephone	+82-02-552-0815		
	Contact person	Lee SeHee		
Product	Product name	IOFIT GOLF PRO		
	Model No.	GPWH	Manufacturer	Salted Venture Co., Ltd.
	Serial No.	None	Country of origin	KOREA
Test date	30-Mar-18		Date of issue	23-Apr-18
Testing location	140-16, Eongmalli-ro, Majang-myeon, Icheon-si, Gyeonggi-do 467-811, R. O. Korea			
Standard	FCC PART 15 Subpart C (15.247), ANSI C 63.10(2013), KDB 558074 D01(2016)			
Measurement facility registration number		659627		
Tested by	Senior Engineer I.K. Hong		(Signature)	
Reviewed by	Engineering Manager K.B. Lee		(Signature)	
Abbreviation				
* Note - This test report is not permitted to copy partly without our permission - This test result is dependent on only equipment to be used - This test result based on a single evaluation of one sample of the above mentioned - Additional Model : GPM-BK, GPL-BK, GPM-WH, GPL-WH, GCM-GY, GCL-GY GCM-SV, GCL-SV, GCM-PK, GCL-PK, GCM-BG, GCL-BG (refer to Appendix 2) - Only Changed an antenna from Basic model (Test result refer to the ETSESTRCE1710-001)				

Contents

1. Laboratory Information	3
2. Description of EUT	4
3. Test Standards	5
4. Measurement condition	6
5. DTS bandwidth	10
5.1 Test procedure	10
5.2 Test instruments and measurement setup	10
5.3 Measurement results	10
5.4 Trace data	11
6. Maximum Peak Output Power	13
6.1 Test procedure	13
6.2 Test instruments and measurement setup	13
6.3 Measurement results	13
6.4 Trace data	14
7. Maximum power spectral density level in the fundamental emission	16
7.1 Test procedure	16
7.2 Test instruments and measurement setup	16
7.3 Measurement results	16
7.4 Trace data	17
8. Emissions in non-restricted frequency bands	19
8.1 Test procedure	19
8.2 Test instruments and measurement setup	19
8.3 Measurement results	19
8.4 Trace data of band-edge & out of emissioin	20
9. Measurement of radiated emission	24
9.1 Measurement equipment	24
9.2 Environmental conditions	24
9.3 Measurement Instrument setting for Radiated Emission	25
9.4 Test Data	26
10. Photographs of test setup	34
10.1.Setup for Radiated Test : (30 ~ 1 000) MHz	34
10.2.Setup for Radiated Test : Above 1 GHz	35
10.4. Photographs of EUT	36

Appendix 1. Antenna Requirement

Appendix 2. Additional model

1. Laboratory Information

1.1 General

This EUT (Equipment Under Test) has been shown to be capable of compliance with the applicable technical standards and is tested in accordance with the measurement procedures as indicated in this report.

ESTECH Lab attests to accuracy of test data. All measurement reported herein were performed by ESTECH Co., Ltd.

ESTECH Lab assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

1.2 Test Lab.

Corporation Name : ESTECH Co., Ltd.

Head Office : Suite 1015 World Meridian II, 123 Gasan Digital 2-ro, Geumcheon-gu, Seoul 153-759, R. O. Korea

EMC/Telecom/Safety Test Lab : 140-16, Eongmali-ro, Majang-myeon, Icheon-si,
Gyeonggi-do 467-811, R. O. Korea

1.3 Official Qualification(s)

MSIP : Granted Accreditation from Ministry of Information & Communication for EMC, Safety and Telecommunication

KOLAS : Accredited Lab By Korea Laboratory Accreditation Schema base on CENELEC requirements

FCC : Conformity Assessment Body(CAB) with registration number 659627 under APEC TEL MRA between the RRA and the FCC

VCCI : Granted Accreditation from Voluntary Control Council for Interference from ITE

2. Description of EUT

2.1 Summary of Equipment Under Test

Modulation Type	: Bluetooth (GFSK)
Transfer Rate	: 1 Mbps
Number of Channel	: 40 ch
PEAK Output Power	: GFSK : 0.67 mW
Rating	: DC 3.0 V (Coin cell Battery x 2EA)
Receipt Date	: 11-Nov-16
X-tal list(s) or Frequencies generated	: The highest operating frequency is 2480 MHz(Bluetooth) Bluetooth : 2.4 GHz

2.2 General descriptions of EUT

- Pressor Sensors
- Coin Cell Battery (CR2032)
- Battery life : 50 hours of continuous use
- Bluetooth 4.2 (BLE)
- OS support : Android, iOS
- IOFIT Golf Pro (GPM-BK) – This device is not for the medical use
- Only changed an antenna from Basic model

3. Test Standards

Test Standard : FCC PART 15 Subpart C (15.247)

This Standard sets out the regulations under which an intentional, unintentional, or incidental radiator may be operated without an individual license. It also contains the technical specifications, administrative requirements and other conditions relating to the marketing of Part 15 devices.

Test Method : ANSI C 63.10 (2009) & KDB558074 D01(2015)

This standard sets forth uniform methods of measurement of radio-frequency (RF) signals and noise emitted from both unintentional and intentional emitters of RF energy in the frequency range 9 kHz to 40 GHz. Methods for the measurement of radiated and AC power-line conducted radio noise are covered and may be applied to any such equipment unless otherwise specified by individual equipment requirements. These methods cover measurement of certain devices that deliberately radiate energy, such as intentional emitters, but does not cover licensed transmitters. This standard is not intended for certification/approval of avionic equipment or for industrial, scientific, and medical (ISM) equipment. These methods apply to the measurement of individual units or systems comprised of multiple units.

Summary of Test Results

Applied Standard : 47 CFR Part 15 Subpart C				remark
Standard	Test Type	Result	Remark	Limit
15.207	AC Power Conducted Emission	N/A		
15.205 & 15.209	Restricted band / Intentional Radiated Emission	Pass	Meet the requirement	
15.247(a)(2)	6 dB Bandwidth	Pass	Meet the requirement	Min. 500 kHz
	Occupied Bandwidth			
15.247(b)(3)	Maximum Peak/average output power	Pass	Meet the requirement	Max. 30 dBm
15.247(c)	Transmitter Radiated Emission	Pass	Meet the requirement	Table 15.209
15.247(e)	Power Spectral Density	Pass	Meet the requirement	Max. 8 dBm
15.247(d)	Band Edge Measurement	Pass	Meet the requirement	20 dB less

4. Measurement Condition

4.1 EUT Operation

a. Channel

Ch.	Frequency	Ch.	Frequency
0	2402 MHz	21	2444 MHz
1	2404 MHz	22	2446 MHz
2	2406 MHz	23	2448 MHz
3	2408 MHz	24	2450 MHz
4	2410 MHz	25	2452 MHz
5	2412 MHz	26	2454 MHz
6	2414 MHz	...	...
...	...	39	2480 MHz
20	2442 MHz		

b. Measurement Channel : Bluetooth : Low(2402 MHz), Middle(2442 MHz), High(2480 MHz)


c. Test Mode : Continuous Output, GFSK

d. Test rate : 1 Mbps

4.2 EUT Operation.

- The EUT was in the following operation mode during all testing
 - * Bluetooth operation check
 - * Transmit mode were measured each channels(Low, Middle, High)

4.3 Configuration and Peripherals



4.4 EUT and Support equipment

Equipment Name	Model Name	S/N	Manufacturer	Remark (FCC ID)
IOFIT GOLF PRO	GPWH	NONE	Salted Venture Co., Ltd.	EUT


4.5 Cable Connecting

Start Equipment		End Equipment		Cable Standard		Remark
Name	I/O port	Name	I/O port	Length	Shielded	
IOFIT GOLF PRO	Wireless (Bluetooth)	—	—	—	—	

4.6 DUTY CYCLE OF TEST SIGNAL

Duty cycle is < 98%, duty factor shall be considered.

duty cycle = $1.088/1.175=0.926$, duty factor = $10 \cdot \log(1/0.6979)=1.562$



5. DTS bandwidth

5.1 Test procedure

558074 D01 DTS Meas Guidance v03r05 Option 2

5.2 Test instruments and measurement setup

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described above (i.e., RBW = 100 kHz, VBW $\geq$ 3 X RBW, peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be $\geq$ 6 dB.

Limits : FCC § 15.247(a)(2)

6dB Bandwidth Test Instruments

Description	Model	Serial Number	Cal. Due Date
Spectrum Analyzer	E4440A	US42041291	4-Jan-18
RF Cable	Length: 30 cm	–	
–Spectrum Analyzer $\Leftrightarrow$ EUT	Loss: 0.5 dB	–	

5.3 Measurement results

EUT	IOFIT GOLF PRO	MODEL	GPWH
MODE	GFSK	ENVIRONMENTAL CONDITION	22.0 °C, 47.0 % R.H.
INPUT POWER	3.0 Vd.c.		

Channel Frequency (MHz)	Occupied Bandwidth(MHz)	Bandwidth at 6dB below(MHz)	Minimum Limit (MHz)	PASS/FAIL
2402	1.33	0.69	0.5	PASS
2442	1.23	0.66	0.5	PASS
2480	1.05	0.67	0.5	PASS

5.4 Trace data (ch_0)



(ch_20)





Estech
your best partner

(ch_39)



6. Maximum peak conducted output power

6.1 Test procedure

KDB 558074 D01 DTS Meas Guidance V03r05 9.1.1 Integrated band power method

6.2 Test instruments and measurement setup

- a) Set the RBW $\geq$ DTS.
- b) Set VBW $\geq 3 \times$ RBW.
- c) Set span $\geq 3 \times$ RBW
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use peak marker function to determine the peak amplitude level.

Limits : FCC § 15.247

Maximum Peak Output Power Test Instruments


Description	Model	Serial Number	Cal. Due Date
Spectrum Analyzer	E4440A	US42041291	4-Jan-18
RF Cable	Length: 30 cm	–	
–Spectrum Analyzer $\Leftrightarrow$ EUT	Loss: 0.5 dB	–	

6.3 Measurement results


EUT	IOFIT GOLF PRO	MODEL	GPWH
MODE	GFSK	ENVIRONMENTAL CONDITION	22.0 °C, 45.0 % R.H.
INPUT POWER	3.0 Vd.c.		

CHANNEL	Channel frequency (MHz)	Conducted Power Output(dBm)			Limit[1W] (dBm)	PASS/FAIL
		Detector	(dBm)	(mW)		
0	2 402	PEAK	–2.03	0.627	30.0	PASS
20	2 442	PEAK	–2.16	0.608	30.0	PASS
39	2 480	PEAK	–2.58	0.552	30.0	PASS


6.4 Trace data (ch_0)



(ch_20)



(ch_39)



7. Maximum power spectral density level in the fundamental emission

7.1 Test procedure

KDB 558074 D01 DTS Meas Guidance V03r05 10.2 Method PKPSD (peak PSD)

7.2 Test instruments and measurement setup

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance, and is optional if the maximum conducted (average) output power was used to demonstrate compliance.

- a) Set analyzer center frequency to DTS channel center frequency.
- b) Set the span to 1.5 times the DTS bandwidth.
- c) Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- d) Set the VBW $\geq 3 \times \text{RBW}$
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level within the RBW.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

Limits FCC § 15.247


The peak power density Test Instruments

Description	Model	Serial Number	Cal. Due Date
Spectrum Analyzer	E440A	US42041291	4-Jan-18
RF Cable	Length: 30 cm	–	
–Spectrum Analyzer $\Leftrightarrow$ EUT	Loss: 0.5 dB	–	


7.3 Measurement results

EUT	IOFIT GOLF PRO	MODEL	GPWH	
MODE	GFSK	ENVIRONMENTAL CONDITION	21.0 °C, 45.0 % R.H.	
INPUT POWER	3.0 Vd.c.			
CHANNEL	Channel Frequency (MHz)	Measured Power Spectral Density (dBm)	Maximum Permissible Power Density (dBm/3kHz)	Margin
0	2 402	−15.72	8.0	23.72
20	2 442	−16.13	8.0	24.13
39	2 480	−15.16	8.0	23.16


7.4 Trace data (ch_0)



(ch_20)



(ch_39)



8. Emissions in non-restricted frequency bands

8.1 Test procedure

KDB 558074 D01 DTS Meas Guidance V03r05 11.0 Emissions in non-restricted frequency

8.2 Test instruments and measurement setup

The DTS rules specify that in any 100 kHz bandwidth outside of the authorized frequency band, the power shall be attenuated according to the following conditions(15.247(d))

- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the RBW = 100 kHz.
- c) Set the VBW $\geq 3 \times$ RBW.
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

Limits FCC § 15.247

Band Edge&Out of Emission Test Instruments

Description	Model	Serial Number	Cal. Due Date
Spectrum Analyzer	E4440A	US42041291	4-Jan-18
RF Cable	Length: 30 cm		–
–Spectrum Analyzer <=> EUT	Loss: 0.5 dB		–

8.3 Measurement results of band-edge & out of emission


EUT	IOFIT GOLF PRO	MODEL	GPWH
MODE	GFSK	ENVIRONMENTAL CONDITION	21.0 °C, 45.0 % R.H
INPUT POWER	3.0 Vd.c.		

CHANNEL	Channel Frequency (MHz)	limit	PASS/FAIL
0	2 402	20dBc	PASS
39	2 480	20dBc	PASS



8.4 Trace data of band-edge & Out of Emission (ch_0)



(ch_39)





(ch_0)







Estech
your best partner

(ch_20)



(ch_39)



9. Measurement of radiated disturbance

Above 30 MHz Electric Field strength was measured in accordance with FCC PART 15.205, 15.209 . The test setup was made according to ANSI C 63.10 (2013) & KDB 558074 D01 Semi-anechoic chamber, which allows a 3 m distance measurement. The EUT was placed in the center of styrofoam. turntable. The height of this table was 0.8 m. The measurement was conducted with both horizontal and vertical antenna polarization. The turntable has fully rotated. For further description of the configuration refer to the picture of the test setup.

9.1 Measurement equipments

Equipment Name	Type	Manufacturer	Serial No.	Next Calibration date
TEST Receiver	ESCI7	ROHDE & SCHWARZ	100916	15-Nov-17
Logbicon Antenna	VULB 9168	SCHWARZBECK	193	12-Oct-17
Turn Table	DT3000-2t	Innco System GmbH	N/A	–
Antenna Mast	MA4000-EP	Innco System GmbH	N/A	–
PREAMPLIFIER	8449B	AGILENT	3008A00581	15-Nov-17
Horn Antenna	BBHA9120D	SCHWARZBECK	469	25-Aug-17
Test Receiver	ESPI7	ROHDE & SCHWARZ	100185	15-Nov-17
Spectrum Analyzer	R3273	ADVANTEST	121200664	21-Oct-17
Turn Table	DT1500-S	Innco System GmbH	N/A	–
Antenna Mast	MA4000-EP	Innco System GmbH	N/A	–
Pyramidal Horn Antenna	3160-09-01	EST-LINDGREN	102642	25-Aug-17
Antenna Master & Turn table controller	CO2000-P	Innco System GmbH	CO2000/642 /28051111/L	–

9.2 Environmental Condition

Below 1 GHz –Test Place : 10 m Semi-anechoic chamber

BT(BLE) MODE

Temperature (°C) : 20.4 °C

Humidity (% R.H.) : 52.2 % R.H.

Above 1 GHz–Test Place : 3 m Semi-anechoic chamber

BT(BLE) MODE

Temperature (°C) : 21.6 °C

Humidity (% R.H.) : 53.2 % R.H.

9.3 Measurement Instrument setting for Radiated Emission

9.3.1 Frequency range below 1 GHz

Detector : Quasi-Peak

9.3.2 Frequency range above 1 GHz

Peak Power Measurement Procedure (KDB 558074 section 12.2.4)

- a. RBW : 1 MHz , VBW : 3 MHz
- b. Trace mode = max hold
- c. Detector : Peak
- d. Sweep time = auto

Average Power Measurement Procedures (KDB 558074 section 12.2.5.2)

- a. Set analyzer center frequency to the frequency associated with the emission
- b. RBW : 1 MHz , VBW : 3 MHz
- c. Detector : RMS
- d. Sweep time = auto

Note

Band	Duty cycle(%)	Ton (ms)	Ton + Toff (ms)	DCF=10*log(1/Duty) (dB)
BT(BLE)	69.8	0.437	0.626	1.56

* This was applied of duty cycle factor for average value because of measured with the EUT transmitting continuously less than 98 % duty cycle at its maximum power control level.

9.4 Test data(30 MHz ~ 1 000 MHz)

Test Date : 30-Mar-18

Measurement Distance : 3 m

Frequency (MHz)	Reading (dB μ V)	Position (V/H)	Height (m)	Correction Factor		Result Value(Quasi-peak)		
				Ant Factor (dB)	Cable (dB)	Limit (dB μ V/m)	Result (dB μ V/m)	Margin (dB)
38.00	13.50	H	1.0	13.24	0.91	40.00	27.65	12.35
52.70	14.90	V	1.5	13.69	1.07	40.00	29.66	10.34
194.20	22.38	H	1.6	10.50	2.13	43.50	35.01	8.49
254.30	28.90	H	1.5	12.02	2.47	46.00	43.39	2.61
513.20	29.40	H	1.5	18.20	3.57	46.00	51.17	-5.17
615.10	32.80	H	1.5	20.09	3.98	46.00	56.87	-10.87
Remark	H : Horizontal, V : Vertical TEST MODE : BT BLE (CH : 20 – 2 442 MHz) *Checked in all 3 axis and the maximum measured data were reported.(Worst data is X axis of position) *CL = Cable Loss(In case of below 1 000 MHz) *Result Value = Reading + Ant Factor + Cable loss *The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection at frequency below 1 GHz.							

9.4-1 Test Data(Low)

Test Date : 30-Mar-18

Measurement Distance : 3 m

Frequency (MHz)	Reading (dB μ V)	Position (V/H)	Height (m)	Correction Factor		Duty Cycle Correction(dB)	Result Value		
				Ant Factor (dB)	AMP & Cable (dB)		Limit (dB μ V/m)	Result (dB μ V/m)	Margin (dB)
PEAK(RBW: 1 MHz VBW: 3 MHz)									
2373.40	54.85	H	1.5	26.03	-30.13	0.00	74.00	50.75	23.25
2373.40	50.99	V	1.6	26.06	-30.12	0.00	74.00	46.93	27.07
4804.00	49.80	H	1.7	30.93	-27.04	0.00	74.00	53.69	20.31
4804.00	46.26	V	1.9	30.93	-27.04	0.00	74.00	50.15	23.85
AV(RBW: 1 MHz VBW: 3 MHz)									
2324.60	30.23	H	1.5	26.01	-30.14	1.56	54.00	27.66	26.34
2367.60	30.78	V	1.6	26.02	-30.14	1.56	54.00	28.22	25.78
4804.00	44.48	H	1.7	30.93	-27.04	1.56	54.00	49.93	4.07
4804.00	29.06	V	1.9	30.93	-27.04	1.56	54.00	34.51	19.49
Remark	H : Horizontal, V : Vertical TEST MODE : CH : 0 – 2 402 MHz (x postion)								
	*The TX signal wasn't detected from 3th harmonics.								
	*Checked in all 3 axis and the maximum measured data were reported.(Worst data is X axis of position)								
	*Total = Reading Value + Antenna Factor + Cable Loss – Amp Gain + Duty Cycle Correction								

9.4-2 Test Data(Middle)

Test Date : 30-Mar-18

Measurement Distance : 3 m

Frequency (MHz)	Reading (dB μ V)	Position (V/H)	Height (m)	Correction Factor		Duty Cycle Correction(dB)	Result Value		
				Ant Factor (dB)	AMP & Cable (dB)		Limit (dB μ V/m)	Result (dB μ V/m)	Margin (dB)
PEAK(RBW: 1 MHz VBW: 3 MHz)									
4884.00	51.43	H	1.5	31.16	-26.81	0.00	74.00	55.78	18.22
4884.00	50.95	V	1.7	31.16	-26.81	0.00	74.00	55.30	18.70
AV(RBW: 1 MHz VBW: 3 MHz)									
4884.00	38.86	H	1.5	31.16	-26.81	1.56	54.00	44.77	9.23
4884.00	29.06	V	1.7	31.16	-26.81	1.56	54.00	34.97	19.03
Remark	H : Horizontal, V : Vertical TEST MODE : CH : 20 – 2 442 MHz (x postion)								
	*The TX signal wasn't detected from 3th harmonics.								
	*Checked in all 3 axis and the maximum measured data were reported.(Worst data is X axis of position)								
	*Total = Reading Value + Antenna Factor + Cable Loss – Amp Gain + Duty Cycle Correction								

9.4-3 Test Data(High)

Test Date : 30-Mar-18

Measurement Distance : 3 m


Frequency (MHz)	Reading (dB μ V)	Position (V/H)	Height (m)	Correction Factor		Duty Cycle Correction(dB)	Result Value		
				Ant Factor (dB)	AMP & Cable (dB)		Limit (dB μ V/m)	Result (dB μ V/m)	Margin (dB)
PEAK(RBW: 1 MHz VBW: 3 MHz)									
2496.75	54.49	H	2.0	26.30	-29.93	0.00	74.00	50.86	23.14
2496.15	47.16	V	1.8	26.30	-29.93	0.00	74.00	43.53	30.47
4960.00	49.92	H	1.6	31.38	-26.70	0.00	74.00	54.60	19.40
4960.00	43.85	V	2.1	31.38	-26.70	0.00	74.00	48.53	25.47
AV(RBW: 1 MHz VBW: 3 MHz)									
2483.50	42.26	H	2.0	26.30	-29.93	1.56	54.00	40.19	13.81
2483.50	32.52	V	1.8	26.30	-29.93	1.56	54.00	30.45	23.55
4960.00	44.46	H	1.6	31.38	-26.70	1.56	54.00	50.70	3.30
4960.00	30.91	V	2.1	31.38	-26.70	1.56	54.00	37.15	16.85
Remark	H : Horizontal, V : Vertical TEST MODE : CH : 39 – 2 480 MHz (x postion)								
	*The TX signal wasn't detected from 3th harmonics.								
	*Checked in all 3 axis and the maximum measured data were reported.(Worst data is X axis of position)								
	*Total = Reading Value + Antenna Factor + Cable Loss – Amp Gain + Duty Cycle Correction								

9.4-4 Restricted Band Edges

Band Edges(CH Low)


Detector mode:Peak

Polarity:Horizontal



Detector mode:Average


Polarity:Horizontal



Band Edges(CH Low)


Detector mode:Peak

Polarity:Vertical



Detector mode:Average


Polarity:Vertical



Band Edges(CH High)


Detector mode:Peak

Polarity:Horizontal



Detector mode:Average


Polarity:Horizontal



Band Edges(CH High)


Detector mode:Peak

Polarity:Vertical



Detector mode:Average

Polarity:Vertical



10. Photographs of test setup

10.1.Setup for Radiated Test : (30 ~ 1 000) MHz

[Front]




[Rear]



10.2.Setup for Radiated Test : Above 1 GHz

[Front]



[Rear]



10.3. Photographs of EUT

[Front]



[Rear]



Appendix 1 . Antenna Requirement

1. Antenna Requirement

1.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.204

1.2 Antenna Connected Construction

The antenna types used in this product are Intergrated helical antenna . The maximum Gain of this antenna is 1.97 dBi.

Appendix 2.

2. additional model

2.1. additional model name

GPM-BK, GPL-BK, GPM-WH, GPL-WH, GCM-GY, GCL-GY
GCM-SV, GCL-SV, GCM-PK, GCL-PK, GCM-BG, GCL-BG

2.2 Description for additional model

It is only changed design of shoes and color