

FCC Part 15C Measurement and Test Report

For

SZZT ELECTRONICS CO.,LTD

SZZT Industrial Park, NO.3 Tongguan Road, Guangming New

District, Shenzhen, Guangdong, China

FCC ID: 2AL7RKS8223

FCC Rule(s): FCC Part 15.225

Product Description: Smart wireless pos

Tested Model: KS8223

Report No.: STR17048102I-6

Tested Date: 2017-04-12 to 2017-05-31

Issued Date: 2017-06-01

Tested By: Leo Lee / Engineer

Leo Lee

Reviewed By: Suan Su / Engineer

Suan Su

Approved & Authorized By: Jandy so / PSQ Manager

Jandy so

Prepared By:

Shenzhen SEM.Test Technology Co., Ltd.

1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road,
Bao'an District, Shenzhen, P.R.C. (518101)

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen SEM.Test Technology Co., Ltd.

TABLE OF CONTENTS

1. GENERAL INFORMATION.....	3
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	3
1.2 TEST STANDARDS.....	4
1.3 TEST METHODOLOGY.....	4
1.4 TEST FACILITY.....	4
1.5 EUT SETUP AND TEST MODE.....	5
1.6 MEASUREMENT UNCERTAINTY.....	5
1.7 TEST EQUIPMENT LIST AND DETAILS.....	5
2. SUMMARY OF TEST RESULTS.....	6
3. ANTENNA REQUIREMENT.....	7
3.1 STANDARD APPLICABLE.....	7
3.2 TEST RESULT.....	7
4. RADIATED EMISSIONS.....	8
4.1 STANDARD APPLICABLE.....	8
4.2 TEST PROCEDURE.....	8
4.3 CORRECTED AMPLITUDE & MARGIN CALCULATION.....	9
4.4 ENVIRONMENTAL CONDITIONS.....	9
4.5 SUMMARY OF TEST RESULTS/PLOTS.....	10
5. OUT OF BAND EMISSIONS.....	13
5.1 STANDARD APPLICABLE.....	13
5.2 TEST PROCEDURE.....	13
5.3 ENVIRONMENTAL CONDITIONS.....	13
5.4 SUMMARY OF TEST RESULTS/PLOTS.....	13
6. FREQUENCY STABILITY.....	15
6.1 STANDARD APPLICABLE.....	15
6.2 TEST PROCEDURE.....	15
6.3 ENVIRONMENTAL CONDITIONS.....	15
6.4 SUMMARY OF TEST RESULTS/PLOTS.....	15
7. CONDUCTED EMISSIONS.....	17
7.1 TEST PROCEDURE.....	17
7.2 BASIC TEST SETUP BLOCK DIAGRAM.....	17
7.3 ENVIRONMENTAL CONDITIONS.....	17
7.4 TEST RECEIVER SETUP.....	17
7.5 SUMMARY OF TEST RESULTS/PLOTS.....	18
7.6 CONDUCTED EMISSIONS TEST DATA.....	18
8. EMISSION BANDWIDTH.....	21
8.1 APPLICABLE STANDARD.....	21
8.2 TEST PROCEDURE.....	21
8.3 ENVIRONMENTAL CONDITIONS.....	21
8.4 SUMMARY OF TEST RESULTS/PLOTS.....	21

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: SZZT ELECTRONICS CO.,LTD
Address of applicant: SZZT Industrial Park,NO.3TongguanRoad,Guangming New District, Shenzhen, Guangdong, China

Manufacturer: SZZT ELECTRONICS CO.,LTD
Address of manufacturer: SZZT Industrial Park,NO.3TongguanRoad,Guangming New District, Shenzhen, Guangdong, China

General Description of EUT	
Product Name:	Smart wireless pos
Brand Name:	SZZT
Model No.:	KS8223
Adding Model(s):	/
Hardware version:	KS8223_MB_V2.1.2
Software version:	V1.0.0
Rated Voltage:	DC 3.7V by battery
Battery Capacity:	5000mAh
Power Adapter:	Model: RJ-AS050200C010 Input: 100`240V, 50/60Hz; Output: DC 5V, 2A
Note: The test data is gathered from a production sample, provided by the manufacturer.	

Technical Characteristics of EUT	
Support Standards:	NFC
Frequency Range:	13.56MHz
Max. Field Strength:	81.52dBuV/m (at 3m)
Antenna Type:	Integral Antenna
Antenna Gain:	1.0dBi
Device Category:	Portable Device

1.2 Test Standards

The following report is prepared on behalf of the SZZT ELECTRONICS CO.,LTD in accordance with FCC Part 15, Subpart C, and section 15.203,15.205,15.209 and 15.225 of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 15, Subpart C, and section 15.203,15.205,15.209 and 15.225 rules.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission/immunity, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard for Testing Unlicensed Wireless Devices, and ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted accordingly in reference to the Operating Instructions.

1.4 Test Facility

FCC – Registration No.: 934118

Shenzhen SEM.Test Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files and the Registration is 934118.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Shenzhen SEM.Test Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

CNAS Registration No.: L4062

Shenzhen SEM.Test Technology Co., Ltd. is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L4062. All measurement facilities used to collect the measurement data are located at 1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road, Bao'an District, Shenzhen, P.R.C (518101).

1.5 EUT Setup and Test Mode

The EUT was operated in the continuous transmitting mode that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	Transmitting	13.56MHz

Special Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
Adapter	Shenzhen ruijin	RJ-AS050200C010	/
Notebook	Lenovo	E445	/

1.6 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
Frequency Deviation	2.3%	$\pm 5\%$
Transmitter Spurious Emissions	Radiated	$\pm 5.1\text{dB}$

1.7 Test Equipment List and Details

No.	Description	Manufacturer	Model	Serial No.	Cal Date	Due Date
SEMT-1072	Spectrum Analyzer	Agilent	E4407B	MY41440400	2015-06-17	2016-06-16
SEMT-1031	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2015-06-17	2016-06-16
SEMT-1007	EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2015-06-17	2016-06-16
SEMT-1008	Amplifier	Agilent	8447F	3113A06717	2015-06-17	2016-06-16
SEMT-1043	Amplifier	C&D	PAP-1G18	2002	2015-06-17	2016-06-16
SEMT-1011	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2015-06-17	2016-06-16
SEMT-1042	Horn Antenna	ETS	3117	00086197	2015-06-17	2016-06-16
SEMT-1069	Loop Antenna	Schwarz beck	FMZB 1516	9773	2015-06-17	2016-06-16
SEMT-1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2015-06-17	2016-06-16
SEMT-1003	L.I.S.N	Schwarz beck	NSLK8126	8126-224	2015-06-17	2016-06-16
SEMT-1002	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2015-06-17	2016-06-16

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§15.203	Antenna Requirement	Compliant
§15.205	Restricted Band of Operation	Compliant
§15.209	Radiated Emission Limit	Compliant
§15.225(a)	Field Strength	Compliant
§15.225(b)(c)	Out of Band Emission	Compliant
§15.225(e)	Frequency Stability	Compliant
§ 15.207(a)	Conducted Emission	Compliant
§ 15.215(c)	Emission Bandwidth	Compliant

N/A: not applicable

3. Antenna Requirement

3.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.2 Test Result

This product has an integral antenna, fulfill the requirement of this section.

4. Radiated Emissions

4.1 Standard Applicable

According to §15.225(a), The field strength of any emissions within the band 13.553–13.567 MHz shall not exceed 15,848 microvolts/meter at 30 meters.

According to §15.225(d) The field strength of any emissions which appear outside of this band shall not exceed the general radiated emission limits in §15.209.


Note: Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.


4.2 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.205 15.225(d) and FCC Part 15.209 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.





Frequency :9kHz-30MHz

RBW=10KHz,

VBW =30KHz

Sweep time= Auto

Trace = max hold

Detector function = peak

Frequency :30MHz-1GHz

RBW=120KHz,

VBW=300KHz

Sweep time= Auto

Trace = max hold

Detector function = peak, QP

Frequency :Above 1GHz

RBW=1MHz,

VBW=3MHz(Peak), 10Hz(AV)

Sweep time= Auto

Trace = max hold

Detector function = peak, AV

4.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} - \text{Corr. Factor}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dB μ V means the emission is 6dB μ V below the maximum limit for Class B. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$

4.4 Environmental Conditions

Temperature:	26° C
--------------	-------

Relative Humidity:	52%
ATM Pressure:	1022 mbar

4.5 Summary of Test Results/Plots

According to the data below, the FCC Part 15.205, 15.209 and 15.225 standards, and had the worst margin of:


-12.27 dB at 530.1014 MHz in the Vertical polarization, 9 kHz to 1 GHz, 3Meters

***Note:** this EUT was tested in 3 orthogonal positions and the worst case position data was reported.*

Frequency	Reading	Correction Factor	Result	Limit	Margin	Polar	Detector
MHz	dBuV/m	dB/m	dBuV/m	dBuV/m	dB	H/V	
13.5600	68.96	12.56	81.52	124.0	-42.48	H	Peak
27.1200	30.17	12.59	42.76	69.5	-26.74	H	Peak
13.5600	63.79	12.56	76.35	124.0	-47.65	V	Peak
27.1200	28.53	12.59	41.12	69.5	-28.38	V	Peak


Plot of Radiated Emissions Test Data

EUT: Smart wireless pos
Tested Model: KS8223
Operating Condition: Transmitting
Comment: DC 3.7V by battery
Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	36.2541	15.77	4.38	20.15	40.00	-19.85	336	100	peak
2	57.3923	14.46	4.99	19.45	40.00	-20.55	175	100	peak
3	110.1816	15.77	4.86	20.63	43.50	-22.87	82	100	peak
4	306.7537	15.06	11.94	27.00	46.00	-19.00	348	100	peak
5	403.2500	15.41	12.55	27.96	46.00	-18.04	53	100	peak
6	654.2318	15.99	17.71	33.70	46.00	-12.30	126	100	peak

Test Specification: Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	36.0007	18.51	4.33	22.84	40.00	-17.16	194	100	peak
2	56.3948	15.15	5.00	20.15	40.00	-19.85	180	100	peak
3	115.7256	14.65	4.84	19.49	43.50	-24.01	80	100	peak
4	370.7023	16.77	11.84	28.61	46.00	-17.39	149	100	peak
5	530.1014	19.89	13.84	33.73	46.00	-12.27	294	100	peak
6	766.0572	15.37	17.79	33.16	46.00	-12.84	168	100	peak

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics. The measurements greater than 20dB below the limit from 9kHz to 30MHz.

5. OUT OF BAND EMISSIONS

5.1 Standard Applicable

According to FCC 15.225 (b) Within the bands 13.410–13.553 MHz and 13.567–13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters. (c) Within the bands 13.110–13.410 MHz and 13.710–14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters.

5.2 Test Procedure

As the radiation test, set the RBW=10kHz VBW=30kHz, observed the outside band of 13.11MHz to 14.01MHz, than mark the higher-level emission for comparing with the FCC rules.


5.3 Environmental Conditions

Temperature:	26° C
Relative Humidity:	57%
ATM Pressure:	1022 mbar

5.4 Summary of Test Results/Plots

Out of band emission

Vertical (Worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	13.3445	35.74	12.57	48.31	80.50	-32.19	200	100	peak
2	13.7675	33.82	12.56	46.38	80.50	-34.12	200	100	peak

6. Frequency Stability

6.1 Standard Applicable

According to 15.225(e) The frequency tolerance of the carrier signal shall be maintained within $\pm 0.01\%$ of the operating frequency over a temperature variation of -20 degrees to $+50$ degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

6.2 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure.

6.3 Environmental Conditions

Relative Humidity:	55%
ATM Pressure:	1015 mbar

6.4 Summary of Test Results/Plots

Reference Frequency: 13.56MHz, Limit: 100ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Error	
		Error (Hz)	Error (ppm)
50	3.7	815	60.1032
40	3.7	530	39.0855
30	3.7	485	35.7670
20	3.7	750	55.3097
10	3.7	275	20.2802
0	3.7	390	28.7611
-10	3.7	475	35.0295
-20	3.7	268	19.7640

Reference Frequency: 13.56MHz, Limit: 100ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Error	
		Error (Hz)	Error (ppm)
20	3.3	770	56.7847
	3.7	750	55.3097
	4.2	755	55.6785


7. Conducted Emissions

7.1 Test Procedure

The setup of EUT is according with per ANSI C63.4-2014 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.

7.2 Basic Test Setup Block Diagram



7.3 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52%
ATM Pressure:	1012 mbar

7.4 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency 150 kHz
Stop Frequency..... 30 MHz
Sweep Speed Auto
IF Bandwidth..... 10 kHz
Quasi-Peak Adapter Bandwidth 9 kHz
Quasi-Peak Adapter Mode Normal

7.5 Summary of Test Results/Plots

According to the data in section 7.6, the EUT complied with the FCC Part 15.207 Conducted margin for this device, with the *worst* margin reading of:


-4.25 dB at **0.7500 MHz** in the **Line, Average** detector, 0.15-30MHz

7.6 Conducted Emissions Test Data

Plot of Conducted Emissions Test Data


EUT: Smart wireless pos
Tested Model: KS8223
Operating Condition: Transmitting
Comment: AC 120V/60Hz; Adapter DC 5V

Test Specification: Neutral



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1*	0.7460	36.07	9.78	45.85	56.00	-10.15	QP
2	0.7500	23.57	9.78	33.35	46.00	-12.65	AVG
3	11.1980	36.88	9.54	46.42	60.00	-13.58	QP
4	11.3180	14.53	9.54	24.07	50.00	-25.93	AVG
5	17.9700	36.07	9.65	45.72	60.00	-14.28	QP
6	18.5380	17.30	9.66	26.96	50.00	-23.04	AVG

Test Specification: Line



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.7500	37.10	9.78	46.88	56.00	-9.12	QP
2*	0.7500	31.97	9.78	41.75	46.00	-4.25	AVG
3	1.3260	30.55	9.75	40.30	56.00	-15.70	QP
4	1.3260	22.94	9.75	32.69	46.00	-13.31	AVG
5	11.7260	37.90	9.55	47.45	60.00	-12.55	QP
6	11.7260	22.21	9.55	31.76	50.00	-18.24	AVG

8. EMISSION BANDWIDTH

8.1 Applicable Standard

According to 15.215 (c), intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

8.2 Test Procedure

According to the ANSI 63.10-2013, the emission bandwidth test method as follows.

Set span = 10kHz, centered on a transmitting channel

RBW $\geq$ 1% 20dB Bandwidth, VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

All the trace to stabilize, use the marker-to-peak function to set the marker to the peak of the emission, use the marker-delta function to measure and record the 20dB down of the emission.


8.3 Environmental Conditions

Temperature:	26 °C
Relative Humidity:	45%
ATM Pressure:	1019 mbar

8.4 Summary of Test Results/Plots

Tx Frequency	20dB Emission bandwidth
13.56MHz	768.509Hz

Please refer to the test plots as below:



***** END OF REPORT *****