

RF EXPOSURE REPORT

for

Model Number: Reolink Argus

FCC ID: 2AL7VAREOLINK

Prepared for : Shenzhen Reo-link Digital Technology Co., Ltd
B509, University Town Business Park, LiShan Road, NanShan,
Address : Shenzhen, Guangdong China 518055

Prepared by : Shenzhen BCTC Testing Co., Ltd.
BCTC Building & 1-2F, East of B Building, Pengzhou Industrial,
Fuyuan 1st Road, Qiaotou Community, Fuyong Street, Bao'an
Address : District, Shenzhen, China

1. RF EXPOSURE EVALUATION

Test Result of RF Exposure Evaluation

According to the KDB-447498 D01 V06, FCC 47CFR § 2.1093 the following RF exposure evaluation shall to demonstrate RF exposure compliance.

$$\left[\frac{\text{(max. power of channel, including tune-up tolerance, mW)}}{\text{(min. test separation distance, mm)}} \right]$$

* $[\sqrt{f(\text{GHz})}]$

	tune up power tolerance (dBm)	Maximum Tune up output power (dBm)	max. output power(mW)	Separation distance mm	RF exposure
802.11b	8 ± 1	9	7.94	5	2.47
802.11g	8 ± 1	9	7.94	5	2.47
802.11n 20MHz	8 ± 1	9	7.94	5	2.47
802.11n 40MHz	7 ± 1	8	6.31	5	1.96

The Max RF exposure is 2.47.

Threshold at which no SAR required is ≤ 3.0 for 1-g SAR, Separation distance is 5mm.

Conclusion:

So no SAR is required.