



FCC §15.247 (i), §2.1091 – RF Exposure

FCC ID: 2AL7VRLC-410W

Applied procedures / limit

According to FCC §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

Note: f is frequency in MHz

* = Power density limit is applicable at frequencies greater than 100 MHz

Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz

* = Plane-wave equivalent power density



MPE PREDICTION

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna, R=0.2m

TEST RESULTS

	Tune up Produce power	Maximum peak output power (dBm)	Output power to antenna (mW)	Antenna Gain (numeric)	Power Density (S) (mW/ cm ²)	Power Density (S) (mW/ cm ²)	Limit (mW/ cm ²)	Result
2462 Ant A	13±1	14	25.12	3.99 (6.01dBi)	0.01994	0.03578	1	Pass
2462 Ant B	12±1	13	19.95	3.99 (6.01dBi)	0.01584			
5180 Ant A	14±1	15	31.62	3.99 (6.01dBi)	0.02510	0.05020	1	Pass
5180 Ant B	14±1	15	31.62	3.99 (6.01dBi)	0.02510			
5825 Ant A	10±1	11	12.59	3.99 (6.01dBi)	0.00999	0.01999	1	Pass
5825 Ant B	10±1	11	12.59	3.99 (6.01dBi)	0.00999			

Antenna A Gain =3dBi, Antenna B Gain =3dBi

MIMO mode: Directional gain=[10log(GA+ G B)] dbi =6.01dBi