



TEST REPORT

FOR FCC PART 15 SUBPART C 15.249

Report Reference No. : CTL2602243017-WF

Compiled by: Andy Su
(printed name+signature)

Reviewed by: Happy Guo
(printed name+signature)

Approved by: Ivan Xie
(printed name+signature)



Product Name..... : Magic Flip AI Stunt Machine Dog

Model/Type reference..... : CV-D903

List Model(s)..... : CV-D903-1, CV-D903-2

Trade Mark..... : N/A

FCC ID..... : 2AL7W-CV-D903

Applicant's name : WEI SHENG DA TOYS FACTORY

Address of applicant..... : No.8th, Qianxi Industrial Area, Lianxia Town Chenghai, Shantou City, Guangdong Province, China

Test specification..... :

Standard : **FCC Part 15.249:**Operation within the bands 920-928 MHz, 2400-2483.5 MHz, 5725-5850 MHz and 24.0 - 24.25 GHz.

TRF Originator : Shenzhen CTL Testing Technology Co., Ltd.

Master TRF : Dated 2011-01

Date of receipt of test item : Feb. 25, 2026

Date of Test Date : Feb. 25, 2026-Apr. 24, 2026

Data of Issue..... : Apr. 29, 2026

Result..... : **Pass**

Shenzhen CTL Testing Technology Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen CTL Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen CTL Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

TEST REPORT

Test Report No. :	CTL2602243017-WF	Apr. 29, 2026
		Date of issue

Equipment under Test : Magic Flip AI Stunt Machine Dog

Sample No. CTL260224301007, CTL260224301016

Model /Type : CV-D903

Listed Models : CV-D903-1, CV-D903-2

Applicant : **WEI SHENG DA TOYS FACTORY**

Address : No.8th, Qianxi Industrial Area, Lianxia Town Chenghai,
Shantou City, Guangdong Province, China

Manufacturer : **WEI SHENG DA TOYS FACTORY**

Address : No.8th, Qianxi Industrial Area, Lianxia Town Chenghai,
Shantou City, Guangdong Province, China

Test result	Pass *
--------------------	---------------

* In the configuration tested, the EUT complied with the standards specified page 5.

This device (product name: Magic Flip AI Stunt Machine Dog) model name: CV-D903,CV-D903-1, CV-D903-2 electrical, PCB, BOM are the same, only the exterior color, model name and the controlled vehicle are different, which does not affect the test results.

The test results presented in this report relate only to the object tested.

This report shall not be reproduced, except in full, without the written approval of the issuing testing laboratory.

**** Modified History ****

[illegible]

Table of Contents

Page

1. SUMMARY	5
1.1. TEST STANDARDS	5
1.2. TEST DESCRIPTION	5
1.3. TEST FACILITY.....	6
1.4. STATEMENT OF THE MEASUREMENT UNCERTAINTY	6
2. GENERAL INFORMATION.....	8
2.1. ENVIRONMENTAL CONDITIONS	8
2.2. GENERAL DESCRIPTION OF EUT	8
2.3. DESCRIPTION OF TEST MODES AND TEST FREQUENCY	8
2.4. EQUIPMENTS USED DURING THE TEST.....	10
2.5. RELATED SUBMITTAL(S) / GRANT(S).....	11
2.6. MODIFICATIONS	11
3. TEST CONDITIONS AND RESULTS.....	12
3.1. CONDUCTED EMISSIONS TEST	12
3.2. RADIATED EMISSIONS AND BAND EDGE.....	13
3.3. OCCUPIED BANDWIDTH MEASUREMENT	34
3.4. ANTENNA REQUIREMENT	36
4. TEST SETUP PHOTOS OF THE EUT	37
5. EXTERNAL AND INTERNAL PHOTOS OF THE EUT	39

1. SUMMARY

1.1. TEST STANDARDS

The tests were performed according to following standards:

[FCC Rules Part 15.249](#): Operation within the bands 902 - 928 MHz, 2400 - 2483.5 MHz, 5725 - 5875 MHz, and 24.0 - 24.25 GHz.

[ANSI C63.10: 2020](#) : American National Standard for Testing Unlicensed Wireless Devices

1.2. Test Description

FCC PART 15.249		
FCC Part 15.249(a)	Field Strength of Fundamental	PASS
FCC Part 15.209	Spurious Emission	PASS
FCC Part 15.209	Band edge	PASS
FCC Part 15.215(c)	20dB bandwidth	PASS
FCC Part 15.207	Conducted Emission	N/A
FCC Part 15.203	Antenna Requirement	PASS

1.3. Test Facility

1.3.1 Address of the test laboratory

Company Name:	Shenzhen CTL Testing Technology Co., Ltd.
Address 1:	Zone A.1/F..Warehouse 2.Baisha Technology Park, No.3011,Shahexi Road, Nanshan District,Shenzhen.518055,P.R.C.
Address 2:	Fl.A1, Bldg.A3, No.2533 GuanGuang Road, Fenghuang Community Fenghuang Street, Guangming District, Shenzhen, Guangdong, PR.C

1.3.2 Test location

All tests were performed at:

Company Name:	Shenzhen CTL Testing Technology Co., Ltd.
☐ Main location	Zone A.1/F..Warehouse 2.Baisha Technology Park, No.3011,Shahexi Road, Nanshan District,Shenzhen.518055,P.R.C.
☒ Satellite location	Fl.A1, Bldg.A3, No.2533 GuanGuang Road, Fenghuang Community Fenghuang Street, Guangming District, Shenzhen, Guangdong, PR.C

1.3.3 Laboratory accreditation

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L7497

Shenzhen CTL Testing Technology Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2017 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA-Lab Cert. No. 4343.01

Shenzhen CTL Testing Technology Co., Ltd, EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

IC CAB identifier: CN0041

Main Company Number :9618B

Satellite Company Number:35187

The 3m alternate test site of Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements with Main Company Number:9618B and Satellite Company Number:35187.

FCC-Registration No.: 399832

Designation No.: CN1216

Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Designation No.: CN1216. Test Firm Registration 399832.

1.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 "Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements" and is documented in the Shenzhen CTL Testing Technology Co., Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole

responsibility of continued compliance of the device.

Hereafter the best measurement capability for CTL laboratory is reported:

Test Item	Measurement Uncertainty	Notes
Transmitter power Radiated	± 2.20 dB	(1)
Occupied Bandwidth	± 0.02 ppm	(1)
Radiated Emission 30~1000MHz	± 4.08 dB	(1)
Radiated Emission Above 1GHz	± 4.32 dB	(1)
Conducted Disturbance 0.15~30MHz	± 2.96 dB	(1)
20dB Emission Bandwidth	$\pm 1.9\%$	(1)
Carrier Frequency Separation	$\pm 1.9\%$	(1)
Maximum Power Spectral Density Level	± 0.98 dB	(1)
Number of Hopping Channel	$\pm 1.9\%$	(1)
Time of Occupancy	$\pm 0.11\%$	(1)
Max Peak Conducted Output Power	± 0.98 dB	(1)
Band-edge Spurious Emission	± 1.21 dB	(1)
Conducted RF Spurious Emission	9kHz-7GHz: ± 1.09 dB 7GHz-26.5GHz: ± 3.27 dB	(1)

- (1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=1.96$.
- (2) Decision rule for Statement of Conformity: The measurement uncertainty is not taken into account but only measured result.

2. GENERAL INFORMATION

2.1. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Normal Temperature:	18-28°C
Relative Humidity:	30-60%
Air Pressure:	965-1030hPa

2.2. General Description of EUT

Product Name:	Magic Flip AI Stunt Machine Dog
Model/Type reference:	CV-D903
Power supply:	DC 3V from battery
Test Voltage	DC 3V
2.4G	
Modulation:	GFSK
Operation frequency:	2405MHz~2475MHz
Channel number:	33
Antenna type:	Built-in antenna
Antenna gain:	0dBi provided by ☒ Applicant ☐ Manufacturer

Note1: For more details, please refer to the user's manual of the EUT.

Note2: Antenna gain provided by the applicant.

Note3: The product cannot be configured to operate outside the current frequency band plan through software configuration, Third parties are not allowed to change any software parameter configuration of the product.

2.3. Description of Test Modes and Test Frequency

The EUT has been tested under typical operating condition. The Applicant provides communication tools software to control the EUT for staying in continuous transmitting and receiving mode for testing. There are 33 channels provided to the EUT and Channel 01/18/32 were selected for testing.

Operation Frequency List :

Channel	Frequency (MHz)
01	2405
02	2406
03	2407
04	2408
05	2409
06	2410
07	2411
08	2414
09	2418
10	2422
11	2425
12	2427
13	2428
14	2430

15	2435
16	2437
17	2440
18	2442
19	2445
20	2446
21	2452
22	2453
23	2454
24	2456
25	2459
26	2462
27	2469
28	2470
29	2471
30	2472
31	2473
32	2474
33	2475

Note: The line display in grey is the channel selected to perform test.

RF Cable List and Details

RF Cable	RF Cable loss	RF Cable loss provided by
RF1.13	0.5dB	☒ Applicant ☐ Manufacturer ☐ Testing Laboratory (CTL)
RG 316	0.8dB	☒ Applicant ☐ Manufacturer ☐ Testing Laboratory (CTL)

2.4. Equipments Used during the Test

Conducted Emission					
Test Equipment	Manufacturer	Model No.	Serial No.	Last calibration	Calibration Due
EMI Test Receiver	ROHDE & SCHWARZ	ESCI	1166.5950.03	2026/01/05	2027/01/04
LISN	ROHDE & SCHWARZ	ESH2-Z5	860014/010	2026/01/05	2027/01/04
Limitator	ROHDE & SCHWARZ	ESH3-Z2	100408	2026/01/05	2027/01/04
Software:					
Name of Software:			Version:		
ES-K1			V1.71		

Radiated Emission					
Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal.Due
Active Loop Antenna	Da Ze	ZN30900A	/	2025/07/02	2026/07/01
ULTRA-BROADBAND ANTENNA	Sunol Sciences Corp.	JB1 Antenna	A061713	2025/07/02	2026/07/01
Horn Antenna	Sunol Sciences Corp.	DRH-118	A062013	2026/01/05	2027/01/04
Horn Antenna	Ocean Microwave	OBH100400	26999002	2025/07/03	2026/07/02
Amplifier	MRT-AP01M06	MRT	S-001	2025/07/02	2026/07/01
Amplifier	Agilent	8449B	3008A02306	2026/01/05	2027/01/04
Amplifier	Brief&Smart	LNA-4018	2104197	2025/07/03	2026/07/02
EMI Test Receiver	ROHDE & SCHWARZ	ESPI	100434	2025/07/02	2026/07/01
Spectrum Analyzer	RS	FSP	1164.4391.38	2025/07/03	2026/07/02
Software:					
Name of Software:			Version:		
EZ_EMC(Below 1GHz)			V1.1.4.2		
EZ_EMC(Above 1GHz)			V1.1.4.2		

RF Conducted					
Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal.Due
Spectrum Analyzer	Keysight	N9020A	MY53420874	2025/07/03	2026/07/02
Temperature/Humidity Meter	Ji Yu	MC501	/	2025/07/03	2026/07/02
Software:					
Name of Software:			Version:		
TST-PASS			V2.0.2		

Maximum Peak Output Power & 20dB Bandwidth & Frequency Separation & Number of hopping frequency & Dwell Time & Out-of-band Emissions					
Test Equipment	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Due Date
Spectrum Analyzer	Keysight	N9020A	MY53420874	2025/07/03	2026/07/02
Power meter	TSTPASS	TSPS2023R	TSCB220016	2025/07/03	2026/07/02
Temperature/Humidity Meter	Ji Yu	MC501	/	2025/07/03	2026/07/02
Test Software					
Name of Software			Version		
TST-PASS			V2.0.2		

2.5. Related Submittal(s) / Grant(s)

This submittal(s) (test report) is intended to comply with Section 15.249 of the FCC Part 15, Subpart C Rules.

2.6. Modifications

No modifications were implemented to meet testing criteria.

3. TEST CONDITIONS AND RESULTS

3.1. Conducted Emissions Test


LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.207

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST CONFIGURATION



TEST PROCEDURE

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system; a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10: 2020.
2. Support equipment, if needed, was placed as per ANSI C63.10: 2020.
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10: 2020.
4. If a EUT received DC power from the USB Port of Notebook PC, the PC's adapter received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
5. All support equipments received AC power from a second LISN, if any.
6. The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7. Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
8. During the above scans, the emissions were maximized by cable manipulation.

TEST RESULTS

Battery powered products do not require this test.

3.2. Radiated Emissions and Band Edge

Limit

According 15.249, the field strength of emissions from intentional radiators operated within 2400MHz-2483.5 MHz shall not exceed 94dB μ V/m (50mV/m):

FCC PART 15.249(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a)

Radiated emission limits

Frequency (MHz)	Distance (Meters)	Radiated (dB μ V/m)	Radiated (μ V/m)
0.009-0.49	3	$20\log(2400/F(\text{KHz}))+40\log(300/3)$	$2400/F(\text{KHz})$
0.49-1.705	3	$20\log(24000/F(\text{KHz}))+40\log(30/3)$	$24000/F(\text{KHz})$
1.705-30	3	$20\log(30)+40\log(30/3)$	30
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

According to §15.249 (a): Except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental frequency	Field strength of fundamental (millivolts/meter)	Field strength of harmonics (microvolts/meter)
902-928 MHz	50	500
2400-2483.5 MHz	50	500
5725-5875 MHz	50	500
24.0-24.25 GHz	250	2500


* Field strength limits are specified at a distance of 3 meters.

* As shown in §15.35(b), for frequencies above 1000 MHz, the field strength limits in paragraphs (a) and (b) of this section are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For point-to-point operation under paragraph (b) of this section, the peak field strength shall not exceed 2500 millivolts/meter at 3 meters along the antenna azimuth.


* Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

TEST CONFIGURATION


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz



Test Procedure

1. Below 1GHz measurement the EUT is placed on a turntable which is 0.8m above ground plane, and above 1GHz measurement EUT was placed on a low permittivity and low loss tangent turn table which is 1.5m above ground plane.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0° to 360° to acquire the highest emissions from EUT
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed.
5. Radiated emission test frequency band from 9KHz to 25GHz.
6. The distance between test antenna and EUT as following table states:

Test Frequency range	Test Antenna Type	Test Distance
9KHz-30MHz	Active Loop Antenna	3
30MHz-1GHz	Bilog Antenna	3
1GHz-18GHz	Horn Antenna	3
18GHz-25GHz	Horn Antenna	1

7. Setting test receiver/spectrum as following table states:

Test Frequency range	Test Receiver/Spectrum Setting	Detector
9KHz-150KHz	RBW=200Hz/VBW=3KHz, Sweep time=Auto	QP
150KHz-30MHz	RBW=9KHz/VBW=100KHz, Sweep time=Auto	QP
30MHz-1GHz	RBW=120KHz/VBW=1000KHz, Sweep time=Auto	QP
1GHz-40GHz	Peak Value: RBW=1MHz/VBW=3MHz, Sweep time=Auto Average Value: RBW=1MHz/VBW=10Hz, Sweep time=Auto	Peak

TEST RESULTS

Remark:

1. We measured Radiated Emission at GFSK mode from 9 KHz to 25GHz and recorded worst case.
2. For below 1GHz testing recorded worst at GFSK low channel.
3. Radiated emission test from 9 KHz to 10th harmonic of fundamental was verified, and no emission found except system noise floor in 9 KHz to 30MHz and not recorded in this report.


For 30MHz-1GHz

Horizontal



Shenzhen CTL Testing Technology Co., Ltd
Tel: +86-755-89486194
Unit 01A&B&C&D-1, Building A3, Guangming Sci-Tech Park, Guan Guang Road, Fenghu

Radiated Emission Measurement



Site LAB Chamber 1 Polarization: **Horizontal** Temperature: 25(C)
Limit: FCC Part15 Class C_30-1000MHz Power: Humidity: 50 %
EUT: Distance: 3m
M/N:
Mode: 2405MHZ
Note: CTL2602243017-WF

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	30.2111	36.92	-10.78	26.14	40.00	13.86	peak	100	266	P	
2	506.4790	40.59	-13.91	26.68	46.00	19.32	peak	100	238	P	
3	677.5798	40.19	-11.45	28.74	46.00	17.26	peak	100	44	P	
4	807.4290	40.59	-9.74	30.85	46.00	15.15	peak	100	146	P	
5	884.5028	40.08	-9.02	31.06	46.00	14.94	peak	100	360	P	
6	919.2865	39.14	-8.52	30.62	46.00	15.38	peak	100	266	P	

Vertical



Shenzhen CTL Testing Technology Co., Ltd

Tel: +86-755-89486194

Unit 01A&B&C&D-1, Building A3, Guangming Sci-Tech Park, Guan Guang Road, Fenghu

Radiated Emission Measurement


File :RF2

Data :#2793

Date: 2026/04/22

Time: 17:44:07

70.0 dBuV/m



Site LAB Chamber 1

Limit: FCC Part15 Class C_30-1000MHz

EUT:

M/N:

Mode: 2405MHZ

Note: CTL2602243017-WF

Polarization: **Vertical**

Power:

Distance: 3m

Temperature: 25(C)

Humidity: 50 %


No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	30.4238	37.50	-10.98	26.52	40.00	13.48	peak	100	11	P	
2	704.2261	40.68	-11.35	29.33	46.00	16.67	peak	100	57	P	
3	739.6604	39.94	-10.75	29.19	46.00	16.81	peak	100	205	P	
4	833.3171	40.46	-9.57	30.89	46.00	15.11	peak	100	251	P	
5	912.8620	40.16	-8.67	31.49	46.00	14.51	peak	100	316	P	
6	952.0937	37.73	-8.42	29.31	46.00	16.69	peak	100	345	P	

For 1GHz to 10GHz
2405MHz

Horizontal



Shenzhen CTL Testing Technology Co., Ltd
Tel: +86-755-89486194
Unit 01A&B&C&D-1, Building A3, Guangming Sci-Tech Park, Guan Guang Road, Fenghu



Site LAB Chamber 1	Polarization: Horizontal	Temperature: 25(C)
Limit: FCC PART 15C ABOVE 1GHz PK	Power:	Humidity: 50 %
EUT:	Distance: 3m	
M/N:		
Mode: 2405MHz		
Note: CTL2602243017-WF		


No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	2573.203	52.14	-14.84	37.30	74.00	36.70	peak	150	0	P	
2	4027.554	48.56	-8.93	39.63	74.00	34.37	peak	150	0	P	
3	7221.150	48.04	-4.09	43.95	74.00	30.05	peak	150	0	P	
4	11204.896	46.22	0.19	46.41	74.00	27.59	peak	150	0	P	
5	15577.899	48.79	3.18	51.97	74.00	22.03	peak	150	0	P	
6	2806.288	52.38	-14.31	38.07	74.00	35.93	peak	150	0	P	

Vertical



Shenzhen CTL Testing Technology Co., Ltd
Tel: +86-755-89486194
Unit 01A&B&C&D-1, Building A3, Guangming Sci-Tech Park, Guan Guang Road, Fenghu

Radiated Emission Measurement



Site LAB Chamber 1 Polarization: **Vertical** Temperature: 25(C)
Limit: FCC PART 15C ABOVE 1GHz PK Power: Humidity: 50 %
EUT: Distance: 3m
M/N:
Mode: 2405MHz
Note: CTL2602243017-WF


No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	2573.203	52.14	-14.84	37.30	74.00	36.70	peak	150	360	P	
2	4050.903	49.80	-8.94	40.86	74.00	33.14	peak	150	360	P	
3	6267.553	49.66	-6.78	42.88	74.00	31.12	peak	150	360	P	
4	11204.896	48.22	0.19	48.41	74.00	25.59	peak	150	360	P	
5	15577.899	49.29	3.18	52.47	74.00	21.53	peak	150	360	P	
6	1819.036	53.86	-22.50	31.36	74.00	42.64	peak	150	360	P	

2440MHz

Horizontal



Shenzhen CTL Testing Technology Co., Ltd
Tel: +86-755-89486194
Unit 01A&B&C&D-1, Building A3, Guangming Sci-Tech Park, Guan Guang Road, Fenghu



Site LAB Chamber 1 Polarization: **Horizontal** Temperature: 25(C)
Limit: FCC PART 15C ABOVE 1GHz PK Power: Humidity: 50 %
EUT: Distance: 3m
M/N:
Mode: 2440MHz
Note: CTL2602243017-WF

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	2573.203	52.14	-14.84	37.30	74.00	36.70	peak	150	360	P	
2	4050.903	49.80	-8.94	40.86	74.00	33.14	peak	150	360	P	
3	4888.151	55.93	-9.29	46.64	74.00	27.36	peak	150	360	P	
4	8489.882	48.75	-4.19	44.56	74.00	29.44	peak	150	360	P	
5	11204.896	47.72	0.19	47.91	74.00	26.09	peak	150	360	P	
6	15577.899	48.79	3.18	51.97	74.00	22.03	peak	150	360	P	

Vertical



Shenzhen CTL Testing Technology Co., Ltd

Tel: +86-755-89486194

Unit 01A&B&C&D-1, Building A3, Guangming Sci-Tech Park, Guan Guang Road, Fenghu


Radiated Emission Measurement

File :RF2

Data :#3032

Date: 2026/04/23

Time: 20:39:04



Site LAB Chamber 1

Limit: FCC PART 15C ABOVE 1GHz PK

EUT:

M/N:

Mode: 2440MHz

Note: CTL2602243017-WF

Polarization: **Vertical**

Power:

Distance: 3m

Temperature: 25(C)

Humidity: 50 %


No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	2573.203	52.14	-14.84	37.30	74.00	36.70	peak	150	0	P	
2	4050.903	49.80	-8.94	40.86	74.00	33.14	peak	150	0	P	
3	4874.043	51.94	-9.46	42.48	74.00	31.52	peak	150	0	P	
4	7221.150	48.54	-4.09	44.45	74.00	29.55	peak	150	0	P	
5	9448.149	47.67	-2.49	45.18	74.00	28.82	peak	150	0	P	
6	15577.899	48.29	3.18	51.47	74.00	22.53	peak	150	0	P	

2475MHz

Horizontal



Shenzhen CTL Testing Technology Co., Ltd
Tel: +86-755-89486194
Unit 01A&B&C&D-1, Building A3, Guangming Sci-Tech Park, Guan Guang Road, Fenghu



Site LAB Chamber 1	Polarization: Horizontal	Temperature: 25(C)
Limit: FCC PART 15C ABOVE 1GHz PK	Power:	Humidity: 50 %
EUT:	Distance: 3m	
M/N:		
Mode: 2475MHz		
Note: CTL2602243017-WF		

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	4888.151	55.43	-9.29	46.14	74.00	27.86	peak	150	0	P	
2	2573.203	52.32	-14.84	37.48	74.00	36.52	peak	150	0	P	
3	4050.903	49.80	-8.94	40.86	74.00	33.14	peak	150	0	P	
4	7263.015	50.35	-4.47	45.88	74.00	28.12	peak	150	0	P	
5	11204.896	49.22	0.19	49.41	74.00	24.59	peak	150	0	P	
6	15577.899	49.79	3.18	52.97	74.00	21.03	peak	150	0	P	

Vertical



Shenzhen CTL Testing Technology Co., Ltd

Tel: +86-755-89486194

Unit 01A&B&C&D-1, Building A3, Guangming Sci-Tech Park, Guan Guang Road, Fenghu


Radiated Emission Measurement

File :RF2

Data :#3035

Date: 2026/04/23

Time: 20:42:49



Site LAB Chamber 1

Limit: FCC PART 15C ABOVE 1GHz PK

EUT:

M/N:

Mode: 2475MHz

Note: CTL2602243017-WF

Polarization: **Vertical**

Power:

Distance: 3m

Temperature: 25(C)

Humidity: 50 %

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	2580.652	52.07	-14.90	37.17	74.00	36.83	peak	150	360	P	
2	4039.212	49.01	-8.91	40.10	74.00	33.90	peak	150	360	P	
3	7179.527	48.55	-5.01	43.54	74.00	30.46	peak	150	360	P	
4	11044.129	47.17	0.99	48.16	74.00	25.84	peak	150	360	P	
5	14366.840	48.40	2.58	50.98	74.00	23.02	peak	150	360	P	
6	9866.789	49.00	-2.19	46.81	74.00	27.19	peak	150	360	P	

REMARKS:


1. Emission level (dBuV/m) =Raw Value (dBuV)+Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
3. Margin value = Limit value- Emission level.
4. The other emission levels were very low against the limit.
5. RBW1MHz VBW3MHz Peak detector is for PK value; RBW 1MHz VBW10Hz Peak detector is for AV value.
6. For fundamental frequency, RBW 3MHz VBW 3MHz Peak detector is for PK Value ; RMS detector is for AV value.
7. While performing the testing, the notch filter is used for avoiding test instrument overload.

Frequency bands
2405MHz

Horizontal



Shenzhen CTL Testing Technology Co., Ltd
Tel: +86-755-89486194
Unit 01A&B&C&D-1, Building A3, Guangming Sci-Tech Park, Guan Guang Road, Fenghu



Site LAB Chamber 1	Polarization: Horizontal	Temperature: 25(C)
Limit: FCC PART 15C	Power:	Humidity: 50 %
EUT:	Distance: 3m	
M/N:		
Mode: 2405MHz		
Note: CTL2602243017-WF		


No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	2310.000	25.45	30.82	56.27	74.00	17.73	peak	150	360	P	
2	2310.000	14.43	30.82	45.25	54.00	8.75	AVG	150	360	P	
3	2390.000	25.71	32.25	57.96	74.00	16.04	peak	150	360	P	
4	2390.000	14.85	32.25	47.10	54.00	6.90	AVG	150	360	P	

Vertical



Shenzhen CTL Testing Technology Co., Ltd
Tel: +86-755-89486194
Unit 01A&B&C&D-1, Building A3, Guangming Sci-Tech Park, Guan Guang Road, Fenghu

Radiated Emission Measurement



Site LAB Chamber 1 Polarization: **Vertical** Temperature: 25(C)
Limit: FCC PART 15C Power: Humidity: 50 %
EUT: Distance: 3m
M/N:
Mode: 2405MHz
Note: CTL2602243017-WF


No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	2310.000	25.09	30.82	55.91	74.00	18.09	peak	150	0	P	
2	2310.000	14.42	30.82	45.24	54.00	8.76	AVG	150	0	P	
3	2390.000	24.98	32.25	57.23	74.00	16.77	peak	150	0	P	
4	2390.000	14.87	32.25	47.12	54.00	6.88	AVG	150	0	P	

Frequency bands
2475MHz

Horizontal



Shenzhen CTL Testing Technology Co., Ltd
Tel: +86-755-89486194
Unit 01A&B&C&D-1, Building A3, Guangming Sci-Tech Park, Guan Guang Road, Fenghu



Site LAB Chamber 1	Polarization: Horizontal	Temperature: 25(C)
Limit: FCC PART 15C	Power:	Humidity: 50 %
EUT:	Distance: 3m	
M/N:		
Mode: 2475MHz		
Note: CTL2602243017-WF		


No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	2483.500	27.10	32.28	59.38	74.00	14.62	peak	150	0	P	
2	2483.500	14.14	32.28	46.42	54.00	7.58	AVG	150	0	P	
3	2500.000	25.08	32.32	57.40	74.00	16.60	peak	150	0	P	
4	2500.000	14.21	32.32	46.53	54.00	7.47	AVG	150	0	P	

Vertical



Shenzhen CTL Testing Technology Co., Ltd
Tel: +86-755-89486194
Unit 01A&B&C&D-1, Building A3, Guangming Sci-Tech Park, Guan Guang Road, Fenghu

Radiated Emission Measurement



Site LAB Chamber 1	Polarization: Vertical	Temperature: 25(C)
Limit: FCC PART 15C	Power:	Humidity: 50 %
EUT:	Distance: 3m	
M/N:		
Mode: 2475MHz		
Note: CTL2602243017-WF		

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	2483.500	24.13	32.28	56.41	74.00	17.59	peak	150	0	P	
2	2483.500	13.82	32.28	46.10	54.00	7.90	AVG	150	0	P	
3	2500.000	24.46	32.32	56.78	74.00	17.22	peak	150	0	P	
4	2500.000	13.85	32.32	46.17	54.00	7.83	AVG	150	0	P	

Field Strength of Fundamental


Remark: This test was performed with EUT in X, Y, Z position and the worst case was found when EUT in X position.

2405MHz

Horizontal



Shenzhen CTL Testing Technology Co., Ltd
Tel: +86-755-89486194
Unit 01A&B&C&D-1, Building A3, Guangming Sci-Tech Park, Guan Guang Road, Fenghu



Site LAB Chamber 1	Polarization: Horizontal	Temperature: 25(C)
Limit: 114	Power:	Humidity: 50 %
EUT:	Distance: 3m	
M/N:		
Mode: 2405MHz		
Note: CTL2602243017-WF		


No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	2405.000	56.67	32.50	89.17	114.00	24.83	peak	150	360	P	
2	2405.000	41.73	32.50	74.23	94.00	19.77	AVG	150	360	P	

Vertical



Shenzhen CTL Testing Technology Co., Ltd
Tel: +86-755-89486194
Unit 01A&B&C&D-1, Building A3, Guangming Sci-Tech Park, Guan Guang Road, Fenghu

Radiated Emission Measurement



Site LAB Chamber 1	Polarization: Vertical	Temperature: 25(C)
Limit: 114	Power:	Humidity: 50 %
EUT:	Distance: 3m	
M/N:		
Mode: 2405MHz		
Note: CTL2602243017-WF		


No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	2405.000	47.64	32.50	80.14	114.00	33.86	peak	150	0	P	
2	2405.000	34.33	32.50	66.83	94.00	27.17	AVG	150	0	P	

Field Strength of Fundamental
2440MHz

Horizontal



Shenzhen CTL Testing Technology Co., Ltd
Tel: +86-755-89486194
Unit 01A&B&C&D-1, Building A3, Guangming Sci-Tech Park, Guan Guang Road, Fenghu



Site LAB Chamber 1	Polarization: Horizontal	Temperature: 25(C)
Limit: 114	Power:	Humidity: 50 %
EUT:	Distance: 3m	
M/N:		
Mode: 2440MHz		
Note: CTL2602243017-WF		

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	2440.000	57.18	32.25	89.43	114.00	24.57	peak	150	360	P	
2	2440.000	41.97	32.25	74.22	94.00	19.78	AVG	150	360	P	

Vertical



Shenzhen CTL Testing Technology Co., Ltd

Tel: +86-755-89486194

Unit 01A&B&C&D-1, Building A3, Guangming Sci-Tech Park, Guan Guang Road, Fenghu

Radiated Emission Measurement


File :RF2

Data :#3043

Date: 2026/04/23

Time: 21:05:42

107.0 dBuV/m



Site LAB Chamber 1

Limit: 114

EUT:

M/N:

Mode: 2440MHz

Note: CTL2602243017-WF

Polarization: **Vertical**

Power:

Distance: 3m

Temperature: 25(C)

Humidity: 50 %


No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	2440.000	48.53	32.25	80.78	114.00	33.22	peak	150	0	P	
2	2440.000	34.59	32.25	66.84	94.00	27.16	AVG	150	0	P	

Field Strength of Fundamental
2475MHz

Horizontal



Shenzhen CTL Testing Technology Co., Ltd
Tel: +86-755-89486194
Unit 01A&B&C&D-1, Building A3, Guangming Sci-Tech Park, Guan Guang Road, Fenghu



Site LAB Chamber 1	Polarization: Horizontal	Temperature: 25(C)
Limit: 114	Power:	Humidity: 50 %
EUT:	Distance: 3m	
M/N:		
Mode: 2475MHz		
Note: CTL2602243017-WF		

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	2475.000	57.28	32.25	89.53	114.00	24.47	peak	150	360	P	
2	2475.000	43.42	32.25	75.67	94.00	18.33	AVG	150	360	P	

Vertical



Shenzhen CTL Testing Technology Co., Ltd

Tel: +86-755-89486194

Unit 01A&B&C&D-1, Building A3, Guangming Sci-Tech Park, Guan Guang Road, Fenghu


Radiated Emission Measurement

File :RF2

Data :#3045

Date: 2026/04/23

Time: 21:08:56



Site LAB Chamber 1

Polarization: **Vertical**

Temperature: 25(C)

Limit: 114

Power:

Humidity: 50 %

EUT:

Distance: 3m

M/N:

Mode: 2475MHz

Note: CTL2602243017-WF

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	2475.000	49.56	32.25	81.81	114.00	32.19	peak	150	0	P	
2	2475.000	35.04	32.25	67.29	94.00	26.71	AVG	150	0	P	

REMARKS:


1. Emission level (dBuV/m) =Raw Value (dBuV)+Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
3. Margin value = Limit value- Emission level.
4. -- Mean the PK detector measured value is below average limit.
5. The other emission levels were very low against the limit.
6. RBW1MHz VBW3MHz Peak detector is for PK value; RBW 1MHz VBW10Hz Peak detector is for AV value.
7. For fundamental frequency, RBW 3MHz VBW 3MHz Peak detector is for PK Value; RMS detector is for AV value.

3.3. Occupied Bandwidth Measurement

Limit

N/A

Test Configuration



Test Procedure


The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100KHz RBW and 300KHz VBW.


The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

Test Results


Modulation	Channel	99% OBW (MHz)	20dB bandwidth (MHz)	Result
GFSK	CH01	1.1507	1.175	Pass
	CH17	1.1583	1.175	
	CH33	1.1643	1.175	

Test plot as follows:





CH17



CH33

3.4. Antenna Requirement

Standard Applicable


For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

Refer to statement below for compliance.

The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

Antenna Connected Construction


The antenna used in this product is a Built-in Antenna, The directional gains of antenna used for transmitting is 0.00dBi.



Antenna

4. Test Setup Photos of the EUT






5. External and Internal Photos of the EUT

External Photos of EUT











Internal Photos of EUT





***** End of Report *****