



FCC RF Test Report

APPLICANT : Commtiva Technology Limited
EQUIPMENT : Smart Phone
BRAND NAME : InFocus
MODEL NAME : VZU
MARKETING NAME : InFocus VZU
FCC ID : 2AL86VZU
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DTS) Digital Transmission System

The product was received on May 07, 2017 and testing was completed on May 24, 2017. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager

**SPORTON INTERNATIONAL INC.**

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.

SPORTON INTERNATIONAL INC.
TEL : 886-3-327-3456
FAX : 886-3-328-4978
FCC ID : 2AL86VZU

Page Number : 1 of 34
Report Issued Date : Jun. 09, 2017
Report Version : Rev. 01
Report Template No.: BU5-FR15CWL Version 2.0



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant.....	5
1.2 Manufacturer.....	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Modification of EUT	5
1.5 Testing Location	6
1.6 Applicable Standards.....	6
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	7
2.1 Carrier Frequency and Channel	7
2.2 Test Mode.....	8
2.3 Connection Diagram of Test System.....	9
2.4 Support Unit used in test configuration and system	9
2.5 EUT Operation Test Setup	10
2.6 Measurement Results Explanation Example.....	10
3 TEST RESULT	11
3.1 6dB and 99% Bandwidth Measurement	11
3.2 Output Power Measurement.....	13
3.3 Power Spectral Density Measurement	14
3.4 Conducted Band Edges and Spurious Emission Measurement	16
3.5 Radiated Band Edges and Spurious Emission Measurement	26
3.6 AC Conducted Emission Measurement.....	30
3.7 Antenna Requirements.....	32
4 LIST OF MEASURING EQUIPMENT	33
5 UNCERTAINTY OF EVALUATION.....	34
APPENDIX A. CONDUCTED TEST RESULTS	
APPENDIX B. AC CONDUCTED EMISSION TEST RESULT	
APPENDIX C. RADIATED SPURIOUS EMISSION	
APPENDIX D. RADIATED SPURIOUS EMISSION PLOTS	
APPENDIX E. DUTY CYCLE PLOTS	
APPENDIX F. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR721738-02C	Rev. 01	Initial issue of report	Jun. 09, 2017

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.1	-	99% Bandwidth	-	Pass	-
3.2	15.247(b)	Power Output Measurement	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass	-
3.4	15.247(d)	Conducted Band Edges	$\leq 20\text{dBc}$	Pass	-
		Conducted Spurious Emission		Pass	-
3.5	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 7.23 dB at 2390.000 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 16.50 dB at 0.558 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-



1 General Description

1.1 Applicant

Commtiva Technology Limited

Grand Pavilion, Hibiscus Way, 802 West Bay Road, P. O. Box 31119, Grand Cayman, KY1-1205
Cayman Islands

1.2 Manufacturer

SHENZHEN HONGFUJIN PRECISION INDURSTY CO., LTD

AREA B, HONGGUAN TECHNOLOGY PARK, FOXCONN, GUANLAN, LONGHUA NEW DISTRICT,
SHENZHEN, GUANGDONG PROVINCE, P.R.CHINA

1.3 Product Feature of Equipment Under Test

WCDMA/LTE, Bluetooth, Wi-Fi 2.4GHz 802.11b/g/n, NFC, and GPS.

Product Specification subjective to this standard	
Antenna Type	WWAN: Fixed Internal Antenna WLAN: Monopole Antenna Bluetooth: Monopole Antenna GPS / Glonass : Monopole Antenna NFC: Loop Antenna

1.4 Modification of EUT

No modifications are made to the EUT during all test items.

1.5 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW0007 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

Test Site	SPORTON INTERNATIONAL INC.	
Test Site Location	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978	
Test Site No.	Sporton Site No.	
	TH05-HY	CO05-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

Test Site	SPORTON INTERNATIONAL INC.	
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd Rd. Guishan Dist, Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855	
Test Site No.	Sporton Site No.	
	03CH15-HY	

Note: The test site complies with ANSI C63.4 2014 requirement.

1.6 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Y plane) were recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437	-	-


2.2 Test Mode

Final test mode of conducted test items and radiated spurious emissions are considering the modulation and worse data rates as below table.

Modulation	Data Rate
802.11b	1 Mbps
802.11g	6 Mbps
802.11n HT20	MCS0

Test Cases	
AC Conducted Emission	Mode 1: WCDMA Band II Idle + Bluetooth Link + WLAN Link + MPEG4 + Earphone + USB Cable (Charging from Adapter)

2.3 Connection Diagram of Test System



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
2.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 1.8 m
3.	Notebook	DELL	Latitude E6320	FCC DoC/ Contains FCC ID: QDS-BRCM1054	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
4.	Bluetooth Earphone	Sony Ericsson	MW600	PY7DDA-2029	N/A	N/A
5.	iPod Earphone	Apple	N/A	Verification	Unshielded, 1.0 m	N/A



2.5 EUT Operation Test Setup

The RF test items, programmed RF utility, "QRCT" installed in the notebook make the EUT provide functions like channel selection and power level for continuous transmitting and receiving signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.2 + 10 = 14.2 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 DTS D01 Meas. Guidance v04.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) = 1MHz and set the Video bandwidth (VBW) = 3MHz.
6. Measure and record the results in the test report.


3.1.4 Test Setup





3.1.5 Test Result of 6dB and 99% Occupied Bandwidth

Please refer to Appendix A.



Note : The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi are used the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v04 section 9.1.2 PKPM1 Peak power meter method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Peak Output Power

Please refer to Appendix A.

3.2.6 Test Result of Average output Power (Reporting Only)

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.


3.3.4 Test Setup





3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.



3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement.


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup






3.4.5 Test Result of Conducted Band Edges and Spurious Emission

Test Mode :	802.11b	Temperature :	21~25°C
Test Band :	2.4GHz Low	Relative Humidity :	51~54%
Test Channel :	01	Test Engineer :	Aking Chang


WLAN 802.11b Channel 01

100kHz PSD reference Level




Date: 12.MAY.2017 01:32:11

Low Channel Plot




Date: 12.MAY.2017 01:34:40

Spurious Emission 30MHz~3GHz



Date: 12.MAY.2017 01:35:16

Spurious Emission 2GHz~25GHz




Date: 12.MAY.2017 01:35:25



Test Mode :	802.11b	Temperature :	21~25°C
Test Band :	2.4GHz Mid	Relative Humidity :	51~54%
Test Channel :	06	Test Engineer :	Aking Chang


WLAN 802.11b Channel 06

100kHz PSD reference Level




Date: 12.MAY.2017 01:37:35

Spurious Emission 30MHz~3GHz



Date: 12.MAY.2017 01:37:47

Spurious Emission 2GHz~25GHz




Date: 12.MAY.2017 01:37:55



Test Mode :	802.11b	Temperature :	21~25°C
Test Band :	2.4GHz High	Relative Humidity :	51~54%
Test Channel :	11	Test Engineer :	Aking Chang


WLAN 802.11b Channel 11

100kHz PSD reference Level




Date: 12.MAY.2017 01:39:24

High Channel Plot




Date: 12.MAY.2017 01:39:34

Spurious Emission 30MHz~3GHz



Date: 12.MAY.2017 01:39:46

Spurious Emission 2GHz~25GHz




Date: 12.MAY.2017 01:39:55



Test Mode :	802.11g	Temperature :	21~25°C
Test Band :	2.4GHz Low	Relative Humidity :	51~54%
Test Channel :	01	Test Engineer :	Aking Chang


WLAN 802.11g Channel 01

100kHz PSD reference Level




Date: 12.MAY.2017 01:42:45

Low Channel Plot




Date: 12.MAY.2017 01:43:00

Spurious Emission 30MHz~3GHz



Date: 12.MAY.2017 01:43:13

Spurious Emission 2GHz~25GHz




Date: 12.MAY.2017 01:43:21



Test Mode :	802.11g	Temperature :	21~25°C
Test Band :	2.4GHz Mid	Relative Humidity :	51~54%
Test Channel :	06	Test Engineer :	Aking Chang


WLAN 802.11g Channel 06

100kHz PSD reference Level




Date: 12.MAY.2017 01:45:30

Spurious Emission 30MHz~3GHz



Date: 12.MAY.2017 01:45:42

Spurious Emission 2GHz~25GHz




Date: 12.MAY.2017 01:45:50



Test Mode :	802.11g	Temperature :	21~25°C
Test Band :	2.4GHz High	Relative Humidity :	51~54%
Test Channel :	11	Test Engineer :	Aking Chang


WLAN 802.11g Channel 11

100kHz PSD reference Level




Date: 12.MAY.2017 01:49:28

High Channel Plot




Date: 12.MAY.2017 01:49:45

Spurious Emission 30MHz~3GHz



Date: 12.MAY.2017 01:49:57

Spurious Emission 2GHz~25GHz




Date: 12.MAY.2017 01:50:06



Test Mode :	802.11n HT20	Temperature :	21~25°C
Test Band :	2.4GHz Low	Relative Humidity :	51~54%
Test Channel :	01	Test Engineer :	Aking Chang


WLAN 802.11n HT20 Channel 01

100kHz PSD reference Level




Date: 12.MAY.2017 01:52:20

Low Channel Plot




Date: 12.MAY.2017 01:53:21

Spurious Emission 30MHz~3GHz



Date: 12.MAY.2017 01:55:25

Spurious Emission 2GHz~25GHz




Date: 12.MAY.2017 01:55:34



Test Mode :	802.11n HT20	Temperature :	21~25°C
Test Band :	2.4GHz Mid	Relative Humidity :	51~54%
Test Channel :	06	Test Engineer :	Aking Chang


WLAN 802.11n HT20 Channel 06

100kHz PSD reference Level




Date: 12.MAY.2017 01:57:24

Spurious Emission 30MHz~3GHz



Date: 12.MAY.2017 01:57:35

Spurious Emission 2GHz~25GHz




Date: 12.MAY.2017 01:57:44

Test Mode :	802.11n HT20	Temperature :	21~25°C
Test Band :	2.4GHz High	Relative Humidity :	51~54%
Test Channel :	11	Test Engineer :	Aking Chang


WLAN 802.11n HT20 Channel 11

100kHz PSD reference Level




Date: 12.MAY.2017 02:03:04

High Channel Plot




Date: 12.MAY.2017 02:03:22

Spurious Emission 30MHz~3GHz



Date: 12.MAY.2017 02:03:34

Spurious Emission 2GHz~25GHz



Date: 12.MAY.2017 02:03:42



3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.




3.5.3 Test Procedures


1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.
For average measurement:
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C and D.

3.5.7 Duty Cycle

Please refer to Appendix E.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C and D.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Power Meter	Anritsu	ML2495A	0932001	300MHz~40GHz	Sep. 29, 2016	May 09, 2017 ~ May 12, 2017	Sep. 28, 2017	Conducted (TH05-HY)
Power Sensor	Anritsu	MA2411B	0846202	300MHz~40GHz	Sep. 29, 2016	May 09, 2017 ~ May 12, 2017	Sep. 28, 2017	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100055	9kHz-40GHz	Jul. 17, 2016	May 09, 2017 ~ May 12, 2017	Jul. 16, 2017	Conducted (TH05-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9 kHz~30 MHz	May 15, 2017	May 22, 2017 ~ May 24, 2017	May 14, 2019	Radiation (03CH15-HY)
EMI Test Receiver	Keysight	N9038A(MXE)	MY55420170	N/A	Mar. 03, 2017	May 22, 2017 ~ May 24, 2017	Mar. 02, 2018	Radiation (03CH15-HY)
Preamplifier	Jet-Power	JAP00101800-30-10P	160118550004	1GHz~18GHz	Apr. 13, 2017	May 22, 2017 ~ May 24, 2017	Apr. 12, 2018	Radiation (03CH15-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170576	18GHz ~ 40GHz	Apr. 27, 2017	May 22, 2017 ~ May 24, 2017	Apr. 26, 2018	Radiation (03CH15-HY)
Preamplifier	MITEQ	JS44-18004000-33-8P	1840917	18GHz ~ 40GHz	Jun. 14, 2016	May 22, 2017 ~ May 24, 2017	Jun. 13, 2017	Radiation (03CH15-HY)
Amplifier	SONOMA	310N	363440	9kHz~1GHz	Nov. 09, 2016	May 22, 2017 ~ May 24, 2017	Nov. 08, 2017	Radiation (03CH15-HY)
Bilog Antenna	TESEQ	CBL6111D&00800N1D01N-06	41912&05	30MHz to 1GHz	Jan. 07, 2017	May 22, 2017 ~ May 24, 2017	Jan. 06, 2018	Radiation (03CH15-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-1620	1G~18GHz	Sep. 30, 2016	May 22, 2017 ~ May 24, 2017	Sep. 29, 2017	Radiation (03CH15-HY)
Preamplifier	Keysight	83017A	MY53270195	1GHz~26.5GHz	Aug. 24, 2016	May 22, 2017 ~ May 24, 2017	Aug. 23, 2017	Radiation (03CH15-HY)
Spectrum Analyzer	Agilent	N9030A	MY52350276	3Hz~44GHz	Mar. 23, 2017	May 22, 2017 ~ May 24, 2017	Mar. 22, 2018	Radiation (03CH15-HY)
Antenna Mast	ChainTek	MBS-520-1	N/A	1m~4m	N/A	May 22, 2017 ~ May 24, 2017	N/A	Radiation (03CH15-HY)
Turn Table	ChainTek	T-200-S-1	N/A	0~360 Degree	N/A	May 22, 2017 ~ May 24, 2017	N/A	Radiation (03CH15-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	May 14, 2017	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESCI 7	100724	9kHz~7GHz	Aug. 30, 2016	May 14, 2017	Aug. 29, 2017	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Nov. 29, 2016	May 14, 2017	Nov. 28, 2017	Conduction (CO05-HY)



5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.7
--	-----

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.14
--	------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.48
--	------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.12
--	------

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Aking Chang	Temperature:	21~25	°C
Test Date:	2017/5/9~2017/05/12	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

2.4GHz Band								
Mod.	Data Rate	NTx	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
11b	1Mbps	1	1	2412	14.45	9.54	0.50	Pass
11b	1Mbps	1	6	2437	14.45	9.54	0.50	Pass
11b	1Mbps	1	11	2462	14.65	10.00	0.50	Pass
11g	6Mbps	1	1	2412	18.10	16.34	0.50	Pass
11g	6Mbps	1	6	2437	18.40	16.34	0.50	Pass
11g	6Mbps	1	11	2462	18.55	16.04	0.50	Pass
HT20	MCS0	1	1	2412	18.95	17.32	0.50	Pass
HT20	MCS0	1	6	2437	18.80	16.32	0.50	Pass
HT20	MCS0	1	11	2462	19.10	17.30	0.50	Pass

TEST RESULTS DATA
Peak Power Table

2.4GHz Band										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
11b	1Mbps	1	1	2412	16.29	30.00	0.18	16.47	36.00	Pass
11b	1Mbps	1	6	2437	16.46	30.00	0.18	16.64	36.00	Pass
11b	1Mbps	1	11	2462	15.98	30.00	0.18	16.16	36.00	Pass
11g	6Mbps	1	1	2412	20.95	30.00	0.18	21.13	36.00	Pass
11g	6Mbps	1	6	2437	20.98	30.00	0.18	21.16	36.00	Pass
11g	6Mbps	1	11	2462	20.50	30.00	0.18	20.68	36.00	Pass
HT20	MCS0	1	1	2412	20.05	30.00	0.18	20.23	36.00	Pass
HT20	MCS0	1	6	2437	20.55	30.00	0.18	20.73	36.00	Pass
HT20	MCS0	1	11	2462	20.89	30.00	0.18	21.07	36.00	Pass

TEST RESULTS DATA
Average Power Table
(Reporting Only)

2.4GHz Band						
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)
11b	1Mbps	1	1	2412	0.10	13.93
11b	1Mbps	1	6	2437	0.10	13.98
11b	1Mbps	1	11	2462	0.10	13.55
11g	6Mbps	1	1	2412	0.65	10.95
11g	6Mbps	1	6	2437	0.65	10.98
11g	6Mbps	1	11	2462	0.65	10.65
HT20	MCS0	1	1	2412	0.70	10.56
HT20	MCS0	1	6	2437	0.70	10.65
HT20	MCS0	1	11	2462	0.70	10.78

TEST RESULTS DATA
Peak Power Density

2.4GHz Band								
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
11b	1Mbps	1	1	2412	-9.42	0.18	8.00	Pass
11b	1Mbps	1	6	2437	-9.48	0.18	8.00	Pass
11b	1Mbps	1	11	2462	-9.62	0.18	8.00	Pass
11g	6Mbps	1	1	2412	-14.78	0.18	8.00	Pass
11g	6Mbps	1	6	2437	-13.98	0.18	8.00	Pass
11g	6Mbps	1	11	2462	-14.88	0.18	8.00	Pass
HT20	MCS0	1	1	2412	-14.76	0.18	8.00	Pass
HT20	MCS0	1	6	2437	-14.42	0.18	8.00	Pass
HT20	MCS0	1	11	2462	-15.39	0.18	8.00	Pass




Appendix B. AC Conducted Emission Test Results

Test Engineer :	Arthur Hsieh	Temperature :	24~26℃
		Relative Humidity :	51~55%

EUT Information

Report NO : 721738-02
Test Mode : Mode 1
Test Voltage : 120Vac/60Hz
Phase : Line

ENV216 Auto Test FCC Power Bar - L



Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	38.0	Off	L1	19.6	28.0	66.0
0.198000	27.9	Off	L1	19.6	35.8	63.7
0.326000	28.8	Off	L1	19.6	30.8	59.6
0.526000	33.3	Off	L1	19.6	22.7	56.0
0.558000	35.8	Off	L1	19.6	20.2	56.0
0.598000	31.8	Off	L1	19.6	24.2	56.0
6.966000	32.8	Off	L1	19.9	27.2	60.0
23.958000	33.8	Off	L1	20.8	26.2	60.0


Final Result 2

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	21.5	Off	L1	19.6	34.5	56.0
0.198000	21.2	Off	L1	19.6	32.5	53.7
0.326000	24.7	Off	L1	19.6	24.9	49.6
0.526000	26.9	Off	L1	19.6	19.1	46.0
0.558000	29.5	Off	L1	19.6	16.5	46.0
0.598000	25.4	Off	L1	19.6	20.6	46.0
6.966000	27.0	Off	L1	19.9	23.0	50.0
23.958000	25.4	Off	L1	20.8	24.6	50.0

EUT Information

Report NO : 721738-02
Test Mode : Mode 1
Test Voltage : 120Vac/60Hz
Phase : Neutral

ENV216 Auto Test FCC Power Bar - N



Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	42.7	Off	N	19.5	23.3	66.0
0.182000	32.5	Off	N	19.5	31.9	64.4
0.198000	31.3	Off	N	19.5	32.4	63.7
0.598000	30.5	Off	N	19.5	25.5	56.0
6.790000	32.4	Off	N	19.9	27.6	60.0
20.310000	38.4	Off	N	20.7	21.6	60.0
23.438000	42.3	Off	N	20.9	17.7	60.0

Final Result 2

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	22.6	Off	N	19.5	33.4	56.0
0.182000	22.5	Off	N	19.5	31.9	54.4
0.198000	21.5	Off	N	19.5	32.2	53.7
0.598000	21.9	Off	N	19.5	24.1	46.0
6.790000	23.7	Off	N	19.9	26.3	50.0
20.310000	27.2	Off	N	20.7	22.8	50.0
23.438000	29.6	Off	N	20.9	20.4	50.0



Appendix C. Radiated Spurious Emission

Test Engineer :	Karl Hou, Watt Tseng, Stan Hsieh	Temperature :	22~24°C
		Relative Humidity :	45~47%

2.4GHz 2400~2483.5MHz

WIFI 802.11b (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b CH 01 2412MHz		2389.59	52.8	-21.2	74	42.78	27.07	3.96	30.93	169	162	P	H
		2389.485	44.38	-9.62	54	34.36	27.07	3.96	30.93	169	162	A	H
	*	2412	99.36	-	-	89.25	27.12	3.99	30.92	169	162	P	H
	*	2412	95.44	-	-	85.33	27.12	3.99	30.92	169	162	A	H
													H
													H
		2389.59	52.08	-21.92	74	42.06	27.07	3.96	30.93	292	195	P	V
		2390	44.1	-9.9	54	34.07	27.07	3.96	30.92	292	195	A	V
	*	2412	98.43	-	-	88.32	27.12	3.99	30.92	292	195	P	V
	*	2412	94.61	-	-	84.5	27.12	3.99	30.92	292	195	A	V
													V
													V
802.11b CH 06 2437MHz		2363.06	50.78	-23.22	74	40.91	26.96	3.94	30.95	161	163	P	H
		2389.94	41.3	-12.7	54	31.27	27.07	3.96	30.92	161	163	A	H
	*	2437	100.21	-	-	89.97	27.23	4	30.91	161	163	P	H
	*	2437	95.52	-	-	85.28	27.23	4	30.91	161	163	A	H
		2488.03	51.84	-22.16	74	41.37	27.4	4.04	30.89	161	163	P	H
		2483.55	41.64	-12.36	54	31.23	27.34	4.04	30.89	161	163	A	H
		2388.96	50.55	-23.45	74	40.53	27.07	3.96	30.93	284	192	P	V
		2389.38	41.26	-12.74	54	31.24	27.07	3.96	30.93	284	192	A	V
	*	2437	98.68	-	-	88.44	27.23	4	30.91	284	192	P	V
	*	2437	95.63	-	-	85.39	27.23	4	30.91	284	192	A	V
		2491.67	50.97	-23.03	74	40.5	27.4	4.04	30.89	284	192	P	V
		2485.79	41.1	-12.9	54	30.69	27.34	4.04	30.89	284	192	A	V



802.11b CH 11 2462MHz	*	2462	100.07	-	-	89.75	27.29	4.01	30.9	160	160	P	H
	*	2462	96.44	-	-	86.12	27.29	4.01	30.9	160	160	A	H
		2484.16	53.06	-20.94	74	42.65	27.34	4.04	30.89	160	160	P	H
		2484.2	44.14	-9.86	54	33.73	27.34	4.04	30.89	160	160	A	H
													H
													H
	*	2462	98.95	-	-	88.63	27.29	4.01	30.9	272	191	P	V
	*	2462	95.79	-	-	85.47	27.29	4.01	30.9	272	191	A	V
		2484.56	52.61	-21.39	74	42.2	27.34	4.04	30.89	272	191	P	V
		2484.52	42.99	-11.01	54	32.58	27.34	4.04	30.89	272	191	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11b (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11b CH 01 2412MHz		4824	43.66	-30.34	74	70.18	31.69	5.69	64.36	100	0	P	H
													H
													H
													H
		4824	43.47	-30.53	74	69.99	31.69	5.69	64.36	100	0	P	V
													V
													V
													V
802.11b CH 06 2437MHz		4874	42.7	-31.3	74	69.14	31.78	5.72	64.4	100	0	P	H
		7311	48.52	-25.48	74	69.79	36.73	7.06	65.55	100	0	P	H
													H
													H
		4874	43.67	-30.33	74	70.11	31.78	5.72	64.4	100	0	P	V
		7311	49.42	-24.58	74	70.69	36.73	7.06	65.55	100	0	P	V
													V
													V
802.11b CH 11 2462MHz		4924	48.68	-25.32	74	75.04	31.88	5.74	64.44	100	0	P	H
		7386	48.98	-25.02	74	70.1	36.99	7.07	65.62	100	0	P	H
													H
													H
		4924	46.46	-27.54	74	72.82	31.88	5.74	64.44	100	0	P	V
		7386	49.88	-24.12	74	71	36.99	7.07	65.62	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11g (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11g CH 01 2412MHz		2390	58.88	-15.12	74	48.85	27.07	3.96	30.92	192	163	P	H
		2390	46.51	-7.49	54	36.48	27.07	3.96	30.92	192	163	A	H
	*	2412	99.98	-	-	89.87	27.12	3.99	30.92	192	163	P	H
	*	2412	92.63	-	-	82.52	27.12	3.99	30.92	192	163	A	H
													H
													H
		2390	54.61	-19.39	74	44.58	27.07	3.96	30.92	292	195	P	V
		2389.905	45.24	-8.76	54	35.21	27.07	3.96	30.92	292	195	A	V
	*	2412	98.06	-	-	87.95	27.12	3.99	30.92	292	195	P	V
	*	2412	90.37	-	-	80.26	27.12	3.99	30.92	292	195	A	V
													V
													V
802.11g CH 06 2437MHz		2368.66	50.47	-23.53	74	40.53	27.01	3.94	30.93	160	162	P	H
		2388.4	41.32	-12.68	54	31.3	27.07	3.96	30.93	160	162	A	H
	*	2437	100.79	-	-	90.55	27.23	4	30.91	160	162	P	H
	*	2437	93.06	-	-	82.82	27.23	4	30.91	160	162	A	H
		2485.51	51.68	-22.32	74	41.27	27.34	4.04	30.89	160	162	P	H
		2489.22	42.12	-11.88	54	31.65	27.4	4.04	30.89	160	162	A	H
		2386.02	50.84	-23.16	74	40.82	27.07	3.96	30.93	284	194	P	V
		2389.94	41.31	-12.69	54	31.28	27.07	3.96	30.92	284	194	A	V
	*	2437	99.04	-	-	88.8	27.23	4	30.91	284	194	P	V
	*	2437	91.44	-	-	81.2	27.23	4	30.91	284	194	A	V
		2492.65	51.07	-22.93	74	40.59	27.4	4.04	30.88	284	194	P	V
		2494.61	41.55	-12.45	54	31.07	27.4	4.04	30.88	284	194	A	V



802.11g CH 11 2462MHz	*	2462	101.03	-	-	90.71	27.29	4.01	30.9	160	137	P	H
	*	2462	93.35	-	-	83.03	27.29	4.01	30.9	160	137	A	H
		2484.4	54.57	-19.43	74	44.16	27.34	4.04	30.89	160	137	P	H
		2483.8	44.33	-9.67	54	33.92	27.34	4.04	30.89	160	137	A	H
													H
													H
	*	2462	100.81	-	-	90.49	27.29	4.01	30.9	282	142	P	V
	*	2462	92.12	-	-	81.8	27.29	4.01	30.9	282	142	A	V
		2483.64	51.76	-22.24	74	41.35	27.34	4.04	30.89	282	142	P	V
		2483.64	43.21	-10.79	54	32.8	27.34	4.04	30.89	282	142	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11g (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11g CH 01 2412MHz		4824	47.56	-26.44	74	74.08	31.69	5.69	64.36	100	0	P	H
													H
													H
													H
		4824	45.31	-28.69	74	71.83	31.69	5.69	64.36	100	0	P	V
													V
													V
													V
802.11g CH 06 2437MHz		4874	43.16	-30.84	74	69.6	31.78	5.72	64.4	100	0	P	H
		7311	48.47	-25.53	74	69.74	36.73	7.06	65.55	100	0	P	H
													H
													H
		4874	42.36	-31.64	74	68.8	31.78	5.72	64.4	100	0	P	V
		7311	49.28	-24.72	74	70.55	36.73	7.06	65.55	100	0	P	V
													V
													V
802.11g CH 11 2462MHz		4924	44.51	-29.49	74	70.87	31.88	5.74	64.44	100	0	P	H
		7386	49.22	-24.78	74	70.34	36.99	7.07	65.62	100	0	P	H
													H
													H
		4924	45.18	-28.82	74	71.54	31.88	5.74	64.44	100	0	P	V
		7386	49.49	-24.51	74	70.61	36.99	7.07	65.62	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 01 2412MHz		2389.8	58.33	-15.67	74	48.3	27.07	3.96	30.92	191	162	P	H
		2390	46.77	-7.23	54	36.74	27.07	3.96	30.92	191	162	A	H
	*	2412	100.01	-	-	89.9	27.12	3.99	30.92	191	162	P	H
	*	2412	92	-	-	81.89	27.12	3.99	30.92	191	162	A	H
													H
													H
		2389.38	55.35	-18.65	74	45.33	27.07	3.96	30.93	289	196	P	V
		2390	45.72	-8.28	54	35.69	27.07	3.96	30.92	289	196	A	V
	*	2412	98.34	-	-	88.23	27.12	3.99	30.92	289	196	P	V
	*	2412	90.65	-	-	80.54	27.12	3.99	30.92	289	196	A	V
													V
													V
802.11n HT20 CH 06 2437MHz		2375.52	50.14	-23.86	74	40.18	27.01	3.96	30.93	162	161	P	H
		2385.46	41.43	-12.57	54	31.47	27.01	3.96	30.93	162	161	A	H
	*	2437	99.72	-	-	89.48	27.23	4	30.91	162	161	P	H
	*	2437	91.02	-	-	80.78	27.23	4	30.91	162	161	A	H
		2484.39	51.37	-22.63	74	40.96	27.34	4.04	30.89	162	161	P	H
		2488.17	42.17	-11.83	54	31.7	27.4	4.04	30.89	162	161	A	H
		2389.94	51.14	-22.86	74	41.11	27.07	3.96	30.92	287	196	P	V
		2385.6	41.6	-12.4	54	31.58	27.07	3.96	30.93	287	196	A	V
	*	2437	98.37	-	-	88.13	27.23	4	30.91	287	196	P	V
	*	2437	90.5	-	-	80.26	27.23	4	30.91	287	196	A	V
		2489.64	51.28	-22.72	74	40.81	27.4	4.04	30.89	287	196	P	V
		2487.82	41.55	-12.45	54	31.08	27.4	4.04	30.89	287	196	A	V



802.11n HT20 CH 11 2462MHz	*	2462	100.86	-	-	90.54	27.29	4.01	30.9	156	162	P	H
	*	2462	93.04	-	-	82.72	27.29	4.01	30.9	156	162	A	H
		2483.6	52.11	-21.89	74	41.7	27.34	4.04	30.89	156	162	P	H
		2483.64	44.68	-9.32	54	34.27	27.34	4.04	30.89	156	162	A	H
													H
													H
	*	2462	99.05	-	-	88.73	27.29	4.01	30.9	277	191	P	V
	*	2462	90.33	-	-	80.01	27.29	4.01	30.9	277	191	A	V
		2485.76	52.25	-21.75	74	41.84	27.34	4.04	30.89	277	191	P	V
		2483.68	43.07	-10.93	54	32.66	27.34	4.04	30.89	277	191	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 01 2412MHz		4824	43.66	-30.34	74	70.18	31.69	5.69	64.36	100	0	P	H
													H
													H
													H
		4824	43.59	-30.41	74	70.11	31.69	5.69	64.36	100	0	P	V
													V
													V
													V
802.11n HT20 CH 06 2437MHz		4874	43.93	-30.07	74	70.37	31.78	5.72	64.4	100	0	P	H
		7311	48.95	-25.05	74	70.22	36.73	7.06	65.55	100	0	P	H
													H
													H
		4874	43.6	-30.4	74	70.04	31.78	5.72	64.4	100	0	P	V
		7311	49.34	-24.66	74	70.61	36.73	7.06	65.55	100	0	P	V
													V
													V
802.11n HT20 CH 11 2462MHz		4924	43.26	-30.74	74	69.62	31.88	5.74	64.44	100	0	P	H
		7386	48.87	-25.13	74	69.99	36.99	7.07	65.62	100	0	P	H
													H
													H
		4924	43.26	-30.74	74	69.62	31.88	5.74	64.44	100	0	P	V
		7386	49.21	-24.79	74	70.33	36.99	7.07	65.62	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Emission below 1GHz

2.4GHz WIFI 802.11g (LF)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz 802.11g LF		30	22.6	-17.4	40	29.87	24.86	0.46	32.59	-	-	P	H
		123.42	29.49	-14.01	43.5	43.51	17.64	0.86	32.58	100	0	P	H
		135.84	29	-14.5	43.5	42.92	17.63	0.93	32.56	-	-	P	H
		423.9	24.71	-21.29	46	32.83	22.75	1.63	32.58	-	-	P	H
		722.1	28.32	-17.68	46	31.09	27.47	2.15	32.51	-	-	P	H
		953.8	31.81	-14.19	46	29.44	30.96	2.44	31.28	-	-	P	H
													H
													H
													H
													H
													H
													H
		34.59	29.66	-10.34	40	40.04	21.74	0.46	32.59	100	0	P	V
		82.92	27.63	-12.37	40	45.49	13.9	0.74	32.59	-	-	P	V
		109.65	31.51	-11.99	43.5	46.14	17.1	0.79	32.59	-	-	P	V
		402.9	27.22	-18.78	46	36.11	22.01	1.58	32.56	-	-	P	V
		483.4	27.82	-18.18	46	34.8	23.8	1.74	32.62	-	-	P	V
		954.5	31.78	-14.22	46	29.37	31	2.44	31.28	-	-	P	V
													V
													V
													V
													V
													V
													V
												V	
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	Peak or Average
H/V	Horizontal or Vertical

A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.



Appendix D. Radiated Spurious Emission Plots

Test Engineer :	Karl Hou, Watt Tseng, Stan Hsieh	Temperature :	22~24°C
		Relative Humidity :	45~47%





Note symbol

-L	Low channel location
-R	High channel location







2.4GHz 2400~2483.5MHz





WIFI 802.11b (Band Edge @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH01 2412MHz	
1	Horizontal	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak Mode : 721738-02 Mode : 7	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak Mode : 721738-02 Mode : 7
Avg.	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 HORIZONTAL Detector : RBW:1000.000KHz VBW:0.300KHz SWT:Auto Project : Peak Mode : 721738-02 Mode : 7	 Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 HORIZONTAL Detector : RBW:1000.000KHz VBW:0.300KHz SWT:Auto Project : Peak Mode : 721738-02 Mode : 7









WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH01 2412MHz	
1	Vertical	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 VERTICAL Detector : Peak Project : 721738-02 Mode : 7	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 VERTICAL Detector : Peak Project : 721738-02 Mode : 7
Avg.	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 VERTICAL Detector : Peak Project : 721738-02 Mode : 7	 Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 VERTICAL Detector : Peak Project : 721738-02 Mode : 7





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH06 2437MHz - L	
1	Horizontal	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 721738-02 Mode : 8	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 721738-02 Mode : 8
Avg.	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 721738-02 Mode : 8	 Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 721738-02 Mode : 8







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH06 2437MHz - R	
1	Horizontal	Fundamental
Peak	 Date: 2017-05-22 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 721738-02 Mode : 8	Left blank
Avg.	 Date: 2017-05-22 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 721738-02 Mode : 8	Left blank

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH06 2437MHz - L	
1	Vertical	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 VERTICAL Detector : Peak Project : 721738-02 Mode : 8	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 VERTICAL Detector : Peak Project : 721738-02 Mode : 8
Avg.	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 VERTICAL Detector : Peak Project : 721738-02 Mode : 8	 Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 VERTICAL Detector : Peak Project : 721738-02 Mode : 8







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH06 2437MHz - R	
1	Vertical	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 VERTICAL Detector : Peak Project : 721738-02 Mode : 8	Left blank
Avg.	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 VERTICAL Detector : Peak Project : 721738-02 Mode : 8	Left blank







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH11 2462MHz	
1	Horizontal	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 721738-02 Mode : 9	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 721738-02 Mode : 9
Avg.	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 721738-02 Mode : 9	 Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 721738-02 Mode : 9







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH11 2462MHz	
1	Vertical	Fundamental
Peak	 Level (dBuV/m) Frequency (MHz) Date: 2017-05-22 PEAK_BE_74 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 721738-02 Mode : 9	 Level (dBuV/m) Frequency (MHz) Date: 2017-05-22 PEAK_74 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 721738-02 Mode : 9
Avg.	 Level (dBuV/m) Frequency (MHz) Date: 2017-05-22 AVG_BE_54 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 VERTICAL RBW:1000.000KHz VBW:0.300KHz SWT:Auto Detector : Peak Project : 721738-02 Mode : 9	 Level (dBuV/m) Frequency (MHz) Date: 2017-05-22 AVG_54 Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 VERTICAL RBW:1000.000KHz VBW:0.300KHz SWT:Auto Detector : Peak Project : 721738-02 Mode : 9





2.4GHz 2400~2483.5MHz
WIFI 802.11g (Band Edge @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH01 2412MHz	
1	Horizontal	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak Mode : 721738-02 Mode : 10	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak Mode : 721738-02 Mode : 10
Avg.	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 HORIZONTAL Detector : RBW:1000.000KHz VBW:1.000KHz SWT:Auto Project : Peak Mode : 721738-02 Mode : 10	 Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 HORIZONTAL Detector : RBW:1000.000KHz VBW:1.000KHz SWT:Auto Project : Peak Mode : 721738-02 Mode : 10





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH01 2412MHz	
1	Vertical	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 VERTICAL Detector : Peak Project : 721738-02 Mode : 10	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 VERTICAL Detector : Peak Project : 721738-02 Mode : 10
Avg.	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 VERTICAL Detector : Peak Project : 721738-02 Mode : 10	 Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 VERTICAL Detector : Peak Project : 721738-02 Mode : 10







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH06 2437MHz - L	
1	Horizontal	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak Mode : 721738-02 Date: 2017-05-22	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak Mode : 721738-02 Date: 2017-05-22
Avg.	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 HORIZONTAL Detector : RBW:1000.000KHz VBW:1.000KHz SWT:Auto Project : Peak Mode : 721738-02 Date: 2017-05-22	 Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 HORIZONTAL Detector : RBW:1000.000KHz VBW:1.000KHz SWT:Auto Project : Peak Mode : 721738-02 Date: 2017-05-22





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH06 2437MHz - R	
1	Horizontal	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 721738-02 Mode : 11	Left blank
Avg.	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 721738-02 Mode : 11	Left blank







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH06 2437MHz - L	
1	Vertical	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 VERTICAL Detector : Peak Project : 721738-02 Mode : 11	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 VERTICAL Detector : Peak Project : 721738-02 Mode : 11
Avg.	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 VERTICAL Detector : Peak Project : 721738-02 Mode : 11	 Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 VERTICAL Detector : Peak Project : 721738-02 Mode : 11







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH06 2437MHz - R	
1	Vertical	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 VERTICAL Detector : Peak Project : 721738-02 Mode : 11	Left Blank
Avg.	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 VERTICAL Detector : Peak Project : 721738-02 Mode : 11	Left Blank



WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH11 2462MHz	
1	Horizontal	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak Mode : 721738-02 Date: 2017-05-22	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak Mode : 721738-02 Date: 2017-05-22
Avg.	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 HORIZONTAL Detector : RBW:1000.000KHz VBW:1.000KHz SWT:Auto Project : Peak Mode : 721738-02 Date: 2017-05-22	 Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 HORIZONTAL Detector : RBW:1000.000KHz VBW:1.000KHz SWT:Auto Project : Peak Mode : 721738-02 Date: 2017-05-22







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH11 2462MHz	
1	Vertical	Fundamental
Peak	 Level (dBuV/m) Frequency (MHz) Date: 2017-05-22 PEAK_BE_74 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 721738-02 Mode : 12	 Level (dBuV/m) Frequency (MHz) Date: 2017-05-22 PEAK_74 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 721738-02 Mode : 12
Avg.	 Level (dBuV/m) Frequency (MHz) Date: 2017-05-22 AVG_BE_54 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 VERTICAL RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak Project : 721738-02 Mode : 12	 Level (dBuV/m) Frequency (MHz) Date: 2017-05-22 AVG_54 Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 VERTICAL RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak Project : 721738-02 Mode : 12







2.4GHz 2400~2483.5MHz





WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH01 2412MHz	
1	Horizontal	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak Mode : 721738-02 Date : 13	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak Mode : 721738-02 Date : 13
Avg.	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 HORIZONTAL Detector : RBW:1000.000KHz VBW:1.000KHz SWT:Auto Project : Peak Mode : 721738-02 Date : 13	 Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 HORIZONTAL Detector : RBW:1000.000KHz VBW:1.000KHz SWT:Auto Project : Peak Mode : 721738-02 Date : 13





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH01 2412MHz	
1	Vertical	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 VERTICAL Detector : Peak Project : 721738-02 Mode : 13	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 VERTICAL Detector : Peak Project : 721738-02 Mode : 13
Avg.	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 VERTICAL Detector : Peak Project : 721738-02 Mode : 13	 Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 VERTICAL Detector : Peak Project : 721738-02 Mode : 13







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH06 2437MHz - L	
1	Horizontal	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 721738-02 Mode : 14	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 721738-02 Mode : 14
Avg.	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 721738-02 Mode : 14	 Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 721738-02 Mode : 14





WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH06 2437MHz - R	
1	Horizontal	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 721738-02 Mode : 14	Left blank
Avg.	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 721738-02 Mode : 14	Left blank







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH06 2437MHz - L	
1	Vertical	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 VERTICAL Detector : Peak Project : 721738-02 Mode : 14	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 VERTICAL Detector : Peak Project : 721738-02 Mode : 14
Avg.	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 VERTICAL Detector : Peak Project : 721738-02 Mode : 14	 Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 VERTICAL Detector : Peak Project : 721738-02 Mode : 14







WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH06 2437MHz - R	
1	Vertical	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 VERTICAL Detector : Peak Project : 721738-02 Mode : 14	Left Blank
Avg.	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 VERTICAL Detector : Peak Project : 721738-02 Mode : 14	Left Blank



WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH11 2462MHz	
1	Horizontal	Fundamental
Peak	 Level (dBuV/m) Frequency (MHz) Date: 2017-05-22 PEAK_BE_74 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 721738-02 Mode : 15	 Level (dBuV/m) Frequency (MHz) Date: 2017-05-22 PEAK_74 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 721738-02 Mode : 15
Avg.	 Level (dBuV/m) Frequency (MHz) Date: 2017-05-22 AVG_BE_54 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 HORIZONTAL RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak Project : 721738-02 Mode : 15	 Level (dBuV/m) Frequency (MHz) Date: 2017-05-22 AVG_54 Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 HORIZONTAL RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak Project : 721738-02 Mode : 15





WIFI	2.4GHz 2400~2483.5MHz Fundamental @ 3m	
ANT	802.11n HT20 CH11 2462MHz	
1	Vertical	Fundamental
Peak	 Site : 03CH15-HY Condition : PEAK_BE_74 3m 91200_15_1620 VERTICAL Detector : Peak Project : 721738-02 Mode : 15	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 VERTICAL Detector : Peak Project : 721738-02 Mode : 15
Avg.	 Site : 03CH15-HY Condition : AVG_BE_54 3m 91200_15_1620 VERTICAL Detector : Peak Project : 721738-02 Mode : 15	 Site : 03CH15-HY Condition : AVG_54 3m 91200_15_1620 VERTICAL Detector : Peak Project : 721738-02 Mode : 15





2.4GHz 2400~2483.5MHz



WIFI 802.11b (Harmonic @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11b CH01 2412MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 721738-02 Mode : 7	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 VERTICAL Detector : Peak Project : 721738-02 Mode : 7



WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11b CH06 2437MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 721738-02 Mode : B	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 VERTICAL Detector : Peak Project : 721738-02 Mode : B





WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11b CH11 2462MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 721738-02 Mode : 9	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 VERTICAL Detector : Peak Project : 721738-02 Mode : 9



2.4GHz 2400~2483.5MHz

WIFI 802.11g (Harmonic @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11g CH01 2412MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 721738-02 Mode : 10	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 VERTICAL Detector : Peak Project : 721738-02 Mode : 10



WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11g CH06 2437MHz	
1	Horizontal	Vertical
Peak Avg.	Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 721738-02 Mode : 11	Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 VERTICAL Detector : Peak Project : 721738-02 Mode : 11





WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11g CH11 2462MHz	
1	Horizontal	Vertical
Peak Avg.	Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 721738-02 Mode : 12	Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 VERTICAL Detector : Peak Project : 721738-02 Mode : 12





2.4GHz 2400~2483.5MHz



WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11n HT20 CH01 2412MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 721738-02 Mode : 13	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 VERTICAL Detector : Peak Project : 721738-02 Mode : 13



WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11n HT20 CH06 2437MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 721738-02 Mode : 14	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 VERTICAL Detector : Peak Project : 721738-02 Mode : 14





WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11n HT20 CH11 2462MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 HORIZONTAL Detector : Peak Project : 721738-02 Mode : 15	 Site : 03CH15-HY Condition : PEAK_74 3m 91200_15_1620 VERTICAL Detector : Peak Project : 721738-02 Mode : 15



2.4GHz 2400~2483.5MHz

Emission below 1GHz


2.4GHz WIFI 802.11g (LF)

WIFI	2.4GHz 2400~2483.5MHz	
ANT	802.11g LF	
1	Horizontal	Vertical
QP / Peak	 Site : 03CH15-HY Condition : QP 3m BILOG_15_41912 HORIZONTAL Detector : Peak Project : 721738-02 Mode : 18	 Site : 03CH15-HY Condition : QP 3m BILOG_15_41912 VERTICAL Detector : Peak Project : 721738-02 Mode : 18


Appendix E. Duty Cycle Plots

Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting
802.11b	97.63	8240	0.12	300Hz
802.11g	86.076	1360	0.74	1kHz
2.4GHz 802.11n HT20	85.135	1260	0.79	1kHz


<802.11b



Date: 9.MAY.2017 21:05:20

802.11g


Date: 9.MAY.2017 21:12:56

802.11n HT20


Date: 9.MAY.2017 21:16:06