

FCC Radio Test Report

FCC ID: 2AL8K-H4

Original Grant

Report No. : TB-FCC153898
Applicant : NZS Inc. DBA Clary Icon
Equipment Under Test (EUT)
EUT Name : Interactive Touch Screen
Model No. : H4 OneScreen
Series Model No. : H* OneScreen (*can be A-Z,0-9,or space, or dash)
Brand Name : One Screen
Receipt Date : 2017-05-06
Test Date : 2017-05-07 to 2017-05-26
Issue Date : 2017-05-27
Standards : FCC Part 15, Subpart C (15.247:2016)
Test Method : ANSI C63.10: 2013
Conclusions : **PASS**

In the configuration tested, the EUT complied with the standards specified above,
The EUT technically complies with the FCC and IC requirements


Test/Witness Engineer :

IVAN SU

**Approved &
Authorized**

:

Ray



This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in the report.

Contents

CONTENTS.....	2
1. GENERAL INFORMATION ABOUT EUT	4
1.1 Client Information.....	4
1.2 General Description of EUT (Equipment Under Test)	4
1.3 Block Diagram Showing the Configuration of System Tested.....	5
1.4 Description of Support Units	5
1.5 Description of Test Mode.....	5
1.6 Description of Test Software Setting	7
1.7 Measurement Uncertainty	7
1.8 Test Facility.....	8
2. TEST SUMMARY.....	9
3. TEST EQUIPMENT.....	10
4. CONDUCTED EMISSION TEST	11
4.1 Test Standard and Limit.....	11
4.2 Test Setup.....	11
4.3 Test Procedure.....	11
4.4 EUT Operating Mode	12
4.5 Test Data.....	12
5. RADIATED EMISSION TEST	17
5.1 Test Standard and Limit.....	17
5.2 Test Setup.....	18
5.3 Test Procedure.....	19
5.4 EUT Operating Condition	19
5.5 Test Data.....	20
6. RESTRICTED BANDS REQUIREMENT	47
6.1 Test Standard and Limit.....	47
6.2 Test Setup.....	47
6.3 Test Procedure.....	47
6.4 EUT Operating Condition	48
6.5 Test Data.....	48
7. BANDWIDTH TEST	69
7.1 Test Standard and Limit.....	69
7.2 Test Setup.....	69
7.3 Test Procedure.....	69
7.4 EUT Operating Condition	69
7.5 Test Data.....	70
8. PEAK OUTPUT POWER TEST.....	78
8.1 Test Standard and Limit.....	78
8.2 Test Setup.....	78

8.3 Test Procedure.....	78
8.4 EUT Operating Condition	78
8.5 Test Data.....	79
9. POWER SPECTRAL DENSITY TEST	82
9.1 Test Standard and Limit.....	82
9.2 Test Setup.....	82
9.3 Test Procedure.....	82
9.4 EUT Operating Condition	82
9.5 Test Data.....	83
10. ANTENNA REQUIREMENT.....	91
10.1 Standard Requirement.....	91
10.2 Antenna Connected Construction.....	91

1. General Information about EUT

1.1 Client Information

Applicant : NZS Inc. DBA Clary Icon
Address : 224 Ferris Square, Suite C, San Diego, California, United States
Manufacturer : Shenzhen Konka E-display Co.,Ltd
Address : 22A, KONKA Building, South Technology Road No.12th, High-tech Industrial Park, Nanshan, Shenzhen,China

1.2 General Description of EUT (Equipment Under Test)

EUT Name	:	Interactive Touch Screen	
Models No.	:	H4 OneScreen, H* OneScreen (*can be A-Z,0-9,or space, or dash)	
Model Difference	:	All these models are identical in the same PCB layout and electrical circuit, the only difference is model name for commercial.	
Product Description	:	Operation Frequency:	802.11b/g/n(HT20): 2412MHz~2462MHz 802.11n(HT40): 2422MHz~2452MHz
	:	Number of Channel:	802.11b/g/n(HT20):11 channels see note(3) 802.11n(HT40):7 channels see note(3)
	:	RF Output Power:	802.11b: 19.16 dBm 802.11g: 15.80 dBm 802.11n (HT20): 14.90 dBm 802.11n (HT40): 13.37 dBm
	:	Antenna Gain:	5 dBi Dipole Antenna
	:	Modulation Type:	802.11b: DSSS (CCK, DQPSK, DBPSK) 802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM)
	:	Bit Rate of Transmitter:	802.11b:11/5.5/2/1 Mbps 802.11g:54/48/36/24/18/12/9/6 Mbps 802.11n:up to 150Mbps
	:		
Power Supply	:	AC Voltage supplied	
Power Rating	:	Input: AC 100~240V, 50/60Hz, 5A	
Connecting I/O Port(S)	:	Please refer to the User's Manual	

Note:


- (1) This Test Report is FCC Part 15.247 for 802.11b/g/n, the test procedure follows the FCC KDB 558074 D01 DTS Meas Guidance v04.
- (2) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.
- (3) Channel List:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2412	05	2432	09	2452
02	2417	06	2437	10	2457
03	2422	07	2442	11	2462
04	2427	08	2447		
Note: CH 01~CH 11 for 802.11b/g/n(HT20), CH 03~CH 09 for 802.11n(HT40)					

(4) The Antenna information about the equipment is provided by the applicant.

1.3 Block Diagram Showing the Configuration of System Tested

Normal Mode/ TX Mode



1.4 Description of Support Units

Equipment Information				
Name	Model	FCC ID/VOC	Manufacturer	Used “√”
Cable Information				
Number	Shielded Type	Ferrite Core	Length	Note
Cable 1	NO	NO	1.8M	

1.5 Description of Test Mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned follow was evaluated respectively.

For Conducted Test	
Final Test Mode	Description
Mode 1	Normal Mode with TX B Mode

For Radiated Test	
Final Test Mode	Description
Mode 2	TX Mode B Mode Channel 01/06/11
Mode 3	TX Mode G Mode Channel 01/06/11
Mode 4	TX Mode N(HT20) Mode Channel 01/06/11
Mode 5	TX Mode N(HT40) Mode Channel 03/06/09

Note:

- (1) For all test, we have verified the construction and function in typical operation. And all the test modes were carried out with the EUT in transmitting operation in maximum power with all kinds of data rate.

According to ANSI C63.10 standards, the measurements are performed at the highest, Middle, lowest available channels, and the worst case data rate as follows:

- 802.11b Mode: CCK (1 Mbps)
- 802.11g Mode: OFDM (6 Mbps)
- 802.11n (HT20) Mode: MCS 0 (6.5 Mbps)
- 802.11n (HT40) Mode: MCS 0 (13 Mbps)

- (2) During the testing procedure, the continuously transmitting with the maximum power mode was programmed by the customer.
- (3) The EUT is considered a fixation unit; in normal use it was positioned on X-plane. The worst case was found positioned on X-plane. Therefore only the test data of this X-plane was used for radiated emission measurement test.

1.6 Description of Test Software Setting

During testing channel&Power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of WLAN.

Test Software Version	RtkWiFiTest-v1.8.1		
Channel	CH 01	CH 06	CH 11
IEEE 802.11b DSSS	DEF	DEF	DEF
IEEE 802.11g OFDM	DEF	DEF	DEF
IEEE 802.11n (HT20)	DEF	DEF	DEF
Channel	CH 03	CH 06	CH 09
IEEE 802.11n (HT40)	DEF	DEF	DEF

1.7 Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

Test Item	Parameters	Expanded Uncertainty (U_{Lab})
Conducted Emission	Level Accuracy: 9kHz~150kHz 150kHz to 30MHz	± 3.42 dB ± 3.42 dB
Radiated Emission	Level Accuracy: 9kHz to 30 MHz	± 4.60 dB
Radiated Emission	Level Accuracy: 30MHz to 1000 MHz	± 4.40 dB
Radiated Emission	Level Accuracy: Above 1000MHz	± 4.20 dB

1.8 Test Facility

The testing report were performed by the Shenzhen Toby Technology Co., Ltd., in their facilities located at 1A/F., Bldg.6, Yusheng Industrial Zone, The National Road No.107 Xixiang Section 467, Xixiang, Bao'an, Shenzhen, Guangdong, China. At the time of testing, the following bodies accredited the Laboratory:

CNAS (L5813)

The Laboratory has been accredited by CNAS to ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories for the competence in the field of testing. And the Registration No.: CNAS L5813.

FCC List No.: (811562)

The Laboratory is listed in the United States of American Federal Communications Commission (FCC), and the registration number is 811562.

IC Registration No.: (11950A-1)

The Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing. The site registration: Site# 11950A-1.

2. Test Summary

FCC Part 15 Subpart C(15.247)/ RSS 247 Issue 1				
Standard Section		Test Item	Judgment	Remark
FCC	IC			
15.203	/	Antenna Requirement	PASS	N/A
15.207	RSS-GEN 7.2.4	Conducted Emission	PASS	N/A
15.205	RSS-GEN 7.2.2	Restricted Bands	PASS	N/A
15.247(a)(2)	RSS 247 5.2 (1)	6dB Bandwidth	PASS	N/A
15.247(b)	RSS 247 5.4 (4)	Peak Output Power	PASS	N/A
15.247(e)	RSS 247 5.2 (2)	Power Spectral Density	PASS	N/A
15.247(d)	RSS 247 5.5	Band Edge	PASS	N/A
15.247(d)& 15.209	RSS 247 5.5	Transmitter Radiated Spurious Emission	PASS	N/A
Note: “/” for no requirement for this test item. N/A is an abbreviation for Not Applicable.				

3. Test Equipment

Conducted Emission Test					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
EMI Test Receiver	Rohde & Schwarz	ESCI	100321	Jul. 22, 2016	Jul. 21, 2017
RF Switching Unit	Compliance Direction Systems Inc	RSU-A4	34403	Jul. 22, 2016	Jul. 21, 2017
AMN	SCHWARZBECK	NNBL 8226-2	8226-2/164	Jul. 22, 2016	Jul. 21, 2017
LISN	Rohde & Schwarz	ENV216	101131	Jul. 22, 2016	Jul. 21, 2017
Radiation Emission Test					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Jul. 22, 2016	Jul. 21, 2017
EMI Test Receiver	Rohde & Schwarz	ESPI	100010/007	Jul. 22, 2016	Jul. 21, 2017
Bilog Antenna	ETS-LINDGREN	3142E	00117537	Mar.25, 2017	Mar. 24, 2018
Bilog Antenna	ETS-LINDGREN	3142E	00117542	Mar.25, 2017	Mar. 24, 2018
Horn Antenna	ETS-LINDGREN	3117	00143207	Mar.24, 2017	Mar. 23, 2018
Horn Antenna	ETS-LINDGREN	3117	00143209	Mar.24, 2017	Mar. 23, 2018
Loop Antenna	Laplace instrument	RF300	0701	Mar.24, 2017	Mar. 23, 2018
Pre-amplifier	Sonoma	310N	185903	Mar.25, 2017	Mar. 24, 2018
Pre-amplifier	HP	8449B	3008A00849	Mar.24, 2017	Mar. 23, 2018
Cable	HUBER+SUHNER	100	SUCOFLEX	Mar.25, 2017	Mar. 24, 2018
Positioning Controller	ETS-LINDGREN	2090	N/A	N/A	N/A
Antenna Conducted Emission					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Jul. 22, 2016	Jul. 21, 2017
Spectrum Analyzer	Rohde & Schwarz	ESCI	100010/007	Jul. 22, 2016	Jul. 21, 2017
Power Meter	Anritsu	ML2495A	25406005	Jul. 22, 2016	Jul. 21, 2017
Power Sensor	Anritsu	ML2411B	25406005	Jul. 22, 2016	Jul. 21, 2017

4. Conducted Emission Test

4.1 Test Standard and Limit

4.1.1 Test Standard

FCC Part 15.207

4.1.2 Test Limit

Conducted Emission Test Limit

Frequency	Maximum RF Line Voltage (dB μ V)	
	Quasi-peak Level	Average Level
150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
500kHz~5MHz	56	46
5MHz~30MHz	60	50


Notes:

(1) *Decreasing linearly with logarithm of the frequency.

(2) The lower limit shall apply at the transition frequencies.

(3) The limit decrease in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

4.2 Test Setup



4.3 Test Procedure

The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.

Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.

I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.

LISN at least 80 cm from nearest part of EUT chassis.

The bandwidth of EMI test receiver is set at 9kHz, and the test frequency band is from 0.15MHz to 30MHz.


4.4 EUT Operating Mode

Please refer to the description of test mode.

4.5 Test Data

Please see the next page.


EUT:	Interactive Touch Screen	Model Name :	H4 OneScreen
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Terminal:	Line		
Test Mode:	Normal Mode with TX B Mod		
Remark:	Only worse case is reported		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1		0.2020	37.62	10.02	47.64	63.52	-15.88	QP
2	*	0.2020	34.12	10.02	44.14	53.52	-9.38	AVG
3		0.2660	28.58	10.02	38.60	61.24	-22.64	QP
4		0.2660	24.05	10.02	34.07	51.24	-17.17	AVG
5		0.4660	23.72	10.02	33.74	56.58	-22.84	QP
6		0.4660	16.58	10.02	26.60	46.58	-19.98	AVG
7		1.4100	23.33	10.06	33.39	56.00	-22.61	QP
8		1.4100	15.83	10.06	25.89	46.00	-20.11	AVG
9		2.8780	20.93	10.03	30.96	56.00	-25.04	QP
10		2.8780	11.27	10.03	21.30	46.00	-24.70	AVG
11		12.9060	26.91	10.22	37.13	60.00	-22.87	QP
12		12.9060	25.92	10.22	36.14	50.00	-13.86	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Interactive Touch Screen	Model Name :	H4 OneScreen
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60Hz		
Terminal:	Neutral		
Test Mode:	Normal Mode with TX B Mod		
Remark:	Only worse case is reported		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1		0.2020	37.38	10.02	47.40	63.52	-16.12	QP
2	*	0.2020	33.87	10.02	43.89	53.52	-9.63	AVG
3		0.2700	28.25	10.02	38.27	61.12	-22.85	QP
4		0.2700	24.02	10.02	34.04	51.12	-17.08	AVG
5		0.4660	23.81	10.02	33.83	56.58	-22.75	QP
6		0.4660	16.01	10.02	26.03	46.58	-20.55	AVG
7		1.3420	23.50	10.06	33.56	56.00	-22.44	QP
8		1.3420	12.20	10.06	22.26	46.00	-23.74	AVG
9		2.4860	22.32	10.04	32.36	56.00	-23.64	QP
10		2.4860	9.42	10.04	19.46	46.00	-26.54	AVG
11		5.8659	19.86	10.00	29.86	60.00	-30.14	QP
12		5.8659	16.88	10.00	26.88	50.00	-23.12	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Interactive Touch Screen	Model Name :	H4 OneScreen
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 240V/60Hz		
Terminal:	Line		
Test Mode:	Normal Mode with TX B Mod		
Remark:	Only worse case is reported		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1		0.2020	35.34	10.02	45.36	63.52	-18.16	QP
2	*	0.2020	30.24	10.02	40.26	53.52	-13.26	AVG
3		0.2660	28.10	10.02	38.12	61.24	-23.12	QP
4		0.2660	22.92	10.02	32.94	51.24	-18.30	AVG
5		0.8059	24.26	10.10	34.36	56.00	-21.64	QP
6		0.8059	13.69	10.10	23.79	46.00	-22.21	AVG
7		1.0060	23.64	10.06	33.70	56.00	-22.30	QP
8		1.0060	13.97	10.06	24.03	46.00	-21.97	AVG
9		2.2740	21.39	10.05	31.44	56.00	-24.56	QP
10		2.2740	9.12	10.05	19.17	46.00	-26.83	AVG
11		3.1380	21.93	10.02	31.95	56.00	-24.05	QP
12		3.1380	10.84	10.02	20.86	46.00	-25.14	AVG

Emission Level= Read Level+ Correct Factor

EUT:	Interactive Touch Screen	Model Name :	H4 OneScreen
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 240V/60Hz		
Terminal:	Neutral		
Test Mode:	Normal Mode with TX B Mod		
Remark:	Only worse case is reported		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.2020	35.47	10.02	45.49	63.52	-18.03	QP
2	*	0.2020	30.39	10.02	40.41	53.52	-13.11	AVG
3		0.2660	27.76	10.02	37.78	61.24	-23.46	QP
4		0.2660	22.78	10.02	32.80	51.24	-18.44	AVG
5		0.4660	24.54	10.02	34.56	56.58	-22.02	QP
6		0.4660	17.09	10.02	27.11	46.58	-19.47	AVG
7		1.1740	23.84	10.06	33.90	56.00	-22.10	QP
8		1.1740	9.27	10.06	19.33	46.00	-26.67	AVG
9		2.8820	22.82	10.03	32.85	56.00	-23.15	QP
10		2.8820	11.31	10.03	21.34	46.00	-24.66	AVG
11		4.2819	20.08	9.98	30.06	56.00	-25.94	QP
12		4.2819	10.86	9.98	20.84	46.00	-25.16	AVG

Emission Level= Read Level+ Correct Factor

5. Radiated Emission Test

5.1 Test Standard and Limit

5.1.1 Test Standard
FCC Part 15.209

5.1.2 Test Limit

Radiated Emission Limits (9 kHz~1000 MHz)

Frequency (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3


Radiated Emission Limit (Above 1000MHz)

Frequency (MHz)	Distance of 3m (dBuV/m)	
	Peak	Average
Above 1000	74	54


Note:

- (1) The tighter limit applies at the band edges.
- (2) Emission Level(dBuV/m)=20log Emission Level(uV/m)


5.2 Test Setup



Below 30MHz Test Setup



Below 1000MHz Test Setup



Above 1GHz Test Setup

5.3 Test Procedure

- (1) Measurements at frequency above 1GHz. The EUT was placed on a rotating 1.5m high above the ground. RF absorbers covered the ground plane with a minimum area of 3.0m by 3.0m between the EUT and measurement receiver antenna. The RF absorber shall not exceed 30cm in high above the conducting floor. The table was rotated 360 degrees to determine the position of the highest radiation.
- (2) The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.
- (3) The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- (4) If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit Bellow 1 GHz, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed. But the Peak Value and average value both need to comply with applicable limit above 1 GHz.
- (5) Testing frequency range below 1GHz the measuring instrument use VBW=120 kHz with Quasi-peak detection.
- (6) Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.
- (7) For the actual test configuration, please see the test setup photo.

5.4 EUT Operating Condition

The Equipment Under Test was set to Continual Transmitting in maximum power.

5.5 Test Data

Remark: During testing above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.

Test data please refer the following pages.


9KHz~30MHz

From 9KHz to 30MHz: Conclusion: PASS

Note: The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

30MHz~1GHz

EUT:	Interactive Touch Screen	Model:	H4 OneScreen
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Horizontal		
Test Mode:	TX B Mode 2412MHz		
Remark:	Only worse case is reported		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		60.0691	54.83	-24.60	30.23	40.00	-9.77	peak
2		101.6443	50.42	-21.84	28.58	43.50	-14.92	peak
3		145.3506	52.31	-21.38	30.93	43.50	-12.57	peak
4	!	167.8243	58.84	-20.78	38.06	43.50	-5.44	peak
5		199.9856	54.84	-19.99	34.85	43.50	-8.65	peak
6	*	857.0247	48.88	-5.14	43.74	46.00	-2.26	peak

*:Maximum data x:Over limit !:over margin

Emission Level= Read Level+ Correct Factor

EUT:	Interactive Touch Screen	Model:	H4 OneScreen
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Vertical		
Test Mode:	TX B Mode 2412MHZ		
Remark:	Only worse case is reported		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		60.0691	58.20	-24.60	33.60	40.00	-6.40	QP
2		97.7982	57.58	-22.04	35.54	43.50	-7.96	peak
3	*	144.3348	61.30	-21.47	39.83	43.50	-3.67	peak
4	!	202.8103	59.08	-19.87	39.21	43.50	-4.29	peak
5		440.1963	50.23	-12.16	38.07	46.00	-7.93	peak
6		599.3212	48.02	-8.74	39.28	46.00	-6.72	peak

*:Maximum data x:Over limit !:over margin

Emission Level= Read Level+ Correct Factor

Above 1GHz


EUT:	Interactive Touch Screen	Model:	H4 OneScreen
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Horizontal		
Test Mode:	TX B Mode 2412MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		4824.720	46.45	13.56	60.01	74.00	-13.99	peak
2	*	4826.360	33.16	13.57	46.73	54.00	-7.27	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Interactive Touch Screen	Model:	H4 OneScreen
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Vertical		
Test Mode:	TX B Mode 2412MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		4824.720	49.20	13.56	62.76	74.00	-11.24	peak
2	*	4826.500	35.83	13.57	49.40	54.00	-4.60	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Interactive Touch Screen	Model:	H4 OneScreen
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Horizontal		
Test Mode:	TX B Mode 2437MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		4874.416	46.22	13.86	60.08	74.00	-13.92	peak
2	*	4874.439	32.41	13.86	46.27	54.00	-7.73	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Interactive Touch Screen	Model:	H4 OneScreen
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Vertical		
Test Mode:	TX B Mode 2437MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4874.363	47.99	13.86	61.85	74.00	-12.15	peak
2	*	4874.398	34.53	13.86	48.39	54.00	-5.61	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Interactive Touch Screen	Model:	H4 OneScreen
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Horizontal		
Test Mode:	TX B Mode 2462MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4924.171	47.00	14.15	61.15	74.00	-12.85	peak
2	*	4924.439	32.38	14.15	46.53	54.00	-7.47	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Interactive Touch Screen	Model:	H4 OneScreen
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Vertical		
Test Mode:	TX B Mode 2462MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		4923.964	46.51	14.15	60.66	74.00	-13.34	peak
2	*	4924.337	32.57	14.15	46.72	54.00	-7.28	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Interactive Touch Screen	Model:	H4 OneScreen
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Horizontal		
Test Mode:	TX G Mode 2412MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4823.828	29.10	13.56	42.66	54.00	-11.34	AVG
2		4824.004	46.50	13.56	60.06	74.00	-13.94	peak

Emission Level= Read Level+ Correct Factor


EUT:	Interactive Touch Screen	Model:	H4 OneScreen
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Vertical		
Test Mode:	TX G Mode 2412MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	4823.558	29.11	13.56	42.67	54.00	-11.33	AVG
2		4824.268	43.42	13.56	56.98	74.00	-17.02	peak

Emission Level= Read Level+ Correct Factor


EUT:	Interactive Touch Screen	Model:	H4 OneScreen
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Horizontal		
Test Mode:	TX G Mode 2437MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4874.053	44.47	13.86	58.33	74.00	-15.67	peak
2	*	4874.447	32.24	13.86	46.10	54.00	-7.90	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Interactive Touch Screen	Model:	H4 OneScreen
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Vertical		
Test Mode:	TX G Mode 2437MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4873.863	45.57	13.86	59.43	74.00	-14.57	peak
2	*	4874.355	29.34	13.86	43.20	54.00	-10.80	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Interactive Touch Screen	Model:	H4 OneScreen
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Horizontal		
Test Mode:	TX G Mode 2462MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4924.385	45.16	14.15	59.31	74.00	-14.69	peak
2	*	4924.500	31.64	14.15	45.79	54.00	-8.21	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Interactive Touch Screen	Model:	H4 OneScreen
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Vertical		
Test Mode:	TX G Mode 2462MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4924.274	45.58	14.15	59.73	74.00	-14.27	peak
2	*	4924.480	31.14	14.15	45.29	54.00	-8.71	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Interactive Touch Screen	Model:	H4 OneScreen
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Horizontal		
Test Mode:	TX N(HT20) Mode 2412MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4823.605	31.60	13.56	45.16	54.00	-8.84	AVG
2		4824.298	45.18	13.56	58.74	74.00	-15.26	peak

Emission Level= Read Level+ Correct Factor


EUT:	Interactive Touch Screen	Model:	H4 OneScreen
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Vertical		
Test Mode:	TX N(HT20) Mode 2412MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4823.776	32.23	13.56	45.79	54.00	-8.21	AVG
2		4824.035	45.27	13.56	58.83	74.00	-15.17	peak

Emission Level= Read Level+ Correct Factor


EUT:	Interactive Touch Screen	Model:	H4 OneScreen
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Horizontal		
Test Mode:	TX N(HT20) Mode 2437MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4873.560	45.27	13.86	59.13	74.00	-14.87	peak
2	*	4874.395	31.53	13.86	45.39	54.00	-8.61	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Interactive Touch Screen	Model:	H4 OneScreen
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Vertical		
Test Mode:	TX N(HT20) Mode 2437MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4874.104	45.38	13.86	59.24	74.00	-14.76	peak
2	*	4874.500	29.29	13.86	43.15	54.00	-10.85	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Interactive Touch Screen	Model:	H4 OneScreen
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Horizontal		
Test Mode:	TX N(HT20) Mode 2462MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		4923.902	43.22	14.15	57.37	74.00	-16.63	peak
2	*	4924.394	31.23	14.15	45.38	54.00	-8.62	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Interactive Touch Screen	Model:	H4 OneScreen
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Vertical		
Test Mode:	TX N(HT20) Mode 2462MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4923.624	44.63	14.15	58.78	74.00	-15.22	peak
2	*	4924.448	29.02	14.15	43.17	54.00	-10.83	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Interactive Touch Screen	Model:	H4 OneScreen
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Horizontal		
Test Mode:	TX N(HT40) Mode 2422MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	4843.552	29.25	13.68	42.93	54.00	-11.07	AVG
2		4844.373	43.90	13.68	57.58	74.00	-16.42	peak

Emission Level= Read Level+ Correct Factor


EUT:	Interactive Touch Screen	Model:	H4 OneScreen
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Vertical		
Test Mode:	TX N(HT40) Mode 2422MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	4843.500	29.28	13.68	42.96	54.00	-11.04	AVG
2		4843.621	44.12	13.68	57.80	74.00	-16.20	peak

Emission Level= Read Level+ Correct Factor


EUT:	Interactive Touch Screen	Model:	H4 OneScreen
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Horizontal		
Test Mode:	TX N(HT40) Mode 2437MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		4873.563	43.94	13.86	57.80	74.00	-16.20	peak
2	*	4874.343	29.30	13.86	43.16	54.00	-10.84	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Interactive Touch Screen	Model:	H4 OneScreen
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Vertical		
Test Mode:	TX N(HT40) Mode 2437MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4873.951	44.08	13.86	57.94	74.00	-16.06	peak
2	*	4874.395	29.32	13.86	43.18	54.00	-10.82	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Interactive Touch Screen	Model:	H4 OneScreen
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Horizontal		
Test Mode:	TX N(HT40) Mode 2452MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4903.710	29.27	14.03	43.30	54.00	-10.70	AVG
2		4904.413	43.89	14.03	57.92	74.00	-16.08	peak

Emission Level= Read Level+ Correct Factor

EUT:	Interactive Touch Screen	Model:	H4 OneScreen
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Vertical		
Test Mode:	TX N(HT40) Mode 2452MHz		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4903.657	29.25	14.03	43.28	54.00	-10.72	AVG
2		4904.341	43.91	14.03	57.94	74.00	-16.06	peak

Emission Level= Read Level+ Correct Factor

6. Restricted Bands Requirement


6.1 Test Standard and Limit

- 6.1.1 Test Standard
 FCC Part 15.247(d)
 FCC Part 15.209
 FCC Part 15.205

6.1.2 Test Limit

Restricted Frequency Band (MHz)	Distance of 3m (dBuV/m)	
	Peak	Average
2310 ~2390	74	54
2483.5 ~2500	74	54

6.2 Test Setup



6.3 Test Procedure

- (1) The measuring distance of 3m shall be used for measurements at frequency up to 1GHz and above 1 GHz. The EUT was placed on a rotating 0.8m high above ground, the table was rotated 360 degrees to determine the position of the highest radiation.
- (2) Measurements at frequency above 1GHz. The EUT was placed on a rotating 1.5m high above the ground. RF absorbers covered the ground plane with a minimum area of 3.0m by 3.0m between the EUT and measurement receiver antenna. The RF absorber shall not exceed 30cm in high above the conducting floor. The table was rotated 360 degrees to determine the position of the highest radiation.

- (3) The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.
- (4) The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- (5) If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit Bellow 1 GHz, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed. But the Peak Value and average value both need to comply with applicable limit above 1 GHz.
- (6) Testing frequency range below 1GHz the measuring instrument use VBW=120 kHz with Quasi-peak detection.
- (7) Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.
- (8) For the actual test configuration, please see the test setup photo.

6.4 EUT Operating Condition


The Equipment Under Test was set to Continual Transmitting in maximum power.

6.5 Test Data

Please see the next page.

(1) Radiation Test


EUT:	Interactive Touch Screen	Model:	H4 OneScreen
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Horizontal		
Test Mode:	TX B Mode 2412MHz		
Remark:	N/A		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		2390.000	42.33	0.77	43.10	74.00	-30.90	peak
2		2390.000	31.14	0.77	31.91	54.00	-22.09	AVG
3	*	2412.800	81.37	0.86	82.23	Fundamental Frequency		AVG
4	X	2413.000	86.23	0.86	87.09	Fundamental Frequency		peak

Emission Level= Read Level+ Correct Factor


EUT:	Interactive Touch Screen	Model:	H4 OneScreen
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Vertical		
Test Mode:	TX B Mode 2412MHz		
Remark:	N/A		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		2390.000	44.57	0.77	45.34	74.00	-28.66	peak
2		2390.000	33.41	0.77	34.18	54.00	-19.82	AVG
3	*	2412.800	88.09	0.86	88.95	Fundamental Frequency		AVG
4	X	2413.100	92.77	0.86	93.63	Fundamental Frequency		peak

Emission Level= Read Level+ Correct Factor


EUT:	Interactive Touch Screen	Model:	H4 OneScreen
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Horizontal		
Test Mode:	TX B Mode 2462MHz		
Remark:	N/A		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	2462.700	80.35	1.08	81.43	Fundamental Frequency		AVG
2	X	2463.000	85.12	1.08	86.20	Fundamental Frequency		peak
3		2483.500	43.20	1.17	44.37	74.00	-29.63	peak
4		2483.500	31.21	1.17	32.38	54.00	-21.62	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Interactive Touch Screen	Model:	H4 OneScreen
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Vertical		
Test Mode:	TX B Mode 2462MHz		
Remark:	N/A		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB Detector
1	*	2462.700	92.28	1.08	93.36	Fundamental Frequency	AVG
2	X	2463.000	96.97	1.08	98.05	Fundamental Frequency	peak
3		2483.500	47.25	1.17	48.42	74.00	-25.58 peak
4		2483.500	36.67	1.17	37.84	54.00	-16.16 AVG

Emission Level= Read Level+ Correct Factor


EUT:	Interactive Touch Screen	Model:	H4 OneScreen
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Horizontal		
Test Mode:	TX G Mode 2412MHz		
Remark:	N/A		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		2390.000	42.86	0.77	43.63	74.00	-30.37	peak
2		2390.000	31.24	0.77	32.01	54.00	-21.99	AVG
3	X	2415.900	84.63	0.88	85.51	Fundamental Frequency		peak
4	*	2418.800	73.09	0.89	73.98	Fundamental Frequency		AVG

Emission Level= Read Level+ Correct Factor


EUT:	Interactive Touch Screen	Model:	H4 OneScreen
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Vertical		
Test Mode:	TX G Mode 2412MHz		
Remark:	N/A		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		2390.000	46.03	0.77	46.80	74.00	-27.20	peak
2		2390.000	34.04	0.77	34.81	54.00	-19.19	AVG
3	X	2415.900	91.00	0.88	91.88	Fundamental Frequency		peak
4	*	2418.800	79.61	0.89	80.50	Fundamental Frequency		AVG

Emission Level= Read Level+ Correct Factor


EUT:	Interactive Touch Screen	Model:	H4 OneScreen
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Horizontal		
Test Mode:	TX G Mode 2462MHz		
Remark:	N/A		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	X	2457.200	82.60	1.05	83.65	Fundamental Frequency		peak
2	*	2468.800	71.16	1.11	72.27	Fundamental Frequency		AVG
3		2483.500	45.57	1.17	46.74	74.00	-27.26	peak
4		2483.500	32.87	1.17	34.04	54.00	-19.96	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Interactive Touch Screen	Model:	H4 OneScreen
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Vertical		
Test Mode:	TX G Mode 2462MHz		
Remark:	N/A		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	X	2465.900	94.69	1.09	95.78	Fundamental Frequency		peak
2	*	2469.100	83.47	1.11	84.58	Fundamental Frequency		AVG
3		2483.500	58.35	1.17	59.52	74.00	-14.48	peak
4		2483.500	40.88	1.17	42.05	54.00	-11.95	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Interactive Touch Screen	Model:	H4 OneScreen
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Horizontal		
Test Mode:	TX N(HT20) Mode 2412MHz		
Remark:	N/A		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		2390.000	42.53	0.77	43.30	74.00	-30.70	peak
2		2390.000	31.55	0.77	32.32	54.00	-21.68	AVG
3	*	2419.000	72.58	0.89	73.47	Fundamental Frequency		AVG
4	X	2419.300	83.58	0.89	84.47	Fundamental Frequency		peak

Emission Level= Read Level+ Correct Factor


EUT:	Interactive Touch Screen	Model:	H4 OneScreen
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Vertical		
Test Mode:	TX N(HT20) Mode 2412MHz		
Remark:	N/A		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		2390.000	46.94	0.77	47.71	74.00	-26.29	peak
2		2390.000	34.42	0.77	35.19	54.00	-18.81	AVG
3	*	2419.100	78.40	0.89	79.29	Fundamental Frequency		AVG
4	X	2419.200	89.29	0.89	90.18	Fundamental Frequency		peak

Emission Level= Read Level+ Correct Factor


EUT:	Interactive Touch Screen	Model:	H4 OneScreen
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Horizontal		
Test Mode:	TX N(HT20) Mode 2462MHz		
Remark:	N/A		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	X	2469.100	81.91	1.11	83.02	Fundamental Frequency		peak
2	*	2469.900	70.74	1.11	71.85	Fundamental Frequency		AVG
3		2483.500	48.04	1.17	49.21	74.00	-24.79	peak
4		2483.500	33.76	1.17	34.93	54.00	-19.07	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Interactive Touch Screen	Model:	H4 OneScreen
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Vertical		
Test Mode:	TX N(HT20) Mode 2462MHz		
Remark:	N/A		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	X	2468.900	93.68	1.11	94.79	Fundamental Frequency		peak
2	*	2470.000	83.18	1.11	84.29	Fundamental Frequency		AVG
3		2483.500	56.54	1.17	57.71	74.00	-16.29	peak
4		2483.500	42.64	1.17	43.81	54.00	-10.19	AVG

Emission Level= Read Level+ Correct Factor


EUT:	Interactive Touch Screen	Model:	H4 OneScreen
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Horizontal		
Test Mode:	TX N(HT40) Mode 2422MHz		
Remark:	N/A		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		2390.000	45.12	0.77	45.89	74.00	-28.11	peak
2		2390.000	31.99	0.77	32.76	54.00	-21.24	AVG
3	X	2418.600	79.84	0.89	80.73	Fundamental Frequency		peak
4	*	2425.000	68.72	0.93	69.65	Fundamental Frequency		AVG

Emission Level= Read Level+ Correct Factor


EUT:	Interactive Touch Screen	Model:	H4 OneScreen
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Vertical		
Test Mode:	TX N(HT40) Mode 2422MHz		
Remark:	N/A		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		2390.000	46.99	0.77	47.76	74.00	-26.24	peak
2		2390.000	35.27	0.77	36.04	54.00	-17.96	AVG
3	X	2428.900	86.17	0.94	87.11	Fundamental Frequency		peak
4	*	2431.300	75.26	0.95	76.21	Fundamental Frequency		AVG

Emission Level= Read Level+ Correct Factor


EUT:	Interactive Touch Screen	Model:	H4 OneScreen
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Horizontal		
Test Mode:	TX N(HT40) Mode 2452MHz		
Remark:	N/A		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	2438.700	67.54	0.98	68.52	Fundamental Frequency		AVG
2	X	2438.900	78.32	0.98	79.30	Fundamental Frequency		peak
3		2483.500	47.30	1.17	48.47	74.00	-25.53	peak
4		2483.500	34.24	1.17	35.41	54.00	-18.59	AVG

Emission Level= Read Level+ Correct Factor

EUT:	Interactive Touch Screen	Model:	H4 OneScreen
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Vertical		
Test Mode:	TX N(HT40) Mode 2452MHz		
Remark:	N/A		





No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	X	2468.700	88.09	1.11	89.20	Fundamental Frequency		peak
2	*	2468.900	77.30	1.11	78.41	Fundamental Frequency		AVG
3		2483.500	55.50	1.17	56.67	74.00	-17.33	peak
4		2483.500	42.56	1.17	43.73	54.00	-10.27	AVG



Emission Level= Read Level+ Correct Factor

(2) Conducted Test



EUT:	Interactive Touch Screen	Model:	H4 OneScreen
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Test Mode:	TX B Mode 2412MHz / TX B Mode 2462MHz		
Remark:	The EUT is programed in continuously transmitting mode		





EUT:	Interactive Touch Screen	Model:	H4 OneScreen
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Test Mode:	TX G Mode 2412MHz / TX G Mode 2462MHz		
Remark:	The EUT is programed in continuously transmitting mode		



EUT:	Interactive Touch Screen	Model:	H4 OneScreen
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Test Mode:	TX N(HT20) Mode 2412MHz / TX N(HT20) Mode 2462MHz		
Remark:	The EUT is programed in continuously transmitting mode		



EUT:	Interactive Touch Screen	Model:	H4 OneScreen
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Test Mode:	TX N(HT40) Mode 2422MHz / TX N(HT40) Mode 2452MHz		
Remark:	The EUT is programed in continuously transmitting mode		



7. Bandwidth Test

7.1 Test Standard and Limit


7.1.1 Test Standard

FCC Part 15.247 (a)(2)

7.1.2 Test Limit

FCC Part 15 Subpart C(15.247)/RSS-210		
Test Item	Limit	Frequency Range(MHz)
Bandwidth	≥ 500 KHz (6dB bandwidth)	2400~2483.5

7.2 Test Setup



7.3 Test Procedure


- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) The bandwidth is measured at an amplitude level reduced 6dB from the reference level. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst -case (i.e the widest) bandwidth.
- (3) Measure the channel separation the spectrum analyzer was set to Resolution Bandwidth:100 kHz, and Video Bandwidth:300 kHz, Detector: Peak, Sweep Time set auto.

7.4 EUT Operating Condition

The EUT was set to continuously transmitting in each mode and low, Digital photo framesdle and high channel for the test.


802.11B Mode

2437 MHz



802.11B Mode

2462 MHz



EUT:	Interactive Touch Screen	Model:	H4 OneScreen
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Test Mode:	TX 802.11G Mode		
Channel frequency (MHz)	6dB Bandwidth (MHz)	99% Bandwidth (MHz)	Limit (MHz)
2412	16.480	16.4636	>=0.5
2437	16.493	16.4669	
2462	16.470	16.4739	
802.11G Mode			
2412 MHz			

Agilent

11:02:37 May 20, 2017

Ch Freq

2.412 GHz

Trig

Free

Occupied Bandwidth

Center 2.41200000 GHz

Ref 20 dBm

Atten 30 dB

#Peak

Log


10

dB/

Offst

1

dB



Center 2.412 GHz

Span 30 MHz

#Res BW 100 kHz

#VBW 300 kHz

Sweep 4 ms (401 pts)

Occupied Bandwidth

16.4636 MHz

Occ BW % Pwr

99.00 %

x dB

-6.00 dB

Transmit Freq Error

244.836 Hz

x dB Bandwidth

16.480 MHz

Freq/Channel

Center Freq

2.41200000 GHz

Start Freq

2.39700000 GHz

Stop Freq

2.42700000 GHz

CF Step

3.00000000 MHz

Auto

Man

Freq Offset

0.00000000 Hz

Signal Track

On

Off


Scale Type

Log

Lin


802.11G Mode

2437 MHz




802.11G Mode

2462 MHz




802.11N(HT20) Mode

2437 MHz



802.11N(HT20) Mode

2462 MHz



EUT:	Interactive Touch Screen	Model:	H4 OneScreen
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Test Mode:	TX 802.11N(HT40) Mode		
Channel frequency (MHz)	6dB Bandwidth (MHz)	99% Bandwidth (MHz)	Limit (MHz)
2422	35.800	35.9768	>=0.5
2437	35.668	35.9782	
2452	35.882	35.9742	
802.11N(HT40) Mode			
2422 MHz			

Agilent

11:08:05 May 20, 2017

Ch Freq

2.422 GHz

Trig

Free

Occupied Bandwidth

Center 2.42200000 GHz

Ref 20 dBm

Atten 30 dB

#Peak

Log


10

dB/

Offst

1

dB



Center 2.422 GHz

Span 60 MHz

#Res BW 100 kHz

#VBW 300 kHz

Sweep 6.216 ms (401 pts)

Occupied Bandwidth

35.9768 MHz

Transmit Freq Error

18.046 kHz

x dB Bandwidth

35.800 MHz

Occ BW % Pwr

99.00 %

x dB

-6.00 dB

Freq/Channel

Center Freq

2.42200000 GHz

Start Freq

2.39200000 GHz

Stop Freq

2.45200000 GHz

CF Step

6.00000000 MHz

Auto

Man

Freq Offset

0.00000000 Hz

Signal Track

On

Off


Scale Type

Log

Lin


802.11N(HT40) Mode

2437 MHz



802.11N(HT40) Mode

2452 MHz



8. Peak Output Power Test

8.1 Test Standard and Limit


8.1.1 Test Standard

FCC Part 15.247 (b)

8.1.2 Test Limit

FCC Part 15 Subpart C(15.247)/RSS-210		
Test Item	Limit	Frequency Range(MHz)
Peak Output Power	1 Watt or 30 dBm	2400~2483.5

8.2 Test Setup



8.3 Test Procedure

The measurement is according to section 9.1.2 of KDB 558074 D01 DTS Meas Guidance v04. The EUT was connected to RF power meter via a broadband power sensor as show the block above. The power sensor video bandwidth is greater than or equal to the DTS bandwidth of the equipment.

8.4 EUT Operating Condition


The EUT was set to continuously transmitting in the max power during the test.

8.5 Test Data


EUT:	Interactive Touch Screen	Model:	H4 OneScreen
Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Mode	Channel frequency (MHz)	Test Result (dBm)	Limit (dBm)
802.11b	2412	18.88	30
	2437	18.80	
	2462	19.16	
802.11g	2412	14.52	
	2437	15.80	
	2462	15.78	
802.11n (HT20)	2412	13.58	
	2437	14.46	
	2462	14.90	
802.11n (HT40)	2422	12.64	
	2437	12.72	
	2452	13.37	
Result: PASS			



Duty Cycle		
Mode	Channel frequency (MHz)	Test Result
802.11b	2412	>98%
	2437	
	2462	
802.11g	2412	
	2437	
	2462	
802.11n (HT20)	2412	
	2437	
	2462	
802.11n (HT40)	2422	
	2437	
	2452	
Please see below plots		

802.11 B Mode 2437 MHz



802.11 G Mode 2437 MHz





9. Power Spectral Density Test

9.1 Test Standard and Limit


9.1.1 Test Standard

FCC Part 15.247 (e)

9.1.2 Test Limit

FCC Part 15 Subpart C(15.247)		
Test Item	Limit	Frequency Range(MHz)
Power Spectral Density	8dBm(in any 3 kHz)	2400~2483.5

9.2 Test Setup



9.3 Test Procedure


The EUT was directly connected to the Spectrum Analyzer and antenna output port as show in the block diagram above. The measurement according to section 10.2 of KDB 558074 D01 DTS Meas Guidance v04.

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Set analyser center frequency to DTS channel center frequency.
- (3) Set the span to 1.5 times the DTS bandwidth.
- (4) Set the RBW to: 3 kHz
- (5) Set the VBW to: 10 kHz
- (6) Detector: peak
- (7) Sweep time: auto
- (8) Allow trace to fully stabilize. Then use the peak marker function to determine the maximum amplitude level.

9.4 EUT Operating Condition


The EUT was set to continuously transmitting in each mode and low, Digital photo framesdle and high channel for the test.

9.5 Test Data




802.11B Mode

2437 MHz




802.11B Mode

2462 MHz




802.11G Mode

2437 MHz




802.11G Mode


2462 MHz




802.11N(HT20) Mode
2437 MHz




802.11N(HT20) Mode
2462 MHz






802.11N(HT40) Mode

2437 MHz



802.11N(HT40) Mode

2452 MHz



10. Antenna Requirement

10.1 Standard Requirement

10.1.1 Standard

FCC Part 15.203

10.1.2 Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

10.2 Antenna Connected Construction

The directional gains of the antenna used for transmitting is 5 dBi, and the antenna de-signed with permanent attachment and no consideration of replacement. Please see the EUT photo for details.

Result

The EUT antenna is a FPC Antenna. It complies with the standard requirement.

Antenna Type
☐ Permanent attached antenna
☒ Unique connector antenna
☐ Professional installation antenna

-----END OF REPORT-----