

## Kenxen Digitech Limited

Application  
For  
Certification

**FCC ID: 2AL8TSDV360T3**

**360° Camera**

**Models: SDV360T3, SDV360T5, SDV360T6**

**Brand name: Kenxen**

**2.4GHz WiFi Transceiver**

**Report No.: 170612165GZU-001**


We hereby certify that the sample of the above item is considered to comply with the requirements of FCC Part 15, Subpart C for Intentional Radiator, mention 47 CFR [10-1-15]

Prepared and Checked by:

Approved by:

Sign on file

Harry Wu  
Project Engineer

 Digitally signed  
by Kidd Yang  
Location:  
Intertek Testing  
Services

---

Kidd Yang  
Senior Project Engineer  
Date: June 12, 2017

- The test results reported in this test report shall refer only to the sample actually tested and shall not refer or be deemed to refer to bulk from which such a sample may be said to have been obtained.
- This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to copy or distribute this report. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results referenced from this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.
- For Terms And Conditions of the services, it can be provided upon request.
- The evaluation data of the report will be kept for 3 years from the date of issuance.

TRF no.: FCC 15C\_Tx\_c

## LIST OF EXHIBITS

### *INTRODUCTION*

|                    |                           |
|--------------------|---------------------------|
| <i>EXHIBIT 1:</i>  | Summary of Tests          |
| <i>EXHIBIT 2:</i>  | General Description       |
| <i>EXHIBIT 3:</i>  | System Test Configuration |
| <i>EXHIBIT 4:</i>  | Measurement Results       |
| <i>EXHIBIT 5:</i>  | Equipment Photographs     |
| <i>EXHIBIT 6:</i>  | Product Labeling          |
| <i>EXHIBIT 7:</i>  | Technical Specifications  |
| <i>EXHIBIT 8:</i>  | Instruction Manual        |
| <i>EXHIBIT 9:</i>  | Confidentiality Request   |
| <i>EXHIBIT 10:</i> | Miscellaneous Information |
| <i>EXHIBIT 11:</i> | Test Equipment List       |

---

## INTERTEK TESTING SERVICES

---

### MEASUREMENT/TECHNICAL REPORT

#### 360° Camera

**Model: SDV360T3, SDV360T5, SDV360T6**

**FCC ID: 2AL8TSDV360T3**

This report concerns (check one)    Original Grant ☒ Class II Change ☐

Equipment Type: DTS - Part 15 Digital Transmission Systems (WiFi transmitter portion)

Deferred grant requested per 47 CFR 0.457(d)(1)(ii)?    Yes ☐ No ☒

If yes, defer until :   
date

Company Name agrees to notify the Commission by:   
date

of the intended date of announcement of the product so that the grant can be issued on that date.

Transition Rules Request per 15.37?    Yes ☐ No ☒

If no, assumed Part 15, Subpart C for intentional radiator - the new 47 CFR [10-01-15] Edition] provision.

Report prepared by:

Harry Wu  
Intertek Testing Services Shenzhen Ltd. Guangzhou Branch  
Block E, No.7-2 Guang Dong Software Science Park,  
Caipin Road, Guangzhou Science City, GETDD  
Guangzhou, China  
Tel / Fax: 86-20-8213 9688/86-20-3205 7538

# INTERTEK TESTING SERVICES

---

## Table of Contents

|      |                                                              |    |
|------|--------------------------------------------------------------|----|
| 1.0  | <b><u>Summary of Test results</u></b> .....                  | 6  |
| 2.0  | <b><u>General Description</u></b> .....                      | 8  |
| 2.1  | Product Description .....                                    | 8  |
| 2.2  | Related Submittal(s) Grants .....                            | 8  |
| 2.3  | Test Methodology .....                                       | 9  |
| 2.4  | Test Facility .....                                          | 9  |
| 3.0  | <b><u>System Test Configuration</u></b> .....                | 11 |
| 3.1  | Justification .....                                          | 11 |
| 3.2  | EUT Exercising Software .....                                | 11 |
| 3.3  | Special Accessories .....                                    | 12 |
| 3.4  | Measurement Uncertainty .....                                | 12 |
| 3.5  | Equipment Modification .....                                 | 12 |
| 3.6  | Support Equipment List and Description .....                 | 12 |
| 4.0  | <b><u>Measurement Results</u></b> .....                      | 14 |
| 4.1  | Maximum Conducted Output Power at Antenna Terminals .....    | 14 |
| 4.2  | Minimum 6 dB RF Bandwidth .....                              | 16 |
| 4.3  | Maximum Power Density Reading .....                          | 24 |
| 4.4  | Out of Band Conducted Emissions .....                        | 31 |
| 4.5  | Out of Band Radiated Emissions .....                         | 49 |
| 4.6  | Transmitter Radiated Emissions in Restricted Bands .....     | 50 |
| 4.7  | Field Strength Calculation .....                             | 51 |
| 4.8  | Radiated Spurious Emission .....                             | 52 |
| 4.9  | Conducted Emission .....                                     | 66 |
| 4.10 | Radiated Emissions from Digital Section of Transceiver ..... | 69 |
| 4.11 | Transmitter Duty Cycle Calculation and Measurements .....    | 70 |
| 5.0  | <b><u>Equipment Photographs</u></b> .....                    | 72 |
| 6.0  | <b><u>Product Labelling</u></b> .....                        | 74 |
| 7.0  | <b><u>Technical Specifications</u></b> .....                 | 76 |
| 8.0  | <b><u>Instruction Manual</u></b> .....                       | 78 |
| 9.0  | <b><u>Confidentiality Request</u></b> .....                  | 80 |
| 10.0 | <b><u>Discussion of Pulse Desensitization</u></b> .....      | 82 |
| 11.0 | <b><u>Test Equipment List</u></b> .....                      | 84 |

---

## INTERTEK TESTING SERVICES

---

### List of attached file

| Exhibit type          | File Description           | Filename             |
|-----------------------|----------------------------|----------------------|
| Test Report           | Test Report                | report.pdf           |
| Test Setup Photo      | Radiated Emission          | radiated photos.pdf  |
| Test Setup Photo      | Conducted Emission         | conducted photos.pdf |
| External Photo        | External Photo             | external photos.pdf  |
| Internal Photo        | Internal Photo             | internal photos.pdf  |
| Block Diagram         | Block Diagram              | block.pdf            |
| Schematics            | Circuit Diagram            | circuit.pdf          |
| Operation Description | Technical Description      | descri.pdf           |
| ID Label/Location     | Label Artwork and Location | label.pdf            |
| User Manual           | User Manual                | manual.pdf           |
| Cover Letter          | Confidentiality Letter     | request.pdf          |
| Cover Letter          | Letter of Agency           | agency.pdf           |

## **INTERTEK TESTING SERVICES**

---

### **EXHIBIT 1**

### **SUMMARY OF TEST RESULTS**

---

## INTERTEK TESTING SERVICES

---

### 1.0 Summary of Test results

#### **360° Camera**

**Model: SDV360T3, SDV360T5, SDV360T6**

**FCC ID: 2AL8TSDV360T3**

| TEST                                   | REFERENCE    | RESULTS          |
|----------------------------------------|--------------|------------------|
| Max. Output power                      | 15.247(b)(3) | Pass             |
| 6 dB Bandwidth                         | 15.247(a)(2) | Pass             |
| Max. Power Density                     | 15.247(e)    | Pass             |
| Out of Band Antenna Conducted Emission | 15.247(d)    | Pass             |
| Radiated Emission in Restricted Bands  | 15.247(d)    | Pass             |
| AC Conducted Emission                  | 15.207       | Pass             |
| Antenna Requirement                    | 15.203       | Pass (See Notes) |

Notes: The EUT uses an Integral Antenna which in accordance to Section 15.203 is considered sufficient to comply with the provisions of this section.

## **INTERTEK TESTING SERVICES**

---

### **EXHIBIT 2**

#### **GENERAL DESCRIPTION**

## INTERTEK TESTING SERVICES

---

### 2.0 General Description

#### 2.1 Product Description

The Equipment Under Test (EUT) is a 360° Camera with WiFi function operating at 2412-2462MHz for 802.11b/g/n-HT20, 11 channels with 5MHz channel spacing and 2422-2452MHz for 802.11n-HT40, 7 channels with 5MHz channel spacing. The EUT was powered by DC 3.7V internal rechargeable battery which can be charged by USB port (DC 5V). For more detailed features description, please refer to the user's manual.

Type of Modulation: BPSK, QPSK, 16QAM, 64QAM, CCK, DQPSK, DBPSK.

Antenna Type: Integral Antenna.

The Models: SDV360T5, SDV360T6 are the same as the Model: SDV360T3 in hardware aspect. The difference in model number serves as marketing strategy.

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

#### 2.2 Related Submittal(s) Grants

This is an application for certification of:

DTS- Part 15 Digital Transmission Systems (2.4GHz WiFi transmitter portion). The data transfer function which subjected to FCC DOC.

## INTERTEK TESTING SERVICES

---

### 2.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.10 (2013) and KDB 558074 D01 V04. Radiated emission measurement was performed in semi-anechoic chamber. Preliminary scans were performed in the semi-anechoic chamber only to determine the worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "Justification Section" of this Application.

### 2.4 Test Facility

The Semi-Anechoic chamber and shield room used to collect the radiated data and conducted data are **EMTEK (Shenzhen) Co., Ltd.** and located at Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052, China. This test facility and site measurement data have been fully placed on file with File Number: 4480A.

**EXHIBIT 3**  
**SYSTEM TEST CONFIGURATION**

## INTERTEK TESTING SERVICES

---

### 3.0 System Test Configuration

#### 3.1 Justification

For emissions testing, the equipment under test (EUT) setup to transmit continuously to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing. During testing, all cables were manipulated to produce worst case emissions. The EUT was powered by a fully-charged DC 3.7V new rechargeable battery which can be charged by an AC/DC adaptor with input of AC 120V, 60Hz. Only the worst case data was reported.

On 802.11b, g, n (20MHz, 40MHz) mode, only one antenna is used, and all data rate were tested and only the worst case data is shown in the report.

For maximizing emissions, the EUT was rotated through 360°, the EUT was placed on the styrene turntable with 0.8m up to 1GHz and 1.5 m above 1GHz. The antenna height and polarization are varied during the search for maximum signal level. The antenna height is varied from 1 to 4 meters. Radiated emissions are taken at three meters unless the signal level is too low for measurement at that distance. If necessary, a pre-amplifier is used and/or the test is conducted at a closer distance.

The EUT placed in the rear of turntable for Radiated Emission test.

All readings are extrapolated back to the equivalent three meter reading using inverse scaling with distance. Analyzer resolution is 100 kHz or greater for frequencies below 1000 MHz. The resolution is 1 MHz or greater for frequencies above 1000 MHz. The spurious emissions more than 20 dB below the permissible value are not reported.

Radiated emission measurement were performed the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

#### 3.2 EUT Exercising Software

The EUT exercise program (provided by client) used during radiated and conducted testing was designed to exercise the various system components in a manner similar to a typical use. The worst case configuration is used in all specified testing.

The parameters of test software setting:

During the test, Channel and power controlling software provided by the applicant was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the application and is going to be fixed on the firmware of the end product.

## INTERTEK TESTING SERVICES

---

### 3.3 Special Accessories

N/A.

### 3.4 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

Uncertainty and Compliance – Unless the standard specifically states that measured values are to be extended by the measurement uncertainty in determining compliance, all compliance determinations are based on the actual measured value.

### 3.5 Equipment Modification

Any modifications installed previous to testing by Kenxen Digitech Limited will be incorporated in each production model sold / leased in the United States.

No modifications were installed by Intertek Testing Services Shenzhen Ltd. Guangzhou Branch.

### 3.6 Support Equipment List and Description

This product was tested in the following configuration:

Refer List:

| Description   | Manufacturer | Detail                                                                |
|---------------|--------------|-----------------------------------------------------------------------|
| Tablet PC     | Samsung      | SM-T700                                                               |
| Mini SD Card  | SanDisk      | 1GB                                                                   |
| USB Cable     | N/A          | Unshielded, 100cm                                                     |
| AC/DC adaptor | TP-Link      | T050100-2A3 (Input: AC 100-240V, 50/60Hz, 0.3A Output: DC 5.0V, 1.0A) |

## **INTERTEK TESTING SERVICES**

---

### **EXHIBIT 4**

### **MEASUREMENT RESULTS**

## INTERTEK TESTING SERVICES

Applicant: Kenxen Digitech Limited

Date of Test: 16 May 2017

Model: SDV360T3

### 4.0 Measurement Results

#### 4.1 Maximum Conducted Output Power at Antenna Terminals, FCC Rules 15.247(b)(3):

The antenna power of the EUT was connected to the input of a broadband peak RF power meter. The power meter have a video bandwidth that is greater than DTS bandwidth and utilize a fast-responding diode detector. Power was read directly at the EUT antenna terminals with cable loss added.

For antennas with gains of 6 dBi or less, maximum allowed Transmitter output is 1 watt (+30 dBm).

| IEEE 802.11b (Antenna Gain = 0dBi) (CCK, 1Mbps) |               |                 |
|-------------------------------------------------|---------------|-----------------|
| Frequency (MHz)                                 | Output in dBm | Output in mWatt |
| Low Channel: 2412                               | 8.3           | 6.8             |
| Middle Channel: 2437                            | 8.8           | 7.6             |
| High Channel: 2462                              | 8.9           | 7.8             |

| IEEE 802.11g (Antenna Gain = 0dBi) (16QAM, 6Mbps) |               |                 |
|---------------------------------------------------|---------------|-----------------|
| Frequency (MHz)                                   | Output in dBm | Output in mWatt |
| Low Channel: 2412                                 | 8.2           | 6.6             |
| Middle Channel: 2437                              | 9.0           | 7.9             |
| High Channel: 2462                                | 8.9           | 7.8             |

| IEEE 802.11n-HT20 (Antenna Gain = 0dBi) (16QAM, 6.5Mbps) |               |                 |
|----------------------------------------------------------|---------------|-----------------|
| Frequency (MHz)                                          | Output in dBm | Output in mWatt |
| Low Channel: 2412                                        | 8.7           | 7.4             |
| Middle Channel: 2437                                     | 9.2           | 8.3             |
| High Channel: 2462                                       | 9.0           | 7.9             |

## INTERTEK TESTING SERVICES

---

| IEEE 802.11n-HT40 (Antenna Gain = 0dBi) (64QAM, 13.5Mbps) |               |                 |
|-----------------------------------------------------------|---------------|-----------------|
| Frequency (MHz)                                           | Output in dBm | Output in mWatt |
| Low Channel: 2422                                         | 8.7           | 7.4             |
| Middle Channel: 2437                                      | 8.8           | 7.6             |
| High Channel: 2452                                        | 8.6           | 7.2             |

Cable loss: 0.5 dB    External Attenuation: 0 dB

Cable loss, external attenuation has been included in OFFSET function

EUT max. output level = 9.2dBm

## INTERTEK TESTING SERVICES

Applicant: Kenxen Digitech Limited

Date of Test: 16 May 2017

Model: SDV360T3

### 4.2 Minimum 6 dB RF Bandwidth, FCC Rule 15.247(a)(2):

The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer RES BW was set to 100 KHz according to FCC KDB 558074 D01 v04. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. A PEAK output reading was taken, a DISPLAY line was drawn 6 dB lower than PEAK level. The 6dB bandwidth was determined from where the channel output spectrum intersected the display line.

Limit: The 6 dB Bandwidth is at least 500 kHz.

| IEEE 802.11b (CCK, 1Mbps) |                      |
|---------------------------|----------------------|
| Frequency (MHz)           | 6 dB Bandwidth (MHz) |
| 2412                      | 10.072               |
| 2437                      | 10.029               |
| 2462                      | 10.020               |

| IEEE 802.11g (16QAM, 6Mbps) |                      |
|-----------------------------|----------------------|
| Frequency (MHz)             | 6 dB Bandwidth (MHz) |
| 2412                        | 16.389               |
| 2437                        | 16.281               |
| 2462                        | 16.281               |


| IEEE 802.11n-HT20 (16QAM, 6.5Mbps) |                      |
|------------------------------------|----------------------|
| Frequency (MHz)                    | 6 dB Bandwidth (MHz) |
| 2412                               | 17.540               |
| 2437                               | 17.583               |
| 2462                               | 17.323               |

## INTERTEK TESTING SERVICES



| IEEE 802.11n-HT40 (64QAM, 13.5Mbps) |                      |
|-------------------------------------|----------------------|
| Frequency (MHz)                     | 6 dB Bandwidth (MHz) |
| 2422                                | 35.080               |
| 2437                                | 35.080               |
| 2452                                | 35.427               |

The test plots are attached as below.

802.11b





# INTERTEK TESTING SERVICES




# INTERTEK TESTING SERVICES

802.11g




TRF no.: FCC 15C\_TX\_c  
 FCC ID: 2A8TSDV360T3

# INTERTEK TESTING SERVICES





802.11n-HT20





TRF no.: FCC 15C\_TX\_c  
FCC ID: 2AL8TSDV360T3

# INTERTEK TESTING SERVICES




# INTERTEK TESTING SERVICES

802.11n-HT40



# INTERTEK TESTING SERVICES



## INTERTEK TESTING SERVICES

Applicant: Kenxen Digitech Limited

Date of Test: 16 May 2017

Model: SDV360T3

### 4.3 Maximum Power Density Reading, FCC Rule 15.247(e):

The Measurement Procedure PKPSD was set according to the FCC KDB 558074 D01 v04.

Antenna output of the EUT was coupled directly to spectrum analyzer; if an external attenuator and/or cable was used, these losses are compensated for with the analyzer OFFSET function.

Limit: The Power Density does not exceed 8dBm/3 kHz.

| IEEE 802.11b (CCK, 1Mbps) |                     |
|---------------------------|---------------------|
| Frequency (MHz)           | Power Density (dBm) |
| 2412                      | -1.50               |
| 2437                      | -1.65               |
| 2462                      | -1.35               |

| IEEE 802.11g (16QAM, 6Mbps) |                                     |
|-----------------------------|-------------------------------------|
| Frequency (MHz)             | Power Density with RBW 100KHz (dBm) |
| 2412                        | -4.43                               |
| 2437                        | -3.83                               |
| 2462                        | -3.92                               |



| IEEE 802.11n-HT20 (16QAM, 6.5Mbps) |                                     |
|------------------------------------|-------------------------------------|
| Frequency (MHz)                    | Power Density with RBW 100KHz (dBm) |
| 2412                               | -3.87                               |
| 2437                               | -3.95                               |
| 2462                               | -3.88                               |

| IEEE 802.11n-HT20 (64QAM, 13.5Mbps) |                                     |
|-------------------------------------|-------------------------------------|
| Frequency (MHz)                     | Power Density with RBW 100KHz (dBm) |
| 2422                                | -5.60                               |
| 2437                                | -5.70                               |
| 2452                                | -5.43                               |

The test plots are attached as below.


## INTERTEK TESTING SERVICES

802.11b




TRF no.: FCC 15C\_TX\_c  
FCC ID: 2AL8TSDV360T3



## INTERTEK TESTING SERVICES



802.11g





## INTERTEK TESTING SERVICES




## INTERTEK TESTING SERVICES

802.11n-HT20




TRF no.: FCC 15C\_TX\_c  
FCC ID: 2A18TSDV360T3

## INTERTEK TESTING SERVICES





802.11n-HT40



TRF no.: FCC 15C\_TX\_c  
FCC ID: 2A8TSDV360T3

## INTERTEK TESTING SERVICES



## INTERTEK TESTING SERVICES

---

Applicant: Kenxen Digitech Limited  
Date of Test: 16 May 2017  
Model: SDV360T3

### 4.4 Out of Band Conducted Emissions, FCC Rule 15.247(d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. The Measurement Procedure was set according to the FCC KDB 558074 D01 v04.

All other types of emissions from the EUT shall meet the general limits for radiated frequencies outside the passband.

Refer to the attached test plots for out of band conducted emissions data with rate of 1Mbps for 802.11b, 6Mbps for 802.11g and 6.5Mbps for 802.11n-HT20 and 13.5Mbps for 802.11n-HT40.



The test plots showed all spurious emission up to the tenth harmonic were measured and they were found to be at least 20 dB below the highest level of the desired power in the passband.

The test plots are attached as below.


## INTERTEK TESTING SERVICES

802.11b


Channel 01 (2412MHz) Reference Level: -1.5dBm




## INTERTEK TESTING SERVICES




Channel 06 (2437MHz) Reference Level: -1.65dBm





## INTERTEK TESTING SERVICES



Channel 11 (2462MHz) Reference Level: -1.35dBm





# INTERTEK TESTING SERVICES




## INTERTEK TESTING SERVICES

802.11g


Channel 01 (2412MHz) Reference Level: -4.43dBm




# INTERTEK TESTING SERVICES




Channel 06 (2437MHz) Reference Level: -3.83dBm





## INTERTEK TESTING SERVICES



Channel 11 (2462MHz) Reference Level: -3.92dBm





# INTERTEK TESTING SERVICES




## INTERTEK TESTING SERVICES

802.11n-HT20

Channel 01 (2412MHz) Reference Level: -3.87dBm





## INTERTEK TESTING SERVICES





## INTERTEK TESTING SERVICES

Channel 06 (2437MHz) Reference Level: -3.95dBm




## INTERTEK TESTING SERVICES

Channel 11 (2462MHz) Reference Level: -3.88dBm




## INTERTEK TESTING SERVICES





802.11n-HT40

Channel 01 (2422MHz) Reference Level: -5.60dBm





TRF no.: FCC 15C\_TX\_c  
 FCC ID: 2A8TSDV360T3

# INTERTEK TESTING SERVICES





## INTERTEK TESTING SERVICES

Channel 06 (2437MHz) Reference Level: -5.70dBm




## INTERTEK TESTING SERVICES

Channel 9 (2452MHz) Reference Level: -5.43dBm



## INTERTEK TESTING SERVICES



## INTERTEK TESTING SERVICES

---

Applicant: Kenxen Digitech Limited

Date of Test: 16 May 2017

Model: SDV360T3

### 4.5 Out of Band Radiated Emissions (for emissions in 4.4 above that are less than 20dB below carrier), FCC Rule 15.247(d):

For out of band emissions that are close to or that exceed the 20dB attenuation requirement described in the specification, radiated measurements were performed at a 3m separation distance to determine whether these emissions complied with the general radiated emission requirement.

☒ Not required, since all emissions are more than 20dB below fundamental

☐ See attached data sheet

## INTERTEK TESTING SERVICES

---

Applicant: Kenxen Digitech Limited

Date of Test: 16 May 2017

Model: SDV360T3

### 4.6 Transmitter Radiated Emissions in Restricted Bands, FCC Rule 15.35(b), (c):

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included. All measurements were performed with peak detection unless otherwise specified.

The data on the following pages list the significant emission frequencies, the limit and the margin of compliance.

## INTERTEK TESTING SERVICES

---

Applicant: Kenxen Digitech Limited

Date of Test: 16 May 2017

Model: SDV360T3

### 4.7 Field Strength Calculation

The field strength is calculated by adding the reading on the Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables, pulse desensitization and average factors (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below.

$$FS = RA + AF + CF - AG + PD$$

Where

- FS = Field Strength in dB $\mu$ V/m
- RA = Receiver Amplitude (including preamplifier) in dB $\mu$ V
- CF = Cable Attenuation Factor in dB
- AF = Antenna Factor in dB
- AG = Amplifier Gain in dB
- PD = Pulse Desensitization in dB

In the radiated emission table which follows, the reading shown on the data table may reflect the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows:

$$FS = RA + AF + CF - AG + PD$$

#### Example

Assume a receiver reading of 62.0 dB $\mu$ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted. The pulse desensitization factor of the spectrum analyzer was 0 dB. The net field strength for comparison to the appropriate emission limit is 42 dB $\mu$ V/m. This value in dB $\mu$ V/m was converted to its corresponding level in  $\mu$ V/m.

$$RA = 62.0 \text{ dB}\mu\text{V}$$

$$AF = 7.4 \text{ dB}$$

$$CF = 1.6 \text{ dB}$$

$$AG = 29.0 \text{ dB}$$

$$PD = 0 \text{ dB}$$

$$FS = 62 + 7.4 + 1.6 - 29 + 0 = 42 \text{ dB}\mu\text{V/m}$$

$$\text{Level in mV/m} = \text{Common Antilogarithm} [(42 \text{ dB}\mu\text{V/m})/20] = 125.9 \mu\text{V/m}$$

## INTERTEK TESTING SERVICES

---

Applicant: Kenxen Digitech Limited  
Date of Test: 16 May 2017  
Model: SDV360T3

### 4.8 Radiated Spurious Emission

Worst Case Radiated Spurious Emission 802.11n-HT20 (TX-Channel 01) at 557.162MHz is passed by 6.2dB margin.

For the electronic filing, the worst case radiated emission configuration photographs are saved with filename: radiated photos.pdf.

## INTERTEK TESTING SERVICES

Applicant: Kenxen Digitech Limited

Date of Test: 16 May 2017

Model: SDV360T3

Worst Case Operating Mode: 802.11n-HT20 (TX-Channel 01)

### Radiated Emissions

| Polarization | Frequency (MHz) | Reading (dBμV) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Net at 3m (dBμV/m) | Limit at 3m (dBμV/m) | Margin (dB) |
|--------------|-----------------|----------------|-------------------|---------------------|--------------------|----------------------|-------------|
| Horizontal   | 222.545         | 31.9           | 20.0              | 18.5                | 30.4               | 46.0                 | -15.6       |
| Horizontal   | 519.850         | 35.8           | 20.0              | 21.4                | 37.2               | 46.0                 | -8.8        |
| Horizontal   | 557.162         | 38.0           | 20.0              | 21.8                | 39.8               | 46.0                 | -6.2        |
| Vertical     | 74.251          | 43.6           | 20.0              | 8.3                 | 31.9               | 40.0                 | -8.1        |
| Vertical     | 222.785         | 36.7           | 20.0              | 12.6                | 29.3               | 46.0                 | -16.7       |
| Vertical     | 556.717         | 36.0           | 20.0              | 21.8                | 37.8               | 46.0                 | -8.2        |

- NOTES:
1. Quasi-Peak detector is used for frequency below 1GHz.
  2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
  3. Negative value in the margin column shows emission below limit.

## INTERTEK TESTING SERVICES

Applicant: Kenxen Digitech Limited

Date of Test: 16 May 2017

Model: SDV360T3

Worst Case Operating Mode: 802.11b (TX-Channel 01)

### Radiated Emissions

| Polarization | Frequency (MHz) | Reading (dBμV) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Net at 3m (dBμV/m) | Peak Limit at 3m (dBμV/m) | Margin (dB) |
|--------------|-----------------|----------------|-------------------|---------------------|--------------------|---------------------------|-------------|
| Horizontal   | *4824.000       | 51.9           | 36.1              | 34.2                | 50.0               | 74.0                      | -24.0       |
| Horizontal   | *2385.030       | 60.5           | 36.7              | 28.4                | 52.2               | 74.0                      | -21.8       |

| Polarization | Frequency (MHz) | Reading (dBμV) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Net at 3m (dBμV/m) | Average Limit at 3m (dBμV/m) | Margin (dB) |
|--------------|-----------------|----------------|-------------------|---------------------|--------------------|------------------------------|-------------|
| Horizontal   | *4824.000       | 38.0           | 36.1              | 34.2                | 36.1               | 54.0                         | -17.9       |
| Horizontal   | *2385.030       | 46.2           | 36.7              | 28.4                | 37.9               | 54.0                         | -16.1       |

- NOTES:
1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
  2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
  3. Negative value in the margin column shows emission below limit.
  4. Horn antenna used for the emission over 1000MHz.
- \* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

## INTERTEK TESTING SERVICES

Applicant: Kenxen Digitech Limited

Date of Test: 16 May 2017

Model: SDV360T3

Worst Case Operating Mode: 802.11b (TX-Channel 06)

### Radiated Emissions

| Polarization | Frequency (MHz) | Reading (dBμV) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Net at 3m (dBμV/m) | Peak Limit at 3m (dBμV/m) | Margin (dB) |
|--------------|-----------------|----------------|-------------------|---------------------|--------------------|---------------------------|-------------|
| Horizontal   | *4874.000       | 51.6           | 36.1              | 34.6                | 50.1               | 74.0                      | -23.9       |
| Horizontal   | *7311.000       | 54.7           | 35.6              | 37.1                | 56.2               | 74.0                      | -17.8       |

| Polarization | Frequency (MHz) | Reading (dBμV) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Net at 3m (dBμV/m) | Average Limit at 3m (dBμV/m) | Margin (dB) |
|--------------|-----------------|----------------|-------------------|---------------------|--------------------|------------------------------|-------------|
| Horizontal   | *4874.000       | 38.1           | 36.1              | 34.6                | 36.6               | 54.0                         | -17.4       |
| Horizontal   | *7311.000       | 39.0           | 35.6              | 37.1                | 40.5               | 54.0                         | -13.5       |

- NOTES: 1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.
- \* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

## INTERTEK TESTING SERVICES

Applicant: Kenxen Digitech Limited

Date of Test: 16 May 2017

Model: SDV360T3

Worst Case Operating Mode: 802.11b (TX-Channel 11)

### Radiated Emissions

| Polarization | Frequency (MHz) | Reading (dBμV) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Net at 3m (dBμV/m) | Peak Limit at 3m (dBμV/m) | Margin (dB) |
|--------------|-----------------|----------------|-------------------|---------------------|--------------------|---------------------------|-------------|
| Horizontal   | *4924.000       | 52.7           | 36.1              | 34.6                | 51.2               | 74.0                      | -22.8       |
| Horizontal   | *7386.000       | 52.9           | 35.6              | 37.2                | 54.5               | 74.0                      | -19.5       |
| Horizontal   | *2484.460       | 61.4           | 36.7              | 28.1                | 52.8               | 74.0                      | -21.2       |

| Polarization | Frequency (MHz) | Reading (dBμV) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Net at 3m (dBμV/m) | Average Limit at 3m (dBμV/m) | Margin (dB) |
|--------------|-----------------|----------------|-------------------|---------------------|--------------------|------------------------------|-------------|
| Horizontal   | *4924.000       | 37.7           | 36.1              | 34.6                | 36.2               | 54.0                         | -17.8       |
| Horizontal   | *7386.000       | 38.7           | 35.6              | 37.2                | 40.3               | 54.0                         | -13.7       |
| Horizontal   | *2484.460       | 48.1           | 36.7              | 28.1                | 39.5               | 54.0                         | -14.5       |

- NOTES: 1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.
- \* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

## INTERTEK TESTING SERVICES

Applicant: Kenxen Digitech Limited

Date of Test: 16 May 2017

Model: SDV360T3

Worst Case Operating Mode: 802.11g (TX-Channel 01)

### Radiated Emissions

| Polarization | Frequency (MHz) | Reading (dBμV) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Net at 3m (dBμV/m) | Peak Limit at 3m (dBμV/m) | Margin (dB) |
|--------------|-----------------|----------------|-------------------|---------------------|--------------------|---------------------------|-------------|
| Horizontal   | *4824.000       | 52.4           | 36.1              | 34.2                | 50.5               | 74.0                      | -23.5       |
| Horizontal   | *2380.000       | 47.9           | 36.7              | 28.8                | 40.0               | 74.0                      | -34.0       |

| Polarization | Frequency (MHz) | Reading (dBμV) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Net at 3m (dBμV/m) | Average Limit at 3m (dBμV/m) | Margin (dB) |
|--------------|-----------------|----------------|-------------------|---------------------|--------------------|------------------------------|-------------|
| Horizontal   | *4824.000       | 39.2           | 36.1              | 34.2                | 37.3               | 54.0                         | -16.7       |
| Horizontal   | *2380.000       | 46.5           | 36.7              | 28.8                | 38.6               | 54.0                         | -15.4       |

- NOTES:
1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
  2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
  3. Negative value in the margin column shows emission below limit.
  4. Horn antenna used for the emission over 1000MHz.
- \* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

## INTERTEK TESTING SERVICES

Applicant: Kenxen Digitech Limited

Date of Test: 16 May 2017

Model: SDV360T3

Worst Case Operating Mode: 802.11g (TX-Channel 06)

### Radiated Emissions

| Polarization | Frequency (MHz) | Reading (dBμV) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Net at 3m (dBμV/m) | Peak Limit at 3m (dBμV/m) | Margin (dB) |
|--------------|-----------------|----------------|-------------------|---------------------|--------------------|---------------------------|-------------|
| Horizontal   | *4874.000       | 51.9           | 36.1              | 34.6                | 50.4               | 74.0                      | -23.6       |
| Horizontal   | *7311.000       | 55.6           | 35.6              | 37.1                | 57.1               | 74.0                      | -16.9       |

| Polarization | Frequency (MHz) | Reading (dBμV) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Net at 3m (dBμV/m) | Average Limit at 3m (dBμV/m) | Margin (dB) |
|--------------|-----------------|----------------|-------------------|---------------------|--------------------|------------------------------|-------------|
| Horizontal   | *4874.000       | 38.3           | 36.1              | 34.6                | 36.8               | 54.0                         | -17.2       |
| Horizontal   | *7311.000       | 41.1           | 35.6              | 37.1                | 42.6               | 54.0                         | -11.4       |

- NOTES:
1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
  2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
  3. Negative value in the margin column shows emission below limit.
  4. Horn antenna used for the emission over 1000MHz.
- \* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

## INTERTEK TESTING SERVICES

Applicant: Kenxen Digitech Limited

Date of Test: 16 May 2017

Model: SDV360T3

Worst Case Operating Mode: 802.11g (TX-Channel 11)

### Radiated Emissions

| Polarization | Frequency (MHz) | Reading (dBμV) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Net at 3m (dBμV/m) | Peak Limit at 3m (dBμV/m) | Margin (dB) |
|--------------|-----------------|----------------|-------------------|---------------------|--------------------|---------------------------|-------------|
| Horizontal   | *4924.000       | 51.9           | 36.1              | 34.6                | 50.4               | 74.0                      | -23.6       |
| Horizontal   | *7386.000       | 54.8           | 35.6              | 37.2                | 56.4               | 74.0                      | -17.6       |
| Horizontal   | *2484.460       | 61.0           | 36.7              | 28.0                | 52.3               | 74.0                      | -21.7       |

| Polarization | Frequency (MHz) | Reading (dBμV) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Net at 3m (dBμV/m) | Average Limit at 3m (dBμV/m) | Margin (dB) |
|--------------|-----------------|----------------|-------------------|---------------------|--------------------|------------------------------|-------------|
| Horizontal   | *4924.000       | 38.4           | 36.1              | 34.6                | 36.9               | 54.0                         | -17.1       |
| Horizontal   | *7386.000       | 41.5           | 35.6              | 37.2                | 43.1               | 54.0                         | -10.9       |
| Horizontal   | *2484.460       | 50.4           | 36.7              | 28.0                | 41.7               | 54.0                         | -12.3       |

- NOTES: 1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.
- \* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

## INTERTEK TESTING SERVICES

Applicant: Kenxen Digitech Limited

Date of Test: 16 May 2017

Model: SDV360T3

Worst Case Operating Mode: 802.11n-HT20 (TX-Channel 01)

### Radiated Emissions

| Polarization | Frequency (MHz) | Reading (dBμV) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Net at 3m (dBμV/m) | Peak Limit at 3m (dBμV/m) | Margin (dB) |
|--------------|-----------------|----------------|-------------------|---------------------|--------------------|---------------------------|-------------|
| Horizontal   | *4824.000       | 52.4           | 36.1              | 34.2                | 50.5               | 74.0                      | -23.5       |
| Horizontal   | *2389.850       | 58.2           | 36.7              | 28.7                | 50.2               | 74.0                      | -23.8       |

| Polarization | Frequency (MHz) | Reading (dBμV) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Net at 3m (dBμV/m) | Average Limit at 3m (dBμV/m) | Margin (dB) |
|--------------|-----------------|----------------|-------------------|---------------------|--------------------|------------------------------|-------------|
| Horizontal   | *4824.000       | 39.0           | 36.1              | 34.2                | 37.1               | 54.0                         | -16.9       |
| Horizontal   | *2389.850       | 47.8           | 36.7              | 28.7                | 39.8               | 54.0                         | -14.2       |

- NOTES: 1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.
- \* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

## INTERTEK TESTING SERVICES

Applicant: Kenxen Digitech Limited

Date of Test: 16 May 2017

Model: SDV360T3

Worst Case Operating Mode: 802.11n-HT20 (TX-Channel 06)

### Radiated Emissions

| Polarization | Frequency (MHz) | Reading (dBμV) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Net at 3m (dBμV/m) | Peak Limit at 3m (dBμV/m) | Margin (dB) |
|--------------|-----------------|----------------|-------------------|---------------------|--------------------|---------------------------|-------------|
| Horizontal   | *4874.000       | 52.2           | 36.1              | 34.2                | 50.3               | 74.0                      | -23.7       |
| Horizontal   | *7311.000       | 54.9           | 35.6              | 37.1                | 56.4               | 74.0                      | -17.6       |

| Polarization | Frequency (MHz) | Reading (dBμV) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Net at 3m (dBμV/m) | Average Limit at 3m (dBμV/m) | Margin (dB) |
|--------------|-----------------|----------------|-------------------|---------------------|--------------------|------------------------------|-------------|
| Horizontal   | *4874.000       | 39.1           | 36.1              | 34.2                | 37.2               | 54.0                         | -16.8       |
| Horizontal   | *7311.000       | 41.5           | 35.6              | 37.1                | 43.0               | 54.0                         | -11.0       |

- NOTES:
1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
  2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
  3. Negative value in the margin column shows emission below limit.
  4. Horn antenna used for the emission over 1000MHz.
- \* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

## INTERTEK TESTING SERVICES

Applicant: Kenxen Digitech Limited

Date of Test: 16 May 2017

Model: SDV360T3

Worst Case Operating Mode: 802.11n-HT20 (TX-Channel 11)

### Radiated Emissions

| Polarization | Frequency (MHz) | Reading (dBμV) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Net at 3m (dBμV/m) | Peak Limit at 3m (dBμV/m) | Margin (dB) |
|--------------|-----------------|----------------|-------------------|---------------------|--------------------|---------------------------|-------------|
| Horizontal   | *4924.000       | 51.9           | 36.1              | 34.6                | 50.4               | 74.0                      | -23.6       |
| Horizontal   | *7386.000       | 55.4           | 35.6              | 37.2                | 57.0               | 74.0                      | -17.0       |
| Horizontal   | *2487.490       | 61.0           | 36.7              | 28.0                | 52.3               | 74.0                      | -21.7       |

| Polarization | Frequency (MHz) | Reading (dBμV) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Net at 3m (dBμV/m) | Average Limit at 3m (dBμV/m) | Margin (dB) |
|--------------|-----------------|----------------|-------------------|---------------------|--------------------|------------------------------|-------------|
| Horizontal   | *4924.000       | 38.7           | 36.1              | 34.6                | 37.2               | 54.0                         | -16.8       |
| Horizontal   | *7386.000       | 41.4           | 35.6              | 37.2                | 43.0               | 54.0                         | -11.0       |
| Horizontal   | *2487.490       | 50.8           | 36.7              | 28.0                | 42.1               | 54.0                         | -11.9       |

- NOTES: 1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.
- \* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

## INTERTEK TESTING SERVICES

Applicant: Kenxen Digitech Limited

Date of Test: 16 May 2017

Model: SDV360T3

Worst Case Operating Mode: 802.11n-HT40 (TX-Channel 03)

### Radiated Emissions

| Polarization | Frequency (MHz) | Reading (dBμV) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Net at 3m (dBμV/m) | Peak Limit at 3m (dBμV/m) | Margin (dB) |
|--------------|-----------------|----------------|-------------------|---------------------|--------------------|---------------------------|-------------|
| Horizontal   | *4844.000       | 52.1           | 36.1              | 34.2                | 50.2               | 74.0                      | -23.8       |
| Horizontal   | *2389.570       | 61.1           | 36.7              | 28.2                | 52.6               | 74.0                      | -21.4       |

| Polarization | Frequency (MHz) | Reading (dBμV) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Net at 3m (dBμV/m) | Average Limit at 3m (dBμV/m) | Margin (dB) |
|--------------|-----------------|----------------|-------------------|---------------------|--------------------|------------------------------|-------------|
|              |                 |                |                   |                     |                    |                              |             |
| Horizontal   | *4844.000       | 39.1           | 36.1              | 34.2                | 37.2               | 54.0                         | -16.8       |
| Horizontal   | *2389.570       | 44.7           | 36.7              | 28.2                | 36.2               | 54.0                         | -17.8       |

- NOTES: 1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.
- \* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

## INTERTEK TESTING SERVICES

Applicant: Kenxen Digitech Limited

Date of Test: 16 May 2017

Model: SDV360T3

Worst Case Operating Mode: 802.11n-HT40 (TX-Channel 06)

### Radiated Emissions

| Polarization | Frequency (MHz) | Reading (dBμV) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Net at 3m (dBμV/m) | Peak Limit at 3m (dBμV/m) | Margin (dB) |
|--------------|-----------------|----------------|-------------------|---------------------|--------------------|---------------------------|-------------|
| Horizontal   | *4874.000       | 52.5           | 36.1              | 34.2                | 50.6               | 74.0                      | -23.4       |
| Horizontal   | *7311.000       | 55.3           | 35.6              | 37.1                | 56.8               | 74.0                      | -17.2       |

| Polarization | Frequency (MHz) | Reading (dBμV) | Pre-Amp Gain (dB) | Antenna Factor (dB) | Net at 3m (dBμV/m) | Average Limit at 3m (dBμV/m) | Margin (dB) |
|--------------|-----------------|----------------|-------------------|---------------------|--------------------|------------------------------|-------------|
| Horizontal   | *4874.000       | 39.3           | 36.1              | 34.2                | 37.4               | 54.0                         | -16.6       |
| Horizontal   | *7311.000       | 41.3           | 35.6              | 37.1                | 42.8               | 54.0                         | -11.2       |

- NOTES: 1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.
- \* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

## INTERTEK TESTING SERVICES

Applicant: Kenxen Digitech Limited

Date of Test: 16 May 2017

Model: SDV360T3

Worst Case Operating Mode: 802.11n-HT40 (TX-Channel 09)

### Radiated Emissions

| Polarization | Frequency<br>(MHz) | Reading<br>(dBμV) | Pre-<br>Amp<br>Gain<br>(dB) | Antenna<br>Factor<br>(dB) | Net<br>at 3m<br>(dBμV/m) | Peak Limit<br>at 3m<br>(dBμV/m) | Margin<br>(dB) |
|--------------|--------------------|-------------------|-----------------------------|---------------------------|--------------------------|---------------------------------|----------------|
| Vertical     | *4904.000          | 51.9              | 36.1                        | 34.6                      | 50.4                     | 74.0                            | -23.6          |
| Vertical     | *2483.200          | 61.9              | 36.7                        | 28.0                      | 53.2                     | 74.0                            | -20.8          |

| Polarization | Frequency<br>(MHz) | Reading<br>(dBμV) | Pre-<br>Amp<br>Gain<br>(dB) | Antenna<br>Factor<br>(dB) | Net<br>at 3m<br>(dBμV/m) | Average Limit<br>at 3m<br>(dBμV/m) | Margin<br>(dB) |
|--------------|--------------------|-------------------|-----------------------------|---------------------------|--------------------------|------------------------------------|----------------|
| Vertical     | *4904.000          | 38.6              | 36.1                        | 34.6                      | 37.1                     | 54.0                               | -16.9          |
| Vertical     | *2483.200          | 43.3              | 36.7                        | 28.0                      | 34.6                     | 54.0                               | -19.4          |

- NOTES: 1. Peak detector is used, RBW=1MHz/VBW=3MHz for peak value and RBW=1MHz / VBW=10Hz for average value.
2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.
- \* Emission within the restricted band meets the requirement of section 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

## INTERTEK TESTING SERVICES

---

### 4.9 Conducted Emission

Worst Case Conducted emission at 0.226MHz is Passed by 17.8dB margin

For electronic filing, the worst case conducted emission configuration photograph is saved with filename: conducted photos.pdf.

## INTERTEK TESTING SERVICES

Applicant: Kenxen Digitech Limited


Date of Test: 16 May 2017

Model: SDV360T3

Worst Case Operating Mode: 802.11n-HT20 (TX-Channel 01)

Line: Live

### Conducted Emission Test - FCC



### Limit and Margin QP

| Frequency (MHz) | QuasiPeak (dB $\mu$ V) | Line | Corr. (dB) | Margin (dB) | Limit (dB $\mu$ V) |
|-----------------|------------------------|------|------------|-------------|--------------------|
| 0.202           | 40.7                   | L1   | 9.7        | 22.8        | 63.5               |
| 0.238           | 42.8                   | L1   | 9.7        | 19.4        | 62.2               |
| 0.622           | 36.4                   | L1   | 9.7        | 19.6        | 56.0               |
| 0.718           | 35.3                   | L1   | 9.7        | 20.7        | 56.0               |
| 3.146           | 27.4                   | L1   | 9.8        | 28.6        | 56.0               |
| 4.390           | 29.4                   | L1   | 9.8        | 26.6        | 56.0               |

### Limit and Margin AV

| Frequency (MHz) | Average (dB $\mu$ V) | Line | Corr. (dB) | Margin (dB) | Limit (dB $\mu$ V) |
|-----------------|----------------------|------|------------|-------------|--------------------|
| 0.202           | 33.2                 | L1   | 9.7        | 20.3        | 53.5               |
| 0.238           | 29.9                 | L1   | 9.7        | 22.3        | 52.2               |
| 0.622           | 24.5                 | L1   | 9.7        | 21.5        | 46.0               |
| 0.718           | 21.2                 | L1   | 9.7        | 24.8        | 46.0               |
| 3.146           | 22.1                 | L1   | 9.8        | 23.9        | 46.0               |
| 4.390           | 24.1                 | L1   | 9.8        | 21.9        | 46.0               |

## INTERTEK TESTING SERVICES

Applicant: Kenxen Digitech Limited


Date of Test: 16 May 2017

Model: SDV360T3

Worst Case Operating Mode: 802.11n-HT20 (TX-Channel 01)

Line: Neutral

### Conducted Emission Test - FCC



### Limit and Margin QP

| Frequency (MHz) | QuasiPeak (dB $\mu$ V) | Line | Corr. (dB) | Margin (dB) | Limit (dB $\mu$ V) |
|-----------------|------------------------|------|------------|-------------|--------------------|
| 0.226           | 44.3                   | N    | 9.7        | 18.3        | 62.6               |
| 0.410           | 36.3                   | N    | 9.7        | 21.3        | 57.6               |
| 0.594           | 37.3                   | N    | 9.7        | 18.7        | 56.0               |
| 2.470           | 28.7                   | N    | 9.7        | 27.3        | 56.0               |
| 4.530           | 28.2                   | N    | 9.8        | 27.8        | 56.0               |
| 14.230          | 32.2                   | N    | 10.0       | 27.8        | 60.0               |

### Limit and Margin AV

| Frequency (MHz) | Average (dB $\mu$ V) | Line | Corr. (dB) | Margin (dB) | Limit (dB $\mu$ V) |
|-----------------|----------------------|------|------------|-------------|--------------------|
| 0.226           | 34.8                 | N    | 9.7        | 17.8        | 52.6               |
| 0.410           | 28.5                 | N    | 9.7        | 19.1        | 47.6               |
| 0.594           | 24.7                 | N    | 9.7        | 21.3        | 46.0               |
| 2.470           | 20.8                 | N    | 9.7        | 25.2        | 46.0               |
| 4.530           | 22.0                 | N    | 9.8        | 24.0        | 46.0               |
| 14.230          | 25.5                 | N    | 10.0       | 24.5        | 50.0               |

## INTERTEK TESTING SERVICES

---

Applicant: Kenxen Digitech Limited

Date of Test: 16 May 2017

Model: SDV360T3

4.10 Radiated Emissions from Digital Section of Transceiver, FCC Ref: 15.109

☐ Not required - No digital part

☐ Test results are attached

☒ Included in the separated report.

## INTERTEK TESTING SERVICES

---

Applicant: Kenxen Digitech Limited

Date of Test: 16 May 2017

Model: SDV360T3

### 4.11 Transmitter Duty Cycle Calculation and Measurements, FCC Rule 15.35(b), (c)

The EUT antenna output port was connected to the input of the spectrum analyzer. The analyzer center frequency was set to EUT RF channel carrier. The SWEP function on the analyzer was set to ZERO SPAN. The Transmitter ON time was determined from the resultant time-amplitude display:

|   |                                                                 |
|---|-----------------------------------------------------------------|
|   | See attached spectrum analyzer chart (s) for Transmitter timing |
|   | See Transmitter timing diagram provided by manufacturer         |
| x | Not applicable, duty cycle was not used.                        |

## **INTERTEK TESTING SERVICES**

---

### **EXHIBIT 5**

### **EQUIPMENT PHOTOGRAPHS**

## INTERTEK TESTING SERVICES

---

### 5.0 Equipment Photographs

For electronic filing, the photographs are saved with filename: external photos.pdf & internal photos.pdf.

**EXHIBIT 6**

**PRODUCT LABELLING**

## INTERTEK TESTING SERVICES

---

### 6.0 **Product Labeling**

For electronic filing, the FCC ID label artwork and location is saved with filename: label.pdf.

**EXHIBIT 7**  
**TECHNICAL SPECIFICATIONS**

## INTERTEK TESTING SERVICES

---

### 7.0 Technical Specifications

For electronic filing, the block diagram and circuit diagram are saved with filename: block.pdf and circuit.pdf respectively.

## **INTERTEK TESTING SERVICES**

---

### **EXHIBIT 8**

### **INSTRUCTION MANUAL**

## INTERTEK TESTING SERVICES

---

### 8.0 **Instruction Manual**

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

## **INTERTEK TESTING SERVICES**

---

### **EXHIBIT 9**

### **CONFIDENTIALITY REQUEST**

## INTERTEK TESTING SERVICES

---

### 9.0 **Confidentiality Request**

For electronic filing, the confidentiality request of the tested EUT is saved with filename: request.pdf.

## **INTERTEK TESTING SERVICES**

---

### **EXHIBIT 10**

### **MISCELLANEOUS INFORMATION**

### 10.0 **Discussion of Pulse Desensitization**

The determination of pulse desensitivity was made in accordance with Hewlett Packard Application Note 150-2, *Spectrum Analysis ... Pulsed RF*.

Pulse desensitivity is not applicable for this device since the transmitter transmits the RF signal continuously.

## **INTERTEK TESTING SERVICES**

---

### **EXHIBIT 11**

### **TEST EQUIPMENT LIST**

## INTERTEK TESTING SERVICES

### 11.0 Test Equipment List

| Equipment No. | Equipment         | Manufacturer    | Model No.              | Serial No.                          | Cal. Date   | Due Date    |
|---------------|-------------------|-----------------|------------------------|-------------------------------------|-------------|-------------|
| EE089         | EMI Test Receiver | Rohde & Schwarz | ESU                    | 1302.6005<br>.26                    | 17-May-2016 | 17-May-2017 |
| EE040         | Pre-Amplifier     | HP              | 8447F                  | 2944A079<br>99                      | 17-May-2016 | 17-May-2017 |
| EE043         | Bilog Antenna     | Schwarzbeck     | VULB9163               | 142                                 | 17-May-2016 | 17-May-2017 |
| EE049         | Power meter       | Anritsu         | ML2487A                | 6K000036<br>13                      | 28-May-2016 | 28-May-2017 |
| EE050         | Power sensor      | Anritsu         | MA2491A                | 32263                               | 28-May-2016 | 28-May-2017 |
| EE147         | Cable             | Schwarzbeck     | AK9513                 | ACRX1                               | 17-May-2016 | 17-May-2017 |
| EE169         | Cable             | Rosenberger     | N/A                    | FP2RX2                              | 17-May-2016 | 17-May-2017 |
| EE168         | Cable             | Schwarzbeck     | AK9513                 | CRPX1                               | 29-May-2016 | 29-May-2017 |
| EE170         | Cable             | Schwarzbeck     | AK9513                 | CRRX2                               | 29-May-2016 | 29-May-2017 |
| EE096         | Pre-Amplifier     | A.H.            | PAM-0126               | 1415261                             | 17-May-2016 | 17-May-2017 |
| EE094         | Horn Antenna      | Schwarzbeck     | BBHA<br>9120           | 707                                 | 29-May-2016 | 29-May-2017 |
| EE097         | Cable             | H+B             | 0.5M<br>SF104-<br>26.5 | 289147/4                            | 29-May-2016 | 29-May-2017 |
| EE100         | Cable             | H+B             | 3M SF104-<br>26.5      | 295838/4                            | 29-May-2016 | 29-May-2017 |
| EE101         | Cable             | H+B             | 6M SF104-<br>26.5      | 295840/4                            | 29-May-2016 | 29-May-2017 |
| EE095         | Horn Antenna      | Schwarzbeck     | BBHA<br>9170           | BBHA917<br>0399                     | 17-May-2016 | 17-May-2017 |
| EE343         | EMI Test Receiver | Rohde & Schwarz | FSV40                  | 132.1-<br>3008K39-<br>100967-<br>AP | 29-May-2016 | 29-May-2017 |
| EE240         | Pre-Amplifier     | Lunar EM        | LNA26G40<br>-40        | J10131310<br>28001                  | 17-May-2016 | 17-May-2017 |
| EE234         | Horn Antenna      | AHS/USA         | SAS-573                | 184                                 | 17-May-2016 | 17-May-2017 |
| EE312         | Cable             | A.H             | SAC-40G-<br>1          | 414                                 | 17-May-2016 | 17-May-2017 |
| EE313         | Cable             | A.H             | SAC-40G-<br>1          | 413                                 | 17-May-2016 | 17-May-2017 |
| EE023         | Test Receiver     | Rohde & Schwarz | ESCS30                 | 879                                 | 29-May-2016 | 29-May-2017 |
| EE145         | L.I.S.N.          | Rohde & Schwarz | ENV216                 | 590                                 | 29-May-2016 | 29-May-2017 |
| EE022         | AMN               | ROHDE & SCHWARZ | B-1492-9               | 856                                 | 26-Jun-2016 | 26-Jun-2017 |