

Table of Contents

1.	TRANSMITTER SPURIOUS EMISSIONS	2
1.1	TRANSMITTER SPURIOUS EMISSIONS FOR BLUETOOTH CLASSIC, BELOW 1GHz	3
1.2	TRANSMITTER SPURIOUS EMISSIONS FOR BLUETOOTH BLE, BELOW 1GHz	15
1.3	TRANSMITTER SPURIOUS EMISSIONS FOR BLUETOOTH CLASSIC, 1GHz-18GHz	21
1.4	TRANSMITTER SPURIOUS EMISSIONS FOR BLUETOOTH BLE, 1GHz-18GHz	33
1.5	TRANSMITTER SPURIOUS EMISSIONS FOR BLUETOOTH CLASSIC, 18GHz-26.5GHz	39
1.6	TRANSMITTER SPURIOUS EMISSIONS FOR BLUETOOTH BLE, 18GHz-26.5GHz	51
1.7	RESTRICTED BANDS FOR BLUETOOTH CLASSIC	57
1.8	RESTRICTED BANDS FOR BLUETOOTH BLE	69
2.	CONDUCTED EMISSIONS	73

Remark: The original sample's model name paralenz camera is changed to PDC-1 according to the client's requirement, while the change has no influence to the EMC performance that no additional test is needed.

1. Transmitter Spurious Emissions

*Note:1, Testing is carried out with frequency rang 9kHz to the tenth harmonics.
2, The margin is greater than 20 dB are not shown in this Appendix.*

1.1 Transmitter Spurious Emissions for Bluetooth Classic, Below 1GHz

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P.R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement

File: TUV 2017

Data: #1744

Date: 2017/07/06



Site: 3m Chamber #2

Polarization: **Vertical**

Temperature: 22 C

Limit: (RE)FCC PART 15 C

Power: AC 120V/60Hz

Humidity: 55 %

EUT: Diving Camera

M/N: Paralenz Camera

Mode: GFSK 2402

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Antenna Height cm	Table Degree degree	Comment
1		37.7600	42.93	-14.93	28.00	40.00	-12.00	QP			
2		71.7100	41.19	-18.05	23.14	40.00	-16.86	QP			
3		151.2500	42.43	-18.23	24.20	43.50	-19.30	QP			
4		319.0600	31.27	-10.74	20.53	46.00	-25.47	QP			
5		504.3300	39.03	-6.34	32.69	46.00	-13.31	QP			
6	*	792.4200	36.83	-0.85	35.98	46.00	-10.02	QP			

*: Maximum data x: Over limit !: over margin

Operator: KK

File: TUV 2017>Data: #1744

Page: 1

Appendix A

50087609 003



Produkte
Products

Page 4 of 74

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement

File: TUV 2017

Data: #1745

Date: 2017/07/06



Site: 3m Chamber #2

Polarization: **Horizontal**

Temperature: 22 C

Limit: (RE)FCC PART 15 C

Power: AC 120V/60Hz

Humidity: 55 %

EUT: Diving Camera

M/N: Paralenz Camera

Mode: GFSK 2402

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1		244.3700	36.24	-12.89	23.35	46.00	-22.65	QP		
2		499.4800	25.15	-6.47	18.68	46.00	-27.32	QP		
3		647.8900	39.12	-3.15	35.97	46.00	-10.03	QP		
4		660.5000	31.76	-2.99	28.77	46.00	-17.23	QP		
5	*	792.4200	39.14	-0.85	38.29	46.00	-7.71	QP		
6		936.9500	29.23	1.89	31.12	46.00	-14.88	QP		

*: Maximum data x: Over limit !: over margin

Operator: KK

File: TUV 2017>Data: #1745

Page: 1

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282




Radiated Emission Measurement

File: TUV 2017

Data: #1746

Date: 2017/07/06



Site: 3m Chamber #2

Polarization: **Horizontal**

Temperature: 22 C

Limit: (RE)FCC PART 15 C

Power: AC 120V/60Hz

Humidity: 55 %

EUT: Diving Camera

M/N: Paralenz Camera

Mode: GFSK 2441

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree	Comment
1		37.7600	33.08	-14.93	18.15	40.00	-21.85	QP		
2		313.2400	29.03	-10.97	18.06	46.00	-27.94	QP		
3		359.8000	31.27	-9.38	21.89	46.00	-24.11	QP		
4		504.3300	38.29	-6.34	31.95	46.00	-14.05	QP		
5		647.8900	34.90	-3.15	31.75	46.00	-14.25	QP		
6	*	792.4200	41.16	-0.85	40.31	46.00	-5.69	QP		

*: Maximum data x: Over limit !: over margin

Operator: KK

File: TUV 2017\Data: #1746

Page: 1

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282




Radiated Emission Measurement

File: TUV 2017

Data: #1747

Date: 2017/07/06



Site: 3m Chamber #2

Polarization: **Vertical**

Temperature: 22 C

Limit: (RE)FCC PART 15 C

Power: AC 120V/60Hz

Humidity: 55 %

EUT: Diving Camera

M/N: Paralenz Camera

Mode: GFSK 2441

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree	Comment
1		35.8200	42.53	-15.78	26.75	40.00	-13.25	QP		
2		143.4900	41.56	-18.31	23.25	43.50	-20.25	QP		
3		244.3700	37.02	-12.89	24.13	46.00	-21.87	QP		
4		504.3300	37.03	-6.34	30.69	46.00	-15.31	QP		
5		647.8900	31.40	-3.15	28.25	46.00	-17.75	QP		
6	*	792.4200	37.37	-0.85	36.52	46.00	-9.48	QP		

*: Maximum data x: Over limit !: over margin

Operator: KK

File: TUV 2017\Data :#1747

Page: 1

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282




Radiated Emission Measurement

File: TUV 2017

Data: #1748

Date: 2017/07/06



Site: 3m Chamber #2

Polarization: **Vertical**

Temperature: 22 C

Limit: (RE)FCC PART 15 C

Power: AC 120V/60Hz

Humidity: 55 %

EUT: Diving Camera

M/N: Paralenz Camera

Mode: GFSK 2480

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1	*	37.7600	44.82	-14.93	29.89	40.00	-10.11	QP		
2		184.2300	42.19	-16.00	26.19	43.50	-17.31	QP		
3		211.3900	42.09	-14.69	27.40	43.50	-16.10	QP		
4		647.8900	33.36	-3.15	30.21	46.00	-15.79	QP		
5		792.4200	29.13	-0.85	28.28	46.00	-17.72	QP		
6		961.2000	27.74	2.37	30.11	54.00	-23.89	QP		

*: Maximum data x: Over limit !: over margin

Operator: KK

File: TUV 2017>Data: #1748

Page: 1

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282




Radiated Emission Measurement

File: TUV 2017

Data: #1749

Date: 2017/07/06



Site: 3m Chamber #2

Polarization: **Horizontal**

Temperature: 22 C

Limit: (RE)FCC PART 15 C

Power: AC 120V/60Hz

Humidity: 55 %

EUT: Diving Camera

M/N: Paralenz Camera

Mode: GFSK 2480

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1		37.7600	32.95	-14.93	18.02	40.00	-21.98	QP		
2		233.7000	30.96	-13.25	17.71	46.00	-28.29	QP		
3		296.7500	30.08	-11.52	18.56	46.00	-27.44	QP		
4		504.3300	36.58	-6.34	30.24	46.00	-15.76	QP		
5		647.8900	37.16	-3.15	34.01	46.00	-11.99	QP		
6	*	792.4200	37.26	-0.85	36.41	46.00	-9.59	QP		

*: Maximum data x: Over limit !: over margin

Operator: KK

File: TUV 2017>Data: #1749

Page: 1

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282




Radiated Emission Measurement

File: TUV 2017

Data: #1750

Date: 2017/07/06



Site: 3m Chamber #2

Polarization: **Horizontal**

Temperature: 22 C

Limit: (RE)FCC PART 15 C

Power: AC 120V/60Hz

Humidity: 55 %

EUT: Diving Camera

M/N: Paralenz Camera

Mode: 8DPSK 2402

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree	Comment
1		37.7600	33.34	-14.93	18.41	40.00	-21.59	QP		
2		504.3300	37.57	-6.34	31.23	46.00	-14.77	QP		
3	*	647.8900	37.46	-3.15	34.31	46.00	-11.69	QP		
4		660.5000	30.45	-2.99	27.46	46.00	-18.54	QP		
5		792.4200	33.40	-0.85	32.55	46.00	-13.45	QP		
6		904.9400	26.37	1.28	27.65	46.00	-18.35	QP		

*:Maximum data x:Over limit !:over margin

Operator: KK

File: TUV 2017\Data :#1750

Page: 1

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282




Radiated Emission Measurement

File: TUV 2017

Data: #1751

Date: 2017/07/06



Site: 3m Chamber #2

Polarization: **Vertical**

Temperature: 22 C

Limit: (RE)FCC PART 15 C

Power: AC 120V/60Hz

Humidity: 55 %

EUT: Diving Camera

M/N: Paralenz Camera

Mode: 8DPSK 2402

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1	*	37.7600	47.53	-14.93	32.60	40.00	-7.40	QP		
2		74.6200	40.96	-18.91	22.05	40.00	-17.95	QP		
3		359.8000	33.44	-9.38	24.06	46.00	-21.94	QP		
4		647.8900	33.60	-3.15	30.45	46.00	-15.55	QP		
5		792.4200	29.66	-0.85	28.81	46.00	-17.19	QP		
6		934.0400	26.47	1.84	28.31	46.00	-17.69	QP		

*:Maximum data x:Over limit !:over margin

Operator: KK

File: TUV 2017>Data: #1751

Page: 1

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282




Radiated Emission Measurement

File: TUV 2017

Data: #1752

Date: 2017/07/06



Site: 3m Chamber #2

Polarization: **Vertical**

Temperature: 22 C

Limit: (RE)FCC PART 15 C

Power: AC 120V/60Hz

Humidity: 55 %

EUT: Diving Camera

M/N: Paralenz Camera

Mode: 8DPSK 2441

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree	Comment
1	*	37.7600	46.78	-14.93	31.85	40.00	-8.15	QP		
2		123.1200	43.92	-17.09	26.83	43.50	-16.67	QP		
3		160.9500	45.77	-17.52	28.25	43.50	-15.25	QP		
4		504.3300	36.89	-6.34	30.55	46.00	-15.45	QP		
5		792.4200	37.14	-0.85	36.29	46.00	-9.71	QP		
6		907.8500	31.67	1.34	33.01	46.00	-12.99	QP		

*: Maximum data x: Over limit !: over margin

Operator: KK

File: TUV 2017>Data: #1752

Page: 1

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282




Radiated Emission Measurement

File: TUV 2017

Data: #1753

Date: 2017/07/06



Site: 3m Chamber #2

Polarization: **Horizontal**

Temperature: 22 C

Limit: (RE)FCC PART 15 C

Power: AC 120V/60Hz

Humidity: 55 %

EUT: Diving Camera

M/N: Paralenz Camera

Mode: 8DPSK 2441

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1		37.7600	33.27	-14.93	18.34	40.00	-21.66	QP		
2		504.3300	39.42	-6.34	33.08	46.00	-12.92	QP		
3		647.8900	37.73	-3.15	34.58	46.00	-11.42	QP		
4		660.5000	30.72	-2.99	27.73	46.00	-18.27	QP		
5		792.4200	29.82	-0.85	28.97	46.00	-17.03	QP		
6	*	907.8500	33.99	1.34	35.33	46.00	-10.67	QP		

*:Maximum data x:Over limit !:over margin

Operator: KK

File: TUV 2017\Data: #1753

Page: 1

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282




Radiated Emission Measurement

File: TUV 2017

Data: #1754

Date: 2017/07/06



Site: 3m Chamber #2

Polarization: **Horizontal**

Temperature: 22 C

Limit: (RE)FCC PART 15 C

Power: AC 120V/60Hz

Humidity: 55 %

EUT: Diving Camera

M/N: Paralenz Camera

Mode: 8DPSK 2480

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree	Comment
1		37.7600	36.63	-14.93	21.70	40.00	-18.30	QP		
2		504.3300	40.31	-6.34	33.97	46.00	-12.03	QP		
3		647.8900	37.80	-3.15	34.65	46.00	-11.35	QP		
4		660.5000	30.22	-2.99	27.23	46.00	-18.77	QP		
5		792.4200	31.13	-0.85	30.28	46.00	-15.72	QP		
6	*	907.8500	36.94	1.34	38.28	46.00	-7.72	QP		

*:Maximum data x:Over limit !:over margin

Operator: KK

File: TUV 2017\Data :#1754

Page: 1

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282




Radiated Emission Measurement

File: TUV 2017

Data: #1755

Date: 2017/07/06



Site: 3m Chamber #2

Polarization: **Vertical**

Temperature: 22 C

Limit: (RE)FCC PART 15 C

Power: AC 120V/60Hz

Humidity: 55 %

EUT: Diving Camera

M/N: Paralenz Camera

Mode: 8DPSK 2480

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1		77.5300	42.34	-19.03	23.31	40.00	-16.69	QP		
2		152.2200	42.39	-18.16	24.23	43.50	-19.27	QP		
3		262.8000	35.04	-12.47	22.57	46.00	-23.43	QP		
4		504.3300	35.51	-6.34	29.17	46.00	-16.83	QP		
5		792.4200	36.30	-0.85	35.45	46.00	-10.55	QP		
6	*	907.8500	37.00	1.34	38.34	46.00	-7.66	QP		

*: Maximum data x: Over limit !: over margin

Operator: KK

File: TUV 2017>Data: #1755

Page: 1

1.2 Transmitter Spurious Emissions for Bluetooth BLE, Below 1GHz

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282




Radiated Emission Measurement

File: TUV 2017

Data: #1756

Date: 2017/07/06



Site: 3m Chamber #2

Polarization: **Vertical**

Temperature: 22 C

Limit: (RE)FCC PART 15 C

Power: AC 120V/60Hz

Humidity: 55 %

EUT: Diving Camera

M/N: Paralenz Camera

Mode: BLE GFSK 2402

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1		35.8200	41.35	-15.78	25.57	40.00	-14.43	QP		
2		71.7100	39.92	-18.05	21.87	40.00	-18.13	QP		
3		152.2200	40.09	-18.16	21.93	43.50	-21.57	QP		
4		504.3300	35.08	-6.34	28.74	46.00	-17.26	QP		
5	*	792.4200	37.83	-0.85	36.98	46.00	-9.02	QP		
6		907.8500	34.57	1.34	35.91	46.00	-10.09	QP		

*:Maximum data x:Over limit !:over margin

Operator: KK

File: TUV 2017\Data: #1756

Page: 1

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282




Radiated Emission Measurement

File: TUV 2017

Data: #1757

Date: 2017/07/06



Site: 3m Chamber #2

Polarization: **Horizontal**

Temperature: 22 C

Limit: (RE)FCC PART 15 C

Power: AC 120V/60Hz

Humidity: 55 %

EUT: Diving Camera

M/N: Paralenz Camera

Mode: BLE GFSK 2402

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1		36.7900	34.32	-15.37	18.95	40.00	-21.05	QP		
2		239.5200	30.44	-12.98	17.46	46.00	-28.54	QP		
3		359.8000	30.65	-9.38	21.27	46.00	-24.73	QP		
4		504.3300	39.23	-6.34	32.89	46.00	-13.11	QP		
5	*	647.8900	38.91	-3.15	35.76	46.00	-10.24	QP		
6		792.4200	36.58	-0.85	35.73	46.00	-10.27	QP		

*:Maximum data x:Over limit !:over margin

Operator: KK

File: TUV 2017\Data: #1757

Page: 1

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282




Radiated Emission Measurement

File: TUV 2017

Data: #1758

Date: 2017/07/06



Site: 3m Chamber #2

Polarization: **Horizontal**

Temperature: 22 C

Limit: (RE)FCC PART 15 C

Power: AC 120V/60Hz

Humidity: 55 %

EUT: Diving Camera

M/N: Paralenz Camera

Mode: BLE GFSK 2440

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1		37.7600	32.01	-14.93	17.08	40.00	-22.92	QP		
2		302.5700	33.85	-11.37	22.48	46.00	-23.52	QP		
3		504.3300	38.48	-6.34	32.14	46.00	-13.86	QP		
4		647.8900	38.29	-3.15	35.14	46.00	-10.86	QP		
5	*	792.4200	40.75	-0.85	39.90	46.00	-6.10	QP		
6		936.9500	29.48	1.89	31.37	46.00	-14.63	QP		

*:Maximum data x:Over limit !:over margin

Operator: KK

File: TUV 2017>Data: #1758

Page: 1

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282




Radiated Emission Measurement

File: TUV 2017

Data: #1759

Date: 2017/07/06



Site: 3m Chamber #2

Polarization: **Vertical**

Temperature: 22 C

Limit: (RE)FCC PART 15 C

Power: AC 120V/60Hz

Humidity: 55 %

EUT: Diving Camera

M/N: Paralenz Camera

Mode: BLE GFSK 2440

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree	Comment
1	*	35.8200	41.03	-15.78	25.25	40.00	-14.75	QP		
2		97.9000	37.03	-15.44	21.59	43.50	-21.91	QP		
3		504.3300	32.62	-6.34	26.28	46.00	-19.72	QP		
4		720.6400	26.92	-2.01	24.91	46.00	-21.09	QP		
5		823.4600	26.13	-0.29	25.84	46.00	-20.16	QP		
6		920.4600	27.02	1.58	28.60	46.00	-17.40	QP		

*:Maximum data x:Over limit !:over margin

Operator: KK

File: TUV 2017>Data: #1759

Page: 1

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282




Radiated Emission Measurement

File: TUV 2017

Data: #1760

Date: 2017/07/06



Site: 3m Chamber #2

Polarization: **Vertical**

Temperature: 22 C

Limit: (RE)FCC PART 15 C

Power: AC 120V/60Hz

Humidity: 55 %

EUT: Diving Camera

M/N: Paralenz Camera

Mode: BLE GFSK 2480

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1		35.8200	40.83	-15.78	25.05	40.00	-14.95	QP		
2		71.7100	39.80	-18.05	21.75	40.00	-18.25	QP		
3		157.0700	39.89	-17.79	22.10	43.50	-21.40	QP		
4	*	504.3300	39.60	-6.34	33.26	46.00	-12.74	QP		
5		647.8900	33.20	-3.15	30.05	46.00	-15.95	QP		
6		792.4200	28.02	-0.85	27.17	46.00	-18.83	QP		

*:Maximum data x:Over limit !:over margin

Operator: KK

File: TUV 2017>Data: #1760

Page: 1

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282




Radiated Emission Measurement

File: TUV 2017

Data: #1761

Date: 2017/07/06



Site: 3m Chamber #2

Polarization: **Horizontal**

Temperature: 22 C

Limit: (RE)FCC PART 15 C

Power: AC 120V/60Hz

Humidity: 55 %

EUT: Diving Camera

M/N: Paralenz Camera

Mode: BLE GFSK 2480

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree	Comment
1		296.7500	31.41	-11.52	19.89	46.00	-26.11	QP		
2		504.3300	38.47	-6.34	32.13	46.00	-13.87	QP		
3	*	647.8900	36.63	-3.15	33.48	46.00	-12.52	QP		
4		660.5000	29.47	-2.99	26.48	46.00	-19.52	QP		
5		792.4200	30.72	-0.85	29.87	46.00	-16.13	QP		
6		936.9500	28.02	1.89	29.91	46.00	-16.09	QP		

*:Maximum data x:Over limit !:over margin

Operator: KK

File: TUV 2017>Data: #1761

Page: 1

1.3 Transmitter Spurious Emissions for Bluetooth Classic, 1GHz-18GHz

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282




Radiated Emission Measurement

File: TUV 2017

Data: #1928

Date: 2017/07/06



Site: 3m Chamber #2

Polarization: **Vertical**

Temperature: 24 C

Limit: (RE)FCC PART 15 C

Power: AC 120V/60Hz

Humidity: 53 %

EUT: Diving Camera

M/N: Paralenz Camera

Mode: GFSK 2402

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1		14328.00	59.81	-8.40	51.41	74.00	-22.59	peak		
2	*	14328.00	44.70	-8.40	36.30	54.00	-17.70	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File: TUV 2017\Data: #1928

Page: 1

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282




Radiated Emission Measurement

File: TUV 2017

Data: #1929

Date: 2017/07/06



Site: 3m Chamber #2

Polarization: **Horizontal**

Temperature: 24 C

Limit: (RE)FCC PART 15 C

Power: AC 120V/60Hz

Humidity: 53 %

EUT: Diving Camera

M/N: Paralenz Camera

Mode: GFSK 2402

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1		15637.00	63.04	-11.60	51.44	74.00	-22.56	peak		
2	*	15637.00	48.50	-11.60	36.90	54.00	-17.10	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File: TUV 2017\Data: #1929

Page: 1

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282




Radiated Emission Measurement

File: TUV 2017

Data: #1930

Date: 2017/07/06



Site: 3m Chamber #2

Polarization: **Vertical**

Temperature: 24 C

Limit: (RE)FCC PART 15 C

Power: AC 120V/60Hz

Humidity: 53 %

EUT: Diving Camera

M/N: Paralenz Camera

Mode: GFSK 2441

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		12917.00	63.54	-12.78	50.76	74.00	-23.24	peak		
2	*	12917.00	48.58	-12.78	35.80	54.00	-18.20	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File: TUV 2017\Data: #1930

Page: 1

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282



Radiated Emission Measurement

File: TUV 2017

Data: #1931

Date: 2017/07/06



Site: 3m Chamber #2

Polarization: **Horizontal**

Temperature: 24 C

Limit: (RE)FCC PART 15 C

Power: AC 120V/60Hz

Humidity: 53 %

EUT: Diving Camera

M/N: Paralenz Camera

Mode: GFSK 2441

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree	Comment
1		14175.00	59.10	-8.13	50.97	74.00	-23.03	peak		
2	*	14175.00	41.33	-8.13	33.20	54.00	-20.80	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File: TUV 2017\Data: #1931

Page: 1

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282




Radiated Emission Measurement

File: TUV 2017

Data: #1932

Date: 2017/07/06



Site: 3m Chamber #2

Polarization: **Vertical**

Temperature: 24 C

Limit: (RE)FCC PART 15 C

Power: AC 120V/60Hz

Humidity: 53 %

EUT: Diving Camera

M/N: Paralenz Camera

Mode: GFSK 2480

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		14685.00	60.74	-9.03	51.71	74.00	-22.29	peak		
2	*	14685.00	46.83	-9.03	37.80	54.00	-16.20	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File: TUV 2017\Data: #1932

Page: 1

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282




Radiated Emission Measurement

File: TUV 2017

Data: #1933

Date: 2017/07/06



Site: 3m Chamber #2

Polarization: **Horizontal**

Temperature: 24 C

Limit: (RE)FCC PART 15 C

Power: AC 120V/60Hz

Humidity: 53 %

EUT: Diving Camera

M/N: Paralenz Camera

Mode: GFSK 2480

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree	Comment
1		14396.00	59.41	-8.52	50.89	74.00	-23.11	peak		
2	*	14396.00	44.42	-8.52	35.90	54.00	-18.10	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File: TUV 2017\Data: #1933

Page: 1

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282




Radiated Emission Measurement

File: TUV 2017

Data: #1934

Date: 2017/07/06



Site: 3m Chamber #2

Polarization: **Vertical**

Temperature: 24 C

Limit: (RE)FCC PART 15 C

Power: AC 120V/60Hz

Humidity: 53 %

EUT: Diving Camera

M/N: Paralenz Camera

Mode: 8DPSK 2402

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree	Comment
1		14702.00	60.28	-9.06	51.22	74.00	-22.78	peak		
2	*	14702.00	44.26	-9.06	35.20	54.00	-18.80	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File: TUV 2017\Data: #1934

Page: 1

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282




Radiated Emission Measurement

File: TUV 2017

Data: #1935

Date: 2017/07/06



Site: 3m Chamber #2

Polarization: **Horizontal**

Temperature: 24 C

Limit: (RE)FCC PART 15 C

Power: AC 120V/60Hz

Humidity: 53 %

EUT: Diving Camera

M/N: Paralenz Camera

Mode: 8DPSK 2402

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1		16249.00	63.04	-11.88	51.16	74.00	-22.84	peak		
2	*	16249.00	49.78	-11.88	37.90	54.00	-16.10	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File: TUV 2017\Data: #1935

Page: 1

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282




Radiated Emission Measurement

File: TUV 2017

Data: #1936

Date: 2017/07/06



Site: 3m Chamber #2

Polarization: **Vertical**

Temperature: 24 C

Limit: (RE)FCC PART 15 C

Power: AC 120V/60Hz

Humidity: 53 %

EUT: Diving Camera

M/N: Paralenz Camera

Mode: 8DPSK 2441

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1		15450.00	62.09	-11.02	51.07	74.00	-22.93	peak		
2	*	15450.00	45.42	-11.02	34.40	54.00	-19.60	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File: TUV 2017\Data: #1936

Page: 1

Shenzhen EMTEK Co., Ltd.
Bldg. 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, 518052 P. R. China
www.emtek.com.cn Tel: +86-755-2695 4280 Fax: +86-755-2695 4282




Radiated Emission Measurement

File: TUV 2017

Data: #1937

Date: 2017/07/06



Site: 3m Chamber #2

Polarization: **Horizontal**

Temperature: 24 C

Limit: (RE)FCC PART 15 C

Power: AC 120V/60Hz

Humidity: 53 %

EUT: Diving Camera

M/N: Paralenz Camera

Mode: 8DPSK 2441

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree	Comment
1		13954.00	60.01	-8.05	51.96	74.00	-22.04	peak		
2	*	13954.00	42.15	-8.05	34.10	54.00	-19.90	AVG		

*:Maximum data x:Over limit !:over margin

Operator: KK

File: TUV 2017\Data: #1937

Page: 1