



FCC TEST REPORT

Test report
On Behalf of
Guangdong Shunde Noon Appliance Manufacturing Co.,Ltd
For
Aroma diffuser
Model No.: DH-JS02S, DH-JS01S, DH-JS02S-W1, DH-JS03S,
DH-JS04S, DH-JS05S, DH-JS06S

FCC ID: 2AL97-DHJS02S

Prepared for : Guangdong Shunde Noon Appliance Manufacturing Co.,Ltd
601Room,6Block,Qide Industrial Park, Beijiao, Shunde, Guangdong, China

Prepared By : Shenzhen HUAK Testing Technology Co., Ltd.
F1-008, Tai Yi Building, No.1, Haicheng West Road, Xixiang Street, Bao'an
District, Shenzhen City, China

Date of Test: Mar. 18, 2017 ~ Jun. 12, 2017

Date of Report: Jun. 12, 2017

Report Number: HUAK170518052-E-1



TEST RESULT CERTIFICATION

Applicant's name : Guangdong Shunde NooN Appliance Manufacturing Co.,Ltd
Address : 601Room, 6Block, Qide Industrial Park, Beijiao, Shunde, Guangdong, China
Manufacture's Name : Guangdong Shunde NooN Appliance Manufacturing Co.,Ltd
Address : 601Room, 6Block, Qide Industrial Park, Beijiao, Shunde, Guangdong, China

Product description

Trade Mark: N/A
Product name : Aroma diffuser
Model and/or type reference : DH-JS02S, DH-JS01S, DH-JS02S-W1, DH-JS03S, DH-JS04S, DH-JS05S, DH-JS06S
Standards : FCC Rules and Regulations Part 15 Subpart C Section 15.249
ANSI C63.10: 2013

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen HUAK Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen HUAK Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Date of Test

Date (s) of performance of tests : Mar. 18, 2017 ~ Jun. 12, 2017

Date of Issue..... : Jun. 12, 2017

Test Result..... : Pass

Testing Engineer :

(Eric Xie)

Technical Manager :

(Dora Qin)

Authorized Signatory :

(Kait Chen)



Table of Contents	Page
1 . TEST SUMMARY	4
2 . GENERAL INFORMATION	5
2.1 GENERAL DESCRIPTION OF EUT	5
Operation of EUT during testing	6
2.2 DESCRIPTION OF TEST SETUP	6
2.3 MEASUREMENT INSTRUMENTS LIST	7
3 . CONDUCTED EMISSIONS TEST	8
3.1 Conducted Power Line Emission Limit	8
3.2 Test Setup	8
3.3 Test Procedure	8
3.4 Test Result	8
4 RADIATED EMISSION TEST	11
4.1 Radiation Limit	11
4.2 Test Setup	11
4.3 Test Procedure	12
4.4 Test Result	12
5 BAND EDGE	24
5.1 Limits	24
5.2 Test Procedure	24
5.3 Test Result	24
6 OCCUPIED BANDWIDTH MEASUREMENT	26
6.1 Test Setup	26
6.2 Test Procedure	26
6.3 Measurement Equipment Used	26
6.4 Test Result	26
7 ANTENNA REQUIREMENT	32
8 PHOTOGRAPH OF TEST	33
8.1 Radiated Emission	33
8.2 Conducted Emission	34



1. TEST SUMMARY

1.1 TEST PROCEDURES AND RESULTS

DESCRIPTION OF TEST	RESULT
CONDUCTED EMISSIONS TEST	COMPLIANT
RADIATED EMISSION TEST	COMPLIANT
BAND EDGE	COMPLIANT
OCCUPIED BANDWIDTH MEASUREMENT	COMPLIANT
ANTENNA REQUIREMENT	COMPLIANT

1.2 TEST FACILITY

Test Firm : QTC Certification & Testing Co., Ltd.
Certificated by FCC, Registration No.: 588523
Address 2nd Floor,B1 Building,Fengyeyuan Industrial Plant, Liuxian 2st. Road,
Xin'an Street, Bao'an District, Shenzhen, China

1.3 MEASUREMENT UNCERTAINTY

Measurement Uncertainty	
Conducted Emission Expanded Uncertainty	= 2.23dB, k=2
Radiated emission expanded uncertainty(9kHz-30MHz)	= 3.08dB, k=2
Radiated emission expanded uncertainty(30MHz-1000MHz)	= 4.42dB, k=2
Radiated emission expanded uncertainty(Above 1GHz)	= 4.06dB, k=2



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	Aroma diffuser
Model Name	DH-JS02S
Trade Mark	N/A
Serial Model	DH-JS01S, DH-JS02S-W1, DH-JS03S, DH-JS04S, DH-JS05S, DH-JS06S
Model Difference	All model's the function, software and electric circuit are the same, only with a product color and model named different. Test sample model: DH-JS02S.
FCC ID	2AL97-DHJS02S
Antenna Type	PCB Antenna
Antenna Gain	0dBi
BT Operation frequency	2402-2480MHz
Number of Channels	79CH
Modulation Type	GFSK, Pi/4 QDPSK, 8DBSK
Power Source	N/A
Power Rating	DC 24V for AC adapter with AC 120V/60Hz, 0.5A
Adapter information	DZ015HL240065U Input:100-240VAC, 50/60Hz, 0.5A Output:DC24V, 0.65A



2.1.1 Carrier Frequency of Channels

Channel List					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	27	2429	54	2456
01	2403	28	2430	55	2457
02	2404	29	2431	56	2458
03	2405	30	2432	57	2459
04	2406	31	2433	58	2460
05	2407	32	2434	59	2461
06	2408	33	2435	60	2462
07	2409	34	2436	61	2463
08	2410	35	2437	62	2464
09	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	39	2441	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	78	2480
25	2427	52	2454		
26	2428	53	2455		

Operation of EUT during testing

Operating Mode

The mode is used: **Transmitting mode**


Low Channel: 2402MHz

Middle Channel: 2441MHz

High Channel: 2480MHz

2.2 DESCRIPTION OF TEST SETUP

Operation of EUT during radiation and conducted testing





2.3 MEASUREMENT INSTRUMENTS LIST

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
1.	EMI Receiver	Rohde & Schwarz	ESCI	100627	Feb. 18, 2017	Feb. 17, 2018
2.	LISN	SchwarzBeck	NSLK 8126	8126377	Feb. 18, 2017	Feb. 17, 2018
3.	RF Switching Unit	Compliance Direction	RSU-M2	38303	Feb. 18, 2017	1 Year
4.	EMI Test Software ES-K1	Rohde & Schwarz	N/A	N/A	N/A	N/A
5.	EMI Test Receiver	Rohde & Schwarz	ESCI	100627	Feb. 18, 2017	Feb. 17, 2018
6.	Trilog Broadband Antenna	Schwarzbeck	VULB9163	VULB 9163-289	Feb. 18, 2017	Feb. 17, 2018
7.	Pre-amplifier	Compliance Direction	PAP-0203	22008	Feb. 18, 2017	Feb. 17, 2018
8.	EMI Test Software EZ-EMC	SHURPLE	N/A	N/A	N/A	N/A
9.	EMI Receiver	Rohde & Schwarz	ESCI	100627	Feb. 18, 2017	Feb. 17, 2018
10.	LISN	SchwarzBeck	NSLK 8126	8126377	Feb. 18, 2017	Feb. 17, 2018
11.	RF Switching Unit	Compliance Direction	RSU-M2	38303	Feb. 18, 2017	Feb. 17, 2018
12.	EMI Test Software ES-K1	Rohde & Schwarz	N/A	N/A	N/A	N/A
13.	EMI Receiver	Rohde & Schwarz	ESCI	100627	Feb. 18, 2017	Feb. 17, 2018
14.	EMI Receiver	Rohde & Schwarz	ESCI	100627	Feb. 18, 2017	Feb. 17, 2018
15.	LISN	SchwarzBeck	NSLK 8126	8126377	Feb. 18, 2017	Feb. 17, 2018
16.	RF Switching Unit	Compliance Direction	RSU-M2	38303	Feb. 18, 2017	Feb. 17, 2018
17.	EMI Test Software ES-K1	Rohde & Schwarz	N/A	N/A	N/A	N/A
18.	Power Meter	R&S	NRVD	SEL0069	Feb. 18, 2017	Feb. 17, 2018
19.	Power Sensor	R&S	URV5-Z2	SEL0071	Feb. 18, 2017	Feb. 17, 2018
20.	Power Sensor	R&S	URV5-Z2	SEL0072	Feb. 18, 2017	Feb. 17, 2018
21.	Software EMC32	R&S	EMC32-S	SEL0082	N/A	N/A
22.	Log-periodic Antenna	Amplifier Reasearch	APT1.580	SEL0073	Feb. 18, 2017	Feb. 17, 2018
23.	Loop Antenna	Schwarz beck	FMZB 1516	9773	Feb. 18, 2017	Feb. 17, 2018
24.	Broadband Antenna	Schwarz beck	VULB9163	9163-333	Feb. 18, 2017	Feb. 17, 2018
25.	Horn Antenna	ETS	3117	00086197	Feb. 18, 2017	Feb. 17, 2018
26.	Horn Antenna	Schwarzbeck	BBHA9170	BBHA91705 82	Feb. 18, 2017	Feb. 17, 2018
27.	Antenna Tripod	Amplifier Reasearch	TP1000A	SEL0074	Feb. 18, 2017	Feb. 17, 2018
28.	High Gain Horn Antenna	Amplifier Reasearch	AT4002A	SEL0075	Feb. 18, 2017	Feb. 17, 2018
29.	Spectrum analyzer	Agilent	N9020A	MY49911004 8	Feb. 18, 2017	Feb. 17, 2018
30.	Spectrum analyzer	Agilent	E4407B	MY46184326	Feb. 18, 2017	Feb. 17, 2018
31.	Spectrum analyzer	R&S	FSP30	836079/035	Feb. 18, 2017	Feb. 17, 2018
32.	RF Cable	Micable	C10-01-01-1	100309	Feb. 18, 2017	Feb. 17, 2018

3. CONDUCTED EMISSIONS TEST

3.1 Conducted Power Line Emission Limit


For unintentional device, according to § 15.107(a) Line Conducted Emission Limits is as following

Frequency (MHz)	Maximum RF Line Voltage (dBμV)			
	CLASS A		CLASS B	
	Q.P.	Ave.	Q.P.	Ave.
0.15 - 0.50	79	66	66-56*	56-46*
0.50 - 5.00	73	60	56	46
5.00 - 30.0	73	60	60	50

* Decreasing linearly with the logarithm of the frequency

For intentional device, according to §15.207(a) Line Conducted Emission Limit is same as above table.

3.2 Test Setup



3.3 Test Procedure

- 1, The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10.
- 2, Support equipment, if needed, was placed as per ANSI C63.10.
- 3, All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4, If a EUT received DC power from the USB Port of Notebook PC, the PC's adapter received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5, All support equipments received AC power from a second LISN, if any.
- 6, The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7, Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.


3.4 Test Result

PASS

Remark: All modes of GFSK, Pi/4 DQPSK, and 8DPSK were test at Low, Middle, and High channel; only the worst result of GFSK Low Channel was reported as below:




Line



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1*	0.1500	51.22	9.85	61.07	66.00	-4.93	QP
2	0.1540	32.11	9.85	41.96	55.78	-13.82	AVG
3	0.1820	47.34	9.82	57.16	64.39	-7.23	QP
4	0.1900	31.39	9.81	41.20	54.04	-12.84	AVG
5	0.2220	43.01	9.80	52.81	62.74	-9.93	QP
6	0.2220	29.13	9.80	38.93	52.74	-13.81	AVG



Neutral



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1*	0.1540	47.35	9.85	57.20	65.78	-8.58	QP
2	0.1540	31.00	9.85	40.85	55.78	-14.93	AVG
3	0.1860	43.62	9.81	53.43	64.21	-10.78	QP
4	0.1980	26.89	9.80	36.69	53.69	-17.00	AVG
5	0.2220	38.80	9.80	48.60	62.74	-14.14	QP
6	0.2260	22.64	9.80	32.44	52.60	-20.16	AVG

4 RADIATED EMISSION TEST

4.1 Radiation Limit


For unintentional device, according to § 15.109(a), except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency (MHz)	Distance (Meters)	Radiated (dB μ V/m)	Radiated (μ V/m)
30-88	3	40	100
88-216	3	43.5	150
216-960	3	46	200
Above 960	3	54	500


For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emissions from intentional radiators at a distance of 3 meters shall not exceed the above table.

4.2 Test Setup


(1) Radiated Emission Test-Up Frequency Below 30MHz



(2) Radiated Emission Test-Up Frequency 30MHz~1GHz



(3) Radiated Emission Test-Up Frequency Above 1GHz



4.3 Test Procedure

1. Below 1GHz measurement the EUT is placed on turntable which is 0.8m above ground plane. And above 1GHz measurement EUT was placed on low permittivity and low tangent turn table which is 1.5m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. The test frequency range from 9KHz to 25GHz per FCC PART 15.33(a).

Note:

For battery operated equipment, the equipment tests shall be performed using a new battery.

4.4 Test Result


PASS

Remark:

1. We measured Radiated Emission at GFSK, $\pi/4$ DQPSK and 8DPSK mode from 9 KHz to 25GHz and recorded worst case at GFSK Low Channel mode.
2. For below 1GHz testing recorded worst at GFSK low channel.




Below 1GHz Test Results:
Antenna polarity: H



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	(°)	(cm)	
1	61.5250	35.39	-10.08	25.31	40.00	-14.69	360	100	peak
2	114.8750	46.92	-11.29	35.63	43.50	-7.87	287	100	peak
3	151.2500	52.48	-12.41	40.07	43.50	-3.43	168	100	peak
4	296.7500	45.61	-5.72	39.89	46.00	-6.11	122	100	peak
5	369.5000	40.14	-2.70	37.44	46.00	-8.56	100	100	peak
6	767.2000	32.72	2.20	34.92	46.00	-11.08	100	100	peak



Antenna polarity: V



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	37.2750	45.74	-8.41	37.33	40.00	-2.67	78	100	peak
2	52.5753	45.21	-8.65	36.56	40.00	-3.44	136	100	peak
3	114.8750	45.79	-11.29	34.50	43.50	-9.00	284	100	peak
4	141.5500	51.11	-12.55	38.56	43.50	-4.94	60	100	peak
5	296.7500	36.97	-5.72	31.25	46.00	-14.75	330	100	peak
6	595.0250	36.37	-0.34	36.03	46.00	-9.97	100	100	peak

Remark:

- (1) Measuring frequencies from 9 KHz to the 1 GHz, Radiated emission test from 9KHz to 30MHz was verified, and no any emission was found except system noise floor.
- (2) * denotes emission frequency which appearing within the Restricted Bands specified in provision of 15.205, then the general radiated emission limits in 15.209 apply.
- (3) The IF bandwidth of EMI Test Receiver between 30MHz to 1GHz was 120KHz, 1 MHz for measuring above 1 GHz, below 30MHz was 10KHz.



Above 1 GHz Test Results:

Note : GFSK, Pi/4 DQPSK and 8DPSK all have been tested,
GFSK Mode (above 1GHz)

CH Low (2402MHz)

Horizontal:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2402	113.27	-5.84	107.43	114	-6.57	peak
2402	84.17	-5.84	78.33	94	-15.67	AVG
4804	58.32	-3.64	54.68	74	-19.32	peak
4804	43.16	-3.64	39.52	54	-14.48	AVG
7206	54.17	-0.95	53.22	74	-20.78	peak
7206	42.26	-0.95	41.31	54	-12.69	AVG
---	---	---	---	---	---	---
---	---	---	---	---	---	---

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Vertical:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2402	110.43	-5.84	104.59	114	-9.41	peak
2402	85.27	-5.84	79.43	94	-14.57	AVG
4804	56.97	-3.64	53.33	74	-20.67	peak
4804	45.15	-3.64	41.51	54	-12.49	AVG
7206	53.16	-0.95	52.21	74	-21.79	peak
7206	37.87	-0.95	36.92	54	-17.08	AVG
---	---	---	---	---	---	---
---	---	---	---	---	---	---

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.



CH Middle (2441MHz)

Horizontal:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2441	108.23	-5.71	102.52	114	-11.48	peak
2441	84.76	-5.71	79.05	94	-14.95	AVG
4882	56.75	-3.51	53.24	74	-20.76	peak
4882	45.15	-3.51	41.64	54	-12.36	AVG
7323	52.13	-0.82	51.31	74	-22.69	peak
7323	37.25	-0.82	36.43	54	-17.57	AVG
---	---	---	---	---	---	---
---	---	---	---	---	---	---

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Vertical:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2441	107.46	-5.71	101.75	114	-12.25	peak
2441	82.68	-5.71	76.97	94	-17.03	AVG
4882	54.14	-3.51	50.63	74	-23.37	peak
4882	45.96	-3.51	42.45	54	-11.55	AVG
7323	52.14	-0.82	51.32	74	-22.68	peak
7323	33.25	-0.82	32.43	54	-21.57	AVG
---	---	---	---	---	---	---
---	---	---	---	---	---	---

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.



CH High (2480MHz)

Horizontal:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2480	106.14	-5.65	100.49	114	-13.51	peak
2480	82.25	-5.65	76.6	94	-17.4	AVG
4960	55.45	-3.43	52.02	74	-21.98	peak
4960	43.38	-3.43	39.95	54	-14.05	AVG
7440	54.25	-0.75	53.5	74	-20.5	peak
7440	38.64	-0.75	37.89	54	-16.11	AVG
---	---	---	---	---	---	---
---	---	---	---	---	---	---

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Vertical:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2480	107.16	-5.65	101.51	114	-12.49	peak
2480	82.54	-5.65	76.89	94	-17.11	AVG
4960	56.46	-3.43	53.03	74	-20.97	peak
4960	42.14	-3.43	38.71	54	-15.29	AVG
7440	53.15	-0.75	52.4	74	-21.6	peak
7440	37.38	-0.75	36.63	54	-17.37	AVG
---	---	---	---	---	---	---
---	---	---	---	---	---	---

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Remark:

- (1) Measuring frequencies from 1 GHz to the 25 GHz.
- (2) "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency.
- (3) * denotes emission frequency which appearing within the Restricted Bands specified in provision of 15.205, then the general radiated emission limits in 15.209 apply.
- (4) Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) The IF bandwidth of EMI Test Receiver between 30MHz to 1GHz was 120KHz, 1 MHz for measuring above 1 GHz, below 30MHz was 10KHz.
- (6) When the test results of Peak Detected below the limits of Average Detected, the Average Detected is not need completed. For example: Top Channel at Fundamental 73.16dBuV/m(PK Value) <93.98(AV Limit), at harmonic 53.20 dBuV/m(PK Value) <54 dBuV/m(AV Limit), the Average Detected not need to completed.



Pi/4 DQPSK Mode (above 1GHz)

CH Low (2402MHz)

Horizontal:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2402	111.13	-5.84	105.29	114	-8.71	peak
2402	83.23	-5.84	77.39	94	-16.61	AVG
4804	57.24	-3.64	53.6	74	-20.4	peak
4804	45.43	-3.64	41.79	54	-12.21	AVG
7206	54.97	-0.95	54.02	74	-19.98	peak
7206	42.41	-0.95	41.46	54	-12.54	AVG
---	---	---	---	---	---	---
---	---	---	---	---	---	---

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Vertical:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2402	109.11	-5.84	103.27	114	-10.73	peak
2402	84.54	-5.84	78.7	94	-15.3	AVG
4804	55.24	-3.64	51.6	74	-22.4	peak
4804	43.19	-3.64	39.55	54	-14.45	AVG
7206	52.04	-0.95	51.09	74	-22.91	peak
7206	37.32	-0.95	36.37	54	-17.63	AVG
---	---	---	---	---	---	---
---	---	---	---	---	---	---

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.



CH Middle (2441MHz)

Horizontal:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2441	106.21	-5.71	100.5	114	-13.5	peak
2441	82.07	-5.71	76.36	94	-17.64	AVG
4882	56.35	-3.51	52.84	74	-21.16	peak
4882	44.32	-3.51	40.81	54	-13.19	AVG
7323	51.43	-0.82	50.61	74	-23.39	peak
7323	37.19	-0.82	36.37	54	-17.63	AVG
---	---	---	---	---	---	---
---	---	---	---	---	---	---

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Vertical:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2441	106.29	-5.71	100.58	114	-13.42	peak
2441	82.22	-5.71	76.51	94	-17.49	AVG
4882	53.19	-3.51	49.68	74	-24.32	peak
4882	45.03	-3.51	41.52	54	-12.48	AVG
7323	52.31	-0.82	51.49	74	-22.51	peak
7323	33.14	-0.82	32.32	54	-21.68	AVG
---	---	---	---	---	---	---
---	---	---	---	---	---	---

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.



CH High (2480MHz)

Horizontal:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2480	105.19	-5.65	99.54	114	-14.46	peak
2480	81.35	-5.65	75.7	94	-18.3	AVG
4960	54.21	-3.43	50.78	74	-23.22	peak
4960	41.65	-3.43	38.22	54	-15.78	AVG
7440	52.17	-0.75	51.42	74	-22.58	peak
7440	36.48	-0.75	35.73	54	-18.27	AVG
---	---	---	---	---	---	---
---	---	---	---	---	---	---

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Vertical:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2480	105.19	-5.65	99.54	114	-14.46	peak
2480	82.13	-5.65	76.48	94	-17.52	AVG
4960	54.64	-3.43	51.21	74	-22.79	peak
4960	42.06	-3.43	38.63	54	-15.37	AVG
7440	53.34	-0.75	52.59	74	-21.41	peak
7440	36.19	-0.75	35.44	54	-18.56	AVG
---	---	---	---	---	---	---
---	---	---	---	---	---	---

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Remark:

- (1) Measuring frequencies from 1 GHz to the 25 GHz.
- (2) "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency.
- (3) * denotes emission frequency which appearing within the Restricted Bands specified in provision of 15.205, then the general radiated emission limits in 15.209 apply.
- (4) Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) The IF bandwidth of EMI Test Receiver between 30MHz to 1GHz was 120KHz, 1 MHz for measuring above 1 GHz, below 30MHz was 10KHz.
- (6) When the test results of Peak Detected below the limits of Average Detected, the Average Detected is not need completed. For example: Top Channel at Fundamental 73.16dBuV/m(PK Value) <93.98(AV Limit), at harmonic 53.20 dBuV/m(PK Value) <54 dBuV/m(AV Limit), the Average Detected not need to completed.



8DPSK Mode (above 1GHz)

CH Low (2402MHz)

Horizontal:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2402	106.39	-5.84	100.55	114	-13.45	peak
2402	82.17	-5.84	76.33	94	-17.67	AVG
4804	55.18	-3.64	51.54	74	-22.46	peak
4804	41.87	-3.64	38.23	54	-15.77	AVG
7206	52.98	-0.95	52.03	74	-21.97	peak
7206	41.07	-0.95	40.12	54	-13.88	AVG
---	---	---	---	---	---	---
---	---	---	---	---	---	---

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Vertical:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2402	104.21	-5.84	98.37	114	-15.63	peak
2402	80.24	-5.84	74.4	94	-19.6	AVG
4804	52.18	-3.64	48.54	74	-25.46	peak
4804	42.17	-3.64	38.53	54	-15.47	AVG
7206	52.07	-0.95	51.12	74	-22.88	peak
7206	35.22	-0.95	34.27	54	-19.73	AVG
---	---	---	---	---	---	---
---	---	---	---	---	---	---

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.



CH Middle (2441MHz)

Horizontal:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2441	103.08	-5.71	97.37	114	-16.63	peak
2441	80.23	-5.71	74.52	94	-19.48	AVG
4882	51.07	-3.51	47.56	74	-26.44	peak
4882	42.11	-3.51	38.6	54	-15.4	AVG
7323	50.37	-0.82	49.55	74	-24.45	peak
7323	34.96	-0.82	34.14	54	-19.86	AVG
---	---	---	---	---	---	---
---	---	---	---	---	---	---

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Vertical:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2441	103.16	-5.71	97.45	114	-16.55	peak
2441	80.23	-5.71	74.52	94	-19.48	AVG
4882	55.22	-3.51	51.71	74	-22.29	peak
4882	41.08	-3.51	37.57	54	-16.43	AVG
7323	53.12	-0.82	52.3	74	-21.7	peak
7323	33.44	-0.82	32.62	54	-21.38	AVG
---	---	---	---	---	---	---
---	---	---	---	---	---	---

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.



CH High (2480MHz)

Horizontal:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2480	102.08	-5.65	96.43	114	-17.57	peak
2480	82.12	-5.65	76.47	94	-17.53	AVG
4960	52.07	-3.43	48.64	74	-25.36	peak
4960	44.18	-3.43	40.75	54	-13.25	AVG
7440	50.57	-0.75	49.82	74	-24.18	peak
7440	37.29	-0.75	36.54	54	-17.46	AVG
---	---	---	---	---	---	---
---	---	---	---	---	---	---

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Vertical:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2480	101.95	-5.65	96.3	114	-17.7	peak
2480	81.38	-5.65	75.73	94	-18.27	AVG
4960	53.76	-3.43	50.33	74	-23.67	peak
4960	41.56	-3.43	38.13	54	-15.87	AVG
7440	51.07	-0.75	50.32	74	-23.68	peak
7440	32.19	-0.75	31.44	54	-22.56	AVG
---	---	---	---	---	---	---
---	---	---	---	---	---	---

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Remark:

- (1) Measuring frequencies from 1 GHz to the 25 GHz.
- (2) "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency.
- (3) * denotes emission frequency which appearing within the Restricted Bands specified in provision of 15.205, then the general radiated emission limits in 15.209 apply.
- (4) Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) The IF bandwidth of EMI Test Receiver between 30MHz to 1GHz was 120KHz, 1 MHz for measuring above 1 GHz, below 30MHz was 10KHz.
- (6) When the test results of Peak Detected below the limits of Average Detected, the Average Detected is not need completed. For example: Top Channel at Fundamental 73.16dBuV/m(PK Value) <93.98(AV Limit), at harmonic 53.20 dBuV/m(PK Value) <54 dBuV/m(AV Limit), the Average Detected not need to completed.



5 BAND EDGE

5.1 Limits

FCC PART 15.249(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

5.2 Test Procedure


The band edge compliance of RF radiated emission should be measured by following the guidance in ANSI C63.10 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization etc. Set RBW to 100KHz and VBM to 300KHz to measure the peak field strength and set RBW to 1MHz and VBW to 10Hz to measure the average radiated field strength. The conducted RF band edge was measured by using a spectrum analyzer. Set span wide enough to capture the highest in-band emission and the emission at the band edge. Set RBW to 100 KHz and VBW to 300 KHz, to measure the conducted peak band edge.

5.3 Test Result

PASS

Note: GFSK, Pi/4 DQPSK and 8DPSK all have been tested, only worse case GFSK is reported.

Radiated Band Edge Test:
Lowest Bandedge
Horizontal (Worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	38.41	-3.80	34.61	54.00	-19.39	Average Detector
2	2310.000	49.27	-3.80	45.47	74.00	-28.53	Peak Detector
3	2390.000	38.44	-3.00	35.44	54.00	-18.56	Average Detector
4	2390.000	49.84	-3.00	46.84	74.00	-27.16	Peak Detector



Highest Bandedge

Horizontal (Worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2479.870	78.21	-2.50	75.71	/	/	Average Detector
2	2480.090	92.91	-2.50	90.41	/	/	Peak Detector
3	2483.500	Delta = 40.96 dBc		39.28	54.00	-14.72	Average Detector
4	2483.500			56.48	74.00	-17.52	Peak Detector
5	2500.000	37.72	-2.40	35.32	54.00	-18.68	Average Detector
6	2500.000	47.42	-2.40	45.02	74.00	-28.98	Peak Detector



6 OCCUPIED BANDWIDTH MEASUREMENT

6.1 Test Setup

Same as Radiated Emission Measurement

6.2 Test Procedure

1. The EUT was placed on a turn table which is 0.8m above ground plane.
2. Set EUT as normal operation.
3. Based on FCC Part15 C Section 15.249(a): RBW= 30KHz. VBW= 300 KHz, Span=3MHz.
4. The useful radiated emission from the EUT was detected by the spectrum analyser with peak detector.

6.3 Measurement Equipment Used

Same as Radiated Emission Measurement

6.4 Test Result


PASS

Modulation	Frequency	20dB Bandwidth (KHz)	Result
GFSK	2402 MHz	886.732	PASS
	2441 MHz	811.926	PASS
	2480 MHz	864.737	PASS
$\pi/4$ DQPSK	2402 MHz	1211	PASS
	2441 MHz	1207	PASS
	2480 MHz	1215	PASS
8DPSK	2402 MHz	1207	PASS
	2441 MHz	1220	PASS
	2480 MHz	1219	PASS




For GFSK
Low Channel:

CH: 2402MHz




Middle Channel:
CH: 2441MHz






High Channel:
CH: 2480MHz



For $\pi/4$ DQPSK


Low Channel:

CH: 2402MHz






Middle Channel:
CH: 2441MHz




High Channel:
CH: 2480MHz




**For 8DPSK****Low Channel:**

CH: 2402MHz


**Middle Channel:**

CH: 2441MHz





High Channel:
CH: 2480MHz



7 ANTENNA REQUIREMENT

Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.249, if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.


Refer to statement below for compliance.

The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

Antenna Connected Construction


The antenna used in this product is a PCB Antenna, The directional gains of antenna used for transmitting is 0dBi.

ANTENNA :



8 PHOTOGRAPH OF TEST

8.1 Radiated Emission



8.2 Conducted Emission

